

Custom Subnet Masks

Problem 1

Number of needed subnets **14**
 Number of needed usable hosts **14**
 Network Address **192.10.10.0**

Address class C

Default subnet mask 255 . 255 . 255 . 0

Custom subnet mask 255 . 255 . 255 . 240

Total number of subnets 16

Total number of host addresses 16

Number of usable addresses 14

Number of bits borrowed 4

Show your work for Problem 1 in the space below.

	256	128	64	32	16	8	4	2	1	Number of Hosts
Number of Subnets	-	2	4	8	16	32	64	128	256	
	128	64	32	16	8	4	2	1	-	Binary values
192 . 10 . 10 . 0	0	0	0	0	0	0	0	0	0	

Add the binary value numbers to the left of the line to create the custom subnet mask.

128
64
32
+16
240

16
-2
14

Observe the total number of hosts.
 Subtract 2 for the number of usable hosts.

Custom Subnet Masks

Problem 2

Number of needed subnets **1000**
 Number of needed usable hosts **60**
 Network Address **165.100.0.0**

Address class B

Default subnet mask 255 . 255 . 0 . 0

Custom subnet mask 255 . 255 . 255 . 192

Total number of subnets 1,024

Total number of host addresses 64

Number of usable addresses 62

Number of bits borrowed 10

Show your work for Problem 2 in the space below.

	65,536	32,768	16,384	8,192	4,096	2,048	1,024	512	256	128	64	32	16	8	4	2
Number of Hosts	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Number of Subnets	-	2	4	8	16	32	64	128	256	512	1024	2048	4096	8192	16384	32768
Binary values	-	128	64	32	16	8	4	2	1	128	64	32	16	8	4	2
<div style="display: flex; justify-content: space-between;"> <div style="width: 60%;"> <p>165 . 100 . 0 0 0 0 0 0 0 0 . 0 0</p> <div style="margin-left: 100px;"> <p>128 128</p> <p>64 +64</p> <hr style="width: 50%; margin: 0;"/> <p>32 192</p> <p>16</p> <p>8</p> <p>4</p> <p>2</p> <p>+1</p> <hr style="width: 50%; margin: 0;"/> <p>255</p> </div> </div> <div style="width: 35%;"> <p>64</p> <p>-2</p> <hr style="width: 50%; margin: 0;"/> <p>62</p> </div> </div>																

Add the binary value numbers to the left of the line to create the custom subnet mask.

Observe the total number of hosts.

Subtract 2 for the number of usable hosts.

Custom Subnet Masks

Problem 3

/26 indicates the total number of bits used for the network and subnetwork portion of the address. All bits remaining belong to the host portion of the address.

Network Address **148.75.0.0 /26**

Address class B

Default subnet mask 255 . 255 . 0 . 0

Custom subnet mask 255 . 255 . 255 . 192

Total number of subnets 1,024

Total number of host addresses 64

Number of usable addresses 62

Number of bits borrowed 10

Show your work for Problem 3 in the space below.

	65,536	32,768	16,384	8,192	4,096	2,048	1,024	512	256	128	64	32	16	8	4	2
Number of Hosts -																
Number of Subnets -	2	4	8	16	32	64	128	256	512	1024	2048	4096	8192	16384	32768	65536
Binary values -	128	64	32	16	8	4	2	1	128	64	32	16	8	4	2	1
148 . 75 . 0 0 0 0 0 0 0 0 . 0 0											0	0	0	0	0	0

Add the binary value numbers to the left of the line to create the custom subnet mask.

128	128
64	+64
32	192
16	
8	
4	
2	
+1	
255	

64	Observe the total number of hosts.
-2	
62	Subtract 2 for the number of usable hosts.

1024	
-2	Subtract 2 for the total number of subnets to get the usable number of subnets.
1,022	

Custom Subnet Masks

Problem 7

Number of needed subnets **2000**
 Number of needed usable hosts **15**
 Network Address **178.100.0.0**

Address class B

Default subnet mask 255.255.0.0

Custom subnet mask 255.255.224

Total number of subnets 2046

Total number of host addresses 32

Number of usable addresses 30

Number of bits borrowed 11

Show your work for Problem 7 in the space below.

Number of Hosts	65,536	32,768	16,384	8,192	4,096	2,048	1,024	512	256	128	64	32	16	8	4	2
Number of Subnets	2	4	8	16	32	64	128	256	512	1024	2048	4096	8192	16384	32768	65536
Binary values	128	64	32	16	8	4	2	1	128	64	32	16	8	4	2	1
	178	100	0	0	0	0	0	0	0	0	0	0	0	0	0	0

Custom Subnet Masks

Problem 15

Number of needed usable hosts **50**

Network Address **172.59.0.0**

Address class B

Default subnet mask 255.255.0.0

Custom subnet mask 255.255.192

Total number of subnets 1022

Total number of host addresses 64

Number of usable addresses 62

Number of bits borrowed 10

Show your work for Problem 15 in the space below.

Subnetting

Problem 1

Number of needed subnets **14**

Number of needed usable hosts **14**

Network Address **192.10.10.0**

Address class C

Default subnet mask 255 . 255 . 255 . 0

Custom subnet mask 255 . 255 . 255 . 240

Total number of subnets 16

Total number of host addresses 16

Number of usable addresses 14

Number of bits borrowed 4

What is the 4th subnet range? 192.10.10.48 to 192.10.10.63

What is the subnet number for the 8th subnet? 192 . 10 . 10 . 112

What is the subnet broadcast address for the 13th subnet? 192 . 10 . 10 . 207

What are the assignable addresses for the 9th subnet? 192.10.10.129 to 192.10.10.142

Show your work for Problem 1 in the space below.

Number of Subnets	256	128	64	32	16	8	4	2	-	Number of Hosts
	2	4	8	16	32	64	128	256		
	128	64	32	16	8	4	2	1	-	Binary values
192. 10 . 10 . 0	0	0	0	0	0	0	0	0	0	
(0)	0	0	0	0	192.10.10.0	to	192.10.10.15			
(1)	0	0	0	1	192.10.10.16	to	192.10.10.31			
(2)	0	0	1	0	192.10.10.32	to	192.10.10.47			
(3)	0	0	1	1	192.10.10.48	to	192.10.10.63			
(4)	0	1	0	0	192.10.10.64	to	192.10.10.79			
(5)	0	1	0	1	192.10.10.80	to	192.10.10.95			
(6)	0	1	1	0	192.10.10.96	to	192.10.10.111			
(7)	0	1	1	1	192.10.10.112	to	192.10.10.127			
(8)	1	0	0	0	192.10.10.128	to	192.10.10.143			
(9)	1	0	0	1	192.10.10.144	to	192.10.10.159			
(10)	1	0	1	0	192.10.10.160	to	192.10.10.175			
(11)	1	0	1	1	192.10.10.176	to	192.10.10.191			
(12)	1	1	0	0	192.10.10.192	to	192.10.10.207			
(13)	1	1	0	1	192.10.10.208	to	192.10.10.223			
(14)	1	1	1	0	192.10.10.224	to	192.10.10.239			
(15)	1	1	1	1	192.10.10.240	to	192.10.10.255			

$$\begin{array}{r}
 128 \\
 64 \\
 32 \\
 +16 \\
 \hline
 \text{Custom subnet mask } 240
 \end{array}$$

$$\begin{array}{r}
 16 \\
 -2 \\
 \hline
 \text{Usable subnets } 14
 \end{array}$$

$$\begin{array}{r}
 16 \\
 -2 \\
 \hline
 \text{Usable hosts } 14
 \end{array}$$

The binary value of the last bit borrowed is the range. In this problem the range is 16.

The first address in each subnet range is the subnet number.

The last address in each subnet range is the subnet broadcast address.

Subnetting

Problem 2

Number of needed subnets **1000**

Number of needed usable hosts **60**

Network Address **165.100.0.0**

Address class B

Default subnet mask 255 . 255 . 0 . 0

Custom subnet mask 255 . 255 . 255 . 192

Total number of subnets 1,024

Total number of host addresses 64

Number of usable addresses 62

Number of bits borrowed 10

What is the 15th subnet range? 165.100.3.128 to 165.100.3.191

What is the subnet number for the 6th subnet? 165 . 100 . 1 . 64

What is the subnet broadcast address for the 6th subnet? 165 . 100 . 1 . 127

What are the assignable addresses for the 9th subnet? 165.100.2.1 to 165.100.0.62

Show your work for **Problem 2** in the space below.

Number of Hosts -	65,536	32,768	16,384	8,192	4,096	2,048	1,024	512	256	128	64	32	16	8	4	2
Number of Subnets -	2	4	8	16	32	64	128	256	512	1024	2048	4096	8192	16384	32768	65536
Binary values -	128	64	32	16	8	4	2	1	128	64	32	16	8	4	2	1
165 . 100 . 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Usable hosts	64	128	64	32	16	8	4	2	1	0	0	0	0	0	0	0
Custom subnet mask	128	64	32	16	8	4	2	1	0	0	0	0	0	0	0	0
	192	128	64	32	16	8	4	2	1	0	0	0	0	0	0	0
	255	255	255	255	255	255	255	255	255	255	255	255	255	255	255	255
The binary value of the last bit borrowed is the range. In this problem the range is 64.	(0)	(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)	(12)	(13)	(14)	(15)
The first address in each subnet range is the subnet number.	165.100.0.0	165.100.0.64	165.100.0.128	165.100.0.192	165.100.0.255	165.100.1.0	165.100.1.64	165.100.1.128	165.100.1.192	165.100.2.0	165.100.2.64	165.100.2.128	165.100.2.192	165.100.3.0	165.100.3.64	165.100.3.128
The last address in each subnet range is the subnet broadcast address.	165.100.0.63	165.100.0.127	165.100.0.191	165.100.0.255	165.100.1.63	165.100.1.127	165.100.1.191	165.100.1.255	165.100.2.63	165.100.2.127	165.100.2.191	165.100.2.255	165.100.3.63	165.100.3.127	165.100.3.191	165.100.3.255
Down to	165.100.255.128	165.100.255.192	165.100.255.255	165.100.255.128	165.100.255.192	165.100.255.255	165.100.255.128	165.100.255.192	165.100.255.255	165.100.255.128	165.100.255.192	165.100.255.255	165.100.255.128	165.100.255.192	165.100.255.255	165.100.255.128

Subnetting

Problem 11

Number of needed usable hosts **8,000**

Network Address **135.70.0.0**

Address class B

Default subnet mask 255.255.0.0

Custom subnet mask 255.255.124

Total number of subnets 8

Total number of host addresses 8192

Number of usable addresses 8190

Number of bits borrowed 3

What is the 6th
subnet range? _____

What is the subnet number
for the 7th subnet? _____

What is the subnet
broadcast address for
the 3rd subnet? _____

What are the assignable
addresses for the 5th
subnet? _____

Show your work for Problem 11 in the space below.

Subnetting

Problem 12

Number of needed usable hosts **45**

Network Address **198.125.50.0**

Address class C

Default subnet mask 255.255.0.0

Custom subnet mask _____

Total number of subnets _____

Total number of host addresses _____

Number of usable addresses _____

Number of bits borrowed _____

What is the 2nd
subnet range? _____

What is the subnet number
for the 2nd subnet? _____


What is the subnet
broadcast address for
the 4th subnet? _____

What are the assignable
addresses for the 3rd
subnet? _____

Show your work for Problem 12 in the space below.

Practical Subnetting 1

Based on the information in the graphic shown, design a network addressing scheme that will supply the **minimum number of subnets**, and allow enough extra subnets and hosts for 100% growth in both areas. Circle each subnet on the graphic and answer the questions below.



Address class	<u>B</u>
Custom subnet mask	<u>255.255.224.0</u>
Minimum number of subnets needed	<u>4</u>
Extra subnets required for 100% growth (Round up to the next whole number)	<u>+ 4</u>
Total number of subnets needed	<u>= 8</u>
Number of host addresses in the largest subnet group	<u>60</u>
Number of addresses needed for 100% growth in the largest subnet (Round up to the next whole number)	<u>+ 60</u>
Total number of address needed for the largest subnet	<u>= 120</u>

Start with the first subnet and arrange your sub-networks from the largest group to the smallest.


IP address range for Research	<u>172.16.0.0 to 172.31.255</u>
IP address range for Marketing	<u>172.16.32.0 to 172.63.255</u>
IP address range for Management	<u>172.16.64.0 to 172.95.255</u>
IP address range for Router A to Router B serial connection	<u>172.16.96.0 to 172.127.255</u>

Show your work for Practical Subnetting 1 in the space below.

[illegible]

Practical Subnetting 2

Based on the information in the graphic shown, design a network addressing scheme that will supply the **minimum number of hosts per subnet**, and allow enough extra subnets and hosts for 30% growth in all areas. Circle each subnet on the graphic and answer the questions below.



Address class	<u>B</u>
Custom subnet mask	<u>255.255.255.224</u>
Minimum number of subnets needed	<u>5</u>
Extra subnets required for 30% growth (Round up to the next whole number)	<u>+ 2</u>
Total number of subnets needed	<u>= 7</u>
Number of host addresses in the largest subnet group	<u>20</u>
Number of addresses needed for 30% growth in the largest subnet (Round up to the next whole number)	<u>+ 6</u>
Total number of address needed for the largest subnet	<u>= 26</u>

Start with the first subnet and arrange your sub-networks from the largest group to the smallest.


IP address range for Tech Ed	<u>135.126.0.0 to 135.126.0.31</u>
IP address range for English	<u>135.126.0.32 to 135.126.0.63</u>
IP address range for Science	<u>135.126.0.64 to 135.126.0.95</u>
IP address range for Router A to Router B serial connection	<u>135.126.0.96 to 135.126.0.127</u>
IP address range for Router A to Router C serial connection	<u>135.126.0.128 to 135.126.0.159</u>

Show your work for Problem 2 in the space below.

Number of Hosts -	65,536	32,768	16,384	8,192	4,096	2,048	1,024	512	256	128	64	32	16	8	4	2
Number of Subnets -	2	4	8	16	32	64	128	256	512	1,024	2,048	4,096	8,192	16,384	32,768	65,536
Binary values -	128	64	32	16	8	4	2	1	128	64	32	16	8	4	2	1
135.126.0.0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
(0)	0															
(1)	1															
(2)		1														
(3)		1	1													
(4)		1	0	0												
(5)		1	0	1												
(6)		1	1	0												
(7)		1	1	1												
(8)	1	0	0	0												
(9)	1	0	0	1												
(10)	1	0	1	0												
(11)	1	0	1	1												
(12)	1	1	0	0												
(13)	1	1	0	1												
(14)	1	1	1	0												
(15)	1	1	1	1												
5 x.3 1.5 (Round up to 2)																
20 x.3 6																
	135.126.0.31	135.126.0.63	135.126.0.95	135.126.0.127	135.126.0.159	135.126.0.191	135.126.0.223	135.126.0.255	135.126.1.31	135.126.1.63	135.126.1.95	135.126.1.127	135.126.1.159	135.126.1.191	135.126.1.223	135.126.1.255
	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to

Practical Subnetting 4

Based on the information in the graphic shown, design a network addressing scheme that will supply the **minimum number of subnets**, and allow enough extra subnets and hosts for 70% growth in all areas. Circle each subnet on the graphic and answer the questions below.



Address class _____

Custom subnet mask _____

Minimum number of subnets needed _____

Extra subnets required for 70% growth **+** _____
(Round up to the next whole number)

Total number of subnets needed **=** _____

Number of host addresses
in the largest subnet group _____

Number of addresses needed for
70% growth in the largest subnet **+** _____
(Round up to the next whole number)

Total number of address
needed for the largest subnet **=** _____

Start with the first subnet and arrange your sub-networks from the largest group to the smallest.

IP address range for New York _____

IP address range for Washington D. C. _____

IP address range for Dallas _____


IP address range for Router A
to Router B serial connection _____

IP address range for Router A
to Router C serial connection _____

Show your work for Problem 4 in the space below.

Practical Subnetting 6

Based on the information in the graphic shown, design a network addressing scheme that will supply the **minimum number of subnets**, and allow enough extra subnets and hosts for 20% growth in all areas. Circle each subnet on the graphic and answer the questions below.



Address class _____

Custom subnet mask _____

Minimum number of subnets needed _____

Extra subnets required for 20% growth $+$ _____
(Round up to the next whole number)

Total number of subnets needed $=$ _____

Start with the first subnet and arrange your sub-networks from the largest group to the smallest.

IP address range for Technology _____

IP address range for Science _____

IP address range for Arts & Drama _____

IP Address range Administration _____

IP address range for Router A
to Router B serial connection _____

IP address range for Router A
to Router C serial connection _____

IP address range for Router B
to Router C serial connection _____

Show your work for Problem 6 in the space below.