

Project Configuration Report

ecen5823-assignment6-DonavonFaceyCU

Target Device:

Target Part: EFR32BG13P632F512GM48

Boards:

- Wireless Starter Kit Mainboard (BRD4001A Rev A01)
- EFR32BG13 2.4 GHz 10 dBm Radio Board (BRD4104A Rev A00)

Target SDK

Gecko SDK Suite v4.3.2: Amazon 202012.00, Bluetooth 6.2.0, Bluetooth Mesh 5.0.2, EmberZNet 7.3.2.0, Flex 3.6.2.0, MCU 6.5.2.0, Micrium OS Kernel 5.14.00, OpenThread 2.3.2.0 (GitHub-e6df00dd6), Platform 4.3.2.0, Sidewalk 1.2.2, Silicon Labs Matter 2.1.1-1.1, USB 1.1.2.0, Wi-SUN 1.7.1.0, Z-Wave SDK 7.20.2.0
SDK Version: 4.3.2

Extensions

- Sidewalk 1.2.2
- Silicon Labs Matter 2.1.1

Project Generators

- Simplicity IDE Project

Installed Software Components:

- Application
 - Utility
 - Assert**
Configurable: true
Configs: app_assert_config.h
 - Log**
Sources: app_log.c
Configurable: true
Configs: app_log_config.h
- Bluetooth
 - Application
 - GATT Services
 - Static GATT Database and Configuration**
Configurable: true
Configs: gatt_configuration.btconf

- Bluetooth Host (Stack)

Bluetooth Core

Sources: sl_bt_stack_init.c, sl_bt_mbedtls_context.c

Configurable: true

Configs: sl_bluetooth_config.h

- Features with Commands and Events

GATT Client

Configurable: false

GATT Server

Configurable: false

Security Manager

Configurable: false

System

Configurable: false

- Bluetooth LE Controller (Link Layer)

Advertising Base Feature

Configurable: true

Configs: sl_bluetooth_advertiser_config.h

Connection

Configurable: true

Configs: sl_bluetooth_connection_config.h

Legacy Advertising

Configurable: false

Scanner Base Feature

Configurable: false

• CMSIS

- DSP

CMSIS-DSP

Configurable: false

• Platform

- Board

- Radio Board

BRD4104A

Configurable: false

- Bootloader

Bootloader Application Interface

Sources: btl_interface_ns.c, btl_interface_storage.c, btl_interface.c, btl_interface_nsc.c

Configurable: true

Configs: btl_interface_cfg_s2c4.h, btl_interface_cfg.h, btl_interface_cfg_s2c1.h,
btl_interface_cfg_s2c2.h, btl_interface_cfg_s2c3.h

- Device

• EFR32BG13P

EFR32BG13P632F512GM48

Sources: startup_efr32bg13p.c, system_efr32bg13p.c

Configurable: true

Configs: device.yaml

- Driver

GLIB Graphics Library

Sources: glib_font_narrow_6x8.c, glib_line.c, glib_string.c, bmp.c, glib.c, glib_polygon.c,
glib_font_number_16x20.c, glib_circle.c, glib_font_normal_8x8.c, glib_rectangle.c,
glib_bitmap.c

Configurable: true

Configs: glib_config.h

GLIB driver for Memory LCD

Sources: dmd_memlcd.c

Configurable: false

• I2C

I2CSPM

Configurable: true

Configs: sl_i2cspm_sensor_config.h

- Peripheral

I2C

Sources: em_i2c.c

Configurable: false

LETIMER

Sources: em_letimer.c

Configurable: false

- Radio

RAIL Utility, PTI

Sources: sl_rail_util_pti.c

Configurable: true

Configs: sl_rail_util_pti_config.h

- Security

- Memory Protection Unit

Simple MPU

Sources: sl_mpu.c

Configurable: false

- Status Code

Status Code Strings

Sources: sl_status.c

Configurable: true

Configs: sl_status_string_config.h

- Utilities

Component Catalog

Configurable: false

• Services

- IO Stream

IO Stream: Recommended Stream

Configurable: false

- Power Manager

Power Manager: Deepsleep

Configurable: false

Pins:

Peripherals:

Peripheral	Software Component	Custom Peripheral Name
ACMP0		
ACMP1		
ADC0		
CMU		
CSEN		
DBG	SWO Debug	
ETM		
GPIO		
I2C0	I2CSPM (sensor)	
I2C1	I2CSPM (sensor)	
IDAC0		
LESENSE		
LETIMER0		
LEUART0		
LFXO		

MODEM		
PCNT0		
PRS Channel CH0		
PRS Channel CH1		
PRS Channel CH2		
PRS Channel CH3		
PRS Channel CH4		
PRS Channel CH5		
PRS Channel CH6		
PRS Channel CH7		
PRS Channel CH8		
PRS Channel CH9		
PRS Channel CH10		
PRS Channel CH11		
PTI	RAIL Utility, PTI	
TIMER0		
TIMER1		
USART0	Memory LCD with usart SPI driver	
USART1	Memory LCD with usart SPI driver	
USART2	Memory LCD with usart SPI driver	
VDAC0		
WTIMER0		