


Tries




Preprocessing Strings

- ◆ Preprocessing the pattern speeds up pattern matching queries
 - After preprocessing the pattern, KMP's algorithm performs pattern matching in time proportional to the text size
- ◆ If the text is large, immutable and searched for often (e.g., works by Shakespeare), we may want to preprocess the text instead of the pattern
- ◆ A trie is a compact data structure for representing a set of strings, such as all the words in a text
 - A trie supports pattern matching queries in time proportional to the pattern size


Standard Tries

- ◆ The standard trie for a set of strings S is an ordered tree such that:
 - Each node but the root is labeled with a character
 - The children of a node are alphabetically ordered
 - The paths from the external nodes to the root yield the strings of S
- ◆ Example: standard trie for the set of strings
 $S = \{ \text{bear, bell, bid, bull, buy, sell, stock, stop} \}$



Analysis of Standard Tries

- ◆ A standard trie uses $O(n)$ space and supports searches, insertions and deletions in time $O(dm)$, where:
 - n total size of the strings in S
 - m size of the string parameter of the operation
 - d size of the alphabet



Word Matching with a Trie


- insert the words of the text into trie
- Each leaf is associated w/ one particular word
- leaf stores indices where associated word begins ("see" starts at index 0 & 24, leaf for "see" stores those indices)

s	e	e	a	b	e	a	r	?	s	e	i	l	s	t	o	c	k	!					
0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23

s	e	e	a	b	u	i	l	?	b	u	y	s	t	o	c	k	!					
24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46


b	i	d	s	t	o	c	k	!	b	i	d	s	t	o	c	k	!				
47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68

h	e	a	r	t	h	e	b	e	i	l	?	s	t	o	p	!			
69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88




Compressed Tries

- A compressed trie has internal nodes of degree at least two
- It is obtained from standard trie by compressing chains of "redundant" nodes
- ex. the "i" and "d" in "bid" are "redundant" because they signify the same word




Compact Representation

- Compact representation of a compressed trie for an array of strings:
 - Stores at the nodes ranges of indices instead of substrings
 - Uses $O(s)$ space, where s is the number of strings in the array
 - Serves as an auxiliary index structure




Suffix Trie

- The suffix trie of a string X is the compressed trie of all the suffixes of X



Analysis of Suffix Tries


- ◆ Compact representation of the suffix trie for a string X of size n from an alphabet of size d
 - Uses $O(n)$ space
 - Supports arbitrary pattern matching queries in X in $O(dm)$ time, where m is the size of the pattern
 - Can be constructed in $O(n)$ time



Encoding Trie (1)


- ◆ A code is a mapping of each character of an alphabet to a binary code-word
- ◆ A prefix code is a binary code such that no code-word is the prefix of another code-word
- ◆ An encoding trie represents a prefix code
 - Each leaf stores a character
 - The code word of a character is given by the path from the root to the leaf storing the character (0 for a left child and 1 for a right child)

00	010	011	10	11
a	b	c	d	e



Encoding Trie (2)

- ◆ Given a text string X , we want to find a prefix code for the characters of X that yields a small encoding for X
 - Frequent characters should have short code-words
 - Rare characters should have long code-words
- ◆ Example
 - $X = \text{abracadabra}$
 - T_1 encodes X into 29 bits
 - T_2 encodes X into 24 bits



Huffman's Algorithm

- ◆ Given a string X , Huffman's algorithm constructs a prefix code that minimizes the size of the encoding of X
- ◆ It runs in time $O(n + d \log d)$, where n is the size of X and d is the number of distinct characters of X
- ◆ A heap-based priority queue is used as an auxiliary structure

Algorithm *HuffmanEncoding*(X)

Input string X of size n

Output optimal encoding trie for X

$C \leftarrow \text{distinctCharacters}(X)$

$\text{computeFrequencies}(C, X)$

$Q \leftarrow$ new empty heap

for all $c \in C$

$T \leftarrow$ new single-node tree storing c

$Q.\text{insert}(\text{getFrequency}(c), T)$

while $Q.\text{size}() > 1$

$f_1 \leftarrow Q.\text{min}()$

$T_1 \leftarrow Q.\text{removeMin}()$

$f_2 \leftarrow Q.\text{min}()$

$T_2 \leftarrow Q.\text{removeMin}()$

$T \leftarrow \text{join}(T_1, T_2)$

$Q.\text{insert}(f_1 + f_2, T)$



return $Q.\text{removeMin}()$

Example

$X = \text{abracadabra}$
Frequencies

a	b	c	d	r
5	2	1	1	2

a	b	c	d	r
5	2	1	1	2



Tries

