

Northeastern University
College of Engineering
Department of Electrical & Computer Engineering

EECE7376: Operating Systems: Interface and Implementation

Homework 4

Instructions

- For programming Problems:
 1. Your code must be well commented by explaining what the lines of your program do. Have at least one comment for every 4 lines of code.
 2. At the beginning of your source code files write your full name, students ID, and any special compiling/running instruction (if any).
 3. Before submitting the source code file(s), your code must compile and tested with a standard GCC compiler (available in the CoE Linux server).
 4. Do not submit any compiled object or executable files.
- **Deliverables:** Submit the following to the homework assignment page on Canvas:
 1. Your homework report developed by a word processor and submitted as one PDF file. For answers that require drawing and if it is difficult on you to use a drawing application, which is preferred, you can neatly hand draw the answer, scan it, and include it into your report. The report includes the following (depending on the assignment contents):
 - a. Answers to the non-programming Problems that show all the details of the steps you follow to reach these answers.
 - b. A summary of your approach to solve the programming Problems.
 - c. The **screen shots** of the **sample run(s)** of your program(s)
 2. Your well-commented programs source code files (i.e., the .cc or .cpp files).

Do NOT submit any files (e.g., the PDF report file and the source code files) as a compressed (zipped) package. Rather, upload each file individually.

Note: You can submit multiple attempts for this homework, however, only what you submit in the last attempt will be graded. This means all required files must be included in this last submission attempt.

Problem 1 (40 Points)

Add a new system call to xv6 to obtain the system date and time. The interface for this system call is the following:

```
struct rtcdate
{
    uint second;
    uint minute;
    uint hour;
    uint day;
    uint month;
    uint year;
};

int date(struct rtcdate *d);
```

As shown above, the system call takes a structure of type `struct rtcdate` as its only argument. The definition of the `struct rtcdate` is already available in file `date.h`. The `date` system call should always return 0.

The list below shows the xv6 files affected by the addition of a new system call. Follow these steps in your implementation:

- `syscall.h`. Add a unique numeric identifier for the new system call.
- `usys.S`. Add a new line of code corresponding to the new system call, following the pattern you observe for existing system calls. The new line of code includes the use of a macro that automatically converts a user-friendly function invocation into a set of instructions that set up the function arguments and execute a trap (`int $64`) instruction with the appropriate system call number in `%eax`.
- `syscall.c`. Add a new entry to the `syscalls` array. Also, add the “extern” declaration of function `sys_date(void)`. The body of the system call reads its arguments from the user, and not from the currently active kernel stack. Therefore, the function implementing the system call takes no explicit arguments in its header.
- `sysproc.c`. Use this kernel source file to append the implementation of the new system call. The body of the system call needs to grab the arguments from the user stack. Function `argint()` is an example of a helper function provided by xv6 for this purpose, which fetches a 32-bit value from the user stack and interprets it as an integer. You can see an example of its invocation in function `sys_kill()`, also available in this file.

However, in our case, we are interested in interpreting the argument passed by the user as a pointer. For this purpose, you may use function `argptr()` instead. In the body of the system call, you can obtain the current date and time with a call to kernel-level function `cmostime()`, defined in `lapic.c`. This function accesses the system clock directly using privileged I/O instructions.

- `user.h`. Add the user prototype of the new system call here. This file is a user-level header file, analogous to the header files provided by LibC in a modern Linux distribution (e.g., `stdio.h`). One of the purposes of this file is providing the prototype for every available system call.

At this point, you may check that your code compiles correctly, but you need to continue to work on the following exercise before you can test the system call.

Problem 2 (20 Points)

Create a new user program named `date.c` that serves as an xv6 command-line tool to obtain the result of the `date()` system call and print the date info on the screen. The program should be invoked from the xv6 shell without any arguments, and should provide the current date and time, in the format `mm/dd/yyyy hh:mm:ss` as follows:

```
$ date
5/4/2015 20:38:6
```

Your new `date` user program should be visible from the xv6 shell when running command `ls`. Test the new `date` command and verify that the output matches the sample output above.

Problem 3 (40 Points)

Following the same approach that you used in solving Problems 1 and 2, add a new system call and a user command to xv6 to allow users to call a command line similar to the `ps` command in Linux. However, your xv6 `ps` command should not take any arguments. The command lists all the `id` of the current processes in the system. For each process, the command also displays the process `state` and the `id` of its parent. When testing it, the command should list the information of at least two processes: the shell process and the process of the `ps` user command itself.

For testing purpose, add the needed code in your user command `ps` program to fork a child and allow the code in the parent to perform the main `ps` task. Now your `ps` command should also display the status of this child. Can you write your code so that the child is presented in different states?