

Blockchain Security | Smart Contract Audits | KYC Development | Marketing



CarCollectorCrypto

Audit

Security Assessment 02. November, 2022

For







| Disclaimer | 3 |
|--|----|
| Description | 5 |
| Project Engagement | 5 |
| Logo | 5 |
| Contract Link | 5 |
| Methodology | 7 |
| Used Code from other Frameworks/Smart Contracts (direct imports) | 8 |
| Tested Contract Files | 9 |
| Source Lines | 10 |
| Risk Level | 10 |
| Capabilities | 11 |
| Inheritance Graph | 12 |
| CallGraph | 13 |
| Scope of Work/Verify Claims | 14 |
| Modifiers and public functions | 24 |
| Source Units in Scope | 26 |
| Critical issues | 27 |
| High issues | 27 |
| Medium issues | 27 |
| Low issues | 27 |
| Informational issues | 28 |
| Commented Code exist | 28 |
| Audit Comments | 29 |
| SWC Attacks | 30 |

Disclaimer

<u>SolidProof.io</u> reports are not, nor should be considered, an "endorsement" or "disapproval" of any particular project or team. These reports are not, nor should be considered, an indication of the economics or value of any "product" or "asset" created by any team. SolidProof.io do not cover testing or auditing the integration with external contract or services (such as Unicrypt, Uniswap, PancakeSwap etc'...)

SolidProof.io Audits do not provide any warranty or guarantee regarding the absolute bug- free nature of the technology analyzed, nor do they provide any indication of the technology proprietors. SolidProof Audits should not be used in any way to make decisions around investment or involvement with any particular project. These reports in no way provide investment advice, nor should be leveraged as investment advice of any sort.

SolidProof.io Reports represent an extensive auditing process intending to help our customers increase the quality of their code while reducing the high level of risk presented by cryptographic tokens and blockchain technology. Blockchain technology and cryptographic assets present a high level of ongoing risk. SolidProof's position is that each company and individual are responsible for their own due diligence and continuous security. SolidProof in no way claims any guarantee of security or functionality of the technology we agree to analyze.

| Version | Date | Description |
|---------|-------------------|---|
| 1.0 | 02. November 2022 | Layout projectAutomated-/Manual-Security TestingSummary |

Network

Binance Smart Chain (BEP20)

Website

www.carcollectorcrypto.com

Twitter

https://twitter.com/CARCC_Token

Facebook

https://www.facebook.com/carcollectorcrypto

Instagram

https://www.instagram.com/carcollectorcrypto/

Youtube

https://www.youtube.com/channel/UCVqGOozyR450OGVH826N3JQ

TikTok

https://www.tiktok.com/@carcollector.cryptotoken

Description

TBA

Project Engagement

During the 1st of November 2022, **CarCollectorCrypto Team** engaged Solidproof.io to audit smart contracts that they created. The engagement was technical in nature and focused on identifying security flaws in the design and implementation of the contracts. They provided Solidproof.io with access to their code repository and whitepaper.





Contract Link v1.0

Provided as files

Vulnerability & Risk Level

Risk represents the probability that a certain source-threat will exploit vulnerability, and the impact of that event on the organization or system. Risk Level is computed based on CVSS version 3.0.

| Level | Value | Vulnerability | Risk (Required Action) |
|---------------|---------|---|---|
| Critical | 9 - 10 | A vulnerability that can disrupt the contract functioning in a number of scenarios, or creates a risk that the contract may be broken. | Immediate action to reduce risk level. |
| High | 7 – 8.9 | A vulnerability that affects the desired outcome when using a contract, or provides the opportunity to use a contract in an unintended way. | Implementation of corrective actions as soon aspossible. |
| Medium | 4 – 6.9 | A vulnerability that could affect the desired outcome of executing the contract in a specific scenario. | Implementation of corrective actions in a certain period. |
| Low | 2 – 3.9 | A vulnerability that does not have a significant impact on possible scenarios for the use of the contract and is probably subjective. | Implementation of certain corrective actions or accepting the risk. |
| Informational | 0 – 1.9 | A vulnerability that have informational character but is not effecting any of the code. | An observation that does not determine a level of risk |

Auditing Strategy and Techniques Applied

Throughout the review process, care was taken to evaluate the repository for security-related issues, code quality, and adherence to specification and best practices. To do so, reviewed line-by-line by our team of expert pentesters and smart contract developers, documenting any issues as there were discovered.


Methodology

The auditing process follows a routine series of steps:

- 1. Code review that includes the following:
 - i) Review of the specifications, sources, and instructions provided to SolidProof to make sure we understand the size, scope, and functionality of the smart contract.
 - ii) Manual review of code, which is the process of reading source code line-byline in an attempt to identify potential vulnerabilities.
 - iii) Comparison to specification, which is the process of checking whether the code does what the specifications, sources, and instructions provided to SolidProof describe.
- 2. Testing and automated analysis that includes the following:
 - i) Test coverage analysis, which is the process of determining whether the test cases are actually covering the code and how much code is exercised when we run those test cases.
 - ii) Symbolic execution, which is analysing a program to determine what inputs causes each part of a program to execute.
- 3. Best practices review, which is a review of the smart contracts to improve efficiency, effectiveness, clarify, maintainability, security, and control based on the established industry and academic practices, recommendations, and research.
- 4. Specific, itemized, actionable recommendations to help you take steps to secure your smart contracts.

Used Code from other Frameworks/Smart Contracts (direct imports)

Imported packages:



Tested Contract Files

This audit covered the following files listed below with a SHA-1 Hash.

A file with a different Hash has been modified, intentionally or otherwise, after the security review. A different Hash could be (but not necessarily) an indication of a changed condition or potential vulnerability that was not within the scope of this review.


v1.0

| File Name | SHA-1 Hash |
|---------------------------------|--|
| contracts/carollectorcrypto.sol | 316b0aca76b5cc792f5615cb35b94f329375edd2 |



Metrics

Source Lines v1.0



Capabilities

Components

| Version | Contracts | Libraries | Interfaces | Abstract |
|---------|-----------|-----------|------------|----------|
| 1.0 | 2 | 2 | 5 | 1 |

Exposed Functions

This section lists functions that are explicitly declared public or payable. Please note that getter methods for public stateVars are not included.

| Versio | n | Public Payable | |
|--------|---|----------------|---|
| 1.0 | | 100 | 6 |

| Version | Version External Internal | | Private | Pure | View |
|---------|---------------------------|----|---------|------|------|
| 1.0 | 69 | 85 | 22 | 19 | 44 |

State Variables

| Version | Total | Public |
|---------|-------|--------|
| 1.0 | 26 | 8 |

Capabilities


| Version | Solidity Versions observed | Experim ental Features | Can Receive Funds | Uses Assembl Y | Has Destroya ble Contract s |
|---------|----------------------------------|------------------------------|-------------------------|--------------------------|---|
| 1.0 | ^0.6.1 2 | | yes | yes (2 asm blocks) | |

| version | Transfer s ETH | Low- Level Calls | Deleg ateCa II | Uses Hash Function s | EC Rec ove r | New/ Create/ Create2 | |
|---------|-------------------|------------------------|----------------------|-------------------------------|-----------------------|----------------------------|--|
|---------|-------------------|------------------------|----------------------|-------------------------------|-----------------------|----------------------------|--|


| 1.0 yes | |
|---------|--|
|---------|--|

Inheritance Graph

v1.0



CallGraph v1.0



Scope of Work/Verify Claims

The above token Team provided us with the files that needs to be tested (Github, Bscscan, Etherscan, files, etc.). The scope of the audit is the main contract (usual the same name as team appended with .sol).

We will verify the following claims:

- 1. Is contract an upgradeable
- 2. Correct implementation of Token standard
- 3. Deployer cannot mint any new tokens
- 4. Deployer cannot burn or lock user funds
- 5. Deployer cannot pause the contract
- 6. Deployer cannot set fees
- 7. Deployer cannot blacklist/antisnipe addresses
- 8. Overall checkup (Smart Contract Security)

Is contract an upgradeable

| Name | |
|-----------------------------|----|
| Is contract an upgradeable? | No |



Correct implementation of Token standard

| ERC20 | | | | | | |
|--------------|---|--------------|----------|--------------|--|--|
| Function | Description | Exist | Tested | Verified | | |
| TotalSupply | Provides information about the total token supply | \checkmark | √ | \checkmark | | |
| BalanceOf | Provides account balance of the owner's account | \checkmark | √ | \checkmark | | |
| Transfer | Executes transfers of a specified number of tokens to a specified address | √ | √ | √ | | |
| TransferFrom | Executes transfers of a specified number of tokens from a specified address | √ | √ | √ | | |
| Approve | Allow a spender to withdraw a set number of tokens from a specified account | 1 | √ | √ | | |
| Allowance | Returns a set number of tokens from a spender to the owner | √ | 1 | ✓ | | |

Write functions of contract v1.0



Deployer cannot mint any new tokens

| Name | Exist | Tested | Status |
|----------------------|-------|--------|--------|
| Deployer cannot mint | - | - | - |



Deployer cannot burn or lock user funds

| Name | Exist | Tested | Status |
|----------------------|--------------|----------|--------|
| Deployer cannot lock | \checkmark | √ | X |
| Deployer cannot burn | - | - | - |

Comments:

v1.0

- · Owner can lock user funds by
 - Setting max tx amount to 0

Deployer cannot pause the contract

| Name | Exist | Tested | Status |
|-----------------------|-------|--------|--------|
| Deployer cannot pause | - | _ | - |



Deployer cannot set fees

| Name | Exist | Tested | Status |
|--|--------------|----------|--------|
| Deployer cannot set fees over 25% | \checkmark | √ | × |
| Deployer cannot set fees to nearly 100% or to 100% | √ | √ | X |

Comments:

v1.0

· Fees can be set without any limitations

Deployer can blacklist/antisnipe addresses

| Name | Exist | Tested | Status |
|---|-------|--------|--------|
| Deployer cannot blacklist/antisnipe addresses | - | - | - |



Overall checkup (Smart Contract Security)




Legend

| Attribute | Symbol |
|--------------------------|--------------|
| Verified / Checked | \checkmark |
| Partly Verified | × |
| Unverified / Not checked | X |
| Not available | - |

Modifiers and public functions

v1.0



Comments

- · Deployer can set following state variables without any limitations
 - _taxFee
 - _liquidityFee
 - numTokensSellToAddToLiquidity
 - maxTxAmount
- Deployer can enable/disable following state variables
 - _isExcluded
 - _excluded
 - isExcludedFromFee

- swapAndLiquifyEnabled
- · <u>Deployer can set following addresses</u>
- Existing Modifiers
 - onlyOwner
 - lockTheSwap
- · If the address is excluded then it is not able to call deliver function
- Owner is able to call "claimTokens" to get whole contract balance (natives only, not tokens)
- · Liquidity will be send to the owner. Beware of this he/she can take out the liquidity

Please check if an OnlyOwner or similar restrictive modifier has been forgotten.

Source Units in Scope v1.0

| Туре | File | Logic Contracts | Interfaces | Lines | nLines | nSLOC | Comment Lines | Complex. Score | Capabilities |
|-------------|---------------------------------|--------------------|------------|-------|--------|-------|------------------|-------------------|--------------|
| ≥ €Q | contracts/carollectorcrypto.sol | 5 | 5 | 1152 | 876 | 521 | 311 | 533 | |
| ≥ €Q | Totals | 5 | 5 | 1152 | 876 | 521 | 311 | 533 | |

Legend

| Attribute | Description |
|------------------|---|
| Lines | total lines of the source unit |
| nLines | normalised lines of the source unit (e.g. normalises functions spanning multiple lines) |
| nSLOC | normalised source lines of code (only source-code lines; no comments, no blank lines) |
| Comment Lines | lines containing single or block comments |
| Complexity Score | a custom complexity score derived from code statements that are known to introduce code complexity (branches, loops, calls, external interfaces,) |

Audit Results

Critical issues

No critical issues

High issues

No high issues

Medium issues

| Issue | File | Type | Line | Description |
|-------|------|------------------|--------------------|---|
| #1 | Main | Regain ownership | See description | Owner can regain ownership after transferring it with following steps: 1. Call lock function to set _previousOwner to the own address 2. Call unlock function to get ownership back 3. Transfer/renounce |
| | | | | ownership 4. Call unlock function to get ownership back |
| | | | | Make sure to set the _previousOwnership back to address zero after using the unlock function |

Low issues

| Issue | File | Type | Line | Description |
|-------|------|---|------|--|
| #1 | Main | Contract doesn't import npm packages from source (like OpenZeppelin etc.) | | We recommend to import all packages from npm directly without flatten the contract. Functions could be modified or can be susceptible to vulnerabilities |
| #2 | Main | A floating pragma is set | 5 | The current pragma Solidity directive is ""^0.6.12"". |

| #3 | Main | Missing Zero Address Validation (missing- zero-check) | 749 748 | Check that the address is not zero |
|----|------|---|--------------------------|---|
| #4 | Main | State variable visibility is not set | 700 | It is best practice to set the visibility of state variables explicitly |
| #5 | Main | Local variables shadowing | 990 779 | Rename the local variables that shadow another component |
| #6 | Main | Missing Events Arithmetic | 884 892 888 880 | Emit an event for critical parameter changes |

Informational issues

| Issue | File | Туре | Line | Description |
|-------|------|-------------------------------------|--------------------|---|
| #1 | Main | Misspelling | See description | Change following words: - tokensIntoLiqudity L711 - swaping L900 - recieve L900 Make sure to change it everywhere else as well. |
| #2 | Main | NatSpec documentation missing | - | If you started to comment your code, also comment all other functions, variables etc. |
| #3 | Main | Old pragma version | See description | We recommend you to use at least pragma version 0.8.x |
| #4 | Main | Unemitted events | 706 | Emit or remove the event |

Commented Code exist

There are some instances of code being commented out in the following files that should be removed:

| File | Line | Comment |
|------|------|--|
| Main | 194 | <pre>// assert(a == b * c + a % b); // There is no case in which this doesn't hold</pre> |
| | 839 | // require(account != 0x7a250d5630B4cF539739dF2C5dAcb4c659F2488D, 'We can not exclude Uniswap router.'); |

Recommendation

Remove the commented code, or address them properly.

Audit Comments

We recommend you to use the special form of comments (NatSpec Format, Follow link for more information https://docs.soliditylang.org/en/latest/natspec-format.html) for your contracts to provide rich documentation for functions, return variables and more. This helps investors to make clear what that variables, functions etc. do.

02. November 2022:

· Read whole report and modifiers section for more information

SWC Attacks

| ID | Title Relationships | | Status |
|--------------------------------------|--|--|--------|
| <u>SW</u> <u>C-1</u> <u>36</u> | Unencrypted Private Data On-Chain | CWE-767: Access to Critical Private Variable via Public Method | PASSED |
| <u>SW</u> <u>C-1</u> <u>35</u> | Code With No Effects | CWE-1164: Irrelevant Code | PASSED |
| <u>SW</u> <u>C-1</u> <u>34</u> | Message call with hardcoded gas amount | CWE-655: Improper Initialization | PASSED |
| <u>SW</u> <u>C-1</u> <u>33</u> | Hash Collisions With Multiple Variable Length Arguments | CWE-294: Authentication Bypass by Capture-replay | PASSED |
| <u>SW</u> <u>C-1</u> <u>32</u> | Unexpected Ether balance | CWE-667: Improper Locking | PASSED |
| <u>SW</u> <u>C-1</u> <u>31</u> | Presence of unused variables | CWE-1164: Irrelevant Code | PASSED |
| <u>SW</u> <u>C-1</u> <u>30</u> | Right-To-Left- Override control character (U+202E) | CWE-451: User Interface (UI) Misrepresentation of Critical Information | PASSED |
| <u>SW</u> <u>C-1</u> <u>29</u> | Typographical Error | CWE-480: Use of Incorrect Operator | PASSED |
| <u>SW</u> <u>C-1</u> <u>28</u> | DoS With Block Gas Limit | CWE-400: Uncontrolled Resource Consumption | PASSED |

| <u>SW</u> <u>C-1</u> <u>27</u> | Arbitrary Jump with Function Type Variable | CWE-695: Use of Low-Level Functionality | PASSED |
|--------------------------------------|--|---|---------------|
| <u>SW</u> <u>C-1</u> <u>25</u> | Incorrect Inheritance Order | CWE-696: Incorrect Behavior Order | PASSED |
| <u>SW</u> <u>C-1</u> <u>24</u> | Write to Arbitrary Storage Location | CWE-123: Write-what-where Condition | PASSED |
| SW C-1 23 | Requirement Violation | CWE-573: Improper Following of Specification by Caller | PASSED |
| <u>SW</u> <u>C-1</u> <u>22</u> | Lack of Proper Signature Verification | CWE-345: Insufficient Verification of Data Authenticity | PASSED |
| <u>SW</u> <u>C-1</u> <u>21</u> | Missing Protection against Signature Replay Attacks | CWE-347: Improper Verification of Cryptographic Signature | PASSED |
| <u>SW</u> <u>C-1</u> <u>20</u> | Weak Sources of Randomness from Chain Attributes | CWE-330: Use of Insufficiently Random Values | PASSED |
| <u>SW</u> <u>C-11</u> <u>9</u> | Shadowing State Variables | CWE-710: Improper Adherence to Coding Standards | NOT PASSED |
| <u>SW</u> <u>C-11</u> <u>8</u> | Incorrect Constructor Name | CWE-665: Improper Initialization | PASSED |
| <u>SW</u> <u>C-11</u> <u>7</u> | Signature Malleability | CWE-347: Improper Verification of Cryptographic Signature | PASSED |

| <u>SW</u> <u>C-11</u> <u>6</u> | Timestamp Dependence | CWE-829: Inclusion of Functionality from Untrusted Control Sphere | PASSED |
|--------------------------------------|---|--|---------------|
| <u>SW</u> <u>C-11</u> <u>5</u> | Authorization through tx.origin | CWE-477: Use of Obsolete Function | PASSED |
| <u>SW</u> <u>C-11</u> <u>4</u> | Transaction Order Dependence | CWE-362: Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition') | PASSED |
| <u>SW</u> <u>C-11</u> <u>3</u> | DoS with Failed Call | CWE-703: Improper Check or Handling of Exceptional Conditions | PASSED |
| <u>SW</u> <u>C-11</u> <u>2</u> | Delegatecall to Untrusted Callee | CWE-829: Inclusion of Functionality from Untrusted Control Sphere | PASSED |
| <u>SW</u> <u>C-11</u> <u>1</u> | Use of Deprecated Solidity Functions | CWE-477: Use of Obsolete Function | PASSED |
| <u>SW</u> <u>C-11</u> <u>O</u> | Assert Violation | CWE-670: Always-Incorrect Control Flow Implementation | PASSED |
| SW C-1 09 | Uninitialized Storage Pointer | CWE-824: Access of Uninitialized Pointer | PASSED |
| <u>SW</u> <u>C-1</u> <u>08</u> | State Variable Default Visibility | CWE-710: Improper Adherence to Coding Standards | NOT PASSED |
| SW C-1 07 | Reentrancy | CWE-841: Improper Enforcement of Behavioral Workflow | PASSED |
| SW C-1 06 | Unprotected SELFDESTRUC T Instruction | CWE-284: Improper Access Control | PASSED |

| <u>SW</u> <u>C-1</u> <u>05</u> | Unprotected Ether Withdrawal | CWE-284: Improper Access Control | PASSED |
|--------------------------------------|--------------------------------------|--|---------------|
| <u>SW</u> <u>C-1</u> <u>04</u> | Unchecked Call Return Value | CWE-252: Unchecked Return Value | PASSED |
| <u>SW</u> <u>C-1</u> <u>03</u> | Floating Pragma | CWE-664: Improper Control of a Resource Through its Lifetime | NOT PASSED |
| <u>SW</u> <u>C-1</u> <u>02</u> | Outdated Compiler Version | CWE-937: Using Components with Known Vulnerabilities | PASSED |
| <u>SW</u> <u>C-1</u> <u>01</u> | Integer Overflow and Underflow | CWE-682: Incorrect Calculation | PASSED |
| <u>SW</u> <u>C-1</u> <u>00</u> | Function Default Visibility | CWE-710: Improper Adherence to Coding Standards | PASSED |
| | | | |







Blockchain Security | Smart Contract Audits | KYC Development | Marketing

MADE IN GERMANY