

# Plotting with ggplot2

Andrew Zieffler

---



This work is licensed under a  
[Creative Commons Attribution  
4.0 International License](https://creativecommons.org/licenses/by/4.0/).

```
# Load the vlss data
> cehd = read.csv("~/Documents/EPsy-8261/data/cehd.csv")
```

```
> head(cehd)
```

	name	title	department	hire_year	years_at_u	annual_pay
1	Carlson,Stephanie M	Professor	ICD	2007	9.341547	131077.8
2	Cicchetti,Dante	Professor	ICD	2005	11.219713	320546.2
3	Gunnar,Megan Rosamond	Professor	ICD	1979	36.922656	200299.6
4	Maratsos,Michael P	Professor	ICD	1971	44.922656	103763.4
5	Masten,Ann S	Professor	ICD	1982	33.746749	176080.6
6	Mazzocco,Michele M	Professor	ICD	2012	4.531143	157351.4

```
> tail(cehd)
```

	name	title	department	hire_year	years_at_u	annual_pay
161	Reinardy,James Robert	Associate Professor	SSW	1993	23.006160	111499.25
162	Renner,Lynette Michelle	Associate Professor	SSW	2013	2.978782	84164.53
163	Shannon,Patricia Jean	Associate Professor	SSW	2009	7.463381	74227.44
164	VeLure Roholt,Ross R	Associate Professor	SSW	1996	19.997262	79018.94
165	Johnston-Goodstar,Caterina Marie	Assistant Professor	SSW	2009	6.965092	68983.47
166	Krentzman,Amy Ruth	Assistant Professor	SSW	2013	3.066393	73207.94

```
> summary(cehd)
```


	name	title	department	hire_year
Albrecht,Lisa D	: 1	Assistant Professor:23	EPSY :33	Min. :1968
Alexander,Nicola	: 1	Associate Professor:72	C&I :28	1st Qu.:1989
Anderson,Melissa Susan	: 1	Professor :71	OLPD :26	Median :2000
Ardichvili,Alexandre Archie:	1		SSW :21	Mean :1998
Arendale,David Ray	: 1		FSoS :16	3rd Qu.:2007
Asher,Nina	: 1		ICD :15	Max. :2015
(Other)	:160		(Other):27	

years_at_u	annual_pay
Min. : 0.9665	Min. : 60750
1st Qu.: 8.9774	1st Qu.: 78266
Median :15.9726	Median : 87939
Mean :17.9151	Mean : 99119
3rd Qu.:26.8481	3rd Qu.:110052
Max. :48.0055	Max. :320546

# Install the **ggplot2** Package

Using the RStudio GUI...

- ▶ Click the **Packages** tab.
- ▶ Click **Install Packages**.
- ▶ Enter *ggplot2* in the text box.
- ▶ Click **Install**.



...or directly from the R command line...

```
> install.packages("ggplot2", dependencies = TRUE)
```

The `library()` function loads the package so that the functions in the package are accessible. Libraries need to be loaded *every* R session.


```
# Load the ggplot2 library  
> library(ggplot2)
```

# Understanding the Basic Syntax

Aesthetic mappings given in the `ggplot()` layer are applied to every subsequent layer

```
> ggplot(data = cehd, aes(x = title, y = annual_pay)) +  
  geom_boxplot()
```

The `geom_boxplot()` function adds the geometric object of boxplots using the global data and aesthetic mapping.




The `+` adds another layer.

# Understanding the Basic Syntax

```
> ggplot(data = cehd, aes(x = title, y = annual_pay)) +  
  geom_boxplot()
```

Plots are built by layering graphical components. In the syntax, the layers are literally *summed* together to form the plot.



## Global Layer

Aesthetic mappings given in the `ggplot()` layer are applied to all layers in the plot

```
> ggplot(data = cehd, aes(x = title, y = annual_pay)) +
```

The `data=` argument indicates the source data frame.

The `aes=` argument sets the aesthetic mapping(s).

The first layer is always `ggplot()`. It contains reference to the **source data** (data frame) and **global aesthetic mappings**.

Aesthetic mappings describe how **variables in the data are mapped to visual properties** (aesthetics) of geoms. They are used to define position (*x*-dimension *y*-dimension), size, color, fill, groupings, etc.

- Aesthetics can be set **globally**—in `ggplot()` layer—or **locally** (only used in a specific geom layer)
- Each aesthetic can be **variable** or **fixed**
  - If the aesthetic is variable it needs to be specified in the `aes()` function
  - If the aesthetic is fixed it should be specified outside the `aes()` function



# Adding Geometric Objects

```
> ggplot(data = cehd, aes(x = title, y = annual_pay)) +  
  geom_boxplot()
```

The `geom_boxplot()` function adds the geometric object of boxplots using the global data and aesthetic mapping.


The `+` adds another layer.

The first layer only sets up the plot, it doesn't actually plot anything. In the subsequent layers, we add geometric objects (e.g., points, boxplots). These objects are plotted based on the aesthetics from the first layer. For example, the syntax above draws boxplots of faculty members' annual pay vertically (the *y*-position is the variable *annual\_pay*. The *x*-position is *title*, so each title will have its own box plot, separated along the *x*-axis.

Geometric objects, or *geoms*, are features that are actually drawn on plot (e.g., lines, points). They are specified using the prefix `geom_` and a suffix that names the feature to be plotted.

- **Points** specified with `geom_point()`
- **Jittered points** specified with `geom_jitter()`
- **Lines** specified with `geom_line()`
- **Boxplots** specified with `geom_boxplot()`

*y*-position



*x*-position


*geometric  
objects*

When layers are added they are "stacked" on top of previous layers. Imagine drawings on separate transparencies, and then those transparencies are stacked.

```
> ggplot(data = cehd, aes(x = title, y = annual_pay)) +  
  geom_boxplot() +  
  geom_jitter()
```



The `geom_jitter()` function adds the geometric object of jittered points using the global data and aesthetic mapping.

The `+` adds another layer.



```
> ggplot(data = cehd, aes(x = title, y = annual_pay, color = title)) +  
  geom_boxplot() +  
  geom_jitter()
```

Global aesthetic mappings  
are applied to *all* layers.



```
> ggplot(data = cehd, aes(x = title, y = annual_pay)) +  
  geom_boxplot(aes(color = title)) +  
  geom_jitter()
```

Local aesthetic mappings (in a particular  
layer) are only applied to that layer.

# Fixed vs Variable Aesthetics

```
> ggplot(data = cehd, aes(x = title, y = annual_pay, color = title)) +  
  geom_boxplot(color = "black", fill = "steelblue") +  
  geom_jitter()
```


The **color=** argument sets the color for the outline in this layer.


The **fill=** argument sets the fill color for this layer.

Notice the quotation marks...color names are character strings.

Aesthetic mappings that are fixed to a particular value (do not vary), rather, do **not** need to be enclosed in the **aes()** function.

Note also that the local aesthetics override the global aesthetics





### Your Turn

Write the syntax to create this scatterplot. Hint to add points, we use `geom_point()`

How would we color the points by department?

```
# Create the plot
> ggplot(data = cehd, aes(x = years_at_u, y = annual_pay)) +
  geom_point()
```

```
# Color the points by department (Option 1)
> ggplot(data = cehd, aes(x = years_at_u, y = annual_pay,
                          color = department)) +
  geom_point()
```

```
# Color the points by department (Option 2)
> ggplot(data = cehd, aes(x = years_at_u, y = annual_pay)) +
  geom_point(aes(color = department))
```





# Point Aesthetics


Two other useful aesthetics for points are `pch=` and `size=` for plotting character and point size, respectively.

```
> ggplot(data = cehd, aes(x = years_at_u, y = annual_pay)) +  
  geom_point(aes(color = department, pch = title), size = 5)
```

The `pch=` argument sets the plotting character.

The `size=` argument sets the point size. (The default size is 4.)

Describe the resulting plot based on the syntax above.



Note: EVERY non-positional aesthetics gets added to the legend.

# Faceting


Faceting creates a separate plot for each subgroup declared

- `facet_wrap()` displays the plots conditioned on a **single predictor**
- `facet_grid()` displays the plots conditioned on **multiple predictors**

```
> ggplot(data = cehd, aes(x = years_at_u, y = annual_pay)) +  
  geom_point() +  
  facet_wrap(~ department)
```


~ sets the predictor for  
conditioning

The scatterplots show the  
relationship between experience  
(years at the university) and pay  
conditioned on department.



```
> ggplot(data = cehd, aes(x = years_at_u, y = annual_pay)) +  
  geom_point() +  
  facet_wrap(~ department, nrow = 2)
```


`nrow=` (and/or `ncol=`)  
sets the number of rows  
or columns in the  
plotting area



# Changing the Axis Label

```
> ggplot(data = cehd, aes(x = years_at_u, y = annual_pay)) +  
  geom_point() +  
  facet_wrap(~ department, nrow = 2) +  
  xlab("Years at the University of Minnesota")
```

`xlab()` can be used to change the label on the  $x$ -axis, and `ylab()` is used to change the label on the  $y$ -axis.




# Changing the Axis Limits

```
> ggplot(data = cehd, aes(x = years_at_u, y = annual_pay)) +  
  geom_point() +  
  facet_wrap(~ department, nrow = 2) +  
  xlab("Years at the University of Minnesota") +  
  ylim(0, 200000)
```

The first value is  
the minimum.

The second value is  
the maximum.

`xlim()` and `ylim()` are used  
to set the limits on the *x*-  
axis and *y*-axis respectively.



# Adios-ing Scientific Notation

Because of the high salaries of a few faculty members, R labelled the values using scientific notation. We can force R to not use scientific notation by setting R's global options with the `options()` function.

```
> options(scipen = 10000)

> ggplot(data = cehd, aes(x = years_at_u, y = annual_pay)) +
  geom_point() +
  facet_wrap(~ department, nrow = 2) +
  xlab("Years at the University of Minnesota")
```

The `scipen=` option takes a numeric value that helps R decide whether to print numeric values in fixed or exponential notation. Positive values bias towards fixed and negative towards scientific notation: fixed notation will be preferred unless it is more than *scipen* digits wider..



# Fine-Tuning Axis Scales

Adding a `scale()` layer allows much more fine-tuning of the axis scales. We have to specify which axis ( $x$  or  $y$ ) and whether the variable plotted along that axis is *continuous* or *discrete*. To fine-tune the  $y$ -axis in our example, we would use the `scale_y_continuous()` layer.

```
> ggplot(data = cehd, aes(x = years_at_u, y = annual_pay)) +  
  geom_point() +  
  facet_wrap(~ department, nrow = 2) +  
  xlab("Years at the University of Minnesota") +  
  scale_y_continuous(  
    name = "Years at the University of Minnesota",  
    breaks = c(50000, 100000, 150000, 200000, 250000, 300000)  
  )
```

The `name=` option labels the scale (it is the same as the `ylab()` layer in this case). The `breaks=` option adds break lines on the axis. There are several other options including `labels=` for labelling the break lines, etc.

# Prettying Up the Scales

We can get other options for labeling using the **scales** package. For example, we can add commas to separate by thousands in long values, or add the \$ for monetary values.

```
> library(scales)

> ggplot(data = cehd, aes(x = years_at_u, y = annual_pay)) +
  geom_point() +
  facet_wrap(~ department, nrow = 2) +
  xlab("Years at the University of Minnesota") +
  scale_y_continuous(labels = dollar)
```

The `labels=dollar` option is a built-in formatter from the **scales** package that adds the dollar sign and commas to the labels on a specified axis. Read more at <http://www.rdocumentation.org/packages/scales/versions/0.4.0>

# Customizing the Color


`scale()` functions can also be used to fine-tune colors and fills. For these you need to specify either *color* or *fill*, and also the palette you want to use. For example, `scale_color_manual()` can be used to manually set the colors when the `color=` argument is used.

```
> ggplot(data = cehd, aes(x = years_at_u, y = annual_pay)) +  
  geom_point(aes(color = title)) +  
  scale_fill_manual(  
    values = c("#599ad3", "#f9a65a", "#9e66ab")  
  )
```


`scale_fill_manual()` allows you to manually set the attributes associated with the fill aesthetic.

The `values=` argument sets the color values for each level of the factor.

Named colors or HEX values (both given as quoted character strings) can be used in `values=` argument of `scale_color_manual()` or `scale_fill_manual()`.



Default color palette




Palette provided with  
`scale_color_manual()`

`scale()` functions can also be used to change the name and labels in the legend.

```
> ggplot(data = cehd, aes(x = years_at_u, y = annual_pay)) +  
  geom_point(aes(color = title)) +  
  scale_fill_manual(  
    values = c("#599ad3", "#f9a65a", "#9e66ab"),  
    name = "Faculty Title"  
  )
```

The `name=` argument changes the title of the legend.



# Choosing a Color Palette

`colors()` will provide a list of all the **named colors** available in R.

```
> colors()

[1] "white"           "aliceblue"        "antiquewhite"
[4] "antiquewhite1"   "antiquewhite2"    "antiquewhite3"
[7] "antiquewhite4"   "aquamarine"       "aquamarine1"
[10] "aquamarine2"     "aquamarine3"      "aquamarine4"
      ⋮                ⋮                ⋮
```

Most universities have official colors. The University of Minnesota's two official colors in HEX (for electronic display) are:

- #ffcc33 (gold)
- #7a0019 (maroon)

See more at: <https://www.ur.umn.edu/brand/requirements-and-guidelines/color-and-type/>

Secondary Colors:										RGB HEX
										
91/0/19 5B0013	255/183/30 FFB71E	0/61/76 0B3D4C	202/119/0 CA7A29	114/110/32 726F2D	97/99/101 616365	145/120/91 91785B				
		127/158/165 809FA6	228/186/127 E5BA7F	184/182/143 B9B790	183/183/183 B7B7B7	211/191/150 D3BF96				
Primary Colors:										RGB HEX
										
122/0/25 7A0019	255/204/51 FFCC33	0/185/228 16BBE6	233/131/0 E98524	190/214/0 BCD530	204/204/204 CCCCCC	226/211/164 E2D3A4				
		127/220/241 87D5EB	224/193/127 F6C17E	222/234/127 DDE681						
										RGB HEX
144/0/33 900021	255/222/122 FFDE7A	161/222/233 A3DCE8	239/203/101 F0CC65	224/233/110 DFE670	213/214/210 D5D6D2	233/222/187 E9DEBB				
		208/238/244 D0EDF5	247/228/177 F7E7B2	239/244/182 EEF2B8	235/235/235 EBEBEB	240/233/209 F0E9D1				

The U of M also has an entire palette of secondary colors available at:  
[https://www.ur.umn.edu/brand/assets/pdf/secondary\\_colors\\_rgb.pdf](https://www.ur.umn.edu/brand/assets/pdf/secondary_colors_rgb.pdf)

# Pre-Selected Color Palettes


There are several "built-in" color palettes available for use in ggplot

Fill Scale	Color Scale	Description
<code>scale_fill_hue()</code>	<code>scale_color_hue()</code>	Colors evenly spaced around the color wheel
<code>scale_fill_grey()</code>	<code>scale_color_grey()</code>	Grey scale palette
<code>scale_fill_brewer()</code>	<code>scale_color_brewer()</code>	ColorBrewer palettes

# Default Color Palette

The `scale_color_hue()` and `scale_fill_hue()` functions use the default color palette. They are useful for changing the name and labels in the legend if you want to use the default palette.

```
> ggplot(data = cehd, aes(x = years_at_u, y = annual_pay)) +  
  geom_point(aes(color = title)) +  
  scale_color_hue(name = "Faculty Title")
```






# Grey Scale Color Palette

The `scale_color_grey()` and `scale_fill_grey()` functions use a greyscale color palette. This is a useful palette if you are printing in black-and-white.

```
> ggplot(data = cehd, aes(x = years_at_u, y = annual_pay)) +  
  geom_point(aes(color = title)) +  
  scale_color_grey(name = "Faculty Title")
```



# Color Brewer

Cynthia Brewer chose color palettes that not only are aesthetically pleasing, but also based on how humans perceive the colors that are displayed.

<http://www.colorbrewer2.org>

She has palettes for three different types of data

- **Qualitative/Categorical**—colors do not have a perceived order
- **Sequential**—colors have a *perceived order* and perceived difference between successive colors is uniform
- **Diverging**—two back-to-back sequential palettes starting from a common color (e.g., for Likert scale data)




There is a very readable introduction to color brewer palettes at <http://mkweb.bcgsc.ca/brewer/>

# Brewer Color Palette

The `scale_color_brewer()` and `scale_fill_brewer()` functions use a Cynthia Brewer's color palettes. You need to specify a palette using the `palette=` argument.


```
> ggplot(data = cehd, aes(x = years_at_u, y = annual_pay)) +  
  geom_point(aes(color = title)) +  
  scale_color_brewer(  
    name = "Faculty Title",  
    palette = "Set2"  
  )
```



# Palettes for Color-Blindness

About 8% of males and ½% of females have some form of color vision deficiency (good chance that someone in your audience will be one of these people)

Color *and* grey-scale palettes have been developed for use with people that have the more common forms of color-blindness



There is more information related to color-blindness and the creation of suitable color palettes for scientific figures at <http://jfly.iam.u-tokyo.ac.jp/color/>


There is a large body of research literature related to the creation of suitable color palettes for figures. As a starting point,

Lumley, T. (2006). Color-coding and color blindness in statistical graphics. *Statistical computing and graphics newsletter*. <http://www.amstat-online.org/sections/graphics/newsletter/Volumes/v172.pdf>

# Fine-Tuning the Theme

```
> ggplot(data = cehd, aes(x = years_at_u, y = annual_pay)) +  
  geom_point(aes(color = department)) +  
  theme(  
    axis.title.x = element_text(face = "bold"),  
    axis.title.y = element_text(face = "italic"),  
    legend.title = element_text(color = "blue")  
  )
```


The `theme()` function can be used to change *every* element in the plot (e.g., grid lines, font, color, etc.). See <http://docs.ggplot2.org/current/theme.html>



## Using "Built-In" Themes

```
> ggplot(data = cehd, aes(x = years_at_u, y = annual_pay)) +  
  geom_point(aes(color = department)) +  
  theme_bw()
```

The `theme_bw()` function is a "built-in" theme that uses a black-and-white background (rather than grey).




## There are many other themes available

- <http://drunks-and-lampposts.com/2012/10/02/clegg-vs-pleb-an-xkcd-esque-chart/>
- <https://github.com/jrnold/ggthemes>

```
# Install the ggthemes library then load it
> library(ggthemes)

> ggplot(data = cehd, aes(x = years_at_u, y = annual_pay)) +
  geom_point(aes(color = department)) +
  theme_ws() +
  scale_color_ws(name = "Faculty Title", palette = "rby")
```




You can also build your own themes and use them.

## Putting It All Together

```
> ggplot(data = cehd, aes(x = years_at_u, y = annual_pay)) +  
  geom_point(aes(color = title)) +  
  scale_color_brewer(name = "Faculty Title", palette = "Blues") +  
  xlab("Years at the University of Minnesota") +  
  scale_y_continuous(name = "Annual Base Salary", labels = dollar) +  
  theme_bw() +  
  facet_wrap(~ department, nrow = 2) +  
  guides(color = FALSE)
```

Make a rough sketch of the plot you think this syntax will produce.





*Figure 1.* Relationship between annual base salary (in U.S. dollars) and years of experience at the University of Minnesota for 2015 CEHD faculty members. This relationship is shown for all eight faculty-hiring departments. The three sequential colors represent the three levels of faculty, namely, Associate Professor (lightest blue); Assistant Professor (medium blue), and Professor (darkest blue).

#protip: It is easier to use a word-processor (e.g., Word) to add the figure title and caption than to try and get it formatted correctly using R.

#protip: When you only have a few colors, include them in the caption rather than as a legend if you have space limits.

# ggplot Resources

- **ggplot2 Cheatsheet:** A one-page (front and back) cheatsheet of ggplot2 syntax with pictures <https://www.rstudio.com/wp-content/uploads/2015/08/ggplot2-cheatsheet.pdf>
- **ggplot2 Extensions:** Third-party and user contributed extensions for some pretty cool plots <http://www.ggplot2-exts.org/index.html>
- **Cookbook for R:** Web-based version of Winston Chang's R Graphics Cookbook <http://www.cookbook-r.com/Graphs/> (The UMN library has electronic access to the actual book. Just search for "R Graphics Cookbook" and log-in with your x500.)
- **extrafonts package:** Use almost any font on your computer in your plots. <http://blog.revolutionanalytics.com/2012/09/how-to-use-your-favorite-fonts-in-r-charts.html>

#protip: Use Google to find out  
how to do just about anything with  
ggplot.