

# **Linear time sort**

# **Count Sort Algorithm**

Adapted from lectures of  
**Prof. Charles Leiserson , MIT &**  
**CLRC textbook 2<sup>nd</sup> ed. Chapters 8**

# Lecture Outline

- Linear Time sorting:
  - Non-comparison-based sort: Count Sort
- Analysis of CountSort

# Sorting in linear time




**Counting sort:** No comparisons between elements.

- *Input:*  $A[1 \dots n]$ , where  $A[j] \in \{1, 2, \dots, k\}$ .
- *Output:*  $B[1 \dots n]$ , sorted.
- *Auxiliary storage:*  $C[1 \dots k]$ .

# Counting sort

```
for  $i \leftarrow 1$  to  $k$   
    do  $C[i] \leftarrow 0$   
for  $j \leftarrow 1$  to  $n$   
    do  $C[A[j]] \leftarrow C[A[j]] + 1$   $\triangleright C[i] = |\{\text{key} = i\}|$   
for  $i \leftarrow 2$  to  $k$   
    do  $C[i] \leftarrow C[i] + C[i-1]$   $\triangleright C[i] = |\{\text{key} \leq i\}|$   
for  $j \leftarrow n$  downto  $1$   
    do  $B[C[A[j]]] \leftarrow A[j]$   
         $C[A[j]] \leftarrow C[A[j]] - 1$ 
```

# Counting sort example



# Loop 1


	1	2	3	4	5
<i>A</i> :	4	1	3	4	3

	1	2	3	4
<i>C</i> :	0	0	0	0

<i>B</i> :					
------------	--	--	--	--	--

**for**  $i \leftarrow 1$  **to**  $k$   
    **do**  $C[i] \leftarrow 0$

## Loop 2



**for**  $j \leftarrow 1$  **to**  $n$   
    **do**  $C[A[j]] \leftarrow C[A[j]] + 1$      $\triangleright C[i] = |\{\text{key} = i\}|$

## Loop 2

	1	2	3	4	5
<i>A</i> :	4	1	3	4	3

	1	2	3	4
<i>C</i> :	1	0	0	1

<i>B</i> :					
------------	--	--	--	--	--

**for**  $j \leftarrow 1$  **to**  $n$   
  **do**  $C[A[j]] \leftarrow C[A[j]] + 1$      $\triangleright C[i] = |\{\text{key} = i\}|$



	1	2	3	4	5
<i>A</i> :	4	1	3	4	3

	1	2	3	4
<i>C</i> :	1	0	1	1

<i>B</i> :					
------------	--	--	--	--	--

**for**  $j \leftarrow 1$  **to**  $n$   
     **do**  $C[A[j]] \leftarrow C[A[j]] + 1$      $\triangleright C[i] = |\{\text{key} = i\}|$

	1	2	3	4	5
<i>A</i> :	4	1	3	4	3

	1	2	3	4
<i>C</i> :	1	0	1	2

<i>B</i> :					
------------	--	--	--	--	--

**for**  $j \leftarrow 1$  **to**  $n$   
     **do**  $C[A[j]] \leftarrow C[A[j]] + 1$      $\triangleright C[i] = |\{\text{key} = i\}|$

	1	2	3	4	5
<i>A</i> :	4	1	3	4	3

	1	2	3	4
<i>C</i> :	1	0	2	2

<i>B</i> :					
------------	--	--	--	--	--

**for**  $j \leftarrow 1$  **to**  $n$   
     **do**  $C[A[j]] \leftarrow C[A[j]] + 1$      $\triangleright C[i] = |\{\text{key} = i\}|$

## Loop 3

	1	2	3	4	5
<i>A</i> :	4	1	3	4	3

	1	2	3	4
<i>C</i> :	1	0	2	2

<i>B</i> :					
------------	--	--	--	--	--

<i>C'</i> :	1	1	2	2
-------------	---	---	---	---

**for**  $i \leftarrow 2$  **to**  $k$

**do**  $C[i] \leftarrow C[i] + C[i-1]$       $\triangleright C[i] = |\{\text{key} \leq i\}|$

	1	2	3	4	5
<i>A</i> :	4	1	3	4	3

	1	2	3	4
<i>C</i> :	1	0	2	2

<i>B</i> :					
------------	--	--	--	--	--

<i>C'</i> :	1	1	3	2
-------------	---	---	---	---

**for**  $i \leftarrow 2$  **to**  $k$

**do**  $C[i] \leftarrow C[i] + C[i-1]$        $\triangleright C[i] = |\{\text{key} \leq i\}|$

	1	2	3	4	5
<i>A</i> :	4	1	3	4	3

	1	2	3	4
<i>C</i> :	1	0	2	2


<i>B</i> :					
------------	--	--	--	--	--

<i>C'</i> :	1	1	3	5
-------------	---	---	---	---


**for**  $i \leftarrow 2$  **to**  $k$

**do**  $C[i] \leftarrow C[i] + C[i-1]$       $\triangleright C[i] = |\{\text{key} \leq i\}|$

## Loop 4





```
for  $j \leftarrow n$  downto 1  
  do  $B[C[A[j]]] \leftarrow A[j]$   
       $C[A[j]] \leftarrow C[A[j]] - 1$ 
```





```
for  $j \leftarrow n$  downto 1  
  do  $B[C[A[j]]] \leftarrow A[j]$   
       $C[A[j]] \leftarrow C[A[j]] - 1$ 
```







```
for  $j \leftarrow n$  downto 1  
  do  $B[C[A[j]]] \leftarrow A[j]$   
       $C[A[j]] \leftarrow C[A[j]] - 1$ 
```



```

for  $j \leftarrow n$  downto 1
  do  $B[C[A[j]]] \leftarrow A[j]$ 
       $C[A[j]] \leftarrow C[A[j]] - 1$ 

```



```

for  $j \leftarrow n$  downto 1
  do  $B[C[A[j]]] \leftarrow A[j]$ 
       $C[A[j]] \leftarrow C[A[j]] - 1$ 
  
```

# Analysis

```
{ for  $i \leftarrow 1$  to  $k$ 
  do  $C[i] \leftarrow 0$ 
{ for  $j \leftarrow 1$  to  $n$ 
  do  $C[A[j]] \leftarrow C[A[j]] + 1$ 
{ for  $i \leftarrow 2$  to  $k$ 
  do  $C[i] \leftarrow C[i] + C[i-1]$ 
{ for  $j \leftarrow n$  downto  $1$ 
  do  $B[C[A[j]]] \leftarrow A[j]$ 
     $C[A[j]] \leftarrow C[A[j]] - 1$ 
.
```

# Analysis

$\Theta(k)$  { **for**  $i \leftarrow 1$  **to**  $k$   
          **do**  $C[i] \leftarrow 0$

$\Theta(n)$  { **for**  $j \leftarrow 1$  **to**  $n$   
          **do**  $C[A[j]] \leftarrow C[A[j]] + 1$

$\Theta(k)$  { **for**  $i \leftarrow 2$  **to**  $k$   
          **do**  $C[i] \leftarrow C[i] + C[i-1]$

$\Theta(n)$  { **for**  $j \leftarrow n$  **downto**  $1$   
          **do**  $B[C[A[j]]] \leftarrow A[j]$   
               $C[A[j]] \leftarrow C[A[j]] - 1$

---

$\Theta(n + k)$

# Running time

If  $k = O(n)$ , then counting sort takes  $\Theta(n)$  time.

- But, sorting takes  $\Omega(n \lg n)$  time!
- Where's the fallacy?

## Answer:

- *Comparison sorting* takes  $\Omega(n \lg n)$  time.
- Counting sort is not a *comparison sort*.
- In fact, not a single comparison between elements occurs!

# Stable Sort

Counting sort is a *stable* sort: it preserves the input order among equal elements.

