

LAB - 6

Huffman Coding & Job Sequencing Problem

Huffman Coding:

CODE:

```
#include <stdio.h>
#include <stdlib.h>
#define MAX 100
struct Node {
    char data;
    unsigned freq;
    struct Node *left, *right;
};
struct Node* newNode(char data, unsigned freq) {
    struct Node* temp = (struct
    Node*)malloc(sizeof(struct Node));
    temp->data = data;
    temp->freq = freq;
    temp->left = temp->right = NULL;
    return temp;
}
struct MinHeap {
    unsigned size;
    struct Node* arr[MAX];
};
void swap(struct Node** a, struct Node** b) {
    struct Node* t = *a;
    *a = *b;
    *b = t;
}
void heapify(struct MinHeap* heap, int i) {
    int smallest = i;
    int left = 2*i + 1;
    int right = 2*i + 2;
    if (left < heap->size && heap->arr[left]->freq <
    heap->arr[smallest]->freq)
        smallest = left;

    if (right < heap->size && heap->arr[right]->freq <
    heap->arr[smallest]->freq)
        smallest = right;

    if (smallest != i) {
```

```

        swap(&heap->arr[i], &heap->arr[smallest]);
        heapify(heap, smallest);
    }
}

struct Node* extractMin(struct MinHeap* heap) {
    struct Node* temp = heap->arr[0];
    heap->arr[0] = heap->arr[--heap->size];
    heapify(heap, 0);
    return temp;
}

void insertHeap(struct MinHeap* heap, struct Node*
node) {
    int i = heap->size++;
    while (i && node->freq < heap->arr[(i-1)/2]->freq)
    {
        heap->arr[i] = heap->arr[(i-1)/2];
        i = (i-1)/2;
    }

    heap->arr[i] = node;
}

struct Node* buildTree(char data[], int freq[], int size)
{
    struct MinHeap heap;
    heap.size = 0;
    for (int i = 0; i < size; i++)
        heap.arr[heap.size++] = newNode(data[i], freq[i]);

    for (int i = (heap.size - 1) / 2; i >= 0; i--)
        heapify(&heap, i);

    while (heap.size > 1) {
        struct Node* left = extractMin(&heap);
        struct Node* right = extractMin(&heap);

        struct Node* top = newNode('$', left->freq +
right->freq);
        top->left = left;
        top->right = right;

        insertHeap(&heap, top);
    }

    return extractMin(&heap);
}

```

```

}
void printCodes(struct Node* root, int arr[], int top)
{
if (root->left) {
arr[top] = 0;
printCodes(root->left, arr, top + 1);
}
if (root->right) {
arr[top] = 1;
printCodes(root->right, arr, top + 1);
}

if (!root->left && !root->right) {
printf("%c: ", root->data);
for (int i = 0; i < top; i++)
printf("%d", arr[i]);
printf("\n");
}
}

int main() {
char data[] = {'A','B','C','D','E','F'};
int freq[] = {5,9,12,13,16,45};
int size = sizeof(data) / sizeof(data[0]);

struct Node* root = buildTree(data, freq, size);

int arr[MAX], top = 0;

printf("Huffman Codes:\n");
printCodes(root, arr, top);

return 0;
}

```

OUTPUT:

```

doniraj@King-of-ghost:~$ nano huffman.c
doniraj@King-of-ghost:~$ gcc huffman.c -o huffman
doniraj@King-of-ghost:~$ ./huffman
Huffman Codes:
F: 0
C: 100
D: 101
A: 1100
B: 1101
E: 111
doniraj@King-of-ghost:~$ |

```

Job Sequencing Problem

CODE:

```
#include <stdio.h>
#include <stdlib.h>
typedef struct {
    int id;
    int deadline;
    int profit;
} Job;

int compare(const void *a, const void *b) {
    Job *j1 = (Job *)a;
    Job *j2 = (Job *)b;
    return j2->profit - j1->profit;
}

int main() {
    int n;
    printf("Enter number of jobs: ");
    scanf("%d", &n);
    Job jobs[n];

    for(int i = 0; i < n; i++) {
        printf("Enter deadline and profit for job %d: ", i+1);
        scanf("%d %d", &jobs[i].deadline, &jobs[i].profit);
        jobs[i].id = i + 1;
    }

    qsort(jobs, n, sizeof(Job), compare);

    int maxDeadline = 0;

    for(int i = 0; i < n; i++)
        if(jobs[i].deadline > maxDeadline)
            maxDeadline = jobs[i].deadline;

    int slot[maxDeadline];

    for(int i = 0; i < maxDeadline; i++)
        slot[i] = -1;
```

```

int totalProfit = 0;

for(int i = 0; i < n; i++) {
    for(int j = jobs[i].deadline - 1; j >= 0; j--) {
        if(slot[j] == -1) {
            slot[j] = jobs[i].id;
            totalProfit += jobs[i].profit;
            break;
        }
    }
}

printf("\nScheduled Jobs: ");
for(int i = 0; i < maxDeadline; i++)
    if(slot[i] != -1)
        printf("J%d ", slot[i]);

printf("\nTotal Profit = %d\n", totalProfit);

return 0;
}

```

OUTPUT:

```

doniraj@King-of-ghost:~$ nano sequencing.c
doniraj@King-of-ghost:~$ gcc sequencing.c -o sequencing
doniraj@King-of-ghost:~$ ./sequencing
Enter number of jobs: 5
Enter deadline and profit for job 1: 4 20
Enter deadline and profit for job 2: 1 10
Enter deadline and profit for job 3: 1 40
Enter deadline and profit for job 4: 3 30
Enter deadline and profit for job 5: 1 45

Scheduled Jobs: J5 J4 J1
Total Profit = 95

```

~DONIRAJ.SALINDRA
~CH.SC.U4CSE24245