

CPSC 340 Formula Sheet

Norms:

$$\|\mathbf{y}\|_2 = \sqrt{\sum_{i=1}^n y_i^2} \quad \|\mathbf{y}\|_1 = \sum_{i=1}^n |y_i|$$

$$\|\mathbf{y}\|_0 = \sum_{i=1}^n (1 \text{ if } y_i \neq 0)$$

$$\|\mathbf{y}\|_\infty = \max(|y_1|, |y_2|, \dots, |y_n|)$$

$$\|W\|_F = \sqrt{\sum_{j=1}^d \sum_{c=1}^k w_{jc}^2}$$

Supervised Learning

K-Nearest Neighbors

- Find k nearest values of \mathbf{x}_i that are most similar to $\tilde{\mathbf{x}}_i$
- Use mode of corresponding y_i

Naive Bayes

$$P(y_i | \mathbf{x}_i) = \frac{P(\mathbf{x}_i | y_i)P(y_i)}{P(\mathbf{x}_i)} \propto P(\mathbf{x}_i | y_i)P(y_i)$$

Conditional Independence Assumption:

$$P(\mathbf{x}_i | y_i) \approx \prod_{j=1}^d P(x_{ij} | y_i)$$

Probability Assumption:

$$P(x_{ij} = k | y_i = c) = \frac{\# \text{ times } (y_i = c, x_{ij} = k)}{n}$$

Laplace Smoothing:

- Add β to numerator, and add 1 for each possible label to denominator.

Regression

Linear Regression:

$$\hat{y}_i = \mathbf{w}^T \mathbf{x}_i$$

Least Squares Objective:

$$f(\mathbf{w}) = \frac{1}{2} \sum_{i=1}^n (\mathbf{w}^T \mathbf{x}_i - y_i)^2$$

Normal Equations:

$$X^T X \mathbf{w} = X^T \mathbf{y}$$

Huber Loss Approximation:

$$h(z) = \begin{cases} \frac{1}{2} z^2 & |z| < 1 \\ |z| - \frac{1}{2} & |z| > 1 \end{cases}$$

Log-sum-exp Approximation:

$$\max_i \{z_i\} \approx \log(\sum_i \exp(z_i))$$

Gradient Descent:

$$\mathbf{w}^{t+1} = \mathbf{w}^t - \alpha^t \nabla f(\mathbf{w}^t)$$

General Polynomial Features ($d = 1$):

$$Z = \begin{bmatrix} 1 & x_1 & x_1^2 & \dots & x_1^p \\ 1 & x_2 & x_2^2 & \dots & x_2^p \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 1 & x_n & x_n^2 & \dots & x_n^p \end{bmatrix}$$

Gaussian Radial Basis Functions:

$$g(\varepsilon) = \exp\left(-\frac{\varepsilon^2}{2\sigma^2}\right)$$

Gaussian Radial Basis Transform:

$$Z = \begin{bmatrix} g(\|\mathbf{x}_1 - \mathbf{x}_1\|) & \dots & g(\|\mathbf{x}_1 - \mathbf{x}_n\|) \\ g(\|\mathbf{x}_2 - \mathbf{x}_1\|) & \dots & g(\|\mathbf{x}_2 - \mathbf{x}_n\|) \\ \vdots & \ddots & \vdots \\ g(\|\mathbf{x}_n - \mathbf{x}_1\|) & \dots & g(\|\mathbf{x}_n - \mathbf{x}_n\|) \end{bmatrix}$$

Gram Matrix:

$$K = XX^T$$

Kernel Trick:

$$\hat{\mathbf{y}} = \tilde{Z}\mathbf{v} = \tilde{Z}Z^T(ZZ^T + \lambda I)\mathbf{y} = \tilde{K}(K + \lambda I)\mathbf{y}$$

Kernel Trick with Polynomials:

$$K_{ij} = (1 + \mathbf{x}_i^T \mathbf{x}_j)^p \quad \tilde{K}_{ij} = (1 + \tilde{\mathbf{x}}_i^T \mathbf{x}_j)^p$$

Linear Classifiers

Binary Classification:

- Encode using $y_i \in \{-1, 1\}$
- Use $\text{sign}(\mathbf{w}^T \mathbf{x}_i)$ as prediction.

0-1 Loss Function (# of classification errors):

$$f(\mathbf{w}) = \|\text{sign}(X\mathbf{w}) - \mathbf{y}\|_0$$

Hinge Loss (convex upper bound on 0-1 loss):

$$f(\mathbf{w}) = \sum_{i=1}^n \max\{0, 1 - y_i \mathbf{w}^T \mathbf{x}_i\}$$

Support Vector Machine:

$$f(\mathbf{w}) = \sum_{i=1}^n \max\{0, 1 - y_i \mathbf{w}^T \mathbf{x}_i\} + \frac{\lambda}{2} \|\mathbf{w}\|_2^2$$

Logistic Loss:

$$f(\mathbf{w}) = \sum_{i=1}^n \log(1 + \exp(-y_i \mathbf{w}^T \mathbf{x}_i))$$

Softmax for class c :

$$P(y_i = c) = \frac{\exp(\mathbf{w}_c^T \mathbf{x}_i)}{\sum_{c=1}^k \exp(\mathbf{w}_c^T \mathbf{x}_i)}$$

Softmax Loss for classes y_i :

$$f(\mathbf{w}) = -\mathbf{w}_{y_i}^T \mathbf{x}_i + \log\left(\sum_{c=1}^k \exp(\mathbf{w}_c^T \mathbf{x}_i)\right)$$

MLE and MAP

Maximum Likelihood Estimation:

$$\hat{\mathbf{w}} \in \underset{\mathbf{w}}{\text{argmax}} \{P(D | \mathbf{w})\}$$

Minimizing Negative Log Likelihood to maximize likelihood:

$$\hat{\mathbf{w}} \in \underset{\mathbf{w}}{\text{argmin}} \{-\log(P(D | \mathbf{w}))\}$$

Maximum a Posteriori Estimation:

$$\hat{\mathbf{w}} \in \underset{\mathbf{w}}{\text{argmax}} \{P(\mathbf{w} | D)\}$$

Minimizing Negative Log Likelihood to maximize a posteriori:

$$\mathbf{w} \in \underset{\mathbf{w}}{\text{argmin}} \left\{ -\sum_{i=1}^n \log(P(\mathbf{D}_i | \mathbf{w})) - \log(P(\mathbf{w})) \right\}$$

Matrix Factorization

$$X \approx ZW \quad \mathbf{x}_i \approx W^T \mathbf{z}_i \quad x_{ij} \approx (\mathbf{w}^j)^T \mathbf{z}_i$$

Principal Component Analysis

PCA Objective Function:

$$f(W, Z) = \sum_{i=1}^n \|\mathbf{W}^T \mathbf{z}_i - \mathbf{x}_i\|_2^2 = \|ZW - X\|_F^2$$

Prediction:

- Center: replace each \tilde{x}_{ij} with $(\tilde{x}_{ij} - \mu_j)$
- Find \tilde{Z} minimizing squared error:
 $\tilde{Z} = \tilde{X}W^T(WW^T)^{-1}$

Gradients:

$$\nabla f(W, Z_0) = Z^T ZW - Z^T X$$

$$\nabla f(W_0, Z) = ZWW^T - XW^T$$

Variance Explained:

$$1 - \frac{\|ZW - X\|_F^2}{\|X\|_F^2}$$

Non-Negative Matrix Factorization

Require Z, W to have non-negative values.

Projected Gradient Algorithm:

$$\mathbf{w}^{t+1/2} = \mathbf{w}^t - \alpha^t \nabla f(\mathbf{w}^t)$$

$$\mathbf{w}_j^{t+1} = \max\{0, \mathbf{w}_j\}$$

Multi-Dimensional Scaling

Traditional MDS cost function:

$$f(Z) = \sum_{i=1}^n \sum_{j=i+1}^n (\|\mathbf{z}_i - \mathbf{z}_j\| - \|\mathbf{x}_i - \mathbf{x}_j\|)^2$$

Neural Networks

Objective function for one hidden layer:

$$f(\mathbf{v}, W) = \frac{1}{2} \sum_{i=1}^n (\mathbf{v}^T \mathbf{h}(W\mathbf{x}_i) - y_i)^2$$

Updated April 18, 2021

<https://github.com/DonneyF/formula-sheets>