Next generation platform for implementing fast gates in ion trap quantum computation

D. Webb S. Saner O. Bazavan M. Minder C.J. Ballance

Ion Trap Quantum Computing Group, Department of Physics, University of Oxford

Scalable trapped-ion quantum computation relies on the development of high-fidelity fast entangling gates in a many ion crystal. Conventional geometric phase gates either suffer from scattering errors or off-resonant carrier excitations. A potential route to achieve fast entanglement is creating a standing wave which can suppress the unwanted carrier coupling.

Non-Adiabatic Mølmer Sørenson Gates

- Two qubit gates are implemented by coupling spin with shared motion of the ions.
- Fast entangling gates enable deeper quantum computational circuit depths for given level of incoherent error.
- But going fast excites multiple motional modes ("spectator modes") which can introduces errors.
- Mølmer Sørenson (MS) interaction is common two-qubit gate which requires a bichromatic field incident on the ions. Using travelling waves gives the Hamiltonian

$$\hat{H}_{MS-TW} = \hbar\Omega\hat{S}_{\phi-\pi/2}\cos(\delta t) + \hbar\Omega\eta\hat{S}_{\phi}\cos(\delta t)(\hat{a}e^{-i\omega_z t} + \hat{a}^{\dagger}e^{i\omega_z t})$$

with the first term being the carrier whilst the second is the desired coupling.

- As these terms do not commute, in the ??interaction picture?? this Hamiltonian may be expressed as [Xref Canzz?X]:

$$\hat{H}_{MS-TW} = \hbar\eta\Omega(J_0(2\Omega/\delta) + J_2(2\Omega/\delta))\cdot\cos(\delta t)\hat{S}_{\phi}(\hat{a}e^{-i\omega_z t} + \hat{a}^{\dagger}e^{i\omega_z t})$$

- **Carrier term:** causes the spin dependent force coupling to be modulated by (J0+J2).
- **Spectator excitation:** Amplitude shaped pulses [ref vera] effectively remove "spectator" error by closing phase loops of all excited modes.





Standing Wave Single and MS Gates

- Using standing wave gives complete control over phase visible to ions.
- This extra freedom allows fast gates by preventing the saturation effect seen in the travelling MS.
- Bichromatic standing wave Hamiltonian where ions are seperated by $n\lambda/2$:

$$\hat{H}_{MS-SW} = \hbar 2\Omega\hat{S}_{\phi}\cos(\delta t)\sin(\Delta\phi/2) + \hbar 2\Omega\eta\hat{S}_{\phi}\cos(\delta t)(\hat{a}e^{-i\omega_z t} + \hat{a}^{\dagger}e^{i\omega_z t})\cos(\Delta\phi/2)$$

- Setting $\Delta\phi = 0$ (ions sitting at antinodes) we suppress the carrier term and maximise sideband coupling.
- However standing waves require phase stabilisation to perform coherent interactions.

Phase Stabilization



- Passively using enclosure and actively by feedback process to AOM.
  1) Fast drifts removed utilising interference of light from the two branches on a photodiode (PD).
  X XX diagram rather than words. 2) As PD lockpoint is 30 cm away from ions, a second feedback loop using the ion as a sensor is required. We do this by performing a $\pi/2$-pulse using arm 1 ($\pi/2$, b1) followed immediately by a $\pi/2$-pulse using arm 2 ($pi/2$, b2). This is equivalent to a zero-delay Ramsey sequence, which gives a signal sensitive on the difference in phase between the two pulses, hence the relative phase be- tween the branches.
- No detriment using lattice: Standard Randomized Benchmarking gave quality of our single qubit rotations per gate to be $\epsilon = 0.173(3)\%$ for a travelling wave and $\epsilon = 0.144(3)\%$ for the standing wave.

Experimental Results

Results from Cnulling:





New Platform

- New ion trap experiment in development for exploring fast gate regime.
- Two high NA lenses allow optical access on both faces of the trap to create an array of singly addressing standing waves.
- 3D segmented trap design from NPL facilitates low heating rates whilst enabling ion shuttling and crystal rotations.
- Calcium 40
- quadropole transition used.
- MuMetal shield and permanent magnets.
- fig: solidworks of new experiment