

UNIVERSITY OF
OXFORD

Lifting the speed limit: fast entangling gates using phase stable optical lattices in trapped ions

Ion Trap Quantum Computing Group, Department of Physics, University of Oxford

Non-Adiabatic Mølmer Sørensen Gates

- Two qubit gates are implemented by coupling spin with shared motion of the ions.
- Fast entangling gates enable deeper quantum computational circuits for a given level of incoherent error.
- Mølmer Sørensen (MS) interaction is common two-qubit gate which requires a bichromatic field incident on the ions. Using a quadrupole transition, travelling wave to interact with the ions gives the Hamiltonian


$$\hat{H}_{MS-TW} = \hbar\Omega\hat{S}_{\phi-\pi/2}\cos(\delta t) + \hbar\Omega\eta\hat{S}_{\phi}\cos(\delta t)(\hat{a}e^{-i\omega_z t} + \hat{a}^\dagger e^{i\omega_z t})$$

with the first term being the carrier whilst the second is the desired coupling.

- As these terms do not commute, in the interaction picture this Hamiltonian may be expressed as [1]:

$$\hat{H}_{MS-TW} = \hbar\eta\Omega(J_0(2\Omega/\delta) + J_2(2\Omega/\delta)) \cdot \cos(\delta t)\hat{S}_{\phi}(\hat{a}e^{-i\omega_z t} + \hat{a}^\dagger e^{i\omega_z t})$$

- Carrier term:** causes the spin dependent force coupling to be modulated by $(J_0 + J_2)$.
- Imperfectly transferring to the interaction picture leads to further gate errors.




Standing Wave Single and MS Gates


- Using standing wave gives complete control over phase visible to ions.
- Bichromatic standing wave Hamiltonian where ions are separated by $n\lambda/2$:

$$\hat{H}_{MS-SW} = \hbar 2\Omega\hat{S}_{\phi}\cos(\delta t)\sin(\Delta\phi/2) + \hbar 2\Omega\eta\hat{S}_{\phi}\cos(\delta t)(\hat{a}e^{-i\omega_z t} + \hat{a}^\dagger e^{i\omega_z t})\cos(\Delta\phi/2)$$


bichromatic standing wave



- Setting $\Delta\phi = 0$ (ions sitting at antinodes) we suppress the carrier term and maximise sideband coupling.
- This extra freedom allows fast gates by preventing the saturation effect seen in the travelling MS.
- Requires standing wave phase stable with respect to the ion position for coherent interactions.
- Additional errors as Non-Adiabatic (fast) gates excite multiple motional modes ("spectator modes").
- Spectator excitation:** Amplitude shaped pulses [2, 3] effectively remove "spectator" error by closing phase loops of all excited modes.



Phase Stabilization




Abstract: Scalable trapped-ion quantum computation relies on the development of high-fidelity fast entangling gates in a many ion crystal. Conventional geometric phase gates either suffer from scattering errors or off-resonant carrier excitations. A potential route to achieve fast entanglement is creating a standing wave which can suppress the unwanted carrier coupling.

We present an experimental realization of this carrier suppression in the 674 nm quadrupole transition of $^{88}\text{Sr}^+$. We produce a phase stable standing wave with residual fluctuations at the ion position of $\lambda/50$. Carrier suppression of 26 dB is demonstrated leading to two qubit MS gates with improved fidelity at shorter gate durations.

Optical lattice driven two qubit gates

- Experimental demonstration of gates at carrier null point with $^{88}\text{Sr}^+$ and 674 nm laser.
- Standard Randomized Benchmarking of single qubit rotations found gate errors of $\epsilon = 0.173(3)\%$ for travelling wave, $\epsilon = 0.144(3)\%$ for standing wave.
- Universal gate set with phase stabilized standing-waves.
- Carrier suppression by 26 dB.
- Standing wave MS maintains $\geq 95\%$ fidelity at short gate durations in contrast to travelling wave MS sharp drop off at $\sim 25 \mu\text{s}$.



New Platform

- New $^{40}\text{Ca}^+$ ion trap experiment in development for exploring fast gate regime using 729 nm quadrupole laser.
- Two high NA lenses create an array of singly addressing standing waves.
- 3D segmented trap design from NPL facilitates low heating rates (expected: < 10 q/s @ 1.5 MHz) whilst enabling ion shuttling and crystal rotations.
- MuMetal shield and permanent magnets for stable B field.

