


Lifting the speed limit: fast entangling gates using phase stable optical lattices in trapped ions

Ion Trap Quantum Computing Group, Department of Physics, University of Oxford

Non-Adiabatic Mølmer Sørenson Gates

- Two qubit gates are implemented by coupling spin with shared motion of the ions.
- Fast entangling gates enable deeper quantum computational circuits for a given level of incoherent error.
- Mølmer Sørenson (MS) interaction is common two-qubit gate which requires a bichromatic field incident on the ions. Using a quadropole transition, travelling wave to interact with the ions gives the Hamiltonian



D_{5/2}

 $\hat{H}_{MS-TW} = \hbar \Omega \hat{S}_{\phi-\pi/2} \cos{(\delta t)} + \hbar \Omega \eta \hat{S}_{\phi} \cos{(\delta t)} (\hat{a} e^{-i\omega_z t} + \hat{a}^{\dagger} e^{i\omega_z t})$ with the first term being the carrier whilst the second is the desired coupling.

• As these terms do not commute, in the interaction picture this Hamiltonian may be expressed as [1]:


$$\hat{H}_{MS-TW} = \hbar \eta \Omega (J_0(2\Omega/\delta) + J_2(2\Omega/\delta)) \cdot \cos(\delta t) \hat{S}_{\phi}(\hat{a}e^{-i\omega_z t} + \hat{a}^{\dagger}e^{i\omega_z t})$$

- Carrier term: causes the spin dependent force coupling to be modulated by (J_0+J_2) .
- Imperfectly transferring to the interaction picture leads to further gate errors.


Standing Wave Single and MS Gates

- Using standing wave gives complete control over phase visible to ions.
- Bichromatic standing wave Hamiltonian where ions are seperated by $n\lambda/2$:

 $\hat{H}_{MS-SW} = \hbar 2\Omega \hat{S}_{\phi} \cos(\delta t) \sin(\Delta \phi/2) + \hbar 2\Omega \eta \hat{S}_{\phi} \cos(\delta t) (\hat{a}e^{-i\omega_z t} + \hat{a}^{\dagger}e^{i\omega_z t}) \cos(\Delta \phi/2)$



- Setting $\Delta \phi = 0$ (ions sitting at antinodes) we suppress the carrier term and maximise sideband coupling.
- This extra freedom allows fast gates by preventing the saturation effect seen in the travelling MS.
 Requires standing wave phase stable with respect to the ion position for coherent interactions.
- Requires standing wave phase stable with respect to the ion position for conerent interactions.
 Additional errors as Non-Adiabatic (fast) gates excite multiple motional modes ("spectator modes").
- Spectator excitation: Amplitude shaped pulses [2, 3] effectively remove "spectator" error by closing phase loops of all excited modes.




Adiabatic

Phase Stabilization

Non-Adiabatic

With pulse shaping





Abstract: Scalable trapped-ion quantum computation relies on the development of high-fidelity fast entangling gates in a many ion crystal. Conventional geometric phase gates either suffer from scattering errors or off-resonant carrier excitations. A potential route to achieve fast entanglement is creating a standing wave which can suppress the unwanted carrier coupling.

We present an experimental realization of this carrier suppression in the 674 nm quadropole transition of 88 Sr⁺. We produce a phase stable standing wave with residual fluctuations at the ion position of $\lambda/50$. Carrier suppression of 26 dB is demonstrated leading to two qubit MS gates with improved fidelity at shorter gate durations.

Optical lattice driven two qubit gates

- Experimental demonstration of gates at carrier null point with ⁸⁸Sr⁺ and 674 nm laser.
- Standard Randomized Benchmarking of single qubit rotations found gate errors of $\epsilon=0.173(3)\%$ for travelling wave, $\epsilon=0.144(3)\%$ for standing wave.
- Universal gate set with phase stabilized standing-waves.
- Carrier suppression by 26 dB.
- Standing wave MS maintains $\geq 95\%$ fidelity at short gate durations in contrast to travelling wave MS sharp drop off at $\sim 25~\mu s$.






Single Qubit monochromatic

standing wave

Qubit transition | Carrier Nulled



New Platform

- New ⁴⁰Ca⁺ ion trap experiment in development for exploring fast gate regime using 729 nm quadropole laser.
- Two high NA lenses create an array of singly addressing standing waves.
- 3D segmented trap design from NPL facilitates low heating rates (expected: $< 10~\rm q/s \ @ 1.5~\rm MHz)$ whilst enabling ion shuttling and crystal rotations.
- MuMetal shield and permanent magnets for stable B field.

