

I-Déployer un Serveur Web et Héberger un Site Statique

```
donsam@donsam-VirtualBox:~$ sudo apt update
[sudo] Mot de passe de donsam :
Réception de :1 http://security.ubuntu.com/ubuntu noble-security InRelease [126
kB]
Atteint :2 http://archive.ubuntu.com/ubuntu noble InRelease
Réception de :3 http://archive.ubuntu.com/ubuntu noble-updates InRelease [126 kB
]
Réception de :4 http://archive.ubuntu.com/ubuntu noble-backports InRelease [126
kB]
Réception de :5 http://security.ubuntu.com/ubuntu noble-security/main amd64 Pack
ages [1 410 kB]
Réception de :6 http://archive.ubuntu.com/ubuntu noble/main Translation-fr [491
kB]
Réception de :7 http://archive.ubuntu.com/ubuntu noble/restricted Translation-fr
 [3 292 B]
Réception de :8 http://archive.ubuntu.com/ubuntu noble/universe Translation-fr [
3 898 kB]
```

```
donsam@donsam-VirtualBox:~$ sudo apt upgrade -y
Lecture des listes de paquets... Fait
Construction de l'arbre des dépendances... Fait
Lecture des informations d'état... Fait
Calcul de la mise à jour... Fait
Les NOUVEAUX paquets suivants seront installés :
  linux-headers-6.14.0-37-generic linux-hwe-6.14-headers-6.14.0-37
  linux-hwe-6.14-tools-6.14.0-37 linux-image-6.14.0-37-generic
  linux-modules-6.14.0-37-generic linux-modules-extra-6.14.0-37-generic
  linux-tools-6.14.0-37-generic
```

Installation du serveur Apache

```
donsam@donsam-VirtualBox:~$ sudo apt install apache2 -y
Lecture des listes de paquets... Fait
Construction de l'arbre des dépendances... Fait
Lecture des informations d'état... Fait
Les paquets supplémentaires suivants seront installés :
  apache2-bin apache2-data apache2-utils libapr1t64 libaprutil1-dbd-sqlite3
  libaprutil1-ldap libaprutil1t64
```

```
donsam@donsam-VirtualBox:~$ sudo systemctl status apache2
● apache2.service - The Apache HTTP Server
   Loaded: loaded (/usr/lib/systemd/system/apache2.service; enabled; preset: v
   Active: active (running) since Sat 2026-01-31 09:01:27 EST; 1min 14s ago
     Docs: https://httpd.apache.org/docs/2.4/
    Main PID: 29718 (apache2)
      Tasks: 55 (limit: 4605)
     Memory: 5.1M (peak: 5.5M)
        CPU: 37ms
    CGroup: /system.slice/apache2.service
            └─29718 /usr/sbin/apache2 -k start
              └─29719 /usr/sbin/apache2 -k start
                └─29721 /usr/sbin/apache2 -k start
```



Ubuntu

Apache2 Default Page

It works!

This is the default welcome page used to test the correct operation of the Apache2 server after installation on Ubuntu systems. It is based on the equivalent page on Debian, from which the Ubuntu Apache packaging is derived. If you can read this page, it means that the Apache HTTP server installed at this site is working properly. You should **replace this file** (located at `/var/www/html/index.html`) before continuing to operate your HTTP server.

If you are a normal user of this web site and don't know what this page is about, this probably means that the site is currently unavailable due to maintenance. If the problem persists, please contact the site's administrator.

Configuration Overview

Ubuntu's Apache2 default configuration is different from the upstream default configuration, and split into several files optimized for interaction with Ubuntu tools. The configuration system is **fully documented in `/usr/share/doc/apache2/README.Debian.gz`**. Refer to this for the full documentation. Documentation for the web server itself can be found by accessing the **manual** if the `apache2-doc` package was installed on this server.

The configuration layout for an Apache2 web server installation on Ubuntu systems is as follows:

```
/etc/apache2/  
|-- apache2.conf  
|   |-- ports.conf  
|-- mods-enabled
```



Création du dossier web

```
donsam@donsam-VirtualBox:~$ cd Bureau
donsam@donsam-VirtualBox:~/Bureau$ mkdir ProjetScolaire
donsam@donsam-VirtualBox:~/Bureau$ cd ProjetScolaire
donsam@donsam-VirtualBox:~/Bureau/ProjetScolaire$ sudo touch index.html
donsam@donsam-VirtualBox:~/Bureau/ProjetScolaire$ sudo touch design.css
donsam@donsam-VirtualBox:~/Bureau/ProjetScolaire$ sudo nano index.html
donsam@donsam-VirtualBox:~/Bureau/ProjetScolaire$ sudo nano design.css
donsam@donsam-VirtualBox:~/Bureau/ProjetScolaire$
```

```
donsam@donsam-VirtualBox: /var/www/html/ProjetScolaire
donsam@donsam-VirtualBox:~$ cd /var/www/html
donsam@donsam-VirtualBox:/var/www/html$ ls
index.html
donsam@donsam-VirtualBox:/var/www/html$ sudo cp -r /home/donsam/ProjetScolaire .
[sudo] Mot de passe de donsam :
donsam@donsam-VirtualBox:/var/www/html$ ls
index.html  ProjetScolaire
donsam@donsam-VirtualBox:/var/www/html$ cd ProjetScolaire
donsam@donsam-VirtualBox:/var/www/html/ProjetScolaire$ ls
design.css  index.html
```

```
donsam@donsam-VirtualBox: /etc/apache2/sites-available
donsam@donsam-VirtualBox:/var/www/html/ProjetScolaire$ sudo chmod -R 755 /var/www/html/ProjetScolaire
donsam@donsam-VirtualBox:/var/www/html/ProjetScolaire$ cd ..
donsam@donsam-VirtualBox:/var/www/html$ cd /etc/apache2
donsam@donsam-VirtualBox:/etc/apache2$ ls
apache2.conf  conf-enabled  magic  mods-enabled  sites-enabled
conf-available  envvars  mods-available  ports.conf  sites-enabled
donsam@donsam-VirtualBox:/etc/apache2$ cd sites-available
donsam@donsam-VirtualBox:/etc/apache2/sites-available$ ls
000-default.conf  default-ssl.conf
donsam@donsam-VirtualBox:/etc/apache2/sites-available$ sudo cp 000-default.conf monsite.conf
donsam@donsam-VirtualBox:/etc/apache2/sites-available$ ls
000-default.conf  default-ssl.conf  monsite.conf
donsam@donsam-VirtualBox:/etc/apache2/sites-available$ sudo chmod 777 000-default.conf
donsam@donsam-VirtualBox:/etc/apache2/sites-available$ sudo nano 000-default.conf
donsam@donsam-VirtualBox:/etc/apache2/sites-available$
```

```
GNU nano 7.2 000-default.conf *
<VirtualHost *:80>
    # The ServerName directive sets the request scheme, hostname and port that
    # the server uses to identify itself. This is used when creating
    # redirection URLs. In the context of virtual hosts, the ServerName
    # specifies what hostname must appear in the request's Host: header to
    # match this virtual host. For the default virtual host (this file) this
    # value is not decisive as it is used as a last resort host regardless.
    # However, you must set it for any further virtual host explicitly.
    #ServerName www.example.com

    ServerAdmin webmaster@localhost
    DocumentRoot /var/www/html/ProjetScolaire
```

Hébergement du site web



Résolution de nom de domaine

```
donsam@donsam-VirtualBox: /etc/apache2/sites-available
GNU nano 7.2 /etc/hosts
127.0.0.1 localhost
127.0.1.1 donsam-VirtualBox
192.168.56.107 centreabel.ht
# The following lines are desirable for IPv6 capable hosts
::1 ip6-localhost ip6-loopback
fe00::0 ip6-localnet
ff00::0 ip6-mcastprefix
ff02::1 ip6-allnodes
ff02::2 ip6-allrouters
```

Test du site web dans firefox

