

4. Iron is extracted from iron oxide inside the blast furnace.



Iron oxide, coke and limestone are all fed in at the top of the furnace.

- (a) Describe the **two** main functions of coke in the furnace.

[3]

.....

.....



.....

.....

.....



- (b) Limestone is added to the furnace to remove some of the impurities as slag. Their removal involves a two-stage process as shown in the following equations.



- (i) A group of students were each asked to calculate the maximum mass of calcium oxide that could be produced from 8.0 g of calcium carbonate in stage 1.

The answers they calculated were as follows:

Student	Answer
Yena	4.4 g
Charlie	4.5 g
Tomasz	5.0 g

Give the name of the student that has correctly calculated the mass of calcium oxide to **one** decimal place.

You **must** show your working.

[3]

$$M_r(\text{CaCO}_3) = 100$$

$$M_r(\text{CaO}) = 56$$

Student



- (ii) In stage 2, the slag that is formed contains calcium silicate.

Calcium silicate is formed when calcium oxide (CaO) combines with silicon dioxide (SiO₂) in a 1:1 ratio, with no other product formed.

Give the chemical formula of the calcium silicate formed in stage 2.

[1]

.....

- (c) Iron reacts with oxygen to form iron(III) oxide.

Complete and balance the equation for this reaction.

[2]

