

Box Model



CSS Terminology



Selector "Targets" a CSS rule **Specificity** The more specific the selector it is, the more likely it is to win against other selectors targeting the same element

Responsive design Looking good on mobile and desktop

Media queries If statements for CSS, apply CSS to browser sizes.

DOM TREE TERMINOLOGY

```
• Parent: <div class="Main">
   - Sibling: <div>Sib</div>
    – Element: <div>
       * Child: a
       * Child: <hr />
       * Child: b
         </div>
    - Sibling: <img src="s.png"/>
      </div>
```

CSS Variables

```
/* Definition */
 --bg: #FEAAFE;
 --gap: 20px;
.MainContent { /* Use */
 background: var(--bg);
 margin: calc(var(--gap) + 5px);
```

GRID CONTAINER

```
display: grid
                       and
                             specify
columns/rows.
                                           h1:before {
grid-template-columns grid-template-rows
                                               content: "-":
      1fr 1fr 1fr
                        1fr 1fr 1fr
50px auto 50px
                      50px auto 90px
   20% 20% auto
                      100px auto 20%
.Container {
  display: grid;
  grid-template-columns: 50px auto 50px; p:nth-child(1) {
  grid-template-rows: 50px auto 90px;
                                           tr:nth-child (odd) {
```

GRID CHILD POSITIONING

Optional: Child elements can be custom positioned and sized.

```
grid-column
                                  grid-row
             2 / 3
           2/ \text{span } 2
                                    1 / 3
                                 1 / span 2
          1 / span 2
. {\tt ChildElement} \ \{
```

```
grid-column: 1 / span 2;
grid-row: 1 / span 2;
```

BEM

Block Standalone entity meaningful on its own. Use camel-case: ComponentName. Element A single part of has no stanblock $_{
m that}$ Use a dash: dalone meaning. ComponentName-descendentName. Modifier A variant of a block (or element). Use two dashes:

ComponentName--modifier.

Block-Element-Modifier Naming

convention for CSS

```
.OkBtn { background: orange; }
.OkBtn-icon { width: 12px; }
.OkBtn--disabled { color: gray; }
<div class="OkBtn--disabled">
    <img src="ok.png"</pre>
        class="OkBtn--icon" />
   Okay
</div>
```

CSS Pseudo-selectors

Pseudo-elements

```
color: blue;
Pseudo-classes
 a:hover { color: blue; }
 /* First p margin */
     margin-left: 10px;
 /* Striped table rows */
```

background: gray;

CSS Animation

```
.Link {
   color: blue;
   padding-left: 10px;
   transition: color 1s,
                padding-left 3s;
.Link:hover {
   color: green;
   padding-left: 20px;
```

Adding JavaScript to HTML

Responding to clicks

```
<div onclick="alert('Hello')">
   Click for annoying pop-up
```

Modifying DOM

```
<div id="a" onclick="
  document.querySelector('#a')
     .innerHTML += '+'
">Plus</div>
```

Running on page load

```
<script src="http://ex.amp/le.js">
</script>
                   // Print to dev
<script>
console.log("hi"); // tools console
</script>
```