

UNIVERSITY OF MILAN  
DEPARTMENT OF COMPUTER SCIENCE

---

# Report of the Real-time Graphics Programming project

---

*Author:*

Diego VALLAURI



# Contents

<b>1</b>	<b>Introduction and purpose of the project</b>	<b>2</b>
<b>2</b>	<b>Terrain</b>	<b>3</b>
2.1	Cell . . . . .	3
2.2	Terrain . . . . .	4
2.3	Blending . . . . .	5
2.3.1	First Part . . . . .	5
2.3.2	Second and third part . . . . .	5
2.3.3	Extra details . . . . .	7
2.4	Final blending . . . . .	9
2.5	Infinite terrain . . . . .	9

# 1 Introduction and purpose of the project

The aim of this project was to create infinite procedural terrain with other aesthetic elements such as water and trees using **OpenGL**. In the following chapters I will describe the different components of the project and how I have implemented them.

## 2 Terrain

The terrain is the main topic of this project so let's start to introduce the different components.

### 2.1 Cell

The main part of the terrain is a cell, a cell is basically a square whose sides have a fixed and equal size and number of vertices. As you can imagine, a cell at first is just a plane, as large as the multiplication **Dimension x Dimension** and with **Vertices x Vertices** number of vertices. Creating a plane is not a difficult task, so I didn't load a model but I generated it manually. First, I created the different vertices and stored them in a vector, then I generated the different indices to create the triangles of the mesh.





Figure 1

Obviously I didn't want flat ground, so I had to introduce some noises. For this task I relied on an existing library called **FastNoiseLite** which implemented different types of noise function. You can set various parameters, such as the type of noise, the seed and the frequency. In this specific case I choose a Perlin noise type, a random seed and a noise frequency of 0.008. By changing these parameters you can get different terrains. In addition, the maximum height of the terrain must also be specified. Then, at the time of creation, each vertex generates a noise that will be multiplied by the maximum height.



(a) Front plane.

(b) Side plane.

Figure 2

For any other information about a cell, you can check the **terrain.h** file.

## 2.2 Terrain

To create a large terrain, I put several cells together, specifically I create a square of cells. Basically I just have to choose the number of cells per row/column and put them close together. What I get now is something pretty awful, because there is no correlation between the height of the adjacent cells but it is totally random.




Figure 3: This image represents 9 cells (3 per row) with random heights.

## 2.3 Blending

The simple solution is to use a blending function between two adjacent cells. we can summarize this process in three parts.

### 2.3.1 First Part

Since I am doing this process on adjacent cells, they obviously need to reach the same height on the common side. The simplest way to accomplish this, is to use a simple lerp function that averages the heights of two common side vertices and assign it to them.




Figure 4

### 2.3.2 Second and third part

The second and third steps are actually the same, the only thing that changes is the cell that is used. In particular, it is necessary to propagate the height update obtained on the "hinge" side. We use again a lerp function but this time it's weighted based on the distance from the melt side. It works like this:

- I apply the blending from the melt side to the opposite side.
- I only change the value of the vertices farther from the "zipper" side. (Otherwise, the two cells will not be connected anymore).

- The blending is weighted, the greater the distance between the vertex and the "hinge" and the less propagation will affect the vertices. The most important thing is that the opposite side will not be affected by the blending as it is very important for connecting more than two cells.

As it is not very easy to explain the process, I have created the image below which I hope will make the process clearer for you. I also write the formula (although it's not that important) where I calculate the weight of the lerp function based on which vertex I am in at the moment (the  $i$  variable is a counter in the for loop). I also write the blend value with four vertices for each row / column in correspondence of each column. As you can see from the example, the first red vertex mixes 0.4 of its height with 0.6 of the new one, in fact it is closer to the hinge, so the blending is greater. Instead the second red vertex, since it is on the opposite side, will not be affected and its value will be the same.




Figure 5: Visual explanation of the second/third part of the blending.

So we first apply this propagation to one of the two cell and then we do it for the other one (which why the second part and the third part are the same).




Figure 6

### 2.3.3 Extra details

I need to explain two more things. The first is why I want to keep the opposite side unaffected by propagation. Mostly in normal terrain, there will be another cell attached to the opposite side where I have probably already applied the blending process. So I don't have to touch the hinge, otherwise the two cells will separate and I'll have to repeat the process for a potentially infinite number of times.




Figure 7: Before the blending of the left terrain.




Figure 8

The second thing is that I also have to interpolate the first cell with the last for each row / column. This is because my terrain will be infinite, so if I move a row / column of cells to the opposite side I need them to match the cell in that part. (Explanation of the moving terrain in the 2.5 section).




Figure 9: Final blending between two cells. (Compare it with figure 6b)

## 2.4 Final blending

I have now got a blend between two cells horizontally, but of course I need it vertically as well. The process is perfectly the same, the only thing to watch out for is not to mix the two interpolations and, before starting the second, you must wait the end of the first.




Figure 10: Example of horizontal and vertical blending between four cells. (The seed of the cells is different from the one used in the previous example).

## 2.5 Infinite terrain