
Esta página web de Splunk contiene reglas de detección creadas por la comunidad, con consultas SPL listas para utilizarse en la creación de alertas:

```
https://research.splunk.com/detections/
```



He analizado y seleccionado las reglas de detección comunitarias basadas en el evento 1 de Sysmon (creación de procesos) que considero que son las más críticas e importantes de monitorizar y alertar en el SIEM Splunk.

Este es mi listado:

1.Dump LSASS via comsvcs DLL

Descripción: Detecta el intento de usar rundll32.exe y la DLL legítima comsvcs.dll para crear una copia de la memoria del proceso LSASS, donde Windows mantiene información sensible de autenticación. Un atacante puede intentar extraer esos datos para robar credenciales y

moverse a otros equipos. La alerta no demuestra por sí sola que el robo haya tenido éxito: hay que revisar usuario, comando y equipo.

Consulta SPL:

```
| tstats `security_content_summariesonly` count min(_time) as firstTime
max(_time) as lastTime FROM datamodel=Endpoint.Processes WHERE
`process_rundll32` Processes.process=*comsvcs.dll* Processes.process IN
("*MiniDump*", "*#24*") BY Processes.action Processes.dest
Processes.original_file_name Processes.parent_process
Processes.parent_process_exec Processes.parent_process_guid
Processes.parent_process_id Processes.parent_process_name
Processes.parent_process_path Processes.process Processes.process_exec
Processes.process_guid Processes.process_hash Processes.process_id
Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name(Processes)` |
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`dump_lsass_via_comsvcs_dll_filter`
```

2.Windows Renamed Powershell Execution

Descripción: Busca PowerShell ejecutado con un nombre de archivo distinto del habitual. Cambiar el nombre de una herramienta conocida puede ayudar a un atacante a esquivar reglas que solo buscan powershell.exe. La detección compara el nombre original del ejecutable con el nombre observado. Conviene comprobar la ruta, el proceso padre, el usuario y la firma del archivo antes de decidir si es malicioso.

Consulta SPL:

```
| tstats `security_content_summariesonly` count min(_time) as firstTime
max(_time) as lastTime from datamodel=Endpoint.Processes where (
Processes.original_file_name = PowerShell.EXE Processes.process_name !=
powershell.exe ) OR ( Processes.original_file_name = pwsh.dll
Processes.process_name != pwsh.exe ) OR ( Processes.original_file_name =
powershell_ise.EXE Processes.process_name != powershell_ise.exe ) by
Processes.action Processes.dest Processes.original_file_name
Processes.parent_process Processes.parent_process_exec
Processes.parent_process_guid Processes.parent_process_id
Processes.parent_process_name Processes.parent_process_path Processes.process
Processes.process_exec Processes.process_guid Processes.process_hash
Processes.process_id Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name(Processes)` |
```

```
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`windows_renamed_powershell_execution_filter`
```

3.Windows LOLBAS Executed As Renamed File

Descripción: Busca programas conocidos por permitir acciones administrativas o ejecutar código —LOLBAS— que se han renombrado para ocultar su identidad. Compara el nombre real del ejecutable con el nombre que aparece en el sistema y consulta información de herramientas conocidas. Puede descubrir evasión de controles, aunque también requiere revisar la ruta y el contexto porque software legítimo puede cambiar de nombre.

Consulta SPL:

```
| tstats `security_content_summariesonly` latest(Processes.parent_process) as
parent_process, latest(Processes.process) as process,
latest(Processes.process_guid) as process_guid count, min(_time) AS firstTime,
max(_time) AS lastTime FROM datamodel=Endpoint.Processes where NOT
Processes.original_file_name IN("-","unknown") AND NOT Processes.process_path
IN ("*\\Program
Files*","*\\PROGRA~*","*\\Windows\\System32\\*","*\\Windows\\Syswow64\\*") by
Processes.action Processes.dest Processes.original_file_name
Processes.parent_process Processes.parent_process_exec
Processes.parent_process_guid Processes.parent_process_id
Processes.parent_process_name Processes.parent_process_path Processes.process
Processes.process_exec Processes.process_guid Processes.process_hash
Processes.process_id Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product |`drop_dm_object_name(Processes)` | where NOT
match(process_name, "(?i)".original_file_name) | lookup local=t
lolbas_file_path lolbas_file_name as original_file_name OUTPUT description as
desc | search desc!="false" | `security_content_ctime(firstTime)` |
`security_content_ctime(lastTime)` |
`windows_lolbas_executed_as_renamed_file_filter`
```

4.Services LOLBAS Execution Process Spawn

Descripción: Detecta procesos poco habituales iniciados por services.exe, el componente de Windows que gestiona los servicios del sistema, cuando el proceso hijo pertenece a una lista de herramientas que pueden ejecutar código o realizar tareas administrativas. Un servicio comprometido puede servir para lanzar comandos con permisos elevados. Hay que comprobar qué servicio originó la ejecución y si la herramienta era esperada en ese equipo.

Consulta SPL:

```
| tstats `security_content_summariesonly` count min(_time) as firstTime
max(_time) as lastTime FROM datamodel=Endpoint.Processes WHERE (
Processes.parent_process_name=services.exe ) (Processes.process_name IN
("Regsvcs.exe", "Ftp.exe", "OfflineScannerShell.exe", "Rasautou.exe",
"Schtasks.exe", "Xwizard.exe", "Dllhost.exe", "Pnputil.exe", "Atbroker.exe",
"Pcwrun.exe", "Ttdinject.exe","Mshta.exe", "Bitsadmin.exe", "Certoc.exe",
"Ieexec.exe", "Microsoft.Workflow.Compiler.exe", "Runscripthelper.exe",
"Forfiles.exe", "Msbuild.exe", "Register-cimprovider.exe", "Tttracer.exe",
"Ie4uinit.exe", "Bash.exe", "Hh.exe", "SettingSyncHost.exe", "Cmstp.exe",
"Mmc.exe", "Stordiag.exe", "Scriptrunner.exe", "Odbcconf.exe",
"Extexport.exe", "Msdt.exe", "WorkFolders.exe", "Diskshadow.exe",
"Mavinject.exe", "Regasm.exe", "Gpscript.exe", "Rundll32.exe", "Regsvr32.exe",
"Msiexec.exe", "Wuauclt.exe", "Presentationhost.exe", "Wmic.exe",
"Runonce.exe", "Syncappvpublishingserver.exe", "Verclsid.exe",
"Infdefaultinstall.exe", "Explorer.exe", "Installutil.exe", "Netsh.exe",
"Wab.exe", "Dnscmd.exe", "At.exe", "Pcalua.exe", "Msconfig.exe")) BY
Processes.action Processes.dest Processes.original_file_name
Processes.parent_process Processes.parent_process_exec
Processes.parent_process_guid Processes.parent_process_id
Processes.parent_process_name Processes.parent_process_path Processes.process
Processes.process_exec Processes.process_guid Processes.process_hash
Processes.process_id Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name(Processes)` |
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`services_lolbas_execution_process_spawn_filter`
```

5.Windows Suspicious VMWare Tools Child Process

Descripción: Busca procesos sospechosos iniciados por vmtoolsd.exe, componente de VMware Tools, como intérpretes de comandos, PowerShell o utilidades que pueden ejecutar código. Como el servicio puede operar con privilegios elevados, un proceso hijo inesperado merece atención. En máquinas virtuales también hay tareas legítimas de mantenimiento, así que se debe revisar el comando completo, la cuenta, la hora y la actividad de administración prevista.

Consulta SPL:

```
| tstats `security_content_summariesonly` count min(_time) as firstTime
max(_time) as lastTime FROM datamodel=Endpoint.Processes WHERE
Processes.parent_process_name=vmtoolsd.exe AND Processes.process_name IN
("powershell.exe","cmd.exe", "msbuild.exe", "microsoft.workflow.compiler.exe",
"searchprotocolhost.exe", "scrcons.exe", "cscript.exe",
"wscript.exe","bitsadmin.exe", "rundll32.exe", "wmic.exe", "mshta.exe",
```

```
"certutil.exe", "schtasks.exe") AND NOT (Processes.process_name="cmd.exe" AND
Processes.process IN ("*\\VMware Tools\\poweroff-vm-default.bat*","*\\VMware
Tools\\poweron-vm-default.bat*")) BY Processes.action Processes.dest
Processes.original_file_name Processes.parent_process
Processes.parent_process_exec Processes.parent_process_guid
Processes.parent_process_id Processes.parent_process_name
Processes.parent_process_path Processes.process Processes.process_exec
Processes.process_guid Processes.process_hash Processes.process_id
Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name(Processes)` |
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`windows_suspicious_vmware_tools_child_process_filter`
```

6.Windows SCCM Smsexec Spawned a Suspicious Child Process

Descripción: Detecta cuando smsexec.exe, componente relacionado con la ejecución remota de Configuration Manager/SCCM, inicia herramientas como cmd, PowerShell, scripts o utilidades de transferencia. Estas acciones pueden ser legítimas durante la administración de equipos, pero también pueden aprovecharse tras comprometer una cuenta o servidor de gestión. La investigación debe confirmar si hubo una distribución autorizada y quién inició la tarea.

Consulta SPL:

```
| tstats `security_content_summariesonly` count min(_time) as firstTime
max(_time) as lastTime from datamodel=Endpoint.Processes where
Processes.parent_process_name="smsexec.exe" Processes.process_name IN (
"bitsadmin.exe", "certutil.exe", "cmd.exe", "conhost.exe", "cscript.exe",
"curl.exe", "mshta.exe", "net.exe", "net1.exe", "powershell.exe", "pwsh.exe",
"reg.exe", "regsvr32.exe", "rundll32.exe", "wmic.exe", "wscript.exe" ) by
Processes.action Processes.dest Processes.original_file_name
Processes.parent_process Processes.parent_process_exec
Processes.parent_process_guid Processes.parent_process_id
Processes.parent_process_name Processes.parent_process_path Processes.process
Processes.process_exec Processes.process_guid Processes.process_hash
Processes.process_id Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name(Processes)` |
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`windows_sccm_smsexec_spawned_a_suspicious_child_process_filter`
```

7.Wmiprvse LOLBAS Execution Process Spawn

Descripción: Busca herramientas de ejecución o administración poco habituales lanzadas por wmiprvse.exe, el proceso que atiende solicitudes de Windows Management Instrumentation (WMI). Los atacantes pueden abusar de WMI para ejecutar comandos de forma remota o dentro del equipo. La alerta señala una relación de procesos sospechosa; hay que revisar el comando, el usuario, el origen de la solicitud y si coincide con una tarea de gestión legítima.

Consulta SPL:

```
| tstats `security_content_summariesonly` count min(_time) as firstTime
max(_time) as lastTime FROM datamodel=Endpoint.Processes WHERE (
Processes.parent_process_name=wmiprvse.exe ) (Processes.process_name IN
("Regsvcs.exe", "Ftp.exe", "OfflineScannerShell.exe", "Rasautou.exe",
"Schtasks.exe", "Xwizard.exe", "Dllhost.exe", "Pnputil.exe", "Atbroker.exe",
"Pcwrun.exe", "Ttdinject.exe","Mshta.exe", "Bitsadmin.exe", "Certoc.exe",
"Ieexec.exe", "Microsoft.Workflow.Compiler.exe", "Runscripthelper.exe",
"Forfiles.exe", "Msbuild.exe", "Register-cimprovider.exe", "Tttracer.exe",
"Ie4uinit.exe", "Bash.exe", "Hh.exe", "SettingSyncHost.exe", "Cmstp.exe",
"Mmc.exe", "Stordiag.exe", "Scriptrunner.exe", "Odbcconf.exe",
"Extexport.exe", "Msdt.exe", "WorkFolders.exe", "Diskshadow.exe",
"Mavinject.exe", "Regasm.exe", "Gpscript.exe", "Rundll32.exe", "Regsvr32.exe",
"Msiexec.exe", "Wuauclt.exe", "Presentationhost.exe", "Wmic.exe",
"Runonce.exe", "Syncappvpublishingserver.exe", "Verclsid.exe",
"Infdefaultinstall.exe", "Explorer.exe", "Installutil.exe", "Netsh.exe",
"Wab.exe", "Dnscmd.exe", "At.exe", "Pcalua.exe", "Msconfig.exe")) BY
Processes.action Processes.dest Processes.original_file_name
Processes.parent_process Processes.parent_process_exec
Processes.parent_process_guid Processes.parent_process_id
Processes.parent_process_name Processes.parent_process_path Processes.process
Processes.process_exec Processes.process_guid Processes.process_hash
Processes.process_id Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name(Processes)` |
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`wmiprvse_lolbas_execution_process_spawn_filter`
```

8.Windows Office Product Spawned Uncommon Process

Descripción: Detecta aplicaciones de Office, como Word o Excel, que inician intérpretes o utilidades como PowerShell, cmd, mshta, rundll32 o wscript. Un documento con macros o contenido malicioso puede utilizar Office como primer paso para ejecutar código. No todo

proceso hijo es malicioso, pero estas combinaciones son inusuales. Revisa el documento abierto, la línea de comandos, el usuario y los procesos posteriores.

Consulta SPL:

```
| tstats `security_content_summariesonly` count min(_time) as firstTime
max(_time) as lastTime from datamodel=Endpoint.Processes where
`process_office_products_parent` AND ( Processes.process_name IN (
bitsadmin.exe, certutil.exe, cmd.exe, cscript.exe, mshta.exe, powershell.exe,
pwsh.exe, regsvr32.exe, rundll32.exe, wmic.exe, wscript.exe ) OR
Processes.original_file_name IN ( bitsadmin.exe, CertUtil.exe, Cmd.Exe,
cscript.exe, MSHTA.EXE, PowerShell.EXE, pwsh.dll, REGSVR32.EXE, RUNDLL32.EXE,
wmic.exe, wscript.exe ) ) by Processes.action Processes.dest
Processes.original_file_name Processes.parent_process
Processes.parent_process_exec Processes.parent_process_guid
Processes.parent_process_id Processes.parent_process_name
Processes.parent_process_path Processes.process Processes.process_exec
Processes.process_guid Processes.process_hash Processes.process_id
Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name(Processes)` |
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`windows_office_product_spawned_uncommon_process_filter`
```

9.Windows Suspicious Child Process Spawned From WebServer

Descripción: Busca intérpretes y utilidades de sistema iniciados por procesos de servidores web, por ejemplo IIS, PHP o Tomcat. Si una aplicación web es vulnerable o una webshell ha sido instalada, un atacante puede ejecutar comandos desde el proceso del servidor. La regla busca señales de esa actividad, como whoami, cmd o PowerShell. Confirma la petición web relacionada y revisa el servidor y la cuenta del servicio.

Consulta SPL:

```
| tstats `security_content_summariesonly` count max(_time) as lastTime,
min(_time) as firstTime FROM datamodel=Endpoint.Processes WHERE (
Processes.process_name IN
("arp.exe","at.exe","bash.exe","bitsadmin.exe","certutil.exe","cmd.exe","cscri
pt.exe",
"dsget.exe","dsquery.exe","find.exe","findstr.exe","fsutil.exe","hostname.exe"
,"ipconfig.exe","ksh.exe","nbstat.exe",
"net.exe","net1.exe","netdom.exe","netsh.exe","netstat.exe","nltest.exe","nslo
okup.exe","ntdsutil.exe","pathping.exe",
```

```
"ping.exe","powershell.exe","pwsh.exe","qprocess.exe","query.exe","qwinsta.exe
","reg.exe","rundll32.exe","sc.exe",
"scrcons.exe","schtasks.exe","sh.exe","systeminfo.exe","tasklist.exe","tracert
.exe","ver.exe","vssadmin.exe",
"wevtutil.exe","whoami.exe","wmic.exe","wscript.exe","wusa.exe","zsh.exe") AND
Processes.parent_process_name IN ("w3wp.exe", "http*.exe", "nginx*.exe",
"php*.exe", "php-cgi*.exe","tomcat*.exe") ) BY Processes.action Processes.dest
Processes.original_file_name Processes.parent_process
Processes.parent_process_exec Processes.parent_process_guid
Processes.parent_process_id Processes.parent_process_name
Processes.parent_process_path Processes.process Processes.process_exec
Processes.process_guid Processes.process_hash Processes.process_id
Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name("Processes")` |
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`windows_suspicious_child_process_spawned_from_webserver_filter`
```

10.Mmc LOLBAS Execution Process Spawn

Descripción: Detecta cuando mmc.exe, la consola de administración de Windows, inicia herramientas que también pueden utilizarse para ejecutar código o realizar tareas del sistema. Aunque los complementos administrativos pueden generar actividad legítima, la aparición de ejecutables como mshta, rundll32 o regsvr32 desde MMC puede indicar abuso de una consola o de un complemento. Comprueba qué consola se abrió y qué acción administrativa estaba en curso.

Consulta SPL:

```
| tstats `security_content_summariesonly` count min(_time) as firstTime
max(_time) as lastTime from datamodel=Endpoint.Processes where
(Processes.parent_process_name=mmc.exe) (Processes.process_name IN
("Regsvcs.exe", "Ftp.exe", "OfflineScannerShell.exe", "Rasautou.exe",
"Schtasks.exe", "Xwizard.exe", "Dllhost.exe", "Pnputil.exe", "Atbroker.exe",
"Pcwrun.exe", "Ttdinject.exe","Mshta.exe", "Bitsadmin.exe", "Certoc.exe",
"Ieexec.exe", "Microsoft.Workflow.Compiler.exe", "Runscripthelper.exe",
"Forfiles.exe", "Msbuild.exe", "Register-cimprovider.exe", "Tttracer.exe",
"Ie4uinit.exe", "Bash.exe", "Hh.exe", "SettingSyncHost.exe", "Cmstp.exe",
"Mmc.exe", "Stordiag.exe", "Scriptrunner.exe", "Odbcconf.exe",
"Extexport.exe", "Msdt.exe", "WorkFolders.exe", "Diskshadow.exe",
"Mavinject.exe", "Regasm.exe", "Gpscript.exe", "Rundll32.exe", "Regsvr32.exe",
"Msiexec.exe", "Wuauclt.exe", "Presentationhost.exe", "Wmic.exe",
"Runonce.exe", "Syncappvpublishingserver.exe", "Verclsid.exe",
"Infdefaultinstall.exe", "Explorer.exe", "Installutil.exe", "Netsh.exe",
"Wab.exe", "Dnscmd.exe", "At.exe", "Pcalua.exe", "Msconfig.exe")) by
```

```
Processes.action Processes.dest Processes.original_file_name
Processes.parent_process Processes.parent_process_exec
Processes.parent_process_guid Processes.parent_process_id
Processes.parent_process_name Processes.parent_process_path Processes.process
Processes.process_exec Processes.process_guid Processes.process_hash
Processes.process_id Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name(Processes)` |
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`mmc_lolbas_execution_process_spawn_filter`
```

11.Windows Suspicious React or Next.js Child Process

Descripción: Busca intérpretes de comandos y utilidades de sistema iniciados por procesos Node.js asociados con servidores de desarrollo React o Next.js. Un servidor de aplicación no debería ejecutar normalmente herramientas como PowerShell, curl o certutil salvo que una tarea concreta lo requiera. La detección puede señalar abuso de una vulnerabilidad o ejecución de comandos desde la aplicación. Revisa la petición, el proceso padre y si el servidor estaba expuesto.

Consulta SPL:

```
| tstats `security_content_summariesonly` count min(_time) as firstTime
max(_time) as lastTime from datamodel=Endpoint.Processes where
Processes.parent_process_name = "node.exe" Processes.parent_process IN ( "*--
experimental-https*", "*--experimental-next-config-strip-types*",
"*\\node_modules\\next*", "*next dev*", "*next start*", "*next\" start*",
"*node_modules\\.bin\\\\..\\next*", "*react-scripts start*", "*start-
server.js*", ) AND ( Processes.process_name IN ( "bash.exe", "bitsadmin.exe",
"calc.exe", "CalculatorApp.exe", "certutil.exe", "cscript.exe", "curl.exe",
"ftp.exe", "ipconfig.exe", "mshta.exe", "netstat.exe", "OpenConsole.exe",
"powershell.exe", "pwsh.exe", "regsvr32.exe", "rundll32.exe", "sh.exe",
"tftp.exe", "wget.exe", "win32calc.exe", "wmic.exe", "wscript.exe", "wsl.exe",
"wt.exe" ) OR ( Processes.process_name = "cmd.exe" AND NOT Processes.process =
"*/d /s /c *" ) OR ( Processes.process_name = "cmd.exe" Processes.process =
"*/d /s /c *" AND NOT ( Processes.process = "*git config --local --get
remote.origin.url*" OR ( Processes.process = "*netstat -ano | findstr /C:*"
Processes.process = "* | findstr LISTENING*" ) OR ( Processes.parent_process =
"*--experimental-https*" Processes.process = "*\\mkcert\\*" Processes.process
IN ("* -CAROOT*", "* -install *") ) ) ) ) by Processes.action Processes.dest
Processes.original_file_name Processes.parent_process
Processes.parent_process_exec Processes.parent_process_guid
Processes.parent_process_id Processes.parent_process_name
Processes.parent_process_path Processes.process Processes.process_exec
Processes.process_guid Processes.process_hash Processes.process_id
```

```
Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name(Processes)` |
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`windows_suspicious_react_or_next_js_child_process_filter`
```

12.Wsmprovhost LOLBAS Execution Process Spawn

Descripción: Detecta procesos tipo LOLBAS iniciados por wsmprovhost.exe, componente que ejecuta comandos recibidos mediante Windows Remote Management (WinRM). Puede ser una administración remota autorizada, pero también una señal de que alguien usa credenciales comprometidas para ejecutar comandos en otro equipo. Comprueba el usuario, el origen de la sesión remota, la hora y las herramientas ejecutadas para distinguir operaciones legítimas de actividad de intrusión.

Consulta SPL:

```
| tstats `security_content_summariesonly` count min(_time) as firstTime
max(_time) as lastTime FROM datamodel=Endpoint.Processes WHERE
Processes.parent_process_name=wsmprovhost.exe Processes.process_name IN
("Regsvcs.exe", "Ftp.exe", "OfflineScannerShell.exe", "Rasautou.exe",
"Schtasks.exe", "Xwizard.exe", "Dllhost.exe", "Pnputil.exe", "Atbroker.exe",
"Pcwrun.exe", "Ttdinject.exe","Mshta.exe", "Bitsadmin.exe", "Certoc.exe",
"Ieexec.exe", "Microsoft.Workflow.Compiler.exe", "Runscripthelper.exe",
"Forfiles.exe", "Msbuild.exe", "Register-cimprovider.exe", "Tttracer.exe",
"Ie4uinit.exe", "Bash.exe", "Hh.exe", "SettingSyncHost.exe", "Cmstp.exe",
"Mmc.exe", "Stordiag.exe", "Scriptrunner.exe", "Odbcconf.exe",
"Extexport.exe", "Msdt.exe", "WorkFolders.exe", "Diskshadow.exe",
"Mavinject.exe", "Regasm.exe", "Gpscript.exe", "Rundll32.exe", "Regsvr32.exe",
"Msiexec.exe", "Wuauclt.exe", "Presentationhost.exe", "Wmic.exe",
"Runonce.exe", "Syncappvpublishingserver.exe", "Verclsid.exe",
"Infdefaultinstall.exe", "Explorer.exe", "Installutil.exe", "Netsh.exe",
"Wab.exe", "Dnscmd.exe", "At.exe", "Pcalua.exe", "Msconfig.exe") BY
Processes.action Processes.dest Processes.original_file_name
Processes.parent_process Processes.parent_process_exec
Processes.parent_process_guid Processes.parent_process_id
Processes.parent_process_name Processes.parent_process_path Processes.process
Processes.process_exec Processes.process_guid Processes.process_hash
Processes.process_id Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name(Processes)` |
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`wsmprovhost_lolbas_execution_process_spawn_filter`
```

13.Wscript Or Cscript Suspicious Child Process

Descripción: Busca cuando Windows Script Host —wscript.exe o cscript.exe— inicia programas que pueden ejecutar comandos o facilitar una intrusión, como PowerShell, cmd, rundll32, mshta o certutil. Los atacantes pueden lanzar scripts VBS o JScript desde archivos adjuntos, descargas o tareas programadas. La alerta no confirma malware por sí sola: revisa el archivo de script, su ruta, el proceso padre y el comando completo.

Consulta SPL:

```
| tstats `security_content_summariesonly` count min(_time) as firstTime
max(_time) as lastTime FROM datamodel=Endpoint.Processes WHERE
Processes.parent_process_name IN ("cscript.exe", "wscript.exe")
Processes.process_name IN ("regsvr32.exe",
"rundll32.exe","winhlp32.exe","certutil.exe","msbuild.exe","cmd.exe","powershe
ll*","pwsh.exe","wmic.exe","mshta.exe") BY Processes.action Processes.dest
Processes.original_file_name Processes.parent_process
Processes.parent_process_exec Processes.parent_process_guid
Processes.parent_process_id Processes.parent_process_name
Processes.parent_process_path Processes.process Processes.process_exec
Processes.process_guid Processes.process_hash Processes.process_id
Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name(Processes)` |
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`wscript_or_cscript_suspicious_child_process_filter`
```

14.Svchost LOLBAS Execution Process Spawn

Descripción: Detecta cuando svchost.exe, proceso que aloja servicios de Windows, inicia herramientas de administración o ejecución que no suelen aparecer como procesos hijos de ese servicio. Los atacantes pueden abusar de servicios o de tareas del sistema para lanzar binarios LOLBAS y ocultar su actividad. La regla excluye algunas combinaciones normales, pero aun así conviene identificar el servicio alojado, el comando y la razón de la ejecución.

Consulta SPL:

```
| tstats `security_content_summariesonly` count min(_time) as firstTime
max(_time) as lastTime FROM datamodel=Endpoint.Processes WHERE
Processes.parent_process = "*" Processes.parent_process_name = "svchost.exe"
Processes.process_name IN ( "At.exe", "Atbroker.exe", "Bash.exe",
"Bitsadmin.exe", "Certoc.exe", "Cmstp.exe", "Diskshadow.exe", "Dnscmd.exe",
"Extexport.exe", "Forfiles.exe", "Ftp.exe", "Gpscript.exe", "Hh.exe",
"Ie4uinit.exe", "Ieexec.exe", "Infdefaultinstall.exe", "Installutil.exe",
```

```
"Mavinject.exe", "Microsoft.Workflow.Compiler.exe", "Msbuild.exe",
"Msconfig.exe", "Msdt.exe", "Msiexec.exe", "Netsh.exe", "Odbcconf.exe",
"OfflineScannerShell.exe", "Pcalua.exe", "Pcwrun.exe", "Pnputil.exe",
"PresentationHost.exe", "Rasautou.exe", "Regasm.exe", "Register-
cimprovider.exe", "Regsvcs.exe", "Regsvr32.exe", "Runonce.exe",
"Runscripthelper.exe", "Schtasks.exe", "Scriptrunner.exe",
"SettingSyncHost.exe", "Stordiag.exe", "Syncappvpublishingserver.exe",
"Ttdinject.exe", "Mshta.exe", "Tttracer.exe", "Verclsid.exe", "Wab.exe",
"Wmic.exe", "WorkFolders.exe", "Wuauclt.exe", "Xwizard.exe" ) NOT (
Processes.parent_process IN ("*-k GPSvcGroup*", "*-k netsvcs", "*-k netsvcs -
p","*-k netsvcs -p -s gpsvc") Processes.process_name = "Gpscript.exe" ) NOT (
Processes.parent_process IN ("*-k netsvcs", "*-k netsvcs -p", "*-k netsvcs -p
-s wuauserv", "-k netsvcs -p -s Schedule") Processes.process_name IN
("Wuauclt.exe", "Schtasks.exe") ) NOT ( Processes.parent_process = "*-k
DcomLaunch*" Processes.process_name IN ("PresentationHost.exe",
"SettingSyncHost.exe") ) BY Processes.action Processes.dest
Processes.original_file_name Processes.parent_process
Processes.parent_process_exec Processes.parent_process_guid
Processes.parent_process_id Processes.parent_process_name
Processes.parent_process_path Processes.process Processes.process_exec
Processes.process_guid Processes.process_hash Processes.process_id
Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name(Processes)` |
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`svchost_lolbas_execution_process_spawn_filter`
```

15.Windows SQLCMD Execution

Descripción: Examina la ejecución de sqlcmd.exe, una utilidad para conectarse a SQL Server y ejecutar consultas. La detección puntúa opciones y comandos que podrían indicar consultas sensibles, uso sospechoso de cuentas administrativas, exportación de resultados, descargas o ejecución de comandos desde la base de datos. El uso de sqlcmd es normal en administración; investiga especialmente las combinaciones de parámetros, las consultas, los archivos de salida y el usuario.

Consulta SPL:

```
| tstats `security_content_summariesonly` count min(_time) as firstTime
max(_time) as lastTime from datamodel=Endpoint.Processes where
(Processes.process_name=sqlcmd.exe OR Processes.original_file_name=sqlcmd.exe)
by Processes.dest Processes.user Processes.parent_process_name
Processes.process_name Processes.process Processes.process_id
Processes.parent_process_id | `drop_dm_object_name(Processes)` | eval
process_lower=lower(process) | eval is_help_check=case( match(process, "(?i)-
```

```
[?]"), 1, match(process_lower, "(?i)--help"), 1, match(process_lower, "(?i)--
version"), 1, true(), 0 ), has_parameters=if(match(process, "-[A-Za-z]"), 1,
0), has_query=case( match(process, "-[Qq]\\s+"), 1, match(process_lower, "--
query\\s+"), 1, match(process_lower, "--initial-query\\s+"), 1, true(), 0 ),
has_output=case( match(process, "-[oO]\\s+"), 1, match(process_lower, "--
output-file\\s+"), 1, true(), 0 ), has_input=case( match(process, "-
[iI]\\s+"), 1, match(process_lower, "--input-file\\s+"), 1, true(), 0 ),
has_url_input=case( match(process, "-[iI]\\s+https?://"), 1,
match(process_lower, "--input-file\\s+https?://"), 1, match(process, "-
[iI]\\s+ftp://"), 1, match(process_lower, "--input-file\\s+ftp://"), 1,
true(), 0 ), has_admin_conn=case( match(process, "-A"), 1,
match(process_lower, "--dedicated-admin-connection"), 1, true(), 0 ),
has_suspicious_auth=case( match(process, "-U\\s+sa\\b"), 1,
match(process_lower, "--user-name\\s+sa\\b"), 1, match(process, "-
U\\s+admin\\b"), 1, match(process_lower, "--user-name\\s+admin\\b"), 1,
match(process, "-E\\b"), 1, match(process_lower, "--use-trusted-connection"),
1, true(), 0 ), has_local_server=case( match(process, "-
S\\s+127\\.0\\.0\\.1"), 1, match(process_lower, "--
server\\s+127\\.0\\.0\\.1"), 1, match(process, "-S\\s+localhost"), 1,
match(process_lower, "--server\\s+localhost"), 1, true(), 0 ),
has_suspicious_output=case( match(process_lower, "-o\\s+.*\\.(txt|csv|dat)"),
1, match(process_lower, "--output-file\\s+.*\\.(txt|csv|dat)"), 1, true(), 0
), has_cert_bypass=case( match(process, "-C"), 1, match(process_lower, "--
trust-server-certificate"), 1, true(), 0 ), has_suspicious_query=case(
match(process_lower, "
(xp_cmdshell|sp_oacreate|sp_execute_external|openrowset|bulk\\s+insert)"), 1,
match(process_lower, "
(master\\.\\.\\.sysdatabases|msdb\\.\\.\\.backuphistory|sysadmin|securityadmin
)"), 1, match(process_lower, "
(select.*from.*sys\\.|select.*password|dump\\s+database)"), 1,
match(process_lower, "
(sp_addextendedproc|sp_makewebtask|sp_addsrvrolemember)"), 1,
match(process_lower, "
(sp_configure.*show\\s+advanced|reconfigure|enable_xp_cmdshell)"), 1,
match(process_lower, "(exec.*master\\.dbo\\.|exec.*msdb\\.dbo\\.)"), 1,
match(process_lower, "
(sp_password|sp_control_dbmasterkey_password|sp_dropextendedproc)"), 1,
match(process_lower, "(powershell|cmd\\.exe|rundll32|regsvr32|certutil)"), 1,
true(), 0 ), has_suspicious_path=case( match(process_lower, "
(\\\\temp\\\\|\\\\windows\\\\|\\\\public\\\\|\\\\users\\\\public\\\\|\\\\progr
amdata\\\\)"), 1, match(process_lower, "(\\\\desktop\\\\.*\\.
(zip|rar|7z|tar|gz))"), 1, match(process_lower, "(\\\\downloads\\\\.*\\.
(dat|bin|tmp))"), 1, match(process_lower, "
(\\\\appdata\\\\local\\\\temp\\\\|\\\\windows\\\\tasks\\\\)"), 1,
match(process_lower, "(\\\\recycler\\\\|\\\\system32\\\\|\\\\system volume
information\\\\)"), 1, match(process_lower, "
```

```
(\\.vbs|\\.ps1|\\.bat|\\.cmd|\\.exe)$"), 1, true(), 0 ),
has_suspicious_combo=case( match(process, "-E") AND match(process_lower, "(?
i)xp_cmdshell"), 1, match(process, "-Q") AND match(process_lower, "(?
i)exec\\s+master"), 1, has_local_server=1 AND has_suspicious_query=1, 1,
true(), 0 ), has_obfuscation=case( match(process_lower, "(char\\(|convert\\
(|cast\\(|declare\\s+@)"), 1, match(process_lower, "(exec\\s+\\
(|exec\\s+@|;\\s*exec)"), 1, match(process, "\\^|\\%|\\+\\+|\\-\\-"), 1,
len(process) > 500, 1, true(), 0 ), has_data_exfil=case( match(process_lower,
"(for\\s+xml|for\\s+json)"), 1, match(process_lower, "
(bulk\\s+insert.*from)"), 1, match(process_lower, "(bcp.*queryout|bcp.*out)"),
1, match(process_lower, "(select.*into.*from|select.*into.*outfile)"), 1,
true(), 0 ) | eval risk_score=0 | eval risk_score=case( is_help_check=1, 0,
has_parameters=0, 0, has_suspicious_combo=1, risk_score + 90,
has_suspicious_query=1, risk_score + 60, has_suspicious_path=1, risk_score +
40, has_url_input=1 AND has_output=1, risk_score + 80, has_query=1 AND
has_output=1, risk_score + 30, has_query=1 AND has_suspicious_output=1,
risk_score + 40, has_admin_conn=1, risk_score + 50, has_suspicious_auth=1,
risk_score + 40, has_local_server=1 AND has_query=1, risk_score + 30,
has_cert_bypass=1, risk_score + 20, has_obfuscation=1, risk_score + 70,
has_data_exfil=1, risk_score + 60, true(), risk_score ) | eval
risk_factors=mvappend( if((is_help_check=0 AND has_parameters=0), null(),
if(has_suspicious_combo=1, "High-risk command combination detected", null())),
if((is_help_check=0 AND has_parameters=0), null(), if(has_suspicious_query=1,
"Suspicious SQL query pattern", null())), if(has_suspicious_path=1,
"Suspicious output path", null()), if(has_url_input=1 AND has_output=1, "File
download attempt", null()), if(has_query=1 AND has_output=1, "Query output to
file", null()), if(has_admin_conn=1, "Admin connection", null()),
if(has_suspicious_auth=1, "Suspicious authentication", null()),
if(has_local_server=1, "Local server connection", null()),
if(has_cert_bypass=1, "Certificate validation bypass", null()),
if(has_obfuscation=1, "Command obfuscation detected", null()),
if(has_data_exfil=1, "Potential data exfiltration", null()) ) | eval
risk_message="SQLCMD execution with risk factors: ".mvjoin(risk_factors, ", ")
| where is_help_check=0 AND (risk_score >= 30 OR (has_parameters=1 AND
has_suspicious_query=1)) | `security_content_ctime(firstTime)` |
`security_content_ctime(lastTime)` | `windows_sqlcmd_execution_filter`
```

16.Child Processes of Spoolsv exe

Descripción: Registra procesos iniciados por spoolsv.exe, el servicio de cola de impresión de Windows. Ese servicio normalmente gestiona trabajos de impresión, por lo que un proceso hijo inesperado puede indicar abuso de una vulnerabilidad del sistema de impresión o ejecución de código a través de un controlador comprometido. La regla es amplia y puede generar falsos positivos; verifica el proceso hijo, su ruta y los controladores o trabajos de impresión activos.

Consulta SPL:

```
| tstats `security_content_summariesonly` count values(Processes.process_name)
as process_name values(Processes.process) as process min(_time) as firstTime
max(_time) as lastTime FROM datamodel=Endpoint.Processes WHERE
Processes.parent_process_name=spoolsv.exe AND
Processes.process_name!=regsvr32.exe BY Processes.action Processes.dest
Processes.original_file_name Processes.parent_process
Processes.parent_process_exec Processes.parent_process_guid
Processes.parent_process_id Processes.parent_process_name
Processes.parent_process_path Processes.process Processes.process_exec
Processes.process_guid Processes.process_hash Processes.process_id
Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name(Processes)` |
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`child_processes_of_spoolsv_exe_filter`
```

17.WinRM Spawning a Process

Descripción: Detecta procesos como cmd, PowerShell, schtasks o certutil iniciados por wsmprovhost.exe durante una sesión WinRM. WinRM permite administración remota legítima, pero también puede ser utilizado para ejecutar comandos después de robar credenciales. La alerta indica que se ha iniciado una herramienta sensible a través de ese mecanismo. Revisa la cuenta, el equipo de origen, el destino y si la sesión remota estaba autorizada.

Consulta SPL:

```
| tstats `security_content_summariesonly` count min(_time) as firstTime
max(_time) as lastTime FROM datamodel=Endpoint.Processes WHERE
Processes.parent_process_name=wsmprovhost.exe Processes.process_name IN
("cmd.exe","sh.exe","bash.exe","powershell.exe","pwsh.exe","schtasks.exe","cer
tutil.exe","whoami.exe","bitsadmin.exe","scp.exe") BY Processes.action
Processes.dest Processes.original_file_name Processes.parent_process
Processes.parent_process_exec Processes.parent_process_guid
Processes.parent_process_id Processes.parent_process_name
Processes.parent_process_path Processes.process Processes.process_exec
Processes.process_guid Processes.process_hash Processes.process_id
Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name(Processes)` |
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`winrm_spawning_a_process_filter`
```

18.Wermgr Process Spawned CMD Or Powershell Process

Descripción: Busca cmd.exe o PowerShell iniciados por wermgr.exe, el componente de Windows relacionado con informes de errores. Ese proceso no suele necesitar lanzar una consola de comandos, así que la relación puede indicar que un programa está intentando disfrazar una ejecución maliciosa como actividad de informe de errores. Comprueba el proceso padre real, la ruta, la línea de comandos y si hubo un fallo de aplicación legítimo.

Consulta SPL:

```
| tstats `security_content_summariesonly` values(Processes.process) as cmdline
min(_time) as firstTime max(_time) as lastTime FROM
datamodel=Endpoint.Processes WHERE Processes.parent_process_name =
"wermgr.exe" `process_cmd` OR `process_powershell` BY Processes.action
Processes.dest Processes.original_file_name Processes.parent_process
Processes.parent_process_exec Processes.parent_process_guid
Processes.parent_process_id Processes.parent_process_name
Processes.parent_process_path Processes.process Processes.process_exec
Processes.process_guid Processes.process_hash Processes.process_id
Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name(Processes)` |
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`wermgr_process_spawned_cmd_or_powershell_process_filter`
```

19.Windows Suspicious Child Process of TieringEngineService.exe

Descripción: La regla asociada detecta procesos hijos sospechosos de TieringEngineService.exe; no demuestra por sí sola la explotación del exploit RedSun. El objetivo es señalar una relación de procesos inusual alrededor de un componente del sistema que podría aprovecharse para ejecutar código con privilegios altos. Si aparece, valida el título y la lógica de la regla original, revisa los procesos y no atribuyas RedSun sin evidencia adicional.

Consulta SPL:

```
| tstats `security_content_summariesonly` count min(_time) as firstTime
max(_time) as lastTime FROM datamodel=Endpoint.Processes WHERE
Processes.parent_process_name="TieringEngineService.exe" ( Processes.process
IN ( "*bitsadmin.exe*", "*cmd.exe*", "*conhost.exe*", "*cscript.exe*",
"*curl.exe*", "*powershell.exe*", "*pwsh.exe*", "*rundll32.exe*", "*wmic.exe*"
) OR Processes.process_name IN ( "bitsadmin.exe", "cmd.exe", "conhost.exe",
```

```
"cscript.exe", "curl.exe", "powershell.exe", "pwsh.exe", "rundll32.exe",
"wmic.exe" ) ) Processes.user IN ( "*AUTHORITY*", "*System*" ) BY
Processes.dest Processes.user Processes.original_file_name
Processes.parent_process Processes.process_name Processes.process
Processes.process_id Processes.parent_process_id Processes.parent_process_name
action parent_process_exec parent_process_guid parent_process_path
process_exec process_guid process_hash process_integrity_level process_path
user_id vendor_product | `drop_dm_object_name(Processes)` |
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`windows_suspicious_child_process_of_tieringengineservice_exe_filter`
```

20.WinRAR Spawning Shell Application

Descripción: Detecta cuando WinRAR inicia una consola o utilidades como cmd, PowerShell, certutil, mshta o bitsadmin. Al extraer un archivo, abrir un archivo adjunto o ejecutar un programa empaquetado, un atacante puede encadenar la herramienta de compresión con comandos maliciosos. También puede haber usos legítimos. Revisa qué archivo se abrió o extrajo, la ruta de origen, el proceso hijo y la línea de comandos completa.

Consulta SPL:

```
| tstats `security_content_summariesonly` count min(_time) as firstTime
max(_time) as lastTime FROM datamodel=Endpoint.Processes WHERE
Processes.parent_process_name=winrar.exe `windows_shells` OR
Processes.process_name IN ("certutil.exe","mshta.exe","bitsadmin.exe") BY
Processes.action Processes.dest Processes.original_file_name
Processes.parent_process Processes.parent_process_exec
Processes.parent_process_guid Processes.parent_process_id
Processes.parent_process_name Processes.parent_process_path Processes.process
Processes.process_exec Processes.process_guid Processes.process_hash
Processes.process_id Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name(Processes)` |
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`winrar_spawning_shell_application_filter`
```

21.Windows Alternate DataStream - Executable Content

Descripción: Detecta la ejecución de contenido ejecutable desde un Alternate Data Stream (ADS) de NTFS, una zona de datos adicional asociada a un archivo. Este mecanismo puede ocultar contenido porque no siempre se ve como un archivo separado en el Explorador. Un atacante puede utilizarlo para guardar o ejecutar una carga útil con menos visibilidad. Revisa la ruta completa, el nombre del flujo y qué proceso intentó ejecutarlo.

Consulta SPL:

```
| tstats count min(_time) as firstTime max(_time) as lastTime
values(Processes.process_current_directory) as directory from
datamodel=Endpoint.Processes where Processes.parent_process_name != "unknown"
Processes.process_name IN ( "appvlp.exe", "bitsadmin.exe", "control.exe",
"cscript.exe", "forfiles.exe", "ftp.exe", "mavinject.exe", "mshta.exe",
"powershell_ise.exe", "powershell.exe", "pwsh.exe", "regini.exe",
"regsvr32.exe", "rundll32.exe", "sc.exe", "wmic.exe", "wscript.exe" ) by
Processes.action Processes.dest Processes.original_file_name
Processes.parent_process Processes.parent_process_exec
Processes.parent_process_guid Processes.parent_process_id
Processes.parent_process_name Processes.parent_process_path Processes.process
Processes.process_exec Processes.process_guid Processes.process_hash
Processes.process_id Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name(Processes)` | regex process="
(\b)\w+(\.\w+)?:\w+(\.\w{2,4})(?!\.)(\b|\s|&)" |
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`windows_alternate_datastream___process_execution_filter`
```

22.Windows Rundll32 with Non-Standard File Extension

Descripción: Busca rundll32.exe cargando o ejecutando contenido cuya extensión o ubicación no coincide con las bibliotecas habituales de Windows. Rundll32 es una herramienta legítima para llamar funciones exportadas de DLL, pero puede abusarse para ejecutar contenido desde rutas temporales o archivos con extensiones poco comunes. La regla intenta encontrar esos patrones anómalos. Comprueba el comando completo, el archivo apuntado, su firma y la ubicación.

Consulta SPL:

```
| tstats `security_content_summariesonly` count min(_time) as firstTime
max(_time) as lastTime FROM datamodel=Endpoint.Processes WHERE
`process_rundll32` ( Processes.parent_process_path IN ( "*:\\PerfLogs\\*",
"*:\\ProgramData\\*", "*:\\Recycle.bin\\*",
"*:\\Users\\Administrator\\Music\\*", "*:\\Users\\Public\\*",
"*:\\Windows\\Cursors\\*", "*:\\Windows\\debug\\*", "*:\\Windows\\fonts\\*",
"*:\\Windows\\INF\\*", "*:\\Windows\\Media\\*", "*:\\Windows\\Prefetch\\*",
"*:\\Windows\\repair\\*", "*:\\Windows\\Tasks\\*", "*\\Temp\\*" ) OR
Processes.parent_process_name IN ( "*cmd.exe*", "*cscript.exe*",
"*mshta.exe*", "*powershell.exe*", "*pwsh.exe*", "*regsvr32.exe*",
"*wscript.exe*" ) ) NOT Processes.process IN ( "*.cpl*", "*.dll*", "*.drv*",
"*.inf*", "*.mui*", "*.ocx*" ) BY Processes.action Processes.dest
```

```
Processes.original_file_name Processes.parent_process_exec
Processes.parent_process_guid Processes.parent_process_id
Processes.parent_process_path Processes.process_exec Processes.process_guid
Processes.process_hash Processes.process_id Processes.process_integrity_level
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product Processes.parent_process_name
Processes.parent_process Processes.process_name Processes.process |
`drop_dm_object_name(Processes)` | rex field=process "^(?<cmd_base_process>
[^\s]+)\s+\"?(?<cmd_base_first_param>[^,^\"^\s]+).*?,(?<cmd_args>.*)$" | rex
field=cmd_base_first_param "^(?<root>[^\\\\]+)\\\\(?<subdirs>[^\\\\]+)" | eval
folder_count = mvcount(split(cmd_base_first_param, "\\")) | where (
folder_count = 3 AND NOT lower(subdirs) IN ( "windows", "program files",
"program files (x86)" ) ) OR like(cmd_base_first_param, "%:\\ProgramData\\%")
OR like(cmd_base_first_param, "%:\\Users\\Public\\%") OR
like(cmd_base_first_param, "%\\AppData\\Local\\Temp\\%") OR
like(cmd_base_first_param, "%\\AppData\\Roaming\\%") |
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`windows_rundll32_with_non_standard_file_extension_filter`
```

23.Web Servers Executing Suspicious Processes

Descripción: Busca comandos sospechosos ejecutados en equipos identificados como servidores web, por ejemplo utilidades para descubrir usuarios, redes, servicios o descargar archivos. Si un servidor web ha sido comprometido, el atacante puede ejecutar comandos para reconocer el sistema y preparar la siguiente fase. La detección depende de que el equipo esté correctamente categorizado como servidor web. Correlaciona el proceso con registros web, cuentas de servicio y conexiones de red.

Consulta SPL:

```
| tstats `security_content_summariesonly` count min(_time) as firstTime
max(_time) as lastTime FROM datamodel=Endpoint.Processes WHERE
Processes.dest_category="web_server" AND (Processes.process="*whoami*" OR
Processes.process="*ping*" OR Processes.process="*iptables*" OR
Processes.process="*wget*" OR Processes.process="*service*" OR
Processes.process="*curl*") BY Processes.action Processes.dest
Processes.original_file_name Processes.parent_process
Processes.parent_process_exec Processes.parent_process_guid
Processes.parent_process_id Processes.parent_process_name
Processes.parent_process_path Processes.process Processes.process_exec
Processes.process_guid Processes.process_hash Processes.process_id
Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name(Processes)` |
```

```
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`web_servers_executing_suspicious_processes_filter`
```

24.Suspicious Rundll32 StartW

Descripción: Detecta el uso de rundll32.exe con el nombre de función StartW, patrón asociado a determinadas técnicas de ejecución de herramientas como Cobalt Strike. Rundll32 permite invocar funciones de bibliotecas, y ciertos usos poco habituales pueden indicar que se está intentando ejecutar código de forma indirecta. Es un indicador concreto, no una confirmación automática de Cobalt Strike. Revisa argumentos, DLL relacionada, firma y conexiones del proceso.

Consulta SPL:

```
| tstats `security_content_summariesonly` count min(_time) as firstTime
max(_time) as lastTime FROM datamodel=Endpoint.Processes WHERE
`process_rundll32` Processes.process IN ("*startw", "*startw *") BY
Processes.action Processes.dest Processes.original_file_name
Processes.parent_process Processes.parent_process_exec
Processes.parent_process_guid Processes.parent_process_id
Processes.parent_process_name Processes.parent_process_path Processes.process
Processes.process_exec Processes.process_guid Processes.process_hash
Processes.process_id Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name(Processes)` |
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`suspicious_rundll32_startw_filter`
```

25.Windows Masquerading Explorer As Child Process

Descripción: Busca explorer.exe iniciado por procesos como cmd, PowerShell, pwsh o regsvr32, en vez de la secuencia habitual de inicio del escritorio. Esta relación puede formar parte de una técnica para disfrazar procesos o ejecutar contenido mediante Explorer. Puede haber excepciones legítimas según el software instalado. Examina el proceso padre, la ruta de explorer.exe, el comando que lo lanzó y cualquier proceso hijo posterior.

Consulta SPL:

```
| tstats `security_content_summariesonly` count min(_time) as firstTime
max(_time) as lastTime from datamodel=Endpoint.Processes where
Processes.parent_process_name IN ( "cmd.exe", "powershell.exe", "pwsh.exe",
"regsvr32.exe" ) Processes.process_name = "explorer.exe" Processes.process IN
("*\\explorer.exe") by Processes.action Processes.dest
```

```
Processes.original_file_name Processes.parent_process
Processes.parent_process_exec Processes.parent_process_guid
Processes.parent_process_id Processes.parent_process_name
Processes.parent_process_path Processes.process Processes.process_exec
Processes.process_guid Processes.process_hash Processes.process_id
Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name("Processes")` |
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`windows_masquerading_explorer_as_child_process_filter`
```

26.CMD Carry Out String Command Parameter

Descripción: Busca el uso del parámetro /c de cmd.exe, que ejecuta una orden y termina la consola. El parámetro también es común en scripts y tareas administrativas, por lo que no es malicioso por sí solo. La detección sirve para localizar cadenas de comandos que pueden formar parte de una segunda etapa, descarga o ejecución. Revisa la orden que sigue a /c, el padre, el usuario y el contexto.

Consulta SPL:

```
| tstats `security_content_summariesonly` min(_time) as firstTime max(_time)
as lastTime FROM datamodel=Endpoint.Processes WHERE `process_cmd` AND
Processes.process IN ("*/c*", "*/k*") BY Processes.action Processes.dest
Processes.original_file_name Processes.parent_process
Processes.parent_process_exec Processes.parent_process_guid
Processes.parent_process_id Processes.parent_process_name
Processes.parent_process_path Processes.process Processes.process_exec
Processes.process_guid Processes.process_hash Processes.process_id
Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name(Processes)` |
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`cmd_carry_out_string_command_parameter_filter`
```

27.Mshta spawning Rundll32 OR Regsvr32 Process

Descripción: Detecta cuando mshta.exe inicia rundll32.exe o regsvr32.exe, combinación que puede encadenar utilidades legítimas para ejecutar código o cargar componentes. Es una relación poco habitual y puede indicar que contenido HTML o un script está preparando otra fase de la intrusión. Investiga el archivo o URL que abrió mshta, los argumentos, las bibliotecas implicadas y si el equipo ejecutaba una aplicación que justifique esa cadena.

Consulta SPL:

```
| tstats `security_content_summariesonly` count min(_time) as firstTime
max(_time) as lastTime FROM datamodel=Endpoint.Processes WHERE
Processes.parent_process_name = "mshta.exe" `process_rundll32` OR
`process_regsvr32` BY Processes.action Processes.dest
Processes.original_file_name Processes.parent_process
Processes.parent_process_exec Processes.parent_process_guid
Processes.parent_process_id Processes.parent_process_name
Processes.parent_process_path Processes.process Processes.process_exec
Processes.process_guid Processes.process_hash Processes.process_id
Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name("Processes")` |
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`mshta_spawning_rundll32_or_regsvr32_process_filter`
```

28.Windows SpeechRuntime Suspicious Child Process

Descripción: Busca comandos como cmd, PowerShell, rundll32, bitsadmin, WMI o cscript iniciados por SpeechRuntime.exe, componente de Windows relacionado con funciones de voz. La relación puede resultar sospechosa porque un servicio de voz no suele necesitar ejecutar esas herramientas. Algunos ataques abusan de componentes COM para iniciar procesos en contextos inesperados. Verifica usuario, sesión, proceso padre, argumentos y cualquier acceso remoto relacionado.

Consulta SPL:

```
| tstats `security_content_summariesonly` count min(_time) as firstTime
max(_time) as lastTime FROM datamodel=Endpoint.Processes WHERE (
Processes.parent_process_name="*SpeechRuntime.exe*" ) Processes.process IN
("*cmd.exe*","*powershell.exe*","*rundll32.exe*","*bitsadmin.exe*","*wmic.exe*
","*cscript.exe*") BY Processes.dest Processes.user
Processes.original_file_name Processes.parent_process Processes.process_name
Processes.process Processes.process_id Processes.parent_process_id
Processes.parent_process_name action parent_process_exec parent_process_guid
parent_process_path process_exec process_guid process_hash
process_integrity_level process_path user_id vendor_product |
`drop_dm_object_name(Processes)` | `security_content_ctime(firstTime)` |
`security_content_ctime(lastTime)` |
`windows_speechruntime_suspicious_child_process_filter`
```

29.Windows Scheduled Task Service Spawned Shell

Descripción: Detecta cuando el servicio del Programador de tareas, alojado en svchost.exe, inicia intérpretes de comandos o motores de scripts. Las tareas programadas son una función normal de Windows, pero un atacante también puede crear tareas para ejecutar comandos o mantener persistencia. La regla se centra en la ejecución de shells por el servicio. Revisa el nombre y definición de la tarea, la cuenta usada y su origen.

Consulta SPL:

```
| tstats `security_content_summariesonly` count min(_time) as firstTime
max(_time) as lastTime from datamodel=Endpoint.Processes where
Processes.parent_process_name="svchost.exe" Processes.parent_process="*-k*"
Processes.parent_process= "*netsvcs*" Processes.parent_process="*-p*"
Processes.parent_process="*-s*" Processes.parent_process="*Schedule*"
Processes.process_name IN( "bash.exe", "cmd.exe", "cscript.exe", "ksh.exe",
"powershell.exe", "pwsh.exe", "scrcons.exe", "sh.exe", "wscript.exe",
"zsh.exe" ) by Processes.action Processes.dest Processes.original_file_name
Processes.parent_process Processes.parent_process_exec
Processes.parent_process_guid Processes.parent_process_id
Processes.parent_process_name Processes.parent_process_path Processes.process
Processes.process_exec Processes.process_guid Processes.process_hash
Processes.process_id Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name(Processes)` |
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`windows_scheduled_task_service_spawned_shell_filter`
```

30.Scheduled Task Deleted Or Created via CMD

Descripción: Busca comandos schtasks.exe ejecutados desde cmd.exe para crear o borrar tareas programadas. Los atacantes pueden crear una tarea que ejecute malware periódicamente o eliminar tareas para ocultar rastros, mientras que administradores también utilizan esta herramienta. La consulta comprueba los parámetros de creación o eliminación y filtra algunos contextos habituales. Verifica la orden completa, el nombre de la tarea, su acción y el usuario responsable.

Consulta SPL:

```
| tstats `security_content_summariesonly` count min(_time) as firstTime
max(_time) as lastTime FROM datamodel=Endpoint.Processes WHERE
Processes.parent_process_name="cmd.exe" Processes.process_name="schtasks.exe"
Processes.process IN ( "*/create*", "*-create*", "*/delete*", "*-delete*" )
NOT Processes.process IN ( "* \"C:\\Program Files (x86)\\*", "* \"C:\\Program
Files\\*", "* \"C:\\Windows\\System32\\*", "* \"C:\\Windows\\SysWOW64\\*", "*
C:\\Program Files (x86)\\*", "* C:\\Program Files\\*", "*
```

```
C:\\Windows\\System32\\*", "* C:\\Windows\\SysWOW64\\*" ) NOT
Processes.user="*$" BY Processes.action Processes.dest
Processes.original_file_name Processes.parent_process
Processes.parent_process_exec Processes.parent_process_guid
Processes.parent_process_id Processes.parent_process_name
Processes.parent_process_path Processes.process Processes.process_exec
Processes.process_guid Processes.process_hash Processes.process_id
Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name(Processes)` |
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`scheduled_task_deleted_or_created_via_cmd_filter`
```

31.Windows List ENV Variables Via SET Command From Uncommon Parent

Descripción: Detecta el uso de cmd.exe con el comando SET para listar variables de entorno cuando el proceso padre no es una consola habitual. Las variables pueden revelar rutas, configuración del equipo o datos útiles para preparar otros comandos. Consultarlas puede ser legítimo, pero si lo hace un proceso inesperado puede formar parte del reconocimiento de un atacante. Revisa qué programa lanzó cmd, el usuario y la actividad que ocurrió después.

Consulta SPL:

```
| tstats `security_content_summariesonly` count min(_time) as firstTime
max(_time) as lastTime FROM datamodel=Endpoint.Processes WHERE
Processes.process_name="cmd.exe" Processes.process IN ("*/c set", "*/c \"set")
AND NOT Processes.parent_process_name IN ("cmd.exe", "explorer.exe",
"powershell*" "pwsh.exe") BY Processes.action Processes.dest
Processes.original_file_name Processes.parent_process
Processes.parent_process_exec Processes.parent_process_guid
Processes.parent_process_id Processes.parent_process_name
Processes.parent_process_path Processes.process Processes.process_exec
Processes.process_guid Processes.process_hash Processes.process_id
Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name(Processes)` |
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`windows_list_env_variables_via_set_command_from_uncommon_parent_filter`
```

32.Windows Scheduled Task Created Via XML

Descripción: Busca la creación de tareas programadas de Windows mediante schtasks.exe con un archivo XML. Los archivos XML permiten definir con detalle la acción, el calendario y la

cuenta de una tarea, por lo que pueden usarse para establecer persistencia. La administración legítima también puede emplearlos. Revisa el contenido XML, el ejecutable configurado, la frecuencia, los permisos requeridos y si la tarea fue aprobada por el administrador.

Consulta SPL:

```
| tstats `security_content_summariesonly` count min(_time) as firstTime
max(_time) as lastTime from datamodel=Endpoint.Processes where
(Processes.process_name=schtasks.exe OR
Processes.original_file_name=schtasks.exe) Processes.process IN ("* /create
*", "* -create *") Processes.process IN ("* /xml *", "* -xml *") by
Processes.action Processes.dest Processes.original_file_name
Processes.parent_process Processes.parent_process_exec
Processes.parent_process_guid Processes.parent_process_id
Processes.parent_process_name Processes.parent_process_path Processes.process
Processes.process_exec Processes.process_guid Processes.process_hash
Processes.process_id Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name(Processes)` |
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`windows_scheduled_task_created_via_xml_filter`
```

33.Windows PowerShell Process With Malicious String

Descripción: Busca procesos de PowerShell cuya línea de comandos contiene cadenas consideradas sospechosas por la regla, como parámetros o fragmentos de comandos asociados a ejecución de scripts maliciosos. PowerShell es una herramienta legítima de administración, así que el resultado requiere contexto. Revisa el comando completo, si está codificado u oculto, el proceso que lo inició, el usuario y los eventos posteriores para determinar si fue una actividad autorizada.

Consulta SPL:

```
| tstats `security_content_summariesonly` count min(_time) as firstTime
max(_time) as lastTime FROM datamodel=Endpoint.Processes WHERE
`process_powershell` BY Processes.action Processes.dest
Processes.original_file_name Processes.parent_process
Processes.parent_process_exec Processes.parent_process_guid
Processes.parent_process_id Processes.parent_process_name
Processes.parent_process_path Processes.process Processes.process_exec
Processes.process_guid Processes.process_hash Processes.process_id
Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name(Processes)` |
```

```
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
lookup local=t malicious_powershell_strings command as process | where
isnotnull(match) | `windows_powershell_process_with_malicious_string_filter`
```

34.Detect Renamed RClone

Descripción: Detecta una copia de rclone ejecutada con otro nombre. Rclone sincroniza y transfiere archivos a múltiples destinos, incluidos servicios de almacenamiento en la nube; por eso puede usarse legítimamente para copias de seguridad o abusarse para sacar datos de una organización. La detección busca reconocer el ejecutable aunque el nombre haya cambiado. Verifica el archivo original, la cuenta, los argumentos y el destino de las transferencias.

Consulta SPL:

```
| tstats `security_content_summariesonly` count min(_time) as firstTime
max(_time) as lastTime FROM datamodel=Endpoint.Processes WHERE (
Processes.original_file_name=rclone.exe AND Processes.process_name!=rclone.exe
) BY Processes.action Processes.dest Processes.original_file_name
Processes.parent_process Processes.parent_process_exec
Processes.parent_process_guid Processes.parent_process_id
Processes.parent_process_name Processes.parent_process_path Processes.process
Processes.process_exec Processes.process_guid Processes.process_hash
Processes.process_id Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name(Processes)` |
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`detect_renamed_rclone_filter`
```

35.WinRM Spawning a Process

Descripción: Busca procesos lanzados a través de WinRM, el mecanismo de Windows para administración remota. Puede tratarse de tareas de soporte autorizadas, pero también de ejecución remota tras el robo de credenciales. En este documento se asocia a la regla original de WinRM Spawning a Process, que observa procesos hijos de wsmprovhost.exe. Confirma si la sesión remota era esperada y revisa la cuenta, el origen y los comandos.

Consulta SPL:

```
| tstats `security_content_summariesonly` count min(_time) as firstTime
max(_time) as lastTime FROM datamodel=Endpoint.Processes WHERE
Processes.parent_process_name=wsmprovhost.exe Processes.process_name IN
("cmd.exe","sh.exe","bash.exe","powershell.exe","pwsh.exe","schtasks.exe","cer
tutil.exe","whoami.exe","bitsadmin.exe","scp.exe") BY Processes.action
```

```
Processes.dest Processes.original_file_name Processes.parent_process
Processes.parent_process_exec Processes.parent_process_guid
Processes.parent_process_id Processes.parent_process_name
Processes.parent_process_path Processes.process Processes.process_exec
Processes.process_guid Processes.process_hash Processes.process_id
Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name(Processes)` |
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`winrm_spawning_a_process_filter`
```

36.Suspicious MSBuild Rename

Descripción: Detecta cuando MSBuild, herramienta legítima para compilar proyectos, aparece ejecutado con un nombre distinto o en un contexto que indica posible renombrado. Los atacantes pueden abusar de MSBuild para ejecutar código aprovechando una utilidad firmada y conocida. La regla compara la identidad del ejecutable con su nombre observado. Verifica la ruta, la firma, el archivo de proyecto usado y si había una compilación autorizada.

Consulta SPL:

```
| tstats `security_content_summariesonly` count min(_time) as firstTime
max(_time) as lastTime FROM datamodel=Endpoint.Processes WHERE
Processes.process_name!=msbuild.exe AND
Processes.original_file_name=MSBuild.exe BY Processes.action Processes.dest
Processes.original_file_name Processes.parent_process
Processes.parent_process_exec Processes.parent_process_guid
Processes.parent_process_id Processes.parent_process_name
Processes.parent_process_path Processes.process Processes.process_exec
Processes.process_guid Processes.process_hash Processes.process_id
Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name(Processes)` |
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`suspicious_msbuild_rename_filter`
```

37.Windows Regsvr32 Renamed Binary

Descripción: Detecta regsvr32.exe ejecutado con un nombre distinto del habitual. Esta utilidad registra componentes COM y puede ser aprovechada para cargar componentes o ejecutar código de manera indirecta. El cambio de nombre puede reducir la eficacia de controles sencillos basados en el nombre del proceso. Comprueba el nombre original del archivo, la

firma, la ruta, los argumentos y si la ejecución coincide con una instalación o tarea administrativa.

Consulta SPL:

```
| tstats `security_content_summariesonly` count min(_time) as firstTime
max(_time) as lastTime FROM datamodel=Endpoint.Processes WHERE
Processes.process_name != regsvr32.exe AND
Processes.original_file_name=regsvr32.exe BY Processes.action Processes.dest
Processes.original_file_name Processes.parent_process
Processes.parent_process_exec Processes.parent_process_guid
Processes.parent_process_id Processes.parent_process_name
Processes.parent_process_path Processes.process Processes.process_exec
Processes.process_guid Processes.process_hash Processes.process_id
Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name(Processes)` |
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`windows_regsvr32_renamed_binary_filter`
```

38.Detect HTML Help Renamed

Descripción: Busca el ejecutable HTML Help de Windows, hh.exe, cuando se ha renombrado. Los atacantes pueden cambiar el nombre de una herramienta conocida para evadir reglas que solo buscan el nombre habitual. La detección se centra en reconocer la identidad original del archivo, aunque el nombre actual sea distinto. Verifica ruta, firma, proceso padre y archivo de ayuda o contenido abierto para distinguir uso normal de abuso.

Consulta SPL:

```
| tstats `security_content_summariesonly` count min(_time) as firstTime
max(_time) as lastTime FROM datamodel=Endpoint.Processes WHERE
Processes.process_name!=hh.exe AND Processes.original_file_name=HH.EXE BY
Processes.action Processes.dest Processes.original_file_name
Processes.parent_process Processes.parent_process_exec
Processes.parent_process_guid Processes.parent_process_id
Processes.parent_process_name Processes.parent_process_path Processes.process
Processes.process_exec Processes.process_guid Processes.process_hash
Processes.process_id Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name(Processes)` |
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`detect_html_help_renamed_filter`
```

39.Windows Service Execution RemCom

Descripción: Detecta la ejecución de RemCom, una herramienta que permite ejecutar comandos como servicio en otro equipo. Puede aparecer en tareas legítimas de administración, pero también es utilizada para movimiento lateral después de comprometer una máquina. La regla identifica señales de ejecución de ese servicio o herramienta. Revisa qué host la inició, qué equipo recibió la conexión, qué cuenta se utilizó y si la operación estaba autorizada.

Consulta SPL:

```
| tstats `security_content_summariesonly` count min(_time) as firstTime
max(_time) as lastTime from datamodel=Endpoint.Processes where
(Processes.process_name=remcom.exe OR Processes.original_file_name=RemCom.exe)
Processes.process="*\\*" Processes.process IN ("*/user:*", "*/pwd:*") by
Processes.action Processes.dest Processes.original_file_name
Processes.parent_process Processes.parent_process_exec
Processes.parent_process_guid Processes.parent_process_id
Processes.parent_process_name Processes.parent_process_path Processes.process
Processes.process_exec Processes.process_guid Processes.process_hash
Processes.process_id Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name(Processes)` |
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`windows_service_execution_remcom_filter`
```

40.Windows Odbcconf Hunting

Descripción: Busca el uso de odbcconf.exe con argumentos que pueden cargar componentes o ejecutar acciones poco habituales. Odbcconf es una herramienta de configuración ODBC de Windows, pero ciertas opciones pueden ser abusadas para ejecutar código indirectamente. La consulta es de tipo hunting y ayuda a localizar patrones para investigar, no necesariamente a confirmar un ataque por sí sola. Revisa los argumentos, la biblioteca referenciada, el usuario y la procedencia del proceso.

Consulta SPL:

```
| tstats `security_content_summariesonly` count min(_time) as firstTime
max(_time) as lastTime FROM datamodel=Endpoint.Processes WHERE
Processes.process_name=odbcconf.exe BY Processes.action Processes.dest
Processes.original_file_name Processes.parent_process
Processes.parent_process_exec Processes.parent_process_guid
Processes.parent_process_id Processes.parent_process_name
```

```
Processes.parent_process_path Processes.process Processes.process_exec
Processes.process_guid Processes.process_hash Processes.process_id
Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name(Processes)` |
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`windows_odbcconf_hunting_filter`
```

41.Detect Renamed 7-Zip

Descripción: Detecta el ejecutable 7-Zip cuando se ha renombrado para ocultar qué programa es. La compresión de archivos es normal, pero el renombrado puede formar parte de una táctica para ocultar herramientas utilizadas para empaquetar datos o preparar una transferencia. La regla intenta identificar el nombre original del archivo pese al nombre visible. Revisa la ruta, el usuario, los archivos manipulados y si la actividad corresponde a una tarea autorizada.

Consulta SPL:

```
| tstats `security_content_summariesonly` count min(_time) as firstTime
max(_time) as lastTime FROM datamodel=Endpoint.Processes WHERE (
Processes.original_file_name=7z*.exe AND Processes.process_name!=7z*.exe ) BY
Processes.action Processes.dest Processes.original_file_name
Processes.parent_process Processes.parent_process_exec
Processes.parent_process_guid Processes.parent_process_id
Processes.parent_process_name Processes.parent_process_path Processes.process
Processes.process_exec Processes.process_guid Processes.process_hash
Processes.process_id Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name(Processes)` |
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`detect_renamed_7_zip_filter`
```

42.Powershell Windows Defender Exclusion Commands

Descripción: Busca comandos de PowerShell que añaden exclusiones a Microsoft Defender. Una exclusión puede ser necesaria para software legítimo, pero también puede permitir que archivos o carpetas maliciosos queden fuera del análisis antivirus. La detección ayuda a localizar cambios de configuración que reducen la protección. Comprueba qué exclusión se añadió, qué usuario la configuró, si existe una solicitud aprobada y qué procesos o archivos se ejecutaron alrededor del cambio.

Consulta SPL:

```
`powershell` EventCode=4104 ScriptBlockText IN ( "*Add-MpPreference *", "*Set-
MpPreference *" ) ScriptBlockText = "*-exclusion*" | fillnull | stats count
min(_time) as firstTime max(_time) as lastTime by dest signature signature_id
user_id vendor_product EventID Guid Opcode Name Path ProcessID ScriptBlockId
ScriptBlockText | `security_content_ctime(firstTime)` |
`security_content_ctime(lastTime)` |
`powershell_windows_defender_exclusion_commands_filter`
```

43.Windows Audit Policy Auditing Option Disabled via Auditpol

Descripción: Detecta el uso de auditpol para desactivar opciones de la política de auditoría de Windows. Si se reduce la auditoría, algunas acciones importantes pueden dejar de registrarse y dificultar una investigación. Administradores pueden modificar la política por motivos válidos, pero un cambio inesperado es relevante. Revisa qué subcategoría se modificó, el estado anterior y posterior, el usuario que ejecutó el comando y si existía una tarea autorizada.

Consulta SPL:

```
| tstats `security_content_summariesonly` values(Processes.process) as process
min(_time) as firstTime max(_time) as lastTime FROM
datamodel=Endpoint.Processes WHERE `process_auditpol`
Processes.process="*/set*" Processes.process="*/option:*"
Processes.process="*/value:disable*" Processes.process IN
("*FullPrivilegeAuditing*", "*AuditBaseObjects*", "*AuditBaseDirectories*") BY
Processes.action Processes.dest Processes.original_file_name
Processes.parent_process Processes.parent_process_exec
Processes.parent_process_guid Processes.parent_process_id
Processes.parent_process_name Processes.parent_process_path Processes.process
Processes.process_exec Processes.process_guid Processes.process_hash
Processes.process_id Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name(Processes)` |
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`windows_audit_policy_auditing_option_disabled_via_auditpol_filter`
```

44.Windows WMIC Shadowcopy Delete

Descripción: Busca comandos WMIC que eliminan copias sombra de Windows. Las copias sombra pueden permitir recuperar versiones anteriores de archivos, por lo que el ransomware a menudo intenta borrarlas para dificultar la recuperación. La ejecución puede ser administrativa, pero si aparece junto a otros indicios de cifrado es especialmente preocupante.

Verifica el comando, la cuenta, los procesos relacionados y si había una operación de mantenimiento o recuperación autorizada.

Consulta SPL:

```
| tstats `security_content_summariesonly` count min(_time) as firstTime
max(_time) as lastTime from datamodel=Endpoint.Processes where
Processes.process_name=wmic.exe Processes.process = "*shadowcopy*"
Processes.process = "*delete*" by Processes.action Processes.dest
Processes.original_file_name Processes.parent_process
Processes.parent_process_exec Processes.parent_process_guid
Processes.parent_process_id Processes.parent_process_name
Processes.parent_process_path Processes.process Processes.process_exec
Processes.process_guid Processes.process_hash Processes.process_id
Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name(Processes)` |
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`windows_wmic_shadowcopy_delete_filter`
```

45.Suspicious wevtutil Usage

Descripción: Detecta usos sospechosos de wevtutil, la utilidad de Windows para consultar y gestionar registros de eventos. Un atacante puede intentar limpiar determinados registros para ocultar actividad, lo que reduce la evidencia disponible para el análisis. Algunas operaciones administrativas también utilizan esta herramienta. Revisa los parámetros exactos —especialmente si indican limpieza—, qué registro se afectó, qué usuario ejecutó la orden y qué eventos precedieron al comando.

Consulta SPL:

```
| tstats `security_content_summariesonly` count min(_time) as firstTime
max(_time) as lastTime FROM datamodel=Endpoint.Processes WHERE (
Processes.process_name="wevtutil.exe" OR
Processes.original_file_name="wevtutil.exe" ) Processes.process IN ("* cl *",
"*clear-log*") Processes.process IN ( "*/Trace*", "*AMSI/Debug*",
"*Application*", "*CiscoSecureEndpoint*", "*Microsoft-Windows-BitLocker*",
"*Microsoft-Windows-Bits*", "*Microsoft-Windows-CAPI2*", "*Microsoft-Windows-
Kernel-File*", "*Microsoft-Windows-Kernel-Process*", "*Microsoft-Windows-
LDAP*", "*Microsoft-Windows-PowerShell*", "*Microsoft-Windows-Sysmon*",
"*Microsoft-Windows-TerminalServices-LocalSessionManager*", "*Microsoft-
Windows-TerminalServices-RemoteConnectionManager*", "*Microsoft-Windows-WMI-
Activity*", "*OpenSSH/*", "*PowerShellCore/*", "*Security*", "*Setup*",
"*System*", "*Windows Firewall With Advanced Security*", "*Windows
```

```
PowerShell*" ) BY Processes.action Processes.dest Processes.original_file_name
Processes.parent_process Processes.parent_process_exec
Processes.parent_process_guid Processes.parent_process_id
Processes.parent_process_name Processes.parent_process_path Processes.process
Processes.process_exec Processes.process_guid Processes.process_hash
Processes.process_id Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name(Processes)` |
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`suspicious_wevtutil_usage_filter`
```

46.Wmic Group Discovery

Descripción: Busca comandos de WMIC utilizados para enumerar grupos locales o consultar información sobre la pertenencia a grupos. Un atacante puede realizar este reconocimiento para descubrir usuarios con privilegios, entender la estructura del equipo y planificar movimientos posteriores. La consulta no implica que haya ocurrido una intrusión, ya que administradores y scripts también consultan esta información. Comprueba el usuario, el proceso padre, la línea de comandos y otras acciones relacionadas.

Consulta SPL:

```
| tstats `security_content_summariesonly` count min(_time) as firstTime
max(_time) as lastTime FROM datamodel=Endpoint.Processes WHERE
Processes.process_name=wmic.exe (Processes.process="*group get name*") BY
Processes.action Processes.dest Processes.original_file_name
Processes.parent_process Processes.parent_process_exec
Processes.parent_process_guid Processes.parent_process_id
Processes.parent_process_name Processes.parent_process_path Processes.process
Processes.process_exec Processes.process_guid Processes.process_hash
Processes.process_id Processes.process_integrity_level Processes.process_name
Processes.process_path Processes.user Processes.user_id
Processes.vendor_product | `drop_dm_object_name(Processes)` |
`security_content_ctime(firstTime)` | `security_content_ctime(lastTime)` |
`wmic_group_discovery_filter`
```