```sql
--This statement creates dimension table d_customer with attributes and primary key is assigned to dimension_customer_id
CREATE TABLE star_schema.d_customer (
 dimension_customer_id INT NOT NULL,
 title varchar(10),
 first_name varchar(50) NOT NULL,
 middle_name varchar(50),
 last_name varchar(50) NOT NULL,
 PRIMARY KEY (dimension_customer_id)
);
--This statement creates dimension table d_product with attributes and primary key is assigned to dimension_product_id
CREATE TABLE star_schema.d_product (
 dimension_product_id INT NOT NULL,
 name varchar(50) NOT NULL,
 PRIMARY KEY (dimension_product_id)
);
--This statement creates dimension table d_date with attributes and primary key is assigned to dimension_date_id
CREATE TABLE star_schema.d_date (
 dimension_date_id INT NOT NULL,
 month_name varchar(10) NOT NULL,
 day_name varchar(10) NOT NULL,
 date date NOT NULL,
 PRIMARY KEY (dimension_date_id)
);
--This statement creates fact table f_sales with attributes, primary key is assigned to sales_id and foreign keys customer_id,
product_id
CREATE TABLE star_schema.f_sales (
 sales_id INT NOT NULL,
 customer_id INT NOT NULL,
 product_id INT NOT NULL,
 date_id INT NOT NULL,
 quantity INT NOT NULL,
 line_total real NOT NULL,
 PRIMARY KEY (sales_id),
 FOREIGN KEY (customer_id) REFERENCES star_schema.d_customer(dimension_customer_id),
 FOREIGN KEY (product_id) REFERENCES star_schema.d_product(dimension_product_id),
 FOREIGN KEY (date_id) REFERENCES star_schema.d_date(dimension_date_id)
);
--This statement inserts attribute vales into dimension d_product table
INSERT INTO star_schema.d_product(dimension_product_id, name)(SELECT dimension_product_id, name FROM
StagingDatabase.staging.stage_dim_product);
--This statement inserts attribute vales into dimension d_customer table
INSERT INTO star_schema.d_customer(dimension_customer_id, title, first_name, middle_name, last_name)(SELECT
dimension_customer_id, title, first_name, middle_name, last_name FROM StagingDatabase.staging.stage_dim_customer);
--This statement inserts attribute vales into dimension d_date table
INSERT INTO star_schema.d_date(dimension_date_id, month_name, day_name, date)(SELECT * FROM
StagingDatabase.staging.stage_dim_date);
--This statement inserts attribute vales into fact f_sales table
INSERT INTO star_schema.f_sales(sales_id, customer_id, product_id, date_id, quantity, line_total) (SELECT sales_id,
customer_id, product_id, date_id, quantity, line_total FROM StagingDatabase.staging.stage_f_sales);

-- This statement returns Top seller products
SELECT FS.product_id, name, COUNT(*) as COUNT FROM star_schema.f_sales AS FS JOIN star_schema.d_product ON
FS.product_id = d_product.dimension_product_id GROUP BY FS.product_id, name ORDER BY COUNT DESC;
```