


Dynamic Linking

CS 35L


Spring 2020 - Lab 1

Building an executable file



Compilation Process

- Preprocessor
 - Expand Header includes, macros, etc
 - -E option in gcc to show the resulting code
- Compiler
 - Generates machine code for certain architecture
- Linker
 - Link all modules together
 - Address resolution
- Loader
 - Loads the executable to memory to start execution



Role of .h Files

c1.c

```
#include "global.h"

int f() {
    return g+1;
}
```

global.h

```
#ifndef INITIALIZE
    int g = 23;
    static int init = 1;
#else
    extern int g;
    static int init = 0;
#endif
```

c2.c

```
#include <stdio.h>
#include "global.h"

int main() {
    if (init)
        // do something, e.g., g=31;
    int t = f();
    printf("Calling f yields %d\n", t);
    return 0;
}
```

Role of .h Files

c1.c

```
#include "global.h"  
  
int f() {  
    return g+1;  
}
```

global.h

```
extern int g;  
static int init = 0;
```

```
#else  
    extern int g;  
    static int init = 0;  
#endif
```

c2.c

```
#define INITIALIZE  
#include <stdio.h>  
#include "global.h"  
  
int main() {  
    if (init)  
        // do something, e.g., g=31;  
    int t = f();  
    printf("Calling f yields %d\n", t);  
    return 0;  
}
```

```
int g = 23;  
static int init = 1;
```

Linking and Loading

- Linker collects procedures and links them together with object modules into one executable program
- Why isn't everything written as just one **big** program, saving the necessity of linking?
 - Efficiency: if just one function is changed in a 100K line program, why recompile the whole program? Just recompile the one function and relink.
 - Multiple-language programs


Linux Libraries

- **Static Library**

- Statically linked
- Every program has its own copy
- More space in memory
- Tied to a specific version of the lib. New version of the lib requires recompile of source code.

- **Shared Library (binding at run-time)**


- Dynamically loaded/linking
 - **Dynamic Linking** – The OS loads the library when needed. A dynamic linker does the linking for the symbol used.
 - **Dynamic Loading** – The program “actively” loads the library it needs (DL API – dlopen(), dlclosel()). More control to the program at run-time. Permits extension of programs to have new functionality.
- Library is shared by multiple programs
- Lower memory footprint
- New version of the lib does not require a recompile of source code using the lib



Img Source : <http://www.ibm.com/developerworks/library/l-dynamic-libraries/>

Static Linking

- Carried out only once to produce an executable file
- If static libraries are called, the linker will copy all the modules referenced by the program to the executable
- Static libraries are typically denoted by the .a file extension (archive)



A previously compiled
collection of standard
program functions

Static Linking

main.c

```
int buf[2] = {1, 2};

int main()
{
    swap();
    return 0;
}
```

swap.c




```
extern int buf[];

int *bufp0 = &buf[0];
static int *bufp1;


void swap()
{
    int temp;

    bufp1 = &buf[1];
    temp = *bufp0;
    *bufp0 = *bufp1;
    *bufp1 = temp;
}
```

Relocatable Object Files





Executable Object File



Even though private to swap, requires allocation in .bss

Dynamic Linking

- Allows a process to add, remove, replace or relocate object modules during its execution.
- If shared libraries are called:
 - Only copy a little reference information when the executable file is created
 - Complete the linking during loading time or running time
- Dynamic libraries are typically denoted by the .so (shared object) file extension
 - .dll (dynamically linked library) on Windows



Dynamic linking

- Unix systems: Code is typically compiled as a *dynamic shared object* (DSO)

- Dynamic vs. static linking resulting size

```
$ gcc -static hello.c -o hello-static
```

```
$ gcc hello.c -o hello-dynamic
```

```
$ ls -l hello
```

```
    80 hello.c
```


```
 13724 hello-dynamic
```

```
   383 hello.s
```

```
1688756 hello-static
```

- If you are the sysadmin, which do you prefer?

Smaller is more efficient



Advantages of dynamic linking

- The executable is typically smaller
- When the library is changed, the code that references it does not usually need to be recompiled
- The executable accesses the .so at run time; therefore, multiple programs can access the same .so at the same time
 - Memory footprint amortized across all programs using the same .so

Disadvantages of dynamic linking

- Performance hit
 - Need to load shared objects (at least once)
 - Need to resolve addresses (once or every time)
- What if the necessary dynamic library is missing?
- What if we have the library, but it is the wrong version? (DLL Hell)

How are libraries dynamically loaded?

Table 1. The DL API

Function	Description
dlopen	Makes an object file accessible to a program
dlsym	Obtains the address of a symbol within a dlopened object file
dlerror	Returns a string error of the last error that occurred
dlclose	Closes an object file

Dynamic loading

```
#include <stdio.h>
#include <dlfcn.h>

int main(int argc, char* argv[]) {
    int i = 10;
    void (*myfunc)(int *);
    void *dl_handle;
    char *error;

    dl_handle = dlopen("libmymath.so", RTLD_LAZY); //vs RTLD_NOW
    if (!dl_handle)
        { printf("dlopen() error - %s\n", dlerror()); return 1; }

    myfunc = dlsym(dl_handle, "mul5");
    error = dlerror();
    if (error != NULL)
        { printf("dlsym mul5 error - %s\n", error); return 1; }
    myfunc(&i);

    myfunc = dlsym(dl_handle, "add1");
    error = dlerror();
    if (error != NULL)
        { printf("dlsym add1 error - %s\n", error); return 1; }
    myfunc(&i);

    printf("i = %d\n", i);
    dlclose(dl_handle);
    return 0;
}
```

Copy this code into main.c

gcc main.c -o main -ldl

You will have to set the environment variable `LD_LIBRARY_PATH` to include a path that contains libmymath.so

GCC Flags

- `-fPIC`: Compiler directive to output position independent code, a characteristic required by shared libraries.
- `-lXXX`: Link with "`libXXX.so`"
 - Without `-L` to directly specify the path, `/usr/lib` is used.
- `-L`: At **compile** time, find `.so` from this path.
- `-Wl, rpath=.`: `-Wl` passes options to linker. `-rpath` at **runtime** finds `.so` from this path.
- `-c`: Generate object code from c code.
- `-shared`: Produce a shared object which can then be linked with other objects to form an executable.

Creating static and shared libs in GCC

- mymath.h

```
#ifndef _ MY_MATH_H
#define _ MY_MATH_H

void mul5(int *i);
void add1(int *i);

#endif
```

- mul5.c

```
#include "mymath.h"

void mul5(int *i)
{
    *i *= 5;
}
```

- add1.c

```
#include "mymath.h"

void add1(int *i)
{
    *i += 1;
}
```

- gcc -c mul5.c -o mul5.o
- gcc -c add1.c -o add1.o
- ar -cvq libmymath.a mul5.o add1.o → (static lib)
- gcc -shared -fpic -o libmymath.so mul5.o add1.o → (shared lib)

Attributes of Functions

- Used to declare certain things about functions called in your program
 - Help the compiler optimize calls and check code
- Also used to control memory placement, code generation options or call/return conventions within the function being annotated
- Introduced by the **attribute** keyword on a declaration, followed by an attribute specification inside double parentheses

Attributes of Functions

- `__attribute__((__constructor__))`
 - Is run when `dlopen()` is called
- `__attribute__((__destructor__))`
 - Is run when `dlclose()` is called
- **Example:**

```
__attribute__((__constructor__))  
void to_run_before (void) {  
    printf("pre_func\n");  
}
```

Lab 7

- Compile a simple math program
- Test the program on test inputs
- Use **ldd** command to see which dynamic libraries are being used.
- Use **strace** command to see what system calls are being made (how are they related to Dynamic Linking?)
- Investigate other commands with **ldd** (depending on your UID)

Lab 7 hint

```
#!/bin/bash
```

```
for x in "$(ls /usr/bin | awk \
\'(NR-your_uid)%251 == 0\')"; do
    y=`which $x`
    ldd $y
done
```

example run, unique sort:

```
./ldd_run | grep so | sort -u
```


Useful Resources

- Useful overview of dynamic libraries: [Click here](#)
- Man page for DL API: [Click here](#)
- www.ibm.com/developerworks/library/l-dynamic-libraries/
- www.ibm.com/developerworks/library/l-lpic1-102-3/
- tldp.org/HOWTO/Program-Library-HOWTO/index.html
- www.yolinux.com/TUTORIALS/LibraryArchives-StaticAndDynamic.html
- man7.org/linux/man-pages/man7/vdso.7.html