

LLM-based Agents Suffer from Hallucinations: A Survey of Taxonomy, Methods, and Directions

Xixun Lin, Yucheng Ning, Jingwen Zhang, Yan Dong, Yilong Liu, Yongxuan Wu, Xiaohua Qi, Nan Sun, Yanmin Shang, Kun Wang, Pengfei Cao, Qingyue Wang, Lixin Zou, Xu Chen, Chuan Zhou, Jia Wu, Peng Zhang, Qingsong Wen, Shirui Pan, Bin Wang, Yanan Cao, Kai Chen, Songlin Hu, Li Guo

Abstract—Driven by the rapid advancements of Large Language Models (LLMs), LLM-based agents have emerged as powerful intelligent systems capable of human-like cognition, reasoning, and interaction. These agents are increasingly being deployed across diverse real-world applications, including student education, scientific research, and financial analysis. However, despite their remarkable potential, LLM-based agents remain vulnerable to hallucination issues, which can result in erroneous task execution and undermine the reliability of the overall system design. Addressing this critical challenge requires a deep understanding and a systematic consolidation of recent advances on LLM-based agents. To this end, we present the first comprehensive survey of hallucinations in LLM-based agents. By carefully analyzing the complete workflow of agents, we propose a new taxonomy that identifies different types of agent hallucinations occurring at different stages. Furthermore, we conduct an in-depth examination of eighteen triggering causes underlying the emergence of agent hallucinations. Through a detailed review of a large number of existing studies, we summarize approaches for hallucination mitigation and detection, and highlight promising directions for future research. We hope this survey will inspire further efforts toward addressing hallucinations in LLM-based agents, ultimately contributing to the development of more robust and reliable agent systems.

Index Terms—LLM-based Agents, Hallucinations, Safety.

I. INTRODUCTION

Language Models (LLMs) [1], [2], [3], [4], [5] have recently showcased extraordinary capabilities across a

X. Lin, Y. Ning, J. Zhang, Y. Dong, Y. Liu, Y. Wu, X. Qi, N. Sun, Y. Shang, Y. Cao, K. Chen, S. Hu, and L. Guo are with Institute of Information Engineering, Chinese Academy of Sciences, School of Cyber Security, University of Chinese Academy of Sciences, Beijing, China.

K. Wang is with Nanyang Technological University, Singapore.

P. Cao is with Institute of Automation, Chinese Academy of Sciences, Beijing, China.

Q. Wang is with Hong Kong University of Science and Technology, Hong Kong, China.

L. Zou is with School of Cyber Science and Engineering, Wuhan University, Wuhan, China.

X. Chen is with Gaoling School of Artificial Intelligence, Renmin University of China, Beijing, China.

C. Zhou is with Academy of Mathematics and Systems Science, Chinese Academy of Sciences, Beijing, China.

J. Wu is with School of Computing, Faculty of Science and Engineering, Macquarie University, Sydney, Australia.

P. Zhang is with the Cyberspace Institute of Advanced Technology, Guangzhou University, Guangzhou, China.

Q. Wen is with Squirrel Ai Learning, Bellevue, USA.

S. Pan is with School of Information and Communication Technology, Griffith University, Gold Coast, Australia.

B. Wang is with Xiaomi Company, Beijing, China.

broad spectrum of tasks, including language generation [6], intent comprehension [7], and knowledge reasoning [8]. These capabilities are largely attributed to the vast scale of training data [9], model architecture innovations [10], and emergent abilities [11] that arise during instruction tuning [12] and in-context learning [13]. Building on these breakthroughs, **LLM-based Agents** [14], [15], [16], [17], [18] are becoming increasingly proficient in task automation across a wide range of fields, marking a critical milestone on the path toward Artificial General Intelligence (AGI) [19]. Moreover, these agents can be orchestrated into a **LLM-based Multi-agent System** (MAS) [20], [21], [22], [23], [24], where different agents with distinct specializations collaborate and interact to solve real-world and complex problems beyond the capacity of any single agent through mutual cooperation, such as knowledge sharing [25] and collaborative coordination [26].

Despite the impressive performance achieved by LLM-based agents, their rapid advancement introduces a spectrum of safety challenges [27], [28], [29]. Among these challenges, **Agent Hallucinations** represents a particularly significant threat [30], [31], [32]. Previous studies on hallucinations have primarily focused on the field of natural language generation (NLG) [13], where hallucinations refer to the phenomenon in which NLG models generate unfaithful or nonsensical text. Ji et al. review recent advances in addressing hallucinations across various NLG tasks [33]. Meanwhile, Huang et al. specifically focus on the causes of LLM hallucinations [34]. In this context, hallucinations in LLMs are categorized into factuality and faithfulness hallucinations. Factuality hallucinations highlight discrepancies between the generated content and verifiable real-world facts [35]; while faithfulness hallucinations refer to deviations from the user's original input [36]. In addition, the authors discuss several effective methods for detecting and mitigating hallucination issues [37].

Unlike the aforementioned settings, the LLM-based agent is a more sophisticated intelligent system, equipped with goal-directed reasoning and action-taking capabilities. Such agents typically comprise three core modules: brain, perception, and action [38]. The brain module is primarily responsible for storing memory and knowledge, supporting reasoning and decision-making for executing tasks; the perception module extends the agent's perceptual space, enabling it to handle multi-modal environmental inputs; and the action module expands the agent's action space, allowing it not only to generate




Fig. 1. An overview of agent goal completion. Within the loop, the LLM-based agent carries out external behaviors such as reasoning, execution, perception, and memorization, guided by its internal belief state. Throughout this process, the environment dynamically evolves in response to the agent's decisions, while task allocation within the LLM-based multi-agent system including broadcasting and structure evolution further enhances the fulfillment of user requirements.

textual outputs but also to invoke tools for completing more complex tasks. Therefore, in LLM-based agents, hallucinations are not "linguistic errors", but rather a broad category of fabricated or misjudged "human-like behaviors" that may occur at any stage of the agent's pipeline. Accordingly, the manifestations and causes of agent hallucinations are considerably more complex. This complexity is reflected in three key aspects:

1) More Diverse Types: Rather than the straightforward response errors of a single model, agent hallucinations are compound behaviors arising from interactions among multiple modules, resulting in a broader and more varied range of hallucination types. **2) Longer Propagation Chains:** The aforementioned hallucinations are mostly localized and single-step errors, whereas agent hallucinations often span multiple steps and involve multi-state transitions. Such hallucinations are not limited to the final output; they may also arise during intermediate processes such as perception and reasoning, where they can propagate and accumulate over time. **3) More Severe Consequences:** Agent hallucinations involve "physically consequential" errors, where incorrect embodied actions can directly affect task execution, system devices, and user experiences in the real world. As a result, the cost and risk associated with agent hallucinations are significantly higher. However, existing reviews of LLM-based agents primarily focus on architectural designs and practical applications, while giving far insufficient attention to the importance and urgency of agent hallucinations.

To this end, we provide an overview of agent hallucinations to fill this important gap and promote the advancement of

agents. In this paper, the interaction dynamics of LLM-based agents are formulated as a partially observable Markov decision process (POMDP) where the agent¹ interacts with the learning environment, makes decisions, receives feedback, and updates its state over multiple time steps. Based on this general POMDP setting, we summarize the contributions of our work below.

- **First Survey.** To the best of our knowledge, this is the first survey to review hallucination issues in LLM-based agents. It encompasses recent research on both mitigation and detection methods, offering a broad perspective on the development of LLM-based agents.
- **Innovative Taxonomy.** We introduce a novel decomposition of agent components into two parts: internal state and external behaviors. The former is characterized by a belief state maintained by the agent, which serves as the most fundamental unit of the agent cognition policy. External behaviors refer to a series of proactive procedures guided by the belief state. Through this internal–external distinction, we can classify agent hallucinations based on the specific stage at which they occur, covering five types of agent hallucinations.
- **Comprehensive Review.** For each type of agent hallucinations, we offer a formal definition, illustrative examples, and an in-depth discussion of representative studies. Based on this, we identify eighteen triggering causes of agent hallucinations. Furthermore, we summarize ten

¹Throughout this paper, we use the term "agent" to denote the LLM-based agent, unless otherwise specified.

general approaches for hallucination mitigation, along with corresponding detection methods, to provide readers with a clear and up-to-date overview of the current research landscape on agent hallucinations.

- **Future Outlook.** By reviewing and summarizing existing solutions to hallucination problems and their possible limitations, we outline several promising directions for future exploration that will need to be fully investigated to advance both academic research and real-world deployment of LLM-based agents.
- **Open Resource.** We provide a well-curated collection of resources, encompassing over 200+ related papers, which we make publicly available on GitHub² to foster community engagement and collaboration.

Paper Organization. The remainder of this paper is structured as follows. Section II introduces the formal definition of LLM-based agents. Based on this definition, Section III presents a new taxonomy of agent hallucinations. Section IV reviews existing solutions, with particular emphasis on methodologies for hallucination mitigation. Section V outlines future research directions. Section VI concludes the survey.

II. FORMAL DEFINITION OF LLM-BASED AGENTS

Fig. 1 provides an overview of agent goal completion. The formal definition of LLM-based agents including interaction dynamics and LLM-based agent loop is given here.

A. Interaction Dynamics

The interaction dynamics between the agent and the learning environment is usually formulated as a Partially Observable Markov Decision Process (POMDP) [39] which is defined as a 8-tuple: $\mathcal{E} = (\mathcal{S}, \mathcal{A}, T, \mathcal{G}, \mathcal{O}, Z, R, \gamma)$. The description of each element in \mathcal{E} is given here:

- \mathcal{S} is the state space where $s \in \mathcal{S}$ represents a true environment state. A POMDP explicitly models an agent decision process in which the agent cannot directly observe the underlying state. Instead, the agents must maintain a **Belief State** to represent its subjective understanding of the learning environment.
- \mathcal{A} is the action space. An action $a \in \mathcal{A}$ involves content generation or the use of external tools, such as scheduling events via calendar APIs and issuing smart home control commands.
- $T : \mathcal{S} \times \mathcal{A} \rightarrow P(\mathcal{S})$ is the state transition probability function. For each state-action pair (s, a) , it specifies a probability distribution over possible subsequent states. For example, executing a “turn off lights” action may result in reaching the desired state with 90% probability, while network latency or system errors could cause the state to remain unchanged with 10% probability.
- \mathcal{G} is the goal space. Each goal $g \in \mathcal{G}$ specifies a particular objective of users.
- \mathcal{O} is the observation space. Each observation $o \in \mathcal{O}$ represents a partial view of s , which can be manifested through different modalities. Partial observability may

stem from multiple factors, such as the complexity of the learning environment and the limitations of the agent’s perceptual capabilities.

- $Z : \mathcal{S} \times \mathcal{A} \rightarrow \mathcal{O}$ is the observation function. For each state-action pair (s, a) , it provides a possible observation o for the agent.
- $R : \mathcal{S} \times \mathcal{A} \rightarrow \mathcal{R}$ is the reward function, where \mathcal{R} is the reward space. For each state-action pair (s, a) , it provides a feedback $r \in \mathcal{R}$, and r is usually expressed in numerical form.
- $\gamma \in [0, 1)$ is the discount factor. It serves to balance the importance between immediate and future rewards. Since events that occur farther in the future are harder to predict accurately, it is generally desirable to reduce the significance of long-term rewards.

B. LLM-based Agent Loop

Given a specific goal g , accomplishing it typically requires multiple execution loops. Furthermore, since the true environment state cannot be directly observed, an LLM-based agent needs to maintain a belief state b_t that represents its internal and subjective understanding of the learning environment. In the multi-loop process, the agent continuously updates b_t , allowing b_t to be dynamically refined across diverse contexts and over extended time spans. b_t is the most fundamental unit in the agent’s loop process, forming the basis of all agentic operations. Based on b_t , we further introduce the agent’s external behaviors including reasoning, execution, perception, and memorization. The concrete calculation in each loop can be given here:

- **Reasoning:** The agent first generates a plan p_t for the next action conditioned on b_t and g :

$$p_t = \Phi(b_t, g). \quad (1)$$

- **Execution:** The agent then translates p_t into an executable action a_t :

$$a_t = E(b_t, p_t). \quad (2)$$

a_t typically involves the invocation of relevant external tools.

- **Feedback:** The learning environment would objectively provide a reward r_t based on s_t and a_t :

$$r_t = R(s_t, a_t). \quad (3)$$

- **Environment Transition:** The learning environment transitions to the next state $s_{t+1} \in \mathcal{S}$ according to the following generated probability distribution:

$$\Pr(s_{t+1}|s_t, a_t) = T(s_t, a_t). \quad (4)$$

- **Perception:** The agent would then perceive s_{t+1} and generate the observation $o_{t+1} \in \mathcal{O}$:

$$o_{t+1} = Z(s_{t+1}, b_t, a_t). \quad (5)$$

- **Memorization:** Both a_t and o_{t+1} are used for updating its external memory module:

$$m_{t+1} = L_M(m_t, a_t, o_{t+1}). \quad (6)$$

²<https://github.com/ASCII-LAB/Awesome-Agent-Hallucinations>.

- **Belief Update:** Based on the above decision-making process and feedback, the agent refines b_t as follows,

$$b_{t+1} = L_B(b_t, m_{t+1}, a_t, r_t, o_{t+1}). \quad (7)$$

The agent ultimately receives a cumulative discounted reward (i.e., $\sum_{t=0}^{\infty} \gamma^t r_t$) as a measure of goal achievement.

Different from the single-agent setting, in the LLM-based MAS, each agent must communicate with other agents to accomplish goals. To model these processes, a communication structure G_t is introduced among N agents. Furthermore, G_t would evolve with time to align with the dynamic adjustments of MAS. Therefore, compared with the above loop, the loop of LLM-based MAS is given as “Reasoning–Execution–Broadcasting–Feedback–Environment Transition–Perception–Memorization–Belief Update–Structure Evolution”. This loop includes two additional procedures: Broadcasting and Structure Evolution. Broadcasting means that the agent broadcasts its message to neighboring nodes according to its plan, while structure evolution indicates that the communication structure G_t can be updated in each iteration. The complete description of the loop of MAS is given in Appendix A.

Definition of Agent hallucinations

According to the proposed internal–external distinction, agent hallucinations refer to fictitious or erroneous operations in LLM-based agents, driven by overconfident “human-like behaviors” in reasoning, execution, perception, memorization, and communication. Unlike LLM hallucinations, which are typically limited to linguistic errors, agent hallucinations go beyond language generation, manifesting as compound deviations arising from the coupling and interaction of multiple modules. These deviations can escalate to task failures and even physical safety risks. In contrast to other types of agent errors, agent hallucinations are often spontaneously generated within the agent’s own cognitive processes, representing an endogenous error form. Furthermore, owing to their cross-module propagation and hidden cognitive nature, agent hallucinations pose an especially serious threat, making them a central challenge in the pursuit of agent safety.

III. TAXONOMY OF AGENT HALLUCINATIONS

We first provide a formal definition of agent hallucinations. Based on this definition, we then introduce the new taxonomy that includes the following five types of agent hallucinations: Reasoning Hallucinations, Execution Hallucinations, Perception hallucinations, Memorization Hallucinations, and Communication Hallucinations, as illustrated in Fig. 2. Detailed descriptions of each type of agent hallucinations are provided in the following sub-sections. Representative hallucination examples are presented in Appendix B.

A. Reasoning Hallucinations

Reasoning serves as the cornerstone of an agent’s functionality, influencing behavior analysis and decision-making [40], [41], [42]. Upon receiving a specific goal g , the agent first leverages its own reasoning capabilities to perform goal understanding for inferring the user’s true intention:

- **Goal Understanding:** This phase occurs before the agent executes multiple loops:

$$\mathcal{I} = \text{Understand}(b_0, g), \quad (8)$$

where \mathcal{I} denotes the inferred intention, and b_0 represents the initial belief state. When \mathcal{I} is complex and relatively difficult to execute, the agent would perform the intention decomposition to decompose \mathcal{I} into a series of manageable sub-intentions $\{\mathcal{I}_t\}_{t=0}^n$.

- **Intention Decomposition:** Typically, there are two decomposition methods: pre-defined decomposition and dynamic decomposition. In the first one, these sub-intentions are specified in advance:

$$\{\mathcal{I}_t\}_{t=0}^n = \text{Pre-decompose}(b_0, \mathcal{I}). \quad (9)$$

In the second one, the sub-intention for each loop is generated by

$$\mathcal{I}_t = \text{Dyn-decompose}(b_t, \mathcal{I}). \quad (10)$$

The decomposition results are dynamically optimized based on the current belief state b_t , enabling timely and continuous refinement for the subsequent workflow [43].

- **Planning Generation:** Each sub-intention \mathcal{I}_t is then mapped to a concrete plan p_t for the current loop:

$$p_t = \text{Plan}(b_t, \mathcal{I}_t). \quad (11)$$

Definition of Reasoning Hallucinations

Reasoning hallucinations refer to the phenomena where LLM-based agents generate seemingly plausible plans which are in fact logically flawed or unsupported. Reasoning hallucinations occur in either of above three stages, and we categorize them into three types: **Goal Understanding Hallucinations (GUHs)**, manifested as misinterpretation of goal semantics, typically caused by problematic objective expression and inadequate subjective comprehension; **Intention Decomposition Hallucinations (IDHs)**, characterized by the flawed decomposition processes that produce irrelevant or infeasible sub-intentions, often due to deficient dependency modeling; **Planning Generation Hallucinations (PGHs)** represent hallucinations that occur when an agent generates each specific plan of a sub-intention, typically caused by the misinterpretation and misapplication of planning information.

The subsequent sub-sections detail the triggering causes that give rise to these three types of reasoning hallucinations.

- 1) **Problematic Objective Expression.** Understanding the user’s true intention from g is the first and essential step for effective




Fig. 2. A taxonomy of agent hallucinations. It includes five hallucination types and nine hallucination sub-types with corresponding triggering causes.

reasoning [44]. Objectively, when the expression of goal information carries a certain degree of semantic vagueness, it can easily lead to erroneous parsing of user intention and induce reasoning hallucinations [45], [46]. This semantic vagueness can be mainly attributed to two issues: **Incomplete Goal Specification** and **Ambiguous Content Presence** [47], [48]. To address semantic vagueness in user input, a plausible and effective approach is to endow the agent with the capability of active clarification [49], [50]. By engaging in appropriate proactive interactions with the user, the agent can gain a deeper understanding of the user's true needs and intentions.

2) *Inadequate Subjective Comprehension*. In addition to above objective issues, there also exist subjective limitations in the agent's comprehension capability. These are mainly manifested as **Instruction-following Deviation** [51], as well as **Long-range Contextual Misuse** [52]. Specifically, instruction following refers to an agent's ability to adhere to user-provided instructions in order to accurately comprehend intentions [53]. When this procedure breaks down, the agent struggles to segment critical fields and extract key information from instructions, leading to distorted understanding and reasoning hallucinations [54], [55], [56]. Additionally, when agents handle excessively long input goals, they may fail to capture long-range contexts and instead over-rely on the most recent tokens, resulting in contextual misuse [57], [58], [59]. Such deficiencies cause agents to violate explicitly stated user preferences [60].

3) *Deficient Dependency Modeling*. Intention decomposition is a crucial phase where agents determine the successive reasoning process via the decomposed sub-intentions [61], [62], [63]. These sub-intentions typically form a sequentially dependent chain, where the completion of each sub-intention pre-supposes the successful fulfillment of its predecessors. Inadequate modeling of dependency relationships among these sub-intentions can give rise to three types of errors: **Sub-intention Omission**, **Sub-intention Redundancy** [64], [65] and **Sub-intentions Disorder**. All three severely compromise reasoning integrity and efficiency, ultimately leading to reasoning hallucinations [66]. Sub-intention omission occurs when agents fail to identify essential sub-intentions, leading to the absence of critical reasoning steps [67]. Sub-intention redundancy arises when agents erroneously introduce task-irrelevant sub-intentions, causing reasoning processes to deviate from the core intention and generating hallucinatory content [68], [69], [67]. Sub-intention disorder refers to the phenomenon in which an agent arranges sub-intentions with a sequential relationship in the wrong order during reasoning, causing it to fail to obtain the results of prerequisite sub-intentions, thereby missing key information and further generating hallucinations [70].

4) *Planning Information Misinterpretation*. In Eq.(11), the agent relies on two key sources of information to generate sub-intention plans: **Operable Objects** and **Self-knowledge**. For operable objects, the agent must recognize both explicit and implicit relational connections between entities (e.g.,

spatial, temporal, or social relationships) [71], [72], [73]. The misinterpreting information related to these operable objects can lead the agent to construct plans based on incorrect assumptions, thereby inducing planning generation hallucinations [74]. With respect to self-knowledge, the agent is expected to plan reasonably within the bound of its own self-knowledge to avoid planning errors. When confronted with planning problems beyond its knowledge boundary, the agent tends to respond with excessive confidence, generating answers that sound certain but are actually incorrect [75].

5) *Planning Information Misapplication.* Even when an agent correctly identifies the operable objects within its knowledge boundary, its ability to effectively utilize them remains constrained by its **Logical Reasoning** and **Introspection Capacity** [76]. Logical fallacies primarily manifest as rule conflicts and causal misattributions [77]. Similar to humans, when agents encounter issues such as rule conflicts, causal inversion, or misattribution during causal reasoning [78], they often fail to complete the reasoning process or resolve underlying logical paradoxes, ultimately leading to erroneous planning [79]. Additionally, introspection is one of the key mechanisms by which agents achieve learning, cognition, and knowledge updating [15], agents that lack sufficient introspection capacity are unable to effectively improve their performance by revisiting logical fallacies in their reasoning [80]. Such agents may misinterpret feedback signals and accurately identify the sources of error [81], thereby making misguided adjustments to their reasoning processes [82]. Even when feedback is correctly interpreted, the introspection process may still be flawed: agents might wrongly judge their reasoning as consistent despite existing logical contradictions, or mistakenly believe they have considered all relevant factors while overlooking critical variables [83].

Definition of Execution Hallucinations

Execution hallucinations refer to the phenomenon where LLM-based agents claim to have completed certain sub-stages during the execution phase, but in reality, they have not actually been performed or accomplished. According to the above two sub-stages, we divide execution hallucinations into two types: **Tool Selection Hallucinations (TSHs)**, where non-existent or irrelevant tools are chosen overconfidently; and **Tool Calling Hallucinations (TCHs)**, involving incorrect, omitted, or fabricated parameter fillings.

B. Execution Hallucinations

The execution phase is where the agent translates its deliberated plan p_t into a concrete, executable action a_t . a_t typically involves invoking external tools, either as a single operation or through multiple parallel instances [84]. Broadly, this execution process in Eq.(2) can be further decomposed into two sub-stages [85]:

- **Tool Selection:** Given p_t and a set of candidate tools $\mathcal{T}_{\text{cand}}$, the agent must first select the appropriate tool $T_s \in$

$\mathcal{T}_{\text{cand}}$ as follows³,

$$T_s = \text{Select}(b_t, p_t, \mathcal{T}_{\text{cand}}). \quad (12)$$

As there are a large number of tools, $\mathcal{T}_{\text{cand}}$ is typically retrieved from a full tool set \mathcal{T} to narrow the selection scope [86]:

$$\mathcal{T}_{\text{cand}} = \text{Retr}(b_t, p_t, \mathcal{T}). \quad (13)$$

- **Tool Calling:** Once T_s is selected, the agent then needs to populate T_s with the tool parameters derived from b_t and p_t to form the final executable action a_t :

$$a_t = \text{Call}(b_t, p_t, T_s). \quad (14)$$

The underlying causes behind these two execution hallucinations are given in the following sub-sections.

1) *Tool Documentation Limitation.* Execution hallucinations often arise when the agent's internal representation of tool behaviors diverges from the actual functionality of tools, frequently due to limitation in **Tool Documentation** [87]. These hallucinations occur because the agent believes it has correctly selected or invoked a tool, even though its decision is based on misleading documentation. Such deficiencies may include redundant information [88], [89], incomplete or inaccurate descriptions [90], [91], or a lack of standardization [92], [93], all of which impair the agent's ability to properly use tools.

2) *Shallow Pattern Understanding.* The agent's shallow understanding of **Tool Patterns** may lead to execution hallucinations wherein the agent confidently invokes invalid or outdated tools, mistakenly assuming successful execution. In fact, effective tool usage requires LLM-based agents to develop deep understanding of tool patterns. This requirement primarily stems from two key factors: First, tools often provide multiple functionalities that can be applied across diverse scenarios, rather than being limited to a single task-specific use case [94]; Second, tools frequently exhibit complex collaborative patterns, such as sequential dependencies and the need for nested calls [95]. However, LLM-based agents are typically trained with insufficient exposure to diverse and complex tool-use scenarios [96], [97], [98]. This limitation makes agents prone to hallucinating tool invocations that may appear plausible or confident, but in fact violate expected patterns or omit essential details, especially when dealing with complex and novel tasks [99].

3) *Weak Dynamic Adaptability.* LLM-based agents are typically trained on relatively static datasets, with their tool-use knowledge embedded in fixed model parameters [97], [98]. However, the execution environment of tools is inherently dynamic and continuously evolving. Tool functionalities may evolve, API interfaces may be modified, and in some cases, tools may be deprecated or replaced [99], [100], [101]. When an agent lacks sufficient adaptability to these **Tool Dynamics**, its tool-use behavior becomes misaligned with the actual environment, thus leading to execution hallucinations wherein the agent confidently invokes outdated or invalid tools while incorrectly assuming successful execution.

³ T_s may denote multiple tools that are invoked in parallel to accelerate execution.

4) Lack of Solvability Awareness. **Tool Solvability** refers to whether the current plan p_t can be successfully executed under existing conditions. It is primarily related to two factors: a) the availability of suitable tools in \mathcal{T} ; b) the clarity and completeness of p_t . A lack of solvability awareness in LLM-based agents can also lead to execution hallucinations, where the agent mistakenly assumes that p_t is solvable and proceeds with unjustified confidence. For example, if no suitable tools are available, any tool retrieved from \mathcal{T} is likely to be irrelevant or even fabricated and non-executable, resulting in tool selection hallucinations [102]. Furthermore, even when a suitable tool exists and is correctly selected, an unclear or incomplete plan p_t can prevent the agent from correctly deriving the required parameters for tool invocation [103]. Consequently, the agent may omit required parameters or fabricate parameter values, falsely believing that the tool call is valid.

C. Perception Hallucinations

Analogous to how humans depend on sensory organs like eyes and ears to acquire information from the external world and convert it into neural signals, LLM-based agents also rely on a perception module to facilitate interaction with the learning environment. The perception module serves as a fundamental interface, extending its perception into a multi-modal space that includes textual, auditory, and visual modalities. As illustrated in Eq.(5), the agent receives the external information (e.g., s_{t+1}) and transforms this information into internal observations (e.g., o_{t+1}) via the perception module. Here we analyze the causes of perception hallucinations.

Definition of Perception Hallucinations

Perception hallucinations refer to the phenomenon where, during the process of receiving and transforming external information, an agent produces internal observations that significantly deviate from or contain factual errors about the actual learning environment. This typically arises from environmental sensor malfunction or limited encoding capability. Such hallucinations undermine the agent's accurate perception and further disrupt subsequent decision-making processes.

1) Environmental Sensor Malfunction. Agents typically rely on environmental sensors to collect external data and convert it into digital signals [104]. Common sensor types include visual sensors (e.g., cameras), auditory sensors (e.g., microphones), tactile sensors (e.g., pressure-sensitive pads), and inertial measurement units (e.g., accelerometers) [30]. When environmental sensor malfunctions occur, such as lens distortion in cameras or signal drift in inertial measurement units, agents may fail to accurately receive raw input information, potentially resulting in perception hallucinations.

2) Limited Encoding Capability. After receiving s_{t+1} , LLM-based agents typically employ a specific encoding module to generate o_{t+1} , which serves as a high-level representation of the received signals such as images and sound waves. However, this encoding process encounters two critical limitations:

a) Insufficient Unimodal Representation: Agents struggle to

extract the key information of individual modality from s_{t+1} . This limitation arises from multiple factors, potentially including insufficient training data quality [105], the Transformer architecture's tendency [10] to overlook local details [106], and training conflicts between the pre-training and fine-tuning stages [107]. **b) Weak Cross-modal Collaboration:** Agents lack an effective mechanism to integrate semantic associations across different modalities, resulting in the incomplete representation of s_{t+1} . When faced with a complex learning environment, LLM-based agents typically perform the procedures of modality alignment and joint encoding to integrate different multi-modal information [108]. However, during this process, LLM-based agents may fail to align modalities due to insufficient cross-modal annotations and imbalanced modality data [109]. Furthermore, in the generation stage, agents may be dominated by the language prior, gradually neglecting non-textual information [110].

Definition of Memorization Hallucinations

Memorization hallucinations refer to the phenomenon in which an agent implicitly assumes its memory to be accurate and reliable, without validating the correctness of the stored content. Consequently, when the agent incorporates its memory module into decision-making, it may rely on outdated, fabricated, or conflated memories, resulting in flawed reasoning or inappropriate actions. Based on the above two operations, we categorize memorization hallucinations into two types: **Memory Retrieval Hallucinations (MRHs)**, where irrelevant or non-existent information are retrieved; and **Memory Update Hallucinations (MUHs)**, involving incorrect modifications and deletions of memory content.

D. Memorization Hallucinations

The memory module is a core component of LLM-based agents, tasked with storing and managing information to facilitate subsequent decision-making [111], [112], [113]. It primarily owns two operations: **Memory Retrieval**: Extracting and integrating relevant information from stored memory to support the current decision process; **Memory Update**: revising and removing existing memory based on newly acquired information or feedback to ensure its accuracy and timeliness.

Subsequently, we analyze the underlying causes that trigger the above two memorization hallucinations.

1) Flawed Memory Initialization. The **Initial Memory** m_0 serves as the foundation of memorization in LLM-based agents, and its quality directly influences the reliability of subsequent memory processes. Biased or incomplete content in m_0 can introduce initialization deficiencies, leading to memorization hallucinations before deployment. In particular, certain biases, particularly those related to gender and nationality, are inherently linked to hallucination issues [34]. Moreover, when critical information is missing (e.g., the time or location of a historical event) in m_0 , agents may rely on inherent biases or assumptions to fill in the gaps, resulting in inaccurate or

fabricated responses in many real-world scenarios [114], [115], [116].

2) *Sub-optimal Retrieval Mechanism.* First, poor **Ranking Strategies** may lead the agent to retrieve memory content that only superficially "appears similar" but lacks true relevance [117], [118]. Additionally, deficiencies in the memory **Indexing Structure** [119], [120], such as inappropriate index granularity or delayed index updates, can further exacerbate this problem, potentially resulting in information loss and the retrieval of outdated memory. Finally, insufficient understanding of **Query Semantics** is also an important problem. If the agent misinterprets the query's intent or overlooks specific task requirements [121], [122], it may fail to capture contextual cues necessary for accurate retrieval.

3) *Imperfect Priority Assignment.* This issue mainly manifests in two aspects: **Forgetting Priority** and **Merging Priority**. For memory forgetting, poorly assigned priorities can result in the elimination of important information or the retention of irrelevant content, ultimately compromising the accuracy of subsequent decisions [112], [123]. Moreover, when the agent merges multiple memory fragments, failure to correctly assess their priorities [124], [125] may result in the merged memory containing inherent conflicts [126], [127]. Some of these conflicts are implicit [128]: Although memory fragments may appear similar, they differ significantly in key semantic details, thereby increasing the difficulty of priority determination.

4) *Inaccurate Information Writing.* When performing long-term tasks and engaging in multi-turn interactions, agents must summarize, structure, and store relevant historical information to the memory module. However, this process is susceptible to **Information Compression** issues, where the generated summaries may be overly general, omit crucial details [129], [130], [131], or introduce distortions due to imperfect abstraction [132], [133], [111]. Additionally, non-standardized **Memory Formats** with disorganized structures can hinder writing efficiency [111], [134]. Memory **Capacity Constraints** exacerbate these challenges, because limited storage may necessitate the selective retention of information [112], [135], increasing the risk that salient but less frequently accessed information is discarded.

E. Communication Hallucinations

Definition of Communication Hallucinations

Communication hallucinations refer to the phenomenon in which LLM-based agents appear to engage in meaningful inter-agent communication, yet the information exchanged is inaccurate, misleading, or fabricated, thereby undermining collaboration. Such hallucinations typically arise from erroneous message propagation, where incorrect information is shared as if reliable; uncoordinated communication protocols, where inconsistent formats or timing lead to misunderstandings; and ineffective network updates, where outdated or poorly synchronized connections distort information flow and hinder task execution.

Compared with the independent operations of a single agent, LLM-based MAS emphasizes collaboration and coordination to harness collective intelligence for solving more complex and demanding tasks [136]. In such systems, effective inter-agent communication serves as an essential requirement [137], facilitating the exchange of ideas and the coordination of plans among agents [138].

The following sub-sections provide a detailed account of triggering causes underlying communication hallucinations.

1) *Erroneous Message Propagation.* In LLM-based MAS, agents fundamentally rely on LLMs [38], [139], [30] to generate messages for exchanging information with other agents. However, since LLMs are prone to the well-known **Factuality and Faithfulness Hallucinations** [34], some agents may produce messages containing inaccurate facts, misinterpretations of shared knowledge, or misleading inferences [140], [141], [142], thereby giving rise to communication hallucinations. Beyond this, **Content Redundancy** is also an important cause, where agents generate unnecessary or repetitive content that obscures critical signals, increases cognitive load, and sometimes leads to redundant task execution steps that manifest as logical errors [143], [144], [141]. **Information Asymmetry** can further exacerbate this issue. Because agents own different roles and positions within MAS, the information accessible to them varies, and such asymmetric settings may yield vague or incomplete instructions that hinder task comprehension [145] and amplify the risk of biased decisions [146].

2) *Uncoordinated Communication Protocols.* Communication protocols govern how agents exchange messages, directly determining the efficiency, reliability, and coordination of their interactions [147], [137], [148]. Without a unified and effective protocol, agents may "talk past each other", leading to communication hallucinations. First, LLM-based MAS usually follows a manner of **Asynchronous Scheduling** [22], so when receiving and processing instructions, agents may encounter issues of information loss and information overload. Such temporal discrepancies can result in information errors, thereby increasing the risk of hallucinatory outputs [149], [150]. Second, communication protocols define the **Message formats**. Current LLM-based agents predominantly rely on the format of natural language [151] which often introduces instruction ambiguity. Adopting structured formats (e.g., JSON) can improve clarity and rigor of expression, which mitigates the risk of miscommunication [152], [153]. Finally, LLM-based MAS demands a robust **Fault-tolerant Design**, incorporating confirmation conditions and synchronization constraints to avoid erroneous decisions caused by message loss or delays in dynamic or noisy environments [154], [155].

3) *Ineffective Network Updates.* Network topology defines how agents are interconnected, determining who communicates with whom and how frequently [137], [20], [156]. As discussed in Appendix A, the network topology is continuously evolving, and network updates reshape the propagation paths of messages within MAS. When network updates are ineffective, they can induce communication hallucinations due to inconsistent or outdated inter-agent connections [141], [142], [157]. Although recently proposed strategies improve the flexibility and responsiveness of MAS, they often suffer from

delayed updates and poor coordination [20], [158], [159]. If the updated network fails to accurately reflect agents' current relevance or expertise, messages may be routed to inappropriate recipients, leading to misunderstandings or redundant reasoning in LLM-based MAS.

IV. SYSTEMATIC METHODOLOGY

In this section, we provide a comprehensive review of recent methods for mitigating and detecting hallucinations in agents. For mitigation, we systematically group existing approaches into three main categories in Section IV-A: **1) Knowledge Utilization**, which leverages external and internal knowledge to address hallucination issues; **2) Paradigm Improvement**, which focuses on developing advanced learning paradigms to prevent agent hallucinations during training and inference; and **3) Post-hoc Verification**, which introduces verification techniques to calibrate agent outputs and reduce the risk of hallucinations. In Fig. 3, we provide a simple illustration of each specific mitigation approach. For detection, existing methods are fewer compared to mitigation, so we place detection methods after mitigation methods. In Section IV-B, we review the available detection approaches corresponding to each type of agent hallucinations.

A. Agent Hallucination Mitigation

1) Knowledge Utilization. This category equips LLM-based agents with accurate and reliable information support, enabling multi-dimensional regulation of their reasoning, execution, perception, and memorization behaviors. This, in turn, helps reduce hallucinatory outputs stemming from knowledge gaps and biases. Here we categorize knowledge utilization into two types: **a) External Knowledge Guidance:** Agent hallucinations often arise from insufficient knowledge guidance. Therefore, external knowledge serves as a critical resource for mitigating hallucinations and enhancing output reliability. **b) Internal Knowledge Enhancement:** This line of research focuses on activating or rectifying the agent's internal knowledge to better mitigate hallucinations.

a) External Knowledge Guidance (EKG)⁴. We categorize the existing approaches of external knowledge guidance into two types: **Expert Knowledge** and **World Models**.

Expert knowledge refers to the domain-specific information distilled from the behaviors and decision-making processes of human experts or high-performing systems during task execution. Owing to its high reliability and precision, expert knowledge serves as a robust external reference, significantly reducing the likelihood of hallucinations across various agentic operations. In related literature, expert knowledge can be manifested different forms, and we list several representative forms: **i) Knowledge base methods:** Expert knowledge can be stored as knowledge bases, such as introspective reasoning knowledge bases [160], action knowledge bases [59], experiential knowledge bases [161], from which agents can retrieve real cases and incorporate them into prompts to support more accurate decision-making [61]. **ii) Rule-based methods:**

expert knowledge can be leveraged to establish rules such as mathematical rules [77], linguistic rules [71], procedural rules [162] or MAS communication protocols [155]. These rules can explicitly constrain the agent's external behaviors, mitigating agent hallucination risks [163]. **iii) Data construction methods:** By leveraging expert annotations and prompting techniques, synthetic datasets can include diverse and targeted instruction-response pairs [164], Q&A pairs [165] or preference pairs [166]. These curated datasets can enhance the agent's capability to handle complex scenarios, including fine-grained reasoning, tool usage, and multi-modal perception.

World models refer to systems that construct useful representations of the world, equipping agents with foundational world knowledge [167]. This enables them to handle real-world problems and reject outputs that contradict established facts, thereby effectively mitigating the occurrence of agent hallucinations [168]. In POMDP setting, world models are particularly important for constructing more accurate estimations of partially observable environments [169], [170]. The scope of world knowledge encompasses a wide range of domains, from fundamental **Physical Principles** [171] such as Newton's laws of motion and the conservation of mass to complex **Social Systems and Structures** [57], [172]. For example, NavMorph [173] leverages the world model to provide knowledge of the physical environment, avoiding navigation biases caused by environmental unfamiliarity, while WKM [174] supplies common-sense knowledge—such as the need to clean ingredients before cooking—to achieve behaviors aligned with human expectations.

b) Internal Knowledge Enhancement (IKE). Current enhancement strategies can be broadly classified into two types: **Internal Knowledge Activation** and **Internal Knowledge Rectification**. The former aims to leverage **Prompt Engineering** to carefully stimulate and utilize the agent's internal knowledge, guiding it to fully exploit its capabilities. Here we highlight several representative prompting techniques: **i) Chain-of-Thought (CoT):** By incorporating step-by-step reasoning instructions [175], [176] into the prompt, CoT guides the agent to break down complex problems and output intermediate steps in a logical sequence, thereby enhancing the accuracy and reliability of handling multi-step tasks. **ii) Tree-of-Thought (ToT):** Building upon CoT, ToT explores and evaluates multiple reasoning paths in parallel [177], [58], fully utilizing the diversified information within the agent's internal knowledge to strengthen the completeness and robustness of its reasoning process. **iii) Constrained Prompting:** By incorporating various forms of constraints [178], [179] such as semantic [180] and spatial constraints [181] into prompts, this approach guides the agent to focus on task-relevant information, effectively reducing the generation of irrelevant content.

Internal knowledge rectification generally involves two representative paradigms. The first is **Knowledge Editing** which replaces inaccurate or outdated knowledge with correct knowledge while minimizing disruptions to other internal knowledge [114]. It is typically divided into two main approaches [182]: the locate-and-edit approach [183], which identifies and modifies specific knowledge components; the

⁴The abbreviation is added here mainly to save space in Table I.




Fig. 3. A simple illustration of approaches to agent hallucination mitigation. It encompasses three branches, knowledge utilization, paradigm improvement, and post-hoc certification, comprising a total of ten representative methods.

meta-learning approach [184], which aims to learn how to update the model's parameters for adjusting knowledge for new information. The second is **Knowledge Unlearning**. In contrast to knowledge editing, it focuses on removing erroneous knowledge to improve the agent's reliability. It includes two main approaches [185]: parameter optimization [186], which fine-tunes model parameters under certain conditions (e.g., parameter update scopes[187]) to forget some targeted knowledge; parameter merging [188], which performs offline operations on model parameters without further training.

2) *Paradigm Improvement*. This section focuses on enhancing the agent's capabilities through general learning paradigms to mitigate hallucinations. We summarize six representative paradigms as follows.

a) *Contrastive Learning (CoL)* is a well-established self-supervised learning paradigm whose core idea is to learn more discriminative representations by comparing similarities and differences between samples [189], [190], [191]. By incorporating contrastive learning, the agent can better identify relevant and accurate patterns, reducing errors when handling unfamiliar or incomplete task inputs and effectively mitigating hallucination issues [192], [193], [194].

b) *Curriculum Learning (CuL)* is a learning paradigm inspired by the way humans learn. Its core idea is to start training the model with "easy" examples and gradually move to "harder" ones, improving learning efficiency and generalization ability [189]. By leveraging curriculum learning, agents rapidly accumulate successful experiences by starting with simpler tasks and gradually transferring this knowledge to

more complex scenarios. This progressive learning paradigm enhances their fundamental capabilities, effectively mitigating agent hallucinations [195], [196], [94].

c) *Reinforcement Learning (RL)* serves as a fundamental learning paradigm, emulating the biological learning process of "trial, feedback, and adjustment". This approach enables agents to interact with their environment and learn to maximize cumulative rewards through iterative trial and error [197]. Through the reinforcement learning paradigm, the agent can adjust its policy based on rewards, thereby optimizing future decision-making, learning to achieve goals in complex environments, and significantly mitigating potential hallucination issues in multi-turn interactions [198], [199], [200], [201], [202]. In addition, there are also studies that aim to improve the reliability of reward signals in order to enhance the overall model effectiveness [203].

d) *Causal Learning (CaL)* refers to the process in statistical machine learning that goes beyond capturing mere correlations and instead aims to model, discover, and leverage causal relationships between variables, thereby enhancing the model's interpretability and generalization ability [204], [205]. In the context of LLM-based agents, identifying and leveraging potential causal relationships within task inputs and decision-making processes enables more accurate understanding of how different factors influence task outcomes. This helps reduce representational errors and logical inconsistencies for mitigating perception [206], [207] and reasoning hallucinations [208], [209].

e) *Graph Learning (GL)* is a class of machine learning

TABLE I

AN OVERVIEW OF MITIGATION METHODS. TO SAVE SPACE, WE USE THE ABBREVIATIONS OF HALLUCINATION TYPES AND MITIGATION METHODS MENTIONED EARLIER. “✓” INDICATES THAT RELATED WORKS ALREADY EXIST; “–” INDICATES THAT IT HAS NOT YET BEEN EXPLORED.

Type	Branch	Knowledge Utilization		Paradigm Improvement						Post-hoc Verification	
		EKG	IKE	CoL	CuL	RL	CaL	GL	DO	SM	VA
Reasoning Hallucinations	GUHs	✓	✓	✓	–	✓	–	–	–	✓	✓
	IDHs	✓	✓	–	–	–	–	✓	✓	✓	✓
	PGHs	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Execution Hallucinations	TSHs	✓	✓	✓	✓	✓	–	✓	–	✓	✓
	TCHs	✓	✓	✓	✓	✓	–	–	–	✓	✓
Perception Hallucinations		✓	✓	✓	–	✓	✓	–	✓	–	✓
Memorization Hallucinations	MRHs	✓	–	–	–	–	–	✓	–	–	✓
	MUHs	✓	✓	✓	–	–	–	✓	–	–	✓
Communication Hallucinations		✓	–	–	–	✓	–	✓	–	✓	✓

paradigms specifically designed to handle graph-structured data, which has been widely applied in various domains such as social networks, bioinformatics, and recommendation systems [210], [211], [212]. It enhances the agent’s capability to organize and manage tasks in a structured and systematic manner, particularly for tool usage and memory updates, thereby reducing the risk of agent hallucinations [213], [17], [214]. For example, ControlLLM [215] builds a tool graph comprising resource and tool nodes, and employs a parallel graph search algorithm to efficiently find appropriate tool paths for mitigating execution hallucinations. More importantly, recent studies leverage graph learning to optimize communication topology in LLM-based MAS [157], [216], [217]. By dynamically learning which agents should communicate, when, and through what channels, the system can suppress noisy message passing while promoting informative interactions.

Unlike the aforementioned training-phase learning paradigms, *f) Decoding Optimization (DO)* is a test-time learning paradigm. This paradigm can improve output quality by adjusting probability distributions or attention patterns in decoding processes, ensuring better alignment with inputs and factual knowledge, thereby reducing hallucinations stemming from reasoning errors [54], [218], [219]. Common decoding strategies include contrastive decoding, self-calibrated attention decoding [220] and fusion decoding [218]. Contrastive decoding [221] selects more reliable and context-consistent outputs by comparing multiple decoding candidates. Self-calibrated attention decoding [220] aims to dynamically adjust the attention weights to capture more informative cues. Fusion decoding incorporates the multi-source information to reduce dependence on single-modal priors for mitigating hallucinations. CGD [222] is one of representative works, which integrates semantic similarity scores between textual and visual content with final-layer token likelihoods to reduce reliance on language priors.

3) *Post-hoc Verification*. This paradigm focuses on monitoring and evaluating outputs after task execution. It generally follows a multi-step process in which, immediately after each

step, the agent assesses the validity, consistency, and factuality of the intermediate decisions and actions generated in that specific step. This assessment helps prevent the accumulation and propagation of hallucinations in long-horizon tasks. Existing approaches can be broadly categorized into two types: **a) Self-verification Mechanism**, in which the agent introspectively reviews its own behaviors using an internal reasoning strategy or prompt-based self-assessment. **b) Validator Assistance**, which leverages another independent system to detect potential flaws in the agent’s outputs.

a) Self-verification Mechanism (SM). Self-verification is a lightweight and model-internal approach wherein agents assess the validity and reliability of their own outputs without relying on external validators. It plays a crucial role in hallucination mitigation [223], and several technical methods have been explored to implement self-verification. Specifically, **Self-reflection** enables agents to revisit and critique their own outputs, often through prompting techniques that encourage introspection and identification of reasoning flaws [89], [224], [15], which can be further facilitated by estimating the agent’s own confidence or uncertainty [225], [226], [50]. **Self-consistency** leverages the generation of multiple candidate outputs, such as diverse reasoning paths or answers, and aggregates them using majority voting or confidence-weighted schemes to select the most reliable results [177], [81], [78]. **Self-questioning** guides the agent to pose and answer critical verification questions grounded in its own reasoning process, enabling the detection of unsupported assertions [227], [228], [74]. Collectively, these strategies establish a foundation for autonomous error detection and correction, empowering agents to self-regulate hallucination risks.

b) Validator Assistance (VA). This approach leverages external validators to verify the correctness of an agent’s outputs, aiming to mitigate hallucinations [141], [142]. According to the types of external validators, we divide existing methods into the following five categories: **Language-based Validators** independently assess the truthfulness or coherence of an agent’s outputs using techniques such as atomic fact




Fig. 4. A typology of methods of agent hallucination detection. We highlight the representative approaches for each type of agent hallucinations.

decomposition and entailment checking [229], [230], [231]. **Retrieval-based Validators** rely on some external sources such as search engines to verify whether outputs aligns with established facts [232]. **Execution-based Validators** evaluate outputs by running generated codes or plans in external execution environments, enabling direct assessment of correctness through functional outcomes [233]. **Simulation-based Validators** validate agent behaviors through interaction with sandboxed environments, allowing for realistic testing in tasks involving embodiment, planning, or sequential control [234]. Building on these categories, an increasing number of studies have explored **Ensemble-based Validators** that integrate multiple types of validators to improve robustness. By enabling cross-verification among different approaches, these methods help mitigate the limitations inherent in individual validation strategies [78]. In the end, Table I summarizes which types of agent hallucinations can be addressed by the ten listed mitigation methods.

B. Agent Hallucination Detection

Based on the introduced taxonomy of agent hallucinations, we summarize the existing detection methods in Fig. 4. From it, we can observe that unlike the mitigation strategies discussed above, research on agent hallucination detection remains relatively limited. Among these detection methods, those addressing perception hallucinations are relatively numerous, whereas methods on memorization hallucinations and

communication hallucinations are comparatively limited. We believe this is because perception belongs to the shallow layers of the agent, making hallucination detection and error identification relatively straightforward, which explains the larger amount of corresponding work. In contrast, memory and communication are part of the deeper layers of the agent, where the final outputs are coupled with computations from numerous intermediate modules. This makes hallucination detection and localization more challenging, and consequently, there is comparatively less work in these areas.

V. FUTURE DIRECTIONS

LLM-based agent hallucinations represent an emerging research frontier that has attracted increasing attention from both academia and industry. As discussed above, a substantial body of work has focused on the mitigation and detection of agent hallucinations. Building upon our established taxonomy and existing literature, this survey introduces several promising directions for future study.

1) Hallucinatory Accumulation Investigation. Most existing studies investigate hallucination instances and their underlying causes within a single agent loop. However, as we emphasize, agent decision-making is inherently a multi-step and sequential process, in which hallucinations can accumulate and amplify over time. In such cases, hallucinations may initially appear as minor issues, but their iterative accumulation can ultimately lead to severe consequences. Compared to single-step scenarios, hallucination accumulation presents a significantly more

complex challenge. Addressing it requires a comprehensive analysis of the agent’s entire decision-making process, thereby facilitating early hallucination detection and mitigation.

2) Accurate Hallucinatory Location. As previously mentioned, in contrast to hallucinations in traditional language models that are typically manifested in textual generation errors, agent hallucinations are far more complex, involving full-chain error propagation across multiple interdependent components. While hallucination taxonomy and attribution we presented in Section III have mapped these issues to specific modules within the agent, promptly and accurately locate the source of agent hallucinations in the final outputs remains a significant challenge. This difficulty stems from the fact that agent hallucinations may arise at any stage of the decision-making pipeline and often exhibit complex characteristics such as hallucinatory accumulation and inter-module dependency. In fact, the limited amount of research on agent hallucination detection in Section IV-B and the difficulty of conducting such works are also related to this issue. Therefore, future study should focus on designing agent systems capable of modeling and tracing their entire execution trajectories [142]. For example, lightweight checkpoints can be injected at each stage to verify whether hallucinations have occurred.

3) Hallucination Mechanistic Interpretability. Mechanistic interpretability (MI) seeks to uncover how hidden representations and internal components of neural networks give rise to specific behaviors [270]. Therefore, MI provides a natural pathway for diagnosing and mitigating hallucinations at the root cause. Recent studies demonstrate that MI techniques, such as feature analysis [271] and causal pathway tracing [272] can reveal the internal sources of hallucinations in LLMs and provide insights for mitigation. However, extending MI to LLM-based agents introduces new challenges. Unlike LLMs, where interpretability analysis is typically performed under single-step prediction with controlled prompt-response settings, agent hallucinations emerge through multi-step sequential interactions involving reasoning, tool use, memorization, and MAS communication. This dynamic process substantially complicates the controlled interventions required for mechanistic analysis. Future research should therefore adapt MI techniques to account for these dynamic and interconnected processes, enabling more precise diagnosis and systematic mitigation of agent hallucinations.

4) Unified Benchmark Construction. Existing benchmarks for agent hallucinations are often limited to a specific hallucination type. For example, Guan et al. propose HALLUSION-BENCH to evaluate hallucination issues in visual-language reasoning [273]; Hu et al. propose MemoryAgentBench to evaluate hallucination issues in agents during memory retrieval and update [274]; Zhang et al. introduce ToolBH to evaluate execution hallucinations in tool use across different scenarios from both depth and breadth perspectives [31]. Therefore, there is a lack of a unified benchmark of hallucination evaluation that can define diverse hallucination scenarios and adopt various evaluation metrics to comprehensively assess the extent of hallucinations in agents’ reasoning, execution, perception, memory, and communication.

5) Continual Self-evolution Capacity. The analysis of agent

hallucinations is typically conducted under the assumption of fixed user goals and static environments. However, in practice, both user demands and environmental configurations evolve continuously over time. To remain effective, agents must possess continual self-evolution capabilities that allow them to dynamically adapt to shifting goals and changing conditions. Throughout this process, agents can consistently refine their cognition to mitigate agent hallucinations stemming from outdated knowledge or delayed updates. Based on this important need, integrating the lifelong learning paradigm [275] with agents to endow them with more effective dynamic adaptation capabilities represents a promising solution.

6) Foundation Architecture Upgrade. Current LLM-based agents primarily rely on the Transformer architecture. However, this architecture faces challenges in handling long-context information and suffers from high computational complexity, which have gradually revealed performance bottlenecks and contributed to the emergence of hallucination issues. Recent works have explored more effective architectural upgrades, such as introducing linear-complexity modules [276] as Transformer components, integrating neural-symbolic systems [277] to enhance model interpretability through symbolic reasoning, and leveraging automated machine learning [278] to design and compose optimal model architectures. In addition, agents typically require a predefined workflow to organize the execution of their various components. While this fixed pattern enhances systematization and controllability, it also reduces flexibility, resulting in limited adaptability and poor scalability. Designing a dynamic self-scheduling agentic system [279] that can autonomously organize task execution and coordinate multi-agent collaboration is a critical direction for future research.

VI. CONCLUSION

This paper presents a comprehensive survey of hallucination issues in LLM-based agents, with the goal of consolidating past progress, clarifying current challenges, and outlining future opportunities. We begin by distinguishing agent components into internal states and external behaviors, and, from this perspective, propose a taxonomy of hallucination types occurring at different stages. We then provide an in-depth overview of each type and identify seventeen underlying causes. Furthermore, we summarize ten general approaches for hallucination mitigation, together with corresponding detection methods. Finally, we discuss promising research directions to guide future exploration in this rapidly evolving domain. We believe this survey can serve as a valuable resource for researchers and practitioners, inspiring and facilitating further progress in the development of LLM-based agents.

REFERENCES

- [1] Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*, 2023.
- [2] Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, et al. Llama: Open and efficient foundation language models. *arXiv preprint arXiv:2302.13971*, 2023.

- [3] Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almehairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*, 2023.
- [4] Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, et al. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*, 2024.
- [5] Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Ruoyu Zhang, Runxin Xu, Qihao Zhu, Shirong Ma, Peiyi Wang, Xiao Bi, et al. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *arXiv preprint arXiv:2501.12948*, 2025.
- [6] Bailin Wang, Zi Wang, Xuezhi Wang, Yuan Cao, Rif A Saurous, and Yoon Kim. Grammar prompting for domain-specific language generation with large language models. *Advances in Neural Information Processing Systems*, 36:65030–65055, 2023.
- [7] Mingyang Geng, Shangwen Wang, Dezun Dong, Haotian Wang, Ge Li, Zhi Jin, Xiaoguang Mao, and Xiangke Liao. Large language models are few-shot summarizers: Multi-intent comment generation via in-context learning. In *Proceedings of the 46th IEEE/ACM International Conference on Software Engineering*, pages 1–13, 2024.
- [8] Linhao Luo, Yuan-Fang Li, Gholamreza Haffari, and Shirui Pan. Reasoning on graphs: Faithful and interpretable large language model reasoning. *arXiv preprint arXiv:2310.01061*, 2023.
- [9] Yue Yu, Yuchen Zhuang, Jieyu Zhang, Yu Meng, Alexander J Ratner, Ranjay Krishna, Jiaming Shen, and Chao Zhang. Large language model as attributed training data generator: A tale of diversity and bias. *Advances in Neural Information Processing Systems*, 36:55734–55784, 2023.
- [10] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.
- [11] Jason Wei, Yi Tay, Rishi Bommasani, Colin Raffel, Barret Zoph, Sebastian Borgeaud, Dani Yogatama, Maarten Bosma, Denny Zhou, Donald Metzler, et al. Emergent abilities of large language models. *arXiv preprint arXiv:2206.07682*, 2022.
- [12] Shayne Longpre, Le Hou, Tu Vu, Albert Webson, Hyung Won Chung, Yi Tay, Denny Zhou, Quoc V Le, Barret Zoph, Jason Wei, et al. The flan collection: Designing data and methods for effective instruction tuning. In *International Conference on Machine Learning*, pages 22631–22648. PMLR, 2023.
- [13] Qingxiu Dong, Lei Li, Damai Dai, Ce Zheng, Jingyuan Ma, Rui Li, Heming Xia, Jingjing Xu, Zhiyong Wu, Tianyu Liu, et al. A survey on in-context learning. *arXiv preprint arXiv:2301.00234*, 2022.
- [14] Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. React: Synergizing reasoning and acting in language models. In *International Conference on Learning Representations (ICLR)*, 2023.
- [15] Noah Shinn, Federico Cassano, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. Reflexion: Language agents with verbal reinforcement learning. *Advances in Neural Information Processing Systems*, 36:8634–8652, 2023.
- [16] Zehui Chen, Kuikun Liu, Qiuchen Wang, Wenwei Zhang, Jiangning Liu, Dahua Lin, Kai Chen, and Feng Zhao. Agent-flan: Designing data and methods of effective agent tuning for large language models. *arXiv preprint arXiv:2403.12881*, 2024.
- [17] Xixi Wu, Yifei Shen, Caihua Shan, Kaitao Song, Siwei Wang, Bohang Zhang, Jiarui Feng, Hong Cheng, Wei Chen, Yun Xiong, and Dongsheng Li. Can graph learning improve planning in llm-based agents? In *Proceedings of Neural Information Processing Systems*, 2024.
- [18] Lei Wang, Chen Ma, Xueyang Feng, Zeyu Zhang, Hao Yang, Jingsen Zhang, Zhiyuan Chen, Jiakai Tang, Xu Chen, Yankai Lin, et al. A survey on large language model based autonomous agents. *Frontiers of Computer Science*, 18(6):186345, 2024.
- [19] Ben Goertzel. Artificial general intelligence: concept, state of the art, and future prospects. *Journal of Artificial General Intelligence*, 5(1):1, 2014.
- [20] Joon Sung Park, Joseph O'Brien, Carrie Jun Cai, Meredith Ringel Morris, Percy Liang, and Michael S Bernstein. Generative agents: Interactive simulacra of human behavior. In *Proceedings of the 36th annual acm symposium on user interface software and technology*, pages 1–22, 2023.
- [21] Guohao Li, Hasan Hammoud, Hani Itani, Dmitrii Khizbulin, and Bernard Ghanem. Camel: Communicative agents for “mind” exploration of large language model society. *Advances in Neural Information Processing Systems*, 36:51991–52008, 2023.
- [22] Sirui Hong, Mingchen Zhuge, Jonathan Chen, Xiawu Zheng, Yuheng Cheng, Jinlin Wang, Ceyao Zhang, Zili Wang, Steven Ka Shing Yau, Zijuan Lin, Liyang Zhou, Chenyu Ran, Lingfeng Xiao, Chenglin Wu, and Jürgen Schmidhuber. MetaGPT: Meta programming for a multi-agent collaborative framework. In *The Twelfth International Conference on Learning Representations*, 2024.
- [23] Chi-Min Chan, Weize Chen, Yusheng Su, Jianxuan Yu, Wei Xue, Shanghang Zhang, Jie Fu, and Zhiyuan Liu. Chateval: Towards better llm-based evaluators through multi-agent debate. *arXiv preprint arXiv:2308.07201*, 2023.
- [24] Taicheng Guo, Xiuying Chen, Yaqi Wang, Ruidi Chang, Shichao Pei, Nitesh V Chawla, Olaf Wiest, and Xiangliang Zhang. Large language model based multi-agents: A survey of progress and challenges. *arXiv preprint arXiv:2402.01680*, 2024.
- [25] Yanwen Ba, Xuan Liu, Xinning Chen, Hao Wang, Yang Xu, Kenli Li, and Shigeng Zhang. Cautiously-optimistic knowledge sharing for cooperative multi-agent reinforcement learning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pages 17299–17307, 2024.
- [26] Kunlun Zhu, Hongyi Du, Zhaochen Hong, Xiaocheng Yang, Shuyi Guo, Zhe Wang, Zhenhailong Wang, Cheng Qian, Xiangru Tang, Heng Ji, et al. Multiagentbench: Evaluating the collaboration and competition of llm agents. *arXiv preprint arXiv:2503.01935*, 2025.
- [27] Zhixin Zhang, Shiyao Cui, Yida Lu, Jingzhuo Zhou, Junxiao Yang, Hongning Wang, and Minlie Huang. Agent-safetybench: Evaluating the safety of llm agents. *arXiv preprint arXiv:2412.14470*, 2024.
- [28] Tongxin Yuan, Zhiwei He, Lingzhong Dong, Yiming Wang, Ruijie Zhao, Tian Xia, Lizhen Xu, Binglin Zhou, Fangqi Li, Zhuosheng Zhang, et al. R-judge: Benchmarking safety risk awareness for llm agents. *arXiv preprint arXiv:2401.10019*, 2024.
- [29] Yu Tian, Xiao Yang, Jingyuan Zhang, Yingpeng Dong, and Hang Su. Evil geniuses: Delving into the safety of llm-based agents. *arXiv preprint arXiv:2311.11855*, 2023.
- [30] Bang Liu, Xinfeng Li, Jiayi Zhang, Jinlin Wang, Tanjin He, Sirui Hong, Hongzhang Liu, Shaokun Zhang, Kaitao Song, Kunlun Zhu, et al. Advances and challenges in foundation agents: From brain-inspired intelligence to evolutionary, collaborative, and safe systems. *arXiv preprint arXiv:2504.01990*, 2025.
- [31] Yuxiang Zhang, Jing Chen, Junjie Wang, Yaxin Liu, Cheng Yang, Chufan Shi, Xinyu Zhu, Zihao Lin, Hanwen Wan, Yujiu Yang, Tetsuya Sakai, Tian Feng, and Hayato Yamana. Toolbehonest: A multi-level hallucination diagnostic benchmark for tool-augmented large language models. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing, EMNLP 2024, Miami, FL, USA, November 12–16, 2024*, pages 11388–11422, 2024.
- [32] Zehang Deng, Yongjian Guo, Changzhou Han, Wanlun Ma, Junwu Xiong, Sheng Wen, and Yang Xiang. Ai agents under threat: A survey of key security challenges and future pathways. *ACM Computing Surveys*, 57(7):1–36, 2025.
- [33] Ziwei Ji, Nayeon Lee, Rita Frieske, Tiezheng Yu, Dan Su, Yan Xu, Etsuko Ishii, Ye Jin Bang, Andrea Madotto, and Pascale Fung. Survey of hallucination in natural language generation. *ACM computing surveys*, 55(12):1–38, 2023.
- [34] Lei Huang, Weijiang Yu, Weitao Ma, Weihong Zhong, Zhangyin Feng, Haotian Wang, Qianglong Chen, Weihua Peng, Xiaocheng Feng, Bing Qin, et al. A survey on hallucination in large language models: Principles, taxonomy, challenges, and open questions. *ACM Transactions on Information Systems*, 43(2):1–55, 2025.
- [35] Sewon Min, Kalpesh Krishna, Xinxi Lyu, Mike Lewis, Wen-tau Yih, Pang Wei Koh, Mohit Iyyer, Luke Zettlemoyer, and Hannaneh Hajishirzi. Factscore: Fine-grained atomic evaluation of factual precision in long form text generation. *arXiv preprint arXiv:2305.14251*, 2023.
- [36] Alexander R Fabbri, Chien-Sheng Wu, Wenhao Liu, and Caiming Xiong. Qafacteval: Improved qa-based factual consistency evaluation for summarization. *arXiv preprint arXiv:2112.08542*, 2021.
- [37] Sheng Liu, Haotian Ye, and James Zou. Reducing hallucinations in large vision-language models via latent space steering. In *The Thirteenth International Conference on Learning Representations*, 2025.
- [38] Zhiheng Xi, Wenxiang Chen, Xin Guo, Wei He, Yiwei Ding, Boyang Hong, Ming Zhang, Junzhe Wang, Senjie Jin, Enyu Zhou, et al. The rise and potential of large language model based agents: A survey. *Science China Information Sciences*, 68(2):121101, 2025.
- [39] Karl Johan Åström. Optimal control of markov processes with incomplete state information i. *Journal of mathematical analysis and applications*, 10:174–205, 1965.
- [40] Pengfei Cao, Tianyi Men, Wencan Liu, Jingwen Zhang, Xuzhao Li, Xixun Lin, Dianbo Sui, Yanan Cao, Kang Liu, and Jun Zhao. Large

- language models for planning: A comprehensive and systematic survey. *arXiv preprint arXiv:2505.19683*, 2025.
- [41] Gaole He, Gianluca Demartini, and Ujwal Gadiraju. Plan-then-execute: An empirical study of user trust and team performance when using llm agents as a daily assistant. In *Proceedings of the 2025 CHI Conference on Human Factors in Computing Systems*, pages 1–22, 2025.
- [42] Zhiwei He, Yiming Wang, Mark Gerstein, Rui Wang, Gongshen Liu, et al. Igniting language intelligence: The hitchhiker’s guide from chain-of-thought reasoning to language agents. *ACM Computing Surveys*, 57(8):1–39, 2025.
- [43] Ranjan Sapkota, Konstantinos I Roumeliotis, and Manoj Karkee. Ai agents vs. agentic ai: A conceptual taxonomy, applications and challenge. *arXiv preprint arXiv:2505.10468*, 2025.
- [44] Xuanming Zhang, Yuxuan Chen, Min-Hsuan Yeh, and Yixuan Li. Metamind: Modeling human social thoughts with metacognitive multi-agent systems. *arXiv preprint arXiv:2505.18943*, 2025.
- [45] Shen Zheng, Jie Huang, and Kevin Chen-Chuan Chang. Why does chatgpt fall short in providing truthful answers? *arXiv preprint arXiv:2304.10513*, 2023.
- [46] Sergey Linok, Tatiana Zemskova, Svetlana Ladanova, Roman Titkov, Dmitry Yudin, Maxim Monastyry, and Aleksei Valenkov. Beyond bare queries: Open-vocabulary object grounding with 3d scene graph. *arXiv preprint arXiv:2406.07113*, 2024.
- [47] Alisa Liu, Zhaofeng Wu, Julian Michael, Alane Suhr, Peter West, Alexander Koller, Swabha Swayamdipta, Noah Smith, and Yejin Choi. We’re afraid language models aren’t modeling ambiguity. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, 2023.
- [48] Aryan Keluskar, Amrita Bhattacharjee, and Huan Liu. Do llms understand ambiguity in text? a case study in open-world question answering. In *2024 IEEE International Conference on Big Data (BigData)*, pages 7485–7490. IEEE, 2024.
- [49] Kasia Kobalczyk, Nicolás Astorga, Tennison Liu, and Mihaela van der Schaar. Active task disambiguation with LLMs. In *The Thirteenth International Conference on Learning Representations*, 2025.
- [50] Maximillian Chen, Ruoxi Sun, Tomas Pfister, and Sercan O Arik. Learning to clarify: Multi-turn conversations with action-based contrastive self-training. In *The Thirteenth International Conference on Learning Representations*, 2025.
- [51] Abhigya Verma, Sriram Puttagunta, Seganrasan Subramanian, and Sravan Ramachandran. Graft: Graph and table reasoning for textual alignment—a benchmark for structured instruction following and visual reasoning. *arXiv preprint arXiv:2508.15690*, 2025.
- [52] Weixin Xu and Ziliang Wang. Scernet: Spatial-channel regulation network for medical ultrasound image segmentation. *arXiv preprint arXiv:2508.13899*, 2025.
- [53] Mahyar Abbasian, Iman Azimi, Amir M Rahmani, and Ramesh Jain. Conversational health agents: A personalized llm-powered agent framework. *arXiv preprint arXiv:2310.02374*, 2023.
- [54] Qidong Huang, Xiaoyi Dong, Pan Zhang, Bin Wang, Conghui He, Jiaqi Wang, Dahua Lin, Weiming Zhang, and Nenghai Yu. Opera: Alleviating hallucination in multi-modal large language models via over-trust penalty and retrospection-allocation. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pages 13418–13427, 2024.
- [55] Jie JW Wu, Manav Chaudhary, Davit Abrahamyan, Arhaan Khaku, Anjiang Wei, and Fatemeh H Fard. Clarifycoder: Clarification-aware fine-tuning for programmatic problem solving. *arXiv preprint arXiv:2504.16331*, 2025.
- [56] Chenyu Shi, Xiao Wang, Qining Ge, Songyang Gao, Xianjun Yang, Tao Gui, Qi Zhang, Xuanjing Huang, Xun Zhao, and Dahua Lin. Navigating the overkill in large language models. *arXiv preprint arXiv:2401.17633*, 2024.
- [57] Zirui Zhao, Wee Sun Lee, and David Hsu. Large language models as commonsense knowledge for large-scale task planning. *Advances in Neural Information Processing Systems*, 36:31967–31987, 2023.
- [58] Zheng Chu, Jingchang Chen, Qianglong Chen, Haotian Wang, Kun Zhu, Xiyuan Du, Weijiang Yu, Ming Liu, and Bing Qin. Beamaggr: Beam aggregation reasoning over multi-source knowledge for multi-hop question answering. *arXiv preprint arXiv:2406.19820*, 2024.
- [59] Yuqi Zhu, Shuofei Qiao, Yixin Ou, Shumin Deng, Shiwei Lyu, Yue Shen, Lei Liang, Jinjie Gu, Huajun Chen, and Ningyu Zhang. Knowagent: Knowledge-augmented planning for llm-based agents. *arXiv preprint arXiv:2403.03101*, 2024.
- [60] Wenqiang Lai, Tianwei Zhang, Tin Lun Lam, and Yuan Gao. Vision-language model-based physical reasoning for robot liquid perception. In *2024 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 9652–9659. IEEE, 2024.
- [61] Ziyue Wang, Junde Wu, Chang Han Low, and Yueming Jin. Medagent-pro: Towards evidence-based multi-modal medical diagnosis via reasoning agent workflow. 2025.
- [62] Alexis R Tudor, Joaquín Arias, and Gopal Gupta. Vecsr: Virtually embodied common sense reasoning system. *arXiv preprint arXiv:2505.02144*, 2025.
- [63] Zixiao Zhao, Jing Sun, Zhe Hou, Zhiyuan Wei, Cheng-Hao Cai, Miao Qiao, and Jin Song Dong. Mactg: Multi-agent collaborative thought graph for automatic programming, 2025.
- [64] Guangya Wan, Yuqi Wu, Jie Chen, and Sheng Li. Cot rerailer: Enhancing the reliability of large language models in complex reasoning tasks through error detection and correction. *arXiv preprint arXiv:2408.13940*, 2024.
- [65] Jiachun Li, Pengfei Cao, Chenhao Wang, Zhuoran Jin, Yubo Chen, Daojian Zeng, Kang Liu, and Jun Zhao. Focus on your question! interpreting and mitigating toxic cot problems in commonsense reasoning. *arXiv preprint arXiv:2402.18344*, 2024.
- [66] Yaoxiang Wang, Zhiyong Wu, Junfeng Yao, and Jinsong Su. Tdag: A multi-agent framework based on dynamic task decomposition and agent generation. *Neural Networks*, page 107200, 2025.
- [67] Rennai Qiu, Chen Qian, Ran Li, Yufan Dang, Weize Chen, Cheng Yang, Yingli Zhang, Ye Tian, Xuantang Xiong, Lei Han, et al. Co-saving: Resource aware multi-agent collaboration for software development. *arXiv preprint arXiv:2505.21898*, 2025.
- [68] Maryam Berijanian, Kuldeep Singh, and Amin Sehati. Comparative analysis of ai agent architectures for entity relationship classification. *arXiv preprint arXiv:2506.02426*, 2025.
- [69] Xiao Yu, Baolin Peng, Ruize Xu, Michel Galley, Hao Cheng, Suman Nath, Jianfeng Gao, and Zhou Yu. Dyna-think: Synergizing reasoning, acting, and world model simulation in ai agents. *arXiv preprint arXiv:2506.00320*, 2025.
- [70] Weizhi Wang, Hong Wang, and Xifeng Yan. Steps: A benchmark for order reasoning in sequential tasks. *arXiv preprint arXiv:2306.04441*, 2023.
- [71] Kun Chu, Xufeng Zhao, Cornelius Weber, and Stefan Wermter. Llm+map: Bimanual robot task planning using large language models and planning domain definition language. *arXiv preprint arXiv:2503.17309*, 2025.
- [72] Xiang Huang, Jiayu Shen, Shanshan Huang, Sitao Cheng, Xiaxia Wang, and Yuzhong Qu. Targa: Targeted synthetic data generation for practical reasoning over structured data. *arXiv preprint arXiv:2412.19544*, 2024.
- [73] Kaiwen Zuo, Yirui Jiang, Fan Mo, and Pietro Lio. Kg4diagnosis: A hierarchical multi-agent llm framework with knowledge graph enhancement for medical diagnosis. In *AAAI Bridge Program on AI for Medicine and Healthcare*, pages 195–204. PMLR, 2025.
- [74] Potsawee Manakul, Adian Liusie, and Mark JF Gales. Selfcheckpt: Zero-resource black-box hallucination detection for generative large language models. *arXiv preprint arXiv:2303.08896*, 2023.
- [75] Xiaou Liu, Tiejin Chen, Longchao Da, Chacha Chen, Zhen Lin, and Hua Wei. Uncertainty quantification and confidence calibration in large language models: A survey. *arXiv preprint arXiv:2503.15850*, 2025.
- [76] Iman Mirzadeh, Keivan Alizadeh, Hooman Shahrokhi, Oncel Tuzel, Samy Bengio, and Mehrdad Farajtabar. Gsm-symbolic: Understanding the limitations of mathematical reasoning in large language models. *arXiv preprint arXiv:2410.05229*, 2024.
- [77] MingShan Liu, Shi Bo, and Jialing Fang. Enhancing mathematical reasoning in large language models with self-consistency-based hallucination detection. *arXiv preprint arXiv:2504.09440*, 2025.
- [78] Jingtian Wu and Claire Cardie. Reasoning court: Combining reasoning, action, and judgment for multi-hop reasoning. *arXiv preprint arXiv:2504.09781*, 2025.
- [79] Wei Xu, Gang Luo, Weiyu Meng, Xiaobing Zhai, Keli Zheng, Ji Wu, Yanrong Li, Abao Xing, Junrong Li, Zhifan Li, et al. Mragent: an llm-based automated agent for causal knowledge discovery in disease via mendelian randomization. *Briefings in Bioinformatics*, 26(2):bbaf140, 2025.
- [80] Nikolas Belle, Dakota Barnes, Alfonso Amayuelas, Ivan Bercovich, Xin Eric Wang, and William Wang. Agents of change: Self-evolving llm agents for strategic planning. *arXiv preprint arXiv:2506.04651*, 2025.
- [81] Tian Liang, Zhiwei He, Wenxiang Jiao, Xing Wang, Yan Wang, Rui Wang, Yujiu Yang, Shuming Shi, and Zhaopeng Tu. Encouraging divergent thinking in large language models through multi-agent debate. *arXiv preprint arXiv:2305.19118*, 2023.

- [82] Wenqi Zhang, Yongliang Shen, Linjuan Wu, Qiuying Peng, Jun Wang, Yuetong Zhuang, and Weiming Lu. Self-contrast: Better reflection through inconsistent solving perspectives. *arXiv preprint arXiv:2401.02009*, 2024.
- [83] Yanhong Li, Chenghao Yang, and Allyson Ettinger. When hindsight is not 20/20: Testing limits on reflective thinking in large language models. *arXiv preprint arXiv:2404.09129*, 2024.
- [84] Dongsheng Zhu, Weixian Shi, Zhengliang Shi, Zhaochun Ren, Shuaiqiang Wang, Lingyong Yan, and Dawei Yin. Divide-and-aggregate: An efficient tool learning method via parallel tool invocation. *arXiv preprint arXiv:2501.12432*, 2025.
- [85] Shishir G Patil, Tianjun Zhang, Xin Wang, and Joseph E Gonzalez. Gorilla: Large language model connected with massive apis. *Advances in Neural Information Processing Systems*, 37:126544–126565, 2024.
- [86] Yujia Qin, Shihao Liang, Yining Ye, Kunlun Zhu, Lan Yan, Yaxi Lu, Yankai Lin, Xin Cong, Xiangru Tang, Bill Qian, et al. Toolilm: Facilitating large language models to master 16000+ real-world apis. *arXiv preprint arXiv:2307.16789*, 2023.
- [87] Cheng-Yu Hsieh, Si-An Chen, Chun-Liang Li, Yasuhisa Fujii, Alexander Ratner, Chen-Yu Lee, Ranjay Krishna, and Tomas Pfister. Tool documentation enables zero-shot tool-usage with large language models. *CoRR*, abs/2308.00675, 2023.
- [88] Siyu Yuan, Kaitao Song, Jiangjie Chen, Xu Tan, Yongliang Shen, Kan Ren, Dongsheng Li, and Deqing Yang. EASYTOOL: enhancing llm-based agents with concise tool instruction. *CoRR*, abs/2401.06201, 2024.
- [89] Changle Qu, Sunhao Dai, Xiaochi Wei, Hengyi Cai, Shuaiqiang Wang, Dawei Yin, Jun Xu, and Ji-Rong Wen. From exploration to mastery: Enabling LLMs to master tools via self-driven interactions. In *The Thirteenth International Conference on Learning Representations*, 2025.
- [90] Ivan Milev, Mislav Balunovic, Maximilian Baader, and Martin T. Vechev. Toolfuzz - automated agent tool testing. *CoRR*, abs/2503.04479, 2025.
- [91] Xinyi Ni, Qiyang Wang, Yukun Zhang, and Pengyu Hong. Toolfactory: Automating tool generation by leveraging LLM to understand REST API documentations. *CoRR*, abs/2501.16945, 2025.
- [92] Zhengliang Shi, Shen Gao, Lingyong Yan, Yue Feng, Xiuyi Chen, Zhumin Chen, Dawei Yin, Suzan Verberne, and Zhaochun Ren. Tool learning in the wild: Empowering language models as automatic tool agents. In *Proceedings of the ACM on Web Conference 2025*, pages 2222–2237. ACM, 2025.
- [93] Pan Lu, Bowen Chen, Sheng Liu, Rahul Thapa, Joseph Boen, and James Zou. Octotools: An agentic framework with extensible tools for complex reasoning. *CoRR*, abs/2502.11271, 2025.
- [94] Shen Gao, Zhengliang Shi, Minghang Zhu, Bowen Fang, Xin Xin, Pengjie Ren, Zhumin Chen, Jun Ma, and Zhaochun Ren. Confucius: Iterative tool learning from introspection feedback by easy-to-difficult curriculum. In *Thirty-Eighth AAAI Conference on Artificial Intelligence*, 2024.
- [95] Ibrahim Abdelaziz, Kinjal Basu, Mayank Agarwal, Sadhana Kumaravel, Matthew Stallone, Rameswar Panda, Yara Rizk, G. P. Shrivatsa Bhargav, Maxwell Crouse, Chulaka Gunasekara, Shajith Ikbal, Sachindra Joshi, Hima Karanam, Vineet Kumar, Asim Munawar, Sumit Neelam, Dinesh Raghu, Udit Sharma, Adriana Meza Soria, Dheeraj Sreedhar, Praveen Venkateswaran, Merve Unuvar, David Cox, Salim Roukos, Luis A. Lastras, and Pavan Kapanipathi. Granite-function calling model: Introducing function calling abilities via multi-task learning of granular tasks. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, 2024.
- [96] Boshi Wang, Hao Fang, Jason Eisner, Benjamin Van Durme, and Yu Su. Llms in the imaginarium: Tool learning through simulated trial and error. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics*, pages 10583–10604, 2024.
- [97] Shishir G. Patil, Tianjun Zhang, Xin Wang, and Joseph E. Gonzalez. Gorilla: Large language model connected with massive apis. In *Advances in Neural Information Processing Systems 38: Annual Conference*, 2024.
- [98] Yujia Qin, Shihao Liang, Yining Ye, Kunlun Zhu, Lan Yan, Yaxi Lu, Yankai Lin, Xin Cong, Xiangru Tang, Bill Qian, Sihan Zhao, Lauren Hong, Runchu Tian, Ruobing Xie, Jie Zhou, Mark Gerstein, Dahai Li, Zhiyuan Liu, and Maosong Sun. Toolilm: Facilitating large language models to master 16000+ real-world apis. In *The Twelfth International Conference on Learning Representations*, 2024.
- [99] Guoxin Chen, Zhong Zhang, Xin Cong, Fangda Guo, Yesai Wu, Yankai Lin, Wenzheng Feng, and Yasheng Wang. Learning evolving tools for large language models. *CoRR*, abs/2410.06617, 2024.
- [100] Elias Lumer, Anmol Gulati, Vamse Kumar Subbiah, Pradeep Honaganahalli Basavaraju, and James A Burke. Scalemcpc: Dynamic and auto-synchronizing model context protocol tools for llm agents. *arXiv preprint arXiv:2505.06416*, 2025.
- [101] R Patrick Xian, Qiming Cui, Stefan Bauer, and Reza Abbasi-Asl. Measuring temporal effects of agent knowledge by date-controlled tool use. *arXiv preprint arXiv:2503.04188*, 2025.
- [102] Hongshen Xu, Su Zhu, Zihan Wang, Hang Zheng, Da Ma, Ruisheng Cao, Shuai Fan, Lu Chen, and Kai Yu. Reducing tool hallucination via reliability alignment. *CoRR*, 2024.
- [103] Wenxuan Wang, Juluan Shi, Chaozheng Wang, Cheryl Lee, Youliang Yuan, Jen-tse Huang, and Michael R Lyu. Learning to ask: When llms meet unclear instruction. *arXiv preprint arXiv:2409.00557*, 2024.
- [104] Amit Ranjan Trivedi, Sina Tayebati, Hemant Kumawat, Nastaran Darabi, Divake Kumar, Adarsh Kumar Kosta, Yeshwanth Venkatesha, Diniti Jayasuriya, Nethmi Jayasinghe, Priyadarshini Panda, et al. Intelligent sensing-to-action for robust autonomy at the edge: Opportunities and challenges. *arXiv preprint arXiv:2502.02692*, 2025.
- [105] Qifan Yu, Juncheng Li, Longhui Wei, Liang Pang, Wentao Ye, Bosheng Qin, Siliang Tang, Qi Tian, and Yuetong Zhuang. Hallucidocor: Mitigating hallucinatory toxicity in visual instruction data. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pages 12944–12953, 2024.
- [106] Jiahui Chen, Jianwei Yang, Haiping Wu, Dianqi Li, Jianfeng Gao, Tianyi Zhou, and Bin Xiao. Florence-vl: Enhancing vision-language models with generative vision encoder and depth-breadth fusion. *arXiv preprint arXiv:2412.04424*, 2024.
- [107] Ziyu Liu, Zeyi Sun, Yuhang Zang, Xiaoyi Dong, Yuhang Cao, Haodong Duan, Dahu Lin, and Jiaqi Wang. Visual-rft: Visual reinforcement fine-tuning. *arXiv preprint arXiv:2503.01785*, 2025.
- [108] Sara Ghazanfari, Alexandre Araujo, Prashanth Krishnamurthy, Siddharth Garg, and Farshad Khorrami. Emma: Efficient visual alignment in multi-modal llms. *arXiv preprint arXiv:2410.02080*, 2024.
- [109] Xin Lai, Zhuotao Tian, Yukang Chen, Yanwei Li, Yuhui Yuan, Shu Liu, and Jiaya Jia. Lisa: Reasoning segmentation via large language model. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pages 9579–9589, 2024.
- [110] Bin Wang, Fan Wu, Xiao Han, Jiahui Peng, Huaping Zhong, Pan Zhang, Xiaoyi Dong, Weijia Li, Wei Li, Jiaqi Wang, et al. Vige: Visual instruction generation and correction. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pages 5309–5317, 2024.
- [111] Zidi Xiong, Yuping Lin, Wenya Xie, Pengfei He, Jiliang Tang, Himabindu Lakkaraju, and Zhen Xiang. How memory management impacts llm agents: An empirical study of experience-following behavior, 2025.
- [112] Charles Packer, Vivian Fang, Shishir_G Patil, Kevin Lin, Sarah Wooders, and Joseph_E Gonzalez. Memgpt: Towards llms as operating systems, 2023.
- [113] Ziheng Huang, Sebastian Gutierrez, Hemanth Kamana, and Stephen MacNeil. Memory sandbox: Transparent and interactive memory management for conversational agents. In *Adjunct Proceedings of the 36th Annual ACM Symposium on User Interface Software and Technology*, pages 1–3, 2023.
- [114] Johnny Li, Saksham Consul, Eda Zhou, James Wong, Naila Farooqui, Yuxin Ye, Nithyashree Manohar, Zhuxiaona Wei, Tian Wu, Ben Echols, et al. Banishing llm hallucinations requires rethinking generalization. *arXiv preprint arXiv:2406.17642*, 2024.
- [115] Aditi Singh, Abul Ehtesham, Saket Kumar, and Tala Talaei Khoei. Agentic retrieval-augmented generation: A survey on agentic rag. *arXiv preprint arXiv:2501.09136*, 2025.
- [116] Karan Singhal, Tao Tu, Juraj Gottweis, Rory Sayres, Ellery Wulczyn, Mohamed Amin, Le Hou, Kevin Clark, Stephen R Pfahl, Heather Cole-Lewis, et al. Toward expert-level medical question answering with large language models. *Nature Medicine*, pages 1–8, 2025.
- [117] Yiteng Tu, Weihang Su, Yujia Zhou, Yiqun Liu, and Qingyao Ai. Rbft: Robust fine-tuning for retrieval-augmented generation against retrieval defects. *arXiv preprint arXiv:2501.18365*, 2025.
- [118] Garima Agrawal, Tharindu Kumarage, Zeyad Alghamdi, and Huanmin Liu. Mindful-rag: A study of points of failure in retrieval augmented generation. *2024 2nd International Conference on Foundation and Large Language Models (FLLM)*, pages 607–611, 2024.
- [119] Xiaoxin He, Yijun Tian, Yifei Sun, Nitesh Chawla, Thomas Laurent, Yann LeCun, Xavier Bresson, and Bryan Hooi. G-retriever: Retrieval-augmented generation for textual graph understanding and question answering. *Advances in Neural Information Processing Systems*, 37:132876–132907, 2024.

- [120] Ali Modarressi, Ayyoob Imani, Mohsen Fayyaz, and Hinrich Schütze. Ret-llm: Towards a general read-write memory for large language models. *ArXiv*, abs/2305.14322, 2023.
- [121] Wan Zhang and Jing Zhang. Hallucination mitigation for retrieval-augmented large language models: a review. *Mathematics*, 13(5):856, 2025.
- [122] Chanwoong Yoon, Gangwoo Kim, Byeongguk Jeon, Sungdong Kim, Yohan Jo, and Jaewoo Kang. Ask optimal questions: Aligning large language models with retriever's preference in conversation. In *Findings of the Association for Computational Linguistics: NAACL 2025*, pages 5899–5921, 2025.
- [123] Lingrui Mei, Jiayu Yao, Yuyao Ge, Yiwei Wang, Baolong Bi, Yujun Cai, Jiazhui Liu, Mingyu Li, Zhong-Zhi Li, Duzhen Zhang, et al. A survey of context engineering for large language models. *arXiv preprint arXiv:2507.13334*, 2025.
- [124] Zhuoran Jin, Pengfei Cao, Yubo Chen, Kang Liu, Xiaojian Jiang, Jiejin Xu, Qiuxia Li, and Jun Zhao. Tug-of-war between knowledge: Exploring and resolving knowledge conflicts in retrieval-augmented language models. *arXiv preprint arXiv:2402.14409*, 2024.
- [125] Hanxing Ding, Liang Pang, Zihao Wei, Huawei Shen, and Xueqi Cheng. Retrieve only when it needs: Adaptive retrieval augmentation for hallucination mitigation in large language models. *arXiv preprint arXiv:2402.10612*, 2024.
- [126] Jiatai Wang, Zhiwei Xu, Di Jin, Xuewen Yang, and Tao Li. Accommodate knowledge conflicts in retrieval-augmented llms: Towards reliable response generation in the wild. *arXiv preprint arXiv:2504.12982*, 2025.
- [127] Kevin Wu, Eric Wu, and James Zou. How faithful are rag models? quantifying the tug-of-war between rag and llms' internal prior. *arXiv e-prints*, pages arXiv–2404, 2024.
- [128] Rongwu Xu, Zehan Qi, Zhijiang Guo, Cunxiang Wang, Hongru Wang, Yue Zhang, and Wei Xu. Knowledge conflicts for llms: A survey. *arXiv preprint arXiv:2403.08319*, 2024.
- [129] Wujiang Xu, Zujie Liang, Kai Mei, Hang Gao, Juntao Tan, and Yongfeng Zhang. A-mem: Agentic memory for llm agents. *arXiv preprint arXiv:2502.12110*, 2025.
- [130] Qitao Qin, Yucong Luo, Yihang Lu, Zhibo Chu, and Xianwei Meng. Towards adaptive memory-based optimization for enhanced retrieval-augmented generation. *arXiv preprint arXiv:2504.05312*, 2025.
- [131] Qingyue Wang, Yanhe Fu, Yanan Cao, Shuai Wang, Zhiliang Tian, and Liang Ding. Recursively summarizing enables long-term dialogue memory in large language models. *Neurocomputing*, 639:130193, 2025.
- [132] Jinyao Guo, Chengpeng Wang, Xiangzhe Xu, Zian Su, and Xiangyu Zhang. Repoaduit: An autonomous llm-agent for repository-level code auditing. *ArXiv*, abs/2501.18160, 2025.
- [133] Ye Ye. Task memory engine (tme): Enhancing state awareness for multi-step llm agent tasks. *arXiv preprint arXiv:2504.08525*, 2025.
- [134] Yu Wang and Xi Chen. Mirix: Multi-agent memory system for llm-based agents. *arXiv preprint arXiv:2507.07957*, 2025.
- [135] Zeyu Zhang, Xiaohe Bo, Chen Ma, Rui Li, Xu Chen, Quanyu Dai, Jieming Zhu, Zhenhua Dong, and Ji-Rong Wen. A survey on the memory mechanism of large language model based agents, 2024.
- [136] Khanh-Tung Tran, Dung Dao, Minh-Duong Nguyen, Quoc-Viet Pham, Barry O'Sullivan, and Hoang D Nguyen. Multi-agent collaboration mechanisms: A survey of llms. *arXiv preprint arXiv:2501.06322*, 2025.
- [137] Bingyu Yan, Xiaoming Zhang, Litian Zhang, Lian Zhang, Ziyi Zhou, Dezhuang Miao, and Chaozhuo Li. Beyond self-talk: A communication-centric survey of llm-based multi-agent systems. *arXiv preprint arXiv:2502.14321*, 2025.
- [138] Giorgio Piatti, Zhijing Jin, Max Kleiman-Weiner, Bernhard Schölkopf, Mrinmaya Sachan, and Rada Mihalcea. Cooperate or collapse: Emergence of sustainable cooperation in a society of llm agents. *Advances in Neural Information Processing Systems*, 37:111715–111759, 2024.
- [139] Yuheng Cheng, Ceyao Zhang, Zhengwen Zhang, Xiangrui Meng, Sirui Hong, Wenhao Li, Zihao Wang, Zekai Wang, Feng Yin, Junhua Zhao, et al. Exploring large language model based intelligent agents: Definitions, methods, and prospects. *arXiv preprint arXiv:2401.03428*, 2024.
- [140] Luke Yoffe, Alfonso Amayuelas, and William Yang Wang. Debunc: mitigating hallucinations in large language model agent communication with uncertainty estimations. *arXiv preprint arXiv:2407.06426*, 2024.
- [141] Mert Cemri, Melissa Z Pan, Shuyi Yang, Lakshya A Agrawal, Bhavya Chopra, Rishabh Tiwari, Kurt Keutzer, Aditya Parameswaran, Dan Klein, Kannan Ramchandran, et al. Why do multi-agent llm systems fail? *arXiv preprint arXiv:2503.13657*, 2025.
- [142] Shaokun Zhang, Ming Yin, Jieyu Zhang, Jiale Liu, Zhiguang Han, Jingyang Zhang, Beibin Li, Chi Wang, Huazheng Wang, Yiran Chen, et al. Which agent causes task failures and when? on automated failure attribution of llm multi-agent systems. *arXiv preprint arXiv:2505.00212*, 2025.
- [143] Guibin Zhang, Yanwei Yue, Zhixun Li, Sukwon Yun, Guancheng Wan, Kun Wang, Dawei Cheng, Jeffrey Xu Yu, and Tianlong Chen. Cut the crap: An economical communication pipeline for LLM-based multi-agent systems. In *The Thirteenth International Conference on Learning Representations*, 2025.
- [144] Zhexuan Wang, Yutong Wang, Xuebo Liu, Liang Ding, Miao Zhang, Jie Liu, and Min Zhang. Agentdropout: Dynamic agent elimination for token-efficient and high-performance llm-based multi-agent collaboration. *arXiv preprint arXiv:2503.18891*, 2025.
- [145] Wei Liu, Chenxi Wang, YiFei Wang, Zihao Xie, Rennai Qiu, Yufan Dang, Zhuoyun Du, Weize Chen, Cheng Yang, and Chen Qian. Autonomous agents for collaborative task under information asymmetry. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*, 2024.
- [146] Haotian Wang, Xiyuan Du, Weijiang Yu, Qianglong Chen, Kun Zhu, Zheng Chu, Lian Yan, and Yi Guan. Learning to break: Knowledge-enhanced reasoning in multi-agent debate system. *Neurocomputing*, 618:129063, 2025.
- [147] Abul Ehtesham, Aditi Singh, Gaurav Kumar Gupta, and Saket Kumar. A survey of agent interoperability protocols: Model context protocol (mcp), agent communication protocol (acp), agent-to-agent protocol (a2a), and agent network protocol (anp). *arXiv preprint arXiv:2505.02279*, 2025.
- [148] Yingxuan Yang, Huacan Chai, Yuanyi Song, Siyuan Qi, Muning Wen, Ning Li, Junwei Liao, Haoyi Hu, Jianghao Lin, Gaowei Chang, et al. A survey of ai agent protocols. *arXiv preprint arXiv:2504.16736*, 2025.
- [149] In Gim, Seung-seob Lee, and Lin Zhong. Asynchronous llm function calling. *arXiv preprint arXiv:2412.07017*, 2024.
- [150] Gonzalo Gonzalez-Pumariega, Leong Su Yean, Neha Sunkara, and Sanjiban Choudhury. Robotouille: An asynchronous planning benchmark for LLM agents. In *The Thirteenth International Conference on Learning Representations*, 2025.
- [151] Gagan Bansal, Jennifer Wortman Vaughan, Saleema Amershi, Eric Horvitz, Adam Fournier, Hussein Mozannar, Victor Dibia, and Daniel S Weld. Challenges in human-agent communication. *arXiv preprint arXiv:2412.10380*, 2024.
- [152] Yingxuan Yang, Qiuying Peng, Jun Wang, and Weinan Zhang. Multi-lm-agent systems: Techniques and business perspectives. *arXiv preprint arXiv:2411.14033*, 2024.
- [153] Zhao Wang, Sota Moriyama, Wei-Yao Wang, Britti Gangopadhyay, and Shingo Takamatsu. Talk structurally, act hierarchically: A collaborative framework for llm multi-agent systems. *arXiv preprint arXiv:2502.11098*, 2025.
- [154] Zijun Liu, Yanzhe Zhang, Peng Li, Yang Liu, and Diyi Yang. A dynamic LLM-powered agent network for task-oriented agent collaboration. In *First Conference on Language Modeling*, 2024.
- [155] Dae Cheol Kwon and Xinyu Zhang. Cp-agentnet: Autonomous and explainable communication protocol design using generative agents. *arXiv preprint arXiv:2503.17850*, 2025.
- [156] Weize Chen, Yusheng Su, Jingwei Zuo, Cheng Yang, Chenfei Yuan, Chi-Min Chan, Heyang Yu, Yaxi Lu, Yi-Hsin Hung, Chen Qian, Yujia Qin, Xin Cong, Ruobing Xie, Zhiyuan Liu, Maosong Sun, and Jie Zhou. Agentverse: Facilitating multi-agent collaboration and exploring emergent behaviors. In *The Twelfth International Conference on Learning Representations*, 2024.
- [157] Mingchen Zhuge, Wenyi Wang, Louis Kirsch, Francesco Faccio, Dmitrii Khizbulin, and Jürgen Schmidhuber. GPTSwarm: Language agents as optimizable graphs. In *Forty-first International Conference on Machine Learning*, 2024.
- [158] Shoucheng Song, Youfang Lin, Sheng Han, Chang Yao, Hao Wu, Shuo Wang, and Kai Lv. Code: Communication delay-tolerant multi-agent collaboration via dual alignment of intent and timeliness. *arXiv preprint arXiv:2501.05207*, 2025.
- [159] RM Aratchige and WMKS Ilmini. Llms working in harmony: A survey on the technological aspects of building effective llm-based multi agent systems. *arXiv preprint arXiv:2504.01963*, 2025.
- [160] Kaiqu Liang, Zixu Zhang, and Jaime F Fisac. Introspective planning: Aligning robots' uncertainty with inherent task ambiguity. *Advances in Neural Information Processing Systems*, 37:71998–72031, 2024.
- [161] Kelin Fu and Kaigui Bian. Knowmap: Efficient knowledge-driven task adaptation for llms. *arXiv preprint arXiv:2506.19527*, 2025.
- [162] Siyu Yuan, Kaitao Song, Jiangjie Chen, Xu Tan, Yongliang Shen, Ren Kan, Dongsheng Li, and Deqing Yang. Easytool: Enhancing llm-based

- agents with concise tool instruction. *arXiv preprint arXiv:2401.06201*, 2024.
- [163] Cheng-Yu Hsieh, Si-An Chen, Chun-Liang Li, Yasuhisa Fujii, Alexander Ratner, Chen-Yu Lee, Ranjay Krishna, and Tomas Pfister. Tool documentation enables zero-shot tool-usage with large language models. *arXiv preprint arXiv:2308.00675*, 2023.
- [164] Ibrahim Abdelaziz, Kinjal Basu, Mayank Agarwal, Sadhana Kumaravel, Matthew Stallone, Rameswar Panda, Yara Rizk, GP Shrivatsa Bhargav, Maxwell Crouse, Chulaka Gunasekara, et al. Granite-function calling model: Introducing function calling abilities via multi-task learning of granular tasks. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing: Industry Track*, pages 1131–1139, 2024.
- [165] Yuhao Dong, Zuyan Liu, Hai-Long Sun, Jingkang Yang, Winston Hu, Yongming Rao, and Ziwei Liu. Insight-v: Exploring long-chain visual reasoning with multimodal large language models. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pages 9062–9072, 2025.
- [166] Kun Huang, Weikai Xu, Yuxuan Liu, Quandong Wang, Pengzhi Gao, Wei Liu, Jian Luan, Bin Wang, and Bo An. Enhance mobile agents thinking process via iterative preference learning. *arXiv preprint arXiv:2505.12299*, 2025.
- [167] Xiaoxiao Long, Qingrui Zhao, Kaiwen Zhang, Zihao Zhang, Dingrui Wang, Yumeng Liu, Zhengjie Shu, Yi Lu, Shouzheng Wang, Xinzhe Wei, et al. A survey: Learning embodied intelligence from physical simulators and world models. *arXiv preprint arXiv:2507.00917*, 2025.
- [168] Jonathan Richens, David Abel, Alexis Bellot, and Tom Everitt. General agents need world models. *arXiv preprint arXiv:2506.01622*, 2025.
- [169] Zhiting Hu and Tianmin Shu. Language models, agent models, and world models: The law for machine reasoning and planning. *arXiv preprint arXiv:2312.05230*, 2023.
- [170] Hongxin Zhang, Zeyuan Wang, Qiushi Lyu, Zheyuan Zhang, Sunli Chen, Tianmin Shu, Behzad Dariush, Kwonjoon Lee, Yilun Du, and Chuang Gan. Combo: compositional world models for embodied multi-agent cooperation. *arXiv preprint arXiv:2404.10775*, 2024.
- [171] Zhihua Duan and Jialin Wang. Enhancing multi-agent consensus through third-party Ilm integration: Analyzing uncertainty and mitigating hallucinations in large language models. *arXiv preprint arXiv:2411.16189*, 2024.
- [172] Hyungjoo Chae, Namyoung Kim, Kai Tzu-iunn Ong, Minju Gwak, Gwanwoo Song, Jihoon Kim, Sunghwan Kim, Dongha Lee, and Jinyoung Yeo. Web agents with world models: Learning and leveraging environment dynamics in web navigation. *arXiv preprint arXiv:2410.13232*, 2024.
- [173] Xuan Yao, Junyu Gao, and Changsheng Xu. Navmorph: A self-evolving world model for vision-and-language navigation in continuous environments. *arXiv preprint arXiv:2506.23468*, 2025.
- [174] Shuofei Qiao, Runnan Fang, Ningyu Zhang, Yuqi Zhu, Xiang Chen, Shumin Deng, Yong Jiang, Pengjun Xie, Fei Huang, and Huajun Chen. Agent planning with world knowledge model. *Advances in Neural Information Processing Systems*, 37:114843–114871, 2024.
- [175] Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, et al. Chain-of-thought prompting elicits reasoning in large language models. *Advances in neural information processing systems*, 35:24824–24837, 2022.
- [176] Kumar Manas, Stefan Zwicklauer, and Adrian Paschke. Cot-tl: Low-resource temporal knowledge representation of planning instructions using chain-of-thought reasoning. In *2024 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 9636–9643. IEEE, 2024.
- [177] Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc Le, Ed Chi, Sharan Narang, Aakanksha Chowdhery, and Denny Zhou. Self-consistency improves chain of thought reasoning in language models. *arXiv preprint arXiv:2203.11171*, 2022.
- [178] Ishika Singh, Valts Blukis, Arsalan Mousavian, Ankit Goyal, Danfei Xu, Jonathan Tremblay, Dieter Fox, Jesse Thomason, and Animesh Garg. Progprompt: Generating situated robot task plans using large language models. In *2023 IEEE International Conference on Robotics and Automation (ICRA)*, pages 11523–11530. IEEE, 2023.
- [179] Nikolai Goncharov and Donald Dansereau. Segment anything in light fields for real-time applications via constrained prompting. In *Proceedings of the Winter Conference on Applications of Computer Vision*, pages 1490–1496, 2025.
- [180] Shangfeng Chen, Xiayang Shi, Pu Li, Yinlin Li, and Jingjing Liu. Refining translations with llms: A constraint-aware iterative prompting approach. *arXiv preprint arXiv:2411.08348*, 2024.
- [181] Jiarui Wu, Zhuo Liu, and Hangfeng He. Mitigating hallucinations in multimodal spatial relations through constraint-aware prompting. *arXiv preprint arXiv:2502.08317*, 2025.
- [182] Yunzhi Yao, Peng Wang, Bozhong Tian, Siyuan Cheng, Zhoubo Li, Shumin Deng, Huajun Chen, and Ningyu Zhang. Editing large language models: Problems, methods, and opportunities. In *The 2023 Conference on Empirical Methods in Natural Language Processing*.
- [183] Xiaopeng Li, Shasha Li, Shezheng Song, Jing Yang, Jun Ma, and Jie Yu. Pmet: Precise model editing in a transformer. *ArXiv*, abs/2308.08742, 2023.
- [184] Nicola De Cao, Wilker Aziz, and Ivan Titov. Editing factual knowledge in language models. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 6491–6506, 2021.
- [185] Nianwen Si, Hao Zhang, Heyu Chang, Wenlin Zhang, Dan Qu, and Weiqiang Zhang. Knowledge unlearning for llms: Tasks, methods, and challenges. *arXiv preprint arXiv:2311.15766*, 2023.
- [186] Guangzhi Sun, Potsawee Manakul, Xiao Zhan, and Mark Gales. Unlearning vs. obfuscation: Are we truly removing knowledge? *arXiv preprint arXiv:2505.02884*, 2025.
- [187] Jiaochen Chen and Difyi Yang. Unlearn what you want to forget: Efficient unlearning for llms. In *The 2023 Conference on Empirical Methods in Natural Language Processing*.
- [188] Gabriel Ilharco, Marco Túlio Ribeiro, Mitchell Wortsman, Ludwig Schmidt, Hannaneh Hajishirzi, and Ali Farhadi. Editing models with task arithmetic. In *The Eleventh International Conference on Learning Representations*.
- [189] Phuc H Le-Khac, Graham Healy, and Alan F Smeaton. Contrastive representation learning: A framework and review. *Ieee Access*, 8:193907–193934, 2020.
- [190] Jiangxia Cao, Xixun Lin, Shu Guo, Luchen Liu, Tingwen Liu, and Bin Wang. Bipartite graph embedding via mutual information maximization. In *Proceedings of the 14th ACM international conference on web search and data mining*, pages 635–643, 2021.
- [191] Xixun Lin, Rui Liu, Yanan Cao, Lixin Zou, Qian Li, Yongxuan Wu, Yang Liu, Dawei Yin, and Guandong Xu. Contrastive modality-disentangled learning for multimodal recommendation. *ACM Transactions on Information Systems*, 43(3):1–31, 2025.
- [192] Yew Ken Chia, GuiZhen Chen, Luu Anh Tuan, Soujanya Poria, and Lidong Bing. Contrastive chain-of-thought prompting. *arXiv preprint arXiv:2311.09277*, 2023.
- [193] Yinghui Li, Haojing Huang, Jiayi Kuang, Yangning Li, Shu-Yu Guo, Chao Qu, Xiaoyu Tan, Hai-Tao Zheng, Ying Shen, and Philip S Yu. Refine knowledge of large language models via adaptive contrastive learning. *arXiv preprint arXiv:2502.07184*, 2025.
- [194] Chaoya Jiang, Haiyang Xu, Mengfan Dong, Jiaxing Chen, Wei Ye, Ming Yan, Qinghao Ye, Ji Zhang, Fei Huang, and Shikun Zhang. Hallucination augmented contrastive learning for multimodal large language model. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pages 27036–27046, 2024.
- [195] Hourui Deng, Hongjie Zhang, Jie Ou, and Chaosheng Feng. Can Ilm be a good path planner based on prompt engineering? mitigating the hallucination for path planning. *arXiv preprint arXiv:2408.13184*, 2024.
- [196] Zhiheng Xi, Wenxiang Chen, Boyang Hong, Senjie Jin, Rui Zheng, Wei He, Yiwen Ding, Shichun Liu, Xin Guo, Junzhe Wang, et al. Training large language models for reasoning through reverse curriculum reinforcement learning. *arXiv preprint arXiv:2402.05808*, 2024.
- [197] Leslie Pack Kaelbling, Michael L Littman, and Andrew W Moore. Reinforcement learning: A survey. *Journal of artificial intelligence research*, 4:237–285, 1996.
- [198] Weimin Xiong, Yifan Song, Qingxiu Dong, Bingchan Zhao, Feifan Song, Xun Wang, and Sujian Li. Mpo: Boosting Ilm agents with meta plan optimization. *arXiv preprint arXiv:2503.02682*, 2025.
- [199] Maohao Shen, Guangtao Zeng, Zhenting Qi, Zhang-Wei Hong, Zhenfang Chen, Wei Lu, Gregory Wornell, Subhro Das, David Cox, and Chuang Gan. Satori: Reinforcement learning with chain-of-action-thought enhances Ilm reasoning via autoregressive search. *arXiv preprint arXiv:2502.02508*, 2025.
- [200] Qiancheng Xu, Yongqi Li, Heming Xia, and Wenjie Li. Enhancing tool retrieval with iterative feedback from large language models. In Yaser Al-Onaizan, Mohit Bansal, and Yun-Nung Chen, editors, *Findings of the Association for Computational Linguistics: EMNLP*, pages 9609–9619, 2024.
- [201] Assaf Ben-Kish, Moran Yanuka, Morris Alper, Raja Giryes, and Hadar Averbuch-Elor. Mocha: Multi-objective reinforcement mitigating caption hallucinations. *arXiv preprint arXiv:2312.03631*, 2, 2023.

- [202] Tianyu Yu, Yuan Yao, Haoye Zhang, Taiwen He, Yifeng Han, Ganqu Cui, Jinyi Hu, Zhiyuan Liu, Hai-Tao Zheng, Maosong Sun, et al. Rhfv: Towards trustworthy mllms via behavior alignment from fine-grained correctional human feedback. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pages 13807–13816, 2024.
- [203] Jiajie Zhang, Zhongni Hou, Xin Lv, Shulin Cao, Zhenyu Hou, Yilin Niu, Lei Hou, Yuxiao Dong, Ling Feng, and Juanzi Li. Longeward: Improving long-context large language models with ai feedback. *arXiv preprint arXiv:2410.21252*, 2024.
- [204] Judea Pearl. Causal inference in statistics: An overview. 2009.
- [205] Xixun Lin, Qing Yu, Yanan Cao, Lixin Zou, Chuan Zhou, Jia Wu, Chenliang Li, Peng Zhang, and Shirui Pan. Generative causality-driven network for graph multi-task learning. *IEEE transactions on pattern analysis and machine intelligence*, 2025.
- [206] Shawn Li, Jiahu Qu, Yuxiao Zhou, Yuehan Qin, Tiansai Yang, and Yue Zhao. Treble counterfactual vlm: A causal approach to hallucination. *arXiv preprint arXiv:2503.06169*, 2025.
- [207] Xinniao Hu, Chun Wang, Ruihe An, ChenYu Shao, Xiaojun Ye, Sheng Zhou, and Liangcheng Li. Causal-llava: Causal disentanglement for mitigating hallucination in multimodal large language models. *arXiv preprint arXiv:2505.19474*, 2025.
- [208] Kangsheng Wang, Xiao Zhang, Zizheng Guo, Tianyu Hu, and Huimin Ma. Csce: Boosting llm reasoning by simultaneous enhancing of causal significance and consistency. *arXiv preprint arXiv:2409.17174*, 2024.
- [209] Ziyi Tang, Ruilin Wang, Weixing Chen, Keze Wang, Yang Liu, Tian-shui Chen, and Liang Lin. Towards causalgpt: A multi-agent approach for faithful knowledge reasoning via promoting causal consistency in llms. *arXiv preprint arXiv:2308.11914*, 2023.
- [210] Feng Xia, Ke Sun, Shuo Yu, Abdul Aziz, Liangtian Wan, Shirui Pan, and Huan Liu. Graph learning: A survey. *IEEE Transactions on Artificial Intelligence*, 2(2):109–127, 2021.
- [211] Xixun Lin, Wenxiao Zhang, Fengzhao Shi, Chuan Zhou, Lixin Zou, Xiangyu Zhao, Dawei Yin, Shirui Pan, and Yanan Cao. Graph neural stochastic diffusion for estimating uncertainty in node classification. In *41st International Conference on Machine Learning (PMLR)*. MLResearchPress, 2024.
- [212] Shichao Zhu, Mufan Li, Guangmou Pan, and Xixun Lin. Ttgl: Large-scale multi-scenario universal graph learning at tiktok. In *Proceedings of the 31st ACM SIGKDD Conference on Knowledge Discovery and Data Mining* V. 2, pages 5249–5259, 2025.
- [213] Yuanchen Bei, Weizhi Zhang, Siwen Wang, Weizhi Chen, Sheng Zhou, Hao Chen, Yong Li, Jiajun Bu, Shirui Pan, Yizhou Yu, et al. Graphs meet ai agents: Taxonomy, progress, and future opportunities. *arXiv preprint arXiv:2506.18019*, 2025.
- [214] Yixin Liu, Guibin Zhang, Kun Wang, Shiyuan Li, and Shirui Pan. Graph-augmented large language model agents: Current progress and future prospects. *arXiv preprint arXiv:2507.21407*, 2025.
- [215] Zhaoyang Liu, Zeqiang Lai, Zhangwei Gao, Erfei Cui, Zhiheng Li, Xizhou Zhu, Lewei Lu, Qifeng Chen, Yu Qiao, Jifeng Dai, and Wenhui Wang. Controlllm: Augment language models with tools by searching on graphs. *arXiv preprint arXiv:2305.10601*, 2023.
- [216] Yingxuan Yang, Huacan Chai, Shuai Shao, Yuanyi Song, Siyuan Qi, Renting Rui, and Weinan Zhang. Agentnet: Decentralized evolutionary coordination for llm-based multi-agent systems. *arXiv preprint arXiv:2504.00587*, 2025.
- [217] Weize Chen, Ziming You, Ran Li, Yitong Guan, Chen Qian, Chenyang Zhao, Cheng Yang, Ruobing Xie, Zhiyuan Liu, and Maosong Sun. Internet of agents: Weaving a web of heterogeneous agents for collaborative intelligence. *arXiv preprint arXiv:2407.07061*, 2024.
- [218] Chenxi Wang, Xiang Chen, Ningyu Zhang, Bozhong Tian, Haoming Xu, Shumin Deng, and Huajun Chen. Mllm can see? dynamic correction decoding for hallucination mitigation. *arXiv preprint arXiv:2410.11779*, 2024.
- [219] Feilong Tang, Chengzhi Liu, Zhongxing Xu, Ming Hu, Zile Huang, Haochen Xue, Ziyang Chen, Zelin Peng, Zhiwei Yang, Sijin Zhou, et al. Seeing far and clearly: Mitigating hallucinations in mllms with attention causal decoding. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pages 26147–26159, 2025.
- [220] Feilong Tang, Zile Huang, Chengzhi Liu, Qiang Sun, Harry Yang, and Ser-Nam Lim. Intervening anchor token: Decoding strategy in alleviating hallucinations for mllms. In *The Thirteenth International Conference on Learning Representations*, 2025.
- [221] Sicong Leng, Hang Zhang, Guanzheng Chen, Xin Li, Shijian Lu, Chunyan Miao, and Lidong Bing. Mitigating object hallucinations in large vision-language models through visual contrastive decoding. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pages 13872–13882, 2024.
- [222] Ailin Deng, Zhirui Chen, and Bryan Hooi. Seeing is believing: Mitigating hallucination in large vision-language models via clip-guided decoding. *arXiv preprint arXiv:2402.15300*, 2024.
- [223] Jesus Moncada-Ramirez, Jose-Luis Matez-Bandera, Javier Gonzalez-Jimenez, and Jose-Raul Ruiz-Sarmiento. Agentic workflows for improving large language model reasoning in robotic object-centered planning. *Robotics*, 14(3):24, 2025.
- [224] Seongyun Lee, Sue Hyun Park, Yongrae Jo, and Minjoon Seo. Volcano: Mitigating multimodal hallucination through self-feedback guided revision. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, 2024.
- [225] Neel P. Bhatt, Yunhao Yang, Rohan Siva, Daniel Milan, ufuk topcu, and Zhangyang Wang. Know where you’re uncertain when planning with multimodal foundation models: A formal framework. In *Eighth Conference on Machine Learning and Systems*, 2025.
- [226] Zhiyuan Hu, Chumin Liu, Xidong Feng, Yilun Zhao, See-Kiong Ng, Anh Tuan Luu, Junxian He, Pang Wei Koh, and Bryan Hooi. Uncertainty of thoughts: Uncertainty-aware planning enhances information seeking in large language models. *arXiv preprint arXiv:2402.03271*, 2024.
- [227] Bar Karov, Dor Zohar, and Yam Marcovitz. Attentive reasoning queries: A systematic method for optimizing instruction-following in large language models. *arXiv preprint arXiv:2503.03669*, 2025.
- [228] Ziwei Ji, Tiezheng Yu, Yan Xu, Nayeon Lee, Etsuko Ishii, and Pascale Fung. Towards mitigating LLM hallucination via self reflection. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, 2023.
- [229] Brian Jalaian, Nathaniel D Bastian, et al. Hydra: An agentic reasoning approach for enhancing adversarial robustness and mitigating hallucinations in vision-language models. *arXiv preprint arXiv:2504.14395*, 2025.
- [230] Fanqi Wan, Xinting Huang, Leyang Cui, Xiaojun Quan, Wei Bi, and Shuming Shi. Knowledge verification to nip hallucination in the bud. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, 2024.
- [231] Yihao Xue, Kristjan Greenewald, Youssef Mrueh, and Baharan Mirza-soleiman. Verify when uncertain: Beyond self-consistency in black box hallucination detection. *arXiv preprint arXiv:2502.15845*, 2025.
- [232] Masha Belyi, Robert Friel, Shuai Shao, and Atindriyo Sanyal. Luna: An evaluation foundation model to catch language model hallucinations with high accuracy and low cost. *arXiv preprint arXiv:2406.00975*, 2024.
- [233] Ansong Ni, Srini Iyer, Dragomir Radev, Ves Stoyanov, Wen-tau Yih, Sida I Wang, and Xi Victoria Lin. Lever: Learning to verify language-to-code generation with execution. In *Proceedings of the 40th International Conference on Machine Learning (ICML’23)*, 2023.
- [234] Jacob Kleiman, Kevin Frank, Joseph Voyles, and Sindy Campagna. Simulation agent: A framework for integrating simulation and large language models for enhanced decision-making. *arXiv preprint arXiv:2505.13761*, 2025.
- [235] Xinyi Li, Yongfeng Zhang, and Edward C Malthouse. Large language model agent for fake news detection. *arXiv preprint arXiv:2405.01593*, 2024.
- [236] Ziqi Liu, Yangbin Chen, Ziyang Zhou, Yilin Li, Mingxuan Hu, Yushan Pan, and Zhijie Xu. Sevade: Self-evolving multi-agent analysis with decoupled evaluation for hallucination-resistant irony detection. *arXiv preprint arXiv:2508.06803*, 2025.
- [237] Yuming Chen, Jiangyan Feng, Haodong Zhang, Lijun Gong, Feng Zhu, Rui Zhao, Qibin Hou, Ming-Ming Cheng, and Yibing Song. Re-aligning language to visual objects with an agentic workflow. *arXiv preprint arXiv:2503.23508*, 2025.
- [238] Tianyi Huang, Jingyuan Yi, Peiyang Yu, and Xiaochuan Xu. Unmasking digital falsehoods: A comparative analysis of llm-based misinformation detection strategies. In *2025 8th International Conference on Advanced Algorithms and Control Engineering (ICAACE)*, pages 2470–2476. IEEE, 2025.
- [239] Xiaoxi Sun, Jinpeng Li, Yan Zhong, Dongyan Zhao, and Rui Yan. Towards detecting llms hallucination via markov chain-based multi-agent debate framework. In *ICASSP 2025-2025 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 1–5. IEEE, 2025.
- [240] Diego Gosmar and Deborah A Dahl. Hallucination mitigation using agentic ai natural language-based frameworks. *arXiv preprint arXiv:2501.13946*, 2025.
- [241] Xiaoyu Pan, Yang Bai, Ke Zou, Yang Zhou, Jun Zhou, Huazhu Fu, Yih-Chung Tham, and Yong Liu. Eh-benchmark ophthalmic hallucination

- benchmark and agent-driven top-down traceable reasoning workflow. *arXiv preprint arXiv:2507.22929*, 2025.
- [242] Xiaoxue Cheng, Junyi Li, Wayne Xin Zhao, Hongzhi Zhang, Fuzheng Zhang, Di Zhang, Kun Gai, and Ji-Rong Wen. Small agent can also rock! empowering small language models as hallucination detector. *arXiv preprint arXiv:2406.11277*, 2024.
- [243] Zhixuan Chu, Lei Zhang, Yichen Sun, Sijiao Xue, Zhibo Wang, Zhan Qin, and Kui Ren. Sora detector: A unified hallucination detection for large text-to-video models. *arXiv preprint arXiv:2405.04180*, 2024.
- [244] Renan Souza, Amal Gueroudji, Stephen DeWitt, Daniel Rosendo, Tirthankar Ghosal, Robert Ross, Prasanna Balaprakash, and Rafael Ferreira da Silva. Prov-agent: Unified provenance for tracking ai agent interactions in agentic workflows. *arXiv preprint arXiv:2508.02866*, 2025.
- [245] Hayley Ross, Ameya Sunil Mahabaleshwaran, and Yoshi Suhara. When2call: When (not) to call tools. *arXiv preprint arXiv:2504.18851*, 2025.
- [246] Yue Cui, Liuyi Yao, Shuchang Tao, Weijie Shi, Yaliang Li, Bolin Ding, and Xiaofang Zhou. Enhancing tool learning in large language models with hierarchical error checklists. *arXiv preprint arXiv:2506.00042*, 2025.
- [247] Jingwen Zhou, Jieshan Chen, Qinghua Lu, Dehai Zhao, and Liming Zhu. Shielda: Structured handling of exceptions in llm-driven agentic workflows. *arXiv preprint arXiv:2508.07935*, 2025.
- [248] Jiazhan Feng, Shijue Huang, Xingwei Qu, Ge Zhang, Yujia Qin, Baoquan Zhong, Chengquan Jiang, Jinxin Chi, and Wanjun Zhong. Retool: Reinforcement learning for strategic tool use in llms. *arXiv preprint arXiv:2504.11536*, 2025.
- [249] Gaurang Sriramanan, Siddhant Bharti, Vinu Sankar Sadasivan, Shoumik Saha, Priyatham Kattakinda, and Soheil Feizi. Llm-check: Investigating detection of hallucinations in large language models. *Advances in Neural Information Processing Systems*, 37:34188–34216, 2024.
- [250] Xiang Chen, Chenxi Wang, Yida Xue, Ningyu Zhang, Xiaoyan Yang, Qiang Li, Yue Shen, Lei Liang, Jinjie Gu, and Huajun Chen. Unified hallucination detection for multimodal large language models. *arXiv preprint arXiv:2402.03190*, 2024.
- [251] Yuyan Chen, Qiang Fu, Yichen Yuan, Zhihao Wen, Ge Fan, Dayiheng Liu, Dongmei Zhang, Zhixu Li, and Yanghua Xiao. Hallucination detection: Robustly discerning reliable answers in large language models. In *Proceedings of the 32nd ACM International Conference on Information and Knowledge Management*, pages 245–255, 2023.
- [252] Ben Snyder, Marius Moisescu, and Muhammad Bilal Zafar. On early detection of hallucinations in factual question answering. In *Proceedings of the 30th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, pages 2721–2732, 2024.
- [253] Hao Fei, Meng Luo, Jundong Xu, Shengqiong Wu, Wei Ji, Mong-Li Lee, and Wynne Hsu. Fine-grained structural hallucination detection for unified visual comprehension and generation in multimodal llm. In *Proceedings of the 1st ACM Multimedia Workshop on Multi-modal Misinformation Governance in the Era of Foundation Models*, pages 13–22, 2024.
- [254] Yuiga Wada, Kazuki Matsuda, Komei Sugiura, and Graham Neubig-Zina. Multimodal fine-grained hallucination detection and editing. *arXiv preprint arXiv:2506.13130*, 2025.
- [255] Mobashir Sadat, Zhengyu Zhou, Lukas Lange, Jun Araki, Arsalan Gundroo, Bingqing Wang, Rakesh R Menon, Md Rizwan Parvez, and Zhe Feng. Delucionqa: Detecting hallucinations in domain-specific question answering. *arXiv preprint arXiv:2312.05200*, 2023.
- [256] Anisha Gunjal, Jihan Yin, and Erhan Bas. Detecting and preventing hallucinations in large vision language models. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pages 18135–18143, 2024.
- [257] Borui Yang, Md Afif Al Mamun, Jie M Zhang, and Gias Uddin. Hallucination detection in large language models with metamorphic relations. *Proceedings of the ACM on Software Engineering*, 2(FSE):425–445, 2025.
- [258] Shengqiong Wu, Hao Fei, Liangming Pan, William Yang Wang, Shuicheng Yan, and Tat-Seng Chua. Combating multimodal llm hallucination via bottom-up holistic reasoning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pages 8460–8468, 2025.
- [259] Haichuan Hu, Congqing He, Xiaochen Xie, and Quanjun Zhang. Lrp4rag: Detecting hallucinations in retrieval-augmented generation via layer-wise relevance propagation. *arXiv preprint arXiv:2408.15533*, 2024.
- [260] Jonathan J Ross, Ekaterina Khramtsova, Anton van der Vegt, Bevan Koopman, and Guido Zuccon. Rarr unraveled: Component-level insights into hallucination detection and mitigation. In *Proceedings of the 48th International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 3286–3295, 2025.
- [261] Ádám Kovács and Gábor Recski. Lettucedetect: A hallucination detection framework for rag applications. *arXiv preprint arXiv:2502.17125*, 2025.
- [262] Baolong Bi, Shenghua Liu, Yiwei Wang, Yilong Xu, Junfeng Fang, Lingrui Mei, and Xueqi Cheng. Parameters vs. context: Fine-grained control of knowledge reliance in language models. *arXiv preprint arXiv:2503.15888*, 2025.
- [263] Rongzhe Wei, Peizhi Niu, Hans Hao-Hsun Hsu, Ruihan Wu, Haoteng Yin, Mohsen Ghassemi, Yifan Li, Vamsi K Potluru, Eli Chien, Kamalika Chaudhuri, et al. Do llms really forget? evaluating unlearning with knowledge correlation and confidence awareness. *arXiv preprint arXiv:2506.05735*, 2025.
- [264] Zhoubo Li, Ningyu Zhang, Yunzhi Yao, Mengru Wang, Xi Chen, and Huajun Chen. Unveiling the pitfalls of knowledge editing for large language models. *arXiv preprint arXiv:2310.02129*, 2023.
- [265] Mingda Chen, Yang Li, Karthik Padthe, Rulin Shao, Alicia Sun, Luke Zettlemoyer, Gargi Ghosh, and Wen-tau Yih. Improving factuality with explicit working memory. *arXiv preprint arXiv:2412.18069*, 2024.
- [266] Zhiyu Li, Shichao Song, Chenyang Xi, Hanyu Wang, Chen Tang, Simin Niu, Ding Chen, Jiawei Yang, Chunyu Li, Qingchen Yu, et al. Memos: A memory os for ai system. *arXiv preprint arXiv:2507.03724*, 2025.
- [267] Boyu Qiao, Kun Li, Wei Zhou, and Songlin Hu. Dynamic simulation framework for disinformation dissemination and correction with social bots. *arXiv preprint arXiv:2507.16848*, 2025.
- [268] Hanjun Luo, Shenyu Dai, Chiming Ni, Xinfeng Li, Guibin Zhang, Kun Wang, Tongliang Liu, and Hanan Salam. Agentauditor: Human-level safety and security evaluation for llm agents. *arXiv preprint arXiv:2506.00641*, 2025.
- [269] Ohav Barbi, Ori Yoran, and Mor Geva. Preventing rogue agents improves multi-agent collaboration. *arXiv preprint arXiv:2502.05986*, 2025.
- [270] Chris Olah. Mechanistic Interpretability, Variables, and the Importance of Interpretable Bases, June 2022.
- [271] Ziwei Ji, Lei Yu, Yeskendir Koishkenov, Yejin Bang, Anthony Hartshorn, Alan Schelten, Cheng Zhang, Pascale Fung, and Nicola Cancedda. Calibrating verbal uncertainty as a linear feature to reduce hallucinations. *arXiv preprint arXiv:2503.14477*, 2025.
- [272] Zhuoran Jin, Pengfei Cao, Hongbang Yuan, Yubo Chen, Jixin Xu, Huaijun Li, Xiaojian Jiang, Kang Liu, and Jun Zhao. Cutting off the head ends the conflict: A mechanism for interpreting and mitigating knowledge conflicts in language models. *arXiv preprint arXiv:2402.18154*, 2024.
- [273] Tianrui Guan, Fuxiao Liu, Xiyang Wu, Ruiqi Xian, Zongxia Li, Xiaoyu Liu, Xijun Wang, Lichang Chen, Furong Huang, Yaser Yacoob, Dinesh Manocha, and Tianyi Zhou. Hallusionbench: An advanced diagnostic suite for entangled language hallucination and visual illusion in large vision-language models. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, 2024.
- [274] Yuanzhe Hu, Yu Wang, and Julian McAuley. Evaluating memory in llm agents via incremental multi-turn interactions. *arXiv preprint arXiv:2507.05257*, 2025.
- [275] Magdalena Biesialska, Katarzyna Biesialska, and Marta R Costa-Jussa. Continual lifelong learning in natural language processing: A survey. *arXiv preprint arXiv:2012.09823*, 2020.
- [276] Tri Dao, Dan Fu, Stefano Ermon, Atri Rudra, and Christopher Ré. Flashattention: Fast and memory-efficient exact attention with io-awareness. *Advances in neural information processing systems*, 35:16344–16359, 2022.
- [277] Kewei Cheng, Nesreen K Ahmed, Ryan A Rossi, Theodore Willke, and Yizhou Sun. Neural-symbolic methods for knowledge graph reasoning: A survey. *ACM Transactions on Knowledge Discovery from Data*, 18(9):1–44, 2025.
- [278] Mitra Baratchi, Can Wang, Steffen Limmer, Jan N Van Rijn, Holger Hoos, Thomas Bäck, and Markus Olhofer. Automated machine learning: past, present and future. *Artificial intelligence review*, 57(5):122, 2024.
- [279] Zelong Li, Shuyuan Xu, Kai Mei, Wenye Hu, Balaji Rama, Om Raheja, Hao Wang, He Zhu, and Yongfeng Zhang. Autoflow: Automated workflow generation for large language model agents. *arXiv preprint arXiv:2407.12821*, 2024.

APPENDIX A LOOP OF LLM-BASED MULTI-AGENT SYSTEM

Different from the single-agent setting, each LLM-based agent in the MAS must communicate with other agents to accomplish goals. To model these processes, a communication structure G_t is introduced among N agents. Furthermore, G_t would evolve with time to align with the dynamic adjustments of MAS. Therefore, compared with Section II-B, the loop of LLM-based MAS includes two additional procedures: **Broadcasting** and **Structure Evolution**.

- **Reasoning:** Each agent i first generates its own plan p_t^i for the next action conditioned on b_t^i and g :

$$p_t^i = \Phi^i(b_t^i, g). \quad (15)$$

- **Execution:** Each agent i then translates p_t^i into an executable action a_t^i :

$$a_t^i = E^i(b_t^i, p_t^i). \quad (16)$$

- **Broadcasting:** The agent i broadcasts its message to its neighbors in G_t according to its plan p_t^i :

$$\{q_t^{i \rightarrow j} \mid j \in N(i)\} = B(b_t^i, p_t^i, G_t). \quad (17)$$

Here $\{q_t^{i \rightarrow j} \mid j \in N(i)\}$ denotes the messages sent by the agent i to its neighbors (i.e., $N(i)$) at the time step t .

- **Feedback:** The learning environment would also provide a reward r_t based on s_t and $\{a_t^i\}_{i=1}^N$:

$$r_t = R(s_t, \{a_t^i\}_{i=1}^N). \quad (18)$$

- **Environment Transition:** The learning environment transitions to s_{t+1} based on s_t and $\{a_t^i\}_{i=1}^N$:

$$\Pr(s_{t+1} \mid s_t, \{a_t^i\}_{i=1}^N) = T(s_t, \{a_t^i\}_{i=1}^N). \quad (19)$$

- **Perception:** Each agent i perceives s_{t+1} to generate the observation o_{t+1}^i :

$$o_{t+1}^i = Z^i(s_{t+1}, b_t^i, a_t^i, \{q_t^{j \rightarrow i} \mid j \in N(i)\}), \quad (20)$$

where $\{q_t^{j \rightarrow i} \mid j \in N(i)\}$ denotes the messages received by the agent i from its neighbors at the time step t .

- **Memorization:** The external memory module of the agent i is updated as follows,

$$m_{t+1}^i = L_M^i(m_t^i, a_t^i, \{q_t^{j \rightarrow i} \mid j \in N(i)\}, o_{t+1}^i). \quad (21)$$

- **Belief Update:** Then the agent i refines its belief state as follows,

$$b_{t+1}^i = L_B^i(b_t^i, m_{t+1}^i, a_t^i, \{q_t^{j \rightarrow i} \mid j \in N(i)\}, r_t^i, o_{t+1}^i, g). \quad (22)$$

- **Structure Evolution:** Based on $\{b_{t+1}^i\}_{i=1}^N$ and G_t , the communication structure can be updated as follows,

$$G_{t+1} = U(G_t, \{b_{t+1}^i\}_{i=1}^N). \quad (23)$$

APPENDIX B HALLUCINATION EXAMPLE EXPLANATION

As shown in Fig. 5, we present the representative examples of each type of agent hallucinations as follows,

- **Goal Understanding Hallucinations.** In this example, the user asks the agent to “recommend a restaurant suitable for dining with elders”. The underlying goal is clearly to find a restaurant whose cuisine is light and easy to digest and whose environment is appropriate for family gatherings. However, the agent recommends “Spicy World”, a restaurant specializing in very spicy crayfish and boiled fish, thereby completely ignoring the prerequisite “suitable for elders”.
- **Intention Decomposition Hallucinations.** In this example, the user asks the agent to plan a “family picnic for 10 people” and explicitly requires that the total budget for “purchasing food” must not exceed 500 yuan. Clearly, this plan must include a sub-intentions for “cost calculation” to verify whether the total expenditure satisfies the budget constraint. However, when decomposing the task, the agent only considers two steps: “choose a venue” and “buy food”, thereby omitting a crucial component in the decomposition of the user’s intention.
- **Planning Generation Hallucinations.** This example illustrates hallucinations arising in the process of generating a concrete plan for a sub-intention derived from intention decomposition, namely “screen venues”. Given the user’s requirements, the chosen venue should explicitly allow picnicking. Nevertheless, the agent selects merely “a lawn that is open all day”, conflating “opening hours” with “time during which picnics are permitted”. In other words, the model hallucinates at the planning stage for the sub-intentions, failing to align the generated plan with the constraints specified in the user’s intent.
- **Perception Hallucinations.** In this example, the user asks the agent to describe the content of an image. In the image, a chair is located to the right of a bookshelf, yet the agent responds that “the chair is to the left of the bookshelf”. This error is a prototypical perceptual hallucination, in which the agent’s visual understanding or spatial localization is systematically biased.
- **Memory Retrieval Hallucinations.** Here, the user asks the agent to “tell me about tomorrow’s meeting schedule”. The memory store contains two relevant events: a project discussion meeting at 10:00 a.m. today and a customer meeting at 1:00 p.m. tomorrow. However, the agent fails to correctly anchor the events to their respective dates and instead treats both meetings as if they were scheduled for tomorrow. This illustrates that hallucinations can arise at the memory retrieval stage, where agents mis-retrieve or mis-align temporally indexed information.
- **Memory Update Hallucinations.** In this example, the user instructs the agent to “cancel all meetings tomorrow morning”. During the memory update process, however, the agent erroneously clears the entire schedule for the following day, including the afternoon meeting. This reflects a hallucination in self-managed memory editing: the




Fig. 5. The depiction of different types of agent hallucinations, each illustrated with a representative example. The detailed explanation is given in Appendix B.

agent performs an overgeneralized or incorrect update, leading to a memory update hallucination.

- **Tool Selection Hallucinations.** The user plans to travel to Kyoto in autumn and asks the agent to recommend tourist attractions. The agent incorrectly calls a non-existent tool named “get kyoto travel info”, whereas the correct tool in the system should be “recommend tourist spots”. This indicates that, when selecting external tools, the agent may “invent” plausible-sounding but non-existent APIs or function names, thereby exhibiting tool selection hallucinations.
- **Tool Calling Hallucinations.** Similar to the previous case, this time the agent selects the correct tool, “recommend tourist spots”, but arbitrarily appends an extra parameter `language=“English”`, which is not part of the tool’s actual specification. This demonstrates that even when the tool name is correct, the agent may hallucinate at the parameter level—engaging in hallucinatory argument extension—which can cause the call to fail or yield unintended behavior.
- **Communication Hallucinations.** This example illustrates an “echo chamber effect” in multi-agent communication, a particularly typical form of communication

hallucination. Initially, the client states that they require a “code review”. As the message passes along a chain of agents, the first agent mishears it as “cold review”, the second relays it as “gold review”, and the third finally interprets it as “old review”. Through multiple rounds of transmission, the information is progressively distorted until it becomes completely detached from the original meaning. This hallucination shows that, when multiple agents collaborate, minor mis-hearings or misinterpretations can be amplified, producing a “telephone game” style accumulation of deviations.