Infor VISUAL API Toolkit Financials Class Library Reference

Copyright © 2024 Infor

Important Notices

The material contained in this publication (including any supplementary information) constitutes and contains confidential and proprietary information of Infor.

By gaining access to the attached, you acknowledge and agree that the material (including any modification, translation or adaptation of the material) and all copyright, trade secrets and all other right, title and interest therein, are the sole property of Infor and that you shall not gain right, title or interest in the material (including any modification, translation or adaptation of the material) by virtue of your review thereof other than the non-exclusive right to use the material solely in connection with and the furtherance of your license and use of software made available to your company from Infor pursuant to a separate agreement, the terms of which separate agreement shall govern your use of this material and all supplemental related materials ("Purpose").

In addition, by accessing the enclosed material, you acknowledge and agree that you are required to maintain such material in strict confidence and that your use of such material is limited to the Purpose described above. Although Infor has taken due care to ensure that the material included in this publication is accurate and complete, Infor cannot warrant that the information contained in this publication is complete, does not contain typographical or other errors, or will meet your specific requirements. As such, Infor does not assume and hereby disclaims all liability, consequential or otherwise, for any loss or damage to any person or entity which is caused by or relates to errors or omissions in this publication (including any supplementary information), whether such errors or omissions result from negligence, accident or any other cause.

Without limitation, U.S. export control laws and other applicable export and import laws govern your use of this material and you will neither export or re-export, directly or indirectly, this material nor any related materials or supplemental information in violation of such laws, or use such materials for any purpose prohibited by such laws.

Trademark Acknowledgements

The word and design marks set forth herein are trademarks and/or registered trademarks of Infor and/or related affiliates and subsidiaries. All rights reserved. All other company, product, trade or service names referenced may be registered trademarks or trademarks of their respective owners.

Publication Information

Release: Infor VISUAL API Toolkit

Publication date: August 13, 2024

About this guide

This guide describes the objects available in the Infor VISUAL API Toolkit Financials class library.

Intended audience

The intended audience of this guide is developers who are using the API Toolkit to extend the VISUAL solution.

Contacting Support

If you have questions about Infor products, go to the Infor Customer Portal at https://customerportal.infor.com/csmcore/

If we update this document after the product release, we will post the new version on this Web site. We recommend that you check this Web site periodically for updated documentation.

If you have comments about Infor documentation, contact https://docs.infor.com/en-us.

Supported languages

These languages are supported for use with the toolkit:

- Visual Basic
- C#

While it is possible to use any .NET-aware programming language with the toolkit, other languages are not officially supported.

Support information

The API Toolkit will be updated regularly as more class members are added to each assembly, schema changes are made, and any reported issues are resolved. Infor Support cannot assist you with developing customized code using the API Toolkit. For assistance with customizations, contact Infor Consulting Services or your channel partner.

The functionality provided within the API Toolkit will not be extended beyond the standard functionality experienced in the VISUAL application itself. Enhancement requests with compelling business cases detailing how suggested alternatives are not viable will be evaluated and considered.

Infor is not responsible for data incorrectly entered to the database through the use of the API Toolkit. Customers must establish a full test environment to ensure that data created by APIs functions in the same manner as data created through the VISUAL interface.

Lsa.Vmfg.Financials Namespace

Classes

	Class	Description
	Account	Maintain Accounts
	BankAccount	Maintain Bank Accounts
	CreditMemoApply	Maintain Credit Memo Applications.
	GLInterfaceAccounts	Maintain General Ledger Interface Accounts
	SFPayables	Maintain Standard Financials Payables
	SFReceivables	Maintain Standard Financials Receivables.

Classes and Infor VISUAL Financials Global Edition

If a Financials Global Edition license has been applied to the VISUAL database you registered for use with APIs, then these classes are read-only:

- Account
- BankAccount
- CreditMemoApply
- SFPayables
- SFReceivables

Account Class

Maintain Accounts

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessDocument
          Lsa.Vmfg.Financials.Account

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class Account : BusinessDocument
```

VB

```
<SerializableAttribute>
Public Class Account
    Inherits BusinessDocument
```

The **Account** type exposes the following members.

Constructors

	Name	Description
	Account()	Business Document Constructor

	Account(String)	Business Document Constructor

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Accounts based on search criteria
	Browse(String, String, String, Int32, Int32)	Retrieve Accounts based on search criteria, limited by record count
	Exists	Determine if a specific Account exists.
	Find	Retrieve a specific Account. Only the top-level table (ACCOUNT) is returned.
	Load(String)	Load a specific Account.
	Load(Stream, String)	Load from stream and rename using new key.
	NewAccountRow	Adds a new row to the ACCOUNT table.
	NewAccountSiteRow	Adds a new row to the ACCOUNT_SITE table.
	Save	Save all previously loaded Accounts to the database. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.

See Also

Lsa.Vmfg.Financials Namespace

Account Constructor

Overload List

	Name	Description
	Account()	Business Document Constructor
	Account(String)	Business Document Constructor

See Also

Account Class

Lsa.Vmfg.Financials Namespace

Account Constructor

Business Document Constructor

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public Account()

VB
Public Sub New

See Also

Account Class

Account Overload

Lsa.Vmfg.Financials Namespace

Account Constructor (String)

Business Document Constructor

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public Account(
    string databaseInstanceName
)
```

VB

```
Public Sub New (
    databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

Account Class

Account Overload

Lsa.Vmfg.Financials Namespace

Account.Account Methods

The Account type exposes the following members.

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Accounts based on search criteria
	Browse(String, String, String, Int32, Int32)	Retrieve Accounts based on search criteria, limited by record count
	Exists	Determine if a specific Account exists.
	Find	Retrieve a specific Account. Only the top-level table (ACCOUNT) is returned.
	Load(String)	Load a specific Account.
	Load(Stream, String)	Load from stream and rename using new key.
	NewAccountRow	Adds a new row to the ACCOUNT table.
	NewAccountSiteRow	Adds a new row to the ACCOUNT_SITE table.
	Save	Save all previously loaded Accounts to the database. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.

See Also

Account Class

Lsa.Vmfg.Financials Namespace

Account.Browse Method

Overload List

	Name	Description
	Browse(String, String, String)	Retrieve Accounts based on search criteria
	Browse(String, String, String, Int32, Int32)	Retrieve Accounts based on search criteria, limited by record count

See Also

Account Class

Lsa.Vmfg.Financials Namespace

Account.Browse Method (String, String, String)

Retrieve Accounts based on search criteria

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
    string columnNames,
    string searchCondition,
    string sortColumns
)
```

VB

```
Public Overridable Function Browse (
    columnNames As String,
    searchCondition As String,
    sortColumns As String
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

Return Value

Type: **DataSet**

See Also

Account Class

Browse Overload

Lsa.Vmfg.Financials Namespace

Account.Browse Method (String, String, String, Int32, Int32)

Retrieve Accounts based on search criteria, limited by record count

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
    string columnNames,
    string searchCondition,
    string sortColumns,
    int startRecord,
    int maxRecords
)
```

VB

```
Public Overridable Function Browse (
    columnNames As String,
    searchCondition As String,
    sortColumns As String,
    startRecord As Integer,
    maxRecords As Integer
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

startRecord

Type: System.Int32

maxRecords

Type: System.Int32

Return Value

Type: **DataSet**

See Also

Account Class

Browse Overload

Lsa.Vmfg.Financials Namespace

Account.Exists Method

Determine if a specific Account exists.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual bool Exists(
    string accountID
)
```

VB

```
Public Overridable Function Exists (
    accountID As String
) As Boolean
```

Parameters

accountID

Type: System.String

Return Value

Type: Boolean

See Also

Account Class

Lsa.Vmfg.Financials Namespace

Account.Find Method

Retrieve a specific Account. Only the top-level table (ACCOUNT) is returned.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Find(
    string accountID
)
```

VB

```
Public Overridable Sub Find (
    accountID As String
)
```

Parameters

accountID

Type: System.String

See Also

Account Class

Lsa.Vmfg.Financials Namespace

Account.Load Method

Overload List

	Name	Description
	Load(String)	Load a specific Account.
	Load(Stream, String)	Load from stream and rename using new key.

See Also

Account Class

Lsa.Vmfg.Financials Namespace

Account.Load Method (String)

Load a specific Account.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
    string accountID
)
```

VB

```
Public Overridable Sub Load (
    accountID As String
)
```

Parameters

accountID

Type: System.String

See Also

Account Class

Load Overload

Lsa.Vmfg.Financials Namespace

Account.Load Method (Stream, String)

Load from stream and rename using new key.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
    Stream stream,
    string accountID
)
```

VB

```
Public Overridable Sub Load (
    stream As Stream,
    accountID As String
)
```

Parameters

stream

Type: System.IO.Stream

accountID

Type: System.String

See Also

Account Class

Load Overload

Lsa.Vmfg.Financials Namespace

Account.NewAccountRow Method

Adds a new row to the ACCOUNT table.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewAccountRow(
    string accountID
)
```

VB

```
Public Overridable Function NewAccountRow (
    accountID As String
) As DataRow
```

Parameters

accountID

Type: System.String

Return Value

Type: **DataRow**

See Also

Account Class

Lsa.Vmfg.Financials Namespace

Account.NewAccountSiteRow Method

Adds a new row to the ACCOUNT_SITE table.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewAccountSiteRow(
    string accountID,
    string siteID
)
```

VB

```
Public Overridable Function NewAccountSiteRow (
    accountID As String,
    siteID As String
) As DataRow
```

Parameters

accountID

Type: System.String

siteID

Type: System.String

Return Value

Type: **DataRow**

See Also

Account Class

Lsa.Vmfg.Financials Namespace

Account.Save Method

Save all previously loaded Accounts to the database. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

Account Class

Lsa.Vmfg.Financials Namespace

BankAccount Class

Maintain Bank Accounts

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessDocument
          Lsa.Vmfg.Financials.BankAccount

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class BankAccount : BusinessDocument
```

VB

```
<SerializableAttribute>
Public Class BankAccount
    Inherits BusinessDocument
```

The **BankAccount** type exposes the following members.

Constructors

	Name	Description
	BankAccount()	Business Documnet Constructor

	BankAccount(String)	Business Document Constructor

Methods

	Name	Description
	Browse(String, String, String)	Retrieve BankAccounts based on search criteria
	Browse(String, String, String, Int32, Int32)	Retrieve BankAccounts based on search criteria, limited by record count
	Exists	Determine if a specific Bank Account exists
	Find	Retrieve a specific Bank Account
	Load(String)	Load a specific Bank Account
	Load(Stream, String)	Load from stream and rename using new key
	NewBankAccountRow	Add a new row to the BANK_ACCOUNT table
	Save	Save all previously loaded Bank Accounts to the database. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.

See Also

Lsa.Vmfg.Financials Namespace

BankAccount Constructor

Overload List

	Name	Description
	BankAccount()	Business Documnet Constructor
	BankAccount(String)	Business Document Constructor

See Also

BankAccount Class

Lsa.Vmfg.Financials Namespace

BankAccount Constructor

Business Documnet Constructor

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public BankAccount()

VB
Public Sub New

See Also

BankAccount Class

BankAccount Overload

Lsa.Vmfg.Financials Namespace

BankAccount Constructor (String)

Business Document Constructor

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public BankAccount(
    string databaseInstanceName
)
```

VB

```
Public Sub New (
    databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

BankAccount Class

BankAccount Overload

Lsa.Vmfg.Financials Namespace

BankAccount.BankAccount Methods

The BankAccount type exposes the following members.

Methods

	Name	Description
	Browse(String, String, String)	Retrieve BankAccounts based on search criteria
	Browse(String, String, String, Int32, Int32)	Retrieve BankAccounts based on search criteria, limited by record count
	Exists	Determine if a specific Bank Account exists
	Find	Retrieve a specific Bank Account
	Load(String)	Load a specific Bank Account
	Load(Stream, String)	Load from stream and rename using new key
	NewBankAccountRow	Add a new row to the BANK_ACCOUNT table
	Save	Save all previously loaded Bank Accounts to the database. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.

See Also

BankAccount Class

Lsa.Vmfg.Financials Namespace

BankAccount.Browse Method

Overload List

	Name	Description
	Browse(String, String, String)	Retrieve BankAccounts based on search criteria
	Browse(String, String, String, Int32, Int32)	Retrieve BankAccounts based on search criteria, limited by record count

See Also

BankAccount Class

Lsa.Vmfg.Financials Namespace

BankAccount.Browse Method (String, String, String)

Retrieve BankAccounts based on search criteria

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
    string columnNames,
    string searchCondition,
    string sortColumns
)
```

VB

```
Public Overridable Function Browse (
    columnNames As String,
    searchCondition As String,
    sortColumns As String
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

Return Value

Type: **DataSet**

See Also

BankAccount Class

Browse Overload

Lsa.Vmfg.Financials Namespace

BankAccount.Browse Method (String, String, String, Int32, Int32)

Retrieve BankAccounts based on search criteria, limited by record count

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
    string columnNames,
    string searchCondition,
    string sortColumns,
    int startRecord,
    int maxRecords
)
```

VB

```
Public Overridable Function Browse (
    columnNames As String,
    searchCondition As String,
    sortColumns As String,
    startRecord As Integer,
    maxRecords As Integer
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

startRecord

Type: System.Int32

maxRecords

Type: System.Int32

Return Value

Type: **DataSet**

See Also

BankAccount Class

Browse Overload

Lsa.Vmfg.Financials Namespace

BankAccount.Exists Method

Determine if a specific Bank Account exists

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual bool Exists(
    string accountID
)
```

VB

```
Public Overridable Function Exists (
    accountID As String
) As Boolean
```

Parameters

accountID

Type: System.String

Return Value

Type: Boolean

See Also

BankAccount Class

Lsa.Vmfg.Financials Namespace

BankAccount.Find Method

Retrieve a specific Bank Account

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Find(
    string accountID
)
```

VB

```
Public Overridable Sub Find (
    accountID As String
)
```

Parameters

accountID

Type: System.String

See Also

BankAccount Class

Lsa.Vmfg.Financials Namespace

BankAccount.Load Method

Overload List

	Name	Description
	Load(String)	Load a specific Bank Account
	Load(Stream, String)	Load from stream and rename using new key

See Also

BankAccount Class

Lsa.Vmfg.Financials Namespace

BankAccount.Load Method (String)

Load a specific Bank Account

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
    string accountID
)
```

VB

```
Public Overridable Sub Load (
    accountID As String
)
```

Parameters

accountID

Type: System.String

See Also

BankAccount Class

Load Overload

Lsa.Vmfg.Financials Namespace

BankAccount.Load Method (Stream, String)

Load from stream and rename using new key

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
    Stream stream,
    string accountID
)
```

VB

```
Public Overridable Sub Load (
    stream As Stream,
    accountID As String
)
```

Parameters

stream

Type: System.IO.Stream

accountID

Type: System.String

See Also

BankAccount Class

Load Overload

Lsa.Vmfg.Financials Namespace

BankAccount.NewBankAccountRow Method

Add a new row to the BANK_ACCOUNT table

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewBankAccountRow(
    string accountID
)
```

VB

```
Public Overridable Function NewBankAccountRow (
    accountID As String
) As DataRow
```

Parameters

accountID

Type: System.String

Return Value

Type: **DataRow**

See Also

BankAccount Class

Lsa.Vmfg.Financials Namespace

BankAccount.Save Method

Save all previously loaded Bank Accounts to the database. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Save()
```

VB

```
Public Overridable Sub Save
```

See Also

BankAccount Class

Lsa.Vmfg.Financials Namespace

CreditMemoApply Class

Maintain Credit Memo Applications.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessDocument
          Lsa.Vmfg.Financials.CreditMemoApply

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class CreditMemoApply : BusinessDocument
```

VB

```
<SerializableAttribute>
Public Class CreditMemoApply
    Inherits BusinessDocument
```

The **CreditMemoApply** type exposes the following members.

Constructors

	Name	Description
	CreditMemoApply()	Business Document Constructor

	CreditMemoApply(String)	Business Document Constructor

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Credit Memo Applications based on selection criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Credit Memo Applications based on selection criteria, limited by record count.
	Exists	Determines whether a specific Credit Memo Application exists.
	Find	Retrieves a specific Credit Memo Application.
	Load(String)	Loads a specific Credit Memo Application.
	Load(Stream, String)	Load from stream and rename using new key.
	NewCreditMemoApplyRow	Inserts a new row into the CREDIT_MEMO_APPLY table.
	Save()	Saves all previously loaded Credit Memo Applications to the database. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.
	Save(Stream)	Save current state of data set to stream. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.

See Also

Lsa.Vmfg.Financials Namespace

CreditMemoApply Constructor

Overload List

	Name	Description
	CreditMemoApply()	Business Document Constructor
	CreditMemoApply(String)	Business Document Constructor

See Also

CreditMemoApply Class

Lsa.Vmfg.Financials Namespace

CreditMemoApply Constructor

Business Document Constructor

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public CreditMemoApply()

VB
Public Sub New

See Also

CreditMemoApply Class

CreditMemoApply Overload

Lsa.Vmfg.Financials Namespace

CreditMemoApply Constructor (String)

Business Document Constructor

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public CreditMemoApply(
    string databaseInstanceName
)
```

VB

```
Public Sub New (
    databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

CreditMemoApply Class

CreditMemoApply Overload

Lsa.Vmfg.Financials Namespace

CreditMemoApply.CreditMemoApply Methods

The CreditMemoApply type exposes the following members.

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Credit Memo Applications based on selection criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Credit Memo Applications based on selection criteria, limited by record count.
	Exists	Determines whether a specific Credit Memo Application exists.
	Find	Retrieves a specific Credit Memo Application.
	Load(String)	Loads a specific Credit Memo Application.
	Load(Stream, String)	Load from stream and rename using new key.
	NewCreditMemoApplyRow	Inserts a new row into the CREDIT_MEMO_APPLY table.
	Save()	Saves all previously loaded Credit Memo Applications to the database. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.
	Save(Stream)	Save current state of data set to stream. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.

See Also

CreditMemoApply Class

Lsa.Vmfg.Financials Namespace

CreditMemoApply.Browse Method

Overload List

	Name	Description
	Browse(String, String, String)	Retrieve Credit Memo Applications based on selection criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Credit Memo Applications based on selection criteria, limited by record count.

See Also

CreditMemoApply Class

Lsa.Vmfg.Financials Namespace

CreditMemoApply.Browse Method (String, String, String)

Retrieve Credit Memo Applications based on selection criteria.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
    string columnNames,
    string searchCondition,
    string sortColumns
)
```

VB

```
Public Overridable Function Browse (
    columnNames As String,
    searchCondition As String,
    sortColumns As String
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

Return Value

Type: **DataSet**

See Also

CreditMemoApply Class

Browse Overload

Lsa.Vmfg.Financials Namespace

CreditMemoApply.Browse Method (String, String, String, Int32, Int32)

Retrieve Credit Memo Applications based on selection criteria, limited by record count.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
    string columnNames,
    string searchCondition,
    string sortColumns,
    int startRecord,
    int maxRecords
)
```

VB

```
Public Overridable Function Browse (
    columnNames As String,
    searchCondition As String,
    sortColumns As String,
    startRecord As Integer,
    maxRecords As Integer
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

startRecord

Type: System.Int32

maxRecords

Type: System.Int32

Return Value

Type: **DataSet**

See Also

CreditMemoApply Class

Browse Overload

Lsa.Vmfg.Financials Namespace

CreditMemoApply.Exists Method

Determines whether a specific Credit Memo Application exists.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual bool Exists(
    string memoVoucherID,
    string invVoucherID
)
```

VB

```
Public Overridable Function Exists (
    memoVoucherID As String,
    invVoucherID As String
) As Boolean
```

Parameters

memoVoucherID

Type: System.String

invVoucherID

Type: System.String

Return Value

Type: Boolean

See Also

CreditMemoApply Class

Lsa.Vmfg.Financials Namespace

CreditMemoApply.Find Method

Retrieves a specific Credit Memo Application.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Find(
    string memoVoucherID,
    string invVoucherID
)
```

VB

```
Public Overridable Sub Find (
    memoVoucherID As String,
    invVoucherID As String
)
```

Parameters

memoVoucherID

Type: System.String

invVoucherID

Type: System.String

See Also

CreditMemoApply Class

Lsa.Vmfg.Financials Namespace

CreditMemoApply.Load Method

Overload List

	Name	Description
	Load(String)	Loads a specific Credit Memo Application.
	Load(Stream, String)	Load from stream and rename using new key.

See Also

CreditMemoApply Class

Lsa.Vmfg.Financials Namespace

CreditMemoApply.Load Method (String)

Loads a specific Credit Memo Application.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
    string invVoucherID
)
```

VB

```
Public Overridable Sub Load (
    invVoucherID As String
)
```

Parameters

invVoucherID

Type: System.String

See Also

CreditMemoApply Class

Load Overload

Lsa.Vmfg.Financials Namespace

CreditMemoApply.Load Method (Stream, String)

Load from stream and rename using new key.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
    Stream stream,
    string invVoucherID
)
```

VB

```
Public Overridable Sub Load (
    stream As Stream,
    invVoucherID As String
)
```

Parameters

stream

Type: System.IO.Stream

invVoucherID

Type: System.String

See Also

CreditMemoApply Class

Load Overload

Lsa.Vmfg.Financials Namespace

CreditMemoApply.NewCreditMemoApplyRow Method

Inserts a new row into the CREDIT_MEMO_APPLY table.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewCreditMemoApplyRow(
    string memoVoucherID,
    string invVoucherID,
    decimal applyAmount
)
```

VB

```
Public Overridable Function NewCreditMemoApplyRow (
    memoVoucherID As String,
    invVoucherID As String,
    applyAmount As Decimal
) As DataRow
```

Parameters

memoVoucherID

Type: System.String

invVoucherID

Type: System.String

applyAmount

Type: System.Decimal

Return Value

Type: **DataRow**

See Also

CreditMemoApply Class

Lsa.Vmfg.Financials Namespace

CreditMemoApply.Save Method

Overload List

	Name	Description
	Save()	Saves all previously loaded Credit Memo Applications to the database. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.
	Save(Stream)	Save current state of data set to stream. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.

See Also

CreditMemoApply Class

Lsa.Vmfg.Financials Namespace

CreditMemoApply.Save Method

Saves all previously loaded Credit Memo Applications to the database. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

CreditMemoApply Class

Save Overload

Lsa.Vmfg.Financials Namespace

CreditMemoApply.Save Method (Stream)

Save current state of data set to stream. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Save(
    Stream stream
)
```

VB

```
Public Overridable Sub Save (
    stream As Stream
)
```

Parameters

stream

Type: System.IO.Stream

See Also

CreditMemoApply Class

Save Overload

Lsa.Vmfg.Financials Namespace

GLInterfaceAccounts Class

Maintain General Ledger Interface Accounts

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessDocument
          Lsa.Vmfg.Financials.GLInterfaceAccounts

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class GLInterfaceAccounts : BusinessDocument
```

VB

```
<SerializableAttribute>
Public Class GLInterfaceAccounts
    Inherits BusinessDocument
```

The **GLInterfaceAccounts** type exposes the following members.

Constructors

	Name	Description
	GLInterfaceAccounts()	Constructor

	GLInterfaceAccounts(String)	Constructor

Methods

	Name	Description
	Browse(String, String, String)	Retrieve GL Interface Accounts based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve GL Interface Accounts based on search criteria, limit record count based on maxRecords.
	Exists	Determines if a specific GL Interface Account exists.
	Find	Loads a specific GL Interface Account.
	Load(String)	Loads all GL Interface Accounts for a specific Entity
	Load(Stream, String)	Load from stream and rename using new key.
	LoadBySite	Loads All GL Interface Accounts for a specific Site
	NewGLInterfaceAccountRow	Inserts a new row into the GL_INTERFACE_ACCT table for a specific Entity.
	NewGLInterfaceAccountSiteRow	Inserts a new row into the GL_INTERFACE_ACCT table for a specfic Site.
	Save	Saves all changes to previously loaded GL Interface Accounts to the database.

Properties

	Name	Description
	DataObjectType	Report types of data object associated with this business object (Overrides **BusinessObject.DataObjectType**.)
	DeferredRevenueAcctID	Gets the Deferred Revenue Account ID
	InvMaterialAcctID	Gets the Inv Material Account ID
	PayableDutyAcctID	Gets the Payables Duty Account ID
	PayableVatAcctID	Gets the Payables VAT Account ID
	PayableVatRcvAcctID	Gets the Payables Vat Rcv Account ID
	POAccrualAcctID	Gets the PO Accrual Account ID
	POReturnExpAcctID	Gets the PO Return Expense Account ID
	POVarianceAcctID	Gets the PO Variance Account ID
	ReceivablesAcctID	Gets the Receivables Account ID
	RecvRevenueAcctID	Gets the Receivables Revenue Account ID
	RoundingAcctID	Gets the Rounding Account ID
	SalesCommExpenseAcctID	Gets the Sales Commissions Expense Account ID

See Also

Lsa.Vmfg.Financials Namespace

GLInterfaceAccounts Constructor

Overload List

	Name	Description
	GLInterfaceAccounts()	Constructor
	GLInterfaceAccounts(String)	Constructor

See Also

GLInterfaceAccounts Class

Lsa.Vmfg.Financials Namespace

GLInterfaceAccounts Constructor

Constructor

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public GLInterfaceAccounts()
```

VB

```
Public Sub New
```

See Also

GLInterfaceAccounts Class

GLInterfaceAccounts Overload

Lsa.Vmfg.Financials Namespace

GLInterfaceAccounts Constructor (String)

Constructor

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public GLInterfaceAccounts(
    string dataspaceName
)
```

VB

```
Public Sub New (
    dataspaceName As String
)
```

Parameters

dataspaceName

Type: System.String

See Also

GLInterfaceAccounts Class

GLInterfaceAccounts Overload

Lsa.Vmfg.Financials Namespace

GLInterfaceAccounts.GLInterfaceAccounts Methods

The GLInterfaceAccounts type exposes the following members.

Methods

	Name	Description
	Browse(String, String, String)	Retrieve GL Interface Accounts based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve GL Interface Accounts based on search criteria, limit record count based on maxRecords.
	Exists	Determines if a specific GL Interface Account exists.
	Find	Loads a specific GL Interface Account.
	Load(String)	Loads all GL Interface Accounts for a specific Entity
	Load(Stream, String)	Load from stream and rename using new key.
	LoadBySite	Loads All GL Interface Accounts for a specific Site
	NewGLInterfaceAccountRow	Inserts a new row into the GL_INTERFACE_ACCT table for a specific Entity.
	NewGLInterfaceAccountSiteRow	Inserts a new row into the GL_INTERFACE_ACCT table for a specfic Site.
	Save	Saves all changes to previously loaded GL Interface Accounts to the database.

See Also

GLInterfaceAccounts Class

Lsa.Vmfg.Financials Namespace

GLInterfaceAccounts.Browse Method

Overload List

	Name	Description
	Browse(String, String, String)	Retrieve GL Interface Accounts based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve GL Interface Accounts based on search criteria, limit record count based on maxRecords.

See Also

GLInterfaceAccounts Class

Lsa.Vmfg.Financials Namespace

GLInterfaceAccounts.Browse Method (String, String, String)

Retrieve GL Interface Accounts based on search criteria.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
    string columnNames,
    string searchCondition,
    string sortColumns
)
```

VB

```
Public Overridable Function Browse (
    columnNames As String,
    searchCondition As String,
    sortColumns As String
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

Return Value

Type: **DataSet**

See Also

GLInterfaceAccounts Class

Browse Overload

Lsa.Vmfg.Financials Namespace

GLInterfaceAccounts.Browse Method (String, String, String, Int32, Int32)

Retrieve GL Interface Accounts based on search criteria, limit record count based on maxRecords.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
    string columnNames,
    string searchCondition,
    string sortColumns,
    int startRecord,
    int maxRecords
)
```

VB

```
Public Overridable Function Browse (
    columnNames As String,
    searchCondition As String,
    sortColumns As String,
    startRecord As Integer,
    maxRecords As Integer
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

startRecord

Type: System.Int32

maxRecords

Type: System.Int32

Return Value

Type: **DataSet**

See Also

GLInterfaceAccounts Class

Browse Overload

Lsa.Vmfg.Financials Namespace

GLInterfaceAccounts.Exists Method

Determines if a specific GL Interface Account exists.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual bool Exists(
    string glInterfaceAcctID
)
```

VB

```
Public Overridable Function Exists (
    glInterfaceAcctID As String
) As Boolean
```

Parameters

glInterfaceAcctID

Type: System.String

Return Value

Type: Boolean

See Also

GLInterfaceAccounts Class

Lsa.Vmfg.Financials Namespace

GLInterfaceAccounts.Find Method

Loads a specific GL Interface Account.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Find(
    string glInterfaceAcctID
)
```

VB

```
Public Overridable Sub Find (
    glInterfaceAcctID As String
)
```

Parameters

glInterfaceAcctID

Type: System.String

See Also

GLInterfaceAccounts Class

Lsa.Vmfg.Financials Namespace

GLInterfaceAccounts.Load Method

Overload List

	Name	Description
	Load(String)	Loads all GL Interface Accounts for a specific Entity
	Load(Stream, String)	Load from stream and rename using new key.

See Also

GLInterfaceAccounts Class

Lsa.Vmfg.Financials Namespace

GLInterfaceAccounts.Load Method (String)

Loads all GL Interface Accounts for a specific Entity

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
    string entityID
)
```

VB

```
Public Overridable Sub Load (
    entityID As String
)
```

Parameters

entityID

Type: System.String

See Also

GLInterfaceAccounts Class

Load Overload

Lsa.Vmfg.Financials Namespace

GLInterfaceAccounts.Load Method (Stream, String)

Load from stream and rename using new key.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
    Stream stream,
    string entityID
)
```

VB

```
Public Overridable Sub Load (
    stream As Stream,
    entityID As String
)
```

Parameters

stream

Type: System.IO.Stream

entityID

Type: System.String

See Also

GLInterfaceAccounts Class

Load Overload

Lsa.Vmfg.Financials Namespace

GLInterfaceAccounts.LoadBySite Method

Loads All GL Interface Accounts for a specific Site

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void LoadBySite(
    string siteID
)
```

VB

```
Public Overridable Sub LoadBySite (
    siteID As String
)
```

Parameters

siteID

Type: System.String

See Also

GLInterfaceAccounts Class

Lsa.Vmfg.Financials Namespace

GLInterfaceAccounts.NewGLInterfaceAccountRow Method

Inserts a new row into the GL_INTERFACE_ACCT table for a specific Entity.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewGLInterfaceAccountRow(
    string entityID,
    string interfaceID
)
```

VB

```
Public Overridable Function NewGLInterfaceAccountRow (
    entityID As String,
    interfaceID As String
) As DataRow
```

Parameters

entityID

Type: System.String

interfaceID

Type: System.String

Return Value

Type: **DataRow**

See Also

GLInterfaceAccounts Class

Lsa.Vmfg.Financials Namespace

GLInterfaceAccounts.NewGLInterfaceAccountSiteRow Method

Inserts a new row into the GL_INTERFACE_ACCT table for a specfic Site.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewGLInterfaceAccountSiteRow(
    string siteID,
    string interfaceID
)
```

VB

```
Public Overridable Function NewGLInterfaceAccountSiteRow (
    siteID As String,
    interfaceID As String
) As DataRow
```

Parameters

siteID

Type: System.String

interfaceID

Type: System.String

Return Value

Type: **DataRow**

See Also

GLInterfaceAccounts Class

Lsa.Vmfg.Financials Namespace

GLInterfaceAccounts.Save Method

Saves all changes to previously loaded GL Interface Accounts to the database.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Save()
```

VB

```
Public Overridable Sub Save
```

See Also

GLInterfaceAccounts Class

Lsa.Vmfg.Financials Namespace

GLInterfaceAccounts.GLInterfaceAccounts Properties

The GLInterfaceAccounts type exposes the following members.

Properties

	Name	Description
	DataObjectType	Report types of data object associated with this business object (Overrides **BusinessObject.DataObjectType**.)
	DeferredRevenueAcctID	Gets the Deferred Revenue Account ID
	InvMaterialAcctID	Gets the Inv Material Account ID
	PayableDutyAcctID	Gets the Payables Duty Account ID
	PayableVatAcctID	Gets the Payables VAT Account ID
	PayableVatRcvAcctID	Gets the Payables Vat Rcv Account ID
	POAccrualAcctID	Gets the PO Accrual Account ID
	POReturnExpAcctID	Gets the PO Return Expense Account ID
	POVarianceAcctID	Gets the PO Variance Account ID
	ReceivablesAcctID	Gets the Receivables Account ID
	RecvRevenueAcctID	Gets the Receivables Revenue Account ID
	RoundingAcctID	Gets the Rounding Account ID
	SalesCommExpenseAcctID	Gets the Sales Commissions Expense Account ID

See Also

GLInterfaceAccounts Class

Lsa.Vmfg.Financials Namespace

GLInterfaceAccounts.DataObjectType Property

Report types of data object associated with this business object

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public override Type DataObjectType { get; }
```

VB

```
Public Overrides ReadOnly Property DataObjectType As Type
    Get
```

Property Value

Type: Type

See Also

GLInterfaceAccounts Class

Lsa.Vmfg.Financials Namespace

GLInterfaceAccounts.DeferredRevenueAcctID Property

Gets the Deferred Revenue Account ID

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public string DeferredRevenueAcctID { get; }
```

VB

```
Public ReadOnly Property DeferredRevenueAcctID As String
    Get
```

Property Value

Type: String

See Also

GLInterfaceAccounts Class

Lsa.Vmfg.Financials Namespace

GLInterfaceAccounts.InvMaterialAcctID Property

Gets the Inv Material Account ID

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public string InvMaterialAcctID { get; }
```

VB

```
Public ReadOnly Property InvMaterialAcctID As String
    Get
```

Property Value

Type: String

See Also

GLInterfaceAccounts Class

Lsa.Vmfg.Financials Namespace

GLInterfaceAccounts.PayableDutyAcctID Property

Gets the Payables Duty Account ID

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public string PayableDutyAcctID { get; }
```

VB

```
Public ReadOnly Property PayableDutyAcctID As String
    Get
```

Property Value

Type: String

See Also

GLInterfaceAccounts Class

Lsa.Vmfg.Financials Namespace

GLInterfaceAccounts.PayableVatAcctID Property

Gets the Payables VAT Account ID

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public string PayableVatAcctID { get; }
```

VB

```
Public ReadOnly Property PayableVatAcctID As String
    Get
```

Property Value

Type: String

See Also

GLInterfaceAccounts Class

Lsa.Vmfg.Financials Namespace

GLInterfaceAccounts.PayableVatRcvAcctID Property

Gets the Payables Vat Rcv Account ID

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public string PayableVatRcvAcctID { get; }
```

VB

```
Public ReadOnly Property PayableVatRcvAcctID As String
    Get
```

Property Value

Type: String

See Also

GLInterfaceAccounts Class

Lsa.Vmfg.Financials Namespace

GLInterfaceAccounts.POAccrualAcctID Property

Gets the PO Accrual Account ID

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public string POAccrualAcctID { get; }
```

VB

```
Public ReadOnly Property POAccrualAcctID As String
    Get
```

Property Value

Type: String

See Also

GLInterfaceAccounts Class

Lsa.Vmfg.Financials Namespace

GLInterfaceAccounts.POReturnExpAcctID Property

Gets the PO Return Expense Account ID

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public string POReturnExpAcctID { get; }
```

VB

```
Public ReadOnly Property POReturnExpAcctID As String
    Get
```

Property Value

Type: String

See Also

GLInterfaceAccounts Class

Lsa.Vmfg.Financials Namespace

GLInterfaceAccounts.POVarianceAcctID Property

Gets the PO Variance Account ID

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public string POVarianceAcctID { get; }
```

VB

```
Public ReadOnly Property POVarianceAcctID As String
    Get
```

Property Value

Type: String

See Also

GLInterfaceAccounts Class

Lsa.Vmfg.Financials Namespace

GLInterfaceAccounts.ReceivablesAcctID Property

Gets the Receivables Account ID

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public string ReceivablesAcctID { get; }
```

VB

```
Public ReadOnly Property ReceivablesAcctID As String
    Get
```

Property Value

Type: String

See Also

GLInterfaceAccounts Class

Lsa.Vmfg.Financials Namespace

GLInterfaceAccounts.RecvRevenueAcctID Property

Gets the Receivables Revenue Account ID

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public string RecvRevenueAcctID { get; }
```

VB

```
Public ReadOnly Property RecvRevenueAcctID As String
    Get
```

Property Value

Type: String

See Also

GLInterfaceAccounts Class

Lsa.Vmfg.Financials Namespace

GLInterfaceAccounts.RoundingAcctID Property

Gets the Rounding Account ID

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public string RoundingAcctID { get; }
```

VB

```
Public ReadOnly Property RoundingAcctID As String
    Get
```

Property Value

Type: String

See Also

GLInterfaceAccounts Class

Lsa.Vmfg.Financials Namespace

GLInterfaceAccounts.SalesCommExpenseAcctID Property

Gets the Sales Commissions Expense Account ID

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public string SalesCommExpenseAcctID { get; }
```

VB

```
Public ReadOnly Property SalesCommExpenseAcctID As String
    Get
```

Property Value

Type: String

See Also

GLInterfaceAccounts Class

Lsa.Vmfg.Financials Namespace

SFPayables Class

Maintain Standard Financials Payables

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessDocument
          Lsa.Vmfg.Financials.SFPayables

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class SFPayables : BusinessDocument
```

VB

```
<SerializableAttribute>
Public Class SFPayables
    Inherits BusinessDocument
```

The **SFPayables** type exposes the following members.

Constructors

	Name	Description
	SFPayables()	Business Document Constructor

	SFPayables(String)	Business Document Constructor

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Payables based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Payables based on search criteria, limited by maxRecords.
	Exists	Determines if a specific Payable exists.
	Find	Retrieves a specific Payable. Only the top-level data table (PAYABLE) is returned.
	Load(String)	Loads a specific Payable
	Load(Stream, String)	Loads from stream and rename using new key.
	NewPayableLineRow(String)	Inserts a new row into the PAYABLE_LINE data table, assigning the next available line number. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.
	NewPayableLineRow(String, Int32)	Inserts a new row into the PAYABLE_LINE data table. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.
	NewPayableRow	Inserts a new row into the PAYABLE data table. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.
	Save	Save changes made to a previously loaded Payble to the database. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.

See Also

Lsa.Vmfg.Financials Namespace

SFPayables Constructor

Overload List

	Name	Description
	SFPayables()	Business Document Constructor
	SFPayables(String)	Business Document Constructor

See Also

SFPayables Class

Lsa.Vmfg.Financials Namespace

SFPayables Constructor

Business Document Constructor

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public SFPayables()

VB
Public Sub New

See Also

SFPayables Class

SFPayables Overload

Lsa.Vmfg.Financials Namespace

SFPayables Constructor (String)

Business Document Constructor

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public SFPayables(
    string databaseInstanceName
)
```

VB

```
Public Sub New (
    databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

SFPayables Class

SFPayables Overload

Lsa.Vmfg.Financials Namespace

SFPayables.SFPayables Methods

The SFPayables type exposes the following members.

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Payables based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Payables based on search criteria, limited by maxRecords.
	Exists	Determines if a specific Payable exists.
	Find	Retrieves a specific Payable. Only the top-level data table (PAYABLE) is returned.
	Load(String)	Loads a specific Payable
	Load(Stream, String)	Loads from stream and rename using new key.
	NewPayableLineRow(String)	Inserts a new row into the PAYABLE_LINE data table, assigning the next available line number. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.
	NewPayableLineRow(String, Int32)	Inserts a new row into the PAYABLE_LINE data table. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.
	NewPayableRow	Inserts a new row into the PAYABLE data table. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.
	Save	Save changes made to a previously loaded Payble to the database. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.

See Also

SFPayables Class

Lsa.Vmfg.Financials Namespace

SFPayables.Browse Method

Overload List

	Name	Description
	Browse(String, String, String)	Retrieve Payables based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Payables based on search criteria, limited by maxRecords.

See Also

SFPayables Class

Lsa.Vmfg.Financials Namespace

SFPayables.Browse Method (String, String, String)

Retrieve Payables based on search criteria.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
    string columnNames,
    string searchCondition,
    string sortColumns
)
```

VB

```
Public Overridable Function Browse (
    columnNames As String,
    searchCondition As String,
    sortColumns As String
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

Return Value

Type: **DataSet**

See Also

SFPayables Class

Browse Overload

Lsa.Vmfg.Financials Namespace

SFPayables.Browse Method (String, String, String, Int32, Int32)

Retrieve Payables based on search criteria, limited by maxRecords.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
    string columnNames,
    string searchCondition,
    string sortColumns,
    int startRecord,
    int maxRecords
)
```

VB

```
Public Overridable Function Browse (
    columnNames As String,
    searchCondition As String,
    sortColumns As String,
    startRecord As Integer,
    maxRecords As Integer
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

startRecord

Type: System.Int32

maxRecords

Type: System.Int32

Return Value

Type: **DataSet**

See Also

SFPayables Class

Browse Overload

Lsa.Vmfg.Financials Namespace

SFPayables.Exists Method

Determines if a specific Payable exists.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual bool Exists(
    string voucherID
)
```

VB

```
Public Overridable Function Exists (
    voucherID As String
) As Boolean
```

Parameters

voucherID

Type: System.String

Return Value

Type: Boolean

See Also

SFPayables Class

Lsa.Vmfg.Financials Namespace

SFPayables.Find Method

Retrieves a specific Payable. Only the top-level data table (PAYABLE) is returned.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Find(
    string voucherID
)
```

VB

```
Public Overridable Sub Find (
    voucherID As String
)
```

Parameters

voucherID

Type: System.String

See Also

SFPayables Class

Lsa.Vmfg.Financials Namespace

SFPayables.Load Method

Overload List

	Name	Description
	Load(String)	Loads a specific Payable
	Load(Stream, String)	Loads from stream and rename using new key.

See Also

SFPayables Class

Lsa.Vmfg.Financials Namespace

SFPayables.Load Method (String)

Loads a specific Payable

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
    string voucherID
)
```

VB

```
Public Overridable Sub Load (
    voucherID As String
)
```

Parameters

voucherID

Type: System.String

See Also

SFPayables Class

Load Overload

Lsa.Vmfg.Financials Namespace

SFPayables.Load Method (Stream, String)

Loads from stream and rename using new key.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
    Stream stream,
    string voucherID
)
```

VB

```
Public Overridable Sub Load (
    stream As Stream,
    voucherID As String
)
```

Parameters

stream

Type: System.IO.Stream

voucherID

Type: System.String

See Also

SFPayables Class

Load Overload

Lsa.Vmfg.Financials Namespace

SFPayables.NewPayableLineRow Method

Overload List

	Name	Description
	NewPayableLineRow(String)	Inserts a new row into the PAYABLE_LINE data table, assigning the next available line number. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.
	NewPayableLineRow(String, Int32)	Inserts a new row into the PAYABLE_LINE data table. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.

See Also

SFPayables Class

Lsa.Vmfg.Financials Namespace

SFPayables.NewPayableLineRow Method (String)

Inserts a new row into the PAYABLE_LINE data table, assigning the next available line number. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewPayableLineRow(
    string voucherID
)
```

VB

```
Public Overridable Function NewPayableLineRow (
    voucherID As String
) As DataRow
```

Parameters

voucherID

Type: System.String

Return Value

Type: **DataRow**

See Also

SFPayables Class

NewPayableLineRow Overload

Lsa.Vmfg.Financials Namespace

SFPayables.NewPayableLineRow Method (String, Int32)

Inserts a new row into the PAYABLE_LINE data table. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewPayableLineRow(
    string voucherID,
    int lineNo
)
```

VB

```
Public Overridable Function NewPayableLineRow (
    voucherID As String,
    lineNo As Integer
) As DataRow
```

Parameters

voucherID

Type: System.String

lineNo

Type: System.Int32

Return Value

Type: **DataRow**

See Also

SFPayables Class

NewPayableLineRow Overload

Lsa.Vmfg.Financials Namespace

SFPayables.NewPayableRow Method

Inserts a new row into the PAYABLE data table. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewPayableRow(
    string voucherID
)
```

VB

```
Public Overridable Function NewPayableRow (
    voucherID As String
) As DataRow
```

Parameters

voucherID

Type: System.String

Return Value

Type: **DataRow**

See Also

SFPayables Class

Lsa.Vmfg.Financials Namespace

SFPayables.Save Method

Save changes made to a previously loaded Payble to the database. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Save()
```

VB

```
Public Overridable Sub Save
```

See Also

SFPayables Class

Lsa.Vmfg.Financials Namespace

SFReceivables Class

Maintain Standard Financials SFReceivables.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessDocument
          Lsa.Vmfg.Financials.SFReceivables

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class SFReceivables : BusinessDocument
```

VB

```
<SerializableAttribute>
Public Class SFReceivables
    Inherits BusinessDocument
```

The **SFReceivables** type exposes the following members.

Constructors

	Name	Description
	SFReceivables()	Data Document Constructor

	SFReceivables(String)	Data Document Constructor

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Receivables, based on a search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Receivables based on a search criteria, and limited by maxRecords.
	Exists	Determines if a specific Receivable exists.
	Find	Retrieves a specific Receivable. Only the top level data table (RECEIVABLE) is returned.
	Load(String)	Loads a specific Receivable.
	Load(Stream, String)	Load from stream and rename using new key.
	NewReceivableLineRow(String)	Inserts a new row into the RECEIVABLE_LINE data table, assigning the next available line number. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.
	NewReceivableLineRow(String, Int32)	Inserts a new row into the RECEIVABLE_LINE data table. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.
	NewReceivableRow(String)	Inserts a new row into the RECEIVABLE data table. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.
	NewReceivableRow(String, String, String)	Inserts a new row into the RECEIVABLE data table for a specific Site and Customer. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.

	Save	Saves all changes made to a previously loaded Receivables to the database. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.

See Also

Lsa.Vmfg.Financials Namespace

SFReceivables Constructor

Overload List

	Name	Description
	SFReceivables()	Data Document Constructor
	SFReceivables(String)	Data Document Constructor

See Also

SFReceivables Class

Lsa.Vmfg.Financials Namespace

SFReceivables Constructor

Data Document Constructor

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public SFReceivables()
```

VB

```
Public Sub New
```

See Also

SFReceivables Class

SFReceivables Overload

Lsa.Vmfg.Financials Namespace

SFReceivables Constructor (String)

Data Document Constructor

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public SFReceivables(
    string databaseInstanceName
)
```

VB

```
Public Sub New (
    databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

SFReceivables Class

SFReceivables Overload

Lsa.Vmfg.Financials Namespace

SFReceivables.SFReceivables Methods

The SFReceivables type exposes the following members.

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Receivables, based on a search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Receivables based on a search criteria, and limited by maxRecords.
	Exists	Determines if a specific Receivable exists.
	Find	Retrieves a specific Receivable. Only the top level data table (RECEIVABLE) is returned.
	Load(String)	Loads a specific Receivable.
	Load(Stream, String)	Load from stream and rename using new key.
	NewReceivableLineRow(String)	Inserts a new row into the RECEIVABLE_LINE data table, assigning the next available line number. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.
	NewReceivableLineRow(String, Int32)	Inserts a new row into the RECEIVABLE_LINE data table. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.
	NewReceivableRow(String)	Inserts a new row into the RECEIVABLE data table. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.
	NewReceivableRow(String, String, String)	Inserts a new row into the RECEIVABLE data table for a specific Site and Customer. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.

	Save	Saves all changes made to a previously loaded Receivables to the database. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.

See Also

SFReceivables Class

Lsa.Vmfg.Financials Namespace

SFReceivables.Browse Method

Overload List

	Name	Description
	Browse(String, String, String)	Retrieve Receivables, based on a search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Receivables based on a search criteria, and limited by maxRecords.

See Also

SFReceivables Class

Lsa.Vmfg.Financials Namespace

SFReceivables.Browse Method (String, String, String)

Retrieve Receivables, based on a search criteria.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
    string columnNames,
    string searchCondition,
    string sortColumns
)
```

VB

```
Public Overridable Function Browse (
    columnNames As String,
    searchCondition As String,
    sortColumns As String
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

Return Value

Type: **DataSet**

See Also

SFReceivables Class

Browse Overload

Lsa.Vmfg.Financials Namespace

SFReceivables.Browse Method (String, String, String, Int32, Int32)

Retrieve Receivables based on a search criteria, and limited by maxRecords.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
    string columnNames,
    string searchCondition,
    string sortColumns,
    int startRecord,
    int maxRecords
)
```

VB

```
Public Overridable Function Browse (
    columnNames As String,
    searchCondition As String,
    sortColumns As String,
    startRecord As Integer,
    maxRecords As Integer
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

startRecord

Type: System.Int32

maxRecords

Type: System.Int32

Return Value

Type: **DataSet**

See Also

SFReceivables Class

Browse Overload

Lsa.Vmfg.Financials Namespace

SFReceivables.Exists Method

Determines if a specific Receivable exists.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual bool Exists(
    string invoiceID
)
```

VB

```
Public Overridable Function Exists (
    invoiceID As String
) As Boolean
```

Parameters

invoiceID

Type: System.String

Return Value

Type: Boolean

See Also

SFReceivables Class

Lsa.Vmfg.Financials Namespace

SFReceivables.Find Method

Retrieves a specific Receivable. Only the top level data table (RECEIVABLE) is returned.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Find(
    string invoiceID
)
```

VB

```
Public Overridable Sub Find (
    invoiceID As String
)
```

Parameters

invoiceID

Type: System.String

See Also

SFReceivables Class

Lsa.Vmfg.Financials Namespace

SFReceivables.Load Method

Overload List

	Name	Description
	Load(String)	Loads a specific Receivable.
	Load(Stream, String)	Load from stream and rename using new key.

See Also

SFReceivables Class

Lsa.Vmfg.Financials Namespace

SFReceivables.Load Method (String)

Loads a specific Receivable.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
    string invoiceID
)
```

VB

```
Public Overridable Sub Load (
    invoiceID As String
)
```

Parameters

invoiceID

Type: System.String

See Also

SFReceivables Class

Load Overload

Lsa.Vmfg.Financials Namespace

SFReceivables.Load Method (Stream, String)

Load from stream and rename using new key.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
    Stream stream,
    string invoiceID
)
```

VB

```
Public Overridable Sub Load (
    stream As Stream,
    invoiceID As String
)
```

Parameters

stream

Type: System.IO.Stream

invoiceID

Type: System.String

See Also

SFReceivables Class

Load Overload

Lsa.Vmfg.Financials Namespace

SFReceivables.NewReceivableLineRow Method

Overload List

	Name	Description
	NewReceivableLineRow(String)	Inserts a new row into the RECEIVABLE_LINE data table, assigning the next available line number. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.
	NewReceivableLineRow(String, Int32)	Inserts a new row into the RECEIVABLE_LINE data table. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.

See Also

SFReceivables Class

Lsa.Vmfg.Financials Namespace

SFReceivables.NewReceivableLineRow Method (String)

Inserts a new row into the RECEIVABLE_LINE data table, assigning the next available line number. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewReceivableLineRow(
    string invoiceID
)
```

VB

```
Public Overridable Function NewReceivableLineRow (
    invoiceID As String
) As DataRow
```

Parameters

invoiceID

Type: System.String

Return Value

Type: **DataRow**

See Also

SFReceivables Class

NewReceivableLineRow Overload

Lsa.Vmfg.Financials Namespace

SFReceivables.NewReceivableLineRow Method (String, Int32)

Inserts a new row into the RECEIVABLE_LINE data table. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewReceivableLineRow(
    string invoiceID,
    int lineNo
)
```

VB

```
Public Overridable Function NewReceivableLineRow (
    invoiceID As String,
    lineNo As Integer
) As DataRow
```

Parameters

invoiceID

Type: System.String

lineNo

Type: System.Int32

Return Value

Type: **DataRow**

See Also

SFReceivables Class

NewReceivableLineRow Overload

Lsa.Vmfg.Financials Namespace

SFReceivables.NewReceivableRow Method

Overload List

	Name	Description
	NewReceivableRow(String)	Inserts a new row into the RECEIVABLE data table. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.
	NewReceivableRow(String, String, String)	Inserts a new row into the RECEIVABLE data table for a specific Site and Customer. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.

See Also

SFReceivables Class

Lsa.Vmfg.Financials Namespace

SFReceivables.NewReceivableRow Method (String)

Inserts a new row into the RECEIVABLE data table. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewReceivableRow(
    string invoiceID
)
```

VB

```
Public Overridable Function NewReceivableRow (
    invoiceID As String
) As DataRow
```

Parameters

invoiceID

Type: System.String

Return Value

Type: **DataRow**

See Also

SFReceivables Class

NewReceivableRow Overload

Lsa.Vmfg.Financials Namespace

SFReceivables.NewReceivableRow Method (String, String, String)

Inserts a new row into the RECEIVABLE data table for a specific Site and Customer. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewReceivableRow(
    string invoiceID,
    string siteID,
    string customerID
)
```

VB

```
Public Overridable Function NewReceivableRow (
    invoiceID As String,
    siteID As String,
    customerID As String
) As DataRow
```

Parameters

invoiceID

Type: System.String

siteID

Type: System.String

customerID

Type: System.String

Return Value

Type: **DataRow**

See Also

SFReceivables Class

NewReceivableRow Overload

Lsa.Vmfg.Financials Namespace

SFReceivables.Save Method

Saves all changes made to a previously loaded Receivables to the database. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.

Namespace: Lsa.Vmfg.Financials
Assembly: VmfgFinancials (in VmfgFinancials.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Save()
```

VB

```
Public Overridable Sub Save
```

See Also

SFReceivables Class

Lsa.Vmfg.Financials Namespace