Infor VISUAL API Toolkit Sales Class Library Reference

Copyright © 2024 Infor

Important Notices

The material contained in this publication (including any supplementary information) constitutes and contains confidential and proprietary information of Infor.

By gaining access to the attached, you acknowledge and agree that the material (including any modification, translation or adaptation of the material) and all copyright, trade secrets and all other right, title and interest therein, are the sole property of Infor and that you shall not gain right, title or interest in the material (including any modification, translation or adaptation of the material) by virtue of your review thereof other than the non-exclusive right to use the material solely in connection with and the furtherance of your license and use of software made available to your company from Infor pursuant to a separate agreement, the terms of which separate agreement shall govern your use of this material and all supplemental related materials ("Purpose").

In addition, by accessing the enclosed material, you acknowledge and agree that you are required to maintain such material in strict confidence and that your use of such material is limited to the Purpose described above. Although Infor has taken due care to ensure that the material included in this publication is accurate and complete, Infor cannot warrant that the information contained in this publication is complete, does not contain typographical or other errors, or will meet your specific requirements. As such, Infor does not assume and hereby disclaims all liability, consequential or otherwise, for any loss or damage to any person or entity which is caused by or relates to errors or omissions in this publication (including any supplementary information), whether such errors or omissions result from negligence, accident or any other cause.

Without limitation, U.S. export control laws and other applicable export and import laws govern your use of this material and you will neither export or re-export, directly or indirectly, this material nor any related materials or supplemental information in violation of such laws, or use such materials for any purpose prohibited by such laws.

Trademark Acknowledgements

The word and design marks set forth herein are trademarks and/or registered trademarks of Infor and/or related affiliates and subsidiaries. All rights reserved. All other company, product, trade or service names referenced may be registered trademarks or trademarks of their respective owners.

Publication Information

Release: Infor VISUAL API Toolkit

Publication date: August 13, 2024

About this guide

This guide describes the objects available in the Infor VISUAL API Toolkit Sales class library.

Intended audience

The intended audience of this guide is developers who are using the API Toolkit to extend the VISUAL solution.

Contacting Support

If you have questions about Infor products, go to the Infor Customer Portal at https://customerportal.infor.com/csmcore/

If we update this document after the product release, we will post the new version on this Web site. We recommend that you check this Web site periodically for updated documentation.

If you have comments about Infor documentation, contact https://docs.infor.com/en-us.

Supported languages

These languages are supported for use with the toolkit:

- Visual Basic
- C#

While it is possible to use any .NET-aware programming language with the toolkit, other languages are not officially supported.

Support information

The API Toolkit will be updated regularly as more class members are added to each assembly, schema changes are made, and any reported issues are resolved. Infor Support cannot assist you with developing customized code using the API Toolkit. For assistance with customizations, contact Infor Consulting Services or your channel partner.

The functionality provided within the API Toolkit will not be extended beyond the standard functionality experienced in the VISUAL application itself. Enhancement requests with compelling business cases detailing how suggested alternatives are not viable will be evaluated and considered.

Infor is not responsible for data incorrectly entered to the database through the use of the API Toolkit. Customers must establish a full test environment to ensure that data created by APIs functions in the same manner as data created through the VISUAL interface.

Lsa.Vmfg.Sales Namespace

Classes

	Class	Description
	BillOfLading	Bill Of Lading Maintenance.
	CopyOrder	Business Transaction to create Customer Orders from existing Orders.
	CopyQuote	Data Transaction to create Quotes from existing Quotes.
	Customer	Maintain Customers.
	CustomerDiscount	Maintain Customer Discounts.
	CustomerOrder	Maintain Customer Orders.
	CustomerPrice	Maintain Customer Prices.
	CustomerPriority	Maintain Customer Priority Codes.
	CustomerTypes	Maintain Customer Type Codes.
	CustOrderType	Maintain Customer Order Types.
	DemandSupplyLink	Maintain Demand Supply Links.
	DiscountPrices	Maintain Price Breaks for Discount Codes.
	OrderFromQuote	Transaction to create new Customer Orders from existing Quotes.
	Priority	Maintain Priority Codes.
	Quote	Maintain Quotes.
	Return	Transaction to perform returns on Customer Orders.
	ReturnMaterialAuth	Maintain Return Material Authorizations.
	SalesRep	Maintain Sales Reps.
	ServiceCharges	Maintain Service Charges.

	Shipment	Transaction to perform Shipments.
	Shipper	Maintain Shippers.
	ShipReason	Maintain Ship Reason Codes.
	ShipToAltWhs	Maintain Customer Ship to Alternate Warehouses.

SalesRep Class and Infor VISUAL Financials Global Edition

If a Financials Global Edition license has been applied to the VISUAL database you registered for use with APIs, then the SalesRep class is read-only.

BillOfLading Class

Bill Of Lading Maintenance.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessDocument
          Lsa.Vmfg.Sales.BillOfLading

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class BillOfLading : BusinessDocument
```

VB

```
<SerializableAttribute>
Public Class BillOfLading
        Inherits BusinessDocument
```

The **BillOfLading** type exposes the following members.

Constructors

	Name	Description
	BillOfLading()	Initializes a new instance of the **BillOfLading** class
	BillOfLading(String)	Initializes a new instance of the **BillOfLading** class

Methods

	Name	Description
	Browse(String, String, String)	Retrieves Bills Of Lading based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieves Bills Of Lading based on search criteria. Number of rows returned is limited by the value of the startRecord and maxRecords parameters.
	Exists	Checks for the existance of a Bill of Lading in the database.
	Find	Retrieves a Bill of Lading row from the database. Only the top-level table is retrieved.
	Load	Loads a Bill of Lading data document from the database.
	NewBillOfLadingLineRow	Adds a new row to the BOL_LINE table.
	NewBillOfLadingRow	Adds a new row to the BOL table.
	Save	Saves any changes made to a previously loaded Bill of Lading to the database.

See Also

Lsa.Vmfg.Sales Namespace

BillOfLading Constructor

Overload List

	Name	Description
	BillOfLading()	Initializes a new instance of the BillOfLading class
	BillOfLading(String)	Initializes a new instance of the BillOfLading class

See Also

BillOfLading Class
Lsa.Vmfg.Sales Namespace

BillOfLading Constructor

Initializes a new instance of the BillOfLading class

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public BillOfLading()

VB
Public Sub New

See Also

BillOfLading Class
BillOfLading Overload
Lsa.Vmfg.Sales Namespace

BillOfLading Constructor (String)

Initializes a new instance of the BillOfLading class

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public BillOfLading(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

BillOfLading Class

BillOfLading Overload

Lsa.Vmfg.Sales Namespace

BillOfLading.BillOfLading Methods

The BillOfLading type exposes the following members.

Methods

	Name	Description
	Browse(String, String, String)	Retrieves Bills Of Lading based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieves Bills Of Lading based on search criteria. Number of rows returned is limited by the value of the startRecord and maxRecords parameters.
	Exists	Checks for the existance of a Bill of Lading in the database.
	Find	Retrieves a Bill of Lading row from the database. Only the top-level table is retrieved.
	Load	Loads a Bill of Lading data document from the database.
	NewBillOfLadingLineRow	Adds a new row to the BOL_LINE table.
	NewBillOfLadingRow	Adds a new row to the BOL table.
	Save	Saves any changes made to a previously loaded Bill of Lading to the database.

See Also

BillOfLading Class

Lsa.Vmfg.Sales Namespace

BillOfLading.Browse Method

Overload List

	Name	Description
	Browse(String, String, String)	Retrieves Bills Of Lading based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieves Bills Of Lading based on search criteria. Number of rows returned is limited by the value of the startRecord and maxRecords parameters.

See Also

BillOfLading Class

Lsa.Vmfg.Sales Namespace

BillOfLading.Browse Method (String, String, String)

Retrieves Bills Of Lading based on search criteria.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

Return Value

Type: **DataSet**

See Also

BillOfLading Class

Browse Overload
Lsa.Vmfg.Sales Namespace

BillOfLading.Browse Method (String, String, String, Int32, Int32)

Retrieves Bills Of Lading based on search criteria. Number of rows returned is limited by the value of the startRecord and maxRecords parameters.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns,
        int startRecord,
        int maxRecords
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String,
        startRecord As Integer,
        maxRecords As Integer
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

startRecord

Type: System.Int32

maxRecords

Type: System.Int32

Return Value

Type: **DataSet**

See Also

BillOfLading Class
Browse Overload
Lsa.Vmfg.Sales Namespace

BillOfLading.Exists Method

Checks for the existance of a Bill of Lading in the database.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual bool Exists(
        string billOfLadingID
)
```

VB

```
Public Overridable Function Exists (
        billOfLadingID As String
) As Boolean
```

Parameters

billOfLadingID

Type: System.String

Return Value

Type: Boolean

See Also

BillOfLading Class

Lsa.Vmfg.Sales Namespace

BillOfLading.Find Method

Retrieves a Bill of Lading row from the database. Only the top-level table is retrieved.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Find(
        string billOfLadingID
)
```

VB

```
Public Overridable Sub Find (
        billOfLadingID As String
)
```

Parameters

billOfLadingID

Type: System.String

See Also

BillOfLading Class

Lsa.Vmfg.Sales Namespace

BillOfLading.Load Method

Loads a Bill of Lading data document from the database.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string billOfLadingID
)
```

VB

```
Public Overridable Sub Load (
        billOfLadingID As String
)
```

Parameters

billOfLadingID

Type: System.String

See Also

BillOfLading Class

Lsa.Vmfg.Sales Namespace

BillOfLading.NewBillOfLadingLineRow Method

Adds a new row to the BOL_LINE table.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewBillOfLadingLineRow(
        string billOfLadingID,
        string nMFCCodeID,
        string packageType
)
```

VB

```
Public Overridable Function NewBillOfLadingLineRow (
        billOfLadingID As String,
        nMFCCodeID As String,
        packageType As String
) As DataRow
```

Parameters

billOfLadingID

Type: System.String

nMFCCodeID

Type: System.String

packageType

Type: System.String

Return Value

Type: **DataRow**

See Also

BillOfLading Class

Lsa.Vmfg.Sales Namespace

BillOfLading.NewBillOfLadingRow Method

Adds a new row to the BOL table.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewBillOfLadingRow(
        string billOfLadingID
)
```

VB

```
Public Overridable Function NewBillOfLadingRow (
        billOfLadingID As String
) As DataRow
```

Parameters

billOfLadingID

Type: System.String

Return Value

Type: **DataRow**

See Also

BillOfLading Class

Lsa.Vmfg.Sales Namespace

BillOfLading.Save Method

Saves any changes made to a previously loaded Bill of Lading to the database.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

BillOfLading Class
Lsa.Vmfg.Sales Namespace

CopyOrder Class

Business Transaction to create Customer Orders from existing Orders.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessTransaction
          Lsa.Vmfg.Sales.CopyOrder

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class CopyOrder : BusinessTransaction
```

VB

```
<SerializableAttribute>
Public Class CopyOrder
        Inherits BusinessTransaction
```

The **CopyOrder** type exposes the following members.

Constructors

	Name	Description
	CopyOrder()	Constructor
	CopyOrder(String)	Constructor

Methods

	Name	Description
	NewCopyOrderRow	Inserts a new row into the previously prepared CopyOrder DataSet.
	Prepare	Creates an empty dataset for the transaction. You must populate the prepared dataset prior to saving the transaction.
	Save	Saves the transaction(s) to the database.

Transaction

	Name	Data set returned by Prepare	Description
	CopyOrder	COPY_ORDER	This transaction will create a new Customer Order from an existing Customer Order.

See Also

Lsa.Vmfg.Sales Namespace

CopyOrder Constructor

Overload List

	Name	Description
	CopyOrder()	Constructor
	CopyOrder(String)	Constructor

See Also

CopyOrder Class
Lsa.Vmfg.Sales Namespace

CopyOrder Constructor

Constructor

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public CopyOrder()

VB
Public Sub New

See Also

CopyOrder Class
CopyOrder Overload
Lsa.Vmfg.Sales Namespace

CopyOrder Constructor (String)

Constructor

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public CopyOrder(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

CopyOrder Class

CopyOrder Overload

Lsa.Vmfg.Sales Namespace

CopyOrder.CopyOrder Methods

The CopyOrder type exposes the following members.

Methods

	Name	Description
	NewCopyOrderRow	Inserts a new row into the previously prepared CopyOrder DataSet.
	Prepare	Creates an empty dataset for the transaction. You must populate the prepared dataset prior to saving the transaction.
	Save	Saves the transaction(s) to the database.

See Also

CopyOrder Class

Lsa.Vmfg.Sales Namespace

CopyOrder.NewCopyOrderRow Method

Inserts a new row into the previously prepared CopyOrder DataSet.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewCopyOrderRow(
        string sourceOrderID
)
```

VB

```
Public Overridable Function NewCopyOrderRow (
        sourceOrderID As String
) As DataRow
```

Parameters

sourceOrderID

Type: System.String

Return Value

Type: **DataRow**

See Also

CopyOrder Class

Lsa.Vmfg.Sales Namespace

CopyOrder.Prepare Method

Creates an empty dataset for the transaction. You must populate the prepared dataset prior to saving the transaction.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Prepare()

VB
Public Overridable Sub Prepare

See Also

CopyOrder Class
Lsa.Vmfg.Sales Namespace

CopyOrder.Save Method

Saves the transaction(s) to the database.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

CopyOrder Class
Lsa.Vmfg.Sales Namespace

CopyOrder

This transaction will create a new Customer Order from an existing Customer Order.

Namespace: Lsa.Vmfg.Sales

Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

DataSet name returned from Prepare: COPY_ORDER

Primary Key: SOURCE_ORDER_ID

Column Name	Type	Description
SOURCE_ORDER_ID	String	The ID of the Customer Order that will be the source of the copy.
COPY_COMM_SHARING	Boolean	Boolean flag to indicate whether the sales commission sharing information from the source order will be carried over to the target order. Default value is false.
COPY_LINE_ITEMS	Boolean	Boolean flag to indicate whether the line item details from the source order will be carried over to the target order. Default value is false.
COPY_DEL_SCHED	Boolean	Boolean flag to indicate whether the line item delivery schedule details from the source order will be carried over to the target order. Default value is false.
TARGET_ORDER_ID	String	ID of the Customer Order being created. If left blank, the new order will be auto numbered.
TARGET_ORDER_STATUS	String	Specifies the status of the newly created order.

See Also

CopyOrder Class

Lsa.Vmfg.Sales Namespace

CopyQuote Class

Data Transaction to create Quotes from existing Quotes.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessTransaction
          Lsa.Vmfg.Sales.CopyQuote

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class CopyQuote : BusinessTransaction
```

VB

```
<SerializableAttribute>
Public Class CopyQuote
        Inherits BusinessTransaction
```

The **CopyQuote** type exposes the following members.

Constructors

	Name	Description
	CopyQuote()	Constructor
	CopyQuote(String)	Constructor

Methods

	Name	Description
	NewCopyQuoteRow	Inserts a new row into the previously prepared CopyQuote DataSet.
	Prepare	Creates an empty dataset for the transaction. You must populate the prepared dataset prior to saving the transaction.
	Save	Saves the transaction(s) to the database.

Transaction

	Name	Data set returned by Prepare	Description
	CopyQuote	COPY_QUOTE	This transaction will create a new Quote from an existing Quote.

See Also

Lsa.Vmfg.Sales Namespace

CopyQuote Constructor

Overload List

	Name	Description
	CopyQuote()	Constructor
	CopyQuote(String)	Constructor

See Also

CopyQuote Class
Lsa.Vmfg.Sales Namespace

CopyQuote Constructor

Constructor

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public CopyQuote()

VB
Public Sub New

See Also

CopyQuote Class
CopyQuote Overload
Lsa.Vmfg.Sales Namespace

CopyQuote Constructor (String)

Constructor

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public CopyQuote(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

CopyQuote Class

CopyQuote Overload

Lsa.Vmfg.Sales Namespace

CopyQuote.CopyQuote Methods

The CopyQuote type exposes the following members.

Methods

	Name	Description
	NewCopyQuoteRow	Inserts a new row into the previously prepared CopyQuote DataSet.
	Prepare	Creates an empty dataset for the transaction. You must populate the prepared dataset prior to saving the transaction.
	Save	Saves the transaction(s) to the database.

See Also

CopyQuote Class

Lsa.Vmfg.Sales Namespace

CopyQuote.NewCopyQuoteRow Method

Inserts a new row into the previously prepared CopyQuote DataSet.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewCopyQuoteRow(
        string quoteID
)
```

VB

```
Public Overridable Function NewCopyQuoteRow (
        quoteID As String
) As DataRow
```

Parameters

quoteID

Type: System.String

Return Value

Type: **DataRow**

See Also

CopyQuote Class

Lsa.Vmfg.Sales Namespace

CopyQuote.Prepare Method

Creates an empty dataset for the transaction. You must populate the prepared dataset prior to saving the transaction.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Prepare()

VB
Public Overridable Sub Prepare

See Also

CopyQuote Class
Lsa.Vmfg.Sales Namespace

CopyQuote.Save Method

Saves the transaction(s) to the database.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

CopyQuote Class
Lsa.Vmfg.Sales Namespace

CopyQuote

This transaction will create a new Quote from an existing Quote.

Namespace: Lsa.Vmfg.Sales

Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

DataSet name returned from Prepare: COPY_QUOTE

Primary Key: SOURCE_ORDER_ID

Column Name	Type	Description
SOURCE_QUOTE_ID	String	The ID of the Quote that will be the source of the copy.
COPY_LINE_PRICES	Boolean	Boolean flag to indicate whether the quoted prices information from the source order will be carried over to the target quote. Default value is false.
COPY_LINE_ITEMS	Boolean	Boolean flag to indicate whether the line item details from the source quote will be carried over to the target quote. Default value is false.
COPY_QUOTE_MASTERS	Boolean	Boolean flag to indicate whether the quote master (from the WORK_ORDER table) associated with the source quote will be created for the target quote. Default value is false.
TARGET_QUOTE_ID	String	ID of Quote being created. If left blank, the new quote will be auto numbered.
TARGET_QUOTE_STATUS	String	Specifies the status of the newly created quote.
SOURCE_QUOTE_STATUS	String	Optional. Allows the status of the source quote to be altered.

See Also

CopyQuote Class

CopyQuote.NewCopyQuoteRow

Lsa.Vmfg.Sales Namespace

Customer Class

Maintain Customers.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessDocument
          Lsa.Vmfg.Sales.Customer

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class Customer : BusinessDocument
```

VB

```
<SerializableAttribute>
Public Class Customer
        Inherits BusinessDocument
```

The **Customer** type exposes the following members.

Constructors

	Name	Description
	Customer()	Constructor
	Customer(String)	Constructor

Methods

	Name	Description
	Browse(String, String, String)	Retrieves Customers based on provided search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieves Customers based on provided search criteria and limited by startRecord and maxRecord parameters.
	Exists	Determine if a specific Customer exists in the database.
	Find	Retrieve a Customer using the key provided. Only the top-level table is retrieved.
	Load(String)	Loads a Customer.
	Load(Stream, String)	Load from stream and rename using new key.
	NewCustContactRow	Inserts a new row into the CUST_CONTACT table, assigning the next available contact number. Note: Use this method to link an existing contact from your master contact list to this customer. To add a new contact to your master contact list and link it to this customer, use the NewCustomerContactRow method.
	NewCustomerAddressRow	Inserts a new row into the CUST_ADDRESS table.
	NewCustomerBinaryRow	Inserts a new row into the CUSTOMER_BINARY table.
	NewCustomerContactRow	Inserts a new row into the CUSTOMER_CONTACT table with the next contact number available. Note: Use this method to add a new contact to your master contact list which in turn will be linked to this customer. To link an existing contact ID from your contact master to this customer, use the NewCustContactRow method.
	NewCustomerForecastRow(String, String, String, DateTime)	Inserts a new row into the CUSTOMER_FORECAST table.
	NewCustomerForecastRow(String, String, String, DateTime, String)	Inserts a new row into the CUSTOMER_FORECAST table.
	NewCustomerRow	Inserts a new row into the CUSTOMER table.
	Save()	Saves changes to previously loaded Customer(s) to the database.
	Save(Stream)	Save current state of dataset to stream.

See Also

Lsa.Vmfg.Sales Namespace

Customer Constructor

Overload List

	Name	Description
	Customer()	Constructor
	Customer(String)	Constructor

See Also

Customer Class
Lsa.Vmfg.Sales Namespace

Customer Constructor

Constructor

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public Customer()

VB
Public Sub New

See Also

Customer Class
Customer Overload
Lsa.Vmfg.Sales Namespace

Customer Constructor (String)

Constructor

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public Customer(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

Customer Class

Customer Overload

Lsa.Vmfg.Sales Namespace

Customer.Customer Methods

The Customer type exposes the following members.

Methods

	Name	Description
	Browse(String, String, String)	Retrieves Customers based on provided search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieves Customers based on provided search criteria and limited by startRecord and maxRecord parameters.
	Exists	Determine if a specific Customer exists in the database.
	Find	Retrieve a Customer using the key provided. Only the top-level table is retrieved.
	Load(String)	Loads a Customer.
	Load(Stream, String)	Load from stream and rename using new key.
	NewCustContactRow	Inserts a new row into the CUST_CONTACT table, assigning the next available contact number. Note: Use this method to link an existing contact from your master contact list to this customer. To add a new contact to your master contact list and link it to this customer, use the NewCustomerContactRow method.
	NewCustomerAddressRow	Inserts a new row into the CUST_ADDRESS table.
	NewCustomerBinaryRow	Inserts a new row into the CUSTOMER_BINARY table.
	NewCustomerContactRow	Inserts a new row into the CUSTOMER_CONTACT table with the next contact number available. Note: Use this method to add a new contact to your master contact list which in turn will be linked to this customer. To link an existing contact ID from your contact master to this customer, use the NewCustContactRow method.
	NewCustomerForecastRow(String, String, String, DateTime)	Inserts a new row into the CUSTOMER_FORECAST table.
	NewCustomerForecastRow(String, String, String, DateTime, String)	Inserts a new row into the CUSTOMER_FORECAST table.
	NewCustomerRow	Inserts a new row into the CUSTOMER table.

	Save()	Saves changes to previously loaded Customer(s) to the database.
	Save(Stream)	Save current state of dataset to stream.

See Also

Customer Class

Lsa.Vmfg.Sales Namespace

Customer.Browse Method

Overload List

	Name	Description
	Browse(String, String, String)	Retrieves Customers based on provided search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieves Customers based on provided search criteria and limited by startRecord and maxRecord parameters.

See Also

Customer Class

Lsa.Vmfg.Sales Namespace

Customer.Browse Method (String, String, String)

Retrieves Customers based on provided search criteria.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

Return Value

Type: **DataSet**

See Also

Customer Class

Browse Overload
Lsa.Vmfg.Sales Namespace

Customer.Browse Method (String, String, String, Int32, Int32)

Retrieves Customers based on provided search criteria and limited by startRecord and maxRecord parameters.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns,
        int startRecord,
        int maxRecords
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String,
        startRecord As Integer,
        maxRecords As Integer
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

startRecord

Type: System.Int32

maxRecords

Type: System.Int32

Return Value

Type: **DataSet**

See Also

Customer Class
Browse Overload
Lsa.Vmfg.Sales Namespace

Customer.Exists Method

Determine if a specific Customer exists in the database.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual bool Exists(
        string customerID
)
```

VB

```
Public Overridable Function Exists (
        customerID As String
) As Boolean
```

Parameters

customerID

Type: System.String

Return Value

Type: Boolean

See Also

Customer Class

Lsa.Vmfg.Sales Namespace

Customer.Find Method

Retrieve a Customer using the key provided. Only the top-level table is retrieved.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Find(
        string customerID
)
```

VB

```
Public Overridable Sub Find (
        customerID As String
)
```

Parameters

customerID

Type: System.String

See Also

Customer Class

Lsa.Vmfg.Sales Namespace

Customer.Load Method

Overload List

	Name	Description
	Load(String)	Loads a Customer.
	Load(Stream, String)	Load from stream and rename using new key.

See Also

Customer Class
Lsa.Vmfg.Sales Namespace

Customer.Load Method (String)

Loads a Customer.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string customerID
)
```

VB

```
Public Overridable Sub Load (
        customerID As String
)
```

Parameters

customerID

Type: System.String

See Also

Customer Class

Load Overload

Lsa.Vmfg.Sales Namespace

Customer.Load Method (Stream, String)

Load from stream and rename using new key.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        Stream stream,
        string customerID
)
```

VB

```
Public Overridable Sub Load (
        stream As Stream,
        customerID As String
)
```

Parameters

stream

Type: System.IO.Stream

customerID

Type: System.String

See Also

Customer Class

Load Overload

Lsa.Vmfg.Sales Namespace

Customer.NewCustContactRow Method

Inserts a new row into the CUST_CONTACT table, assigning the next available contact number. Note: Use this method to link an existing contact from your master contact list to this customer. To add a new contact to your master contact list and link it to this customer, use the NewCustomerContactRow method.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewCustContactRow(
        string contactID,
        string customerID
)
```

VB

```
Public Overridable Function NewCustContactRow (
        contactID As String,
        customerID As String
) As DataRow
```

Parameters

contactID

Type: System.String

customerID

Type: System.String

Return Value

Type: **DataRow**

See Also

Customer Class

Lsa.Vmfg.Sales Namespace

Customer.NewCustomerAddressRow Method

Inserts a new row into the CUST_ADDRESS table.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewCustomerAddressRow(
        string customerID,
        long lineNo
)
```

VB

```
Public Overridable Function NewCustomerAddressRow (
        customerID As String,
        lineNo As Long
) As DataRow
```

Parameters

customerID

Type: System.String

lineNo

Type: System.Int64

Return Value

Type: **DataRow**

See Also

Customer Class

Lsa.Vmfg.Sales Namespace

Customer.NewCustomerBinaryRow Method

Inserts a new row into the CUSTOMER_BINARY table.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewCustomerBinaryRow(
        string customerID,
        string binaryType
)
```

VB

```
Public Overridable Function NewCustomerBinaryRow (
        customerID As String,
        binaryType As String
) As DataRow
```

Parameters

customerID

Type: System.String

binaryType

Type: System.String

Return Value

Type: **DataRow**

Remarks

Only binary type "D" (long text) is currently supported.

See Also

Customer Class

Lsa.Vmfg.Sales Namespace

Customer.NewCustomerContactRow Method

Inserts a new row into the CUSTOMER_CONTACT table with the next contact number available. Note: Use this method to add a new contact to your master contact list which in turn will be linked to this customer. To link an existing contact ID from your contact master to this customer, use the NewCustContactRow method.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewCustomerContactRow(
        string customerID
)
```

VB

```
Public Overridable Function NewCustomerContactRow (
        customerID As String
) As DataRow
```

Parameters

customerID

Type: System.String

Return Value

Type: **DataRow**

See Also

Customer Class

Lsa.Vmfg.Sales Namespace

Customer.NewCustomerForecastRow Method

Overload List

	Name	Description
	NewCustomerForecastRow(String, String, String, DateTime)	Inserts a new row into the CUSTOMER_FORECAST table.
	NewCustomerForecastRow(String, String, String, DateTime, String)	Inserts a new row into the CUSTOMER_FORECAST table.

See Also

Customer Class

Lsa.Vmfg.Sales Namespace

Customer.NewCustomerForecastRow Method (String, String, String, DateTime)

Inserts a new row into the CUSTOMER_FORECAST table.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewCustomerForecastRow(
        string customerID,
        string forecastID,
        string partID,
        DateTime reqDate
)
```

VB

```
Public Overridable Function NewCustomerForecastRow (
        customerID As String,
        forecastID As String,
        partID As String,
        reqDate As DateTime
) As DataRow
```

Parameters

customerID

Type: System.String

forecastID

Type: System.String

partID

Type: System.String

reqDate

Type: System.DateTime

Return Value

Type: **DataRow**

Remarks

Use this function only if you are not forecasting by Warehouse ID.

See Also

Customer Class
NewCustomerForecastRow Overload
Lsa.Vmfg.Sales Namespace

Customer.NewCustomerForecastRow Method (String, String, String, DateTime, String)

Inserts a new row into the CUSTOMER_FORECAST table.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewCustomerForecastRow(
        string customerID,
        string forecastID,
        string partID,
        DateTime reqDate,
        string warehouseID
)
```

VB

```
Public Overridable Function NewCustomerForecastRow (
        customerID As String,
        forecastID As String,
        partID As String,
        reqDate As DateTime,
        warehouseID As String
) As DataRow
```

Parameters

customerID

Type: System.String

forecastID

Type: System.String

partID

Type: System.String

reqDate

Type: System.DateTime

warehouseID

Type: System.String

Return Value

Type: **DataRow**

Remarks

Use this function only if you are forecasting by Warehouse ID.

See Also

Customer Class
NewCustomerForecastRow Overload
Lsa.Vmfg.Sales Namespace

Customer.NewCustomerRow Method

Inserts a new row into the CUSTOMER table.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewCustomerRow(
        string customerID
)
```

VB

```
Public Overridable Function NewCustomerRow (
        customerID As String
) As DataRow
```

Parameters

customerID

Type: System.String

Return Value

Type: **DataRow**

See Also

Customer Class

Lsa.Vmfg.Sales Namespace

Customer.Save Method

Overload List

	Name	Description
	Save()	Saves changes to previously loaded Customer(s) to the database.
	Save(Stream)	Save current state of dataset to stream.

See Also

Customer Class
Lsa.Vmfg.Sales Namespace

Customer.Save Method

Saves changes to previously loaded Customer(s) to the database.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

Customer Class
Save Overload
Lsa.Vmfg.Sales Namespace

Customer.Save Method (Stream)

Save current state of dataset to stream.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Save(
        Stream stream
)
```

VB

```
Public Overridable Sub Save (
        stream As Stream
)
```

Parameters

stream

Type: System.IO.Stream

See Also

Customer Class

Save Overload

Lsa.Vmfg.Sales Namespace

CustomerDiscount Class

Maintain Customer Discounts.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessDocument
          Lsa.Vmfg.Sales.CustomerDiscount

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class CustomerDiscount : BusinessDocument
```

VB

```
<SerializableAttribute>
Public Class CustomerDiscount
        Inherits BusinessDocument
```

The **CustomerDiscount** type exposes the following members.

Constructors

	Name	Description
	CustomerDiscount()	Initializes a new instance of the **CustomerDiscount** class
	CustomerDiscount(String)	Initializes a new instance of the **CustomerDiscount** class

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Customer Discounts based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Customer Discounts information based on search criteria. This retrieves a limited range of data based on the startRecord and maxRecords parameters.
	Exists	Determine if a specific Customer Discount exists in the database.
	Find	Retrieve a specific Customer Discount.
	Load()	Retrieve all of the Customer Discounts from the database.
	Load(String)	Retrieve a specific Customer Discount from the database.
	Load(Stream, String)	Load from stream and rename using new key.
	NewCustomerDiscountRow	Adds a row to the CUSTOMER_DISCOUNT table.
	Save	Save All previously loaded Customer Discounts to the database.

See Also

Lsa.Vmfg.Sales Namespace

CustomerDiscount Constructor

Overload List

	Name	Description
	CustomerDiscount()	Initializes a new instance of the CustomerDiscount class
	CustomerDiscount(String)	Initializes a new instance of the CustomerDiscount class

See Also

CustomerDiscount Class
Lsa.Vmfg.Sales Namespace

CustomerDiscount Constructor

Initializes a new instance of the CustomerDiscount class

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public CustomerDiscount()

VB
Public Sub New

See Also

CustomerDiscount Class
CustomerDiscount Overload
Lsa.Vmfg.Sales Namespace

CustomerDiscount Constructor (String)

Initializes a new instance of the CustomerDiscount class

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public CustomerDiscount(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

CustomerDiscount Class

CustomerDiscount Overload

Lsa.Vmfg.Sales Namespace

CustomerDiscount.CustomerDiscount Methods

The CustomerDiscount type exposes the following members.

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Customer Discounts based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Customer Discounts information based on search criteria. This retrieves a limited range of data based on the startRecord and maxRecords parameters.
	Exists	Determine if a specific Customer Discount exists in the database.
	Find	Retrieve a specific Customer Discount.
	Load()	Retrieve all of the Customer Discounts from the database.
	Load(String)	Retrieve a specific Customer Discount from the database.
	Load(Stream, String)	Load from stream and rename using new key.
	NewCustomerDiscountRow	Adds a row to the CUSTOMER_DISCOUNT table.
	Save	Save All previously loaded Customer Discounts to the database.

See Also

CustomerDiscount Class

Lsa.Vmfg.Sales Namespace

CustomerDiscount.Browse Method

Overload List

	Name	Description
	Browse(String, String, String)	Retrieve Customer Discounts based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Customer Discounts information based on search criteria. This retrieves a limited range of data based on the startRecord and maxRecords parameters.

See Also

CustomerDiscount Class

Lsa.Vmfg.Sales Namespace

CustomerDiscount.Browse Method (String, String, String)

Retrieve Customer Discounts based on search criteria.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

Return Value

Type: **DataSet**

See Also

CustomerDiscount Class
Browse Overload
Lsa.Vmfg.Sales Namespace

CustomerDiscount.Browse Method (String, String, String, Int32, Int32)

Retrieve Customer Discounts information based on search criteria. This retrieves a limited range of data based on the startRecord and maxRecords parameters.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns,
        int startRecord,
        int maxRecords
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String,
        startRecord As Integer,
        maxRecords As Integer
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

startRecord

Type: System.Int32

maxRecords

Type: System.Int32

Return Value

Type: **DataSet**

See Also

CustomerDiscount Class
Browse Overload
Lsa.Vmfg.Sales Namespace

CustomerDiscount.Exists Method

Determine if a specific Customer Discount exists in the database.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual bool Exists(
        string discountCode
)
```

VB

```
Public Overridable Function Exists (
        discountCode As String
) As Boolean
```

Parameters

discountCode

Type: System.String

Return Value

Type: Boolean

See Also

CustomerDiscount Class

Lsa.Vmfg.Sales Namespace

CustomerDiscount.Find Method

Retrieve a specific Customer Discount.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Find(
        string discountCode
)
```

VB

```
Public Overridable Sub Find (
        discountCode As String
)
```

Parameters

discountCode

Type: System.String

See Also

CustomerDiscount Class

Lsa.Vmfg.Sales Namespace

CustomerDiscount.Load Method

Overload List

	Name	Description
	Load()	Retrieve all of the Customer Discounts from the database.
	Load(String)	Retrieve a specific Customer Discount from the database.
	Load(Stream, String)	Load from stream and rename using new key.

See Also

CustomerDiscount Class
Lsa.Vmfg.Sales Namespace

CustomerDiscount.Load Method

Retrieve all of the Customer Discounts from the database.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Load()

VB
Public Overridable Sub Load

See Also

CustomerDiscount Class
Load Overload
Lsa.Vmfg.Sales Namespace

CustomerDiscount.Load Method (String)

Retrieve a specific Customer Discount from the database.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string discountCode
)
```

VB

```
Public Overridable Sub Load (
        discountCode As String
)
```

Parameters

discountCode

Type: System.String

See Also

CustomerDiscount Class

Load Overload

Lsa.Vmfg.Sales Namespace

CustomerDiscount.Load Method (Stream, String)

Load from stream and rename using new key.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        Stream stream,
        string discountCode
)
```

VB

```
Public Overridable Sub Load (
        stream As Stream,
        discountCode As String
)
```

Parameters

stream

Type: System.IO.Stream

discountCode

Type: System.String

See Also

CustomerDiscount Class

Load Overload

Lsa.Vmfg.Sales Namespace

CustomerDiscount.NewCustomerDiscountRow Method

Adds a row to the CUSTOMER_DISCOUNT table.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public DataRow NewCustomerDiscountRow(
        string discountCode
)
```

VB

```
Public Function NewCustomerDiscountRow (
        discountCode As String
) As DataRow
```

Parameters

discountCode

Type: System.String

Return Value

Type: **DataRow**

See Also

CustomerDiscount Class

Lsa.Vmfg.Sales Namespace

CustomerDiscount.Save Method

Save All previously loaded Customer Discounts to the database.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

CustomerDiscount Class
Lsa.Vmfg.Sales Namespace

CustomerOrder Class

Maintain Customer Orders.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessDocument
          Lsa.Vmfg.Sales.CustomerOrder

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class CustomerOrder : BusinessDocument
```

VB

```
<SerializableAttribute>
Public Class CustomerOrder
        Inherits BusinessDocument
```

The **CustomerOrder** type exposes the following members.

Constructors

	Name	Description
	CustomerOrder()	Business Document Constructor
	CustomerOrder(String)	Business Document Constructor

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Customer Orders based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Customer Orders based on search criteria, and limited by the values in the startRecord and maxRecords parameters.
	Exists	Determines if a specific Customer Order exists.
	Find	Retrieve the specified Customer Order. Only returns the top-level data table (CUSTOMER_ORDER).
	Load(String)	Loads a specific Customer Order.
	Load(Stream, String)	Load from stream and rename using new key.
	NewCustLineBillingRow	Inserts a new row into the CUST_LINE_BILLING table.
	NewCustLineBinaryRow	Inserts a new row into the CUST_LINE_BINARY table. Only the binary type "D" (long text) is supported.
	NewCustOrderBinaryRow	Inserts a new row into the CUST_ORDER_BINARY table. Only the binary type "D" (long text) is supported.
	NewCustOrderShareRow	Inserts a new row into the CUST_ORDER_SHARE table.
	NewCustOrdlWipVasRow	Inserts a new row into the CUST_ORDL_WIP_VAS table.
	NewOrderLineDelSchedRow(String, Int64)	Inserts a new row into the CUST_LINE_DEL table. Auto number DEL_SCHED_LINE_NO.
	NewOrderLineDelSchedRow(String, Int64, Int64)	Inserts a new row into the CUST_LINE_DEL table.
	NewOrderLineRow(String)	Inserts a new row into the CUST_ORDER_LINE table. Auto number LINE_NO.
	NewOrderLineRow(String, Int64)	Inserts a new row into the CUST_ORDER_LINE table.
	NewOrderRow	Inserts a new row into the CUSTOMER_ORDER table.
	NewSelectedOptionsRow	Inserts a new row into the SELECTED_OPTIONS table

	Save()	Saves the previously loaded Customer Order to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

Lsa.Vmfg.Sales Namespace

CustomerOrder Constructor

Overload List

	Name	Description
	CustomerOrder()	Business Document Constructor
	CustomerOrder(String)	Business Document Constructor

See Also

CustomerOrder Class
Lsa.Vmfg.Sales Namespace

CustomerOrder Constructor

Business Document Constructor

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public CustomerOrder()

VB
Public Sub New

See Also

CustomerOrder Class
CustomerOrder Overload
Lsa.Vmfg.Sales Namespace

CustomerOrder Constructor (String)

Business Document Constructor

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public CustomerOrder(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

CustomerOrder Class

CustomerOrder Overload

Lsa.Vmfg.Sales Namespace

CustomerOrder.CustomerOrder Methods

The CustomerOrder type exposes the following members.

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Customer Orders based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Customer Orders based on search criteria, and limited by the values in the startRecord and maxRecords parameters.
	Exists	Determines if a specific Customer Order exists.
	Find	Retrieve the specified Customer Order. Only returns the top-level data table (CUSTOMER_ORDER).
	Load(String)	Loads a specific Customer Order.
	Load(Stream, String)	Load from stream and rename using new key.
	NewCustLineBillingRow	Inserts a new row into the CUST_LINE_BILLING table.
	NewCustLineBinaryRow	Inserts a new row into the CUST_LINE_BINARY table. Only the binary type "D" (long text) is supported.
	NewCustOrderBinaryRow	Inserts a new row into the CUST_ORDER_BINARY table. Only the binary type "D" (long text) is supported.
	NewCustOrderShareRow	Inserts a new row into the CUST_ORDER_SHARE table.
	NewCustOrdlWipVasRow	Inserts a new row into the CUST_ORDL_WIP_VAS table.
	NewOrderLineDelSchedRow(String, Int64)	Inserts a new row into the CUST_LINE_DEL table. Auto number DEL_SCHED_LINE_NO.
	NewOrderLineDelSchedRow(String, Int64, Int64)	Inserts a new row into the CUST_LINE_DEL table.
	NewOrderLineRow(String)	Inserts a new row into the CUST_ORDER_LINE table. Auto number LINE_NO.
	NewOrderLineRow(String, Int64)	Inserts a new row into the CUST_ORDER_LINE table.

	NewOrderRow	Inserts a new row into the CUSTOMER_ORDER table.
	NewSelectedOptionsRow	Inserts a new row into the SELECTED_OPTIONS table
	Save()	Saves the previously loaded Customer Order to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

CustomerOrder Class

Lsa.Vmfg.Sales Namespace

CustomerOrder.Browse Method

Overload List

	Name	Description
	Browse(String, String, String)	Retrieve Customer Orders based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Customer Orders based on search criteria, and limited by the values in the startRecord and maxRecords parameters.

See Also

CustomerOrder Class

Lsa.Vmfg.Sales Namespace

CustomerOrder.Browse Method (String, String, String)

Retrieve Customer Orders based on search criteria.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

Return Value

Type: **DataSet**

See Also

CustomerOrder Class

Browse Overload

Lsa.Vmfg.Sales Namespace

CustomerOrder.Browse Method (String, String, String, Int32, Int32)

Retrieve Customer Orders based on search criteria, and limited by the values in the startRecord and maxRecords parameters.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns,
        int startRecord,
        int maxRecords
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String,
        startRecord As Integer,
        maxRecords As Integer
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

startRecord

Type: System.Int32

maxRecords

Type: System.Int32

Return Value

Type: **DataSet**

See Also

CustomerOrder Class
Browse Overload
Lsa.Vmfg.Sales Namespace

CustomerOrder.Exists Method

Determines if a specific Customer Order exists.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual bool Exists(
        string orderID
)
```

VB

```
Public Overridable Function Exists (
        orderID As String
) As Boolean
```

Parameters

orderID

Type: System.String

Return Value

Type: Boolean

See Also

CustomerOrder Class

Lsa.Vmfg.Sales Namespace

CustomerOrder.Find Method

Retrieve the specified Customer Order. Only returns the top-level data table (CUSTOMER_ORDER).

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Find(
        string orderID
)
```

VB

```
Public Overridable Sub Find (
        orderID As String
)
```

Parameters

orderID

Type: System.String

See Also

CustomerOrder Class

Lsa.Vmfg.Sales Namespace

CustomerOrder.Load Method

Overload List

	Name	Description
	Load(String)	Loads a specific Customer Order.
	Load(Stream, String)	Load from stream and rename using new key.

See Also

CustomerOrder Class
Lsa.Vmfg.Sales Namespace

CustomerOrder.Load Method (String)

Loads a specific Customer Order.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string orderID
)
```

VB

```
Public Overridable Sub Load (
        orderID As String
)
```

Parameters

orderID

Type: System.String

See Also

CustomerOrder Class

Load Overload

Lsa.Vmfg.Sales Namespace

CustomerOrder.Load Method (Stream, String)

Load from stream and rename using new key.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        Stream stream,
        string orderID
)
```

VB

```
Public Overridable Sub Load (
        stream As Stream,
        orderID As String
)
```

Parameters

stream

Type: System.IO.Stream

orderID

Type: System.String

See Also

CustomerOrder Class

Load Overload

Lsa.Vmfg.Sales Namespace

CustomerOrder.NewCustLineBillingRow Method

Inserts a new row into the CUST_LINE_BILLING table.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewCustLineBillingRow(
        string orderID,
        int custOrderLineNo,
        int eventSeqNo
)
```

VB

```
Public Overridable Function NewCustLineBillingRow (
        orderID As String,
        custOrderLineNo As Integer,
        eventSeqNo As Integer
) As DataRow
```

Parameters

orderID

Type: System.String

custOrderLineNo

Type: System.Int32

eventSeqNo

Type: System.Int32

Return Value

Type: **DataRow**

See Also

CustomerOrder Class

Lsa.Vmfg.Sales Namespace

CustomerOrder.NewCustLineBinaryRow Method

Inserts a new row into the CUST_LINE_BINARY table. Only the binary type "D" (long text) is supported.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewCustLineBinaryRow(
        string orderID,
        int custOrderLineNo,
        string binaryType
)
```

VB

```
Public Overridable Function NewCustLineBinaryRow (
        orderID As String,
        custOrderLineNo As Integer,
        binaryType As String
) As DataRow
```

Parameters

orderID

Type: System.String

custOrderLineNo

Type: System.Int32

binaryType

Type: System.String

Return Value

Type: **DataRow**

See Also

CustomerOrder Class

Lsa.Vmfg.Sales Namespace

CustomerOrder.NewCustOrderBinaryRow Method

Inserts a new row into the CUST_ORDER_BINARY table. Only the binary type "D" (long text) is supported.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewCustOrderBinaryRow(
        string orderID,
        string binaryType
)
```

VB

```
Public Overridable Function NewCustOrderBinaryRow (
        orderID As String,
        binaryType As String
) As DataRow
```

Parameters

orderID

Type: System.String

binaryType

Type: System.String

Return Value

Type: **DataRow**

See Also

CustomerOrder Class

Lsa.Vmfg.Sales Namespace

CustomerOrder.NewCustOrderShareRow Method

Inserts a new row into the CUST_ORDER_SHARE table.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewCustOrderShareRow(
        string orderID,
        string salesrepID
)
```

VB

```
Public Overridable Function NewCustOrderShareRow (
        orderID As String,
        salesrepID As String
) As DataRow
```

Parameters

orderID

Type: System.String

salesrepID

Type: System.String

Return Value

Type: **DataRow**

See Also

CustomerOrder Class

Lsa.Vmfg.Sales Namespace

CustomerOrder.NewCustOrdlWipVasRow Method

Inserts a new row into the CUST_ORDL_WIP_VAS table.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewCustOrdlWipVasRow(
        string orderID,
        int custOrderLineNo,
        string wipVasID
)
```

VB

```
Public Overridable Function NewCustOrdlWipVasRow (
        orderID As String,
        custOrderLineNo As Integer,
        wipVasID As String
) As DataRow
```

Parameters

orderID

Type: System.String

custOrderLineNo

Type: System.Int32

wipVasID

Type: System.String

Return Value

Type: **DataRow**

See Also

CustomerOrder Class

Lsa.Vmfg.Sales Namespace

CustomerOrder.NewOrderLineDelSchedRow Method

Overload List

	Name	Description
	NewOrderLineDelSchedRow(String, Int64)	Inserts a new row into the CUST_LINE_DEL table. Auto number DEL_SCHED_LINE_NO.
	NewOrderLineDelSchedRow(String, Int64, Int64)	Inserts a new row into the CUST_LINE_DEL table.

See Also

CustomerOrder Class

Lsa.Vmfg.Sales Namespace

CustomerOrder.NewOrderLineDelSchedRow Method (String, Int64)

Inserts a new row into the CUST_LINE_DEL table. Auto number DEL_SCHED_LINE_NO.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewOrderLineDelSchedRow(
        string orderID,
        long orderLineNo
)
```

VB

```
Public Overridable Function NewOrderLineDelSchedRow (
        orderID As String,
        orderLineNo As Long
) As DataRow
```

Parameters

orderID

Type: System.String

orderLineNo

Type: System.Int64

Return Value

Type: **DataRow**

See Also

CustomerOrder Class

NewOrderLineDelSchedRow Overload

Lsa.Vmfg.Sales Namespace

CustomerOrder.NewOrderLineDelSchedRow Method (String, Int64, Int64)

Inserts a new row into the CUST_LINE_DEL table.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewOrderLineDelSchedRow(
        string orderID,
        long orderLineNo,
        long lineNo
)
```

VB

```
Public Overridable Function NewOrderLineDelSchedRow (
        orderID As String,
        orderLineNo As Long,
        lineNo As Long
) As DataRow
```

Parameters

orderID

Type: System.String

orderLineNo

Type: System.Int64

lineNo

Type: System.Int64

Return Value

Type: **DataRow**

See Also

CustomerOrder Class
NewOrderLineDelSchedRow Overload
Lsa.Vmfg.Sales Namespace

CustomerOrder.NewOrderLineRow Method

Overload List

	Name	Description
	NewOrderLineRow(String)	Inserts a new row into the CUST_ORDER_LINE table. Auto number LINE_NO.
	NewOrderLineRow(String, Int64)	Inserts a new row into the CUST_ORDER_LINE table.

See Also

CustomerOrder Class

Lsa.Vmfg.Sales Namespace

CustomerOrder.NewOrderLineRow Method (String)

Inserts a new row into the CUST_ORDER_LINE table. Auto number LINE_NO.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewOrderLineRow(
        string orderID
)
```

VB

```
Public Overridable Function NewOrderLineRow (
        orderID As String
) As DataRow
```

Parameters

orderID

Type: System.String

Return Value

Type: **DataRow**

Remarks

To generate a new Work Order from the Customer Order Line, set the value of Data Column NEW_WO to true.

When generating a new Work Order, you can control the numbering of the Work Order by setting these Data Column values:

JOB_ID – The BASE_ID of the new WORK_ORDER.

LOT_ID – The LOT_ID of the new WORK_ORDER. Default value = "1".

SPLIT_ID – The SPLIT_ID of the new WORK_ORDER. Default value = "0".

Leaving the JOB_ID blank will cause the new Work Order ID to be automatically generated.

You can also control the status of the new Work Order by setting the value of the NEW_WO_STATUS Data Column.

Valid values are "U", "F", "R". The default value is "R".

See Also

CustomerOrder Class

NewOrderLineRow Overload

Lsa.Vmfg.Sales Namespace

CustomerOrder.NewOrderLineRow Method (String, Int64)

Inserts a new row into the CUST_ORDER_LINE table.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewOrderLineRow(
        string orderID,
        long lineNo
)
```

VB

```
Public Overridable Function NewOrderLineRow (
        orderID As String,
        lineNo As Long
) As DataRow
```

Parameters

orderID

Type: System.String

lineNo

Type: System.Int64

Return Value

Type: **DataRow**

Remarks

To generate a new Work Order from the Customer Order Line, set the value of Data Column NEW_WO to true.

When generating a new Work Order, you can control the numbering of the Work Order by setting these Data Column values:

JOB_ID – The BASE_ID of the new WORK_ORDER.

LOT_ID – The LOT_ID of the new WORK_ORDER. Default value = "1".

SPLIT_ID – The SPLIT_ID of the new WORK_ORDER. Default value = "0".

Leaving the JOB_ID blank will cause the new Work Order ID to be automatically generated.

You can also control the status of the new Work Order by setting the value of the NEW_WO_STATUS Data Column.

Valid values are "U", "F", "R". The default value is "R".

See Also

CustomerOrder Class

NewOrderLineRow Overload

Lsa.Vmfg.Sales Namespace

CustomerOrder.NewOrderRow Method

Inserts a new row into the CUSTOMER_ORDER table.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewOrderRow(
        string orderID
)
```

VB

```
Public Overridable Function NewOrderRow (
        orderID As String
) As DataRow
```

Parameters

orderID

Type: System.String

Return Value

Type: **DataRow**

See Also

CustomerOrder Class

Lsa.Vmfg.Sales Namespace

CustomerOrder.NewSelectedOptionsRow Method

Inserts a new row into the SELECTED_OPTIONS table

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewSelectedOptionsRow(
        string orderID,
        int custOrderLineNo,
        int seqNo
)
```

VB

```
Public Overridable Function NewSelectedOptionsRow (
        orderID As String,
        custOrderLineNo As Integer,
        seqNo As Integer
) As DataRow
```

Parameters

orderID

Type: System.String

custOrderLineNo

Type: System.Int32

seqNo

Type: System.Int32

Return Value

Type: **DataRow**

See Also

CustomerOrder Class

Lsa.Vmfg.Sales Namespace

CustomerOrder.Save Method

Overload List

	Name	Description
	Save()	Saves the previously loaded Customer Order to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

CustomerOrder Class
Lsa.Vmfg.Sales Namespace

CustomerOrder.Save Method

Saves the previously loaded Customer Order to the database.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

CustomerOrder Class
Save Overload
Lsa.Vmfg.Sales Namespace

CustomerOrder.Save Method (Stream)

Save current state of data set to stream.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Save(
        Stream stream
)
```

VB

```
Public Overridable Sub Save (
        stream As Stream
)
```

Parameters

stream

Type: System.IO.Stream

See Also

CustomerOrder Class

Save Overload

Lsa.Vmfg.Sales Namespace

CustomerPrice Class

Maintain Customer Prices.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessDocument
          Lsa.Vmfg.Sales.CustomerPrice

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class CustomerPrice : BusinessDocument
```

VB

```
<SerializableAttribute>
Public Class CustomerPrice
        Inherits BusinessDocument
```

The **CustomerPrice** type exposes the following members.

Constructors

	Name	Description
	CustomerPrice()	Initializes a new instance of the **CustomerPrice** class
	CustomerPrice(String)	Initializes a new instance of the **CustomerPrice** class

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Customer Price information based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Customer Price information based on search criteria, limited by the values of the startRecord and maxRecords parameters.
	Exists	Determine if a specific Customer Price record exists.
	Find	Retrieve a specific Customer Price for a given Customer / Part / Selling UM combination.
	Load()	Load all Customer Prices.
	Load(String, String, String)	Load a specific Customer Price for a given Customer / Part / Selling UM combination.
	NewCustomerPrice(String, String, String, Decimal, String, String, String)	Adds a customer price For byDateCode, use "O" for Orders, "S" for Shipments, "B" for Both Orders and Shipments
	NewCustomerPrice(String, String, String, Decimal, String, String, String, Int32, Int32, Int32, Int32, Int32, Int32, Int32, Int32, Int32, Int32, Decimal, Decimal, Decimal, Decimal, Decimal, Decimal, Decimal, Decimal, Decimal, Decimal)	Adds a customer price for the specified customer. Specify quantities and prices of the customer price entry. Use 0 (zero) for each break price and quantity if you do not wish to specify a value.
	Save()	Save all previously loaded Customer Price data to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

Lsa.Vmfg.Sales Namespace

CustomerPrice Constructor

Overload List

	Name	Description
	CustomerPrice()	Initializes a new instance of the CustomerPrice class
	CustomerPrice(String)	Initializes a new instance of the CustomerPrice class

See Also

CustomerPrice Class
Lsa.Vmfg.Sales Namespace

CustomerPrice Constructor

Initializes a new instance of the CustomerPrice class

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public CustomerPrice()

VB
Public Sub New

See Also

CustomerPrice Class
CustomerPrice Overload
Lsa.Vmfg.Sales Namespace

CustomerPrice Constructor (String)

Initializes a new instance of the CustomerPrice class

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public CustomerPrice(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

CustomerPrice Class

CustomerPrice Overload

Lsa.Vmfg.Sales Namespace

CustomerPrice.CustomerPrice Methods

The CustomerPrice type exposes the following members.

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Customer Price information based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Customer Price information based on search criteria, limited by the values of the startRecord and maxRecords parameters.
	Exists	Determine if a specific Customer Price record exists.
	Find	Retrieve a specific Customer Price for a given Customer / Part / Selling UM combination.
	Load()	Load all Customer Prices.
	Load(String, String, String)	Load a specific Customer Price for a given Customer / Part / Selling UM combination.
	NewCustomerPrice(String, String, String, Decimal, String, String, String)	Adds a customer price For byDateCode, use "O" for Orders, "S" for Shipments, "B" for Both Orders and Shipments
	NewCustomerPrice(String, String, String, Decimal, String, String, String, Int32, Int32, Int32, Int32, Int32, Int32, Int32, Int32, Int32, Decimal, Decimal, Decimal, Decimal, Decimal, Decimal, Decimal, Decimal, Decimal, Decimal)	Adds a customer price for the specified customer. Specify quantities and prices of the customer price entry. Use 0 (zero) for each break price and quantity if you do not wish to specify a value.
	Save()	Save all previously loaded Customer Price data to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

CustomerPrice Class

Lsa.Vmfg.Sales Namespace

CustomerPrice.Browse Method

Overload List

	Name	Description
	Browse(String, String, String)	Retrieve Customer Price information based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Customer Price information based on search criteria, limited by the values of the startRecord and maxRecords parameters.

See Also

CustomerPrice Class

Lsa.Vmfg.Sales Namespace

CustomerPrice.Browse Method (String, String, String)

Retrieve Customer Price information based on search criteria.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

Return Value

Type: **DataSet**

See Also

CustomerPrice Class

Browse Overload

Lsa.Vmfg.Sales Namespace

CustomerPrice.Browse Method (String, String, String, Int32, Int32)

Retrieve Customer Price information based on search criteria, limited by the values of the startRecord and maxRecords parameters.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns,
        int startRecord,
        int maxRecords
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String,
        startRecord As Integer,
        maxRecords As Integer
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

startRecord

Type: System.Int32

maxRecords

Type: System.Int32

Return Value

Type: **DataSet**

See Also

CustomerPrice Class
Browse Overload
Lsa.Vmfg.Sales Namespace

CustomerPrice.Exists Method

Determine if a specific Customer Price record exists.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual bool Exists(
        string customerID,
        string partID,
        string sellingUM
)
```

VB

```
Public Overridable Function Exists (
        customerID As String,
        partID As String,
        sellingUM As String
) As Boolean
```

Parameters

customerID

Type: System.String

partID

Type: System.String

sellingUM

Type: System.String

Return Value

Type: Boolean

See Also

CustomerPrice Class

Lsa.Vmfg.Sales Namespace

CustomerPrice.Find Method

Retrieve a specific Customer Price for a given Customer / Part / Selling UM combination.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Find(
        string customerID,
        string partID,
        string sellingUM
)
```

VB

```
Public Overridable Sub Find (
        customerID As String,
        partID As String,
        sellingUM As String
)
```

Parameters

customerID

Type: System.String

partID

Type: System.String

sellingUM

Type: System.String

See Also

CustomerPrice Class

Lsa.Vmfg.Sales Namespace

CustomerPrice.Load Method

Overload List

	Name	Description
	Load()	Load all Customer Prices.
	Load(String, String, String)	Load a specific Customer Price for a given Customer / Part / Selling UM combination.

See Also

CustomerPrice Class

Lsa.Vmfg.Sales Namespace

CustomerPrice.Load Method

Load all Customer Prices.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Load()

VB
Public Overridable Sub Load

See Also

CustomerPrice Class
Load Overload
Lsa.Vmfg.Sales Namespace

CustomerPrice.Load Method (String, String, String)

Load a specific Customer Price for a given Customer / Part / Selling UM combination.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string customerID,
        string partID,
        string sellingUM
)
```

VB

```
Public Overridable Sub Load (
        customerID As String,
        partID As String,
        sellingUM As String
)
```

Parameters

customerID

Type: System.String

partID

Type: System.String

sellingUM

Type: System.String

See Also

CustomerPrice Class

Load Overload

Lsa.Vmfg.Sales Namespace

CustomerPrice.NewCustomerPrice Method

Overload List

	Name	Description
	NewCustomerPrice(String, String, String, Decimal, String, String, String)	Adds a customer price For byDateCode, use "O" for Orders, "S" for Shipments, "B" for Both Orders and Shipments
	NewCustomerPrice(String, String, String, Decimal, String, String, String, Int32, Int32, Int32, Int32, Int32, Int32, Int32, Int32, Int32, Decimal, Decimal, Decimal, Decimal, Decimal, Decimal, Decimal, Decimal, Decimal)	Adds a customer price for the specified customer. Specify quantities and prices of the customer price entry. Use 0 (zero) for each break price and quantity if you do not wish to specify a value.

See Also

CustomerPrice Class

Lsa.Vmfg.Sales Namespace

CustomerPrice.NewCustomerPrice Method (String, String, String, Decimal, String, String, String)

Adds a customer price For byDateCode, use "O" for Orders, "S" for Shipments, "B" for Both Orders and Shipments

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public DataRow NewCustomerPrice(
        string customerID,
        string partID,
        string sellingUM,
        decimal defaultUnitPrice,
        string effectiveDate,
        string discontinueDate,
        string byDateCode
)
```

VB

```
Public Function NewCustomerPrice (
        customerID As String,
        partID As String,
        sellingUM As String,
        defaultUnitPrice As Decimal,
        effectiveDate As String,
        discontinueDate As String,
        byDateCode As String
) As DataRow
```

Parameters

customerID

Type: System.String

partID

Type: System.String

sellingUM

Type: System.String

defaultUnitPrice
Type: System.Decimal
effectiveDate
Type: System.String
discontinueDate
Type: System.String
byDateCode
Type: System.String

Return Value

Type: **DataRow**

See Also

CustomerPrice Class
NewCustomerPrice Overload
Lsa.Vmfg.Sales Namespace

CustomerPrice.NewCustomerPrice Method (String, String, String, Decimal, String, String, String, Int32, Int32, Int32, Int32, Int32, Int32, Int32, Int32, Int32, Int32, Decimal, Decimal, Decimal, Decimal, Decimal, Decimal, Decimal, Decimal, Decimal, Decimal)

Adds a customer price for the specified customer. Specify quantities and prices of the customer price entry. Use 0 (zero) for each break price and quantity if you do not wish to specify a value.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public DataRow NewCustomerPrice(
        string customerID,
        string partID,
        string sellingUM,
        decimal defaultUnitPrice,
        string effectiveDate,
        string discontinueDate,
        string byDateCode,
        int qtyBreak1,
        int qtyBreak2,
        int qtyBreak3,
        int qtyBreak4,
        int qtyBreak5,
        int qtyBreak6,
        int qtyBreak7,
        int qtyBreak8,
        int qtyBreak9,
        int qtyBreak10,
        decimal unitPrice1,
        decimal unitPrice2,
        decimal unitPrice3,
        decimal unitPrice4,
        decimal unitPrice5,
        decimal unitPrice6,
        decimal unitPrice7,
        decimal unitPrice8,
        decimal unitPrice9,
        decimal unitPrice10
)
```

VB

```
Public Function NewCustomerPrice (
        customerID As String,
        partID As String,
        sellingUM As String,
        defaultUnitPrice As Decimal,
        effectiveDate As String,
        discontinueDate As String,
        byDateCode As String,
        qtyBreak1 As Integer,
        qtyBreak2 As Integer,
        qtyBreak3 As Integer,
        qtyBreak4 As Integer,
        qtyBreak5 As Integer,
        qtyBreak6 As Integer,
        qtyBreak7 As Integer,
        qtyBreak8 As Integer,
        qtyBreak9 As Integer,
        qtyBreak10 As Integer,
        unitPrice1 As Decimal,
        unitPrice2 As Decimal,
        unitPrice3 As Decimal,
        unitPrice4 As Decimal,
        unitPrice5 As Decimal,
        unitPrice6 As Decimal,
        unitPrice7 As Decimal,
        unitPrice8 As Decimal,
        unitPrice9 As Decimal,
        unitPrice10 As Decimal
) As DataRow
```

Parameters

customerID

Type: System.String

partID

Type: System.String

sellingUM

Type: System.String

defaultUnitPrice

Type: System.Decimal

effectiveDate

Type: System.String

discontinueDate

Type: System.String

byDateCode

Type: System.String

qtyBreak1

Type: System.Int32

qtyBreak2

Type: System.Int32

qtyBreak3

Type: System.Int32

qtyBreak4

Type: System.Int32

qtyBreak5

Type: System.Int32

qtyBreak6

Type: System.Int32

qtyBreak7

Type: System.Int32

qtyBreak8

Type: System.Int32

qtyBreak9

Type: System.Int32

qtyBreak10

Type: System.Int32

unitPrice1

Type: System.Decimal

unitPrice2

Type: System.Decimal

unitPrice3

Type: System.Decimal

unitPrice4

Type: System.Decimal

unitPrice5

Type: System.Decimal

unitPrice6

Type: System.Decimal

unitPrice7

Type: System.Decimal

unitPrice8

Type: System.Decimal

unitPrice9

Type: System.Decimal

unitPrice10

Type: System.Decimal

Return Value

Type: **DataRow**

See Also

CustomerPrice Class

NewCustomerPrice Overload

Lsa.Vmfg.Sales Namespace

CustomerPrice.Save Method

Overload List

	Name	Description
	Save()	Save all previously loaded Customer Price data to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

CustomerPrice Class
Lsa.Vmfg.Sales Namespace

CustomerPrice.Save Method

Save all previously loaded Customer Price data to the database.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

CustomerPrice Class
Save Overload
Lsa.Vmfg.Sales Namespace

CustomerPrice.Save Method (Stream)

Save current state of data set to stream.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Save(
        Stream stream
)
```

VB

```
Public Overridable Sub Save (
        stream As Stream
)
```

Parameters

stream

Type: System.IO.Stream

See Also

CustomerPrice Class

Save Overload

Lsa.Vmfg.Sales Namespace

CustomerPriority Class

Maintain Customer Priority Codes.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessDocument
          Lsa.Vmfg.Sales.CustomerPriority

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class CustomerPriority : BusinessDocument
```

VB

```
<SerializableAttribute>
Public Class CustomerPriority
        Inherits BusinessDocument
```

The **CustomerPriority** type exposes the following members.

Constructors

	Name	Description
	CustomerPriority()	Constructor
	CustomerPriority(String)	Constructor

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Customer Priority Code information based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Customer Priority Code information based on search criteria, limited by startRecord and maxRecords parameters.
	Exists	Deterime if a specific Customer Priority Code exists.
	Find	Retrieve a specific Customer Priority Code.
	Load()	Load all of the Customer Priority Codes.
	Load(String)	Load a specific Customer Priority Code.
	NewCustomerPriorityRow	Inserts a new row into the CUST_PRIORITY type table.
	Save	Save all previously loaded Customer Priority Codes to the database.

See Also

Lsa.Vmfg.Sales Namespace

CustomerPriority Constructor

Overload List

	Name	Description
	CustomerPriority()	Constructor
	CustomerPriority(String)	Constructor

See Also

CustomerPriority Class
Lsa.Vmfg.Sales Namespace

CustomerPriority Constructor

Constructor

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public CustomerPriority()

VB
Public Sub New

See Also

CustomerPriority Class
CustomerPriority Overload
Lsa.Vmfg.Sales Namespace

CustomerPriority Constructor (String)

Constructor

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public CustomerPriority(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

CustomerPriority Class
CustomerPriority Overload
Lsa.Vmfg.Sales Namespace

CustomerPriority.CustomerPriority Methods

The CustomerPriority type exposes the following members.

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Customer Priority Code information based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Customer Priority Code information based on search criteria, limited by startRecord and maxRecords parameters.
	Exists	Deterime if a specific Customer Priority Code exists.
	Find	Retrieve a specific Customer Priority Code.
	Load()	Load all of the Customer Priority Codes.
	Load(String)	Load a specific Customer Priority Code.
	NewCustomerPriorityRow	Inserts a new row into the CUST_PRIORITY type table.
	Save	Save all previously loaded Customer Priority Codes to the database.

See Also

CustomerPriority Class

Lsa.Vmfg.Sales Namespace

CustomerPriority.Browse Method

Overload List

	Name	Description
	Browse(String, String, String)	Retrieve Customer Priority Code information based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Customer Priority Code information based on search criteria, limited by startRecord and maxRecords parameters.

See Also

CustomerPriority Class

Lsa.Vmfg.Sales Namespace

CustomerPriority.Browse Method (String, String, String)

Retrieve Customer Priority Code information based on search criteria.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

Return Value

Type: **DataSet**

See Also

CustomerPriority Class
Browse Overload
Lsa.Vmfg.Sales Namespace

CustomerPriority.Browse Method (String, String, String, Int32, Int32)

Retrieve Customer Priority Code information based on search criteria, limited by startRecord and maxRecords parameters.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns,
        int startRecord,
        int maxRecords
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String,
        startRecord As Integer,
        maxRecords As Integer
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

startRecord

Type: System.Int32

maxRecords

Type: System.Int32

Return Value

Type: **DataSet**

See Also

CustomerPriority Class
Browse Overload
Lsa.Vmfg.Sales Namespace

CustomerPriority.Exists Method

Deterime if a specific Customer Priority Code exists.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual bool Exists(
        string code
)
```

VB

```
Public Overridable Function Exists (
        code As String
) As Boolean
```

Parameters

code

Type: System.String

Return Value

Type: Boolean

See Also

CustomerPriority Class

Lsa.Vmfg.Sales Namespace

CustomerPriority.Find Method

Retrieve a specific Customer Priority Code.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Find(
        string priorityCode
)
```

VB

```
Public Overridable Sub Find (
        priorityCode As String
)
```

Parameters

priorityCode

Type: System.String

See Also

CustomerPriority Class

Lsa.Vmfg.Sales Namespace

CustomerPriority.Load Method

Overload List

	Name	Description
	Load()	Load all of the Customer Priority Codes.
	Load(String)	Load a specific Customer Priority Code.

See Also

CustomerPriority Class
Lsa.Vmfg.Sales Namespace

CustomerPriority.Load Method

Load all of the Customer Priority Codes.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Load()

VB
Public Overridable Sub Load

See Also

CustomerPriority Class
Load Overload
Lsa.Vmfg.Sales Namespace

CustomerPriority.Load Method (String)

Load a specific Customer Priority Code.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string priorityCode
)
```

VB

```
Public Overridable Sub Load (
        priorityCode As String
)
```

Parameters

priorityCode

Type: System.String

See Also

CustomerPriority Class

Load Overload

Lsa.Vmfg.Sales Namespace

CustomerPriority.NewCustomerPriorityRow Method

Inserts a new row into the CUST_PRIORITY type table.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public DataRow NewCustomerPriorityRow(
        string code
)
```

VB

```
Public Function NewCustomerPriorityRow (
        code As String
) As DataRow
```

Parameters

code

Type: System.String

Return Value

Type: **DataRow**

See Also

CustomerPriority Class

Lsa.Vmfg.Sales Namespace

CustomerPriority.Save Method

Save all previously loaded Customer Priority Codes to the database.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

CustomerPriority Class
Lsa.Vmfg.Sales Namespace

CustomerTypes Class

Maintain Customer Type Codes.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessDocument
          Lsa.Vmfg.Sales.CustomerTypes

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class CustomerTypes : BusinessDocument
```

VB

```
<SerializableAttribute>
Public Class CustomerTypes
        Inherits BusinessDocument
```

The **CustomerTypes** type exposes the following members.

Constructors

	Name	Description
	CustomerTypes()	Initializes a new instance of the **CustomerTypes** class
	CustomerTypes(String)	Initializes a new instance of the **CustomerTypes** class

Methods

	Name	Description
	Browse(String, String, String)	Retrieves Customer Type Codes based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieves Customer Type Codes based on search criteria, limited by startRecord and maxRecords parameters.
	Exists	Deterime if a specific Customer Type Code exists.
	Find	Retrieves a specific Customer Type Code.
	Load()	Loads all Customer Type Codes.
	Load(String)	Loads a specific Customer Type Code.
	Load(Stream, String)	Load from stream and rename using new key.
	NewCustomerTypeRow	Adds a new row to the CUSTOMER_TYPE table.
	Save()	Save all previously loaded Customer Type Code(s) to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

Lsa.Vmfg.Sales Namespace

CustomerTypes Constructor

Overload List

	Name	Description
	CustomerTypes()	Initializes a new instance of the CustomerTypes class
	CustomerTypes(String)	Initializes a new instance of the CustomerTypes class

See Also

CustomerTypes Class
Lsa.Vmfg.Sales Namespace

CustomerTypes Constructor

Initializes a new instance of the CustomerTypes class

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public CustomerTypes()

VB
Public Sub New

See Also

CustomerTypes Class
CustomerTypes Overload
Lsa.Vmfg.Sales Namespace

CustomerTypes Constructor (String)

Initializes a new instance of the CustomerTypes class

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public CustomerTypes(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

CustomerTypes Class
CustomerTypes Overload
Lsa.Vmfg.Sales Namespace

CustomerTypes.CustomerTypes Methods

The CustomerTypes type exposes the following members.

Methods

	Name	Description
	Browse(String, String, String)	Retrieves Customer Type Codes based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieves Customer Type Codes based on search criteria, limited by startRecord and maxRecords parameters.
	Exists	Deterime if a specific Customer Type Code exists.
	Find	Retrieves a specific Customer Type Code.
	Load()	Loads all Customer Type Codes.
	Load(String)	Loads a specific Customer Type Code.
	Load(Stream, String)	Load from stream and rename using new key.
	NewCustomerTypeRow	Adds a new row to the CUSTOMER_TYPE table.
	Save()	Save all previously loaded Customer Type Code(s) to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

CustomerTypes Class

Lsa.Vmfg.Sales Namespace

CustomerTypes.Browse Method

Overload List

	Name	Description
	Browse(String, String, String)	Retrieves Customer Type Codes based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieves Customer Type Codes based on search criteria, limited by startRecord and maxRecords parameters.

See Also

CustomerTypes Class

Lsa.Vmfg.Sales Namespace

CustomerTypes.Browse Method (String, String, String)

Retrieves Customer Type Codes based on search criteria.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

Return Value

Type: **DataSet**

See Also

CustomerTypes Class
Browse Overload
Lsa.Vmfg.Sales Namespace

CustomerTypes.Browse Method (String, String, String, Int32, Int32)

Retrieves Customer Type Codes based on search criteria, limited by startRecord and maxRecords parameters.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns,
        int startRecord,
        int maxRecords
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String,
        startRecord As Integer,
        maxRecords As Integer
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

startRecord

Type: System.Int32

maxRecords

Type: System.Int32

Return Value

Type: **DataSet**

See Also

CustomerTypes Class
Browse Overload
Lsa.Vmfg.Sales Namespace

CustomerTypes.Exists Method

Deterime if a specific Customer Type Code exists.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual bool Exists(
        string type
)
```

VB

```
Public Overridable Function Exists (
        type As String
) As Boolean
```

Parameters

type

Type: System.String

Return Value

Type: Boolean

See Also

CustomerTypes Class

Lsa.Vmfg.Sales Namespace

CustomerTypes.Find Method

Retrieves a specific Customer Type Code.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Find(
        string type
)
```

VB

```
Public Overridable Sub Find (
        type As String
)
```

Parameters

type

Type: System.String

See Also

CustomerTypes Class

Lsa.Vmfg.Sales Namespace

CustomerTypes.Load Method

Overload List

	Name	Description
	Load()	Loads all Customer Type Codes.
	Load(String)	Loads a specific Customer Type Code.
	Load(Stream, String)	Load from stream and rename using new key.

See Also

CustomerTypes Class
Lsa.Vmfg.Sales Namespace

CustomerTypes.Load Method

Loads all Customer Type Codes.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Load()

VB
Public Overridable Sub Load

See Also

CustomerTypes Class
Load Overload
Lsa.Vmfg.Sales Namespace

CustomerTypes.Load Method (String)

Loads a specific Customer Type Code.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string type
)
```

VB

```
Public Overridable Sub Load (
        type As String
)
```

Parameters

type

Type: System.String

See Also

CustomerTypes Class

Load Overload

Lsa.Vmfg.Sales Namespace

CustomerTypes.Load Method (Stream, String)

Load from stream and rename using new key.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        Stream stream,
        string type
)
```

VB

```
Public Overridable Sub Load (
        stream As Stream,
        type As String
)
```

Parameters

stream

Type: System.IO.Stream

type

Type: System.String

See Also

CustomerTypes Class

Load Overload

Lsa.Vmfg.Sales Namespace

CustomerTypes.NewCustomerTypeRow Method

Adds a new row to the CUSTOMER_TYPE table.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public DataRow NewCustomerTypeRow(
        string type
)
```

VB

```
Public Function NewCustomerTypeRow (
        type As String
) As DataRow
```

Parameters

type

Type: System.String

Return Value

Type: **DataRow**

See Also

CustomerTypes Class

Lsa.Vmfg.Sales Namespace

CustomerTypes.Save Method

Overload List

	Name	Description
	Save()	Save all previously loaded Customer Type Code(s) to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

CustomerTypes Class
Lsa.Vmfg.Sales Namespace

CustomerTypes.Save Method

Save all previously loaded Customer Type Code(s) to the database.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

CustomerTypes Class
Save Overload
Lsa.Vmfg.Sales Namespace

CustomerTypes.Save Method (Stream)

Save current state of data set to stream.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Save(
        Stream stream
)
```

VB

```
Public Overridable Sub Save (
        stream As Stream
)
```

Parameters

stream

Type: System.IO.Stream

See Also

CustomerTypes Class

Save Overload

Lsa.Vmfg.Sales Namespace

CustOrderType Class

Maintain Customer Order Types.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessDocument
          Lsa.Vmfg.Sales.CustOrderType

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class CustOrderType : BusinessDocument
```

VB

```
<SerializableAttribute>
Public Class CustOrderType
        Inherits BusinessDocument
```

The **CustOrderType** type exposes the following members.

Constructors

	Name	Description
	CustOrderType()	Constructor
	CustOrderType(String)	Constructor

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Customer Order Types based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Customer Order Types based on search criteria, limited by startRecord and maxRecords parameters.
	Exists	Determine if a specific Customer Order Type exists.
	Find	Retrieve a specific Customer Order Type.
	Load()	Load all Customer Order Types.
	Load(String)	Load a specific Customer Order Type.
	Load(Stream, String)	Load from stream and rename using new key.
	NewCustOrderTypeRow	Adds a new row to the CUST_ORDER_TYPE table.
	Save()	Save all previously loaded Customer Order Types to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

Lsa.Vmfg.Sales Namespace

CustOrderType Constructor

Overload List

	Name	Description
	CustOrderType()	Constructor
	CustOrderType(String)	Constructor

See Also

CustOrderType Class
Lsa.Vmfg.Sales Namespace

CustOrderType Constructor

Constructor

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public CustOrderType()

VB
Public Sub New

See Also

CustOrderType Class
CustOrderType Overload
Lsa.Vmfg.Sales Namespace

CustOrderType Constructor (String)

Constructor

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public CustOrderType(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

CustOrderType Class
CustOrderType Overload
Lsa.Vmfg.Sales Namespace

CustOrderType.CustOrderType Methods

The CustOrderType type exposes the following members.

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Customer Order Types based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Customer Order Types based on search criteria, limited by startRecord and maxRecords parameters.
	Exists	Determine if a specific Customer Order Type exists.
	Find	Retrieve a specific Customer Order Type.
	Load()	Load all Customer Order Types.
	Load(String)	Load a specific Customer Order Type.
	Load(Stream, String)	Load from stream and rename using new key.
	NewCustOrderTypeRow	Adds a new row to the CUST_ORDER_TYPE table.
	Save()	Save all previously loaded Customer Order Types to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

CustOrderType Class

Lsa.Vmfg.Sales Namespace

CustOrderType.Browse Method

Overload List

	Name	Description
	Browse(String, String, String)	Retrieve Customer Order Types based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Customer Order Types based on search criteria, limited by startRecord and maxRecords parameters.

See Also

CustOrderType Class

Lsa.Vmfg.Sales Namespace

CustOrderType.Browse Method (String, String, String)

Retrieve Customer Order Types based on search criteria.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

Return Value

Type: **DataSet**

See Also

CustOrderType Class
Browse Overload
Lsa.Vmfg.Sales Namespace

CustOrderType.Browse Method (String, String, String, Int32, Int32)

Retrieve Customer Order Types based on search criteria, limited by startRecord and maxRecords parameters.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns,
        int startRecord,
        int maxRecords
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String,
        startRecord As Integer,
        maxRecords As Integer
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

startRecord

Type: System.Int32

maxRecords

Type: System.Int32

Return Value

Type: **DataSet**

See Also

CustOrderType Class
Browse Overload
Lsa.Vmfg.Sales Namespace

CustOrderType.Exists Method

Determine if a specific Customer Order Type exists.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual bool Exists(
        string type
)
```

VB

```
Public Overridable Function Exists (
        type As String
) As Boolean
```

Parameters

type

Type: System.String

Return Value

Type: Boolean

See Also

CustOrderType Class

Lsa.Vmfg.Sales Namespace

CustOrderType.Find Method

Retrieve a specific Customer Order Type.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Find(
        string type
)
```

VB

```
Public Overridable Sub Find (
        type As String
)
```

Parameters

type

Type: System.String

See Also

CustOrderType Class

Lsa.Vmfg.Sales Namespace

CustOrderType.Load Method

Overload List

	Name	Description
	Load()	Load all Customer Order Types.
	Load(String)	Load a specific Customer Order Type.
	Load(Stream, String)	Load from stream and rename using new key.

See Also

CustOrderType Class
Lsa.Vmfg.Sales Namespace

CustOrderType.Load Method

Load all Customer Order Types.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Load()

VB
Public Overridable Sub Load

See Also

CustOrderType Class
Load Overload
Lsa.Vmfg.Sales Namespace

CustOrderType.Load Method (String)

Load a specific Customer Order Type.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string type
)
```

VB

```
Public Overridable Sub Load (
        type As String
)
```

Parameters

type

Type: System.String

See Also

CustOrderType Class

Load Overload

Lsa.Vmfg.Sales Namespace

CustOrderType.Load Method (Stream, String)

Load from stream and rename using new key.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        Stream stream,
        string type
)
```

VB

```
Public Overridable Sub Load (
        stream As Stream,
        type As String
)
```

Parameters

stream

Type: System.IO.Stream

type

Type: System.String

See Also

CustOrderType Class

Load Overload

Lsa.Vmfg.Sales Namespace

CustOrderType.NewCustOrderTypeRow Method

Adds a new row to the CUST_ORDER_TYPE table.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public DataRow NewCustOrderTypeRow(
        string type
)
```

VB

```
Public Function NewCustOrderTypeRow (
        type As String
) As DataRow
```

Parameters

type

Type: System.String

Return Value

Type: **DataRow**

See Also

CustOrderType Class

Lsa.Vmfg.Sales Namespace

CustOrderType.Save Method

Overload List

	Name	Description
	Save()	Save all previously loaded Customer Order Types to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

CustOrderType Class
Lsa.Vmfg.Sales Namespace

CustOrderType.Save Method

Save all previously loaded Customer Order Types to the database.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

CustOrderType Class
Save Overload
Lsa.Vmfg.Sales Namespace

CustOrderType.Save Method (Stream)

Save current state of data set to stream.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Save(
        Stream stream
)
```

VB

```
Public Overridable Sub Save (
        stream As Stream
)
```

Parameters

stream

Type: System.IO.Stream

See Also

CustOrderType Class

Save Overload

Lsa.Vmfg.Sales Namespace

DemandSupplyLink Class

Maintain Demand Supply Links.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessDocument
          Lsa.Vmfg.Sales.DemandSupplyLink

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class DemandSupplyLink : BusinessDocument
```

VB

```
<SerializableAttribute>
Public Class DemandSupplyLink
        Inherits BusinessDocument
```

The **DemandSupplyLink** type exposes the following members.

Constructors

	Name	Description
	DemandSupplyLink()	Constructor
	DemandSupplyLink(String)	Constructor

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Demand Supply Links based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Demand Supply Links based on search criteria, limited by the values in the startRecord and maxRecords parameters.
	Exists	Determine if a specific Demand Supply Link exists.
	Find	Retrieve a specific Demand Supply Link from the database.
	Load(String)	Loads a specific Demand Supply Link, based on the ID provided.
	Load(String, String)	Loads a Demand Supply Link, based on the demand type and demand base ID provided.
	Load(String, String, Int32)	Loads a Demand Supply Link, based on the demand type, demand base ID and demand seq no provided.
	Load(String, String, String)	Loads a Demand Supply Link, based on the demand type, demand base ID and demand lot ID provided.
	Load(String, String, Int32, Int32)	Loads a Demand Supply Link, based on the demand type, demand base ID, demand seq no, and demand no provided.
	Load(String, String, String, String)	Loads a Demand Supply Link, based on the demand type, demand base ID, demand lot ID, and demand split ID provided.
	Load(String, String, String, String, String)	Loads a Demand Supply Link, based on the demand type, demand base ID, demand lot ID, demand split ID, and demand sub ID provided.
	Load(String, String, String, String, String, Int32, Int32)	Loads a Demand Supply Link, based on the demand type, demand base ID, demand lot ID, demand split ID, demand sub ID, and demand no provided.
	NewDemandSupplyLinkRow	Insert a new row into the DEMAND_SUPPLY_LINK table.
	Save	Save all previously loaded Demand Supply Links to the database.

See Also

Lsa.Vmfg.Sales Namespace

DemandSupplyLink Constructor

Overload List

	Name	Description
	DemandSupplyLink()	Constructor
	DemandSupplyLink(String)	Constructor

See Also

DemandSupplyLink Class
Lsa.Vmfg.Sales Namespace

DemandSupplyLink Constructor

Constructor

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public DemandSupplyLink()

VB
Public Sub New

See Also

DemandSupplyLink Class
DemandSupplyLink Overload
Lsa.Vmfg.Sales Namespace

DemandSupplyLink Constructor (String)

Constructor

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public DemandSupplyLink(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

DemandSupplyLink Class
DemandSupplyLink Overload
Lsa.Vmfg.Sales Namespace

DemandSupplyLink.DemandSupplyLink Methods

The DemandSupplyLink type exposes the following members.

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Demand Supply Links based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Demand Supply Links based on search criteria, limited by the values in the startRecord and maxRecords parameters.
	Exists	Determine if a specific Demand Supply Link exists.
	Find	Retrieve a specific Demand Supply Link from the database.
	Load(String)	Loads a specific Demand Supply Link, based on the ID provided.
	Load(String, String)	Loads a Demand Supply Link, based on the demand type and demand base ID provided.
	Load(String, String, Int32)	Loads a Demand Supply Link, based on the demand type, demand base ID and demand seq no provided.
	Load(String, String, String)	Loads a Demand Supply Link, based on the demand type, demand base ID and demand lot ID provided.
	Load(String, String, Int32, Int32)	Loads a Demand Supply Link, based on the demand type, demand base ID, demand seq no, and demand no provided.
	Load(String, String, String, String)	Loads a Demand Supply Link, based on the demand type, demand base ID, demand lot ID, and demand split ID provided.
	Load(String, String, String, String, String)	Loads a Demand Supply Link, based on the demand type, demand base ID, demand lot ID, demand split ID, and demand sub ID provided.
	Load(String, String, String, String, String, Int32, Int32)	Loads a Demand Supply Link, based on the demand type, demand base ID, demand lot ID, demand split ID, demand sub ID, and demand no provided.
	NewDemandSupplyLinkRow	Insert a new row into the DEMAND_SUPPLY_LINK table.

	Save	Save all previously loaded Demand Supply Links to the database.

See Also

DemandSupplyLink Class

Lsa.Vmfg.Sales Namespace

DemandSupplyLink.Browse Method

Overload List

	Name	Description
	Browse(String, String, String)	Retrieve Demand Supply Links based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Demand Supply Links based on search criteria, limited by the values in the startRecord and maxRecords parameters.

See Also

DemandSupplyLink Class

Lsa.Vmfg.Sales Namespace

DemandSupplyLink.Browse Method (String, String, String)

Retrieve Demand Supply Links based on search criteria.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

Return Value

Type: **DataSet**

See Also

DemandSupplyLink Class
Browse Overload
Lsa.Vmfg.Sales Namespace

DemandSupplyLink.Browse Method (String, String, String, Int32, Int32)

Retrieve Demand Supply Links based on search criteria, limited by the values in the startRecord and maxRecords parameters.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns,
        int startRecord,
        int maxRecords
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String,
        startRecord As Integer,
        maxRecords As Integer
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

startRecord

Type: System.Int32

maxRecords

Type: System.Int32

Return Value

Type: **DataSet**

See Also

DemandSupplyLink Class
Browse Overload
Lsa.Vmfg.Sales Namespace

DemandSupplyLink.Exists Method

Determine if a specific Demand Supply Link exists.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual bool Exists(
        string id
)
```

VB

```
Public Overridable Function Exists (
        id As String
) As Boolean
```

Parameters

id

Type: System.String

Return Value

Type: Boolean

See Also

DemandSupplyLink Class

Lsa.Vmfg.Sales Namespace

DemandSupplyLink.Find Method

Retrieve a specific Demand Supply Link from the database.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Find(
        string id
)
```

VB

```
Public Overridable Sub Find (
        id As String
)
```

Parameters

id

Type: System.String

See Also

DemandSupplyLink Class

Lsa.Vmfg.Sales Namespace

DemandSupplyLink.Load Method

Overload List

	Name	Description
	Load(String)	Loads a specific Demand Supply Link, based on the ID provided.
	Load(String, String)	Loads a Demand Supply Link, based on the demand type and demand base ID provided.
	Load(String, String, Int32)	Loads a Demand Supply Link, based on the demand type, demand base ID and demand seq no provided.
	Load(String, String, String)	Loads a Demand Supply Link, based on the demand type, demand base ID and demand lot ID provided.
	Load(String, String, Int32, Int32)	Loads a Demand Supply Link, based on the demand type, demand base ID, demand seq no, and demand no provided.
	Load(String, String, String, String)	Loads a Demand Supply Link, based on the demand type, demand base ID, demand lot ID, and demand split ID provided.
	Load(String, String, String, String, String)	Loads a Demand Supply Link, based on the demand type, demand base ID, demand lot ID, demand split ID, and demand sub ID provided.
	Load(String, String, String, String, String, Int32, Int32)	Loads a Demand Supply Link, based on the demand type, demand base ID, demand lot ID, demand split ID, demand sub ID, and demand no provided.

See Also

DemandSupplyLink Class

Lsa.Vmfg.Sales Namespace

DemandSupplyLink.Load Method (String)

Loads a specific Demand Supply Link, based on the ID provided.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string id
)
```

VB

```
Public Overridable Sub Load (
        id As String
)
```

Parameters

id

Type: System.String

See Also

DemandSupplyLink Class
Load Overload
Lsa.Vmfg.Sales Namespace

DemandSupplyLink.Load Method (String, String)

Loads a Demand Supply Link, based on the demand type and demand base ID provided.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string demandType,
        string demandBaseID
)
```

VB

```
Public Overridable Sub Load (
        demandType As String,
        demandBaseID As String
)
```

Parameters

demandType

Type: System.String

demandBaseID

Type: System.String

See Also

DemandSupplyLink Class

Load Overload

Lsa.Vmfg.Sales Namespace

DemandSupplyLink.Load Method (String, String, Int32)

Loads a Demand Supply Link, based on the demand type, demand base ID and demand seq no provided.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string demandType,
        string demandBaseID,
        int demandSeqNo
)
```

VB

```
Public Overridable Sub Load (
        demandType As String,
        demandBaseID As String,
        demandSeqNo As Integer
)
```

Parameters

demandType

Type: System.String

demandBaseID

Type: System.String

demandSeqNo

Type: System.Int32

See Also

DemandSupplyLink Class

Load Overload

Lsa.Vmfg.Sales Namespace

DemandSupplyLink.Load Method (String, String, String)

Loads a Demand Supply Link, based on the demand type, demand base ID and demand lot ID provided.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string demandType,
        string demandBaseID,
        string demandLotID
)
```

VB

```
Public Overridable Sub Load (
        demandType As String,
        demandBaseID As String,
        demandLotID As String
)
```

Parameters

demandType

Type: System.String

demandBaseID

Type: System.String

demandLotID

Type: System.String

See Also

DemandSupplyLink Class

Load Overload

Lsa.Vmfg.Sales Namespace

DemandSupplyLink.Load Method (String, String, Int32, Int32)

Loads a Demand Supply Link, based on the demand type, demand base ID, demand seq no, and demand no provided.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string demandType,
        string demandBaseID,
        int demandSeqNo,
        int demandNo
)
```

VB

```
Public Overridable Sub Load (
        demandType As String,
        demandBaseID As String,
        demandSeqNo As Integer,
        demandNo As Integer
)
```

Parameters

demandType

Type: System.String

demandBaseID

Type: System.String

demandSeqNo

Type: System.Int32

demandNo

Type: System.Int32

See Also

DemandSupplyLink Class
Load Overload
Lsa.Vmfg.Sales Namespace

DemandSupplyLink.Load Method (String, String, String, String)

Loads a Demand Supply Link, based on the demand type, demand base ID, demand lot ID, and demand split ID provided.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string demandType,
        string demandBaseID,
        string demandLotID,
        string demandSplitID
)
```

VB

```
Public Overridable Sub Load (
        demandType As String,
        demandBaseID As String,
        demandLotID As String,
        demandSplitID As String
)
```

Parameters

demandType

Type: System.String

demandBaseID

Type: System.String

demandLotID

Type: System.String

demandSplitID

Type: System.String

See Also

DemandSupplyLink Class
Load Overload
Lsa.Vmfg.Sales Namespace

DemandSupplyLink.Load Method (String, String, String, String, String)

Loads a Demand Supply Link, based on the demand type, demand base ID, demand lot ID, demand split ID, and demand sub ID provided.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string demandType,
        string demandBaseID,
        string demandLotID,
        string demandSplitID,
        string demandSubID
)
```

VB

```
Public Overridable Sub Load (
        demandType As String,
        demandBaseID As String,
        demandLotID As String,
        demandSplitID As String,
        demandSubID As String
)
```

Parameters

demandType

Type: System.String

demandBaseID

Type: System.String

demandLotID

Type: System.String

demandSplitID

Type: System.String

demandSubID

Type: System.String

See Also

DemandSupplyLink Class
Load Overload
Lsa.Vmfg.Sales Namespace

DemandSupplyLink.Load Method (String, String, String, String, String, Int32, Int32)

Loads a Demand Supply Link, based on the demand type, demand base ID, demand lot ID, demand split ID, demand sub ID, and demand no provided.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string demandType,
        string demandBaseID,
        string demandLotID,
        string demandSplitID,
        string demandSubID,
        int demandSeqNo,
        int demandNo
)
```

VB

```
Public Overridable Sub Load (
        demandType As String,
        demandBaseID As String,
        demandLotID As String,
        demandSplitID As String,
        demandSubID As String,
        demandSeqNo As Integer,
        demandNo As Integer
)
```

Parameters

demandType

Type: System.String

demandBaseID

Type: System.String

demandLotID

Type: System.String

demandSplitID
Type: System.String
demandSubID
Type: System.String
demandSeqNo
Type: System.Int32
demandNo
Type: System.Int32

See Also

DemandSupplyLink Class
Load Overload
Lsa.Vmfg.Sales Namespace

DemandSupplyLink.NewDemandSupplyLinkRow Method

Insert a new row into the DEMAND_SUPPLY_LINK table.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewDemandSupplyLinkRow(
        string id
)
```

VB

```
Public Overridable Function NewDemandSupplyLinkRow (
        id As String
) As DataRow
```

Parameters

id

Type: System.String

Return Value

Type: **DataRow**

See Also

DemandSupplyLink Class

Lsa.Vmfg.Sales Namespace

DemandSupplyLink.Save Method

Save all previously loaded Demand Supply Links to the database.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

DemandSupplyLink Class
Lsa.Vmfg.Sales Namespace

DiscountPrices Class

Maintain Price Breaks for Discount Codes.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessDocument
          Lsa.Vmfg.Sales.DiscountPrices

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public class DiscountPrices : BusinessDocument

VB
Public Class DiscountPrices   Inherits BusinessDocument

The **DiscountPrices** type exposes the following members.

Constructors

	Name	Description
	DiscountPrices()	Constructor
	DiscountPrices(String)	Constructor

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Discount Prices based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Discount Prices based on search criteria, limited by the sortColumns and maxRecords parameters.
	Exists	Detmerine if a specific a Discount Price exists.
	Find	Retrieves a specific Discount Price.
	Load()	Loads all Discount Prices.
	Load(String, String, String)	Loads a specific Discount Price.
	NewDiscountPriceRow	Inserts a new row into the DISCOUNT_PRICE table.
	Save	Save all changes to previously loaded Discount Price data to the database.

See Also

Lsa.Vmfg.Sales Namespace

DiscountPrices Constructor

Overload List

	Name	Description
	DiscountPrices()	Constructor
	DiscountPrices(String)	Constructor

See Also

DiscountPrices Class
Lsa.Vmfg.Sales Namespace

DiscountPrices Constructor

Constructor

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public DiscountPrices()

VB
Public Sub New

See Also

DiscountPrices Class
DiscountPrices Overload
Lsa.Vmfg.Sales Namespace

DiscountPrices Constructor (String)

Constructor

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public DiscountPrices(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

DiscountPrices Class

DiscountPrices Overload

Lsa.Vmfg.Sales Namespace

DiscountPrices.DiscountPrices Methods

The DiscountPrices type exposes the following members.

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Discount Prices based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Discount Prices based on search criteria, limited by the sortColumns and maxRecords parameters.
	Exists	Detmerine if a specific a Discount Price exists.
	Find	Retrieves a specific Discount Price.
	Load()	Loads all Discount Prices.
	Load(String, String, String)	Loads a specific Discount Price.
	NewDiscountPriceRow	Inserts a new row into the DISCOUNT_PRICE table.
	Save	Save all changes to previously loaded Discount Price data to the database.

See Also

DiscountPrices Class

Lsa.Vmfg.Sales Namespace

DiscountPrices.Browse Method

Overload List

	Name	Description
	Browse(String, String, String)	Retrieve Discount Prices based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Discount Prices based on search criteria, limited by the sortColumns and maxRecords parameters.

See Also

DiscountPrices Class

Lsa.Vmfg.Sales Namespace

DiscountPrices.Browse Method (String, String, String)

Retrieve Discount Prices based on search criteria.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

Return Value

Type: **DataSet**

See Also

DiscountPrices Class
Browse Overload
Lsa.Vmfg.Sales Namespace

DiscountPrices.Browse Method (String, String, String, Int32, Int32)

Retrieve Discount Prices based on search criteria, limited by the sortColumns and maxRecords parameters.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns,
        int startRecord,
        int maxRecords
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String,
        startRecord As Integer,
        maxRecords As Integer
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

startRecord

Type: System.Int32

maxRecords

Type: System.Int32

Return Value

Type: **DataSet**

See Also

DiscountPrices Class
Browse Overload
Lsa.Vmfg.Sales Namespace

DiscountPrices.Exists Method

Detmerine if a specific a Discount Price exists.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual bool Exists(
        string discountCode,
        string partID,
        string sellingUM
)
```

VB

```
Public Overridable Function Exists (
        discountCode As String,
        partID As String,
        sellingUM As String
) As Boolean
```

Parameters

discountCode

Type: System.String

partID

Type: System.String

sellingUM

Type: System.String

Return Value

Type: Boolean

See Also

DiscountPrices Class

Lsa.Vmfg.Sales Namespace

DiscountPrices.Find Method

Retrieves a specific Discount Price.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Find(
        string discountCode,
        string partID,
        string sellingUM
)
```

VB

```
Public Overridable Sub Find (
        discountCode As String,
        partID As String,
        sellingUM As String
)
```

Parameters

discountCode

Type: System.String

partID

Type: System.String

sellingUM

Type: System.String

See Also

DiscountPrices Class

Lsa.Vmfg.Sales Namespace

DiscountPrices.Load Method

Overload List

	Name	Description
	Load()	Loads all Discount Prices.
	Load(String, String, String)	Loads a specific Discount Price.

See Also

DiscountPrices Class
Lsa.Vmfg.Sales Namespace

DiscountPrices.Load Method

Loads all Discount Prices.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Load()

VB
Public Overridable Sub Load

See Also

DiscountPrices Class
Load Overload
Lsa.Vmfg.Sales Namespace

DiscountPrices.Load Method (String, String, String)

Loads a specific Discount Price.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string discountCode,
        string partID,
        string sellingUM
)
```

VB

```
Public Overridable Sub Load (
        discountCode As String,
        partID As String,
        sellingUM As String
)
```

Parameters

discountCode

Type: System.String

partID

Type: System.String

sellingUM

Type: System.String

See Also

DiscountPrices Class

Load Overload

Lsa.Vmfg.Sales Namespace

DiscountPrices.NewDiscountPriceRow Method

Inserts a new row into the DISCOUNT_PRICE table.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public DataRow NewDiscountPriceRow(
        string discountCode,
        string siteID,
        string partID,
        string sellingUM
)
```

VB

```
Public Function NewDiscountPriceRow (
        discountCode As String,
        siteID As String,
        partID As String,
        sellingUM As String
) As DataRow
```

Parameters

discountCode

Type: System.String

siteID

Type: System.String

partID

Type: System.String

sellingUM

Type: System.String

Return Value

Type: **DataRow**

See Also

DiscountPrices Class

Lsa.Vmfg.Sales Namespace

DiscountPrices.Save Method

Save all changes to previously loaded Discount Price data to the database.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

DiscountPrices Class
Lsa.Vmfg.Sales Namespace

OrderFromQuote Class

Transaction to create new Customer Orders from existing Quotes.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessTransaction
          Lsa.Vmfg.Sales.OrderFromQuote

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class OrderFromQuote : BusinessTransaction
```

VB

```
<SerializableAttribute>
Public Class OrderFromQuote
        Inherits BusinessTransaction
```

The **OrderFromQuote** type exposes the following members.

Constructors

	Name	Description
	OrderFromQuote()	Business Transaction Constructor
	OrderFromQuote(String)	Business Transaction Constructor

Methods

	Name	Description
	NewOrderFromQuoteLineRow	Inserts a new row into the ORDER_FROM_QUOTE_LINE transaction data table.
	NewOrderFromQuoteRow	Inserts a new row into the ORDER_FROM_QUOTE transaction data table.
	Prepare	Creates an empty dataset for the transaction. This method returns an empty dataset that you must populate prior to saving the transaction.
	Save	Saves the transaction(s).

Transaction

	Name	Data set returned by Prepare	Description
	OrderFromQuote	ORDER_FROM_QUOTE	This transaction will create a new Customer Order from an existing Quote.

See Also

Lsa.Vmfg.Sales Namespace

OrderFromQuote Constructor

Overload List

	Name	Description
	OrderFromQuote()	Business Transaction Constructor
	OrderFromQuote(String)	Business Transaction Constructor

See Also

OrderFromQuote Class
Lsa.Vmfg.Sales Namespace

OrderFromQuote Constructor

Business Transaction Constructor

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public OrderFromQuote()

VB
Public Sub New

See Also

OrderFromQuote Class
OrderFromQuote Overload
Lsa.Vmfg.Sales Namespace

OrderFromQuote Constructor (String)

Business Transaction Constructor

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public OrderFromQuote(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

OrderFromQuote Class

OrderFromQuote Overload

Lsa.Vmfg.Sales Namespace

OrderFromQuote.OrderFromQuote Methods

The OrderFromQuote type exposes the following members.

Methods

	Name	Description
	NewOrderFromQuoteLineRow	Inserts a new row into the ORDER_FROM_QUOTE_LINE transaction data table.
	NewOrderFromQuoteRow	Inserts a new row into the ORDER_FROM_QUOTE transaction data table.
	Prepare	Creates an empty dataset for the transaction. This method returns an empty dataset that you must populate prior to saving the transaction.
	Save	Saves the transaction(s).

See Also

OrderFromQuote Class

Lsa.Vmfg.Sales Namespace

OrderFromQuote.NewOrderFromQuoteLineRow Method

Inserts a new row into the ORDER_FROM_QUOTE_LINE transaction data table.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewOrderFromQuoteLineRow(
        string quoteID,
        int quoteLineNo,
        decimal qty
)
```

VB

```
Public Overridable Function NewOrderFromQuoteLineRow (
        quoteID As String,
        quoteLineNo As Integer,
        qty As Decimal
) As DataRow
```

Parameters

quoteID

Type: System.String

quoteLineNo

Type: System.Int32

qty

Type: System.Decimal

Return Value

Type: **DataRow**

Transaction

	Name	Data set returned by Prepare	Description
	OrderFromQuote	ORDER_FROM_QUOTE	This transaction will create a new Customer Order from an existing Quote.

See Also

OrderFromQuote Class
Lsa.Vmfg.Sales Namespace

OrderFromQuote.NewOrderFromQuoteRow Method

Inserts a new row into the ORDER_FROM_QUOTE transaction data table.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewOrderFromQuoteRow(
        string quoteID
)
```

VB

```
Public Overridable Function NewOrderFromQuoteRow (
        quoteID As String
) As DataRow
```

Parameters

quoteID

Type: System.String

Return Value

Type: **DataRow**

Transaction

	Name	Data set returned by Prepare	Description
	OrderFromQuote	ORDER_FROM_QUOTE	This transaction will create a new Customer Order from an existing Quote.

See Also

OrderFromQuote Class
Lsa.Vmfg.Sales Namespace

OrderFromQuote.Prepare Method

Creates an empty dataset for the transaction. This method returns an empty dataset that you must populate prior to saving the transaction.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Prepare()

VB
Public Overridable Sub Prepare

See Also

OrderFromQuote Class
Lsa.Vmfg.Sales Namespace

OrderFromQuote.Save Method

Saves the transaction(s).

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

OrderFromQuote Class
Lsa.Vmfg.Sales Namespace

OrderFromQuote

This transaction will create a new Customer Order from an existing Quote.

Namespace: Lsa.Vmfg.Sales

Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

DataSet name returned from Prepare: ORDER_FROM_QUOTE

Primary Key: QUOTE_ID

Column Name	Type	Description
QUOTE_ID	String	The ID of the Quote that will be the source of the new Customer Order.
SITE_ID	String	The Site ID of the Quote
DESIRED_SHIP_DATE	Date	Setting for the desired ship date of the newly created order. Defaults to current date.
PROMISE_DATE	Date	Optional.
CUSTOMER_ID	String	The value of the customer ID for the new order. If left blank, the customer ID from the source Quote ID is used.
CUST_ORDER_ID	String	The value of the customer order ID for the new order. If left blank, the new order will be auto numbered.
CUSTOMER_PO_REF	String	Optional.
ORDER_STATUS	String	The value for the status of the new order. Default value is “F”.
CREATE_WORK_ORDERS	Boolean	Boolean flag to indicate whether new linked work orders for the new order will be created from the source quote master. Default value is false (do not create work orders).
USER_ORDER_ID	Boolean	Boolean flag, if set to true, indicates that the newly created work order’s base ID is to be set to the new customer order ID. If set to false, the new work order’s base Ids will be auto numbered.
COPY_SPECS	Boolean	If true, the quote specs will be copied over to the customer order. Default value is false.
COPY_USER_DEFINED	Boolean	If true, the user defined fields for the source quote will be copied over to the

Column Name	Type	Description
		target customer order. Default value is false.
COPY_HEADER_INFO	Boolean	If true, the header information from the quote record is copied to the new customer order. If false, the header information is populated from the values in the customer table. Default is false.

See Also

OrderFromQuote Class
OrderFromQuote.NewOrderFromQuoteLineRow
OrderFromQuote.NewOrderFromQuoteRow
Lsa.Vmfg.Sales Namespace

Priority Class

Maintain Priority Codes.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessDocument
          Lsa.Vmfg.Sales.Priority

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class Priority : BusinessDocument
```

VB

```
<SerializableAttribute>
Public Class Priority
        Inherits BusinessDocument
```

The **Priority** type exposes the following members.

Constructors

	Name	Description
	Priority()	Constructor
	Priority(String)	Constructor

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Priority Codes based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Priority Codes based on search criteria, limited by the values in the startRecord and maxRecords parameters.
	Exists	Determine if a specific Priority Code exists.
	Find	Retrieve a specific Priority Code.
	Load()	Loads all Priority Codes.
	Load(String)	Loads a specific Priority Code.
	Load(Stream, String)	Load from stream and rename using new key.
	NewPriorityRow	Inserts a new row into the PRIORITY table.
	Save()	Save all previously loaded Priority Codes to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

Lsa.Vmfg.Sales Namespace

Priority Constructor

Overload List

	Name	Description
	Priority()	Constructor
	Priority(String)	Constructor

See Also

Priority Class
Lsa.Vmfg.Sales Namespace

Priority Constructor

Constructor

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public Priority()

VB
Public Sub New

See Also

Priority Class
Priority Overload
Lsa.Vmfg.Sales Namespace

Priority Constructor (String)

Constructor

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public Priority(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

Priority Class

Priority Overload

Lsa.Vmfg.Sales Namespace

Priority.Priority Methods

The Priority type exposes the following members.

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Priority Codes based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Priority Codes based on search criteria, limited by the values in the startRecord and maxRecords parameters.
	Exists	Determine if a specific Priority Code exists.
	Find	Retrieve a specific Priority Code.
	Load()	Loads all Priority Codes.
	Load(String)	Loads a specific Priority Code.
	Load(Stream, String)	Load from stream and rename using new key.
	NewPriorityRow	Inserts a new row into the PRIORITY table.
	Save()	Save all previously loaded Priority Codes to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

Priority Class

Lsa.Vmfg.Sales Namespace

Priority.Browse Method

Overload List

	Name	Description
	Browse(String, String, String)	Retrieve Priority Codes based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Priority Codes based on search criteria, limited by the values in the startRecord and maxRecords parameters.

See Also

Priority Class

Lsa.Vmfg.Sales Namespace

Priority.Browse Method (String, String, String)

Retrieve Priority Codes based on search criteria.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

Return Value

Type: **DataSet**

See Also

Priority Class

Browse Overload
Lsa.Vmfg.Sales Namespace

Priority.Browse Method (String, String, String, Int32, Int32)

Retrieve Priority Codes based on search criteria, limited by the values in the startRecord and maxRecords parameters.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns,
        int startRecord,
        int maxRecords
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String,
        startRecord As Integer,
        maxRecords As Integer
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

startRecord

Type: System.Int32

maxRecords

Type: System.Int32

Return Value

Type: **DataSet**

See Also

Priority Class
Browse Overload
Lsa.Vmfg.Sales Namespace

Priority.Exists Method

Determine if a specific Priority Code exists.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual bool Exists(
        string code
)
```

VB

```
Public Overridable Function Exists (
        code As String
) As Boolean
```

Parameters

code

Type: System.String

Return Value

Type: Boolean

See Also

Priority Class

Lsa.Vmfg.Sales Namespace

Priority.Find Method

Retrieve a specific Priority Code.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Find(
        string code
)
```

VB

```
Public Overridable Sub Find (
        code As String
)
```

Parameters

code

Type: System.String

See Also

Priority Class

Lsa.Vmfg.Sales Namespace

Priority.Load Method

Overload List

	Name	Description
	Load()	Loads all Priority Codes.
	Load(String)	Loads a specific Priority Code.
	Load(Stream, String)	Load from stream and rename using new key.

See Also

Priority Class
Lsa.Vmfg.Sales Namespace

Priority.Load Method

Loads all Priority Codes.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Load()

VB
Public Overridable Sub Load

See Also

Priority Class
Load Overload
Lsa.Vmfg.Sales Namespace

Priority.Load Method (String)

Loads a specific Priority Code.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string code
)
```

VB

```
Public Overridable Sub Load (
        code As String
)
```

Parameters

code

Type: System.String

See Also

Priority Class
Load Overload
Lsa.Vmfg.Sales Namespace

Priority.Load Method (Stream, String)

Load from stream and rename using new key.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        Stream stream,
        string code
)
```

VB

```
Public Overridable Sub Load (
        stream As Stream,
        code As String
)
```

Parameters

stream

Type: System.IO.Stream

code

Type: System.String

See Also

Priority Class

Load Overload

Lsa.Vmfg.Sales Namespace

Priority.NewPriorityRow Method

Inserts a new row into the PRIORITY table.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public DataRow NewPriorityRow(
        string code
)
```

VB

```
Public Function NewPriorityRow (
        code As String
) As DataRow
```

Parameters

code

Type: System.String

Return Value

Type: **DataRow**

See Also

Priority Class

Lsa.Vmfg.Sales Namespace

Priority.Save Method

Overload List

	Name	Description
	Save()	Save all previously loaded Priority Codes to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

Priority Class
Lsa.Vmfg.Sales Namespace

Priority.Save Method

Save all previously loaded Priority Codes to the database.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

Priority Class
Save Overload
Lsa.Vmfg.Sales Namespace

Priority.Save Method (Stream)

Save current state of data set to stream.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Save(
        Stream stream
)
```

VB

```
Public Overridable Sub Save (
        stream As Stream
)
```

Parameters

stream

Type: System.IO.Stream

See Also

Priority Class

Save Overload

Lsa.Vmfg.Sales Namespace

Quote Class

Maintain Quotes.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessDocument
          Lsa.Vmfg.Sales.Quote

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class Quote : BusinessDocument
```

VB

```
<SerializableAttribute>
Public Class Quote
        Inherits BusinessDocument
```

The **Quote** type exposes the following members.

Constructors

	Name	Description
	Quote()	Constructor
	Quote(String)	Constructor

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Quotes based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Quotes based on search criteria, limited by the values of the startRecord and maxRecords parameters.
	Exists	Determines if a specific Quote exists.
	Find	Retrieves a specific Quote record from the database. Note: Only the top-level table (QUOTE) is returned.
	Load	Loads a specific Quote.
	NewQuoteBinaryRow	Inserts a new row into the QUOTE_BINARY table. Only Binary type "D" (long text) is supported.
	NewQuotedOptionsRow	Inserts a new row into the QUOTED_OPTIONS table
	NewQuoteLineBinaryRow	Inserts a new row into the QUOTE_LINE_BINARY table. Only Binary type "D" (long text) is supported.
	NewQuoteLineRow(String)	Inserts a new row into the QUOTE_LINE table. Auto numbers LINE_NO.
	NewQuoteLineRow(String, Int32)	Inserts a new row into the QUOTE_LINE table
	NewQuotePriceRow	Inserts a new line into the QUOTE_PRICE table.
	NewQuoteRow	Inserts a new row into the QUOTE table.
	Save	Saves all previously loaded Quotes to the database.

See Also

Lsa.Vmfg.Sales Namespace

Quote Constructor

Overload List

	Name	Description
	Quote()	Constructor
	Quote(String)	Constructor

See Also

Quote Class
Lsa.Vmfg.Sales Namespace

Quote Constructor

Constructor

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public Quote()

VB
Public Sub New

See Also

Quote Class
Quote Overload
Lsa.Vmfg.Sales Namespace

Quote Constructor (String)

Constructor

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public Quote(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

Quote Class

Quote Overload

Lsa.Vmfg.Sales Namespace

Quote.Quote Methods

The Quote type exposes the following members.

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Quotes based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Quotes based on search criteria, limited by the values of the startRecord and maxRecords parameters.
	Exists	Determines if a specific Quote exists.
	Find	Retrieves a specific Quote record from the database. Note: Only the top-level table (QUOTE) is returned.
	Load	Loads a specific Quote.
	NewQuoteBinaryRow	Inserts a new row into the QUOTE_BINARY table. Only Binary type "D" (long text) is supported.
	NewQuotedOptionsRow	Inserts a new row into the QUOTED_OPTIONS table
	NewQuoteLineBinaryRow	Inserts a new row into the QUOTE_LINE_BINARY table. Only Binary type "D" (long text) is supported.
	NewQuoteLineRow(String)	Inserts a new row into the QUOTE_LINE table. Auto numbers LINE_NO.
	NewQuoteLineRow(String, Int32)	Inserts a new row into the QUOTE_LINE table
	NewQuotePriceRow	Inserts a new line into the QUOTE_PRICE table.
	NewQuoteRow	Inserts a new row into the QUOTE table.
	Save	Saves all previously loaded Quotes to the database.

See Also

Quote Class

Lsa.Vmfg.Sales Namespace

Quote.Browse Method

Overload List

	Name	Description
	Browse(String, String, String)	Retrieve Quotes based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Quotes based on search criteria, limited by the values of the startRecord and maxRecords parameters.

See Also

Quote Class

Lsa.Vmfg.Sales Namespace

Quote.Browse Method (String, String, String)

Retrieve Quotes based on search criteria.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

Return Value

Type: **DataSet**

See Also

Quote Class

Browse Overload
Lsa.Vmfg.Sales Namespace

Quote.Browse Method (String, String, String, Int32, Int32)

Retrieve Quotes based on search criteria, limited by the values of the startRecord and maxRecords parameters.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns,
        int startRecord,
        int maxRecords
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String,
        startRecord As Integer,
        maxRecords As Integer
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

startRecord

Type: System.Int32

maxRecords

Type: System.Int32

Return Value

Type: **DataSet**

See Also

Quote Class
Browse Overload
Lsa.Vmfg.Sales Namespace

Quote.Exists Method

Determines if a specific Quote exists.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual bool Exists(
        string quoteID
)
```

VB

```
Public Overridable Function Exists (
        quoteID As String
) As Boolean
```

Parameters

quoteID

Type: System.String

Return Value

Type: Boolean

See Also

Quote Class

Lsa.Vmfg.Sales Namespace

Quote.Find Method

Retrieves a specific Quote record from the database. Note: Only the top-level table (QUOTE) is returned.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Find(
        string quoteID
)
```

VB

```
Public Overridable Sub Find (
        quoteID As String
)
```

Parameters

quoteID

Type: System.String

See Also

Quote Class

Lsa.Vmfg.Sales Namespace

Quote.Load Method

Loads a specific Quote.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string quoteID
)
```

VB

```
Public Overridable Sub Load (
        quoteID As String
)
```

Parameters

quoteID

Type: System.String

See Also

Quote Class

Lsa.Vmfg.Sales Namespace

Quote.NewQuoteBinaryRow Method

Inserts a new row into the QUOTE_BINARY table. Only Binary type "D" (long text) is supported.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewQuoteBinaryRow(
        string quoteID,
        string binaryType
)
```

VB

```
Public Overridable Function NewQuoteBinaryRow (
        quoteID As String,
        binaryType As String
) As DataRow
```

Parameters

quoteID

Type: System.String

binaryType

Type: System.String

Return Value

Type: **DataRow**

See Also

Quote Class

Lsa.Vmfg.Sales Namespace

Quote.NewQuotedOptionsRow Method

Inserts a new row into the QUOTED_OPTIONS table

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewQuotedOptionsRow(
        string quoteID,
        int lineNo,
        int seqNo
)
```

VB

```
Public Overridable Function NewQuotedOptionsRow (
        quoteID As String,
        lineNo As Integer,
        seqNo As Integer
) As DataRow
```

Parameters

quoteID

Type: System.String

lineNo

Type: System.Int32

seqNo

Type: System.Int32

Return Value

Type: **DataRow**

See Also

Quote Class

Lsa.Vmfg.Sales Namespace

Quote.NewQuoteLineBinaryRow Method

Inserts a new row into the QUOTE_LINE_BINARY table. Only Binary type "D" (long text) is supported.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewQuoteLineBinaryRow(
        string quoteID,
        int quoteLineNo,
        string binaryType
)
```

VB

```
Public Overridable Function NewQuoteLineBinaryRow (
        quoteID As String,
        quoteLineNo As Integer,
        binaryType As String
) As DataRow
```

Parameters

quoteID

Type: System.String

quoteLineNo

Type: System.Int32

binaryType

Type: System.String

Return Value

Type: **DataRow**

See Also

Quote Class

Lsa.Vmfg.Sales Namespace

Quote.NewQuoteLineRow Method

Overload List

	Name	Description
	NewQuoteLineRow(String)	Inserts a new row into the QUOTE_LINE table. Auto numbers LINE_NO.
	NewQuoteLineRow(String, Int32)	Inserts a new row into the QUOTE_LINE table

See Also

Quote Class

Lsa.Vmfg.Sales Namespace

Quote.NewQuoteLineRow Method (String)

Inserts a new row into the QUOTE_LINE table. Auto numbers LINE_NO.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewQuoteLineRow(
        string quoteID
)
```

VB

```
Public Overridable Function NewQuoteLineRow (
        quoteID As String
) As DataRow
```

Parameters

quoteID

Type: System.String

Return Value

Type: **DataRow**

See Also

Quote Class

NewQuoteLineRow Overload

Lsa.Vmfg.Sales Namespace

Quote.NewQuoteLineRow Method (String, Int32)

Inserts a new row into the QUOTE_LINE table

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewQuoteLineRow(
        string quoteID,
        int lineNo
)
```

VB

```
Public Overridable Function NewQuoteLineRow (
        quoteID As String,
        lineNo As Integer
) As DataRow
```

Parameters

quoteID

Type: System.String

lineNo

Type: System.Int32

Return Value

Type: **DataRow**

See Also

Quote Class

NewQuoteLineRow Overload

Lsa.Vmfg.Sales Namespace

Quote.NewQuotePriceRow Method

Inserts a new line into the QUOTE_PRICE table.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewQuotePriceRow(
        string quoteID,
        long lineNo,
        decimal qty
)
```

VB

```
Public Overridable Function NewQuotePriceRow (
        quoteID As String,
        lineNo As Long,
        qty As Decimal
) As DataRow
```

Parameters

quoteID

Type: System.String

lineNo

Type: System.Int64

qty

Type: System.Decimal

Return Value

Type: **DataRow**

See Also

Quote Class

Lsa.Vmfg.Sales Namespace

Quote.NewQuoteRow Method

Inserts a new row into the QUOTE table.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewQuoteRow(
        string quoteID
)
```

VB

```
Public Overridable Function NewQuoteRow (
        quoteID As String
) As DataRow
```

Parameters

quoteID

Type: System.String

Return Value

Type: **DataRow**

See Also

Quote Class

Lsa.Vmfg.Sales Namespace

Quote.Save Method

Saves all previously loaded Quotes to the database.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

Quote Class
Lsa.Vmfg.Sales Namespace

Return Class

Transaction to perform returns on Customer Orders.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessTransaction
          Lsa.Vmfg.Sales.Return

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class Return : BusinessTransaction
```

VB

```
<SerializableAttribute>
Public Class Return
        Inherits BusinessTransaction
```

The **Return** type exposes the following members.

Constructors

	Name	Description
	Return()	Business Transaction Constructor
	Return(String)	Business Transaction Constructor

Methods

	Name	Description
	NewReturnDelSchedLineRow	Inserts a new row into the DEL_SCHED_LINE transaction data table.
	NewReturnLineRow	Inserts a new row into the RETURN_LINE transaction data table.
	NewReturnRow	Inserts a new row into the RETURN transaction data table.
	NewReturnTraceRow	Inserts a new row into the TRACE transaction data table.
	Prepare	Creates an empty dataset for the transaction. This method returns an empty dataset that you must populate prior to saving the transaction.
	Save	Saves the transaction(s).

Transaction

	Name	Data set returned by Prepare	Description
	Return	RETURN	This transaction will create a new Shipment Return from an existing Customer Order.

See Also

Lsa.Vmfg.Sales Namespace

Return Constructor

Overload List

	Name	Description
	Return()	Business Transaction Constructor
	Return(String)	Business Transaction Constructor

See Also

Return Class
Lsa.Vmfg.Sales Namespace

Return Constructor

Business Transaction Constructor

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public Return()

VB
Public Sub New

See Also

Return Class
Return Overload
Lsa.Vmfg.Sales Namespace

Return Constructor (String)

Business Transaction Constructor

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public Return(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

Return Class

Return Overload

Lsa.Vmfg.Sales Namespace

Return.Return Methods

The Return type exposes the following members.

Methods

	Name	Description
	NewReturnDelSchedLineRow	Inserts a new row into the DEL_SCHED_LINE transaction data table.
	NewReturnLineRow	Inserts a new row into the RETURN_LINE transaction data table.
	NewReturnRow	Inserts a new row into the RETURN transaction data table.
	NewReturnTraceRow	Inserts a new row into the TRACE transaction data table.
	Prepare	Creates an empty dataset for the transaction. This method returns an empty dataset that you must populate prior to saving the transaction.
	Save	Saves the transaction(s).

See Also

Return Class

Lsa.Vmfg.Sales Namespace

Return.NewReturnDelSchedLineRow Method

Inserts a new row into the DEL_SCHED_LINE transaction data table.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewReturnDelSchedLineRow(
        string custOrderID,
        int custOrderLineNo,
        int delSchedLineNo
)
```

VB

```
Public Overridable Function NewReturnDelSchedLineRow (
        custOrderID As String,
        custOrderLineNo As Integer,
        delSchedLineNo As Integer
) As DataRow
```

Parameters

custOrderID

Type: System.String

custOrderLineNo

Type: System.Int32

delSchedLineNo

Type: System.Int32

Return Value

Type: **DataRow**

Transaction

	Name	Data set returned by Prepare	Description
	Return	RETURN	This transaction will create a new Shipment Return from an existing Customer Order.

See Also

Return Class

Lsa.Vmfg.Sales Namespace

Return.NewReturnLineRow Method

Inserts a new row into the RETURN_LINE transaction data table.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewReturnLineRow(
        string custOrderID,
        int custOrderLineNo
)
```

VB

```
Public Overridable Function NewReturnLineRow (
        custOrderID As String,
        custOrderLineNo As Integer
) As DataRow
```

Parameters

custOrderID

Type: System.String

custOrderLineNo

Type: System.Int32

Return Value

Type: **DataRow**

Transaction

	Name	Data set returned by Prepare	Description
	Return	RETURN	This transaction will create a new Shipment Return from an existing Customer Order.

See Also

Return Class

Lsa.Vmfg.Sales Namespace

Return.NewReturnRow Method

Inserts a new row into the RETURN transaction data table.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewReturnRow(
        string custOrderID
)
```

VB

```
Public Overridable Function NewReturnRow (
        custOrderID As String
) As DataRow
```

Parameters

custOrderID

Type: System.String

Return Value

Type: **DataRow**

Transaction

	Name	Data set returned by Prepare	Description
	Return	RETURN	This transaction will create a new Shipment Return from an existing Customer Order.

See Also

Return Class

Lsa.Vmfg.Sales Namespace

Return.NewReturnTraceRow Method

Inserts a new row into the TRACE transaction data table.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewReturnTraceRow(
        string custOrderID,
        int custOrderLineNo,
        string traceID
)
```

VB

```
Public Overridable Function NewReturnTraceRow (
        custOrderID As String,
        custOrderLineNo As Integer,
        traceID As String
) As DataRow
```

Parameters

custOrderID

Type: System.String

custOrderLineNo

Type: System.Int32

traceID

Type: System.String

Return Value

Type: **DataRow**

Transaction

	Name	Data set returned by Prepare	Description
	Return	RETURN	This transaction will create a new Shipment Return from an existing Customer Order.

See Also

Return Class

Lsa.Vmfg.Sales Namespace

Return.Prepare Method

Creates an empty dataset for the transaction. This method returns an empty dataset that you must populate prior to saving the transaction.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Prepare()

VB
Public Overridable Sub Prepare

See Also

Return Class
Lsa.Vmfg.Sales Namespace

Return.Save Method

Saves the transaction(s).

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

Return Class
Lsa.Vmfg.Sales Namespace

Return

This transaction will create a new Shipment Return from an existing Customer Order.

Namespace: Lsa.Vmfg.Sales

Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

DataSet name returned from Prepare: RETURN

Primary Key: CUST_ORDER_ID

Column Name	Type	Description
CUST_ORDER_ID	String	The ID of the Customer Order being returned.
TRANSACTION_DATE	Date	Date of return transaction. Defaults to current date.
PACKLIST_ID	String	Unique ID for this Shipper (packlist). Will be automatically generated if left blank.
RETURN_ALL	Boolean	When this flag is set to true, the customer order will be returned in full. When this feature is used, the sub-tables for this transaction are populated automatically. You cannot use this feature if the order has either a delivery schedule or parts requiring lot / serial number tracing.
REOPEN_ORDER	Boolean	When this flag is set to true, the Customer Order will be reopened (status changed to Released).
REOPEN_WORKORDER	Boolean	When this flag is set to true, the Work Order associated with the return will be reopened.
RMA_ID	String	The Return Material Authorization ID for the Customer Order. Optional.
USER_ID	String	The User ID of the person performing the transaction. Defaults to SYSADM.
SITE_ID	String	Site ID of the Customer Order being returned. Defaults to site ID of the Customer Order.

Sub-Table Name: RETURN_LINE

Primary Key: CUST_ORDER_ID, CUST_ORDER_LINE

This table is required, unless the header table is set to RETURN_ALL.

Column Name	Type	Description
CUST_ORDER_ID	String	The ID of the Customer Order being returned. Must match the ID of the header table.
CUST_ORDER_LINE_NO	Integer	Line number of the order being returned.
USER_QTY	Decimal	The quantity being returned, in the shipping unit of measure.
ACT_FREIGHT	Decimal	Actual Freight amount. Optional.
WAREHOUSE_ID	String	Optional. If not specified, tries to locate the part's primary warehouse ID. If not found, uses the first valid warehouse found.
LOCATION_ID	String	Optional. Defaults to the part's primary location ID.

Sub-Table Name: DEL_SCHED_LINE

Primary Key: CUST_ORDER_ID, CUST_ORDER_LINE_NO, DEL_SCHED_LINE_NO

This sub-table is only applicable if the customer order line has a delivery schedule.

Column Name	Type	Description
CUST_ORDER_ID	String	The ID of the Customer Order being returned. Must match the ID of the header and line tables.
CUST_ORDER_LINE_NO	Integer	Line number of the order being returned. Must match an existing line number from the line table.
DEL_SCHED_LINE_NO	Integer	The line number of the delivery schedule being returned.
USER_QTY	Decimal	The quantity being returned for this delivery schedule line.

Sub-Table Name: TRACE

Primary Key: CUST_ORDER_ID, CUST_ORDER_LINE_NO, TRACE_ID

The TRACE_INFO sub-recordset may or may not be required, depending on the Part's trace profile.

Column Name	Type	Description
CUST_ORDER_ID	String	The ID of the Customer Order being returned. Must match the ID of the header and line tables.

Column Name	Type	Description
CUST_ORDER_LINE_NO	Integer	Line number of the order being returned. Must match an existing line number from the line table.
TRACE_ID	String	Trace ID. Lot or serial number for the parts being reported. If the part's trace profile supports auto numbering, and you wish to have the Trace IDs auto numbered, you must set the TRACE_ID values to the format "<n>" where n is a unique integer.
ALPHA_PROPERTY_1	String	May be required, depending on the Part's trace profile.
ALPHA_PROPERTY_2	String	May be required, depending on the Part's trace profile.
ALPHA_PROPERTY_3	String	May be required, depending on the Part's trace profile.
ALPHA_PROPERTY_4	String	May be required, depending on the Part's trace profile.
ALPHA_PROPERTY_5	String	May be required, depending on the Part's trace profile.
NUMERIC_PROPERTY_1	String	May be required, depending on the Part's trace profile.
NUMERIC_PROPERTY_2	String	May be required, depending on the Part's trace profile.
NUMERIC_PROPERTY_3	String	May be required, depending on the Part's trace profile.
NUMERIC_PROPERTY_4	String	May be required, depending on the Part's trace profile.
NUMERIC_PROPERTY_5	String	May be required, depending on the Part's trace profile.
EXPIRATION_DATE	Date	Expiration date. Determines shelf life of lot. Optional.
QTY		Quantity of transaction associated directly with this trace ID. The sum of all trace detail QTY fields must equal the total returned quantity for the associated return line item.
COMMENTS	String	Optional user comments on specific lot or serial number.
OWNER_ID	String	Owner ID. Optional.

See Also

Return Class
Return.NewReturnDelSchedLineRow
Return.NewReturnLineRow
Return.NewReturnRow
Return.NewReturnTraceRow
Lsa.Vmfg.Sales Namespace

ReturnMaterialAuth Class

Maintain Return Material Authorizations.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessDocument
          Lsa.Vmfg.Sales.ReturnMaterialAuth

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class ReturnMaterialAuth : BusinessDocument
```

VB

```
<SerializableAttribute>
Public Class ReturnMaterialAuth
        Inherits BusinessDocument
```

The **ReturnMaterialAuth** type exposes the following members.

Constructors

	Name	Description
	ReturnMaterialAuth()	Business Document Constructor
	ReturnMaterialAuth(String)	Business Document Constructor

Methods

	Name	Description
	Browse(String, String, String)	Retrieves RMA rows based on a search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieves RMA rows based on a search criteria, limited by the values of the startRecord and maxRecords parameters.
	Exists	Determines if a specific RMA exists.
	Find	Retrieves a specific RMA. Note: only the top-level table (RMA) is returned.
	Load(String)	Loads a specific RMA.
	Load(Stream, String)	Loads from stream and rename using new key.
	NewRMABinaryRow	Inserts a new row into the RMA_BINARY table. Note: Only binary types of "D" (long text) are supported.
	NewRMALineBinaryRow	Inserts a new row into the RMA_LINE_BINARY table. Note: Only binary types of "D" (long text) are supported.
	NewRMALineRow(String)	Inserts a new row into the RMA_LINE table. Auto numbers LINE_NO.
	NewRMALineRow(String, Int64)	Inserts a new row into the RMA_LINE table.
	NewRMARow	Inserts a new row into the RMA table.
	Save()	Saves all previously loaded RMAs to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

Lsa.Vmfg.Sales Namespace

ReturnMaterialAuth Constructor

Overload List

	Name	Description
	ReturnMaterialAuth()	Business Document Constructor
	ReturnMaterialAuth(String)	Business Document Constructor

See Also

ReturnMaterialAuth Class
Lsa.Vmfg.Sales Namespace

ReturnMaterialAuth Constructor

Business Document Constructor

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public ReturnMaterialAuth()

VB
Public Sub New

See Also

ReturnMaterialAuth Class
ReturnMaterialAuth Overload
Lsa.Vmfg.Sales Namespace

ReturnMaterialAuth Constructor (String)

Business Document Constructor

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public ReturnMaterialAuth(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

ReturnMaterialAuth Class

ReturnMaterialAuth Overload

Lsa.Vmfg.Sales Namespace

ReturnMaterialAuth.ReturnMaterialAuth Methods

The ReturnMaterialAuth type exposes the following members.

Methods

	Name	Description
	Browse(String, String, String)	Retrieves RMA rows based on a search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieves RMA rows based on a search criteria, limited by the values of the startRecord and maxRecords parameters.
	Exists	Determines if a specific RMA exists.
	Find	Retrieves a specific RMA. Note: only the top-level table (RMA) is returned.
	Load(String)	Loads a specific RMA.
	Load(Stream, String)	Loads from stream and rename using new key.
	NewRMABinaryRow	Inserts a new row into the RMA_BINARY table. Note: Only binary types of "D" (long text) are supported.
	NewRMALineBinaryRow	Inserts a new row into the RMA_LINE_BINARY table. Note: Only binary types of "D" (long text) are supported.
	NewRMALineRow(String)	Inserts a new row into the RMA_LINE table. Auto numbers LINE_NO.
	NewRMALineRow(String, Int64)	Inserts a new row into the RMA_LINE table.
	NewRMARow	Inserts a new row into the RMA table.
	Save()	Saves all previously loaded RMAs to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

ReturnMaterialAuth Class

Lsa.Vmfg.Sales Namespace

ReturnMaterialAuth.Browse Method

Overload List

	Name	Description
	Browse(String, String, String)	Retrieves RMA rows based on a search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieves RMA rows based on a search criteria, limited by the values of the startRecord and maxRecords parameters.

See Also

ReturnMaterialAuth Class

Lsa.Vmfg.Sales Namespace

ReturnMaterialAuth.Browse Method (String, String, String)

Retrieves RMA rows based on a search criteria.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

Return Value

Type: **DataSet**

See Also

ReturnMaterialAuth Class

Browse Overload

Lsa.Vmfg.Sales Namespace

ReturnMaterialAuth.Browse Method (String, String, String, Int32, Int32)

Retrieves RMA rows based on a search criteria, limited by the values of the startRecord and maxRecords parameters.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns,
        int startRecord,
        int maxRecords
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String,
        startRecord As Integer,
        maxRecords As Integer
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

startRecord

Type: System.Int32

maxRecords

Type: System.Int32

Return Value

Type: **DataSet**

See Also

ReturnMaterialAuth Class
Browse Overload
Lsa.Vmfg.Sales Namespace

ReturnMaterialAuth.Exists Method

Determines if a specific RMA exists.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual bool Exists(
        string id
)
```

VB

```
Public Overridable Function Exists (
        id As String
) As Boolean
```

Parameters

id

Type: System.String

Return Value

Type: Boolean

See Also

ReturnMaterialAuth Class

Lsa.Vmfg.Sales Namespace

ReturnMaterialAuth.Find Method

Retrieves a specific RMA. Note: only the top-level table (RMA) is returned.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Find(
        string id
)
```

VB

```
Public Overridable Sub Find (
        id As String
)
```

Parameters

id

Type: System.String

See Also

ReturnMaterialAuth Class

Lsa.Vmfg.Sales Namespace

ReturnMaterialAuth.Load Method

Overload List

	Name	Description
	Load(String)	Loads a specific RMA.
	Load(Stream, String)	Loads from stream and rename using new key.

See Also

ReturnMaterialAuth Class
Lsa.Vmfg.Sales Namespace

ReturnMaterialAuth.Load Method (String)

Loads a specific RMA.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string id
)
```

VB

```
Public Overridable Sub Load (
        id As String
)
```

Parameters

id

Type: System.String

See Also

ReturnMaterialAuth Class

Load Overload

Lsa.Vmfg.Sales Namespace

ReturnMaterialAuth.Load Method (Stream, String)

Loads from stream and rename using new key.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        Stream stream,
        string id
)
```

VB

```
Public Overridable Sub Load (
        stream As Stream,
        id As String
)
```

Parameters

stream

Type: System.IO.Stream

id

Type: System.String

See Also

ReturnMaterialAuth Class

Load Overload

Lsa.Vmfg.Sales Namespace

ReturnMaterialAuth.NewRMABinaryRow Method

Inserts a new row into the RMA_BINARY table. Note: Only binary types of "D" (long text) are supported.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewRMABinaryRow(
        string rmaID,
        string binaryType
)
```

VB

```
Public Overridable Function NewRMABinaryRow (
        rmaID As String,
        binaryType As String
) As DataRow
```

Parameters

rmaID

Type: System.String

binaryType

Type: System.String

Return Value

Type: **DataRow**

See Also

ReturnMaterialAuth Class

Lsa.Vmfg.Sales Namespace

ReturnMaterialAuth.NewRMALineBinaryRow Method

Inserts a new row into the RMA_LINE_BINARY table. Note: Only binary types of "D" (long text) are supported.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewRMALineBinaryRow(
        string ReturnMaterialAuthID,
        long lineNo,
        string type
)
```

VB

```
Public Overridable Function NewRMALineBinaryRow (
        ReturnMaterialAuthID As String,
        lineNo As Long,
        type As String
) As DataRow
```

Parameters

ReturnMaterialAuthID

Type: System.String

lineNo

Type: System.Int64

type

Type: System.String

Return Value

Type: **DataRow**

See Also

ReturnMaterialAuth Class

Lsa.Vmfg.Sales Namespace

ReturnMaterialAuth.NewRMALineRow Method

Overload List

	Name	Description
	NewRMALineRow(String)	Inserts a new row into the RMA_LINE table. Auto numbers LINE_NO.
	NewRMALineRow(String, Int64)	Inserts a new row into the RMA_LINE table.

See Also

ReturnMaterialAuth Class

Lsa.Vmfg.Sales Namespace

ReturnMaterialAuth.NewRMALineRow Method (String)

Inserts a new row into the RMA_LINE table. Auto numbers LINE_NO.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewRMALineRow(
        string rmaID
)
```

VB

```
Public Overridable Function NewRMALineRow (
        rmaID As String
) As DataRow
```

Parameters

rmaID

Type: System.String

Return Value

Type: **DataRow**

See Also

ReturnMaterialAuth Class
NewRMALineRow Overload
Lsa.Vmfg.Sales Namespace

ReturnMaterialAuth.NewRMALineRow Method (String, Int64)

Inserts a new row into the RMA_LINE table.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewRMALineRow(
        string rmaID,
        long lineNo
)
```

VB

```
Public Overridable Function NewRMALineRow (
        rmaID As String,
        lineNo As Long
) As DataRow
```

Parameters

rmaID

Type: System.String

lineNo

Type: System.Int64

Return Value

Type: **DataRow**

See Also

ReturnMaterialAuth Class

NewRMALineRow Overload

Lsa.Vmfg.Sales Namespace

ReturnMaterialAuth.NewRMARow Method

Inserts a new row into the RMA table.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewRMARow(
        string id
)
```

VB

```
Public Overridable Function NewRMARow (
        id As String
) As DataRow
```

Parameters

id

Type: System.String

Return Value

Type: **DataRow**

See Also

ReturnMaterialAuth Class

Lsa.Vmfg.Sales Namespace

ReturnMaterialAuth.Save Method

Overload List

	Name	Description
	Save()	Saves all previously loaded RMAs to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

ReturnMaterialAuth Class
Lsa.Vmfg.Sales Namespace

ReturnMaterialAuth.Save Method

Saves all previously loaded RMAs to the database.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

ReturnMaterialAuth Class
Save Overload
Lsa.Vmfg.Sales Namespace

ReturnMaterialAuth.Save Method (Stream)

Save current state of data set to stream.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Save(
        Stream stream
)
```

VB

```
Public Overridable Sub Save (
        stream As Stream
)
```

Parameters

stream

Type: System.IO.Stream

See Also

ReturnMaterialAuth Class

Save Overload

Lsa.Vmfg.Sales Namespace

SalesRep Class

Maintain Sales Reps.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessDocument
          Lsa.Vmfg.Sales.SalesRep

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class SalesRep : BusinessDocument
```

VB

```
<SerializableAttribute>
Public Class SalesRep
        Inherits BusinessDocument
```

The **SalesRep** type exposes the following members.

Constructors

	Name	Description
	SalesRep()	Constructor
	SalesRep(String)	Constructor

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Sales Reps based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Sales Reps base on search criteria, limited by the values in the startRecord and maxRecords parameters.
	Exists	Determines if a specific Sales Rep exists.
	Find	Retrieve a specific Sales Rep.
	Load()	Loads all Sales Reps.
	Load(String)	Loads a specific Sales Rep.
	Load(Stream, String)	Load from stream and rename using new key.
	NewSalesRepRow	Inserts a new row into the SALES_REP table.
	NewSalesRepShareRow	Inserts a new row into the SALES_REP_SHARE table.
	Save()	Save all previously loaded Sales Reps to the database. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.
	Save(Stream)	Save current state of data set to stream. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.

See Also

Lsa.Vmfg.Sales Namespace

SalesRep Constructor

Overload List

	Name	Description
	SalesRep()	Constructor
	SalesRep(String)	Constructor

See Also

SalesRep Class
Lsa.Vmfg.Sales Namespace

SalesRep Constructor

Constructor

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public SalesRep()

VB
Public Sub New

See Also

SalesRep Class
SalesRep Overload
Lsa.Vmfg.Sales Namespace

SalesRep Constructor (String)

Constructor

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public SalesRep(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

SalesRep Class

SalesRep Overload

Lsa.Vmfg.Sales Namespace

SalesRep.SalesRep Methods

The SalesRep type exposes the following members.

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Sales Reps based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Sales Reps base on search criteria, limited by the values in the startRecord and maxRecords parameters.
	Exists	Determines if a specific Sales Rep exists.
	Find	Retrieve a specific Sales Rep.
	Load()	Loads all Sales Reps.
	Load(String)	Loads a specific Sales Rep.
	Load(Stream, String)	Load from stream and rename using new key.
	NewSalesRepRow	Inserts a new row into the SALES_REP table.
	NewSalesRepShareRow	Inserts a new row into the SALES_REP_SHARE table.
	Save()	Save all previously loaded Sales Reps to the database. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.
	Save(Stream)	Save current state of data set to stream. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.

See Also

SalesRep Class

Lsa.Vmfg.Sales Namespace

SalesRep.Browse Method

Overload List

	Name	Description
	Browse(String, String, String)	Retrieve Sales Reps based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Sales Reps base on search criteria, limited by the values in the startRecord and maxRecords parameters.

See Also

SalesRep Class

Lsa.Vmfg.Sales Namespace

SalesRep.Browse Method (String, String, String)

Retrieve Sales Reps based on search criteria.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

Return Value

Type: **DataSet**

See Also

SalesRep Class

Browse Overload
Lsa.Vmfg.Sales Namespace

SalesRep.Browse Method (String, String, String, Int32, Int32)

Retrieve Sales Reps base on search criteria, limited by the values in the startRecord and maxRecords parameters.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns,
        int startRecord,
        int maxRecords
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String,
        startRecord As Integer,
        maxRecords As Integer
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

startRecord

Type: System.Int32

maxRecords

Type: System.Int32

Return Value

Type: **DataSet**

See Also

SalesRep Class
Browse Overload
Lsa.Vmfg.Sales Namespace

SalesRep.Exists Method

Determines if a specific Sales Rep exists.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual bool Exists(
        string id
)
```

VB

```
Public Overridable Function Exists (
        id As String
) As Boolean
```

Parameters

id

Type: System.String

Return Value

Type: Boolean

See Also

SalesRep Class

Lsa.Vmfg.Sales Namespace

SalesRep.Find Method

Retrieve a specific Sales Rep.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Find(
        string id
)
```

VB

```
Public Overridable Sub Find (
        id As String
)
```

Parameters

id

Type: System.String

See Also

SalesRep Class

Lsa.Vmfg.Sales Namespace

SalesRep.Load Method

Overload List

	Name	Description
	Load()	Loads all Sales Reps.
	Load(String)	Loads a specific Sales Rep.
	Load(Stream, String)	Load from stream and rename using new key.

See Also

SalesRep Class
Lsa.Vmfg.Sales Namespace

SalesRep.Load Method

Loads all Sales Reps.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Load()

VB
Public Overridable Sub Load

See Also

SalesRep Class
Load Overload
Lsa.Vmfg.Sales Namespace

SalesRep.Load Method (String)

Loads a specific Sales Rep.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string id
)
```

VB

```
Public Overridable Sub Load (
        id As String
)
```

Parameters

id

Type: System.String

See Also

SalesRep Class
Load Overload
Lsa.Vmfg.Sales Namespace

SalesRep.Load Method (Stream, String)

Load from stream and rename using new key.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        Stream stream,
        string id
)
```

VB

```
Public Overridable Sub Load (
        stream As Stream,
        id As String
)
```

Parameters

stream

Type: System.IO.Stream

id

Type: System.String

See Also

SalesRep Class

Load Overload

Lsa.Vmfg.Sales Namespace

SalesRep.NewSalesRepRow Method

Inserts a new row into the SALES_REP table.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public DataRow NewSalesRepRow(
        string id
)
```

VB

```
Public Function NewSalesRepRow (
        id As String
) As DataRow
```

Parameters

id

Type: System.String

Return Value

Type: **DataRow**

See Also

SalesRep Class

Lsa.Vmfg.Sales Namespace

SalesRep.NewSalesRepShareRow Method

Inserts a new row into the SALES_REP_SHARE table.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewSalesRepShareRow(
        string salesRepID,
        string shareSalesRepID
)
```

VB

```
Public Overridable Function NewSalesRepShareRow (
        salesRepID As String,
        shareSalesRepID As String
) As DataRow
```

Parameters

salesRepID

Type: System.String

shareSalesRepID

Type: System.String

Return Value

Type: **DataRow**

See Also

SalesRep Class

Lsa.Vmfg.Sales Namespace

SalesRep.Save Method

Overload List

	Name	Description
	Save()	Save all previously loaded Sales Reps to the database. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.
	Save(Stream)	Save current state of data set to stream. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.

See Also

SalesRep Class

Lsa.Vmfg.Sales Namespace

SalesRep.Save Method

Save all previously loaded Sales Reps to the database. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

SalesRep Class
Save Overload
Lsa.Vmfg.Sales Namespace

SalesRep.Save Method (Stream)

Save current state of data set to stream. NOTE: If a VISUAL Global Financials license key is located in the VISUAL database, this method is not supported and will fail if called.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Save(
        Stream stream
)
```

VB

```
Public Overridable Sub Save (
        stream As Stream
)
```

Parameters

stream

Type: System.IO.Stream

See Also

SalesRep Class
Save Overload
Lsa.Vmfg.Sales Namespace

ServiceCharges Class

Maintain Service Charges.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessDocument
          Lsa.Vmfg.Sales.ServiceCharges

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class ServiceCharges : BusinessDocument
```

VB

```
<SerializableAttribute>
Public Class ServiceCharges
        Inherits BusinessDocument
```

The **ServiceCharges** type exposes the following members.

Constructors

	Name	Description
	ServiceCharges()	Business Document Constructor
	ServiceCharges(String)	Business Document Constructor

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Service Charges based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Service Charges based on search criteria, limited by the values of the startRecord and maxRecords parameters.
	Exists	Determines if a specific Service Charge exists.
	Find	Retrieves a specific Service Charge.
	Load()	Loads all Service Charges.
	Load(String)	Loads a specific Service Charge.
	Load(Stream, String)	Loads from stream and rename using new key.
	NewServiceChargeRow(String)	Inserts a new row into the SERVICE_CHARGE table.
	NewServiceChargeRow(String, String)	Inserts a row into the SERVICE_CHARGE table for a specific Site ID.
	Save()	Saves all previously loaded Service Charges to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

Lsa.Vmfg.Sales Namespace

ServiceCharges Constructor

Overload List

	Name	Description
	ServiceCharges()	Business Document Constructor
	ServiceCharges(String)	Business Document Constructor

See Also

ServiceCharges Class
Lsa.Vmfg.Sales Namespace

ServiceCharges Constructor

Business Document Constructor

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public ServiceCharges()

VB
Public Sub New

See Also

ServiceCharges Class
ServiceCharges Overload
Lsa.Vmfg.Sales Namespace

ServiceCharges Constructor (String)

Business Document Constructor

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public ServiceCharges(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

ServiceCharges Class

ServiceCharges Overload

Lsa.Vmfg.Sales Namespace

ServiceCharges.ServiceCharges Methods

The ServiceCharges type exposes the following members.

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Service Charges based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Service Charges based on search criteria, limited by the values of the startRecord and maxRecords parameters.
	Exists	Determines if a specific Service Charge exists.
	Find	Retrieves a specific Service Charge.
	Load()	Loads all Service Charges.
	Load(String)	Loads a specific Service Charge.
	Load(Stream, String)	Loads from stream and rename using new key.
	NewServiceChargeRow(String)	Inserts a new row into the SERVICE_CHARGE table.
	NewServiceChargeRow(String, String)	Inserts a row into the SERVICE_CHARGE table for a specific Site ID.
	Save()	Saves all previously loaded Service Charges to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

ServiceCharges Class

Lsa.Vmfg.Sales Namespace

ServiceCharges.Browse Method

Overload List

	Name	Description
	Browse(String, String, String)	Retrieve Service Charges based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Service Charges based on search criteria, limited by the values of the startRecord and maxRecords parameters.

See Also

ServiceCharges Class

Lsa.Vmfg.Sales Namespace

ServiceCharges.Browse Method (String, String, String)

Retrieve Service Charges based on search criteria.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

Return Value

Type: **DataSet**

See Also

ServiceCharges Class
Browse Overload
Lsa.Vmfg.Sales Namespace

ServiceCharges.Browse Method (String, String, String, Int32, Int32)

Retrieve Service Charges based on search criteria, limited by the values of the startRecord and maxRecords parameters.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns,
        int startRecord,
        int maxRecords
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String,
        startRecord As Integer,
        maxRecords As Integer
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

startRecord

Type: System.Int32

maxRecords

Type: System.Int32

Return Value

Type: **DataSet**

See Also

ServiceCharges Class
Browse Overload
Lsa.Vmfg.Sales Namespace

ServiceCharges.Exists Method

Determines if a specific Service Charge exists.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual bool Exists(
        string id
)
```

VB

```
Public Overridable Function Exists (
        id As String
) As Boolean
```

Parameters

id

Type: System.String

Return Value

Type: Boolean

See Also

ServiceCharges Class

Lsa.Vmfg.Sales Namespace

ServiceCharges.Find Method

Retrieves a specific Service Charge.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Find(
        string id
)
```

VB

```
Public Overridable Sub Find (
        id As String
)
```

Parameters

id

Type: System.String

See Also

ServiceCharges Class

Lsa.Vmfg.Sales Namespace

ServiceCharges.Load Method

Overload List

	Name	Description
	Load()	Loads all Service Charges.
	Load(String)	Loads a specific Service Charge.
	Load(Stream, String)	Loads from stream and rename using new key.

See Also

ServiceCharges Class
Lsa.Vmfg.Sales Namespace

ServiceCharges.Load Method

Loads all Service Charges.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Load()

VB
Public Overridable Sub Load

See Also

ServiceCharges Class
Load Overload
Lsa.Vmfg.Sales Namespace

ServiceCharges.Load Method (String)

Loads a specific Service Charge.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string id
)
```

VB

```
Public Overridable Sub Load (
        id As String
)
```

Parameters

id

Type: System.String

See Also

ServiceCharges Class

Load Overload

Lsa.Vmfg.Sales Namespace

ServiceCharges.Load Method (Stream, String)

Loads from stream and rename using new key.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        Stream stream,
        string id
)
```

VB

```
Public Overridable Sub Load (
        stream As Stream,
        id As String
)
```

Parameters

stream

Type: System.IO.Stream

id

Type: System.String

See Also

ServiceCharges Class

Load Overload

Lsa.Vmfg.Sales Namespace

ServiceCharges.NewServiceChargeRow Method

Overload List

	Name	Description
	NewServiceChargeRow(String)	Inserts a new row into the SERVICE_CHARGE table.
	NewServiceChargeRow(String, String)	Inserts a row into the SERVICE_CHARGE table for a specific Site ID.

See Also

ServiceCharges Class

Lsa.Vmfg.Sales Namespace

ServiceCharges.NewServiceChargeRow Method (String)

Inserts a new row into the SERVICE_CHARGE table.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public DataRow NewServiceChargeRow(
        string id
)
```

VB

```
Public Function NewServiceChargeRow (
        id As String
) As DataRow
```

Parameters

id

Type: System.String

Return Value

Type: **DataRow**

See Also

ServiceCharges Class

NewServiceChargeRow Overload

Lsa.Vmfg.Sales Namespace

ServiceCharges.NewServiceChargeRow Method (String, String)

Inserts a row into the SERVICE_CHARGE table for a specific Site ID.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public DataRow NewServiceChargeRow(
        string id,
        string siteID
)
```

VB

```
Public Function NewServiceChargeRow (
        id As String,
        siteID As String
) As DataRow
```

Parameters

id

Type: System.String

siteID

Type: System.String

Return Value

Type: **DataRow**

See Also

ServiceCharges Class

NewServiceChargeRow Overload

Lsa.Vmfg.Sales Namespace

ServiceCharges.Save Method

Overload List

	Name	Description
	Save()	Saves all previously loaded Service Charges to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

ServiceCharges Class
Lsa.Vmfg.Sales Namespace

ServiceCharges.Save Method

Saves all previously loaded Service Charges to the database.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

ServiceCharges Class
Save Overload
Lsa.Vmfg.Sales Namespace

ServiceCharges.Save Method (Stream)

Save current state of data set to stream.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Save(
        Stream stream
)
```

VB

```
Public Overridable Sub Save (
        stream As Stream
)
```

Parameters

stream

Type: System.IO.Stream

See Also

ServiceCharges Class

Save Overload

Lsa.Vmfg.Sales Namespace

Shipment Class

Transaction to perform Shipments.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessTransaction
          Lsa.Vmfg.Sales.Shipment

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class Shipment : BusinessTransaction
```

VB

```
<SerializableAttribute>
Public Class Shipment
        Inherits BusinessTransaction
```

The **Shipment** type exposes the following members.

Constructors

	Name	Description
	Shipment()	Business Transaction Constructor
	Shipment(String)	Business Transaction Constructor

Methods

	Name	Description
	NewPalletDetailsRow	Inserts a new row into the PALLET_DETAILS transaction data table.
	NewShipmentDelSchedLineRow	Inserts a new row into the DEL_SCHED_LINE transaction data table.
	NewShipmentLineRow	Inserts a new row into the SHIPMENT_LINE transaction data table.
	NewShipmentRow	Inserts a new row into the SHIPMENT transaction data table.
	NewShipmentTraceRow	Inserts a new row into the TRACE transaction data table.
	Prepare	Creates an empty dataset for the transaction. This method returns an empty dataset that you must populate prior to saving the transaction.
	Save	Saves the transaction(s).

Transaction

	Name	Data set returned by Prepare	Description
	Shipment	SHIPMENT	This transaction will save a Shipper and all related transactions to cause inventory to be transacted accordingly. Please note that it is hierarchical. Each Shipper header has one to many shipper lines, and each shipper line may have one to many trace entries and delivery schedule lines.

See Also

Lsa.Vmfg.Sales Namespace

Shipment Constructor

Overload List

	Name	Description
	Shipment()	Business Transaction Constructor
	Shipment(String)	Business Transaction Constructor

See Also

Shipment Class
Lsa.Vmfg.Sales Namespace

Shipment Constructor

Business Transaction Constructor

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public Shipment()

VB
Public Sub New

See Also

Shipment Class
Shipment Overload
Lsa.Vmfg.Sales Namespace

Shipment Constructor (String)

Business Transaction Constructor

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public Shipment(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

Shipment Class

Shipment Overload

Lsa.Vmfg.Sales Namespace

Shipment.Shipment Methods

The Shipment type exposes the following members.

Methods

	Name	Description
	NewPalletDetailsRow	Inserts a new row into the PALLET_DETAILS transaction data table.
	NewShipmentDelSchedLineRow	Inserts a new row into the DEL_SCHED_LINE transaction data table.
	NewShipmentLineRow	Inserts a new row into the SHIPMENT_LINE transaction data table.
	NewShipmentRow	Inserts a new row into the SHIPMENT transaction data table.
	NewShipmentTraceRow	Inserts a new row into the TRACE transaction data table.
	Prepare	Creates an empty dataset for the transaction. This method returns an empty dataset that you must populate prior to saving the transaction.
	Save	Saves the transaction(s).

See Also

Shipment Class

Lsa.Vmfg.Sales Namespace

Shipment.NewPalletDetailsRow Method

Inserts a new row into the PALLET_DETAILS transaction data table.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewPalletDetailsRow(
        string custOrderID,
        int custOrderLineNo,
        string palletID
)
```

VB

```
Public Overridable Function NewPalletDetailsRow (
        custOrderID As String,
        custOrderLineNo As Integer,
        palletID As String
) As DataRow
```

Parameters

custOrderID

Type: System.String

custOrderLineNo

Type: System.Int32

palletID

Type: System.String

Return Value

Type: **DataRow**

Transaction

	Name	Data set returned by Prepare	Description
	Shipment	SHIPMENT	This transaction will save a Shipper and all related transactions to cause inventory to be transacted accordingly. Please note that it is hierarchical. Each Shipper header has one to many shipper lines, and each shipper line may have one to many trace entries and delivery schedule lines.

See Also

Shipment Class

Lsa.Vmfg.Sales Namespace

Shipment.NewShipmentDelSchedLineRow Method

Inserts a new row into the DEL_SCHED_LINE transaction data table.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewShipmentDelSchedLineRow(
        string custOrderID,
        int custOrderLineNo,
        int delSchedLineNo
)
```

VB

```
Public Overridable Function NewShipmentDelSchedLineRow (
        custOrderID As String,
        custOrderLineNo As Integer,
        delSchedLineNo As Integer
) As DataRow
```

Parameters

custOrderID

Type: System.String

custOrderLineNo

Type: System.Int32

delSchedLineNo

Type: System.Int32

Return Value

Type: **DataRow**

Transaction

	Name	Data set returned by Prepare	Description
	Shipment	SHIPMENT	This transaction will save a Shipper and all related transactions to cause inventory to be transacted accordingly. Please note that it is hierarchical. Each Shipper header has one to many shipper lines, and each shipper line may have one to many trace entries and delivery schedule lines.

See Also

Shipment Class

Lsa.Vmfg.Sales Namespace

Shipment.NewShipmentLineRow Method

Inserts a new row into the SHIPMENT_LINE transaction data table.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewShipmentLineRow(
        string custOrderID,
        int custOrderLineNo
)
```

VB

```
Public Overridable Function NewShipmentLineRow (
        custOrderID As String,
        custOrderLineNo As Integer
) As DataRow
```

Parameters

custOrderID

Type: System.String

custOrderLineNo

Type: System.Int32

Return Value

Type: **DataRow**

Transaction

	Name	Data set returned by Prepare	Description
	Shipment	SHIPMENT	This transaction will save a Shipper and all related transactions to cause inventory to be transacted accordingly. Please note that it is hierarchical. Each Shipper header has one to many shipper lines, and each shipper line may have one to many trace entries and delivery schedule lines.

See Also

Shipment Class

Lsa.Vmfg.Sales Namespace

Shipment.NewShipmentRow Method

Inserts a new row into the SHIPMENT transaction data table.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewShipmentRow(
        string custOrderID
)
```

VB

```
Public Overridable Function NewShipmentRow (
        custOrderID As String
) As DataRow
```

Parameters

custOrderID

Type: System.String

Return Value

Type: **DataRow**

Transaction

	Name	Data set returned by Prepare	Description
	Shipment	SHIPMENT	This transaction will save a Shipper and all related transactions to cause inventory to be transacted accordingly. Please note that it is hierarchical. Each Shipper header has one to many shipper lines, and each shipper line may have one to many trace entries and delivery schedule lines.

See Also

Shipment Class

Lsa.Vmfg.Sales Namespace

Shipment.NewShipmentTraceRow Method

Inserts a new row into the TRACE transaction data table.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewShipmentTraceRow(
        string custOrderID,
        int custOrderLineNo,
        string traceID
)
```

VB

```
Public Overridable Function NewShipmentTraceRow (
        custOrderID As String,
        custOrderLineNo As Integer,
        traceID As String
) As DataRow
```

Parameters

custOrderID

Type: System.String

custOrderLineNo

Type: System.Int32

traceID

Type: System.String

Return Value

Type: **DataRow**

Transaction

	Name	Data set returned by Prepare	Description
	Shipment	SHIPMENT	This transaction will save a Shipper and all related transactions to cause inventory to be transacted accordingly. Please note that it is hierarchical. Each Shipper header has one to many shipper lines, and each shipper line may have one to many trace entries and delivery schedule lines.

See Also

Shipment Class

Lsa.Vmfg.Sales Namespace

Shipment.Prepare Method

Creates an empty dataset for the transaction. This method returns an empty dataset that you must populate prior to saving the transaction.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Prepare()

VB
Public Overridable Sub Prepare

See Also

Shipment Class
Lsa.Vmfg.Sales Namespace

Shipment.Save Method

Saves the transaction(s). Shipments are intended to be saved individually.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

Shipment Class
Lsa.Vmfg.Sales Namespace

Shipment

This transaction will save a Shipper and all related transactions to cause inventory to be transacted accordingly. Please note that it is hierarchical. Each Shipper header has one to many shipper lines, and each shipper line may have one to many trace entries and delivery schedule lines.

Namespace: Lsa.Vmfg.Sales

Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

DataSet name returned from Prepare: SHIPMENT

Primary Key: CUST_ORDER_ID

Column Name	Type	Description
CUST_ORDER_ID	String	The ID of the Customer Order being shipped.
TRANSACTION_DATE	Date	Date of shipment transaction. Defaults to current date.
PACKLIST_ID	String	Unique ID for this Shipper (packlist). Will be automatically generated if left blank.
SHIP_ALL	Boolean	When this flag is set to true, the customer order will be shipped in full. This is analogous to clicking “Ship All” in VISUAL. When this feature is used, the sub-tables for this transaction are populated automatically. You cannot use this feature if the order has either a delivery schedule or parts requiring lot / serial number tracing.
FOB_POINT	String	Free on board code for the order. Optional, not validated.
SHIP_VIA	String	Shipping method for the order. Optional, not validated.
SHIPPER_STATUS	String	Status of this shipper. Used by editable packlists. Optional. Valid values are “S”, “1”, “2”, “3”, “A”. Defaults to “A”.
SHIP_TO_ID	String	Ship to address ID for the customer. Optional. If not provided, customer’s default shipping address will be used.
RMA_ID	String	Return Material Authorization ID. Optional.

Column Name	Type	Description
CLOSE_SHORT	Boolean	Boolean flag, signifies final disposition of customer order in the event that the shipped quantity is less than the ordered quantity. A value of “true” will close the order, “false” will leave the order open. Default value is “false”.
ALLOW_OVERSHIPMENT	Boolean	Boolean flag to determine if over shipments (where this transaction’s quantity plus the quantity already shipped exceeds the ordered quantity) will be allowed. Default value is “false”.
USER_ID	String	The User ID of the person performing the transaction. Defaults to SYSADM.
SITE_ID	String	Site ID of the Customer Order being shipped. Defaults to site ID of the Customer Order.

Sub-Table Name: SHIPMENT_LINE

Primary Key: CUST_ORDER_ID, CUST_ORDER_LINE

Column Name	Type	Description
CUST_ORDER_ID	String	The ID of the Customer Order being shipped. Must match the ID of the header table.
CUST_ORDER_LINE_NO	Integer	Line number of the order being shipped.
USER_QTY	Decimal	The quantity being shipped, in the shipping unit of measure.
WAREHOUSE_ID	String	Optional. If not specified, tries to locate the Part’s primary warehouse ID. If not found, uses the first valid warehouse found.
LOCATION_ID	String	Optional. Defaults to the Part’s primary location ID.
NMFC_CODE_ID	String	National Motor Freight Code. Optional. If specified, value must exist in database.
ACT_FREIGHT	Decimal	Actual Freight amount. Optional.
CARTON_COUNT	Integer	Optional.
SHIPPING_WEIGHT	Decimal	Optional.

Column Name	Type	Description
WEIGHT_UM	String	Unit of Measure for Shipping Weight. Optional. If specified, value must exist in database.
SHIPPING_UM	Decimal	Shipping Unit of Measure. Optional. If specified, value must exist in database.
PACKAGE_TYPE	String	Optional. If specified, value must exist in database.
HTS_CODE	String	Harmonized Tariff Code. Optional.
COUNTRY_OF_ORIGIN	String	Optional.
VAT_CODE	String	Value Added Tax Code. Only applicable if VAT is enabled.
SALES_TAX_GROUP_ID	String	Optional. If specified, value must exist in database.
SHIP_DIMENSIONS	String	Optional.

Sub-Table Name: DEL_SCHED_LINE

Primary Key: CUST_ORDER_ID, CUST_ORDER_LINE_NO, DEL_SCHED_LINE_NO

This sub-table is only applicable if the customer order line has a delivery schedule.

Column Name	Type	Description
CUST_ORDER_ID	String	The ID of the Customer Order being shipped. Must match the ID of the header and line tables.
CUST_ORDER_LINE_NO	Integer	Line number of the order being shipped. Must match an existing line number from the line table.
DEL_SCHED_LINE_NO	Integer	The line number of the delivery schedule being shipped.
USER_QTY	Decimal	The quantity being shipped for this delivery schedule line.
SHIP_TO_ID	String	Optional.

Sub-Table Name: TRACE

Primary Key: CUST_ORDER_ID, CUST_ORDER_LINE_NO, TRACE_ID

The TRACE_INFO sub-recordset may or may not be required, depending on the Part's trace profile.

Column Name	Type	Description
CUST_ORDER_ID	String	The ID of the Customer Order being shipped. Must match the ID of the header and line tables.
CUST_ORDER_LINE_NO	Integer	Line number of the order being shipped. Must match an existing line number from the line table.
TRACE_ID	String	Trace ID. Lot or serial number for the parts being reported. If the part's trace profile supports auto numbering, and you wish to have the Trace IDs auto numbered, you must set the TRACE_ID values to the format "<n>" where n is a unique integer.
EXPIRATION_DATE	Date	Expiration date. Determines shelf life of lot. Optional.
QTY		Quantity of transaction associated directly with this trace ID. The sum of all trace detail QTY fields must equal the total shipped quantity for the associated shipper line item.
COMMENTS	String	Optional user comments on specific lot or serial number.
OWNER_ID	String	Owner ID. Optional.

Sub-Table Name: PALLET_DETAILS

Primary Key: CUST_ORDER_ID, CUST_ORDER_LINE_NO, PALLET_ID

This sub-table is used for pallet details for a shipment. This table may or may not be required based on whether the customer associated with the Customer Order requires pallet detail information.

Column Name	Type	Description
CUST_ORDER_ID	String	The ID of the Customer Order being shipped. Must match the ID of the header and line tables. Required.
CUST_ORDER_LINE_NO	Integer	Line number of the order being shipped. Must match an existing line number from the line table. Required
PALLET_ID	String	The ID of the pallet containing the Customer Order line. Required.
CARTON_COUNT	Integer	Number of cartons on the pallet. Required.

Column Name	Type	Description
SHIPPING_WEIGHT	Decimal	Weight of the pallet. Optional.
QTY_PER_PKG	String	Quantity per package. Optional.
PACKAGE_TYPE	String	Package type. Optional.

See Also

Shipment Class
Shipment.NewPalletDetailsRow
Shipment.NewShipmentDelSchedLineRow
Shipment.NewShipmentLineRow
Shipment.NewShipmentRow
Shipment.NewShipmentTraceRow
Lsa.Vmfg.Sales Namespace

Shipper Class

Maintain Shippers.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessDocument
          Lsa.Vmfg.Sales.Shipper

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class Shipper : BusinessDocument
```

VB

```
<SerializableAttribute>
Public Class Shipper
        Inherits BusinessDocument
```

The **Shipper** type exposes the following members.

Constructors

	Name	Description
	Shipper()	Business Document Constructor
	Shipper(String)	Business Document Constructor

Methods

	Name	Description
	Browse(String, String, String)	Returns Shipper rows based on a search criteria.
	Browse(String, String, String, Int32, Int32)	Returns Shipper rows based on a search criteria, limited by the values of the startRecord and maxRecords parameters.
	Exists	Determines if a specific Shipper exists in the database.
	Find	Retrieves a specific Shipper from the database. Only the top-level table (SHIPPER) is returned.
	Load	Loads a specific Shipper.
	Save	Saves all previously loaded shippers to the database.

Remarks

Note: Only Shipper headers may be inserted through this data document. Shipper headers created here are not associated with any inventory transactions, thus they are 'pre shipment' documents. Complete shippers (with line items) must be created via the Shipment Data Transaction. Existing Shippers may be modified and deleted via this data document.

See Also

Lsa.Vmfg.Sales Namespace

Shipper Constructor

Overload List

	Name	Description
	Shipper()	Business Document Constructor
	Shipper(String)	Business Document Constructor

See Also

Shipper Class
Lsa.Vmfg.Sales Namespace

Shipper Constructor

Business Document Constructor

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public Shipper()

VB
Public Sub New

See Also

Shipper Class
Shipper Overload
Lsa.Vmfg.Sales Namespace

Shipper Constructor (String)

Business Document Constructor

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public Shipper(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

Shipper Class

Shipper Overload

Lsa.Vmfg.Sales Namespace

Shipper.Shipper Methods

The Shipper type exposes the following members.

Methods

	Name	Description
	Browse(String, String, String)	Returns Shipper rows based on a search criteria.
	Browse(String, String, String, Int32, Int32)	Returns Shipper rows based on a search criteria, limited by the values of the startRecord and maxRecords parameters.
	Exists	Determines if a specific Shipper exists in the database.
	Find	Retrieves a specific Shipper from the database. Only the top-level table (SHIPPER) is returned.
	Load	Loads a specific Shipper.
	Save	Saves all previously loaded shippers to the database.

See Also

Shipper Class

Lsa.Vmfg.Sales Namespace

Shipper.Browse Method

Overload List

	Name	Description
	Browse(String, String, String)	Returns Shipper rows based on a search criteria.
	Browse(String, String, String, Int32, Int32)	Returns Shipper rows based on a search criteria, limited by the values of the startRecord and maxRecords parameters.

See Also

Shipper Class

Lsa.Vmfg.Sales Namespace

Shipper.Browse Method (String, String, String)

Returns Shipper rows based on a search criteria.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

Return Value

Type: **DataSet**

See Also

Shipper Class

Browse Overload
Lsa.Vmfg.Sales Namespace

Shipper.Browse Method (String, String, String, Int32, Int32)

Returns Shipper rows based on a search criteria, limited by the values of the startRecord and maxRecords parameters.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns,
        int startRecord,
        int maxRecords
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String,
        startRecord As Integer,
        maxRecords As Integer
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

startRecord

Type: System.Int32

maxRecords

Type: System.Int32

Return Value

Type: **DataSet**

See Also

Shipper Class
Browse Overload
Lsa.Vmfg.Sales Namespace

Shipper.Exists Method

Determines if a specific Shipper exists in the database.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual bool Exists(
        string packlsitID
)
```

VB

```
Public Overridable Function Exists (
        packlsitID As String
) As Boolean
```

Parameters

packlsitID

Type: System.String

Return Value

Type: Boolean

See Also

Shipper Class

Lsa.Vmfg.Sales Namespace

Shipper.Find Method

Retrieves a specific Shipper from the database. Only the top-level table (SHIPPER) is returned.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Find(
        string packlsitID
)
```

VB

```
Public Overridable Sub Find (
        packlsitID As String
)
```

Parameters

packlsitID

Type: System.String

See Also

Shipper Class

Lsa.Vmfg.Sales Namespace

Shipper.Load Method

Loads a specific Shipper.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string packlsitID
)
```

VB

```
Public Overridable Sub Load (
        packlsitID As String
)
```

Parameters

packlsitID

Type: System.String

See Also

Shipper Class

Lsa.Vmfg.Sales Namespace

Shipper.Save Method

Saves all previously loaded shippers to the database.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

Shipper Class
Lsa.Vmfg.Sales Namespace

ShipReason Class

Maintain Ship Reason Codes.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessDocument
          Lsa.Vmfg.Sales.ShipReason

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class ShipReason : BusinessDocument
```

VB

```
<SerializableAttribute>
Public Class ShipReason
        Inherits BusinessDocument
```

The **ShipReason** type exposes the following members.

Constructors

	Name	Description
	ShipReason()	Business Documnet Constructor
	ShipReason(String)	Business Document Constructor

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Ship Reason Codes based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Ship Reason Codes based on search criteria, limited by start record and record count.
	Exists	Determine if a specific Ship Reason Code exists.
	Find	Retrieve a specific Ship Reason Code.
	Load()	Load all Ship Reason Codes.
	Load(String, String)	Load a specific Ship Reason Code.
	NewShipReasonRow	Add a new SHIP_REASON row
	Save	Save all previously loaded Ship Reason Codes to the database.

See Also

Lsa.Vmfg.Sales Namespace

ShipReason Constructor

Overload List

	Name	Description
	ShipReason()	Business Documnet Constructor
	ShipReason(String)	Business Document Constructor

See Also

ShipReason Class
Lsa.Vmfg.Sales Namespace

ShipReason Constructor

Business Documnet Constructor

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public ShipReason()

VB
Public Sub New

See Also

ShipReason Class
ShipReason Overload
Lsa.Vmfg.Sales Namespace

ShipReason Constructor (String)

Business Document Constructor

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public ShipReason(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

ShipReason Class

ShipReason Overload

Lsa.Vmfg.Sales Namespace

ShipReason.ShipReason Methods

The ShipReason type exposes the following members.

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Ship Reason Codes based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Ship Reason Codes based on search criteria, limited by start record and record count.
	Exists	Determine if a specific Ship Reason Code exists.
	Find	Retrieve a specific Ship Reason Code.
	Load()	Load all Ship Reason Codes.
	Load(String, String)	Load a specific Ship Reason Code.
	NewShipReasonRow	Add a new SHIP_REASON row
	Save	Save all previously loaded Ship Reason Codes to the database.

See Also

ShipReason Class

Lsa.Vmfg.Sales Namespace

ShipReason.Browse Method

Overload List

	Name	Description
	Browse(String, String, String)	Retrieve Ship Reason Codes based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Ship Reason Codes based on search criteria, limited by start record and record count.

See Also

ShipReason Class

Lsa.Vmfg.Sales Namespace

ShipReason.Browse Method (String, String, String)

Retrieve Ship Reason Codes based on search criteria.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

Return Value

Type: **DataSet**

See Also

ShipReason Class

Browse Overload

Lsa.Vmfg.Sales Namespace

ShipReason.Browse Method (String, String, String, Int32, Int32)

Retrieve Ship Reason Codes based on search criteria, limited by start record and record count.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns,
        int startRecord,
        int maxRecords
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String,
        startRecord As Integer,
        maxRecords As Integer
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

startRecord

Type: System.Int32

maxRecords

Type: System.Int32

Return Value

Type: **DataSet**

See Also

ShipReason Class

Browse Overload

Lsa.Vmfg.Sales Namespace

ShipReason.Exists Method

Determine if a specific Ship Reason Code exists.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual bool Exists(
        string shipReasonType,
        string shipReasonCode
)
```

VB

```
Public Overridable Function Exists (
        shipReasonType As String,
        shipReasonCode As String
) As Boolean
```

Parameters

shipReasonType

Type: System.String

shipReasonCode

Type: System.String

Return Value

Type: Boolean

See Also

ShipReason Class

Lsa.Vmfg.Sales Namespace

ShipReason.Find Method

Retrieve a specific Ship Reason Code.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Find(
        string shipReasonType,
        string shipReasonCode
)
```

VB

```
Public Overridable Sub Find (
        shipReasonType As String,
        shipReasonCode As String
)
```

Parameters

shipReasonType

Type: System.String

shipReasonCode

Type: System.String

See Also

ShipReason Class

Lsa.Vmfg.Sales Namespace

ShipReason.Load Method

Overload List

	Name	Description
	Load()	Load all Ship Reason Codes.
	Load(String, String)	Load a specific Ship Reason Code.

See Also

ShipReason Class
Lsa.Vmfg.Sales Namespace

ShipReason.Load Method

Load all Ship Reason Codes.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Load()

VB
Public Overridable Sub Load

See Also

ShipReason Class
Load Overload
Lsa.Vmfg.Sales Namespace

ShipReason.Load Method (String, String)

Load a specific Ship Reason Code.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string shipReasonType,
        string shipReasonCode
)
```

VB

```
Public Overridable Sub Load (
        shipReasonType As String,
        shipReasonCode As String
)
```

Parameters

shipReasonType

Type: System.String

shipReasonCode

Type: System.String

See Also

ShipReason Class

Load Overload

Lsa.Vmfg.Sales Namespace

ShipReason.NewShipReasonRow Method

Add a new SHIP_REASON row

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewShipReasonRow(
        string shipReasonType,
        string shipReasonCode
)
```

VB

```
Public Overridable Function NewShipReasonRow (
        shipReasonType As String,
        shipReasonCode As String
) As DataRow
```

Parameters

shipReasonType

Type: System.String

shipReasonCode

Type: System.String

Return Value

Type: **DataRow**

See Also

ShipReason Class

Lsa.Vmfg.Sales Namespace

ShipReason.Save Method

Save all previously loaded Ship Reason Codes to the database.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

ShipReason Class
Lsa.Vmfg.Sales Namespace

ShipToAltWhs Class

Maintain Customer Ship to Alternate Warehouses.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessDocument
          Lsa.Vmfg.Sales.ShipToAltWhs

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class ShipToAltWhs : BusinessDocument
```

VB

```
<SerializableAttribute>
Public Class ShipToAltWhs
        Inherits BusinessDocument
```

The **ShipToAltWhs** type exposes the following members.

Constructors

	Name	Description
	ShipToAltWhs()	Constructor
	ShipToAltWhs(String)	Constructor

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Customer Shipto Alt Warehouses based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Customer Shipto Alt Warehouses based on search criteria, limited by the values of the startRecord and maxRecords parameters.
	Exists	Determines if a specific Customer Shipto Alt Warehouse exists.
	Find	Retrieves Customer Shipto Alt Warehouses for a specific customer and warehouse.
	Load()	Loads all Customer Shipto Alt Warehouses.
	Load(String)	Loads all Customer Shipto Alt Warehouses for a specific customer ID.
	Load(String, String)	Loads all Customer Shipto Alt Warehouses for a specific customer ID and Shipto ID.
	NewShipToAltWhsRow	Adds a new row to the SHIPTO_ALT_WAREHS table.
	Save	Save all previously loaded Customer Shipto Alt Warehouses to the database.

See Also

Lsa.Vmfg.Sales Namespace

ShipToAltWhs Constructor

Overload List

	Name	Description
	ShipToAltWhs()	Constructor
	ShipToAltWhs(String)	Constructor

See Also

ShipToAltWhs Class
Lsa.Vmfg.Sales Namespace

ShipToAltWhs Constructor

Constructor

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public ShipToAltWhs()

VB
Public Sub New

See Also

ShipToAltWhs Class
ShipToAltWhs Overload
Lsa.Vmfg.Sales Namespace

ShipToAltWhs Constructor (String)

Constructor

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public ShipToAltWhs(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

ShipToAltWhs Class
ShipToAltWhs Overload
Lsa.Vmfg.Sales Namespace

ShipToAltWhs.ShipToAltWhs Methods

The ShipToAltWhs type exposes the following members.

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Customer Shipto Alt Warehouses based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Customer Shipto Alt Warehouses based on search criteria, limited by the values of the startRecord and maxRecords parameters.
	Exists	Determines if a specific Customer Shipto Alt Warehouse exists.
	Find	Retrieves Customer Shipto Alt Warehouses for a specific customer and warehouse.
	Load()	Loads all Customer Shipto Alt Warehouses.
	Load(String)	Loads all Customer Shipto Alt Warehouses for a specific customer ID.
	Load(String, String)	Loads all Customer Shipto Alt Warehouses for a specific customer ID and Shipto ID.
	NewShipToAltWhsRow	Adds a new row to the SHIPTO_ALT_WAREHS table.
	Save	Save all previously loaded Customer Shipto Alt Warehouses to the database.

See Also

ShipToAltWhs Class

Lsa.Vmfg.Sales Namespace

ShipToAltWhs.Browse Method

Overload List

	Name	Description
	Browse(String, String, String)	Retrieve Customer Shipto Alt Warehouses based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Customer Shipto Alt Warehouses based on search criteria, limited by the values of the startRecord and maxRecords parameters.

See Also

ShipToAltWhs Class

Lsa.Vmfg.Sales Namespace

ShipToAltWhs.Browse Method (String, String, String)

Retrieve Customer Shipto Alt Warehouses based on search criteria.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

Return Value

Type: **DataSet**

See Also

ShipToAltWhs Class
Browse Overload
Lsa.Vmfg.Sales Namespace

ShipToAltWhs.Browse Method (String, String, String, Int32, Int32)

Retrieve Customer Shipto Alt Warehouses based on search criteria, limited by the values of the startRecord and maxRecords parameters.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns,
        int startRecord,
        int maxRecords
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String,
        startRecord As Integer,
        maxRecords As Integer
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

startRecord

Type: System.Int32

maxRecords

Type: System.Int32

Return Value

Type: **DataSet**

See Also

ShipToAltWhs Class
Browse Overload
Lsa.Vmfg.Sales Namespace

ShipToAltWhs.Exists Method

Determines if a specific Customer Shipto Alt Warehouse exists.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual bool Exists(
        string customerID,
        string shiptoID
)
```

VB

```
Public Overridable Function Exists (
        customerID As String,
        shiptoID As String
) As Boolean
```

Parameters

customerID

Type: System.String

shiptoID

Type: System.String

Return Value

Type: Boolean

See Also

ShipToAltWhs Class

Lsa.Vmfg.Sales Namespace

ShipToAltWhs.Find Method

Retrieves Customer Shipto Alt Warehouses for a specific customer and warehouse.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Find(
        string customerID,
        string warehouseID
)
```

VB

```
Public Overridable Sub Find (
        customerID As String,
        warehouseID As String
)
```

Parameters

customerID

Type: System.String

warehouseID

Type: System.String

See Also

ShipToAltWhs Class

Lsa.Vmfg.Sales Namespace

ShipToAltWhs.Load Method

Overload List

	Name	Description
	Load()	Loads all Customer Shipto Alt Warehouses.
	Load(String)	Loads all Customer Shipto Alt Warehouses for a specific customer ID.
	Load(String, String)	Loads all Customer Shipto Alt Warehouses for a specific customer ID and Shipto ID.

See Also

ShipToAltWhs Class

Lsa.Vmfg.Sales Namespace

ShipToAltWhs.Load Method

Loads all Customer Shipto Alt Warehouses.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Load()

VB
Public Overridable Sub Load

See Also

ShipToAltWhs Class
Load Overload
Lsa.Vmfg.Sales Namespace

ShipToAltWhs.Load Method (String)

Loads all Customer Shipto Alt Warehouses for a specific customer ID.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string customerID
)
```

VB

```
Public Overridable Sub Load (
        customerID As String
)
```

Parameters

customerID

Type: System.String

See Also

ShipToAltWhs Class

Load Overload

Lsa.Vmfg.Sales Namespace

ShipToAltWhs.Load Method (String, String)

Loads all Customer Shipto Alt Warehouses for a specific customer ID and Shipto ID.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string customerID,
        string shiptoID
)
```

VB

```
Public Overridable Sub Load (
        customerID As String,
        shiptoID As String
)
```

Parameters

customerID

Type: System.String

shiptoID

Type: System.String

See Also

ShipToAltWhs Class

Load Overload

Lsa.Vmfg.Sales Namespace

ShipToAltWhs.NewShipToAltWhsRow Method

Adds a new row to the SHIPTO_ALT_WAREHS table.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public DataRow NewShipToAltWhsRow(
        string customerID,
        string shipToID,
        string warehouseID
)
```

VB

```
Public Function NewShipToAltWhsRow (
        customerID As String,
        shipToID As String,
        warehouseID As String
) As DataRow
```

Parameters

customerID

Type: System.String

shipToID

Type: System.String

warehouseID

Type: System.String

Return Value

Type: **DataRow**

See Also

ShipToAltWhs Class

Lsa.Vmfg.Sales Namespace

ShipToAltWhs.Save Method

Save all previously loaded Customer Shipto Alt Warehouses to the database.

Namespace: Lsa.Vmfg.Sales
Assembly: VmfgSales (in VmfgSales.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

ShipToAltWhs Class
Lsa.Vmfg.Sales Namespace