Infor VISUAL API Toolkit Purchasing Class Library Reference

Copyright © 2017 Infor

Important Notices

The material contained in this publication (including any supplementary information) constitutes and contains confidential and proprietary information of Infor.

By gaining access to the attached, you acknowledge and agree that the material (including any modification, translation or adaptation of the material) and all copyright, trade secrets and all other right, title and interest therein, are the sole property of Infor and that you shall not gain right, title or interest in the material (including any modification, translation or adaptation of the material) by virtue of your review thereof other than the non-exclusive right to use the material solely in connection with and the furtherance of your license and use of software made available to your company from Infor pursuant to a separate agreement, the terms of which separate agreement shall govern your use of this material and all supplemental related materials ("Purpose").

In addition, by accessing the enclosed material, you acknowledge and agree that you are required to maintain such material in strict confidence and that your use of such material is limited to the Purpose described above. Although Infor has taken due care to ensure that the material included in this publication is accurate and complete, Infor cannot warrant that the information contained in this publication is complete, does not contain typographical or other errors, or will meet your specific requirements. As such, Infor does not assume and hereby disclaims all liability, consequential or otherwise, for any loss or damage to any person or entity which is caused by or relates to errors or omissions in this publication (including any supplementary information), whether such errors or omissions result from negligence, accident or any other cause.

Without limitation, U.S. export control laws and other applicable export and import laws govern your use of this material and you will neither export or re-export, directly or indirectly, this material nor any related materials or supplemental information in violation of such laws, or use such materials for any purpose prohibited by such laws.

Trademark Acknowledgements

The word and design marks set forth herein are trademarks and/or registered trademarks of Infor and/or related affiliates and subsidiaries. All rights reserved. All other company, product, trade or service names referenced may be registered trademarks or trademarks of their respective owners.

Publication Information

Release: Infor VISUAL API Toolkit

Publication date: June 6, 2017

About this guide

This guide describes the objects available in the Infor VISUAL API Toolkit Purchasing class library.

Intended audience

The intended audience of this guide is developers who are using the API Toolkit to extend the VISUAL solution.

Contacting Infor

If you have questions about Infor products, go to the Infor Xtreme Support portal at www.infor.com/inforxtreme.

If we update this document after the product release, we will post the new version on this Web site. We recommend that you check this Web site periodically for updated documentation.

If you have comments about Infor documentation, contact documentation@infor.com.

Supported languages

These languages are supported for use with the toolkit:

- Visual Basic
- C#

While it is possible to use any .NET-aware programming language with the toolkit, other languages are not officially supported.

Support information

The API Toolkit will be updated regularly as more class members are added to each assembly, schema changes are made, and any reported issues are resolved. Infor Support cannot assist you with developing customized code using the API Toolkit. For assistance with customizations, contact Infor Consulting Services or your channel partner.

The functionality provided within the API Toolkit will not be extended beyond the standard functionality experienced in the VISUAL application itself. Enhancement requests with compelling business cases detailing how suggested alternatives are not viable will be evaluated and considered.

Only the public members that are described in the API toolkit documentation are supported for use. No other private or public members are supported.

Infor is not responsible for data incorrectly entered to the database through the use of the API Toolkit. Customers must establish a full test environment to ensure that data created by APIs functions in the same manner as data created through the VISUAL interface.

Lsa.Vmfg.Purchasing Namespace

Classes

	Class	Description
	CopyOrder	Transaction to create new Purchase Orders from existing Purchase Orders.
	DemandSupplyLink	Maintain Demand Supply Links. This Data Document only applies to Demand Supply Links to Purchase Orders.
	GetInspectionReceivers	Service to obtain all Purchase Receipts held in inspection for a given Site.
	PurchaseOrder	Maintain Purchase Orders.
	Receipt	Purchase Receipt Transaction.
	Receiver	Maintain Receivers. Note: Only Receiver headers may be inserted through this data document. Receiver headers created here are not associated with any inventory transactions, thus they are 'pre receipt' documents. Complete Receivers (with line items) must be created via the Receipt Data Transaction.
	ReceivingInspection	Receiving Inspection Transaction.
	RequestForQuote	Maintain Requests For Quote.
	Return	Purchase Return Transaction.
	Service	Maintain Services.
	ServiceDispatch	Service Dispatch Transaction.
	VendBankAccount	Maintain Vendor Bank Accounts.
	Vendor	Maintain Vendors.
	VendorPart	Maintain Vendor Parts.
	VendorRemitAddress	Maintain Vendor Remit to Addresses.

CopyOrder Class

Transaction to create new Purchase Orders from existing Purchase Orders.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessTransaction
          Lsa.Vmfg.Purchasing.CopyOrder

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class CopyOrder : BusinessTransaction
```

VB

```
<SerializableAttribute>
Public Class CopyOrder
        Inherits BusinessTransaction
```

The **CopyOrder** type exposes the following members.

Constructors

	Name	Description
	CopyOrder()	Business Transaction Constructor
	CopyOrder(String)	Business Transaction Constructor

Methods

	Name	Description
	NewCopyOrderRow	Inserts a new row into the COPY_ORDER Data Table. See CopyOrder.
	Prepare	Creates an empty dataset for the transaction. You must populate the dataset prior to saving the transaction.
	Save	Saves the transaction(s).

Transaction

	Name	Data set returned by Prepare	Description
	CopyOrderr	COPY_ORDER	This transaction will copy an existing Purchase Order to a new Purchase Order.

See Also

Lsa.Vmfg.Purchasing Namespace

CopyOrder Constructor

Overload List

	Name	Description
	CopyOrder()	Business Transaction Constructor
	CopyOrder(String)	Business Transaction Constructor

See Also

CopyOrder Class
Lsa.Vmfg.Purchasing Namespace

CopyOrder Constructor

Business Transaction Constructor

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public CopyOrder()

VB
Public Sub New

See Also

CopyOrder Class
CopyOrder Overload
Lsa.Vmfg.Purchasing Namespace

CopyOrder Constructor (String)

Business Transaction Constructor

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public CopyOrder(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

CopyOrder Class

CopyOrder Overload

Lsa.Vmfg.Purchasing Namespace

CopyOrder.CopyOrder Methods

The CopyOrder type exposes the following members.

Methods

	Name	Description
	NewCopyOrderRow	Inserts a new row into the COPY_ORDER Data Table. See CopyOrder.
	Prepare	Creates an empty dataset for the transaction. You must populate the dataset prior to saving the transaction.
	Save	Saves the transaction(s).

See Also

CopyOrder Class

Lsa.Vmfg.Purchasing Namespace

CopyOrder.NewCopyOrderRow Method

Inserts a new row into the COPY_ORDER Data Table. See CopyOrder for the definition of the input data table for this transaction.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewCopyOrderRow(
        string sourceOrderID
)
```

VB

```
Public Overridable Function NewCopyOrderRow (
        sourceOrderID As String
) As DataRow
```

Parameters

sourceOrderID

Type: System.String

Return Value

Type: **DataRow**

See Also

CopyOrder

CopyOrder Class

Lsa.Vmfg.Purchasing Namespace

CopyOrder.Prepare Method

Creates an empty dataset for the transaction. You must populate the dataset prior to saving the transaction.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Prepare()

VB
Public Overridable Sub Prepare

See Also

CopyOrder Class
Lsa.Vmfg.Purchasing Namespace

CopyOrder.Save Method

Saves the transaction(s).

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

CopyOrder Class
Lsa.Vmfg.Purchasing Namespace

CopyOrder

This transaction will copy an existing Purchase Order to a new Purchase Order.

Namespace: Lsa.Vmfg.Purchasing

Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

DataSet name returned from Prepare: COPY_ORDER

Primary Key: SOURCE_ORDER_ID

Column Name	Type	Description
SOURCE_ORDER_ID	String	The ID of an existing Purchase Order, the source for the copy.
COPY_LINKS	Boolean	Boolean flag to determine if links to demand orders for the source purchase order will be created for the new order. Valid values are true and false. Default value is false (do not copy links).
COPY_LINE_ITEMS	Boolean	Boolean flag to determine if line items from the source purchase order are copied to the new order. Valid values are true and false. Default value is false (do not copy line items).
COPY_DEL_SCHED	Boolean	Boolean flag to determine if delivery schedule line items from the source purchase order will copied to the new order. Valid values are true and false. Default value is false (do not copy delivery schedule line items).
TARGET_ORDER_ID	String	The ID of the target purchase order. Leave blank for auto number.
TARGET_ORDER_STATUS	String	The status of the newly created order. Default is “R” if no status provided.
CLOSE_SOURCE_ORDER	Boolean	Boolean flag to determine if the source order’s status is to be set to “C” (closed) after the copy. Valid values are true and false. Default value is false (do not alter the source status).

See Also

CopyOrder Class

CopyOrder.NewCopyOrderRow

Lsa.Vmfg.Purchasing Namespace

DemandSupplyLink Class

Maintain Demand Supply Links. This Data Document only applies to Demand Supply Links to Purchase Orders.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessDocument
          Lsa.Vmfg.Purchasing.DemandSupplyLink

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class DemandSupplyLink : BusinessDocument
```

VB

```
<SerializableAttribute>
Public Class DemandSupplyLink
        Inherits BusinessDocument
```

The **DemandSupplyLink** type exposes the following members.

Constructors

	Name	Description
	DemandSupplyLink()	Business Document Constructor
	DemandSupplyLink(String)	Business Document Constructor

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Demand Supply Links based on search critera.
	Browse(String, String, String, Int32, Int32)	Retrieve Demand Supply Links based on search critera. Number of rows returned is limited by the value of maxRecords.
	Exists(String)	Determines if a specific Demand Supply Link exists in the database.
	Exists(String, Int32)	Determines if a specific Demand Supply Link exists in the database.
	Exists(String, Int32, Int32)	Determines if a specific Demand Supply Link exists in the database.
	Find	Retrieves a specific Demand Supply Link from the database.
	Load(String)	Loads a specific Demand Supply Link from the database.
	Load(Stream, String)	Load from stream and rename using new key.
	Load(String, String, Int32)	Loads a specific Demand Supply Link from the database, based on the supply type, supply base id, and supply seq no provided.
	Load(String, String, Int32, Int32)	Loads a specific Demand Supply Link from the database, based on the supply type, supply base id, supply seq no, and supply no provided.
	NewDemandSupplyLinkRow(String)	Inserts a new row into the DEMAND_SUPPLY_LINK data table.
	NewDemandSupplyLinkRow(String, String, String)	Inserts a new row into the DEMAND_SUPPLY_LINK data table.
	Save()	Saves all previously loaded Demand Supply Links to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

Lsa.Vmfg.Purchasing Namespace

DemandSupplyLink Constructor

Overload List

	Name	Description
	DemandSupplyLink()	Business Document Constructor
	DemandSupplyLink(String)	Business Document Constructor

See Also

DemandSupplyLink Class
Lsa.Vmfg.Purchasing Namespace

DemandSupplyLink Constructor

Business Document Constructor

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public DemandSupplyLink()

VB
Public Sub New

See Also

DemandSupplyLink Class
DemandSupplyLink Overload
Lsa.Vmfg.Purchasing Namespace

DemandSupplyLink Constructor (String)

Business Document Constructor

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public DemandSupplyLink(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

DemandSupplyLink Class

DemandSupplyLink Overload

Lsa.Vmfg.Purchasing Namespace

DemandSupplyLink.DemandSupplyLink Methods

The DemandSupplyLink type exposes the following members.

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Demand Supply Links based on search critera.
	Browse(String, String, String, Int32, Int32)	Retrieve Demand Supply Links based on search critera. Number of rows returned is limited by the value of maxRecords.
	Exists(String)	Determines if a specific Demand Supply Link exists in the database.
	Exists(String, Int32)	Determines if a specific Demand Supply Link exists in the database.
	Exists(String, Int32, Int32)	Determines if a specific Demand Supply Link exists in the database.
	Find	Retrieves a specific Demand Supply Link from the database.
	Load(String)	Loads a specific Demand Supply Link from the database.
	Load(Stream, String)	Load from stream and rename using new key.
	Load(String, String, Int32)	Loads a specific Demand Supply Link from the database, based on the supply type, supply base id, and supply seq no provided.
	Load(String, String, Int32, Int32)	Loads a specific Demand Supply Link from the database, based on the supply type, supply base id, supply seq no, and supply no provided.
	NewDemandSupplyLinkRow(String)	Inserts a new row into the DEMAND_SUPPLY_LINK data table.
	NewDemandSupplyLinkRow(String, String, String)	Inserts a new row into the DEMAND_SUPPLY_LINK data table.
	Save()	Saves all previously loaded Demand Supply Links to the database.

	Save(Stream)	Save current state of data set to stream.

See Also

DemandSupplyLink Class
Lsa.Vmfg.Purchasing Namespace

DemandSupplyLink.Browse Method

Overload List

	Name	Description
	Browse(String, String, String)	Retrieve Demand Supply Links based on search critera.
	Browse(String, String, String, Int32, Int32)	Retrieve Demand Supply Links based on search critera. Number of rows returned is limited by the value of maxRecords.

See Also

DemandSupplyLink Class

Lsa.Vmfg.Purchasing Namespace

DemandSupplyLink.Browse Method (String, String, String)

Retrieve Demand Supply Links based on search critera.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

Return Value

Type: **DataSet**

See Also

DemandSupplyLink Class

Browse Overload

Lsa.Vmfg.Purchasing Namespace

DemandSupplyLink.Browse Method (String, String, String, Int32, Int32)

Retrieve Demand Supply Links based on search critera. Number of rows returned is limited by the value of maxRecords.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns,
        int startRecord,
        int maxRecords
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String,
        startRecord As Integer,
        maxRecords As Integer
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

startRecord

Type: System.Int32

maxRecords

Type: System.Int32

Return Value

Type: **DataSet**

See Also

DemandSupplyLink Class
Browse Overload
Lsa.Vmfg.Purchasing Namespace

DemandSupplyLink.Exists Method

Overload List

	Name	Description
	Exists(String)	Determines if a specific Demand Supply Link exists in the database.
	Exists(String, Int32)	Determines if a specific Demand Supply Link exists in the database.
	Exists(String, Int32, Int32)	Determines if a specific Demand Supply Link exists in the database.

See Also

DemandSupplyLink Class
Lsa.Vmfg.Purchasing Namespace

DemandSupplyLink.Exists Method (String)

Determines if a specific Demand Supply Link exists in the database.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual bool Exists(
        string id
)
```

VB

```
Public Overridable Function Exists (
        id As String
) As Boolean
```

Parameters

id

Type: System.String

Return Value

Type: Boolean

See Also

DemandSupplyLink Class

Exists Overload

Lsa.Vmfg.Purchasing Namespace

DemandSupplyLink.Exists Method (String, Int32)

Determines if a specific Demand Supply Link exists in the database.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual bool Exists(
        string supplyBaseID,
        int supplySeqNo
)
```

VB

```
Public Overridable Function Exists (
        supplyBaseID As String,
        supplySeqNo As Integer
) As Boolean
```

Parameters

supplyBaseID

Type: System.String

supplySeqNo

Type: System.Int32

Return Value

Type: Boolean

See Also

DemandSupplyLink Class

Exists Overload

Lsa.Vmfg.Purchasing Namespace

DemandSupplyLink.Exists Method (String, Int32, Int32)

Determines if a specific Demand Supply Link exists in the database.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual bool Exists(
        string supplyBaseID,
        int supplySeqNo,
        int supplyNo
)
```

VB

```
Public Overridable Function Exists (
        supplyBaseID As String,
        supplySeqNo As Integer,
        supplyNo As Integer
) As Boolean
```

Parameters

supplyBaseID

Type: System.String

supplySeqNo

Type: System.Int32

supplyNo

Type: System.Int32

Return Value

Type: Boolean

See Also

DemandSupplyLink Class

Exists Overload

Lsa.Vmfg.Purchasing Namespace

DemandSupplyLink.Find Method

Retrieves a specific Demand Supply Link from the database.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Find(
        string id
)
```

VB

```
Public Overridable Sub Find (
        id As String
)
```

Parameters

id

Type: System.String

See Also

DemandSupplyLink Class

Lsa.Vmfg.Purchasing Namespace

DemandSupplyLink.Load Method

Overload List

	Name	Description
	Load(String)	Loads a specific Demand Supply Link from the database.
	Load(Stream, String)	Load from stream and rename using new key.
	Load(String, String, Int32)	Loads a specific Demand Supply Link from the database, based on the supply type, supply base id, and supply seq no provided.
	Load(String, String, Int32, Int32)	Loads a specific Demand Supply Link from the database, based on the supply type, supply base id, supply seq no, and supply no provided.

See Also

DemandSupplyLink Class

Lsa.Vmfg.Purchasing Namespace

DemandSupplyLink.Load Method (String)

Loads a specific Demand Supply Link from the database.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string id
)
```

VB

```
Public Overridable Sub Load (
        id As String
)
```

Parameters

id

Type: System.String

See Also

DemandSupplyLink Class

Load Overload

Lsa.Vmfg.Purchasing Namespace

DemandSupplyLink.Load Method (Stream, String)

Load from stream and rename using new key.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        Stream stream,
        string id
)
```

VB

```
Public Overridable Sub Load (
        stream As Stream,
        id As String
)
```

Parameters

stream

Type: System.IO.Stream

id

Type: System.String

See Also

DemandSupplyLink Class

Load Overload

Lsa.Vmfg.Purchasing Namespace

DemandSupplyLink.Load Method (String, String, Int32)

Loads a specific Demand Supply Link from the database, based on the supply type, supply base id, and supply seq no provided.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string supplyType,
        string supplyBaseID,
        int supplySeqNo
)
```

VB

```
Public Overridable Sub Load (
        supplyType As String,
        supplyBaseID As String,
        supplySeqNo As Integer
)
```

Parameters

supplyType

Type: System.String

supplyBaseID

Type: System.String

supplySeqNo

Type: System.Int32

See Also

DemandSupplyLink Class

Load Overload

Lsa.Vmfg.Purchasing Namespace

DemandSupplyLink.Load Method (String, String, Int32, Int32)

Loads a specific Demand Supply Link from the database, based on the supply type, supply base id, supply seq no, and supply no provided.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string supplyType,
        string supplyBaseID,
        int supplySeqNo,
        int supplyNo
)
```

VB

```
Public Overridable Sub Load (
        supplyType As String,
        supplyBaseID As String,
        supplySeqNo As Integer,
        supplyNo As Integer
)
```

Parameters

supplyType

Type: System.String

supplyBaseID

Type: System.String

supplySeqNo

Type: System.Int32

supplyNo

Type: System.Int32

See Also

DemandSupplyLink Class
Load Overload
Lsa.Vmfg.Purchasing Namespace

DemandSupplyLink.NewDemandSupplyLinkRow Method

Overload List

	Name	Description
	NewDemandSupplyLinkRow(String)	Inserts a new row into the DEMAND_SUPPLY_LINK data table.
	NewDemandSupplyLinkRow(String, String, String)	Inserts a new row into the DEMAND_SUPPLY_LINK data table.

See Also

DemandSupplyLink Class

Lsa.Vmfg.Purchasing Namespace

DemandSupplyLink.NewDemandSupplyLinkRow Method (String)

Inserts a new row into the DEMAND_SUPPLY_LINK data table.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewDemandSupplyLinkRow(
        string id
)
```

VB

```
Public Overridable Function NewDemandSupplyLinkRow (
        id As String
) As DataRow
```

Parameters

id

Type: System.String

Return Value

Type: **DataRow**

See Also

DemandSupplyLink Class
NewDemandSupplyLinkRow Overload
Lsa.Vmfg.Purchasing Namespace

DemandSupplyLink.NewDemandSupplyLinkRow Method (String, String, String)

Inserts a new row into the DEMAND_SUPPLY_LINK data table.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewDemandSupplyLinkRow(
        string id,
        string demandSiteID,
        string supplySiteID
)
```

VB

```
Public Overridable Function NewDemandSupplyLinkRow (
        id As String,
        demandSiteID As String,
        supplySiteID As String
) As DataRow
```

Parameters

id

Type: System.String

demandSiteID

Type: System.String

supplySiteID

Type: System.String

Return Value

Type: **DataRow**

See Also

DemandSupplyLink Class
NewDemandSupplyLinkRow Overload
Lsa.Vmfg.Purchasing Namespace

DemandSupplyLink.Save Method

Overload List

	Name	Description
	Save()	Saves all previously loaded Demand Supply Links to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

DemandSupplyLink Class
Lsa.Vmfg.Purchasing Namespace

DemandSupplyLink.Save Method

Saves all previously loaded Demand Supply Links to the database.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

DemandSupplyLink Class
Save Overload
Lsa.Vmfg.Purchasing Namespace

DemandSupplyLink.Save Method (Stream)

Save current state of data set to stream.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Save(
        Stream stream
)
```

VB

```
Public Overridable Sub Save (
        stream As Stream
)
```

Parameters

stream

Type: System.IO.Stream

See Also

DemandSupplyLink Class

Save Overload

Lsa.Vmfg.Purchasing Namespace

GetInspectionReceivers Class

Service to obtain all Purchase Receipts held in inspection for a given Site.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessService
          Lsa.Vmfg.Purchasing.GetInspectionReceivers

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class GetInspectionReceivers : BusinessService
```

VB

```
<SerializableAttribute>
Public Class GetInspectionReceivers
        Inherits BusinessService
```

The **GetInspectionReceivers** type exposes the following members.

Constructors

	Name	Description
	GetInspectionReceivers()	Business Document Constructor
	GetInspectionReceivers(String)	Business Document Constructor

Methods

	Name	Description
	Execute	Executes the service.
	NewInputRow	Adds a new request row to the Service.
	Prepare	Prepares the service for execution.

Remarks

Site ID is required. All other input columns are optional and act as filters. For example, if the value for WAREHOUSE_ID were set to “ABC”, only eligible receipts for the specified SITE ***and*** warehouse “ABC” will be selected.

Service input data table name = GET_INSPECTION_RECEIVERS.

Service input data columns:

Column Name	Data Type	Required
SITE_ID	string	Y
PART_ID	string	N
WAREHOUSE_ID	string	N
LOCATION_ID	string	N
RECEIVER_ID	string	N
RECEIVER_LINE_NO	integer	N
PURC_ORDER_ID	string	N
PURC_ORDER_LINE_NO	integer	N

Service output data table = INSPECTION_RECEIVERS. This table holds the results from the execution of the service.

Service output data columns:

Column Name	Data Type	Description
SITE_ID	string	Value from the input table.
RECEIVER_ID	string	RECEIVER.ID

RECEIVER_LINE_NO	integer	RECEIVER.LINE_NO
PURC_ORDER_ID	string	RECEIVER_LINE.PURC_ORDER_ID
PURC_ORDER_LINE_NO	integer	RECEIVER_LINE.PURC_ORDER_LINE_NO
PART_ID	string	PURC_ORDER_LINE.PART_ID
INSP_REASON_CODE	string	RECEIVER_LINE.INSP_REASON_CD
DATA_COLL_COMPLETE	string	RECEIVER_LINE.DATA_COLL_COMP
TRANSACTION_DATE	DateTime	INVENTORY_TRANS.TRANSACTION_DATE
VENDOR_ID	string	PURCHASE_ORDER.VENDOR_ID
INSPECTION_ID	string	INSPECTION_ORDER.ID
INSPECTION_DOC_ID	string	INSPECTION_ORDER.DOCUMENT_ID
STATUS	string	INSPECTION_ORDER.STATUS
QTY_RECEIVED	decimal	INSPECTION_ORDER.QTY_RECEIVED
QTY_ACCEPTED	decimal	INSPECTION_ORDER.QTY_ACCEPTED
QTY_REJECTED	decimal	INSPECTION_ORDER.QTY_REJECTED
PURCHASE_UM	string	PURC_ORDER_LINE.PURCHASE_UM
STOCK_UM	string	PART.STOCK_UM
PIECE_TRACKED	string	PART.PIECE_TRACKED
LENGTH	decimal	PURC_ORDER_LINE.LENGTH
WIDTH	decimal	PURC_ORDER_LINE.WIDTH
HEIGHT	decimal	PURC_ORDER_LINE.HEIGHT

Service output data table = INSPECTION_RECEIVERS_TRACE. This table will only be populated if the Part is defined as requiring Trace for receipts. Service output data columns:

Column Name	Data Type	Description
SITE_ID	string	Value from parent table.
RECEIVER_ID	string	Value from parent table.

Column Name	Data Type	Description
RECEIVER_LINE_NO	integer	Value from parent table.
TRACE_ID	string	TRACE_INV_TRANS.TRACE_ID
QTY	Decimal	TRACE_INV_TRANS.QTY

See Also

Lsa.Vmfg.Purchasing Namespace

GetInspectionReceivers Constructor

Overload List

	Name	Description
	GetInspectionReceivers()	Business Document Constructor
	GetInspectionReceivers(String)	Business Document Constructor

See Also

GetInspectionReceivers Class
Lsa.Vmfg.Purchasing Namespace

GetInspectionReceivers Constructor

Business Document Constructor

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public GetInspectionReceivers()

VB
Public Sub New

See Also

GetInspectionReceivers Class
GetInspectionReceivers Overload
Lsa.Vmfg.Purchasing Namespace

GetInspectionReceivers Constructor (String)

Business Document Constructor

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public GetInspectionReceivers(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

GetInspectionReceivers Class

GetInspectionReceivers Overload

Lsa.Vmfg.Purchasing Namespace

GetInspectionReceivers.GetInspectionReceivers Methods

The GetInspectionReceivers type exposes the following members.

Methods

	Name	Description
	Execute	Executes the service.
	NewInputRow	Adds a new request row to the Service.
	Prepare	Prepares the service for execution.

See Also

GetInspectionReceivers Class
Lsa.Vmfg.Purchasing Namespace

GetInspectionReceivers.Execute Method

Executes the service.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Execute()

VB
Public Overridable Sub Execute

See Also

GetInspectionReceivers Class
Lsa.Vmfg.Purchasing Namespace

GetInspectionReceivers.NewInputRow Method

Adds a new request row to the Service.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewInputRow(
        string siteID
)
```

VB

```
Public Overridable Function NewInputRow (
        siteID As String
) As DataRow
```

Parameters

siteID

Type: System.String

VMFG Site ID. Required. Only Receivers for this Site ID will be queried.

Return Value

Type: **DataRow**

See Also

GetInspectionReceivers Class

Lsa.Vmfg.Purchasing Namespace

GetInspectionReceivers.Prepare Method

Prepares the service for execution.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Prepare()

VB
Public Overridable Sub Prepare

See Also

GetInspectionReceivers Class
Lsa.Vmfg.Purchasing Namespace

PurchaseOrder Class

Maintain Purchase Orders.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessDocument
          Lsa.Vmfg.Purchasing.PurchaseOrder

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class PurchaseOrder : BusinessDocument
```

VB

```
<SerializableAttribute>
Public Class PurchaseOrder
        Inherits BusinessDocument
```

The **PurchaseOrder** type exposes the following members.

Constructors

	Name	Description
	PurchaseOrder()	Business Document Constructor
	PurchaseOrder(String)	Business Document Constructor

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Purchase Orders based on search critera.
	Browse(String, String, String, Int32, Int32)	Retrieve Purchase Orders based on search critera. Number of rows returned is limited by the value of maxRecords.
	Exists	Determines if a specific Purchase Order exists.
	Find	Retrieves a specific Purchase Order from the database. Only the top-level table (PURCHASE_ORDER) is returned.
	Load(String)	Loads a specific Purchase Order.
	Load(Stream, String)	Loads from stream and rename using new key.
	NewOrderLineDelSchedRow(String, Int64)	Inserts a new row into the PURC_LINE_DEL data table. Auto Numbers the line.
	NewOrderLineDelSchedRow(String, Int64, Int64)	Inserts a new row into the PURC_LINE_DEL data table.
	NewOrderLineRow(String)	Inserts a new row into the PURC_ORDER_LINE table. Auto number LINE_NO.
	NewOrderLineRow(String, Int64)	Inserts a new row into the PURC_ORDER_LINE table.
	NewOrderRow	Inserts a new row into the PURCHASE_ORDER table.
	NewPurcLineBinaryRow	Inserts a new row into the PURC_LINE_BINARY data table. Only binary type of "D" (long text) is supported.
	NewPurcOrderBinaryRow	Inserts a new row into the PURC_ORDER_BINARY table. Only binary type of "D" (long text) is supported.
	Save()	Saves all previously loaded Purchase Order to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

Lsa.Vmfg.Purchasing Namespace

PurchaseOrder Constructor

Overload List

	Name	Description
	PurchaseOrder()	Business Document Constructor
	PurchaseOrder(String)	Business Document Constructor

See Also

PurchaseOrder Class
Lsa.Vmfg.Purchasing Namespace

PurchaseOrder Constructor

Business Document Constructor

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public PurchaseOrder()

VB
Public Sub New

See Also

PurchaseOrder Class
PurchaseOrder Overload
Lsa.Vmfg.Purchasing Namespace

PurchaseOrder Constructor (String)

Business Document Constructor

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public PurchaseOrder(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

PurchaseOrder Class

PurchaseOrder Overload

Lsa.Vmfg.Purchasing Namespace

PurchaseOrder.PurchaseOrder Methods

The PurchaseOrder type exposes the following members.

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Purchase Orders based on search critera.
	Browse(String, String, String, Int32, Int32)	Retrieve Purchase Orders based on search critera. Number of rows returned is limited by the value of maxRecords.
	Exists	Determines if a specific Purchase Order exists.
	Find	Retrieves a specific Purchase Order from the database. Only the top-level table (PURCHASE_ORDER) is returned.
	Load(String)	Loads a specific Purchase Order.
	Load(Stream, String)	Loads from stream and rename using new key.
	NewOrderLineDelSchedRow(String, Int64)	Inserts a new row into the PURC_LINE_DEL data table. Auto Numbers the line.
	NewOrderLineDelSchedRow(String, Int64, Int64)	Inserts a new row into the PURC_LINE_DEL data table.
	NewOrderLineRow(String)	Inserts a new row into the PURC_ORDER_LINE table. Auto number LINE_NO.
	NewOrderLineRow(String, Int64)	Inserts a new row into the PURC_ORDER_LINE table.
	NewOrderRow	Inserts a new row into the PURCHASE_ORDER table.
	NewPurcLineBinaryRow	Inserts a new row into the PURC_LINE_BINARY data table. Only binary type of "D" (long text) is supported.
	NewPurcOrderBinaryRow	Inserts a new row into the PURC_ORDER_BINARY table. Only binary type of "D" (long text) is supported.
	Save()	Saves all previously loaded Purchase Order to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

PurchaseOrder Class

Lsa.Vmfg.Purchasing Namespace

PurchaseOrder.Browse Method

Overload List

	Name	Description
	Browse(String, String, String)	Retrieve Purchase Orders based on search critera.
	Browse(String, String, String, Int32, Int32)	Retrieve Purchase Orders based on search critera. Number of rows returned is limited by the value of maxRecords.

See Also

PurchaseOrder Class

Lsa.Vmfg.Purchasing Namespace

PurchaseOrder.Browse Method (String, String, String)

Retrieve Purchase Orders based on search critera.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

Return Value

Type: **DataSet**

See Also

PurchaseOrder Class

Browse Overload

Lsa.Vmfg.Purchasing Namespace

PurchaseOrder.Browse Method (String, String, String, Int32, Int32)

Retrieve Purchase Orders based on search critera. Number of rows returned is limited by the value of maxRecords.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns,
        int startRecord,
        int maxRecords
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String,
        startRecord As Integer,
        maxRecords As Integer
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

startRecord

Type: System.Int32

maxRecords

Type: System.Int32

Return Value

Type: **DataSet**

See Also

PurchaseOrder Class
Browse Overload
Lsa.Vmfg.Purchasing Namespace

PurchaseOrder.Exists Method

Determines if a specific Purchase Order exists.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual bool Exists(
        string orderID
)
```

VB

```
Public Overridable Function Exists (
        orderID As String
) As Boolean
```

Parameters

orderID

Type: System.String

Return Value

Type: Boolean

See Also

PurchaseOrder Class

Lsa.Vmfg.Purchasing Namespace

PurchaseOrder.Find Method

Retrieves a specific Purchase Order from the database. Only the top-level table (PURCHASE_ORDER) is returned.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Find(
        string orderID
)
```

VB

```
Public Overridable Sub Find (
        orderID As String
)
```

Parameters

orderID

Type: System.String

See Also

PurchaseOrder Class

Lsa.Vmfg.Purchasing Namespace

PurchaseOrder.Load Method

Overload List

	Name	Description
	Load(String)	Loads a specific Purchase Order.
	Load(Stream, String)	Loads from stream and rename using new key.

See Also

PurchaseOrder Class
Lsa.Vmfg.Purchasing Namespace

PurchaseOrder.Load Method (String)

Loads a specific Purchase Order.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string orderID
)
```

VB

```
Public Overridable Sub Load (
        orderID As String
)
```

Parameters

orderID

Type: System.String

See Also

PurchaseOrder Class

Load Overload

Lsa.Vmfg.Purchasing Namespace

PurchaseOrder.Load Method (Stream, String)

Loads from stream and rename using new key.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        Stream stream,
        string orderID
)
```

VB

```
Public Overridable Sub Load (
        stream As Stream,
        orderID As String
)
```

Parameters

stream

Type: System.IO.Stream

orderID

Type: System.String

See Also

PurchaseOrder Class

Load Overload

Lsa.Vmfg.Purchasing Namespace

PurchaseOrder.NewOrderLineDelSchedRow Method

Overload List

	Name	Description
	NewOrderLineDelSchedRow(String, Int64)	Inserts a new row into the PURC_LINE_DEL data table. Auto Numbers the line.
	NewOrderLineDelSchedRow(String, Int64, Int64)	Inserts a new row into the PURC_LINE_DEL data table.

See Also

PurchaseOrder Class

Lsa.Vmfg.Purchasing Namespace

PurchaseOrder.NewOrderLineDelSchedRow Method (String, Int64)

Inserts a new row into the PURC_LINE_DEL data table. Auto Numbers the line.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewOrderLineDelSchedRow(
        string orderID,
        long orderLineNo
)
```

VB

```
Public Overridable Function NewOrderLineDelSchedRow (
        orderID As String,
        orderLineNo As Long
) As DataRow
```

Parameters

orderID

Type: System.String

orderLineNo

Type: System.Int64

Return Value

Type: **DataRow**

See Also

PurchaseOrder Class

NewOrderLineDelSchedRow Overload

Lsa.Vmfg.Purchasing Namespace

PurchaseOrder.NewOrderLineDelSchedRow Method (String, Int64, Int64)

Inserts a new row into the PURC_LINE_DEL data table.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewOrderLineDelSchedRow(
        string orderID,
        long orderLineNo,
        long lineNo
)
```

VB

```
Public Overridable Function NewOrderLineDelSchedRow (
        orderID As String,
        orderLineNo As Long,
        lineNo As Long
) As DataRow
```

Parameters

orderID

Type: System.String

orderLineNo

Type: System.Int64

lineNo

Type: System.Int64

Return Value

Type: **DataRow**

See Also

PurchaseOrder Class

NewOrderLineDelSchedRow Overload

Lsa.Vmfg.Purchasing Namespace

PurchaseOrder.NewOrderLineRow Method

Overload List

	Name	Description
	NewOrderLineRow(String)	Inserts a new row into the PURC_ORDER_LINE table. Auto number LINE_NO.
	NewOrderLineRow(String, Int64)	Inserts a new row into the PURC_ORDER_LINE table.

See Also

PurchaseOrder Class

Lsa.Vmfg.Purchasing Namespace

PurchaseOrder.NewOrderLineRow Method (String)

Inserts a new row into the PURC_ORDER_LINE table. Auto number LINE_NO.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewOrderLineRow(
        string orderID
)
```

VB

```
Public Overridable Function NewOrderLineRow (
        orderID As String
) As DataRow
```

Parameters

orderID

Type: System.String

Return Value

Type: **DataRow**

See Also

PurchaseOrder Class

NewOrderLineRow Overload

Lsa.Vmfg.Purchasing Namespace

PurchaseOrder.NewOrderLineRow Method (String, Int64)

Inserts a new row into the PURC_ORDER_LINE table.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewOrderLineRow(
        string orderID,
        long lineNo
)
```

VB

```
Public Overridable Function NewOrderLineRow (
        orderID As String,
        lineNo As Long
) As DataRow
```

Parameters

orderID

Type: System.String

lineNo

Type: System.Int64

Return Value

Type: **DataRow**

See Also

PurchaseOrder Class

NewOrderLineRow Overload

Lsa.Vmfg.Purchasing Namespace

PurchaseOrder.NewOrderRow Method

Inserts a new row into the PURCHASE_ORDER table.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewOrderRow(
        string orderID
)
```

VB

```
Public Overridable Function NewOrderRow (
        orderID As String
) As DataRow
```

Parameters

orderID

Type: System.String

Return Value

Type: **DataRow**

See Also

PurchaseOrder Class

Lsa.Vmfg.Purchasing Namespace

PurchaseOrder.NewPurcLineBinaryRow Method

Inserts a new row into the PURC_LINE_BINARY data table. Only binary type of "D" (long text) is supported.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewPurcLineBinaryRow(
        string orderID,
        int purcOrderLineNo,
        string binaryType
)
```

VB

```
Public Overridable Function NewPurcLineBinaryRow (
        orderID As String,
        purcOrderLineNo As Integer,
        binaryType As String
) As DataRow
```

Parameters

orderID

Type: System.String

purcOrderLineNo

Type: System.Int32

binaryType

Type: System.String

Return Value

Type: **DataRow**

See Also

PurchaseOrder Class

Lsa.Vmfg.Purchasing Namespace

PurchaseOrder.NewPurcOrderBinaryRow Method

Inserts a new row into the PURC_ORDER_BINARY table. Only binary type of "D" (long text) is supported.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewPurcOrderBinaryRow(
        string orderID,
        string binaryType
)
```

VB

```
Public Overridable Function NewPurcOrderBinaryRow (
        orderID As String,
        binaryType As String
) As DataRow
```

Parameters

orderID

Type: System.String

binaryType

Type: System.String

Return Value

Type: **DataRow**

See Also

PurchaseOrder Class

Lsa.Vmfg.Purchasing Namespace

PurchaseOrder.Save Method

Overload List

	Name	Description
	Save()	Saves all previously loaded Purchase Order to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

PurchaseOrder Class
Lsa.Vmfg.Purchasing Namespace

PurchaseOrder.Save Method

Saves all previously loaded Purchase Order to the database.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

PurchaseOrder Class
Save Overload
Lsa.Vmfg.Purchasing Namespace

PurchaseOrder.Save Method (Stream)

Save current state of data set to stream.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Save(
        Stream stream
)
```

VB

```
Public Overridable Sub Save (
        stream As Stream
)
```

Parameters

stream

Type: System.IO.Stream

See Also

PurchaseOrder Class

Save Overload

Lsa.Vmfg.Purchasing Namespace

Receipt Class

Purchase Receipt Transaction.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessTransaction
          Lsa.Vmfg.Purchasing.Receipt

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class Receipt : BusinessTransaction
```

VB

```
<SerializableAttribute>
Public Class Receipt
        Inherits BusinessTransaction
```

The **Receipt** type exposes the following members.

Constructors

	Name	Description
	Receipt()	Business Transaction Constructor
	Receipt(String)	Business Transaction Constructor

Methods

	Name	Description
	NewReceiptDelSchedLineRow	Inserts a new row into the DEL_SCHED_LINE Data Table. See Receipt.
	NewReceiptLineRow	Inserts a new row into the RECEIPT_LINE Data Table. See Receipt.
	NewReceiptRow	Inserts a new row into the RECEIPT Data Table. See Receipt.
	NewReceiptTraceRow	Inserts a new row into the TRACE Data Table. See Receipt.
	Prepare	Creates an empty dataset for the transaction. You must populate the dataset prior to saving the transaction.
	Save	Saves the transaction(s).

Transaction

	Name	Data set returned by Prepare	Description
	Receipt	RECEIPT	This transaction will save a Receiver and all related transactions to cause inventory to be adjusted accordingly. Please note that it is hierarchical. Each Receiver header has one to many receiver lines, these lines may have one to many delivery schedule lines, and each receiver line may have one to many trace entries.

See Also

Lsa.Vmfg.Purchasing Namespace

Receipt Constructor

Overload List

	Name	Description
	Receipt()	Business Transaction Constructor
	Receipt(String)	Business Transaction Constructor

See Also

Receipt Class
Lsa.Vmfg.Purchasing Namespace

Receipt Constructor

Business Transaction Constructor

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public Receipt()

VB
Public Sub New

See Also

Receipt Class
Receipt Overload
Lsa.Vmfg.Purchasing Namespace

Receipt Constructor (String)

Business Transaction Constructor

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public Receipt(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

Receipt Class

Receipt Overload

Lsa.Vmfg.Purchasing Namespace

Receipt.Receipt Methods

The Receipt type exposes the following members.

Methods

	Name	Description
	NewReceiptDelSchedLineRow	Inserts a new row into the DEL_SCHED_LINE Data Table. See Receipt.
	NewReceiptLineRow	Inserts a new row into the RECEIPT_LINE Data Table. See Receipt.
	NewReceiptRow	Inserts a new row into the RECEIPT Data Table. See Receipt.
	NewReceiptTraceRow	Inserts a new row into the TRACE Data Table. See Receipt.
	Prepare	Creates an empty dataset for the transaction. You must populate the dataset prior to saving the transaction.
	Save	Saves the transaction(s).

See Also

Receipt Class

Lsa.Vmfg.Purchasing Namespace

Receipt.NewReceiptDelSchedLineRow Method

Inserts a new row into the DEL_SCHED_LINE Data Table.

See Receipt for further information about the input values for this transaction.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewReceiptDelSchedLineRow(
        string purcOrderID,
        int purcOrderLineNo,
        int delSchedLineNo
)
```

VB

```
Public Overridable Function NewReceiptDelSchedLineRow (
        purcOrderID As String,
        purcOrderLineNo As Integer,
        delSchedLineNo As Integer
) As DataRow
```

Parameters

purcOrderID

Type: System.String

purcOrderLineNo

Type: System.Int32

delSchedLineNo

Type: System.Int32

Return Value

Type: **DataRow**

See Also

Receipt

Receipt Class

Lsa.Vmfg.Purchasing Namespace

Receipt.NewReceiptLineRow Method

Inserts a new row into the RECEIPT_LINE Data Table.

See Receipt for further information about the input values for this transaction.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewReceiptLineRow(
        string purcOrderID,
        int purcOrderLineNo
)
```

VB

```
Public Overridable Function NewReceiptLineRow (
        purcOrderID As String,
        purcOrderLineNo As Integer
) As DataRow
```

Parameters

purcOrderID

Type: System.String

purcOrderLineNo

Type: System.Int32

Return Value

Type: **DataRow**

See Also

Receipt

Receipt Class

Lsa.Vmfg.Purchasing Namespace

Receipt.NewReceiptRow Method

Inserts a new row into the RECEIPT Data Table.

See Receipt for further information about the input values for this transaction.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewReceiptRow(
        string purcOrderID
)
```

VB

```
Public Overridable Function NewReceiptRow (
        purcOrderID As String
) As DataRow
```

Parameters

purcOrderID

Type: System.String

Return Value

Type: **DataRow**

See Also

Receipt

Receipt Class

Lsa.Vmfg.Purchasing Namespace

Receipt.NewReceiptTraceRow Method

Inserts a new row into the TRACE Data Table.

See Receipt for further information about the input values for this transaction.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewReceiptTraceRow(
        string purcOrderID,
        int purcOrderLineNo,
        string traceID
)
```

VB

```
Public Overridable Function NewReceiptTraceRow (
        purcOrderID As String,
        purcOrderLineNo As Integer,
        traceID As String
) As DataRow
```

Parameters

purcOrderID

Type: System.String

purcOrderLineNo

Type: System.Int32

traceID

Type: System.String

Return Value

Type: **DataRow**

See Also

Receipt

Receipt Class

Lsa.Vmfg.Purchasing Namespace

Receipt.Prepare Method

Creates an empty dataset for the transaction. You must populate the dataset prior to saving the transaction.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Prepare()

VB
Public Overridable Sub Prepare

See Also

Receipt Class
Lsa.Vmfg.Purchasing Namespace

Receipt.Save Method

Saves the transaction(s).

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

Receipt Class
Lsa.Vmfg.Purchasing Namespace

Receipt

This transaction will save a Receiver and all related transactions to cause inventory to be adjusted accordingly. Please note that it is hierarchical. Each Receiver header has one to many receiver lines, these lines may have one to many delivery schedule lines, and each receiver line may have one to many trace entries.

Namespace: Lsa.Vmfg.Purchasing

Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Dataset name returned from Prepare: RECEIPT

Primary Key: PURC_ORDER_ID

Column Name	Type	Description
TRANSACTION_DATE	Date	Date of transaction. Defaults to current date.
RECEIVER_ID	String	Receiver ID of receiver being created. If not provided, receiver will be automatically numbered.
PURC_ORDER_ID	String	Purchase Order ID being received. Required.
FREE_ON_BOARD	String	Free on board code for the order. Optional, not validated.
SHIP_VIA	String	Shipping method for the order. Optional, not validated.
SITE_ID	String	The Site ID for the order. Required.
CLOSE_SHORT	Boolean	Boolean flag, signifies final disposition of purchase order in the event that the received quantity is less than the ordered quantity. A value of “true” will close the order, “false” will leave the order open. Default value is “false”.
USER_ID	String	The User ID of the person performing the transaction. Defaults to SYSADM.
RECEIVE_ALL	Boolean	If set to true, will receive the purchase order in its entirety. If this feature is used, you do not populate any of the sub-tables for this transaction, they will be populated automatically. This is analogous to clicking the “Receive All” button in Visual. Note that this feature cannot be used if the purchase order has existing delivery schedules or requires lot / serial number tracing.

Sub-Table Name: RECEIPT_LINE

Primary Key: PURC_ORDER_ID, PURC_ORDER_LINE_NO

This table is required, unless the header table is set to RECEIVE_ALL.

Column Name	Type	Description
PURC_ORDER_ID	String	Purchase Order being received. This value must match an existing value in the RECEIPT table defined above.
PURC_ORDER_LINE_NO	Integer	The purchase order line number being received. Required.
SITE_ID	String	The Site ID associated with the order line. Optional. Will default to the Order Site ID if blank.
USER_QTY	Decimal	If the Part is not defined as piece tracked, the quantity being received, in the purchasing unit of measure. If the Part is defined as piece tracked, leave this field blank and use PIECE_COUNT instead.
STOCK_QTY	Decimal	The order line quantity converted to the stock unit of measure.
LENGTH	Decimal	Length of pieces being received. Required if Part is defined as piece tracked by length.
WIDTH	Decimal	Width of pieces being received. Required if Part is defined as piece tracked by width.
HEIGHT	Decimal	Height of pieces being received. Required if Part is defined as piece tracked by height.
RECEIVE_TO_INSP	Boolean	Boolean flag, when set, signifies that parts are being received to an inspection (on hold) location. Valid values true or false. Defaults to false.
WAREHOUSE_ID	String	The warehouse to which the parts are being received. Defaults to either the Part's primary warehouse / location or the Part's default hold warehouse / location if RECV_TO_INSP is true.
LOCATION_ID	String	The location to which the parts are being received. Defaults to the Part's primary warehouse / location or the Part's default hold warehouse / location if RECV_TO_INSP is true.
HTS_CODE	String	Harmonized Tariff code.

Sub-Table Name: DEL_SCHED_LINE

Primary Key: PURC_ORDER_ID, PURC_ORDER_LINE_NO, DEL_SCHED_LINE_NO

The DEL_SCHED_LINE sub-table is only applicable for purchase orders containing delivery schedules.

Column Name	Type	Description
PURC_ORDER_ID	String	Purchase Order being received. This value must match an existing value in the RECEIPT and RECEIPT_LINE tables.
PURC_ORDER_LINE_NO	Integer	Line Number of the purchase order being received. This value must match an existing value in the RECEIPT_LINE table.
DEL_SCHED_LINE_NO	Integer	The line number of the delivery schedule being received.
USER_QTY	Decimal	For non-piece tracked parts, the quantity of this delivery schedule line being received, stated in purchasing unit of measure. For piece tracked parts, leave this field blank and use PIECE_COUNT instead.
PIECE_COUNT	Integer	The number of pieces being received. For piece tracked parts only. Leave blank for non-piece tracked parts.
STOCK_QTY	Decimal	The order line quantity converted to the stock unit of measure.

Sub-Table Name: TRACE

Primary Key: PURC_ORDER_ID, PURC_ORDER_LINE_NO, TRACE_ID

The TRACE sub-table is only applicable for purchase order lines with parts defined as traceable for receipt transactions.

Column Name	Type	Description
PURC_ORDER_ID	String	The ID of the purchase order being received.
PURC_ORDER_LINE_NO	Integer	The PO line number this row of trace information belongs to.
TRACE_ID	String	Trace ID. Lot or serial number for the parts being received. If the part's trace profile supports auto numbering, and you wish to have the Trace Ids auto numbered, you must set the TRACE_ID values to the format "<n>" where n is a unique integer.
ALPHA_PROPERTY_1	String	May be required, depending on the Part's trace profile.
ALPHA_PROPERTY_2	String	May be required, depending on the Part's trace profile.

Column Name	Type	Description
ALPHA_PROPERTY_3	String	May be required, depending on the Part's trace profile.
ALPHA_PROPERTY_4	String	May be required, depending on the Part's trace profile.
ALPHA_PROPERTY_5	String	May be required, depending on the Part's trace profile.
NUMERIC_PROPERTY_1	Decimal	May be required, depending on the Part's trace profile.
NUMERIC_PROPERTY_2	Decimal	May be required, depending on the Part's trace profile.
NUMERIC_PROPERTY_3	Decimal	May be required, depending on the Part's trace profile.
NUMERIC_PROPERTY_4	Decimal	May be required, depending on the Part's trace profile.
NUMERIC_PROPERTY_5	Decimal	May be required, depending on the Part's trace profile.
COMMENTS	String	Optional user comments on specific lot or serial number.
EXPIRATION_DATE	Date	Expiration date. Determines shelf life of lot. Optional.
QTY	Decimal	Quantity of transaction associated directly with this trace ID. The sum of all trace detail QTY fields must equal the total received quantity for the associated receiver line item.
DISP_IN_QTY	Decimal	
DISP_OUT_QTY	Decimal	
UNAVAILABLE_QTY	Decimal	
OWNER_ID	String	
LOT_ID	String	
SERIAL_ID	String	
COMMITTED_QTY	Decimal	
PRODUCTION_DATE	DateTime	
RECEIVE_BY_DATE	DateTime	
AVAILABLE_DATE	DateTime	

Column Name	Type	Description
SHIP_BY_DATE	DateTime	

See Also

Receipt Class
Receipt.NewReceiptDelSchedLineRow
Receipt.NewReceiptLineRow
Receipt.NewReceiptRow
Receipt.NewReceiptTraceRow
Lsa.Vmfg.Purchasing Namespace

Receiver Class

Maintain Receivers. Note: Only Receiver headers may be inserted through this data document. Receiver headers created here are not associated with any inventory transactions, thus they are 'pre receipt' documents. Complete Receivers (with line items) must be created via the Receipt Data Transaction.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessDocument
          Lsa.Vmfg.Purchasing.Receiver

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class Receiver : BusinessDocument
```

VB

```
<SerializableAttribute>
Public Class Receiver
        Inherits BusinessDocument
```

The **Receiver** type exposes the following members.

Constructors

	Name	Description
	Receiver()	Business Transaction Constructor

	Receiver(String)	Business Transaction Constructor

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Receivers based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Receivers based on search criteria, limited by record count
	Exists	Determine if a specific Receiver exists.
	Find	Retrieves a specific Receiver. Only the top-level table (RECEIVER) is returned.
	Load	Load a specific Receiver.
	Save	Save all previously loaded Receivers to the database.

See Also

Lsa.Vmfg.Purchasing Namespace

Receiver Constructor

Overload List

	Name	Description
	Receiver()	Business Transaction Constructor
	Receiver(String)	Business Transaction Constructor

See Also

Receiver Class
Lsa.Vmfg.Purchasing Namespace

Receiver Constructor

Business Transaction Constructor

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public Receiver()

VB
Public Sub New

See Also

Receiver Class
Receiver Overload
Lsa.Vmfg.Purchasing Namespace

Receiver Constructor (String)

Business Transaction Constructor

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public Receiver(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

Receiver Class

Receiver Overload

Lsa.Vmfg.Purchasing Namespace

Receiver.Receiver Methods

The Receiver type exposes the following members.

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Receivers based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Receivers based on search criteria, limited by record count
	Exists	Determine if a specific Receiver exists.
	Find	Retrieves a specific Receiver. Only the top-level table (RECEIVER) is returned.
	Load	Load a specific Receiver.
	Save	Save all previously loaded Receivers to the database.

See Also

Receiver Class

Lsa.Vmfg.Purchasing Namespace

Receiver.Browse Method

Overload List

	Name	Description
	Browse(String, String, String)	Retrieve Receivers based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Receivers based on search criteria, limited by record count

See Also

Receiver Class
Lsa.Vmfg.Purchasing Namespace

Receiver.Browse Method (String, String, String)

Retrieve Receivers based on search criteria.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

Return Value

Type: **DataSet**

See Also

Receiver Class

Browse Overload

Lsa.Vmfg.Purchasing Namespace

Receiver.Browse Method (String, String, String, Int32, Int32)

Retrieve Receivers based on search criteria, limited by record count

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns,
        int startRecord,
        int maxRecords
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String,
        startRecord As Integer,
        maxRecords As Integer
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

startRecord

Type: System.Int32

maxRecords

Type: System.Int32

Return Value

Type: **DataSet**

See Also

Receiver Class
Browse Overload
Lsa.Vmfg.Purchasing Namespace

Receiver.Exists Method

Determine if a specific Receiver exists.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual bool Exists(
        string receiverID
)
```

VB

```
Public Overridable Function Exists (
        receiverID As String
) As Boolean
```

Parameters

receiverID

Type: System.String

Return Value

Type: Boolean

See Also

Receiver Class

Lsa.Vmfg.Purchasing Namespace

Receiver.Find Method

Retrieves a specific Receiver. Only the top-level table (RECEIVER) is returned.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Find(
        string receiverID
)
```

VB

```
Public Overridable Sub Find (
        receiverID As String
)
```

Parameters

receiverID

Type: System.String

See Also

Receiver Class

Lsa.Vmfg.Purchasing Namespace

Receiver.Load Method

Load a specific Receiver.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string receiverID
)
```

VB

```
Public Overridable Sub Load (
        receiverID As String
)
```

Parameters

receiverID

Type: System.String

See Also

Receiver Class

Lsa.Vmfg.Purchasing Namespace

Receiver.Save Method

Save all previously loaded Receivers to the database.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

Receiver Class
Lsa.Vmfg.Purchasing Namespace

ReceivingInspection Class

Receiving Inspection Transaction.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessTransaction
          Lsa.Vmfg.Purchasing.ReceivingInspection

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class ReceivingInspection : BusinessTransaction
```

VB

```
<SerializableAttribute>
Public Class ReceivingInspection
        Inherits BusinessTransaction
```

The **ReceivingInspection** type exposes the following members.

Constructors

	Name	Description
	ReceivingInspection()	Business Transaction Constructor
	ReceivingInspection(String)	Business Transaction Constructor

Methods

	Name	Description
	NewInspectionRow	Inserts a new row into the RECEIVING_INSPECTION Data Table.
	NewInspectionTraceRow	Inserts a new row into the TRACE Data Table. Only applies for Traced Parts.
	Prepare	Creates an empty dataset for the transaction. You must populate the dataset prior to saving the transaction.
	Save	Saves the transaction(s).

See Also

Lsa.Vmfg.Purchasing Namespace

ReceivingInspection Constructor

Overload List

	Name	Description
	ReceivingInspection()	Business Transaction Constructor
	ReceivingInspection(String)	Business Transaction Constructor

See Also

ReceivingInspection Class
Lsa.Vmfg.Purchasing Namespace

ReceivingInspection Constructor

Business Transaction Constructor

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public ReceivingInspection()

VB
Public Sub New

See Also

ReceivingInspection Class
ReceivingInspection Overload
Lsa.Vmfg.Purchasing Namespace

ReceivingInspection Constructor (String)

Business Transaction Constructor

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public ReceivingInspection(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

ReceivingInspection Class

ReceivingInspection Overload

Lsa.Vmfg.Purchasing Namespace

ReceivingInspection.ReceivingInspection Methods

The ReceivingInspection type exposes the following members.

Methods

	Name	Description
	NewInspectionRow	Inserts a new row into the RECEIVING_INSPECTION Data Table.
	NewInspectionTraceRow	Inserts a new row into the TRACE Data Table.
	Prepare	Creates an empty dataset for the transaction. You must populate the dataset prior to saving the transaction.
	Save	Saves the transaction(s).

See Also

ReceivingInspection Class
Lsa.Vmfg.Purchasing Namespace

ReceivingInspection.NewInspectionRow Method

Inserts a new row into the RECEIVING_INSPECTION Data Table.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewInspectionRow(
        string receiverID,
        int receiverLineNo
)
```

VB

```
Public Overridable Function NewInspectionRow (
        receiverID As String,
        receiverLineNo As Integer
) As DataRow
```

Parameters

receiverID

Type: System.String

receiverLineNo

Type: System.Int32

Return Value

Type: **DataRow**

See Also

ReceivingInspection Class

Lsa.Vmfg.Purchasing Namespace

ReceivingInspection.NewInspectionTraceRow Method

Inserts a new row into the TRACE Data Table. Only use this method if you are dealing with Traced Parts.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewInspectionTraceRow(
        string receiverID,
        int receiverLineNo,
        string traceID
)
```

VB

```
Public Overridable Function NewInspectionTraceRow (
        receiverID As String,
        receiverLineNo As Integer,
        traceID As String
) As DataRow
```

Parameters

receiverID

Type: System.String

receiverLineNo

Type: System.Int32

traceID

Type: System.String

Return Value

Type: **DataRow**

See Also

ReceivingInspection Class

Lsa.Vmfg.Purchasing Namespace

ReceivingInspection.Prepare Method

Creates an empty dataset for the transaction. You must populate the dataset prior to saving the transaction.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Prepare()

VB
Public Overridable Sub Prepare

See Also

ReceivingInspection Class
Lsa.Vmfg.Purchasing Namespace

ReceivingInspection.Save Method

Saves the transaction(s).

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

ReceivingInspection Class
Lsa.Vmfg.Purchasing Namespace

ReceivingInspection Transaction

The input dataset for the ReceivingInspection transaction consists of two data tables.

The first data table is named RECEIVING_INSPECTION and is required. The second data table is named TRACE and is only required if the Receiver Line specifies a Part ID that requires Part Traceability on receipts.

Data Table name returned from Prepare: RECEIVING_INSPECTION

Primary Key: RECEIVER_ID, RECEIVER_LINE_NO.

Column Name	Type	Description
RECEIVER_ID	String	The Receiver ID for which Receiving Inspection will be performed on. Required.
RECEIVER_LINE_NO	Integer	The line number of the Receiver ID being processed. Required.
TRANSACTION_DATE	Date	Defines the transaction date for all inventory transactions generated by this transaction. Defaults to the current date.
QTY_RELEASED	Decimal	The quantity released i.e. the quantity that has passed inspection. Defaults to 0.
QTY_REJECTED	Decimal	The quantity that has failed inspection. Defaults to 0.
RELEASE_TO_WAREHOUSE_ID	String	Warehouse ID the accepted parts will be released to. Optional. Defaults to Part's primary warehouse.
RELEASE_TO_LOCATION_ID	String	Location ID the accepted parts will be released to. Optional. Defaults to Part's primary location.
INSPECTION_REASON	String	Reason for the inspection. Optional. If used, the value must exist in the INSPECTION_REASON table.
DATA_COLLECTION_COMPLETE	String	Flag to indicate that Data Collection is complete. Optional. Valid values "Y" or "N". Default is "N".

Data Table name returned from Prepare: TRACE

Primary Key: RECEIVER_ID, RECEIVER_LINE_NO, TRACE_ID.

Column Name	Type	Description
RECEIVER_ID	String	The Receiver ID for which Receiving Inspection will be performed on. Required.
RECEIVER_LINE_NO	Integer	The line number of the Receiver ID being processed. Required.
TRACE_ID	String	The Trace ID / Lot Serial Number assigned when the lot was initially received into inspection. Required.
QTY_RELEASED	Decimal	The quantity released i.e. the quantity that has passed inspection. Defaults to 0.
QTY_REJECTED	Decimal	The quantity that has failed inspection. Defaults to 0.

RequestForQuote Class

Maintain Requests For Quote.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessDocument
          Lsa.Vmfg.Purchasing.RequestForQuote

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class RequestForQuote : BusinessDocument
```

VB

```
<SerializableAttribute>
Public Class RequestForQuote
        Inherits BusinessDocument
```

The **RequestForQuote** type exposes the following members.

Constructors

	Name	Description
	RequestForQuote()	Business Document Constructor
	RequestForQuote(String)	Business Document Constructor

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Requests For Quote based on search critera.
	Browse(String, String, String, Int32, Int32)	Retrieve Requests For Quote based on search critera. Number of rows returned is limited by the value of maxRecords.
	Exists	Determines if a specific Request For Quote exists in the database.
	Find	Retrieves a specific Request For Quote. Only the top-level table (RFQ) is returned.
	Load(String)	Loads a specific Request For Quote.
	Load(Stream, String)	Load from stream and rename using new key.
	NewRfqBinaryRow	Inserts a new row into the RFQ_BINARY table. Only the binary type "D" (long text) is supported.
	NewRfqLineBinaryRow	Inserts a new row into the RFQ_LINE_BINARY table. Only the binary type "D" (long text) is supported.
	NewRfqLineRow(String)	Inserts a new row into the RFQ_LINE table. Auto number LINE_NO.
	NewRfqLineRow(String, Int64)	Inserts a new row into the RFQ_LINE table.
	NewRfqRow	Inserts a new row into the REQUEST_FOR_QUOTE table.
	Save()	Saves all previously loaded Requests For Quote to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

Lsa.Vmfg.Purchasing Namespace

RequestForQuote Constructor

Overload List

	Name	Description
	RequestForQuote()	Business Document Constructor
	RequestForQuote(String)	Business Document Constructor

See Also

RequestForQuote Class
Lsa.Vmfg.Purchasing Namespace

RequestForQuote Constructor

Business Document Constructor

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public RequestForQuote()

VB
Public Sub New

See Also

RequestForQuote Class
RequestForQuote Overload
Lsa.Vmfg.Purchasing Namespace

RequestForQuote Constructor (String)

Business Document Constructor

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public RequestForQuote(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

RequestForQuote Class

RequestForQuote Overload

Lsa.Vmfg.Purchasing Namespace

RequestForQuote.RequestForQuote Methods

The RequestForQuote type exposes the following members.

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Requests For Quote based on search critera.
	Browse(String, String, String, Int32, Int32)	Retrieve Requests For Quote based on search critera. Number of rows returned is limited by the value of maxRecords.
	Exists	Determines if a specific Request For Quote exists in the database.
	Find	Retrieves a specific Request For Quote. Only the top-level table (RFQ) is returned.
	Load(String)	Loads a specific Request For Quote.
	Load(Stream, String)	Load from stream and rename using new key.
	NewRfqBinaryRow	Inserts a new row into the RFQ_BINARY table. Only the binary type "D" (long text) is supported.
	NewRfqLineBinaryRow	Inserts a new row into the RFQ_LINE_BINARY table. Only the binary type "D" (long text) is supported.
	NewRfqLineRow(String)	Inserts a new row into the RFQ_LINE table. Auto number LINE_NO.
	NewRfqLineRow(String, Int64)	Inserts a new row into the RFQ_LINE table.
	NewRfqRow	Inserts a new row into the REQUEST_FOR_QUOTE table.
	Save()	Saves all previously loaded Requests For Quote to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

RequestForQuote Class

Lsa.Vmfg.Purchasing Namespace

RequestForQuote.Browse Method

Overload List

	Name	Description
	Browse(String, String, String)	Retrieve Requests For Quote based on search critera.
	Browse(String, String, String, Int32, Int32)	Retrieve Requests For Quote based on search critera. Number of rows returned is limited by the value of maxRecords.

See Also

RequestForQuote Class

Lsa.Vmfg.Purchasing Namespace

RequestForQuote.Browse Method (String, String, String)

Retrieve Requests For Quote based on search critera.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

Return Value

Type: **DataSet**

See Also

RequestForQuote Class

Browse Overload

Lsa.Vmfg.Purchasing Namespace

RequestForQuote.Browse Method (String, String, String, Int32, Int32)

Retrieve Requests For Quote based on search critera. Number of rows returned is limited by the value of maxRecords.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns,
        int startRecord,
        int maxRecords
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String,
        startRecord As Integer,
        maxRecords As Integer
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

startRecord

Type: System.Int32

maxRecords

Type: System.Int32

Return Value

Type: **DataSet**

See Also

RequestForQuote Class
Browse Overload
Lsa.Vmfg.Purchasing Namespace

RequestForQuote.Exists Method

Determines if a specific Request For Quote exists in the database.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual bool Exists(
        string rfqID
)
```

VB

```
Public Overridable Function Exists (
        rfqID As String
) As Boolean
```

Parameters

rfqID

Type: System.String

Return Value

Type: Boolean

See Also

RequestForQuote Class

Lsa.Vmfg.Purchasing Namespace

RequestForQuote.Find Method

Retrieves a specific Request For Quote. Only the top-level table (RFQ) is returned.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Find(
        string rfqID
)
```

VB

```
Public Overridable Sub Find (
        rfqID As String
)
```

Parameters

rfqID

Type: System.String

See Also

RequestForQuote Class

Lsa.Vmfg.Purchasing Namespace

RequestForQuote.Load Method

Overload List

	Name	Description
	Load(String)	Loads a specific Request For Quote.
	Load(Stream, String)	Load from stream and rename using new key.

See Also

RequestForQuote Class
Lsa.Vmfg.Purchasing Namespace

RequestForQuote.Load Method (String)

Loads a specific Request For Quote.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string rfqID
)
```

VB

```
Public Overridable Sub Load (
        rfqID As String
)
```

Parameters

rfqID

Type: System.String

See Also

RequestForQuote Class

Load Overload

Lsa.Vmfg.Purchasing Namespace

RequestForQuote.Load Method (Stream, String)

Load from stream and rename using new key.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        Stream stream,
        string rfqID
)
```

VB

```
Public Overridable Sub Load (
        stream As Stream,
        rfqID As String
)
```

Parameters

stream

Type: System.IO.Stream

rfqID

Type: System.String

See Also

RequestForQuote Class

Load Overload

Lsa.Vmfg.Purchasing Namespace

RequestForQuote.NewRfqBinaryRow Method

Inserts a new row into the RFQ_BINARY table. Only the binary type "D" (long text) is supported.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewRfqBinaryRow(
        string rfqID,
        string binaryType
)
```

VB

```
Public Overridable Function NewRfqBinaryRow (
        rfqID As String,
        binaryType As String
) As DataRow
```

Parameters

rfqID

Type: System.String

binaryType

Type: System.String

Return Value

Type: **DataRow**

See Also

RequestForQuote Class

Lsa.Vmfg.Purchasing Namespace

RequestForQuote.NewRfqLineBinaryRow Method

Inserts a new row into the RFQ_LINE_BINARY table. Only the binary type "D" (long text) is supported.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewRfqLineBinaryRow(
        string rfqID,
        int rfqLineNo,
        string binaryType
)
```

VB

```
Public Overridable Function NewRfqLineBinaryRow (
        rfqID As String,
        rfqLineNo As Integer,
        binaryType As String
) As DataRow
```

Parameters

rfqID

Type: System.String

rfqLineNo

Type: System.Int32

binaryType

Type: System.String

Return Value

Type: **DataRow**

See Also

RequestForQuote Class

Lsa.Vmfg.Purchasing Namespace

RequestForQuote.NewRfqLineRow Method

Overload List

	Name	Description
	NewRfqLineRow(String)	Inserts a new row into the RFQ_LINE table. Auto number LINE_NO.
	NewRfqLineRow(String, Int64)	Inserts a new row into the RFQ_LINE table.

See Also

RequestForQuote Class
Lsa.Vmfg.Purchasing Namespace

RequestForQuote.NewRfqLineRow Method (String)

Inserts a new row into the RFQ_LINE table. Auto number LINE_NO.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewRfqLineRow(
        string rfqID
)
```

VB

```
Public Overridable Function NewRfqLineRow (
        rfqID As String
) As DataRow
```

Parameters

rfqID

Type: System.String

Return Value

Type: **DataRow**

See Also

RequestForQuote Class

NewRfqLineRow Overload

Lsa.Vmfg.Purchasing Namespace

RequestForQuote.NewRfqLineRow Method (String, Int64)

Inserts a new row into the RFQ_LINE table.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewRfqLineRow(
        string rfqID,
        long lineNo
)
```

VB

```
Public Overridable Function NewRfqLineRow (
        rfqID As String,
        lineNo As Long
) As DataRow
```

Parameters

rfqID

Type: System.String

lineNo

Type: System.Int64

Return Value

Type: **DataRow**

See Also

RequestForQuote Class

NewRfqLineRow Overload

Lsa.Vmfg.Purchasing Namespace

RequestForQuote.NewRfqRow Method

Inserts a new row into the REQUEST_FOR_QUOTE table.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewRfqRow(
        string rfqID
)
```

VB

```
Public Overridable Function NewRfqRow (
        rfqID As String
) As DataRow
```

Parameters

rfqID

Type: System.String

Return Value

Type: **DataRow**

See Also

RequestForQuote Class

Lsa.Vmfg.Purchasing Namespace

RequestForQuote.Save Method

Overload List

	Name	Description
	Save()	Saves all previously loaded Requests For Quote to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

RequestForQuote Class
Lsa.Vmfg.Purchasing Namespace

RequestForQuote.Save Method

Saves all previously loaded Requests For Quote to the database.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

RequestForQuote Class
Save Overload
Lsa.Vmfg.Purchasing Namespace

RequestForQuote.Save Method (Stream)

Save current state of data set to stream.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Save(
        Stream stream
)
```

VB

```
Public Overridable Sub Save (
        stream As Stream
)
```

Parameters

stream

Type: System.IO.Stream

See Also

RequestForQuote Class

Save Overload

Lsa.Vmfg.Purchasing Namespace

Return Class

Purchase Return Transaction.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessTransaction
          Lsa.Vmfg.Purchasing.Return

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class Return : BusinessTransaction
```

VB

```
<SerializableAttribute>
Public Class Return
        Inherits BusinessTransaction
```

The **Return** type exposes the following members.

Constructors

	Name	Description
	Return()	Business Transaction Constructor
	Return(String)	Business Transaction Constructor

Methods

	Name	Description
	NewReturnDelSchedLineRow	Inserts a new row into the DEL_SCHED_LINE Data Table. See Return.
	NewreturnLineRow	Inserts a new row into the RETURN_LINE Data Table. See Return.
	NewReturnRow	Inserts a new row into the RETURN Data Table. See Return.
	NewReturnTraceRow	Inserts a new row into the TRACE Data Table. See Return.
	Prepare	Creates an empty dataset for the transaction. You must populate the dataset prior to saving the transaction.
	Save	Saves the transactions(s)

Transaction

	Name	Data set returned by Prepare	Description
	Return	RETURN	This transaction will create a new Purchase Receipt Return from an existing Purchase Order.

See Also

Lsa.Vmfg.Purchasing Namespace

Return Constructor

Overload List

	Name	Description
	Return()	Business Transaction Constructor
	Return(String)	Business Transaction Constructor

See Also

Return Class
Lsa.Vmfg.Purchasing Namespace

Return Constructor

Business Transaction Constructor

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public Return()

VB
Public Sub New

See Also

Return Class
Return Overload
Lsa.Vmfg.Purchasing Namespace

Return Constructor (String)

Business Transaction Constructor

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public Return(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

Return Class

Return Overload

Lsa.Vmfg.Purchasing Namespace

Return.Return Methods

The Return type exposes the following members.

Methods

	Name	Description
	NewReturnDelSchedLineRow	Inserts a new row into the DEL_SCHED_LINE Data Table. See Return.
	NewreturnLineRow	Inserts a new row into the RETURN_LINE Data Table. See Return.
	NewReturnRow	Inserts a new row into the RETURN Data Table.
	NewReturnTraceRow	Inserts a new row into the TRACE Data Table. See Return.
	Prepare	Creates an empty dataset for the transaction. You must populate the dataset prior to saving the transaction.
	Save	Saves the transactions(s)

See Also

Return Class
Lsa.Vmfg.Purchasing Namespace

Return.NewReturnDelSchedLineRow Method

Inserts a new row into the DEL_SCHED_LINE Data Table.

See Return for the definition of the input data tables for this transaction.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewReturnDelSchedLineRow(
        string purcOrderID,
        int purcOrderLineNo,
        int delSchedLineNo
)
```

VB

```
Public Overridable Function NewReturnDelSchedLineRow (
        purcOrderID As String,
        purcOrderLineNo As Integer,
        delSchedLineNo As Integer
) As DataRow
```

Parameters

purcOrderID

Type: System.String

purcOrderLineNo

Type: System.Int32

delSchedLineNo

Type: System.Int32

Return Value

Type: **DataRow**

See Also

Return

Return Class

Lsa.Vmfg.Purchasing Namespace

Return.NewreturnLineRow Method

Inserts a new row into the RETURN_LINE Data Table.

See Return for the definition of the input data tables for this transaction.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewreturnLineRow(
        string purcOrderID,
        int purcOrderLineNo
)
```

VB

```
Public Overridable Function NewreturnLineRow (
        purcOrderID As String,
        purcOrderLineNo As Integer
) As DataRow
```

Parameters

purcOrderID

Type: System.String

purcOrderLineNo

Type: System.Int32

Return Value

Type: **DataRow**

See Also

Return

Return Class

Lsa.Vmfg.Purchasing Namespace

Return.NewReturnRow Method

Inserts a new row into the RETURN Data Table.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewReturnRow(
        string purcOrderID
)
```

VB

```
Public Overridable Function NewReturnRow (
        purcOrderID As String
) As DataRow
```

Parameters

purcOrderID

Type: System.String

Return Value

Type: **DataRow**

Remarks

Please refer to the written documentation for the schema of this data table.

See Also

Return Class

Lsa.Vmfg.Purchasing Namespace

Return.NewReturnTraceRow Method

Inserts a new row into the TRACE Data Table.

See Return for the definition of the input data tables for this transaction.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewReturnTraceRow(
        string purcOrderID,
        int purcOrderLineNo,
        string traceID
)
```

VB

```
Public Overridable Function NewReturnTraceRow (
        purcOrderID As String,
        purcOrderLineNo As Integer,
        traceID As String
) As DataRow
```

Parameters

purcOrderID

Type: System.String

purcOrderLineNo

Type: System.Int32

traceID

Type: System.String

Return Value

Type: **DataRow**

See Also

Return

Return Class

Lsa.Vmfg.Purchasing Namespace

Return.Prepare Method

Creates an empty dataset for the transaction. You must populate the dataset prior to saving the transaction.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Prepare()

VB
Public Overridable Sub Prepare

See Also

Return Class
Lsa.Vmfg.Purchasing Namespace

Return.Save Method

Saves the transactions(s)

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

Return Class
Lsa.Vmfg.Purchasing Namespace

Return

This transaction will create a new Purchase Receipt Return from an existing Purchase Order.

Namespace: Lsa.Vmfg.Purchasing

Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

DataSet name returned from Prepare: RETURN

Primary Key: PURC_ORDER_ID

Column Name	Type	Description
PURC_ORDER_ID	String	The ID of the Purchase Order being returned.
TRANSACTION_DATE	Date	Date of return transaction. Defaults to current date.
RECEIVER_ID	String	Unique ID for this Receiver. Will be automatically generated if left blank.
RETURN_ALL	Boolean	When this flag is set to true, the purchase order will be returned in full. When this feature is used, the sub-tables for this transaction are populated automatically. You cannot use this feature if the order has either a delivery schedule or parts requiring lot / serial number tracing.
REOPEN_ORDER	Boolean	When this flag is set to true, the Purchase Order will be reopened (status changed to Released).
REOPEN_LINKED_OPS	Boolean	When this flag is set to true, the Work Order Operations associated with the return will be reopened.
REOPEN_LINKED_REQS	String	When this flag is set to true, the Work Order Requirements associated with the return will be reopened.
USER_ID	String	The User ID of the person performing the transaction. Defaults to SYSADM.
SITE_ID	String	Site ID of the Purchase Order being returned. Defaults to site ID of the Purchase Order.

Sub-Table Name: RETURN_LINE

Primary Key: PURC_ORDER_ID, PURC_ORDER_LINE

This table is required, unless the header table is set to RETURN_ALL.

Column Name	Type	Description
PURC_ORDER_ID	String	The ID of the Purchase Order being returned. Must match the ID of the header table.
PURC_ORDER_LINE_NO	Integer	Line number of the order being returned.
USER_QTY	Decimal	The quantity being returned, in the receiver unit of measure.
STOCK_QTY	Decimal	
PIECE_COUNT	Integer	The number of pieces being returned. For piece tracked parts only. Leave blank for non-piece tracked parts.
LENGTH	Decimal	Length of pieces being returned. Required if Part is defined as piece tracked by length.
WIDTH	Decimal	Width of pieces being returned. Required if Part is defined as piece tracked by width.
HEIGHT	Decimal	Height of pieces being returned. Required if Part is defined as piece tracked by height.
LOCATION_ID	String	Optional. Defaults to the part's primary location ID.
WAREHOUSE_ID	String	Optional. If not specified, tries to locate the part's primary warehouse ID. If not found, uses the first valid warehouse found.

Sub-Table Name: DEL_SCHED_LINE

Primary Key: PURC_ORDER_ID, PURC_ORDER_LINE_NO, DEL_SCHED_LINE_NO

This sub-table is only applicable if the customer order line has a delivery schedule.

Column Name	Type	Description
PURC_ORDER_ID	String	The ID of the Purchase Order being returned. Must match the ID of the header and line tables.
PURC_ORDER_LINE_NO	Integer	Line number of the order being returned. Must match an existing line number from the line table.
DEL_SCHED_LINE_NO	Integer	The line number of the delivery schedule being returned.
USER_QTY	Decimal	The quantity being returned for this delivery schedule line.

Column Name	Type	Description
STOCK_QTY	Decimal	
PIECE_COUNT		The number of pieces being returned. For piece tracked parts only. Leave blank for non-piece tracked parts.

Sub-Table Name: TRACE

Primary Key: PURC_ORDER_ID, PURC_ORDER_LINE_NO, TRACE_ID

The TRACE_INFO sub-recordset may or may not be required, depending on the Part's trace profile.

Column Name	Type	Description
PURC_ORDER_ID	String	The ID of the Purchase Order being returned. Must match the ID of the header and line tables.
PURC_ORDER_LINE_NO	Integer	Line number of the order being returned. Must match an existing line number from the line table.
TRACE_ID	String	Trace ID. Lot or serial number for the parts being reported. If the part's trace profile supports auto numbering, and you wish to have the Trace IDs auto numbered, you must set the TRACE_ID values to the format "<n>" where n is a unique integer.
EXPIRATION_DATE	Date	Expiration date. Determines shelf life of lot. Optional.
QTY	Decimal	Quantity of transaction associated directly with this trace ID. The sum of all trace detail QTY fields must equal the total returned quantity for the associated return line item.
COMMENTS	String	Optional user comments on specific lot or serial number.
OWNER_ID	String	Owner ID. Optional.

See Also

Return Class

Return.NewReturnDelSchedLineRow

Return.NewreturnLineRow

Return.NewReturnRow

Return.NewReturnTraceRow
Lsa.Vmfg.Purchasing Namespace

Service Class

Maintain Services.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessDocument
          Lsa.Vmfg.Purchasing.Service

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class Service : BusinessDocument
```

VB

```
<SerializableAttribute>
Public Class Service
        Inherits BusinessDocument
```

The **Service** type exposes the following members.

Constructors

	Name	Description
	Service()	Business Document Constructor
	Service(String)	Business Docuement Constructor

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Service rows based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Service rows based on search criteria. Number of rows returned is limited by the value of maxRecords.
	Exists	Determines if a specific Service exists.
	Find	Retrieves a specific Service row from the database. Only the top-level table (SERVICE) is returned.
	Load(String)	Loads a specific Service.
	Load(Stream, String)	Load from stream and rename using new key.
	NewServiceBinaryRow	Inserts a new row into the SERVICE_BINARY table. Only binary type = "D" (long text) is supported.
	NewServiceRow	Inserts a new row into the SERVICE table.
	NewServiceSiteRow	Inserts a new row into the SERVICE_SITE table.
	NewServiceUnitConvRow	Inserts a new row into the SERVICE_UNIT_CONV table.
	Save()	Saves all prviously loaded Services to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

Lsa.Vmfg.Purchasing Namespace

Service Constructor

Overload List

	Name	Description
	Service()	Business Document Constructor
	Service(String)	Business Docuement Constructor

See Also

Service Class
Lsa.Vmfg.Purchasing Namespace

Service Constructor

Business Document Constructor

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public Service()

VB
Public Sub New

See Also

Service Class
Service Overload
Lsa.Vmfg.Purchasing Namespace

Service Constructor (String)

Business Docuement Constructor

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public Service(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

Service Class

Service Overload

Lsa.Vmfg.Purchasing Namespace

Service.Service Methods

The Service type exposes the following members.

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Service rows based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Service rows based on search criteria. Number of rows returned is limited by the value of maxRecords.
	Exists	Determines if a specific Service exists.
	Find	Retrieves a specific Service row from the database. Only the top-level table (SERVICE) is returned.
	Load(String)	Loads a specific Service.
	Load(Stream, String)	Load from stream and rename using new key.
	NewServiceBinaryRow	Inserts a new row into the SERVICE_BINARY table. Only binary type = "D" (long text) is supported.
	NewServiceRow	Inserts a new row into the SERVICE table.
	NewServiceSiteRow	Inserts a new row into the SERVICE_SITE table.
	NewServiceUnitConvRow	Inserts a new row into the SERVICE_UNIT_CONV table.
	Save()	Saves all prviously loaded Services to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

Service Class

Lsa.Vmfg.Purchasing Namespace

Service.Browse Method

Overload List

	Name	Description
	Browse(String, String, String)	Retrieve Service rows based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Service rows based on search criteria. Number of rows returned is limited by the value of maxRecords.

See Also

Service Class

Lsa.Vmfg.Purchasing Namespace

Service.Browse Method (String, String, String)

Retrieve Service rows based on search criteria.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

Return Value

Type: **DataSet**

See Also

Service Class

Browse Overload

Lsa.Vmfg.Purchasing Namespace

Service.Browse Method (String, String, String, Int32, Int32)

Retrieve Service rows based on search criteria. Number of rows returned is limited by the value of maxRecords.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns,
        int startRecord,
        int maxRecords
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String,
        startRecord As Integer,
        maxRecords As Integer
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

startRecord

Type: System.Int32

maxRecords

Type: System.Int32

Return Value

Type: **DataSet**

See Also

Service Class
Browse Overload
Lsa.Vmfg.Purchasing Namespace

Service.Exists Method

Determines if a specific Service exists.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual bool Exists(
        string serviceID
)
```

VB

```
Public Overridable Function Exists (
        serviceID As String
) As Boolean
```

Parameters

serviceID

Type: System.String

Return Value

Type: Boolean

See Also

Service Class

Lsa.Vmfg.Purchasing Namespace

Service.Find Method

Retrieves a specific Service row from the database. Only the top-level table (SERVICE) is returned.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Find(
        string serviceID
)
```

VB

```
Public Overridable Sub Find (
        serviceID As String
)
```

Parameters

serviceID

Type: System.String

See Also

Service Class

Lsa.Vmfg.Purchasing Namespace

Service.Load Method

Overload List

	Name	Description
	Load(String)	Loads a specific Service.
	Load(Stream, String)	Load from stream and rename using new key.

See Also

Service Class
Lsa.Vmfg.Purchasing Namespace

Service.Load Method (String)

Loads a specific Service.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string serviceID
)
```

VB

```
Public Overridable Sub Load (
        serviceID As String
)
```

Parameters

serviceID

Type: System.String

See Also

Service Class

Load Overload

Lsa.Vmfg.Purchasing Namespace

Service.Load Method (Stream, String)

Load from stream and rename using new key.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        Stream stream,
        string serviceID
)
```

VB

```
Public Overridable Sub Load (
        stream As Stream,
        serviceID As String
)
```

Parameters

stream

Type: System.IO.Stream

serviceID

Type: System.String

See Also

Service Class

Load Overload

Lsa.Vmfg.Purchasing Namespace

Service.NewServiceBinaryRow Method

Inserts a new row into the SERVICE_BINARY table. Only binary type = "D" (long text) is supported.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewServiceBinaryRow(
        string serviceID,
        string binaryType
)
```

VB

```
Public Overridable Function NewServiceBinaryRow (
        serviceID As String,
        binaryType As String
) As DataRow
```

Parameters

serviceID

Type: System.String

binaryType

Type: System.String

Return Value

Type: **DataRow**

See Also

Service Class

Lsa.Vmfg.Purchasing Namespace

Service.NewServiceRow Method

Inserts a new row into the SERVICE table.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewServiceRow(
        string serviceID
)
```

VB

```
Public Overridable Function NewServiceRow (
        serviceID As String
) As DataRow
```

Parameters

serviceID

Type: System.String

Return Value

Type: **DataRow**

See Also

Service Class

Lsa.Vmfg.Purchasing Namespace

Service.NewServiceSiteRow Method

Inserts a new row into the SERVICE_SITE table.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewServiceSiteRow(
        string serviceID,
        string siteID
)
```

VB

```
Public Overridable Function NewServiceSiteRow (
        serviceID As String,
        siteID As String
) As DataRow
```

Parameters

serviceID

Type: System.String

siteID

Type: System.String

Return Value

Type: **DataRow**

See Also

Service Class

Lsa.Vmfg.Purchasing Namespace

Service.NewServiceUnitConvRow Method

Inserts a new row into the SERVICE_UNIT_CONV table.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewServiceUnitConvRow(
        string serviceID,
        string fromUM,
        string toUM
)
```

VB

```
Public Overridable Function NewServiceUnitConvRow (
        serviceID As String,
        fromUM As String,
        toUM As String
) As DataRow
```

Parameters

serviceID

Type: System.String

fromUM

Type: System.String

toUM

Type: System.String

Return Value

Type: **DataRow**

See Also

Service Class

Lsa.Vmfg.Purchasing Namespace

Service.Save Method

Overload List

	Name	Description
	Save()	Saves all prviously loaded Services to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

Service Class
Lsa.Vmfg.Purchasing Namespace

Service.Save Method

Saves all prviously loaded Services to the database.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

Service Class
Save Overload
Lsa.Vmfg.Purchasing Namespace

Service.Save Method (Stream)

Save current state of data set to stream.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Save(
        Stream stream
)
```

VB

```
Public Overridable Sub Save (
        stream As Stream
)
```

Parameters

stream

Type: System.IO.Stream

See Also

Service Class

Save Overload

Lsa.Vmfg.Purchasing Namespace

ServiceDispatch Class

Service Dispatch Transaction.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessTransaction
          Lsa.Vmfg.Purchasing.ServiceDispatch

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class ServiceDispatch : BusinessTransaction
```

VB

```
<SerializableAttribute>
Public Class ServiceDispatch
        Inherits BusinessTransaction
```

The **ServiceDispatch** type exposes the following members.

Constructors

	Name	Description
	ServiceDispatch()	Business Transaction Constructor.
	ServiceDispatch(String)	Business Transaction Constructor.

Methods

	Name	Description
	NewServiceDispatchLineRow	Inserts a new row into the DISPATCH_LINE Data Table. See ServiceDispatch.
	NewServiceDispatchRow	Inserts a new row into the DISPATCH Data Table. See ServiceDispatch.
	Prepare	Creates an empty dataset for the transaction. You must populate the dataset prior to saving the transaction.
	Save	Saves the transaction(s).

Transaction

	Name	Data set returned by Prepare	Description
	ServiceDispatch	DISPATCH	This transaction will save a Service Dispatch record and all related transactions to cause parts to be dispatched to outside services accordingly. Please note that it is hierarchical. Each service dispatch header has one to many service dispatch lines.

See Also

Lsa.Vmfg.Purchasing Namespace

ServiceDispatch Constructor

Overload List

	Name	Description
	ServiceDispatch()	Business Transaction Constructor.
	ServiceDispatch(String)	Business Transaction Constructor.

See Also

ServiceDispatch Class
Lsa.Vmfg.Purchasing Namespace

ServiceDispatch Constructor

Business Transaction Constructor.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public ServiceDispatch()

VB
Public Sub New

See Also

ServiceDispatch Class
ServiceDispatch Overload
Lsa.Vmfg.Purchasing Namespace

ServiceDispatch Constructor (String)

Business Transaction Constructor.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public ServiceDispatch(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

ServiceDispatch Class

ServiceDispatch Overload

Lsa.Vmfg.Purchasing Namespace

ServiceDispatch.ServiceDispatch Methods

The ServiceDispatch type exposes the following members.

Methods

	Name	Description
	NewServiceDispatchLineRow	Inserts a new row into the DISPATCH_LINE Data Table. See ServiceDispatch.
	NewServiceDispatchRow	Inserts a new row into the DISPATCH Data Table. See ServiceDispatch.
	Prepare	Creates an empty dataset for the transaction. You must populate the dataset prior to saving the transaction.
	Save	Saves the transaction(s).

See Also

ServiceDispatch Class

Lsa.Vmfg.Purchasing Namespace

ServiceDispatch.NewServiceDispatchLineRow Method

Inserts a new row into the DISPATCH_LINE Data Table.

See ServiceDispatch for the definition of the input data tables for this transaction.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewServiceDispatchLineRow(
        string purcOrderID,
        int purcOrderLineNo
)
```

VB

```
Public Overridable Function NewServiceDispatchLineRow (
        purcOrderID As String,
        purcOrderLineNo As Integer
) As DataRow
```

Parameters

purcOrderID

Type: System.String

purcOrderLineNo

Type: System.Int32

Return Value

Type: **DataRow**

See Also

ServiceDispatch

ServiceDispatch Class

Lsa.Vmfg.Purchasing Namespace

ServiceDispatch.NewServiceDispatchRow Method

Inserts a new row into the DISPATCH Data Table.

See ServiceDispatch for the definition of the input data tables for this transaction.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewServiceDispatchRow(
        string purcOrderID
)
```

VB

```
Public Overridable Function NewServiceDispatchRow (
        purcOrderID As String
) As DataRow
```

Parameters

purcOrderID

Type: System.String

Return Value

Type: **DataRow**

See Also

ServiceDispatch

ServiceDispatch Class

Lsa.Vmfg.Purchasing Namespace

ServiceDispatch.Prepare Method

Creates an empty dataset for the transaction. You must populate the dataset prior to saving the transaction.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Prepare()

VB
Public Overridable Sub Prepare

See Also

ServiceDispatch Class
Lsa.Vmfg.Purchasing Namespace

ServiceDispatch.Save Method

Saves the transaction(s).

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

ServiceDispatch Class
Lsa.Vmfg.Purchasing Namespace

ServiceDispatch

This transaction will save a Service Dispatch record and all related transactions to cause parts to be dispatched to outside services accordingly. Please note that it is hierarchical. Each service dispatch header has one to many service dispatch lines.

Namespace: Lsa.Vmfg.Purchasing

Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Dataset name returned from Prepare: DISPATCH

Primary Key: PURC_ORDER_ID

Column Name	Type	Description
TRANSACTION_DATE	Date	Date of transaction. Defaults to current date.
PURC_ORDER_ID	String	Purchase Order ID being dispatched. Required.
DISPATCH_ID	String	Dispatch ID of dispatch being created. If not provided, dispatch will be automatically numbered.
SHIP_TO_ADDR_NO	Integer	Ship to address. Optional. Defaults to the associated purchase order's dispatch address.
SHIP_FROM_ADDR_NO	Integer	Ship from address. Optional. Defaults to the associated purchase order's ship to address.
FREE_ON_BOARD	String	Free on board code for the dispatch. Optional, not validated. Defaults to the associated purchase order's free on board code.
SHIP_VIA	String	Shipping method for the dispatch. Optional, not validated. Defaults to the associated purchase order's ship via code.
SHIP_REASON_CD	String	Ship reason code. Optional.
CARRIER_ID	String	Carrier ID. Optional.
FREIGHT_TERMS	String	Freight terms code. Optional.
SITE_ID	String	The Site ID of the dispatch. If not provided, defaults to associated purchase order's site ID.
USER_ID	String	The User ID of the person performing the transaction. Defaults to SYSADM.

Sub-Table Name: DISPATCH_LINE

Primary Key: PURC_ORDER_ID, PURC_ORDER_LINE_NO

This table is required.

Column Name	Type	Description
PURC_ORDER_ID	String	Purchase Order being dispatched. This value must match an existing value in the DISPATCH table defined above.
PURC_ORDER_LINE_NO	Integer	The purchase order line number being dispatched. Required.
LINE_NO	Integer	Dispatch line number. Line numbers are set automatically during the transaction.
SITE_ID	String	The Site ID associated with the order line. Optional. Defaults to the purchase order Site ID if blank.
USER_QTY	Decimal	User dispatch quantity. Required.
USAGE_QTY	Decimal	Usage quantity of the dispatch in the unit of measure of the service being dispatched. Will default to USER_QTY if the purchase order unit of measure and service unit of measure are the same.
ACT_FREIGHT	Decimal	Actual freight of the dispatch. Optional. Defaults to zero if not provided.
SHIPPING_WEIGHT	Decimal	Shipping weight of the dispatch. Optional.
WEIGHT_UM	String	Shipping weight unit of measure. Optional.
SHIPPING_UM	String	Shipping unit of measure. Optional.
WORKORDER_BASE_ID	String	Work Order link Base ID. Optional.
WORKORDER_LOT_ID	String	Work Order link Lot ID. Optional.
WORKORDER_SPLIT_ID	String	Work Order link Split ID. Optional.
WORKORDER_SUB_ID	String	Work Order link Sub ID (leg/detail). Optional.
OPERATION_SEQ_NO	Integer	Operation sequence number of the linked work order. Optional.

See Also

ServiceDispatch Class
ServiceDispatch.NewServiceDispatchLineRow
ServiceDispatch.NewServiceDispatchRow
Lsa.Vmfg.Purchasing Namespace

VendBankAccount Class

Maintain Vendor Bank Accounts.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessDocument
          Lsa.Vmfg.Purchasing.VendBankAccount

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class VendBankAccount : BusinessDocument
```

VB

```
<SerializableAttribute>
Public Class VendBankAccount
        Inherits BusinessDocument
```

The **VendBankAccount** type exposes the following members.

Constructors

	Name	Description
	VendBankAccount()	Business Document Constructor
	VendBankAccount(String)	Business Document Constructor

Methods

	Name	Description
	Browse(String, String, String)	Retrieves Vendor Bank Accounts based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieves Vendor Bank Accounts based on search criteria. Number of rows returned is limited by the value of maxRecords.
	Exists	Determines if a specific Vendor Bank Account exists.
	Find	Retrieves a specific Vendor Bank Account.
	Load()	Loads all Vendor Bank Accounts.
	Load(String)	Loads a specific Vendor Bank Account.
	Load(Stream, String)	Load from stream and rename using new key.
	NewVendBankAccountRow	Inserts a new row into the VEND_BANK_ACCOUNT data table.
	Save()	Saves all previously loaded Vendor Bank Account(s) to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

Lsa.Vmfg.Purchasing Namespace

VendBankAccount Constructor

Overload List

	Name	Description
	VendBankAccount()	Business Document Constructor
	VendBankAccount(String)	Business Document Constructor

See Also

VendBankAccount Class
Lsa.Vmfg.Purchasing Namespace

VendBankAccount Constructor

Business Document Constructor

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public VendBankAccount()

VB
Public Sub New

See Also

VendBankAccount Class
VendBankAccount Overload
Lsa.Vmfg.Purchasing Namespace

VendBankAccount Constructor (String)

Business Document Constructor

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public VendBankAccount(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

VendBankAccount Class

VendBankAccount Overload

Lsa.Vmfg.Purchasing Namespace

VendBankAccount.VendBankAccount Methods

The VendBankAccount type exposes the following members.

Methods

	Name	Description
	Browse(String, String, String)	Retrieves Vendor Bank Accounts based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieves Vendor Bank Accounts based on search criteria. Number of rows returned is limited by the value of maxRecords.
	Exists	Determines if a specific Vendor Bank Account exists.
	Find	Retrieves a specific Vendor Bank Account.
	Load()	Loads all Vendor Bank Accounts.
	Load(String)	Loads a specific Vendor Bank Account.
	Load(Stream, String)	Load from stream and rename using new key.
	NewVendBankAccountRow	Inserts a new row into the VEND_BANK_ACCOUNT data table.
	Save()	Saves all previously loaded Vendor Bank Account(s) to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

VendBankAccount Class

Lsa.Vmfg.Purchasing Namespace

VendBankAccount.Browse Method

Overload List

	Name	Description
	Browse(String, String, String)	Retrieves Vendor Bank Accounts based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieves Vendor Bank Accounts based on search criteria. Number of rows returned is limited by the value of maxRecords.

See Also

VendBankAccount Class

Lsa.Vmfg.Purchasing Namespace

VendBankAccount.Browse Method (String, String, String)

Retrieves Vendor Bank Accounts based on search criteria.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

Return Value

Type: **DataSet**

See Also

VendBankAccount Class

Browse Overload

Lsa.Vmfg.Purchasing Namespace

VendBankAccount.Browse Method (String, String, String, Int32, Int32)

Retrieves Vendor Bank Accounts based on search criteria. Number of rows returned is limited by the value of maxRecords.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns,
        int startRecord,
        int maxRecords
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String,
        startRecord As Integer,
        maxRecords As Integer
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

startRecord

Type: System.Int32

maxRecords

Type: System.Int32

Return Value

Type: **DataSet**

See Also

VendBankAccount Class
Browse Overload
Lsa.Vmfg.Purchasing Namespace

VendBankAccount.Exists Method

Determines if a specific Vendor Bank Account exists.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual bool Exists(
        string id
)
```

VB

```
Public Overridable Function Exists (
        id As String
) As Boolean
```

Parameters

id

Type: System.String

Return Value

Type: Boolean

See Also

VendBankAccount Class

Lsa.Vmfg.Purchasing Namespace

VendBankAccount.Find Method

Retrieves a specific Vendor Bank Account.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Find(
        string id
)
```

VB

```
Public Overridable Sub Find (
        id As String
)
```

Parameters

id

Type: System.String

See Also

VendBankAccount Class

Lsa.Vmfg.Purchasing Namespace

VendBankAccount.Load Method

Overload List

	Name	Description
	Load()	Loads all Vendor Bank Accounts.
	Load(String)	Loads a specific Vendor Bank Account.
	Load(Stream, String)	Load from stream and rename using new key.

See Also

VendBankAccount Class
Lsa.Vmfg.Purchasing Namespace

VendBankAccount.Load Method

Loads all Vendor Bank Accounts.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Load()

VB
Public Overridable Sub Load

See Also

VendBankAccount Class
Load Overload
Lsa.Vmfg.Purchasing Namespace

VendBankAccount.Load Method (String)

Loads a specific Vendor Bank Account.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string id
)
```

VB

```
Public Overridable Sub Load (
        id As String
)
```

Parameters

id

Type: System.String

See Also

VendBankAccount Class

Load Overload

Lsa.Vmfg.Purchasing Namespace

VendBankAccount.Load Method (Stream, String)

Load from stream and rename using new key.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        Stream stream,
        string id
)
```

VB

```
Public Overridable Sub Load (
        stream As Stream,
        id As String
)
```

Parameters

stream

Type: System.IO.Stream

id

Type: System.String

See Also

VendBankAccount Class

Load Overload

Lsa.Vmfg.Purchasing Namespace

VendBankAccount.NewVendBankAccountRow Method

Inserts a new row into the VEND_BANK_ACCOUNT data table.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewVendBankAccountRow(
        string id
)
```

VB

```
Public Overridable Function NewVendBankAccountRow (
        id As String
) As DataRow
```

Parameters

id

Type: System.String

Return Value

Type: **DataRow**

See Also

VendBankAccount Class

Lsa.Vmfg.Purchasing Namespace

VendBankAccount.Save Method

Overload List

	Name	Description
	Save()	Saves all previously loaded Vendor Bank Account(s) to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

VendBankAccount Class
Lsa.Vmfg.Purchasing Namespace

VendBankAccount.Save Method

Saves all previously loaded Vendor Bank Account(s) to the database.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

VendBankAccount Class
Save Overload
Lsa.Vmfg.Purchasing Namespace

VendBankAccount.Save Method (Stream)

Save current state of data set to stream.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Save(
        Stream stream
)
```

VB

```
Public Overridable Sub Save (
        stream As Stream
)
```

Parameters

stream

Type: System.IO.Stream

See Also

VendBankAccount Class

Save Overload

Lsa.Vmfg.Purchasing Namespace

Vendor Class

Maintain Vendors.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessDocument
          Lsa.Vmfg.Purchasing.Vendor

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class Vendor : BusinessDocument
```

VB

```
<SerializableAttribute>
Public Class Vendor
        Inherits BusinessDocument
```

The **Vendor** type exposes the following members.

Constructors

	Name	Description
	Vendor()	Business Document Constructor
	Vendor(String)	Business Document Constructor

Methods

	Name	Description
	Browse(String, String, String)	Retrieves Vendors based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieves Vendors based on search criteria. Number of rows returned is limited based on the value of maxRecords.
	Exists	Determines if a specific Vendor exists.
	Find	Retrieves a specific Vendor.. Only the top-level table (VENDOR) is returned.
	Load(String)	Loads a specific Vendor.
	Load(Stream, String)	Load from stream and rename using new key.
	NewVendContactRow	Inserts a new row into the VEND_CONTACT table, assigning the next available contact number. Note: Use this method to link an existing contact from your master contact list to this vendor. To add a new contact to your master contact list and link it to this vender, use the NewVendorContactRow method.
	NewVendorAddressRow	Inserts a new row into the VENDOR_ADDRESS data table.
	NewVendorBinaryRow	Inserts a new row into the VENDOR_BINARY table. Only binary type = "D" (long text) is supported.
	NewVendorContactRow	Inserts a new row into the VENDOR_CONTACT table with the next contact number available. Note: Use this method to add a new contact to your master contact list which in turn will be linked to this vendor. To link an existing contact ID from your contact master to this vendor, use the NewVendContactRow method.
	NewVendorPartRow	Inserts a new row into the VENDOR_PART data table.
	NewVendorQuoteRow(String, String)	Inserts a new row into the VENDOR_QUOTE data table.
	NewVendorQuoteRow(String, String, String)	Inserts a new row into the VENDOR_QUOTE data table.
	NewVendorQuoteRow(String, String, String, String)	Inserts a new row into the VENDOR_QUOTE data table.
	NewVendorRemitAddrRow	Inserts a new row into the VENDOR_REMIT_ADDR data table.

	NewVendorRow(String)	Inserts a new row into the VENDOR data table.
	NewVendorRow(String, String, String)	Inserts a new row into the VENDOR data table for a specified Entity and Currency.
	NewVendorServiceRow	Inserts a new row into the VENDOR_SERVICE data table.
	Save()	Saves all previously loaded Vendors to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

Lsa.Vmfg.Purchasing Namespace

Vendor Constructor

Overload List

	Name	Description
	Vendor()	Business Document Constructor
	Vendor(String)	Business Document Constructor

See Also

Vendor Class
Lsa.Vmfg.Purchasing Namespace

Vendor Constructor

Business Document Constructor

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public Vendor()

VB
Public Sub New

See Also

Vendor Class
Vendor Overload
Lsa.Vmfg.Purchasing Namespace

Vendor Constructor (String)

Business Document Constructor

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public Vendor(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

Vendor Class

Vendor Overload

Lsa.Vmfg.Purchasing Namespace

Vendor.Vendor Methods

The Vendor type exposes the following members.

Methods

	Name	Description
	Browse(String, String, String)	Retrieves Vendors based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieves Vendors based on search criteria. Number of rows returned is limited based on the value of maxRecords.
	Exists	Determines if a specific Vendor exists.
	Find	Retrieves a specific Vendor.. Only the top-level table (VENDOR) is returned.
	Load(String)	Loads a specific Vendor.
	Load(Stream, String)	Load from stream and rename using new key.
	NewVendContactRow	Inserts a new row into the VEND_CONTACT table, assigning the next available contact number. Note: Use this method to link an existing contact from your master contact list to this vendor. To add a new contact to your master contact list and link it to this vender, use the NewVendorContactRow method.
	NewVendorAddressRow	Inserts a new row into the VENDOR_ADDRESS data table.
	NewVendorBinaryRow	Inserts a new row into the VENDOR_BINARY table. Only binary type = "D" (long text) is supported.
	NewVendorContactRow	Inserts a new row into the VENDOR_CONTACT table with the next contact number available. Note: Use this method to add a new contact to your master contact list which in turn will be linked to this vendor. To link an existing contact ID from your contact master to this vendor, use the NewVendContactRow method.
	NewVendorPartRow	Inserts a new row into the VENDOR_PART data table.
	NewVendorQuoteRow(String, String)	Inserts a new row into the VENDOR_QUOTE data table.
	NewVendorQuoteRow(String, String, String)	Inserts a new row into the VENDOR_QUOTE data table.

	NewVendorQuoteRow(String, String, String, String)	Inserts a new row into the VENDOR_QUOTE data table.
	NewVendorRemitAddrRow	Inserts a new row into the VENDOR_REMIT_ADDR data table.
	NewVendorRow(String)	Inserts a new row into the VENDOR data table.
	NewVendorRow(String, String, String)	Inserts a new row into the VENDOR data table for a specified Entity and Currency.
	NewVendorServiceRow	Inserts a new row into the VENDOR_SERVICE data table.
	Save()	Saves all previously loaded Vendors to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

Vendor Class

Lsa.Vmfg.Purchasing Namespace

Vendor.Browse Method

Overload List

	Name	Description
	Browse(String, String, String)	Retrieves Vendors based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieves Vendors based on search criteria. Number of rows returned is limited based on the value of maxRecords.

See Also

Vendor Class

Lsa.Vmfg.Purchasing Namespace

Vendor.Browse Method (String, String, String)

Retrieves Vendors based on search criteria.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

Return Value

Type: **DataSet**

See Also

Vendor Class

Browse Overload

Lsa.Vmfg.Purchasing Namespace

Vendor.Browse Method (String, String, String, Int32, Int32)

Retrieves Vendors based on search criteria. Number of rows returned is limited based on the value of maxRecords.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns,
        int startRecord,
        int maxRecords
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String,
        startRecord As Integer,
        maxRecords As Integer
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

startRecord

Type: System.Int32

maxRecords

Type: System.Int32

Return Value

Type: **DataSet**

See Also

Vendor Class
Browse Overload
Lsa.Vmfg.Purchasing Namespace

Vendor.Exists Method

Determines if a specific Vendor exists.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual bool Exists(
        string vendorID
)
```

VB

```
Public Overridable Function Exists (
        vendorID As String
) As Boolean
```

Parameters

vendorID

Type: System.String

Return Value

Type: Boolean

See Also

Vendor Class

Lsa.Vmfg.Purchasing Namespace

Vendor.Find Method

Retrieves a specific Vendor.. Only the top-level table (VENDOR) is returned.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Find(
        string vendorID
)
```

VB

```
Public Overridable Sub Find (
        vendorID As String
)
```

Parameters

vendorID

Type: System.String

See Also

Vendor Class

Lsa.Vmfg.Purchasing Namespace

Vendor.Load Method

Overload List

	Name	Description
	Load(String)	Loads a specific Vendor.
	Load(Stream, String)	Load from stream and rename using new key.

See Also

Vendor Class
Lsa.Vmfg.Purchasing Namespace

Vendor.Load Method (String)

Loads a specific Vendor.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string vendorID
)
```

VB

```
Public Overridable Sub Load (
        vendorID As String
)
```

Parameters

vendorID

Type: System.String

See Also

Vendor Class

Load Overload

Lsa.Vmfg.Purchasing Namespace

Vendor.Load Method (Stream, String)

Load from stream and rename using new key.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        Stream stream,
        string vendorID
)
```

VB

```
Public Overridable Sub Load (
        stream As Stream,
        vendorID As String
)
```

Parameters

stream

Type: System.IO.Stream

vendorID

Type: System.String

See Also

Vendor Class

Load Overload

Lsa.Vmfg.Purchasing Namespace

Vendor.NewVendContactRow Method

Inserts a new row into the VEND_CONTACT table, assigning the next available contact number. Note: Use this method to link an existing contact from your master contact list to this vendor. To add a new contact to your master contact list and link it to this vender, use the NewVendorContactRow method.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewVendContactRow(
        string contactID,
        string vendorID
)
```

VB

```
Public Overridable Function NewVendContactRow (
        contactID As String,
        vendorID As String
) As DataRow
```

Parameters

contactID

Type: System.String

vendorID

Type: System.String

Return Value

Type: **DataRow**

See Also

Vendor Class

Lsa.Vmfg.Purchasing Namespace

Vendor.NewVendorAddressRow Method

Inserts a new row into the VENDOR_ADDRESS data table.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewVendorAddressRow(
        string vendorID,
        int addrNo
)
```

VB

```
Public Overridable Function NewVendorAddressRow (
        vendorID As String,
        addrNo As Integer
) As DataRow
```

Parameters

vendorID

Type: System.String

addrNo

Type: System.Int32

Return Value

Type: **DataRow**

See Also

Vendor Class

Lsa.Vmfg.Purchasing Namespace

Vendor.NewVendorBinaryRow Method

Inserts a new row into the VENDOR_BINARY table. Only binary type = "D" (long text) is supported.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewVendorBinaryRow(
        string vendorID,
        string binaryType
)
```

VB

```
Public Overridable Function NewVendorBinaryRow (
        vendorID As String,
        binaryType As String
) As DataRow
```

Parameters

vendorID

Type: System.String

binaryType

Type: System.String

Return Value

Type: **DataRow**

See Also

Vendor Class

Lsa.Vmfg.Purchasing Namespace

Vendor.NewVendorContactRow Method

Inserts a new row into the VENDOR_CONTACT table with the next contact number available. Note: Use this method to add a new contact to your master contact list which in turn will be linked to this vendor. To link an existing contact ID from your contact master to this vendor, use the NewVendContactRow method.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewVendorContactRow(
        string vendorID
)
```

VB

```
Public Overridable Function NewVendorContactRow (
        vendorID As String
) As DataRow
```

Parameters

vendorID

Type: System.String

Return Value

Type: **DataRow**

See Also

Vendor Class

Lsa.Vmfg.Purchasing Namespace

Vendor.NewVendorPartRow Method

Inserts a new row into the VENDOR_PART data table.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewVendorPartRow(
        string vendorID,
        string partID
)
```

VB

```
Public Overridable Function NewVendorPartRow (
        vendorID As String,
        partID As String
) As DataRow
```

Parameters

vendorID

Type: System.String

partID

Type: System.String

Return Value

Type: **DataRow**

See Also

Vendor Class

Lsa.Vmfg.Purchasing Namespace

Vendor.NewVendorQuoteRow Method

Overload List

	Name	Description
	NewVendorQuoteRow(String, String)	Inserts a new row into the VENDOR_QUOTE data table.
	NewVendorQuoteRow(String, String, String)	Inserts a new row into the VENDOR_QUOTE data table.
	NewVendorQuoteRow(String, String, String, String)	Inserts a new row into the VENDOR_QUOTE data table.

See Also

Vendor Class

Lsa.Vmfg.Purchasing Namespace

Vendor.NewVendorQuoteRow Method (String, String)

Inserts a new row into the VENDOR_QUOTE data table.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewVendorQuoteRow(
        string vendorID,
        string vendorPartID
)
```

VB

```
Public Overridable Function NewVendorQuoteRow (
        vendorID As String,
        vendorPartID As String
) As DataRow
```

Parameters

vendorID

Type: System.String

vendorPartID

Type: System.String

Return Value

Type: **DataRow**

See Also

Vendor Class

NewVendorQuoteRow Overload

Lsa.Vmfg.Purchasing Namespace

Vendor.NewVendorQuoteRow Method (String, String, String)

Inserts a new row into the VENDOR_QUOTE data table.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewVendorQuoteRow(
        string vendorID,
        string vendorPartID,
        string mfgName
)
```

VB

```
Public Overridable Function NewVendorQuoteRow (
        vendorID As String,
        vendorPartID As String,
        mfgName As String
) As DataRow
```

Parameters

vendorID

Type: System.String

vendorPartID

Type: System.String

mfgName

Type: System.String

Return Value

Type: **DataRow**

See Also

Vendor Class

NewVendorQuoteRow Overload

Lsa.Vmfg.Purchasing Namespace

Vendor.NewVendorQuoteRow Method (String, String, String, String)

Inserts a new row into the VENDOR_QUOTE data table.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewVendorQuoteRow(
        string vendorID,
        string vendorPartID,
        string mfgName,
        string mfgPartID
)
```

VB

```
Public Overridable Function NewVendorQuoteRow (
        vendorID As String,
        vendorPartID As String,
        mfgName As String,
        mfgPartID As String
) As DataRow
```

Parameters

vendorID

Type: System.String

vendorPartID

Type: System.String

mfgName

Type: System.String

mfgPartID

Type: System.String

Return Value

Type: **DataRow**

See Also

Vendor Class
NewVendorQuoteRow Overload
Lsa.Vmfg.Purchasing Namespace

Vendor.NewVendorRemitAddrRow Method

Inserts a new row into the VENDOR_REMIT_ADDR data table.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewVendorRemitAddrRow(
        string vendorID,
        int addrNo
)
```

VB

```
Public Overridable Function NewVendorRemitAddrRow (
        vendorID As String,
        addrNo As Integer
) As DataRow
```

Parameters

vendorID

Type: System.String

addrNo

Type: System.Int32

Return Value

Type: **DataRow**

See Also

Vendor Class

Lsa.Vmfg.Purchasing Namespace

Vendor.NewVendorRow Method

Overload List

	Name	Description
	NewVendorRow(String)	Inserts a new row into the VENDOR data table.
	NewVendorRow(String, String, String)	Inserts a new row into the VENDOR data table for a specified Entity and Currency.

See Also

Vendor Class

Lsa.Vmfg.Purchasing Namespace

Vendor.NewVendorRow Method (String)

Inserts a new row into the VENDOR data table.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewVendorRow(
        string vendorID
)
```

VB

```
Public Overridable Function NewVendorRow (
        vendorID As String
) As DataRow
```

Parameters

vendorID

Type: System.String

Return Value

Type: **DataRow**

See Also

Vendor Class

NewVendorRow Overload

Lsa.Vmfg.Purchasing Namespace

Vendor.NewVendorRow Method (String, String, String)

Inserts a new row into the VENDOR data table for a specified Entity and Currency.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewVendorRow(
        string vendorID,
        string entityID,
        string currencyID
)
```

VB

```
Public Overridable Function NewVendorRow (
        vendorID As String,
        entityID As String,
        currencyID As String
) As DataRow
```

Parameters

vendorID

Type: System.String

entityID

Type: System.String

currencyID

Type: System.String

Return Value

Type: **DataRow**

See Also

Vendor Class

NewVendorRow Overload

Lsa.Vmfg.Purchasing Namespace

Vendor.NewVendorServiceRow Method

Inserts a new row into the VENDOR_SERVICE data table.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewVendorServiceRow(
        string vendorID,
        string serviceID
)
```

VB

```
Public Overridable Function NewVendorServiceRow (
        vendorID As String,
        serviceID As String
) As DataRow
```

Parameters

vendorID

Type: System.String

serviceID

Type: System.String

Return Value

Type: **DataRow**

See Also

Vendor Class

Lsa.Vmfg.Purchasing Namespace

Vendor.Save Method

Overload List

	Name	Description
	Save()	Saves all previously loaded Vendors to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

Vendor Class
Lsa.Vmfg.Purchasing Namespace

Vendor.Save Method

Saves all previously loaded Vendors to the database.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

Vendor Class
Save Overload
Lsa.Vmfg.Purchasing Namespace

Vendor.Save Method (Stream)

Save current state of data set to stream.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Save(
        Stream stream
)
```

VB

```
Public Overridable Sub Save (
        stream As Stream
)
```

Parameters

stream

Type: System.IO.Stream

See Also

Vendor Class

Save Overload

Lsa.Vmfg.Purchasing Namespace

VendorPart Class

Maintain Vendor Parts.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessDocument
          Lsa.Vmfg.Purchasing.VendorPart

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class VendorPart : BusinessDocument
```

VB

```
<SerializableAttribute>
Public Class VendorPart
        Inherits BusinessDocument
```

The **VendorPart** type exposes the following members.

Constructors

	Name	Description
	VendorPart()	Business Document Constructor
	VendorPart(String)	Business Document Constructor

Methods

	Name	Description
	Browse(String, String, String)	Retrieves Vendor Parts based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieves Vendor Parts based on search criteria. Number of rows returned is limited by the value of maxRecords.
	Exists	Determines if a specific Vendor Part exists in the database.
	Find	Retrieves a specific Vendor Part from the database.
	Load(String)	Loads all Vendor Parts for a specific vendor.
	Load(Stream, String)	Load from stream and rename using new key.
	Load(String, String)	Loads a specific Vendor Part.
	NewVendorPartRow(String, String)	Inserts a new row into the VENDOR_PART data table.
	NewVendorPartRow(String, String, String)	Inserts a new row into the VENDOR_PART data table.
	Save()	Saves all changes made to previously loaded Vendor Part data to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

Lsa.Vmfg.Purchasing Namespace

VendorPart Constructor

Overload List

	Name	Description
	VendorPart()	Business Document Constructor
	VendorPart(String)	Business Document Constructor

See Also

VendorPart Class
Lsa.Vmfg.Purchasing Namespace

VendorPart Constructor

Business Document Constructor

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public VendorPart()

VB
Public Sub New

See Also

VendorPart Class
VendorPart Overload
Lsa.Vmfg.Purchasing Namespace

VendorPart Constructor (String)

Business Document Constructor

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public VendorPart(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

VendorPart Class

VendorPart Overload

Lsa.Vmfg.Purchasing Namespace

VendorPart.VendorPart Methods

The VendorPart type exposes the following members.

Methods

	Name	Description
	Browse(String, String, String)	Retrieves Vendor Parts based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieves Vendor Parts based on search criteria. Number of rows returned is limited by the value of maxRecords.
	Exists	Determines if a specific Vendor Part exists in the database.
	Find	Retrieves a specific Vendor Part from the database.
	Load(String)	Loads all Vendor Parts for a specific vendor.
	Load(Stream, String)	Load from stream and rename using new key.
	Load(String, String)	Loads a specific Vendor Part.
	NewVendorPartRow(String, String)	Inserts a new row into the VENDOR_PART data table.
	NewVendorPartRow(String, String, String)	Inserts a new row into the VENDOR_PART data table.
	Save()	Saves all changes made to previously loaded Vendor Part data to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

VendorPart Class

Lsa.Vmfg.Purchasing Namespace

VendorPart.Browse Method

Overload List

	Name	Description
	Browse(String, String, String)	Retrieves Vendor Parts based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieves Vendor Parts based on search criteria. Number of rows returned is limited by the value of maxRecords.

See Also

VendorPart Class

Lsa.Vmfg.Purchasing Namespace

VendorPart.Browse Method (String, String, String)

Retrieves Vendor Parts based on search criteria.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

Return Value

Type: **DataSet**

See Also

VendorPart Class

Browse Overload
Lsa.Vmfg.Purchasing Namespace

VendorPart.Browse Method (String, String, String, Int32, Int32)

Retrieves Vendor Parts based on search criteria. Number of rows returned is limited by the value of maxRecords.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns,
        int startRecord,
        int maxRecords
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String,
        startRecord As Integer,
        maxRecords As Integer
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

startRecord

Type: System.Int32

maxRecords

Type: System.Int32

Return Value

Type: **DataSet**

See Also

VendorPart Class
Browse Overload
Lsa.Vmfg.Purchasing Namespace

VendorPart.Exists Method

Determines if a specific Vendor Part exists in the database.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual bool Exists(
        string vendorID,
        string partID
)
```

VB

```
Public Overridable Function Exists (
        vendorID As String,
        partID As String
) As Boolean
```

Parameters

vendorID

Type: System.String

partID

Type: System.String

Return Value

Type: Boolean

See Also

VendorPart Class

Lsa.Vmfg.Purchasing Namespace

VendorPart.Find Method

Retrieves a specific Vendor Part from the database.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Find(
        string vendorID,
        string partID
)
```

VB

```
Public Overridable Sub Find (
        vendorID As String,
        partID As String
)
```

Parameters

vendorID

Type: System.String

partID

Type: System.String

See Also

VendorPart Class

Lsa.Vmfg.Purchasing Namespace

VendorPart.Load Method

Overload List

	Name	Description
	Load(String)	Loads all Vendor Parts for a specific vendor.
	Load(Stream, String)	Load from stream and rename using new key.
	Load(String, String)	Loads a specific Vendor Part.

See Also

VendorPart Class
Lsa.Vmfg.Purchasing Namespace

VendorPart.Load Method (String)

Loads all Vendor Parts for a specific vendor.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string vendorID
)
```

VB

```
Public Overridable Sub Load (
        vendorID As String
)
```

Parameters

vendorID

Type: System.String

See Also

VendorPart Class

Load Overload

Lsa.Vmfg.Purchasing Namespace

VendorPart.Load Method (Stream, String)

Load from stream and rename using new key.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        Stream stream,
        string vendorID
)
```

VB

```
Public Overridable Sub Load (
        stream As Stream,
        vendorID As String
)
```

Parameters

stream

Type: System.IO.Stream

vendorID

Type: System.String

See Also

VendorPart Class

Load Overload

Lsa.Vmfg.Purchasing Namespace

VendorPart.Load Method (String, String)

Loads a specific Vendor Part.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string vendorID,
        string partID
)
```

VB

```
Public Overridable Sub Load (
        vendorID As String,
        partID As String
)
```

Parameters

vendorID

Type: System.String

partID

Type: System.String

See Also

VendorPart Class

Load Overload

Lsa.Vmfg.Purchasing Namespace

VendorPart.NewVendorPartRow Method

Overload List

	Name	Description
	NewVendorPartRow(String, String)	Inserts a new row into the VENDOR_PART data table.
	NewVendorPartRow(String, String, String)	Inserts a new row into the VENDOR_PART data table.

See Also

VendorPart Class

Lsa.Vmfg.Purchasing Namespace

VendorPart.NewVendorPartRow Method (String, String)

Inserts a new row into the VENDOR_PART data table.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewVendorPartRow(
        string vendorID,
        string partID
)
```

VB

```
Public Overridable Function NewVendorPartRow (
        vendorID As String,
        partID As String
) As DataRow
```

Parameters

vendorID

Type: System.String

partID

Type: System.String

Return Value

Type: **DataRow**

See Also

VendorPart Class

NewVendorPartRow Overload

Lsa.Vmfg.Purchasing Namespace

VendorPart.NewVendorPartRow Method (String, String, String)

Inserts a new row into the VENDOR_PART data table.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewVendorPartRow(
        string vendorID,
        string partID,
        string siteID
)
```

VB

```
Public Overridable Function NewVendorPartRow (
        vendorID As String,
        partID As String,
        siteID As String
) As DataRow
```

Parameters

vendorID

Type: System.String

partID

Type: System.String

siteID

Type: System.String

Return Value

Type: **DataRow**

See Also

VendorPart Class

NewVendorPartRow Overload

Lsa.Vmfg.Purchasing Namespace

VendorPart.Save Method

Overload List

	Name	Description
	Save()	Saves all changes made to previously loaded Vendor Part data to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

VendorPart Class
Lsa.Vmfg.Purchasing Namespace

VendorPart.Save Method

Saves all changes made to previously loaded Vendor Part data to the database.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

VendorPart Class
Save Overload
Lsa.Vmfg.Purchasing Namespace

VendorPart.Save Method (Stream)

Save current state of data set to stream.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Save(
        Stream stream
)
```

VB

```
Public Overridable Sub Save (
        stream As Stream
)
```

Parameters

stream

Type: System.IO.Stream

See Also

VendorPart Class

Save Overload

Lsa.Vmfg.Purchasing Namespace

VendorRemitAddress Class

Maintain Vendor Remit to Addresses.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessDocument
          Lsa.Vmfg.Purchasing.VendorRemitAddress

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class VendorRemitAddress : BusinessDocument
```

VB

```
<SerializableAttribute>
Public Class VendorRemitAddress
        Inherits BusinessDocument
```

The **VendorRemitAddress** type exposes the following members.

Constructors

	Name	Description
	VendorRemitAddress()	Business Document Constructor
	VendorRemitAddress(String)	Business Document Constructor

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Vendor Remit Addresses based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Vendor Remit Addresses based on search criteria. Number of rows returned is limited by the value of maxRecords.
	Exists	Determines if a specific Vendor Remit Address exists in the database.
	Find	Retrieves a specific Vendor Remit Address.
	Load()	Loads all Vendor Remit Addresses.
	Load(String)	Loads all Vendor Remit Addresses for a given vendor.
	Load(Stream, String)	Load from stream and rename using new key.
	Load(String, Int32)	Loads a specific Vendor Remit Address.
	NewVendorRemitAddressRow	Inserts a new row into the VENDOR_REMIT_ADDRESS data table.
	Save()	Saves all previously loaded Vendor Remit Addresses to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

Lsa.Vmfg.Purchasing Namespace

VendorRemitAddress Constructor

Overload List

	Name	Description
	VendorRemitAddress()	Business Document Constructor
	VendorRemitAddress(String)	Business Document Constructor

See Also

VendorRemitAddress Class
Lsa.Vmfg.Purchasing Namespace

VendorRemitAddress Constructor

Business Document Constructor

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public VendorRemitAddress()

VB
Public Sub New

See Also

VendorRemitAddress Class
VendorRemitAddress Overload
Lsa.Vmfg.Purchasing Namespace

VendorRemitAddress Constructor (String)

Business Document Constructor

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public VendorRemitAddress(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

VendorRemitAddress Class

VendorRemitAddress Overload

Lsa.Vmfg.Purchasing Namespace

VendorRemitAddress.VendorRemitAddress Methods

The VendorRemitAddress type exposes the following members.

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Vendor Remit Addresses based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Vendor Remit Addresses based on search criteria. Number of rows returned is limited by the value of maxRecords.
	Exists	Determines if a specific Vendor Remit Address exists in the database.
	Find	Retrieves a specific Vendor Remit Address.
	Load()	Loads all Vendor Remit Addresses.
	Load(String)	Loads all Vendor Remit Addresses for a given vendor.
	Load(Stream, String)	Load from stream and rename using new key.
	Load(String, Int32)	Loads a specific Vendor Remit Address.
	NewVendorRemitAddressRow	Inserts a new row into the VENDOR_REMIT_ADDRESS data table.
	Save()	Saves all previously loaded Vendor Remit Addresses to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

VendorRemitAddress Class

Lsa.Vmfg.Purchasing Namespace

VendorRemitAddress.Browse Method

Overload List

	Name	Description
	Browse(String, String, String)	Retrieve Vendor Remit Addresses based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Vendor Remit Addresses based on search criteria. Number of rows returned is limited by the value of maxRecords.

See Also

VendorRemitAddress Class

Lsa.Vmfg.Purchasing Namespace

VendorRemitAddress.Browse Method (String, String, String)

Retrieve Vendor Remit Addresses based on search criteria.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

Return Value

Type: **DataSet**

See Also

VendorRemitAddress Class

Browse Overload

Lsa.Vmfg.Purchasing Namespace

VendorRemitAddress.Browse Method (String, String, String, Int32, Int32)

Retrieve Vendor Remit Addresses based on search criteria. Number of rows returned is limited by the value of maxRecords.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns,
        int startRecord,
        int maxRecords
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String,
        startRecord As Integer,
        maxRecords As Integer
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

startRecord

Type: System.Int32

maxRecords

Type: System.Int32

Return Value

Type: **DataSet**

See Also

VendorRemitAddress Class
Browse Overload
Lsa.Vmfg.Purchasing Namespace

VendorRemitAddress.Exists Method

Determines if a specific Vendor Remit Address exists in the database.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual bool Exists(
        string vendorID,
        int addrNo
)
```

VB

```
Public Overridable Function Exists (
        vendorID As String,
        addrNo As Integer
) As Boolean
```

Parameters

vendorID

Type: System.String

addrNo

Type: System.Int32

Return Value

Type: Boolean

See Also

VendorRemitAddress Class
Lsa.Vmfg.Purchasing Namespace

VendorRemitAddress.Find Method

Retrieves a specific Vendor Remit Address.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Find(
        string vendorID,
        int addrNo
)
```

VB

```
Public Overridable Sub Find (
        vendorID As String,
        addrNo As Integer
)
```

Parameters

vendorID

Type: System.String

addrNo

Type: System.Int32

See Also

VendorRemitAddress Class

Lsa.Vmfg.Purchasing Namespace

VendorRemitAddress.Load Method

Overload List

	Name	Description
	Load()	Loads all Vendor Remit Addresses.
	Load(String)	Loads all Vendor Remit Addresses for a given vendor.
	Load(Stream, String)	Load from stream and rename using new key.
	Load(String, Int32)	Loads a specific Vendor Remit Address.

See Also

VendorRemitAddress Class
Lsa.Vmfg.Purchasing Namespace

VendorRemitAddress.Load Method

Loads all Vendor Remit Addresses.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Load()

VB
Public Overridable Sub Load

See Also

VendorRemitAddress Class
Load Overload
Lsa.Vmfg.Purchasing Namespace

VendorRemitAddress.Load Method (String)

Loads all Vendor Remit Addresses for a given vendor.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string vendorID
)
```

VB

```
Public Overridable Sub Load (
        vendorID As String
)
```

Parameters

vendorID

Type: System.String

See Also

VendorRemitAddress Class

Load Overload

Lsa.Vmfg.Purchasing Namespace

VendorRemitAddress.Load Method (Stream, String)

Load from stream and rename using new key.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        Stream stream,
        string vendorID
)
```

VB

```
Public Overridable Sub Load (
        stream As Stream,
        vendorID As String
)
```

Parameters

stream

Type: System.IO.Stream

vendorID

Type: System.String

See Also

VendorRemitAddress Class

Load Overload

Lsa.Vmfg.Purchasing Namespace

VendorRemitAddress.Load Method (String, Int32)

Loads a specific Vendor Remit Address.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string vendorID,
        int addrNo
)
```

VB

```
Public Overridable Sub Load (
        vendorID As String,
        addrNo As Integer
)
```

Parameters

vendorID

Type: System.String

addrNo

Type: System.Int32

See Also

VendorRemitAddress Class

Load Overload

Lsa.Vmfg.Purchasing Namespace

VendorRemitAddress.NewVendorRemitAddressRow Method

Inserts a new row into the VENDOR_REMIT_ADDRESS data table.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewVendorRemitAddressRow(
        string vendorID,
        int addrNo
)
```

VB

```
Public Overridable Function NewVendorRemitAddressRow (
        vendorID As String,
        addrNo As Integer
) As DataRow
```

Parameters

vendorID

Type: System.String

addrNo

Type: System.Int32

Return Value

Type: **DataRow**

See Also

VendorRemitAddress Class
Lsa.Vmfg.Purchasing Namespace

VendorRemitAddress.Save Method

Overload List

	Name	Description
	Save()	Saves all previously loaded Vendor Remit Addresses to the database.
	Save(Stream)	Save current state of data set to stream.

See Also

VendorRemitAddress Class
Lsa.Vmfg.Purchasing Namespace

VendorRemitAddress.Save Method

Saves all previously loaded Vendor Remit Addresses to the database.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

VendorRemitAddress Class
Save Overload
Lsa.Vmfg.Purchasing Namespace

VendorRemitAddress.Save Method (Stream)

Save current state of data set to stream.

Namespace: Lsa.Vmfg.Purchasing
Assembly: VmfgPurchasing (in VmfgPurchasing.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Save(
        Stream stream
)
```

VB

```
Public Overridable Sub Save (
        stream As Stream
)
```

Parameters

stream

Type: System.IO.Stream

See Also

VendorRemitAddress Class

Save Overload

Lsa.Vmfg.Purchasing Namespace