Infor VISUAL API Toolkit Trace Class Library Reference

Copyright © 2024 Infor

Important Notices

The material contained in this publication (including any supplementary information) constitutes and contains confidential and proprietary information of Infor.

By gaining access to the attached, you acknowledge and agree that the material (including any modification, translation or adaptation of the material) and all copyright, trade secrets and all other right, title and interest therein, are the sole property of Infor and that you shall not gain right, title or interest in the material (including any modification, translation or adaptation of the material) by virtue of your review thereof other than the non-exclusive right to use the material solely in connection with and the furtherance of your license and use of software made available to your company from Infor pursuant to a separate agreement, the terms of which separate agreement shall govern your use of this material and all supplemental related materials ("Purpose").

In addition, by accessing the enclosed material, you acknowledge and agree that you are required to maintain such material in strict confidence and that your use of such material is limited to the Purpose described above. Although Infor has taken due care to ensure that the material included in this publication is accurate and complete, Infor cannot warrant that the information contained in this publication is complete, does not contain typographical or other errors, or will meet your specific requirements. As such, Infor does not assume and hereby disclaims all liability, consequential or otherwise, for any loss or damage to any person or entity which is caused by or relates to errors or omissions in this publication (including any supplementary information), whether such errors or omissions result from negligence, accident or any other cause.

Without limitation, U.S. export control laws and other applicable export and import laws govern your use of this material and you will neither export or re-export, directly or indirectly, this material nor any related materials or supplemental information in violation of such laws, or use such materials for any purpose prohibited by such laws.

Trademark Acknowledgements

The word and design marks set forth herein are trademarks and/or registered trademarks of Infor and/or related affiliates and subsidiaries. All rights reserved. All other company, product, trade or service names referenced may be registered trademarks or trademarks of their respective owners.

Publication Information

Release: Infor VISUAL API Toolkit

Publication date: August 13, 2024

About this guide

This guide describes the objects available in the Infor VISUAL API Toolkit Trace class library.

Intended audience

The intended audience of this guide is developers who are using the API Toolkit to extend the VISUAL solution.

Contacting Support

If you have questions about Infor products, go to the Infor Customer Portal at https://customerportal.infor.com/csmcore/

If we update this document after the product release, we will post the new version on this Web site. We recommend that you check this Web site periodically for updated documentation.

If you have comments about Infor documentation, contact https://docs.infor.com/en-us.

Supported languages

These languages are supported for use with the toolkit:

- Visual Basic
- C#

While it is possible to use any .NET-aware programming language with the toolkit, other languages are not officially supported.

Support information

The API Toolkit will be updated regularly as more class members are added to each assembly, schema changes are made, and any reported issues are resolved. Infor Support cannot assist you with developing customized code using the API Toolkit. For assistance with customizations, contact Infor Consulting Services or your channel partner.

The functionality provided within the API Toolkit will not be extended beyond the standard functionality experienced in the VISUAL application itself. Enhancement requests with compelling business cases detailing how suggested alternatives are not viable will be evaluated and considered.

Infor is not responsible for data incorrectly entered to the database through the use of the API Toolkit. Customers must establish a full test environment to ensure that data created by APIs functions in the same manner as data created through the VISUAL interface.

Lsa.Vmfg.Trace Namespace

Classes

	Class	Description
	Trace	Part Trace Maintenance. You cannot add or delete Trace records using this Business Document. You can modify existing Trace records, provided if certain business logic edits have been passed.
	TraceProfile	Maintain Trace Profiles.

Trace Class

Part Trace Maintenance. You cannot add or delete Trace records using this Business Document. You can modify existing Trace records, provided if certain business logic edits have been passed.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessDocument
          Lsa.Vmfg.Trace.Trace

Namespace: Lsa.Vmfg.Trace
Assembly: VmfgTrace (in VmfgTrace.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class Trace : BusinessDocument
```

VB

```
<SerializableAttribute>
Public Class Trace
        Inherits BusinessDocument
```

The **Trace** type exposes the following members.

Constructors

	Name	Description
	Trace()	Initializes a new instance of the **Trace** class
	Trace(String)	Initializes a new instance of the **Trace** class

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Part Trace records based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Part Trace records based on search criteria, limited by record count.
	Exists	Determine if a specific Part Trace ID exists.
	Find	Retrieve a specific Part Trace record. Only the top-level table (TRACE) is returned.
	Load()	Load all Part Trace records.
	Load(String, String)	Load a specific Part Trace ID.
	Load(Stream, String, String)	Load from stream and rename using new key.
	Save	Save all previously loaded Part Trace records to the database.

See Also

Lsa.Vmfg.Trace Namespace

Trace Constructor

Overload List

	Name	Description
	Trace()	Initializes a new instance of the Trace class
	Trace(String)	Initializes a new instance of the Trace class

See Also

Trace Class
Lsa.Vmfg.Trace Namespace

Trace Constructor

Initializes a new instance of the Trace class

Namespace: Lsa.Vmfg.Trace
Assembly: VmfgTrace (in VmfgTrace.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public Trace()

VB
Public Sub New

See Also

Trace Class
Trace Overload
Lsa.Vmfg.Trace Namespace

Trace Constructor (String)

Initializes a new instance of the Trace class

Namespace: Lsa.Vmfg.Trace
Assembly: VmfgTrace (in VmfgTrace.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public Trace(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

Trace Class

Trace Overload

Lsa.Vmfg.Trace Namespace

Trace.Trace Methods

The Trace type exposes the following members.

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Part Trace records based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Part Trace records based on search criteria, limited by record count.
	Exists	Determine if a specific Part Trace ID exists.
	Find	Retrieve a specific Part Trace record. Only the top-level table (TRACE) is returned.
	Load()	Load all Part Trace records.
	Load(String, String)	Load a specific Part Trace ID.
	Load(Stream, String, String)	Load from stream and rename using new key.
	Save	Save all previously loaded Part Trace records to the database.

See Also

Trace Class

Lsa.Vmfg.Trace Namespace

Trace.Browse Method

Overload List

	Name	Description
	Browse(String, String, String)	Retrieve Part Trace records based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Part Trace records based on search criteria, limited by record count.

See Also

Trace Class

Lsa.Vmfg.Trace Namespace

Trace.Browse Method (String, String, String)

Retrieve Part Trace records based on search criteria.

Namespace: Lsa.Vmfg.Trace
Assembly: VmfgTrace (in VmfgTrace.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

Return Value

Type: **DataSet**

See Also

Trace Class

Browse Overload
Lsa.Vmfg.Trace Namespace

Trace.Browse Method (String, String, String, Int32, Int32)

Retrieve Part Trace records based on search criteria, limited by record count.

Namespace: Lsa.Vmfg.Trace
Assembly: VmfgTrace (in VmfgTrace.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns,
        int startRecord,
        int maxRecords
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String,
        startRecord As Integer,
        maxRecords As Integer
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

startRecord

Type: System.Int32

maxRecords

Type: System.Int32

Return Value

Type: **DataSet**

See Also

Trace Class
Browse Overload
Lsa.Vmfg.Trace Namespace

Trace.Exists Method

Determine if a specific Part Trace ID exists.

Namespace: Lsa.Vmfg.Trace
Assembly: VmfgTrace (in VmfgTrace.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual bool Exists(
        string partID,
        string traceID
)
```

VB

```
Public Overridable Function Exists (
        partID As String,
        traceID As String
) As Boolean
```

Parameters

partID

Type: System.String

traceID

Type: System.String

Return Value

Type: Boolean

See Also

Trace Class

Lsa.Vmfg.Trace Namespace

Trace.Find Method

Retrieve a specific Part Trace record. Only the top-level table (TRACE) is returned.

Namespace: Lsa.Vmfg.Trace
Assembly: VmfgTrace (in VmfgTrace.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Find(
        string partID,
        string traceID
)
```

VB

```
Public Overridable Sub Find (
        partID As String,
        traceID As String
)
```

Parameters

partID

Type: System.String

traceID

Type: System.String

See Also

Trace Class

Lsa.Vmfg.Trace Namespace

Trace.Load Method

Overload List

	Name	Description
	Load()	Load all Part Trace records.
	Load(String, String)	Load a specific Part Trace ID.
	Load(Stream, String, String)	Load from stream and rename using new key.

See Also

Trace Class
Lsa.Vmfg.Trace Namespace

Trace.Load Method

Load all Part Trace records.

Namespace: Lsa.Vmfg.Trace
Assembly: VmfgTrace (in VmfgTrace.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Load()

VB
Public Overridable Sub Load

See Also

Trace Class
Load Overload
Lsa.Vmfg.Trace Namespace

Trace.Load Method (String, String)

Load a specific Part Trace ID.

Namespace: Lsa.Vmfg.Trace
Assembly: VmfgTrace (in VmfgTrace.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string partID,
        string traceID
)
```

VB

```
Public Overridable Sub Load (
        partID As String,
        traceID As String
)
```

Parameters

partID

Type: System.String

traceID

Type: System.String

See Also

Trace Class

Load Overload

Lsa.Vmfg.Trace Namespace

Trace.Load Method (Stream, String, String)

Load from stream and rename using new key.

Namespace: Lsa.Vmfg.Trace
Assembly: VmfgTrace (in VmfgTrace.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        Stream stream,
        string partID,
        string traceID
)
```

VB

```
Public Overridable Sub Load (
        stream As Stream,
        partID As String,
        traceID As String
)
```

Parameters

stream

Type: System.IO.Stream

partID

Type: System.String

traceID

Type: System.String

See Also

Trace Class

Load Overload

Lsa.Vmfg.Trace Namespace

Trace.Save Method

Save all previously loaded Part Trace records to the database.

Namespace: Lsa.Vmfg.Trace
Assembly: VmfgTrace (in VmfgTrace.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Save()

VB
Public Overridable Sub Save

See Also

Trace Class
Lsa.Vmfg.Trace Namespace

TraceProfile Class

Maintain Trace Profiles.

Inheritance Hierarchy

System.Object
  System.MarshalByRefObject
    System.ComponentModel.Component
      BusinessObject
        BusinessDocument
          Lsa.Vmfg.Trace.TraceProfile

Namespace: Lsa.Vmfg.Trace
Assembly: VmfgTrace (in VmfgTrace.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
[SerializableAttribute]
public class TraceProfile : BusinessDocument
```

VB

```
<SerializableAttribute>
Public Class TraceProfile
        Inherits BusinessDocument
```

The **TraceProfile** type exposes the following members.

Constructors

	Name	Description
	TraceProfile()	Initializes a new instance of the **TraceProfile** class
	TraceProfile(String)	Initializes a new instance of the **TraceProfile** class

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Trace Profiles based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Trace Profiles based on search criteria, limited by record count.
	Exists	Determine if a specific Trace Profile exists.
	Find	Retrieve a specific Trace Profile.
	Load()	Load all Trace Profiles.
	Load(String, String)	Load a specific Trace Profile.
	Load(Stream, String, String)	Load from stream and rename using new key.
	NewTraceProfileRow	Inserts a new row into the TRACE_PROFILE table.

Properties

	Name	Description
	DataObjectType	Report types of data object associated with this business object (Overrides **BusinessObject.DataObjectType**.)

See Also

Lsa.Vmfg.Trace Namespace

TraceProfile Constructor

Overload List

	Name	Description
	TraceProfile()	Initializes a new instance of the TraceProfile class
	TraceProfile(String)	Initializes a new instance of the TraceProfile class

See Also

TraceProfile Class
Lsa.Vmfg.Trace Namespace

TraceProfile Constructor

Initializes a new instance of the TraceProfile class

Namespace: Lsa.Vmfg.Trace
Assembly: VmfgTrace (in VmfgTrace.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public TraceProfile()

VB
Public Sub New

See Also

TraceProfile Class
TraceProfile Overload
Lsa.Vmfg.Trace Namespace

TraceProfile Constructor (String)

Initializes a new instance of the TraceProfile class

Namespace: Lsa.Vmfg.Trace
Assembly: VmfgTrace (in VmfgTrace.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public TraceProfile(
        string databaseInstanceName
)
```

VB

```
Public Sub New (
        databaseInstanceName As String
)
```

Parameters

databaseInstanceName

Type: System.String

See Also

TraceProfile Class

TraceProfile Overload

Lsa.Vmfg.Trace Namespace

TraceProfile.TraceProfile Methods

The TraceProfile type exposes the following members.

Methods

	Name	Description
	Browse(String, String, String)	Retrieve Trace Profiles based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Trace Profiles based on search criteria, limited by record count.
	Exists	Determine if a specific Trace Profile exists.
	Find	Retrieve a specific Trace Profile.
	Load()	Load all Trace Profiles.
	Load(String, String)	Load a specific Trace Profile.
	Load(Stream, String, String)	Load from stream and rename using new key.
	NewTraceProfileRow	Inserts a new row into the TRACE_PROFILE table.

See Also

TraceProfile Class

Lsa.Vmfg.Trace Namespace

TraceProfile.Browse Method

Overload List

	Name	Description
	Browse(String, String, String)	Retrieve Trace Profiles based on search criteria.
	Browse(String, String, String, Int32, Int32)	Retrieve Trace Profiles based on search criteria, limited by record count.

See Also

TraceProfile Class

Lsa.Vmfg.Trace Namespace

TraceProfile.Browse Method (String, String, String)

Retrieve Trace Profiles based on search criteria.

Namespace: Lsa.Vmfg.Trace
Assembly: VmfgTrace (in VmfgTrace.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

Return Value

Type: **DataSet**

See Also

TraceProfile Class

Browse Overload
Lsa.Vmfg.Trace Namespace

TraceProfile.Browse Method (String, String, String, Int32, Int32)

Retrieve Trace Profiles based on search criteria, limited by record count.

Namespace: Lsa.Vmfg.Trace
Assembly: VmfgTrace (in VmfgTrace.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataSet Browse(
        string columnNames,
        string searchCondition,
        string sortColumns,
        int startRecord,
        int maxRecords
)
```

VB

```
Public Overridable Function Browse (
        columnNames As String,
        searchCondition As String,
        sortColumns As String,
        startRecord As Integer,
        maxRecords As Integer
) As DataSet
```

Parameters

columnNames

Type: System.String

searchCondition

Type: System.String

sortColumns

Type: System.String

startRecord

Type: System.Int32

maxRecords

Type: System.Int32

Return Value

Type: **DataSet**

See Also

TraceProfile Class

Browse Overload

Lsa.Vmfg.Trace Namespace

TraceProfile.Exists Method

Determine if a specific Trace Profile exists.

Namespace: Lsa.Vmfg.Trace
Assembly: VmfgTrace (in VmfgTrace.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual bool Exists(
        string siteID,
        string partID
)
```

VB

```
Public Overridable Function Exists (
        siteID As String,
        partID As String
) As Boolean
```

Parameters

siteID

Type: System.String

partID

Type: System.String

Return Value

Type: Boolean

See Also

TraceProfile Class

Lsa.Vmfg.Trace Namespace

TraceProfile.Find Method

Retrieve a specific Trace Profile.

Namespace: Lsa.Vmfg.Trace
Assembly: VmfgTrace (in VmfgTrace.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Find(
        string siteID,
        string partID
)
```

VB

```
Public Overridable Sub Find (
        siteID As String,
        partID As String
)
```

Parameters

siteID

Type: System.String

partID

Type: System.String

See Also

TraceProfile Class

Lsa.Vmfg.Trace Namespace

TraceProfile.Load Method

Overload List

	Name	Description
	Load()	Load all Trace Profiles.
	Load(String, String)	Load a specific Trace Profile.
	Load(Stream, String, String)	Load from stream and rename using new key.

See Also

TraceProfile Class
Lsa.Vmfg.Trace Namespace

TraceProfile.Load Method

Load all Trace Profiles.

Namespace: Lsa.Vmfg.Trace
Assembly: VmfgTrace (in VmfgTrace.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#
public virtual void Load()

VB
Public Overridable Sub Load

See Also

TraceProfile Class
Load Overload
Lsa.Vmfg.Trace Namespace

TraceProfile.Load Method (String, String)

Load a specific Trace Profile.

Namespace: Lsa.Vmfg.Trace
Assembly: VmfgTrace (in VmfgTrace.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        string siteID,
        string partID
)
```

VB

```
Public Overridable Sub Load (
        siteID As String,
        partID As String
)
```

Parameters

siteID

Type: System.String

partID

Type: System.String

See Also

TraceProfile Class

Load Overload

Lsa.Vmfg.Trace Namespace

TraceProfile.Load Method (Stream, String, String)

Load from stream and rename using new key.

Namespace: Lsa.Vmfg.Trace
Assembly: VmfgTrace (in VmfgTrace.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual void Load(
        Stream stream,
        string siteID,
        string partID
)
```

VB

```
Public Overridable Sub Load (
        stream As Stream,
        siteID As String,
        partID As String
)
```

Parameters

stream

Type: System.IO.Stream

siteID

Type: System.String

partID

Type: System.String

See Also

TraceProfile Class

Load Overload

Lsa.Vmfg.Trace Namespace

TraceProfile.NewTraceProfileRow Method

Inserts a new row into the TRACE_PROFILE table.

Namespace: Lsa.Vmfg.Trace
Assembly: VmfgTrace (in VmfgTrace.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public virtual DataRow NewTraceProfileRow(
        string siteID,
        string partID
)
```

VB

```
Public Overridable Function NewTraceProfileRow (
        siteID As String,
        partID As String
) As DataRow
```

Parameters

siteID

Type: System.String

partID

Type: System.String

Return Value

Type: **DataRow**

See Also

TraceProfile Class

Lsa.Vmfg.Trace Namespace

TraceProfile.TraceProfile Properties

The TraceProfile type exposes the following members.

Properties

	Name	Description
	DataObjectType	Report types of data object associated with this business object (Overrides **BusinessObject.DataObjectType**.)

See Also

TraceProfile Class
Lsa.Vmfg.Trace Namespace

TraceProfile.DataObjectType Property

Report types of data object associated with this business object

Namespace: Lsa.Vmfg.Trace
Assembly: VmfgTrace (in VmfgTrace.dll) Version: 8.1.100.0 (8.1.100.0)

Syntax

C#

```
public override Type DataObjectType { get; }
```

VB

```
Public Overrides ReadOnly Property DataObjectType As Type
        Get
```

Property Value

Type: Type

See Also

TraceProfile Class
Lsa.Vmfg.Trace Namespace