



Wajdi Ben Saad
ESSAI, Sept, 2015

Wajdi Ben Saad

Today we are learning :

- SAS libraries
- Reading data from external files
 - txt and csv
 - Datalines
- SET statement
- PROC Print
- PROC Freq
- PROC Means

Wajdi Ben Saad

SAS libraries

Wajdi Ben Saad

SAS libraries

- LIBNAME statement assigns a libref
- Libref (short for "Library Reference") is an alias or nickname for a directory or folder for **SAS datasets**

Wajdi Ben Saad

SAS libraries

- LIBNAME statement assigns a libref
- Libref (short for "Library Reference") is an alias or nickname for a directory or folder for **SAS datasets**
- Dataset references contain two parts:
 - libref
 - dataset-name
 - Looks like: *libref.dataset-name*
- If libref is blank, the default is the Work library

Wajdi Ben Saad

SAS work library

- Work is a temporary library
- SAS datasets created in Work only exist during SAS session
- Once SAS session ends, datasets are erased
- Do not need to assign a libref for Work or specify it in dataset references

```
data Test_Scores;
is the same as
data work.Test_Scores;
```

Wajdi Ben Saad

SAS libraries

```
libname mozart 'c:\books\learning';

data mozart.test_mozart;
input id (1-3) name $ 1;
input id (1 Source=Source) Name (1);
datalines;
1 50 55 98 0000
2 78 77 75 00000
3 88 51 52 000000
;
run;
```


LIBNAME statement:
Assigns a libref

Use the libref for saving data and
for retrieving data


```
libname ORPDSAS 'D:\Data\ORPDS_SHARED\SAS Training\SAS 101 - Learning SAS by Example\Data\SAS Datasets';

data orpdsas.testdata; set mozart.test_mozart;
run;
```

Wajdi Ben Saad



Wajdi Ben Saad



Wajdi Ben Saad

LIBNAME examples

```
libname mozart 'c:\books\learning';
```

```
libname ORPDSAS 'D:\Data\ORPDS_SHARED\SAS Training\SAS 101 - Learning SAS by Example\Data\SAS Datasets';
```

```
libname locald '\\tsclient\D\SAS\data';
```

Wajdi Ben Saad

Reading external data

Wajdi Ben Saad

Reading data from a text file

```
data demographics;
infile 'D:\Data\ORPDS_SHARED\SAS Training\SAS 101 - Learning SAS by Example\Data\Text and CSV\data.txt';
input Gender $
Age
Height
Weight;
run;
```

INFILE – where to find the data

INPUT – variable names to associate with each data value
(\$ indicates character variable. Otherwise numeric.)

Wajdi Ben Saad

Reading data from a text file

The SAS System 13:41 Wednesday				
Obs	Gender	Age	Height	Weight
1	M	50	68	155
2	F	23	60	101
3	M	65	72	220
4	F	35	65	120
5	M	15	71	166

Results of PROC Print of "Demographics"

Obs – short for "observation" (part of PROC Print output)
Numbers observations from 1 to N

Wajdi Ben Saad

Reading data from a csv file

Four variables: Gender, Age, Height (in inches), Weight (in pounds)

Variables separated by commas

Wajdi Ben Saad

Reading data from a csv file

```
data demographics;
infile 'D:\Data\CHPR_SHARES\SAS Training\SAS 101 - Learning SAS by Example\Data\Text and CSV\mydata.csv' dsd;
input Gender $
Age
Height
Weight;
run;
```

dsd option (delimiter-sensitive data):

- ☐ Changes default delimiter from blank to comma
- ☐ If two delimiters in a row, assumes missing value between
- ☐ Quotes stripped from character values

Wajdi Ben Saad

Reading data from a csv file

The SAS System 13:41 Wednesday				
Obs	Gender	Age	Height	Weight
1	M	50	68	155
2	F	23	60	101
3	M	65	72	220
4	F	35	65	120
5	M	15	71	166

Results of PROC Print of "Demographics"

SAS data results are the same

Wajdi Ben Saad

Other delimiters

- **dlim=** (or **delimiter=**) option to specify data delimiters other than blanks or commas
 - Example: `infile 'D:\Data\mydata.txt' dlim='|';`
- **dsd** and **dlim=** options together
 - Performs all functions of dsd, but overrides default delimiter

Wajdi Ben Saad

Datalines

- Allows dataset to be created within SAS program
- Can be useful for creating a quick set of test data
- Use either **datalines** or **cards** options
- Follow with semi-colon **after** last line of data

```
data demographics;
infile datalines;
input Gender $ Age Height Weight;
datalines;
M 50 68 155
F 23 60 101
M 65 72 220
F 35 65 120
M 15 71 166
;
```


Wajdi Ben Saad

SET statement

Wajdi Ben Saad

SET statement

- After you've brought your data into a SAS dataset, most of your DATA steps will look like this:



Wajdi Ben Saad

SET statement

- The SET statement is similar to an INPUT statement
 - Except instead of a raw data file, you are reading observations from a SAS dataset
- Can read in temporary or permanent SAS datasets

```

libname WORKSET "c:\book\learning2";

data testdata;
set WORKSET.test_data;
where score ge 90;
add gender='F';
run;

data WORKSET;
set testdata;
if score ge 90 then top_perc = 'Top 2 Percent';
else if score ge 85 then top_perc = 'Top 5 Percent';
else if score ge 80 then top_perc = 'Top 10 Percent';
run;

```

Wajdi Ben Saad

PROC Print

Wajdi Ben Saad

PROC Print

- PROC Print can be used to list the data in a SAS dataset

```

data demographics;
input Gender Age Height Weight;
datalines;
M 50 68 155
F 23 60 101
M 45 72 220
F 35 65 130
M 15 71 166
;

proc print; run;

```

Wajdi Ben Saad

PROC Print

The SAS System				
Obs	Gender	Age	Height	Weight
1	M	50	68	155
2	F	23	60	101
3	M	45	72	220
4	F	35	65	130
5	M	15	71	166

Results of PROC Print of "Demographics"

Wajdi Ben Saad

PROC Print

- Many options to control output of PROC Print
 - `noobs` – Suppresses “OBS” column in output
 - `(obs=2)` – Only prints the first two observations
 - Can put in any number: 1 through N
 - Must be placed in parentheses after `data=` option
 - `var` statement – Only prints listed variables

```
proc print noobs data=demographics (obs=2);
var Gender Height;
run;
```

Wajdi Ben Saad

PROC Print

Gender	Height
M	68
F	60

We'll discuss other PROC Print options in later chapters

Wajdi Ben Saad

PROC Freq

Wajdi Ben Saad

PROC Freq

- PROC Freq can be used to run simple frequency tables on your data

```
data demographics;
infile datalines;
input Gender $ Age Height Weight;
datalines;
M 50 60 155
F 53 60 101
M 65 72 220
F 35 65 120
M 32 74 188
.;
proc freq run;
```

Wajdi Ben Saad

PROC Freq

The FREQ Procedure				
Gender	Frequency	Percent	Cumulative Frequency	Cumulative Percent
M	3	60.00	3	100.00
F	2	40.00	5	100.00

Age	Frequency	Percent	Cumulative Frequency	Cumulative Percent
15	1	20.00	1	20.00
25	1	20.00	2	40.00
35	1	20.00	3	60.00
50	1	20.00	4	80.00
65	1	20.00	5	100.00

Height	Frequency	Percent	Cumulative Frequency	Cumulative Percent
60	1	20.00	1	20.00
65	1	20.00	2	40.00
68	1	20.00	3	60.00
71	1	20.00	4	80.00
72	1	20.00	5	100.00

Weight	Frequency	Percent	Cumulative Frequency	Cumulative Percent
101	1	20.00	1	20.00
120	1	20.00	2	40.00
155	1	20.00	3	60.00
188	1	20.00	4	80.00
220	1	20.00	5	100.00

Results of PROC Freq of "Demographics"

Wajdi Ben Saad

PROC Freq

- Use the `table` statement to only print selected variables
- Use the `nocum` option to suppress cumulative statistics
- Use the `noperc` option to suppress percent statistics
- Can use options together or separately

```
proc freq data=demographics;
table Gender / nocum noperc;
run;
```

Wajdi Ben Saad

PROC Freq

- Can create simple cross-tabulations

```
proc freq data=demographics;
  table Gender*Height;
run;
```

The FREQ Procedure

Table of Gender by Height

Gender	Height	Frequency	Percent	New Pct	Col Pct
F	101	12	6	10	0
	120	8	15.62	3.13	0.00
	155	2	3.91	0.00	50.00
	166	0	0.00	0.00	0.00
M	101	4	7.82	14.29	0
	120	3	5.77	6.25	50.00
	155	14	26.92	28.13	43.75
	166	21	39.18	81.00	100.00
Total		18	33.33	100.00	

Wajdi Ben Saad

PROC Freq

- Use the `list` option to display cross-tab tables in a list format

```
proc freq data=demographics;
  table Gender*Height / list;
run;
```

The FREQ Procedure

Gender	Height	Frequency	Percent	Cumulative Frequency	Cumulative Percent
F	101	12	6.25	12	18.75
F	120	8	12.50	20	31.25
F	155	2	3.13	22	34.38
F	166	0	0.00	22	34.38
M	101	4	6.25	26	39.58
M	120	3	4.69	29	44.27
M	155	14	21.21	43	65.45
M	166	21	31.52	64	96.97
M	220	14	21.21	78	100.00

Wajdi Ben Saad

PROC Means

Wajdi Ben Saad

PROC Means

- PROC Means can be used to run simple summary statistics on your data

```
data demographics;
  infile datalines;
  input Gender $ Age Height Weight;
  datalines;
  F 50 60 100
  F 23 60 101
  M 65 72 220
  F 35 65 133
  F 15 71 165
  proc means; run;
```

Wajdi Ben Saad

PROC Means

The MEANS Procedure

Variable	N	Mean	Std Dev	Minimum	Maximum
Age	5	37.000000	20.218863	15.000000	65.000000
Height	5	67.200000	4.862545	60.000000	72.000000
Weight	5	155.000000	44.955815	101.000000	220.000000

Results of PROC Means of "Demographics"

Wajdi Ben Saad

PROC Means

- Many options to control output of PROC Means
 - `NMISS Mean Median` – Examples of statistics that can be specified in PROC Means
 - (see later slide for list of statistical keywords)
 - `class` statement – Allows for grouping by categorical variables
 - `var` statement – Only provides statistics for listed analysis variables

```
proc means data=demographics NMISS Mean Median;
  class Gender;
  var Height;
run;
```

Wajdi Ben Saad

PROC Means

The MEANS Procedure

Analysis Variable : Height

Gender	N	Obs	N Miss	Mean	Median
F	2	0	0	62.5000000	62.5000000
M	3	0	0	70.3333333	71.0000000

We'll discuss other PROC Freq and PROC Means options in later chapters

Wajdi Ben Saad

PROC Means

Descriptive statistics keyword

CSS	RANGE
CV	SKEWNESS SKEW
KURTOSIS KURT	STDDEV STD
LCLM	STDERR
MAX	SUM
MEAN	SUMWGT
MIN	UCLM
MODE	USS
N	VAR
NMISS	

Quantile statistics keyword

MEDIAN P50	Q3 P75
P1	P90
P5	P95
P10	P99
Q1 P25	QRANGE

Hypothesis testing keyword

PROBT PRT	T
-------------	---

Examples of statistics
that can be run with
PROC Means

Wajdi Ben Saad