User guide

Current feature guide / คู่มือคุณสมบัติปัจจุบัน

Invitation/account update - 10 October 2026

Email/link invitations now accept any signed-in Google/Discord account, require explicit acceptance and allow one successful use. Automatic email-matched joining has been removed. Users can set a persistent display name; managers additionally see the original provider name and verified email. See current behavior and API. This replaces older descriptions of preassignment and email-matching below.

ภาษาไทย · Operational status

Contents

1. Open and sign in 2. Navigation and categories 3. Groups 4. Invitations 5. Activities and approval 6. Reminders 7. Install on your Home Screen

1. Open and sign in

Visit https://calendar.toomtoom.online/. Non-members of public groups see general holidays/observances. Sign in with Google or Discord to join/create groups. Private groups require membership; a copied URL is not permission. Calendar roles never grant server control-panel access.

2. Navigation and categories

Desktop has a left sidebar. On mobile, open it with ☐; close with ×, an outside tap, or by choosing a page. Category filters, theme and account actions are inside. The compact group control stays in the header. Choose month/week/list, Today, arrows or mobile swipes. Search filters displayed activities.

Every group includes general dates from the shared dataset without copying. Defaults are education, community, important days and holidays. Optional categories include public/substitute/bank holidays, Buddhist/holy days, royal observances, traditions, Thai/international dates and Islamic calendar. A category is a filter, not a guarantee of complete source data.

Member filters are stored per group in the database; guest filters and theme use browser storage. Display currently combines only the selected group's activities with general dates. Multi-group display remains pending.

3. Groups

Open the group control to create a group, join by invitation or switch groups. New groups are private. The current group is remembered. Owners/managers manage invitations and member roles. Editors can edit native published activities; members can submit and edit their own pending proposals.

4. Invitations

Select group → group menu → Manage group / Invite members. Choose one method:

- Link: create, copy and share the link yourself.

- Email: enter recipient, role and validity, then Send invitation. No additional checkbox. Configured SMTP is required. Failed sends report failure and retain a usable invitation link.

- Code: create and copy a join code.

Email invitations match the provider-verified address at sign-in. They do not fabricate accounts. Confirmed CSV imports queue invitation emails per recipient. Existing memberships and suspensions are respected. Revoke unused invitations in history.

5. Activities and approval

Choose a date or Add activity. Enter title, description, dates, all-day or start/end times, category and color. Approval follows the group's manual/trusted/all policy. Check My activities for proposal status. Managers review pending submissions. Policy changes apply to new proposals, not old pending records.

Imported general dates are read-only for members. Fix them at the source; corrections become visible to all groups on their next fetch. Native activities remain in their group.

6. Reminders

My settings provides notification categories, lead time and all-day time. Display and reminder categories are separate. All-day reminders occur the previous day at 12:00 and on the date at the configured time, default 07:00, Asia/Bangkok. Manager settings control review notifications.

Device notification permission is separate. The inbox remains available when system Push/badging is unsupported. Delivery depends on server uptime, permission and browser/device support. See NOTIFICATIONS.md and CURRENT-STATUS.md for verified limits.

7. Install on your Home Screen

On iPhone, iPad and Android, a short introduction appears once per browser after approximately five seconds, without interrupting another open dialog. Close it or choose Later; future visits do not show it automatically. Reopen it using Add to Home Screen at the bottom of the sidebar. Clearing website storage or changing browsers may show it again. Standalone app windows hide the installation invitation.

- iPhone/iPad: open the calendar in Safari → Share → Add to Home Screen → enable Open as Web App if available → Add. If missing, scroll the share sheet and use Edit Actions. In-app browsers should open the site in Safari first. Websites cannot launch the native installation prompt on iOS.

- Android: when supported and ready, tap Install app and confirm the browser prompt. Otherwise use the browser menu → Install app / Add to Home Screen. Open the site in Chrome as a fallback for in-app browsers.

Installation guide on the website includes both languages and a theme switch. Installation does not automatically grant notification permission. Native installation has not been verified on physical iOS/Android devices in this update.

Sources: Apple guide, MDN installation API.

Public default and loading screen (10 October 2026)

The default public view has no selected group and shows "ยังไม่มีปฏิทิน". GET /api/public/events reads only the shared, published dataset, without group-local activities or group labels. It does not depend on CS SKRU membership/visibility. Signed-in users can still resume their selected calendar; explicit group links retain their group context and existing access checks.

public/boot.js displays an animated turtle splash while the initial session, group, catalog and event data load. It ends immediately on tutel:ready, with no artificial minimum delay. A slow request exposes retry after 15 seconds; load failure exposes an error and retry. prefers-reduced-motion disables animations. Installation onboarding waits until the loading overlay closes. Native operating-system splash screens remain controlled by the browser/OS; this animation runs inside the web app.

Delete and restore a calendar

Only the calendar owner can delete it: open the group menu → Manage group → Delete calendar, then type its exact name. Managers, editors and server administrators do not gain deletion rights from their other roles.

Deletion moves the group into Calendar trash for 30 days. Members cannot open it, group reminders stop and existing invitations are revoked. Open the group menu → Calendar trash → Restore calendar to recover activities, membership and settings before the deadline. Old invitations remain revoked; create new invitations after restoring. A previously suspended calendar remains suspended after restoration.

After 30 days the cleanup worker permanently removes group-local activities, memberships, invitations, bindings and notification records from the live database. Shared holidays/general dates and user accounts remain. Existing backups and audit history have separate retention and are not erased by this feature. Delivery already in progress or messages already sent cannot be recalled. The legacy bot reminder system is separate: its reminders are not disabled by this website operation until the grouped worker migration is enabled.

See Group deletion internals for implementation and retention details.

Group and event workflows

Find the controls

The calendar remains the main screen. Open the group selector to search your calendars, select one, create/join, choose calendars to display together, open trash or leave. Group administration contains invitations, all group events, Discord bindings, export and audit history. Account settings contain linked sign-in identities, ownership requests and active sessions. Advanced event actions are inside "Manage and history"; draft/recurrence fields are collapsed inside the event editor.

Membership and ownership

Members can leave without deleting authored activities. An owner must transfer ownership or trash the calendar before leaving. Removal by a manager also preserves events. Managers cannot remove an owner or another manager; use suspension rather than removal to prevent rejoining. Owner transfer is a seven-day request: the existing owner stays owner until the target, who must remain an active member, accepts. The former owner becomes a manager. Requests can be cancelled or declined. Trashing a calendar cancels its ownership request.

Leaving/removal writes a membership exit marker. Old email invitations will not silently re-add the account at login. Explicit acceptance of a valid invitation remains available, without overriding an existing membership role;

blocked memberships cannot accept. CSV preview skips existing verified-email members and preserves their roles. Invalid or duplicate CSV rows require correction before submission. Delivery acceptance does not prove inbox receipt.

Display several calendars

Default is the selected calendar only. Choose additional calendars in the group menu; preferences are stored per account in account_views. The selected calendar is always included and remains the destination for new events. Every additional group must be a current, unblocked membership in an unsuspended group. Stale or removed selections are filtered. Shared general dates are deduplicated by event ID and remain stored once. Group names appear in details, agenda rows and event tooltips. Guest root shows only general dates; a public group link may show published group activities without sign-in, while private links require access.

Events

Drafts are saved without publishing or notifying reviewers. Submit a draft to apply the group's existing manual/trusted/automatic approval policy. Rejection requires a reason. Nonprivileged edits follow the approval policy again. Group-local activities may be cancelled, moved to trash and restored within 30 days. Cancellation removes an event from the published calendar but keeps history. Resubmit a cancelled item to use the approval policy again. Trash restores the previous lifecycle; it does not automatically publish a pending or cancelled item. Imported dates remain managed at their source.

Daily, weekly and monthly recurrence is bounded to one year. The database stores a series once and expands occurrences for reads, instead of copying events. Monthly events on the 31st skip months without a 31st. Edit the whole series from the main edit button; authorized immediate publishers can edit one occurrence in its advanced menu. A review-dependent user must edit the series for approval instead of publishing a one-off override. Cancel one occurrence or the whole series. An exception stores only changed fields; cancelled occurrence entries and overrides are retained with the series. Editing a series does not clear its exceptions automatically.

Activity history records who performed an action and when; it is not a full prior-content diff. Export produces JSON containing group-local event content/status/recurrence, without secrets, member emails or account identifiers. This export is for portability/reference, not a complete recovery backup: occurrence exceptions, memberships and audit are not included. Consistent SQLite backups remain the full recovery mechanism.

Notifications and sessions

Users choose publication/review/reminder/change alerts by group. Optional daily summaries combine today's matching events once at the configured all-day reminder time. Quiet hours use Asia/Bangkok and suppress device delivery while preserving the web inbox. Equal start/end is rejected. Quiet hours do not postpone device messages or change group Discord schedules. Already dispatched messages cannot be recalled. Pending/claimed Discord jobs containing changed events are expired to avoid delivering outdated snapshots; there is no automatic second daily Discord summary after an edit. The website's change alerts are distinct from the legacy bot scheduler.

Account settings show approximate device types and expiry for active sessions, allow revoking another session, or all others. Old sessions without device metadata are labelled unknown. Unlinking an identity requires another linked identity to remain and revokes other sessions. OAuth linking requires proving both identities; no email-only merge. Session revocation does not unsubscribe independently registered device push subscriptions:

turn off device notifications in notification settings if needed.

Developer map and API

- groups/lifecycle.js: membership exits, ownership requests, multi-group account views.

- events/workflow.js: additive event lifecycle schema, actions, history, exports and cleanup.

- events/recurrence.js: bounded virtual occurrences.

- auth/account-settings.js: session metadata, revocation and identity unlinking.

- public/workspace.js: secondary dialogs and event action menus.

- public/groups.js: group navigation/admin; public/settings.js: member and notification settings.

API / Purpose

POST /api/group/leave / Leave current group; owner receives 409

DELETE /api/members/:id / Remove a lower-ranked member

POST /api/group/transfer / Create/replace seven-day ownership request

GET/DELETE /api/group/transfer / Inspect/cancel outgoing request

GET /api/ownership-requests / List incoming requests

POST /api/ownership-requests/:id/respond / {accept: true/false}

GET/PUT /api/account/view / {groupIds: [...]} up to 20 extra groups

GET /api/events?groups=id,id / Authorized aggregate with one shared dataset

GET /api/group/events / Manager's local activity inventory

GET /api/events/trash / Own recoverable events, or all for managers/owners

POST /api/events/:id/action / trash, restore, cancel, submit, cancelOccurrence, editOccurrence

GET /api/events/:id/history / Authorized action history

GET /api/group/export / Manager JSON export

GET/DELETE /api/accounts[/provider] / Linked identities/unlink

GET /api/account/sessions / Safe metadata; never bearer tokens/session hashes

DELETE /api/account/sessions/:id / Revoke another own session

POST /api/account/logout-others / Revoke all other sessions

Writes use session authentication and CSRF. Group APIs enforce group context and member/manager/real-owner requirements. Public reads never expose review notes. Existing event status CHECK remains pending/published/rejected; lifecycle adds active/draft/cancelled/trash separately, preserving the database rather than rebuilding it. The ten-minute cleanup removes expired event trash and exceptions. Group purge removes related lifecycle tables, and account merges transfer/clean new account references.

Secrets and databases are never part of a source deployment.

Deployment boundaries

Grouped Discord worker activation is still a coordinated migration, with CALENDAR_GROUPS_ENABLED=0 preserved until legacy channels have migrated. /calendar connect obtains a same-Discord-account, single-use binding grant once grouped integration is enabled. The Calendar Discord OAuth app itself is not a second bot runtime. Main server-panel emergency owner transfer is a privileged override with audit, distinct from ordinary web owner acceptance. The website still runs on homeserver; Oracle bot failover does not host the website.

These calendar additions were reviewed and formatted; no destructive production membership/event/ownership tests or email batches were performed. Music skip/loop regressions were separately tested (19 relevant automated cases). Do not interpret service startup as full OAuth, push or device validation.

Group history and directory (10 October 2026)

All authorized group members can read member names, group roles and join timestamps, and a paginated activity history with actor names, item titles and Bangkok timestamps. Management writes remain restricted. New audit snapshots preserve readable names after item deletion; old actions are not reconstructed. No invitation tokens or email addresses are exposed. See Group history and directory for API changes, implementation and retention limitations. Server source changes require a restart as part of deployment.

Current source and learning material / โค้ดและสื่อเรียนรู้ปัจจุบัน

The repository conventions are documented in CODE-STYLE.md. The independent Learning Lab is at D:/Tutel-Learning-Lab, contains current snapshots of both repositories, and is not deployed or published with either project. Earlier architecture examples are explicitly identified as historical; current feature explanations take precedence.

Current feature guide / คู่มือการเปลี่ยนแปลงล่าสุด

Updated 10 October 2026. This page describes the current source; the readability cleanup is a local source change until deployed separately.

Groups and viewing links / กลุ่มและลิงก์ดูปฏิทิน

Open the selected group name in the top bar to open กลุ่มปฏิทิน. Everyone who may read that calendar can use คัดลอกลิงก์ปฏิทิน; management permissions are not required. Owners also see the same link in group management beside viewing visibility. Links have the form /g/<slug>.

Public viewing permits the group link without signing in. A private calendar still requires an authorized member session: copying a link does not change its visibility or grant membership. The default site view shows only shared general dates with no selected CS SKRU group. Shared dates are read once and combined with group activities, not cloned into each new group.

กดชื่อกลุ่มด้านบน → กลุ่มปฏิทิน → คัดลอกลิงก์ปฏิทิน สมาชิกและผู้ชมที่อ่านกลุ่มได้ก็คัดลอกได้
ปฏิทินส่วนตัวไม่ได้กลายเป็นสาธารณะเพียงเพราะส่งลิงก์ ลิงก์ดูปฏิทินกับลิงก์เชิญสมาชิกทำหน้าที่ต่างกัน

Invitations and account names / คำเชิญและชื่อบัญชี

Email and ordinary link invitations require explicit acceptance using any Google or Discord account, and allow one successful use. An invitation is not automatically accepted merely because the email matches. Anyone holding the link can use it before the recipient; avoid forwarding a single-use invitation unintentionally. Code invitations follow their configured use limit.

CSV columns are email,name,role; email is required, name is optional and role selects the invitation permission. Existing members are skipped by CSV import. Accepting an invitation while already a member consumes it without changing the saved membership role; role changes belong in member management.

ตั้งค่าของฉัน allows a custom display name, maximum 100 characters. Clearing it restores the current provider name. Authorized managers/owners can additionally see the original provider name and verified email; ordinary member listings do not expose email addresses.

Editing an activity from the calendar / แก้กิจกรรมจากปฏิทิน

Open your own editable group activity in the selected calendar and use แก้ไข in its detail dialog. This reuses the activity editor from กิจกรรมของฉัน. Imported/shared dates and activities from another selected context are not editable through this shortcut. The server checks authorization again; can_edit in the event response is only a UI hint.

Scheduled notifications / การแจ้งเตือนตามเวลา

Creating, editing, approving, cancelling or deleting an activity no longer sends event-change notifications. Audit history is retained and already delivered inbox items are not retroactively removed.

- Tomorrow summary: 12:00 Bangkok, if enabled.

- Today's summary: the user's saved day time; a new preference defaults to 07:00 Bangkok.

- Timed activities: configured lead time, then at the activity start, if enabled.

- All-day activity: covered by today's summary; when that summary is off, an individual day reminder may be used.

- Categories, quiet hours and prior opt-outs remain respected. No summary is sent for an empty set.

Quiet hours suppress device Push, while the web inbox still records the notification. Browser/OS permission and an active subscription are required for Push. Scheduled web reminders and the legacy Discord scheduler are separate; grouped Discord worker cutover is still pending. See Reminder policy.

Feedback and files / Feedback และไฟล์แนบ

Sign in, choose Feedback, add a title/message/category and optionally up to 3 JPG/PNG/WebP images, each up to 5 MB. A draft survives closing the dialog until the page reloads. X and Cancel close this dialog independently of other dialogs. The limit is 5 submissions per account per hour.

Images are decoded and resized to at most 1600 pixels per side, converted to static WebP and stored outside the public directory. Group managers do not gain access to the server's Feedback inbox. Only main-panel administrators can view all messages and set New / In progress / Done. There is no reply thread or attachment purge UI yet.

Developer reading order / ลำดับอ่านโค้ด

src/server.js → authentication/group access → feature routes → SQLite statements → browser modules. Read public/feedback.js for static templates and multipart upload; src/feedback/routes.js for validation/private file storage; src/integrations/control/routes.js for the privileged server-panel bridge. Read src/notifications/scheduler.js for reminders and src/notifications/service.js for deduplication/Push.

See Source readability, Developer handbook, API and current deployment. Format/syntax checks do not replace full browser, OAuth, audio or device tests.

Invitation links and display names / คำเชิญและชื่อที่แสดง

Current behavior - 10 October 2026

Email is the delivery destination, not a restriction on the accepting account. The holder of an email/link invitation signs in with any Google or Discord account and explicitly accepts. Email and link invitations allow exactly one successful acceptance; codes retain their configured use count. Startup also caps older email/link invitations at one use. Previously redeemed links are therefore exhausted; send a fresh invitation if needed.

OAuth login and listing groups no longer automatically redeem invitations by email matching. CSV sends a separate one-use link to each address. The first account to successfully accept owns that redemption. Merely viewing the URL or signing in does not consume it. Expired, revoked, suspended-group and blocked-membership failures do not consume it. The SQLite transaction serializes acceptance. A successful acceptance by an existing member also consumes the link but preserves the member's existing role; it does not promote/demote them or duplicate the join history.

อีเมลเป็นที่รับคำเชิญ ผู้ถือ link ใช้ Google หรือ Discord บัญชีใดก็ได้ ต้องกดรับคำเชิญหลังเข้าสู่ระบบ ลิงก์ใช้สำเร็จได้ 1 ครั้ง รวมถึงลิงก์เก่า ระบบไม่เข้ากลุ่มให้อัตโนมัติเพียงเพราะอีเมลตรงกัน CSV ส่งลิงก์แยกให้แต่ละคน การเปิดอ่านเมลหรือกดดูเว็บยังไม่ใช้สิทธิ์ สมาชิกเดิมกดรับได้แต่สิทธิ์ไม่เปลี่ยน ผู้ที่ถูกระงับยังเข้าร่วมไม่ได้

Display names

ตั้งค่าของฉัน → ชื่อที่แสดง lets the signed-in user set a name of up to 100 characters. Initially it is the provider's profile name. A custom name survives subsequent OAuth sign-ins. Leaving the field blank restores the latest recorded provider name. This changes presentation across the account's groups, not identity, email, permissions or membership.

users.name remains the effective public name; additive custom_name and provider_name columns distinguish the override and latest provider name. Existing records seed provider_name from the current name during migration. Name snapshots already stored in audit/Feedback records remain historical snapshots.

The own-profile API is GET /api/account/profile and PUT /api/account/profile with {name}. Writes require the user's session and CSRF. It cannot edit another user's name.

Ordinary members see public display names in the directory. Calendar owners/managers and main-panel admins additionally see originalName and provider-verified emails; these private fields are omitted for ordinary readers. Only verified emails already supplied by Google/Discord are available; Discord may not supply an email. The provider name is the last recorded provider profile name, not an immutable/legal name.

ตั้งชื่อเองได้ใน ตั้งค่าของฉัน ถ้าเว้นว่างจะกลับไปใช้ชื่อจากบัญชี Google/Discord ชื่อที่ตั้งใช้ทุกกลุ่มและไม่ถูกเขียนทับตอน login หน้าแอดมินแสดงชื่อที่ใช้ พร้อมชื่อบัญชีเดิมและอีเมลที่ยืนยันแล้ว สมาชิกทั่วไปไม่เห็นอีเมลของคนอื่น การตั้งชื่อไม่เปลี่ยนสิทธิ์หรือประวัติเดิม

Deployment

Deploy the Calendar auth, group schema/invitation routes, account settings, members/control API and corresponding web assets together. The main panel's member renderer must also be updated. Do not copy

.env, live databases or private attachments into Git or release archives. Schema changes are additive; take a consistent SQLite backup before restart. See FEEDBACK.md for attachment storage requirements.

การแจ้งเตือนกิจกรรม / Event reminders

อัปเดต 10 ตุลาคม 2569: แจ้งเตือนกิจกรรมเฉพาะตามกำหนดเวลา ไม่ส่งเมื่อเพิ่ม แก้ไข ลบ ยกเลิก หรืออนุมัติ รายการเหล่านี้ยังอยู่ในประวัติกลุ่ม

- วันพรุ่งนี้: สรุปเวลา 12:00 น. เวลาไทย เปิด/ปิดได้ในการตั้งค่าของฉัน

- วันกิจกรรม: สรุปตามเวลาเตือนทั้งวันที่ผู้ใช้เลือก เปิด/ปิดได้

- กิจกรรมมีเวลา: เตือนก่อนเริ่มตาม leadMinutes และเมื่อถึงเวลาเริ่ม ตามตัวเลือกเตือนกิจกรรม

- กิจกรรมทั้งวัน: ถ้าปิดสรุปรายวันแต่ยังเปิดเตือนกิจกรรม จะเตือนวันจริงตาม dayTime;
ถ้าเปิดสรุปรายวันจะรวมในสรุปเพื่อไม่เตือนซ้ำ

- เคารพหมวดที่เลือกและช่วงงดรบกวน ค่าเดิมที่ผู้ใช้ปิดสรุปรายวันไว้ยังคงเดิม

- Discord ยังคงใช้การตั้งค่าของแต่ละกลุ่ม/ช่อง: วันพรุ่งนี้ตอนเที่ยง, วันจริงตาม dailyTime, ก่อนเริ่มเมื่อเปิด timed ไม่ส่งจากการแก้ไขกิจกรรม

- การแจ้งเตือนบัญชี เช่น ขอรับโอนเจ้าของ และการกดทดสอบอุปกรณ์ยังทำงาน

- แจ้งเตือนที่ส่งไปแล้วก่อนอัปเดตยังอยู่ในกล่องข้อความ

เปิดกิจกรรมของตนเองจากปฏิทินแล้วกดแก้กิจกรรมได้ เช่นเดียวกับหน้ากิจกรรมของฉัน เซิร์ฟเวอร์ส่ง can_edit จากสิทธิ์จริงโดยไม่เผย owner_id ในรายการปฏิทิน; API แก้ไขยังตรวจบัญชีและสิทธิ์กลุ่มทุกครั้ง วันสำคัญจากแหล่งกลาง/รายการนำเข้าแก้ไม่ได้จากหน้านี้

English

Event notifications are scheduled reminders only: tomorrow's summary at 12:00 Bangkok time, the current-day summary at the configured dayTime, and timed reminders before/start. Creation, edits, removal/cancellation, publication and review outcomes no longer trigger event notifications. Audit history is retained. Existing user opt-outs and quiet hours are respected. Discord uses its per-binding reminder configuration. Account notifications and explicit device tests remain available.

Members can edit their own events from the calendar detail dialog. The event list supplies a permission-derived can_edit flag; write endpoints still enforce session, CSRF and group permissions. Imported/shared source events remain read-only.

Feedback / ส่งความคิดเห็น

User workflow

Sign in with Google or Discord, then choose Feedback beside account actions on desktop or in the mobile sidebar. Select Problem, Suggestion or Other, enter a title (120 characters) and description (5,000 characters), and optionally attach up to three JPG, PNG or WebP images, each at most 5 MB. Previews support removal before submission. Closing the dialog preserves the draft in memory until reload; a successful submission clears it.

The form explains that account name, applicable group name, page path and submission time accompany the message. Invite/connect tokens and query strings are not stored in the page path. Group context is captured when the dialog opens; only a group the user belongs to can be associated with the message. Feedback does not require group management permission.

สำหรับผู้ใช้

เข้าสู่ระบบก่อน แล้วกด Feedback ใกล้ส่วนบัญชีบนคอม หรือใน sidebar บนมือถือ เลือกแจ้งปัญหา / เสนอแนะ / อื่น ๆ กรอกหัวข้อและรายละเอียด แนบรูปได้ 3 รูป รูปละ 5 MB มีภาพตัวอย่างและปุ่มลบก่อนส่ง
การปิดหน้าต่างยังเก็บร่างไว้ในหน้านี้ เมื่อส่งสำเร็จจึงล้างร่าง

ระบบส่งชื่อบัญชี กลุ่มที่เกี่ยวข้อง หน้าที่เปิดและเวลาส่งร่วมกับข้อความ กล่องรับอยู่ใน Control Panel หลัก แอดมินกลุ่มปฏิทินไม่มีสิทธิ์อ่านกล่องนี้
ไม่ใช่ระบบแชทและยังไม่มีการตอบกลับหรือแจ้งเตือนผลการดำเนินการให้ผู้ส่งอัตโนมัติ

Administration

The Tutel Hub main panel provides กล่อง Feedback, unread counts, 50-item pagination, category/status filters, message detail, private image viewing and explicit read/status updates. Opening a detail marks it read. Statuses are independent of the read flag: new, in_progress, done. A separate control-panel admin session is required. The Calendar browser's platform-admin flag does not grant access to the service inbox.

API and authorization

- POST /api/feedback: authenticated Calendar session + CSRF and origin protection; multipart fields category, title, message, groupId, pagePath; images use repeated images fields.

- GET /api/feedback/images/:id: authenticated original submitter only. Attachment URLs are not public links.

- GET /internal/v1/control/feedback?page=1&status=&category=: service control secret, paginated {items,page,hasMore,unread}.

- GET /internal/v1/control/feedback/:id: control secret; message and attachment IDs.

- PUT /internal/v1/control/feedback/:id: control secret; optional {status,read}; stores update actor and time.

- GET /internal/v1/control/feedback/images/:id: control secret; WebP bytes.

The main panel proxies these routes through /api/calendar-admin/feedback… after enforcing its own login/admin checks and CSRF for writes. Neither service secret nor Calendar cookies are sent to the panel

browser.

Storage and operations

src/feedback/routes.js creates additive SQLite tables feedback and feedback_images. Messages preserve sender/group names as submission-time snapshots. Images are private files; the default directory is feedback/ beside DATABASE_PATH, outside the public web directory. FEEDBACK_UPLOAD_DIR optionally overrides it and must remain outside public/static directories and version control.

Multer holds bounded multipart input in memory; Sharp checks the decoded format, rejects unsupported/animated images, bounds decoded pixels at 25 million, rotates and resizes to at most 1600 × 1600, then re-encodes WebP without original metadata. Processing is sequential within each request. A process-local cap permits two concurrent uploads; users can submit five messages per hour, enforced again inside the SQLite transaction. File writes use opaque UUID names and restrictive permissions. On failure, newly written files are removed and the database transaction rolls back.

Back up both the SQLite database and image directory. SQLite-only backups will not include attachments. There is currently no automatic retention purge, operator deletion UI, malware scanning service, or shared image storage across hosts. Configure private backup and disk monitoring accordingly. Existing account/group removal does not automatically erase Feedback snapshots; support removal is an operator responsibility. Group managers cannot access Feedback just because it mentions their group.

Install dependencies (npm ci) and restart the Calendar service after deploying this feature; Sharp requires a compatible native package for the target platform. Update the main panel source and restart its service to expose the inbox. This document describes implementation, not proof that a production deployment or end-to-end test has happened.

Current status - 10 October 2026

Current feature guide / คู่มือคุณสมบัติปัจจุบัน

Calendar web runs on homeserver through its existing HTTPS tunnel. Public general dates are shared once; selected groups hold their own activities. Google/Discord OAuth, queued invitations and accepted email delivery have been configured. One explicitly authorized Gmail invitation was observed in the inbox; no mass CSV test was sent.

Implemented: mobile sidebar/themes, initial loading screen and installation guide, public default without CS SKRU selection, calendar trash with 30-day recovery, leaving/removing members, seven-day accepted ownership transfer, CSV existing-member skip, multi-group display, event drafts/cancellation/trash/history, bounded virtual recurrence and occurrence exceptions, JSON export, daily web summaries and quiet hours, account linking/unlinking and session controls.

See WORKFLOWS.md and WORKFLOWS.th.md for exact scope and API contracts. Calendar workflow changes were reviewed/formatted and the service startup is checked after deployment. No destructive calendar/member/ownership production test was performed. Physical-device installation/Push validation remains pending.

Grouped Discord worker is prepared but not enabled: CALENDAR_GROUPS_ENABLED=0 remains until legacy channel migration and coordinated bot-host cutover. Original Discord reminders are separate and are not automatically disabled by web group deletion. Calendar OAuth app is not a second bot runtime. Website hosting does not fail over to Oracle. Main server-panel APIs remain privileged and separate from group managers.

Music Loop default is off for guilds without a saved preference. Skip in a one-song loop restarts that song; a queued successor takes priority when skipping a song loop. Intentional decoder termination no longer marks playback failed. Nineteen relevant automated regressions passed; actual Discord audio was not exercised by synthetic tests. See repository history for source publication; runtime deployment is separate.

Group history and directory (10 October 2026)

All authorized group members can read member names, group roles and join timestamps, and a paginated activity history with actor names, item titles and Bangkok timestamps. Management writes remain restricted. New audit snapshots preserve readable names after item deletion; old actions are not reconstructed. No invitation tokens or email addresses are exposed. See Group history and directory for API changes, implementation and retention limitations. Server source changes require a restart as part of deployment.

Feedback, identity, scheduled reminders and source cleanup

The homeserver has the Feedback submission/inbox integration, custom display names with privileged original-name/email detail, any-account single-use email/link invitations, own-event editing shortcut, scheduled-only event notifications and a copy-calendar-link control for all authorized viewers. Existing inbox history remains intact. Website hosting remains on homeserver; no Oracle work is part of this cleanup.

The new project-wide readability pass reformats control-flow blocks, local declarations, embedded HTML and long SQL. It is a local source change until a separate deployment; formatter/syntax validation is not end-to-end behavioral testing. See CURRENT-FEATURES.md and CODE-STYLE.md.

Source readability / แนวทางเขียนโค้ดให้อ่านง่าย

Updated 10 October 2026. These conventions apply to the entire repository.

Formatting

- ESM JavaScript, explicit .js imports, two spaces, LF, semicolons and single quotes.

- Prettier uses a 100-column target. HTML uses htmlWhitespaceSensitivity: ignore so nested tags can occupy separate lines.

- Use npm run format before review and npm run format:check to inspect consistency. Formatting does not prove runtime correctness.

- Keep credentials, runtime databases, uploads, backups and generated lockfiles outside formatter input where configured.

Reading order inside a module

1. Imports and configuration constants. 2. Small helpers with a single clear responsibility. 3. Exported registration/setup functions and the workflows they coordinate. 4. Resource teardown beside the code that owns the resource.

Use one declaration per statement. Give related declarations one paragraph; separate validation, state changes, I/O and rendering with blank lines. Every if, else and loop body has braces, including early returns. Leave else if as one chain. Do not add blank lines after every statement.

HTML in JavaScript

Mark static HTML templates with /* HTML */ so Prettier also formats the nested markup. Long forms should be a named template constant. Attributes wrap when needed and closing tags remain aligned. This comment is a formatting hint, not an HTML sanitizer.

const FORM = /* HTML */

<form class="example-form">

<label>

Title

<input name="title" required />

</label>

<button type="submit">Save</button>

</form>

function renderName(element, name) { element.textContent = name; }

Use textContent/DOM creation for user-controlled text. Never interpolate submitted titles, names or messages into trusted markup. Preserve DOM identifiers, permission checks and cache-version conventions while

reorganizing source.

SQL and authorization

Put long SQL into multiline templates with clauses and field lists separated. Keep bound placeholders and .get/.all/.run arguments in matching order. Do not interpolate user input into SQL or construct arbitrary table/column names.

const query = db.prepare(

SELECT id, name

FROM users

WHERE id = ?

const user = query.get(userId);

This illustration explains formatting; it is not a replacement for a route's authentication, group authorization, CSRF or input validation. SQLite SQL whitespace can be reformatted outside quoted values; strings inside quotes must stay unchanged.

Boundaries and comments

Keep HTTP handlers, domain decisions, persistence and browser presentation in their existing feature folders. The music repository owns Discord audio and the private server panel. Calendar owns web accounts, groups, activities, Feedback storage and SQLite. Communicate through the existing protected HTTP contract; never share a live SQLite file or browser-visible service secret.

Comments explain intent, resource ownership, security assumptions and edge cases. Avoid narrating obvious assignments. Split a large function when a named workflow boundary exists; moving lines solely to make a file shorter creates unnecessary indirection.

ภาษาไทย

โค้ดหนึงย่อหน้าควรทำหน้าทีเดียว เช่น เตรียมข้อมูล ตรวจสิทธิ์ ตรวจ input บันทึกข้อมูล หรือวาดหน้า เว้นบรรทัดเมือเปลียนหน้าที ใช้ชือทีอ่านแล้วรู้ว่าเก็บอะไร แยกตัวแปรแต่ละตัว และใส่วงเล็บปีกกาทุกเงือนไข/ลูป เพือให้เห็นขอบเขตชัดเจน

HTML ทีอยู่ใน JavaScript ต้องจัด nested tags ด้วย ไม่ใช่จัดเฉพาะ JavaScript รอบนอก ส่วน SQL ยาวแบ่ง SELECT/FROM/JOIN/WHERE และรายการคอลัมน์ แต่ยังต้องใช้ parameter binding เหมือนเดิม การจัดรูปแบบไม่ใช่การอุดช่องโหว่ และไม่ใช่การทดสอบเสียง OAuth หรือการส่งอีเมล