คู่มือผู้ใช้ Tutel Calendar

Current feature guide / คู่มือคุณสมบัติปัจจุบัน

Invitation/account update - 10 October 2026

Email/link invitations now accept any signed-in Google/Discord account, require explicit acceptance and allow one successful use. Automatic email-matched joining has been removed. Users can set a persistent display name; managers additionally see the original provider name and verified email. See current behavior and API. This replaces older descriptions of preassignment and email-matching below.

English · สถานะจริง

สารบัญ

1. เข้าเว็บและบัญชี 2. เมนูและหมวดหมู่ 3. กลุ่มและสิทธิ์ 4. เชิญสมาชิก 5. กิจกรรมและการอนุมัติ 6. ตั้งแจ้งเตือน 7. เพิ่มแอปลงหน้าจอโฮม

1. เข้าเว็บและบัญชี

เปิด https://calendar.toomtoom.online/ ผู้ชมทียังไม่เป็นสมาชิกเห็นวันทั่วไปของกลุ่มสาธารณะ เข้าระบบด้วย Google/Discord เพื่อสร้างหรือเข้าร่วมกลุ่ม กลุ่มส่วนตัวต้องมีสิทธิ์สมาชิก การรู้ลิงก์ไม่ใช่สิทธิ์
ผู้จัดการปฏิทินไม่ใช่ผู้ดูแลเซิร์ฟเวอร์

2. เมนูและหมวดหมู่

บนคอมมี sidebar ด้านซ้าย มือถือกด ☐ เพื่อเปิด ปิดด้วย × แตะนอกเมนู หรือเลือกหน้า หมวดหมู่ ธีมและบัญชีอยู่ด้านใน ชื่อกลุ่มด้านบนเปิดเมนูเปลี่ยนกลุ่ม เลือกเดือน/สัปดาห์/รายการ ใช้วันนี้ ลูกศร หรือปัดซ้าย-ขวาบนมือถือและค้นหาได้

ทุกกลุ่มรวมวันทั่วไปจากข้อมูลชุดกลาง ไม่สร้างสำเนาเมื่อสร้างกลุ่ม ค่าเริ่มต้นมีการศึกษา กิจกรรม/ชุมชน วันสำคัญและวันหยุด หมวดอื่นเลือกเพิ่มได้ เช่นวันหยุดราชการ ชดเชย ธนาคาร พุทธ วันพระ สถาบันพระมหากษัตริย์ ประเพณี ไทย สากล และมุสลิม การมีหมวดไม่ได้แปลว่ามีข้อมูลวันครบจากต้นทาง

สมาชิกบันทึกหมวดแสดงผลแยกกลุ่มในฐานข้อมูล ผู้ชมเก็บใน browser storage ธีมเก็บในเครื่องนั้น ตอนนี้แสดงกลุ่มทีเลือกพร้อมวันกลาง เลือกแสดงหลายกลุ่มทีมีสิทธิ์อ่านพร้อมกันได้จากการตั้งค่ามุมมอง โดยค่าเริ่มต้นเลือกเฉพาะกลุ่มปัจจุบัน

3. กลุ่มและสิทธิ์

เปิดชื่อกลุ่มเพื่อสร้าง เข้าร่วมด้วยคำเชิญ หรือสลับกลุ่ม กลุ่มใหม่เป็นส่วนตัว เจ้าของ/ผู้จัดการดูแลสมาชิก คำเชิญ และการอนุมัติ Editor แก้กิจกรรม native ทีเผยแพร่ได้ Member ส่งข้อเสนอและแก้ของตนทียังรอตรวจได้

4. เชิญสมาชิก

เลือกกลุ่ม เปิดจัดการกลุ่ม/เชิญสมาชิก แล้วเลือกวิธีเดียว:

- ลิงก์: สร้างแล้วคัดลอกส่งเอง

- อีเมล: ใส่ผู้รับ สิทธิ์ อายุ แล้วกดส่งได้เลย ไม่มี checkbox ซ้ำ หากส่งไม่สำเร็จระบบเก็บลิงก์ไว้และบอกข้อผิดพลาด

- รหัส: สร้างแล้วคัดลอกให้ผู้รับ

ผู้รับลิงก์เข้าสู่ระบบด้วย Google หรือ Discord บัญชีใดก็ได้แล้วกดรับคำเชิญ ลิงก์อีเมลใช้สำเร็จได้ครั้งเดียว ไม่ต้องมีอีเมลตรงกับปลายทาง คำเชิญไม่สร้างบัญชีปลอม CSV ทียืนยันแล้วสร้างคำเชิญและเข้าคิวส่งอีเมลทีละคน ไม่เปลียนสิทธิ์เดิมและไม่ปลดระงับเอง ดูประวัติหรือเพิกถอนคำเชิญทียังไม่ใช้ได้

5. กิจกรรมและการอนุมัติ

กดวันทีหรือเพิมกิจกรรม ใส่ชือ รายละเอียด วันที ทังวันหรือเวลา หมวดและสี ผลลัพธ์ขึนกับ manual/trusted/all ของกลุ่ม ดูสถานะทีกิจกรรมของฉัน ผู้จัดการเปิดตรวจอนุมัติ การเปลียนโหมดไม่อนุมัติรายการเก่าทีรอตรวจเอง

วันทัวไปทีนำเข้าแก้ในเว็บสมาชิกไม่ได้ ต้องแก้ต้นทาง เมืออัปเดตทุกกลุ่มจะอ่านรายการกลางใหม่เหมือนกัน กิจกรรมทีผู้ใช้เพิมยังเป็นของกลุ่มเดิม

6. ตังแจ้งเตือน

ตังค่าของฉันเลือกหมวดเตือน ระยะล่วงหน้า และเวลาทังวัน หมวดแสดงผลกับหมวดแจ้งเตือนคนละค่า ทังวันเตือนก่อนหนึงวันเทียงและวันจริงเวลาเริมต้น 07:00 ตาม Asia/Bangkok ผู้จัดการตังเตือนข้อเสนอรอตรวจแยกได้

การเตือนเข้าเครืองต้องอนุญาต browser และรองรับอุปกรณ์ กล่องแจ้งเตือนยังใช้ได้เมือไม่รองรับ Push/badge การได้รับเมลจริงและ Push บนอุปกรณ์ยังไม่ยืนยันครบ ดู NOTIFICATIONS.md และ CURRENT-STATUS.md

7. เพิมแอปลงหน้าจอโฮม

เมือเข้าจาก iPhone/iPad หรือ Android ระบบจะแนะนำการติดตังหนึงครังต่อเบราว์เซอร์ หลังเข้าเว็บประมาณ 5 วินาที หากกำลังเปิดหน้าล็อกอินหรือหน้าต่างอืนจะรอก่อน ปิดหรือกดไว้ทีหลังแล้วครังต่อไปจะไม่ขึนเอง เปิดอีกครังได้จาก เพิมลงหน้าจอโฮม ด้านล่าง sidebar ถ้าล้างข้อมูลเว็บหรือเปลียนเบราว์เซอร์อาจขึนใหม่ หากเปิดเป็นแอปอยู่แล้วจะซ่อนคำชวนติดตัง

iPhone / iPad

1. เปิด calendar.toomtoom.online ใน Safari หากเปิดจาก Discord ให้เปิดลิงก์ใน Safari ก่อน 2. แตะ แชร์ รูปสีเหลียมมีลูกศรขึน อาจอยู่ในเมนูเพิมเติมของ Safari 3. เลือนแล้วเลือก เพิมไปยังหน้าจอโฮม (Add to Home Screen) 4. ถ้ามี เปิดเป็นเว็บแอป (Open as Web App) ให้เปิด ตังชือแล้วแตะ เพิม 5. เปิดไอคอน Tutel☐ จากหน้าจอโฮม

หาตัวเลือกไม่พบ ให้เลือนเมนูแชร์ลงแล้วเลือก แก้ไขการทำงาน (Edit Actions) เว็บไม่สามารถเรียกหน้าติดตังแบบ Android บน iOS ได้ การอนุญาตแจ้งเตือนเป็นอีกขันตอนในตังค่าของแอป

Android

กด ติดตังแอป แล้วกดยืนยันของเบราว์เซอร์ เมือเบราว์เซอร์รองรับและพร้อมให้ติดตัง ถ้าไม่ขึนให้เปิดใน Chrome แล้วเลือกเมนู ☐ → ติดตังแอป / เพิมลงในหน้าจอหลัก ชือเมนูขึนกับเบราว์เซอร์

คู่มือบนเว็บ รองรับมือถือและเปลียนธีมได้ ยังไม่ได้ทดสอบการติดตังจริงบนเครือง iOS/Android ในการอัปเดตนี

อ้างอิง: Apple, MDN

Public default and loading screen (10 October 2026)

The default public view has no selected group and shows "ยังไม่มีปฏิทิน". GET /api/public/events reads only the shared, published dataset, without group-local activities or group labels. It does not depend on CS SKRU membership/visibility. Signed-in users can still resume their selected calendar; explicit group links retain their group context and existing access checks.

public/boot.js displays an animated turtle splash while the initial session, group, catalog and event data load. It ends immediately on tutel:ready, with no artificial minimum delay. A slow request exposes retry after 15 seconds; load failure exposes an error and retry. prefers-reduced-motion disables animations. Installation onboarding waits until the loading overlay closes. Native operating-system splash screens remain controlled by the browser/OS; this animation runs inside the web app.

ลบปฏิทินและกู้คืน

เฉพาะเจ้าของปฏิทิน: เปิดเมนูกลุ่ม → จัดการกลุ่ม → ลบปฏิทินนี้ แล้วพิมพ์ชื่อปฏิทินให้ตรงเพื่อยืนยัน ผู้จัดการ ผู้แก้ไข และผู้ดูแลเซิร์ฟเวอร์ไม่ได้สิทธิ์ลบจากบทบาทเหล่านั้น

กลุ่มจะอยู่ในถังขยะ 30 วัน สมาชิกเข้าไม่ได้ ระบบแจ้งเตือนของกลุ่มหยุด และคำเชิญเดิมถูกยกเลิก
เจ้าของกู้คืนได้จากเมนูกลุ่ม → ถังขยะปฏิทิน → กู้คืนปฏิทิน กิจกรรม สมาชิก และการตั้งค่าจะกลับมา
แต่ต้องสร้างคำเชิญใหม่ หากกลุ่มถูกระงับก่อนลบ การกู้คืนจะยังคงสถานะระงับเดิมไว้

เมื่อครบกำหนด ระบบลบกิจกรรมเฉพาะกลุ่ม สมาชิก คำเชิญ การเชื่อม Discord
และประวัติแจ้งเตือนของกลุ่มออกจากฐานข้อมูลที่ใช้งานจริง วันทั่วไปที่ใช้ร่วมกันและบัญชีผู้ใช้ยังอยู่
การลบนี้ไม่ได้ล้างไฟล์สำรองหรือประวัติการตรวจสอบซึ่งมีนโยบายเก็บรักษาแยกกัน
ข้อความที่ส่งไปแล้วหรือการส่งที่เริ่มทำงานแล้วเรียกคืนไม่ได้ ส่วนระบบแจ้งเตือนของบอทเดิมแยกจากเว็บนี้
การลบผ่านเว็บยังไม่หยุดการแจ้งเตือนของบอทเดิมจนกว่าจะเปลี่ยนไปใช้ worker ของระบบกลุ่ม

รายละเอียดสำหรับผู้พัฒนา: Group deletion internals

คู่มือระบบกลุ่มและกิจกรรม

เมนูไม่รก

หน้าปฏิทินยังเป็นหน้าหลัก กดชื่อกลุ่มเพื่อค้นหา เปลี่ยนกลุ่ม สร้าง/เข้าร่วม เลือกดูหลายกลุ่ม เปิดถังขยะ หรือออกจากกลุ่ม
การจัดการกลุ่มรวมคำเชิญ กิจกรรมทั้งหมด ช่องแจ้งเตือน Discord ส่งออก และประวัติ ส่วนบัญชีของฉันรวมบัญชีที่เชื่อม
คำขอโอนเจ้าของ และอุปกรณ์ที่เข้าสู่ระบบ การจัดการกิจกรรมรองอยู่ใน “จัดการและประวัติ”
ช่องฉบับร่างและกิจกรรมซ้ำจะพับไว้ก่อน

ออกจากกลุ่มและโอนเจ้าของ

สมาชิกออกเองได้ กิจกรรมที่เคยสร้างยังอยู่และไม่รับแจ้งเตือนกลุ่มอีก เจ้าของต้องโอนให้สมาชิกที่ยอมรับก่อน
หรือย้ายปฏิทินเข้าถังขยะ ผู้จัดการนำสมาชิกและผู้แก้ไขออกได้ แต่เอาเจ้าของหรือผู้จัดการอีกคนออกไม่ได้
หากต้องห้ามกลับเข้ากลุ่มให้ใช้ระงับ การนำออกเพียงอย่างเดียวไม่ได้ห้ามรับคำเชิญใหม่

คำขอโอนเจ้าของใช้ได้ 7 วัน เจ้าของเดิมยังมีสิทธิ์จนผู้รับยอมรับ ผู้รับต้องยังเป็นสมาชิกที่ไม่ถูกระงับ
หลังยอมรับเจ้าของเดิมจะเป็นผู้จัดการ ผู้ส่งยกเลิกได้ ผู้รับปฏิเสธได้ และการลบกลุ่มจะยกเลิกคำขอที่ค้าง
การรับบทบาทไม่ได้เพิ่มสิทธิ์เข้าถึง control panel เซิร์ฟเวอร์

ผู้ที่ออกหรือถูกนำออกจะไม่ถูกคำเชิญอีเมลเดิมดึงกลับเข้ากลุ่มอัตโนมัติเมื่อ login
แต่กดรับคำเชิญที่ยังใช้ได้เองเพื่อกลับเข้าได้ สิทธิ์สมาชิกเดิมไม่ถูกเปลี่ยนด้วยคำเชิญ การนำเข้า CSV
จะแสดงจำนวนและข้ามอีเมลที่ยืนยันแล้วและเป็นสมาชิกอยู่ ต้องแก้อีเมลผิดและรายการซ้ำก่อนส่ง
สถานะผู้ให้บริการรับอีเมลไม่ยืนยันว่าถึงกล่องขาเข้า

ดูหลายกลุ่ม

เริมต้นเห็นเฉพาะกลุ่มทีกำลังเลือก เมนู "ปฏิทินทีแสดงร่วมกัน" ให้ตีกกลุ่มอืนและจำไว้ในบัญชี
กิจกรรมใหม่ยังเพิมลงกลุ่มปัจจุบัน ระบบตรวจสิทธิ์ทุกกลุ่มทีเลือกและตัดกลุ่มทีออกหรือถูกระงับออก
วันทัวไปแสดงครังเดียว ไม่คัดลอกลงแต่ละกลุ่ม รายละเอียด รายการรายวัน และ tooltip ระบุชือกลุ่ม หน้าเว็บทัวไปของผู้ไม่ login มีเฉพาะวันทัวไป ส่วนลิงก์กลุ่มสาธารณะดูรายการทีเผยแพร่ได้โดยไม่ login กลุ่มส่วนตัวยังต้องมีสิทธิ์

ฉบับร่างและกิจกรรมซ้ำ

เลือกบันทึกเป็นฉบับร่างเพือเก็บงานก่อน ยังไม่เผยแพร่หรือแจ้งผู้ตรวจ เมือต้องการส่งให้กดส่งฉบับร่าง
ระบบใช้กฎอนุมัติของกลุ่ม การไม่อนุมัติต้องระบุเหตุผล ผู้ทีไม่ได้สิทธิ์เผยแพร่โดยตรงจะต้องผ่านกฎอนุมัติอีกครังเมือแก้ไข

กิจกรรมทีเพิมในกลุ่มยกเลิกได้โดยยังเก็บประวัติ หรือย้ายเข้าถังขยะและกู้คืนภายใน 30 วัน การกู้คืนคืนสถานะเดิม
ไม่บังคับเผยแพร่รายการทีรออนุมัติหรือเคยยกเลิก กิจกรรมทีนำเข้าหรือวันกลางต้องแก้ทีต้นทาง

ดังซ้ำทุกวัน สัปดาห์ หรือเดือนได้ถึงหนึงปี ระบบเก็บกิจกรรมหลักหนึงรายการและคำนวณวันทีตอนอ่าน
ไม่สร้างสำเนาจำนวนมาก วันที 31 จะข้ามเดือนทีไม่มีวันที 31 ปุมแก้หลักแก้ทังชุด
เมนูรองของแต่ละครังให้ผู้ทีมีสิทธิ์เผยแพร่แก้เฉพาะครังหรือยกเลิกครังนันได้ ถ้าต้องผ่านการอนุมัติให้แก้ทังชุดเพือส่งตรวจ
การแก้ทังชุดไม่ล้างข้อยกเว้นเดิมอัตโนมัติ

ประวัติบอกผู้ทำ เวลา และประเภทการทำงาน ไม่ได้เก็บภาพเนือหาก่อน/หลังทุกฉบับ การส่งออกเป็น JSON
มีเนือหากิจกรรมเฉพาะกลุ่มและกฎซ้ำ ไม่มี secret อีเมลสมาชิก หรือข้อมูล session ไฟล์ส่งออกไม่ใช่ backup เต็ม:
ไม่รวมข้อยกเว้น สมาชิก และประวัติ ต้องใช้ไฟล์สำรอง SQLite สำหรับกู้ระบบทังหมด

แจ้งเตือนและบัญชี

ตังแจ้งเตือนกิจกรรมใหม่ ผลตรวจ ก่อนเริม และการเปลียน/ยกเลิกแยกตามกลุ่มได้
เปิดสรุปวันนีเพือรวมกิจกรรมทีตรงหมวดเป็นการแจ้งครังเดียวตามเวลาเตือนทังวัน ช่วงงดรบกวนใช้เวลาไทย
งดส่งเข้าอุปกรณ์แต่เก็บในเว็บ ไม่ส่งย้อนหลังเมือพ้นช่วง ไม่เปลียนเวลาแจ้งในห้อง Discord
และต้องตังเวลาเริม/สินสุดต่างกัน ข้อความทีส่งหรือเริมส่งแล้วเรียกคืนไม่ได้ งาน Discord
ทียังรอและมีข้อมูลกิจกรรมเก่าจะถูกยกเลิก ไม่ส่งสรุปรายวันซ้ำอัตโนมัติหลังแก้กิจกรรม

หน้าอุปกรณ์แสดงชนิดโดยประมาณและวันหมดอายุ session เลือกออกจากเครืองอืนหรือทังหมดทีไม่ใช่เครืองปัจจุบันได้
บัญชีทีเชือมต้องเหลืออย่างน้อยหนึงบัญชีจึงถอดอีกบัญชีได้ และการถอดจะออกจาก session อืน การออกจาก session
ไม่ได้ยกเลิก Push subscription แยกของอุปกรณ์ ให้ปิดแจ้งเตือนอุปกรณ์ผ่านการตังค่าหากต้องการด้วย

ส่วนทีต้องแยกให้เข้าใจ

โค้ดปฏิทินจัดการข้อมูล กลุ่ม และงานแจ้งเตือน ส่วน TutelBot รับงานเพือส่ง Discord
การเปิดระบบกลุ่มของบอทต้องย้ายช่องเดิมและตัง CALENDAR_GROUPS_ENABLED พร้อมกันทัง homeserver/Oracle
จึงยังคงระบบเดิมไว้ก่อน แอป Tutel Calendar ใน Discord Developer ใช้ OAuth ไม่ใช่บอทอีกตัว เมือเปิดระบบแล้วใช้
/calendar connect ในช่องเป้าหมาย เปิดลิงก์ด้วย Discord คนเดียวกับผู้สัง เลือกกลุ่มและยืนยัน จากนันตังเวลา หมวด
และทดสอบในช่องแจ้งเตือน Discord

เว็บยังรันบน homeserver บอทสำรอง Oracle ไม่ได้ทำให้เว็บสลับเครืองตาม ส่วนการโอนฉุกเฉินผ่าน control panel
หลักเป็นสิทธิ์ผู้ดูแลแพลตฟอร์มแยกจากขันตอนเจ้าของทัวไป มีประวัติตรวจสอบ

รายละเอียด API ตารางฐานข้อมูล โครงสร้างไฟล์ และข้อจำกัด: WORKFLOWS.md
งานปฏิทินนีตรวจโค้ดและจัดรูปแบบแล้ว ไม่ได้ทดสอบลบ/ออก/โอนกับกลุ่มจริงหรือส่งอีเมลเป็นชุด
การเริมบริการสำเร็จไม่ได้เท่ากับทดสอบครบทุกอุปกรณ์หรือ Push ส่วนบอทเพลงทดสอบ regression ทีเกียวข้องผ่าน 19 กรณีแล้ว

ประวัติและรายชื่อสมาชิก (10 ตุลาคม 2026)

สมาชิกทุก role อ่านรายชื่อ สิทธิ์ และเวลาที่เข้าร่วมกลุ่มเดียวกันได้ พร้อมหน้าประวัติแบ่งหน้า แสดงว่าใครทำอะไรกับรายการไหน เวลาไทย ปุ่มจัดการยังจำกัด role บันทึกใหม่เก็บชื่อสำรองหลังลบรายการ ไม่สร้างประวัติเก่าย้อนหลัง ไม่แสดงอีเมลหรือ token คำเชิญ ดู คู่มือประวัติกลุ่ม สำหรับ API โครงสร้างและข้อจำกัด ต้องเริ่มเซิร์ฟเวอร์ใหม่เมื่อ deploy โค้ดรุ่นนี

Current source and learning material / โค้ดและสื่อเรียนรู้ปัจจุบัน

The repository conventions are documented in CODE-STYLE.md. The independent Learning Lab is at D:/Tutel-Learning-Lab, contains current snapshots of both repositories, and is not deployed or published with either project. Earlier architecture examples are explicitly identified as historical; current feature explanations take precedence.

Current feature guide / คู่มือการเปลี่ยนแปลงล่าสุด

Updated 10 October 2026. This page describes the current source; the readability cleanup is a local source change until deployed separately.

Groups and viewing links / กลุ่มและลิงก์ดูปฏิทิน

Open the selected group name in the top bar to open กลุ่มปฏิทิน. Everyone who may read that calendar can use คัดลอกลิงก์ปฏิทิน; management permissions are not required. Owners also see the same link in group management beside viewing visibility. Links have the form /g/<slug>.

Public viewing permits the group link without signing in. A private calendar still requires an authorized member session: copying a link does not change its visibility or grant membership. The default site view shows only shared general dates with no selected CS SKRU group. Shared dates are read once and combined with group activities, not cloned into each new group.

กดชื่อกลุ่มด้านบน → กลุ่มปฏิทิน → คัดลอกลิงก์ปฏิทิน สมาชิกและผู้ชมที่อ่านกลุ่มได้ก็คัดลอกได้
ปฏิทินส่วนตัวไม่ได้กลายเป็นสาธารณะเพียงเพราะส่งลิงก์ ลิงก์ดูปฏิทินกับลิงก์เชิญสมาชิกทำหน้าที่ต่างกัน

Invitations and account names / คำเชิญและชื่อบัญชี

Email and ordinary link invitations require explicit acceptance using any Google or Discord account, and allow one successful use. An invitation is not automatically accepted merely because the email matches. Anyone holding the link can use it before the recipient; avoid forwarding a single-use invitation unintentionally. Code invitations follow their configured use limit.

CSV columns are email,name,role; email is required, name is optional and role selects the invitation permission. Existing members are skipped by CSV import. Accepting an invitation while already a member consumes it without changing the saved membership role; role changes belong in member management.

ตั้งค่าของฉัน allows a custom display name, maximum 100 characters. Clearing it restores the current provider name. Authorized managers/owners can additionally see the original provider name and verified email; ordinary member listings do not expose email addresses.

Editing an activity from the calendar / แก้กิจกรรมจากปฏิทิน

Open your own editable group activity in the selected calendar and use แก้ไข in its detail dialog. This reuses the activity editor from กิจกรรมของฉัน. Imported/shared dates and activities from another selected context are not editable through this shortcut. The server checks authorization again; can_edit in the event response is only a UI hint.

Scheduled notifications / การแจ้งเตือนตามเวลา

Creating, editing, approving, cancelling or deleting an activity no longer sends event-change notifications. Audit history is retained and already delivered inbox items are not retroactively removed.

- Tomorrow summary: 12:00 Bangkok, if enabled.

- Today's summary: the user's saved day time; a new preference defaults to 07:00 Bangkok.

- Timed activities: configured lead time, then at the activity start, if enabled.

- All-day activity: covered by today's summary; when that summary is off, an individual day reminder may be used.

- Categories, quiet hours and prior opt-outs remain respected. No summary is sent for an empty set.

Quiet hours suppress device Push, while the web inbox still records the notification. Browser/OS permission and an active subscription are required for Push. Scheduled web reminders and the legacy Discord scheduler are separate; grouped Discord worker cutover is still pending. See Reminder policy.

Feedback and files / Feedback และไฟล์แนบ

Sign in, choose Feedback, add a title/message/category and optionally up to 3 JPG/PNG/WebP images, each up to 5 MB. A draft survives closing the dialog until the page reloads. X and Cancel close this dialog independently of other dialogs. The limit is 5 submissions per account per hour.

Images are decoded and resized to at most 1600 pixels per side, converted to static WebP and stored outside the public directory. Group managers do not gain access to the server's Feedback inbox. Only main-panel administrators can view all messages and set New / In progress / Done. There is no reply thread or attachment purge UI yet.

Developer reading order / ลำดับอ่านโค้ด

src/server.js → authentication/group access → feature routes → SQLite statements → browser modules. Read public/feedback.js for static templates and multipart upload; src/feedback/routes.js for validation/private file storage; src/integrations/control/routes.js for the privileged server-panel bridge. Read src/notifications/scheduler.js for reminders and src/notifications/service.js for deduplication/Push.

See Source readability, Developer handbook, API and current deployment. Format/syntax checks do not replace full browser, OAuth, audio or device tests.

Invitation links and display names / คำเชิญและชื่อที่แสดง

Current behavior - 10 October 2026

Email is the delivery destination, not a restriction on the accepting account. The holder of an email/link invitation signs in with any Google or Discord account and explicitly accepts. Email and link invitations allow exactly one successful acceptance; codes retain their configured use count. Startup also caps older email/link invitations at one use. Previously redeemed links are therefore exhausted; send a fresh invitation if needed.

OAuth login and listing groups no longer automatically redeem invitations by email matching. CSV sends a separate one-use link to each address. The first account to successfully accept owns that redemption. Merely viewing the URL or signing in does not consume it. Expired, revoked, suspended-group and blocked-membership failures do not consume it. The SQLite transaction serializes acceptance. A successful acceptance by an existing member also consumes the link but preserves the member's existing role; it does not promote/demote them or duplicate the join history.

อีเมลเป็นที่รับคำเชิญ ผู้ถือ link ใช้ Google หรือ Discord บัญชีใดก็ได้ ต้องกดรับคำเชิญหลังเข้าสู่ระบบ ลิงก์ใช้สำเร็จได้ 1 ครั้ง รวมถึงลิงก์เก่า ระบบไม่เข้ากลุ่มให้อัตโนมัติเพียงเพราะอีเมลตรงกัน CSV ส่งลิงก์แยกให้แต่ละคน
การเปิดอ่านเมลหรือกดดูเว็บยังไม่ใช้สิทธิ์ สมาชิกเดิมกดรับได้แต่สิทธิ์ไม่เปลี่ยน ผู้ที่ถูกระงับยังเข้าร่วมไม่ได้

Display names

ตั้งค่าของฉัน → ชื่อที่แสดง lets the signed-in user set a name of up to 100 characters. Initially it is the provider's profile name. A custom name survives subsequent OAuth sign-ins. Leaving the field blank restores the latest recorded provider name. This changes presentation across the account's groups, not identity, email, permissions or membership.

users.name remains the effective public name; additive custom_name and provider_name columns distinguish the override and latest provider name. Existing records seed provider_name from the current name during migration. Name snapshots already stored in audit/Feedback records remain historical snapshots.

The own-profile API is GET /api/account/profile and PUT /api/account/profile with {name}. Writes require the user's session and CSRF. It cannot edit another user's name.

Ordinary members see public display names in the directory. Calendar owners/managers and main-panel admins additionally see originalName and provider-verified emails; these private fields are omitted for ordinary readers. Only verified emails already supplied by Google/Discord are available; Discord may not supply an email. The provider name is the last recorded provider profile name, not an immutable/legal name.

ตั้งชื่อเองได้ใน ตั้งค่าของฉัน ถ้าเว้นว่างจะกลับไปใช้ชื่อจากบัญชี Google/Discord
ชื่อที่ตั้งใช้ทุกกลุ่มและไม่ถูกเขียนทับตอน login หน้าแอดมินแสดงชื่อที่ใช้ พร้อมชื่อบัญชีเดิมและอีเมลที่ยืนยันแล้ว
สมาชิกทั่วไปไม่เห็นอีเมลของคนอื่น การตั้งชื่อไม่เปลี่ยนสิทธิ์หรือประวัติเดิม

Deployment

Deploy the Calendar auth, group schema/invitation routes, account settings, members/control API and corresponding web assets together. The main panel's member renderer must also be updated. Do not copy

.env, live databases or private attachments into Git or release archives. Schema changes are additive; take a consistent SQLite backup before restart. See FEEDBACK.md for attachment storage requirements.

การแจ้งเตือนกิจกรรม / Event reminders

อัปเดต 10 ตุลาคม 2569: แจ้งเตือนกิจกรรมเฉพาะตามกำหนดเวลา ไม่ส่งเมื่อเพิ่ม แก้ไข ลบ ยกเลิก หรืออนุมัติ รายการเหล่านี้ยังอยู่ในประวัติกลุ่ม

- วันพรุ่งนี้: สรุปเวลา 12:00 น. เวลาไทย เปิด/ปิดได้ในการตั้งค่าของฉัน

- วันกิจกรรม: สรุปตามเวลาเตือนทั้งวันที่ผู้ใช้เลือก เปิด/ปิดได้

- กิจกรรมมีเวลา: เตือนก่อนเริ่มตาม leadMinutes และเมื่อถึงเวลาเริ่ม ตามตัวเลือกเตือนกิจกรรม

- กิจกรรมทั้งวัน: ถ้าปิดสรุปรายวันแต่ยังเปิดเตือนกิจกรรม จะเตือนวันจริงตาม dayTime;
ถ้าเปิดสรุปรายวันจะรวมในสรุปเพื่อไม่เตือนซ้ำ

- เคารพหมวดที่เลือกและช่วงงดรบกวน ค่าเดิมที่ผู้ใช้ปิดสรุปรายวันไว้ยังคงเดิม

- Discord ยังคงใช้การตั้งค่าของแต่ละกลุ่ม/ช่อง: วันพรุ่งนี้ตอนเที่ยง, วันจริงตาม dailyTime, ก่อนเริ่มเมื่อเปิด timed ไม่ส่งจากการแก้ไขกิจกรรม

- การแจ้งเตือนบัญชี เช่น ขอรับโอนเจ้าของ และการกดทดสอบอุปกรณ์ยังทำงาน

- แจ้งเตือนที่ส่งไปแล้วก่อนอัปเดตยังอยู่ในกล่องข้อความ

เปิดกิจกรรมของตนเองจากปฏิทินแล้วกดแก้กิจกรรมได้ เช่นเดียวกับหน้ากิจกรรมของฉัน เซิร์ฟเวอร์ส่ง can_edit จากสิทธิ์จริงโดยไม่เผย owner_id ในรายการปฏิทิน; API แก้ไขยังตรวจบัญชีและสิทธิ์กลุ่มทุกครั้ง วันสำคัญจากแหล่งกลาง/รายการนำเข้าแก้ไม่ได้จากหน้านี้

English

Event notifications are scheduled reminders only: tomorrow's summary at 12:00 Bangkok time, the current-day summary at the configured dayTime, and timed reminders before/start. Creation, edits, removal/cancellation, publication and review outcomes no longer trigger event notifications. Audit history is retained. Existing user opt-outs and quiet hours are respected. Discord uses its per-binding reminder configuration. Account notifications and explicit device tests remain available.

Members can edit their own events from the calendar detail dialog. The event list supplies a permission-derived can_edit flag; write endpoints still enforce session, CSRF and group permissions. Imported/shared source events remain read-only.

Feedback / ส่งความคิดเห็น

User workflow

Sign in with Google or Discord, then choose Feedback beside account actions on desktop or in the mobile sidebar. Select Problem, Suggestion or Other, enter a title (120 characters) and description (5,000 characters), and optionally attach up to three JPG, PNG or WebP images, each at most 5 MB. Previews support removal before submission. Closing the dialog preserves the draft in memory until reload; a successful submission clears it.

The form explains that account name, applicable group name, page path and submission time accompany the message. Invite/connect tokens and query strings are not stored in the page path. Group context is captured when the dialog opens; only a group the user belongs to can be associated with the message. Feedback does not require group management permission.

สำหรับผู้ใช้

เข้าสู่ระบบก่อน แล้วกด Feedback ใกล้ส่วนบัญชีบนคอม หรือใน sidebar บนมือถือ เลือกแจ้งปัญหา / เสนอแนะ / อื่น ๆ กรอกหัวข้อและรายละเอียด แนบรูปได้ 3 รูป รูปละ 5 MB มีภาพตัวอย่างและปุ่มลบก่อนส่ง
การปิดหน้าต่างยังเก็บร่างไว้ในหน้านี้ เมื่อส่งสำเร็จจึงล้างร่าง

ระบบส่งชื่อบัญชี กลุ่มที่เกี่ยวข้อง หน้าที่เปิดและเวลาส่งร่วมกับข้อความ กล่องรับอยู่ใน Control Panel หลัก แอดมินกลุ่มปฏิทินไม่มีสิทธิ์อ่านกล่องนี้ ไม่ใช่ระบบแชทและยังไม่มีการตอบกลับหรือแจ้งเตือนผลการดำเนินการให้ผู้ส่งอัตโนมัติ

Administration

The Tutel Hub main panel provides กล่อง Feedback, unread counts, 50-item pagination, category/status filters, message detail, private image viewing and explicit read/status updates. Opening a detail marks it read. Statuses are independent of the read flag: new, in_progress, done. A separate control-panel admin session is required. The Calendar browser's platform-admin flag does not grant access to the service inbox.

API and authorization

- POST /api/feedback: authenticated Calendar session + CSRF and origin protection; multipart fields category, title, message, groupId, pagePath; images use repeated images fields.

- GET /api/feedback/images/:id: authenticated original submitter only. Attachment URLs are not public links.

- GET /internal/v1/control/feedback?page=1&status=&category=: service control secret, paginated {items,page,hasMore,unread}.

- GET /internal/v1/control/feedback/:id: control secret; message and attachment IDs.

- PUT /internal/v1/control/feedback/:id: control secret; optional {status,read}; stores update actor and time.

- GET /internal/v1/control/feedback/images/:id: control secret; WebP bytes.

The main panel proxies these routes through /api/calendar-admin/feedback… after enforcing its own login/admin checks and CSRF for writes. Neither service secret nor Calendar cookies are sent to the panel

browser.

Storage and operations

src/feedback/routes.js creates additive SQLite tables feedback and feedback_images. Messages preserve sender/group names as submission-time snapshots. Images are private files; the default directory is feedback/ beside DATABASE_PATH, outside the public web directory. FEEDBACK_UPLOAD_DIR optionally overrides it and must remain outside public/static directories and version control.

Multer holds bounded multipart input in memory; Sharp checks the decoded format, rejects unsupported/animated images, bounds decoded pixels at 25 million, rotates and resizes to at most 1600 × 1600, then re-encodes WebP without original metadata. Processing is sequential within each request. A process-local cap permits two concurrent uploads; users can submit five messages per hour, enforced again inside the SQLite transaction. File writes use opaque UUID names and restrictive permissions. On failure, newly written files are removed and the database transaction rolls back.

Back up both the SQLite database and image directory. SQLite-only backups will not include attachments. There is currently no automatic retention purge, operator deletion UI, malware scanning service, or shared image storage across hosts. Configure private backup and disk monitoring accordingly. Existing account/group removal does not automatically erase Feedback snapshots; support removal is an operator responsibility. Group managers cannot access Feedback just because it mentions their group.

Install dependencies (npm ci) and restart the Calendar service after deploying this feature; Sharp requires a compatible native package for the target platform. Update the main panel source and restart its service to expose the inbox. This document describes implementation, not proof that a production deployment or end-to-end test has happened.

Current status - 10 October 2026

Current feature guide / คู่มือคุณสมบัติปัจจุบัน

Calendar web runs on homeserver through its existing HTTPS tunnel. Public general dates are shared once; selected groups hold their own activities. Google/Discord OAuth, queued invitations and accepted email delivery have been configured. One explicitly authorized Gmail invitation was observed in the inbox; no mass CSV test was sent.

Implemented: mobile sidebar/themes, initial loading screen and installation guide, public default without CS SKRU selection, calendar trash with 30-day recovery, leaving/removing members, seven-day accepted ownership transfer, CSV existing-member skip, multi-group display, event drafts/cancellation/trash/history, bounded virtual recurrence and occurrence exceptions, JSON export, daily web summaries and quiet hours, account linking/unlinking and session controls.

See WORKFLOWS.md and WORKFLOWS.th.md for exact scope and API contracts. Calendar workflow changes were reviewed/formatted and the service startup is checked after deployment. No destructive calendar/member/ownership production test was performed. Physical-device installation/Push validation remains pending.

Grouped Discord worker is prepared but not enabled: CALENDAR_GROUPS_ENABLED=0 remains until legacy channel migration and coordinated bot-host cutover. Original Discord reminders are separate and are not automatically disabled by web group deletion. Calendar OAuth app is not a second bot runtime. Website hosting does not fail over to Oracle. Main server-panel APIs remain privileged and separate from group managers.

Music Loop default is off for guilds without a saved preference. Skip in a one-song loop restarts that song; a queued successor takes priority when skipping a song loop. Intentional decoder termination no longer marks playback failed. Nineteen relevant automated regressions passed; actual Discord audio was not exercised by synthetic tests. See repository history for source publication; runtime deployment is separate.

Group history and directory (10 October 2026)

All authorized group members can read member names, group roles and join timestamps, and a paginated activity history with actor names, item titles and Bangkok timestamps. Management writes remain restricted. New audit snapshots preserve readable names after item deletion; old actions are not reconstructed. No invitation tokens or email addresses are exposed. See Group history and directory for API changes, implementation and retention limitations. Server source changes require a restart as part of deployment.

Feedback, identity, scheduled reminders and source cleanup

The homeserver has the Feedback submission/inbox integration, custom display names with privileged original-name/email detail, any-account single-use email/link invitations, own-event editing shortcut, scheduled-only event notifications and a copy-calendar-link control for all authorized viewers. Existing inbox history remains intact. Website hosting remains on homeserver; no Oracle work is part of this cleanup.

The new project-wide readability pass reformats control-flow blocks, local declarations, embedded HTML and long SQL. It is a local source change until a separate deployment; formatter/syntax validation is not end-to-end behavioral testing. See CURRENT-FEATURES.md and CODE-STYLE.md.

Source readability / แนวทางเขียนโค้ดให้อ่านง่าย

Updated 10 October 2026. These conventions apply to the entire repository.

Formatting

- ESM JavaScript, explicit .js imports, two spaces, LF, semicolons and single quotes.

- Prettier uses a 100-column target. HTML uses htmlWhitespaceSensitivity: ignore so nested tags can occupy separate lines.

- Use npm run format before review and npm run format:check to inspect consistency. Formatting does not prove runtime correctness.

- Keep credentials, runtime databases, uploads, backups and generated lockfiles outside formatter input where configured.

Reading order inside a module

1. Imports and configuration constants. 2. Small helpers with a single clear responsibility. 3. Exported registration/setup functions and the workflows they coordinate. 4. Resource teardown beside the code that owns the resource.

Use one declaration per statement. Give related declarations one paragraph; separate validation, state changes, I/O and rendering with blank lines. Every if, else and loop body has braces, including early returns. Leave else if as one chain. Do not add blank lines after every statement.

HTML in JavaScript

Mark static HTML templates with /* HTML */ so Prettier also formats the nested markup. Long forms should be a named template constant. Attributes wrap when needed and closing tags remain aligned. This comment is a formatting hint, not an HTML sanitizer.

const FORM = /* HTML */

<form class="example-form">

<label>

Title

<input name="title" required />

</label>

<button type="submit">Save</button>

</form>

function renderName(element, name) { element.textContent = name; }

Use textContent/DOM creation for user-controlled text. Never interpolate submitted titles, names or messages into trusted markup. Preserve DOM identifiers, permission checks and cache-version conventions while

reorganizing source.

SQL and authorization

Put long SQL into multiline templates with clauses and field lists separated. Keep bound placeholders and .get/.all/.run arguments in matching order. Do not interpolate user input into SQL or construct arbitrary table/column names.

const query = db.prepare(

SELECT id, name

FROM users

WHERE id = ?

const user = query.get(userId);

This illustration explains formatting; it is not a replacement for a route's authentication, group authorization, CSRF or input validation. SQLite SQL whitespace can be reformatted outside quoted values; strings inside quotes must stay unchanged.

Boundaries and comments

Keep HTTP handlers, domain decisions, persistence and browser presentation in their existing feature folders. The music repository owns Discord audio and the private server panel. Calendar owns web accounts, groups, activities, Feedback storage and SQLite. Communicate through the existing protected HTTP contract; never share a live SQLite file or browser-visible service secret.

Comments explain intent, resource ownership, security assumptions and edge cases. Avoid narrating obvious assignments. Split a large function when a named workflow boundary exists; moving lines solely to make a file shorter creates unnecessary indirection.

ภาษาไทย

โค้ดหนึงย่อหน้าควรทำหน้าทีเดียว เช่น เตรียมข้อมูล ตรวจสิทธิ์ ตรวจ input บันทึกข้อมูล หรือวาดหน้า เว้นบรรทัดเมือเปลียนหน้าที ใช้ชือทีอ่านแล้วรู้ว่าเก็บอะไร แยกตัวแปรแต่ละตัว และใส่วงเล็บปีกกาทุกเงือนไข/ลูป เพือให้เห็นขอบเขตชัดเจน

HTML ทีอยู่ใน JavaScript ต้องจัด nested tags ด้วย ไม่ใช่จัดเฉพาะ JavaScript รอบนอก ส่วน SQL ยาวแบ่ง SELECT/FROM/JOIN/WHERE และรายการคอลัมน์ แต่ยังต้องใช้ parameter binding เหมือนเดิม การจัดรูปแบบไม่ใช่การอุดช่องโหว่ และไม่ใช่การทดสอบเสียง OAuth หรือการส่งอีเมล