关于完成修改后,提交修改步骤:

1. git status -> 查看需要提交的内容;

```
android@ubuntu:~/work/v2520Debug/baseline/packages/apps$ git status
尚未暂存以备提交的变更:
(使用 "git add <file>..." 更新要提交的内容)
(使用 "git checkout -- <file>..." 丢弃工作区的改动)
```

- 2. repo sync . -> 同步 , 防止修改冲突 ;
- 3. git add /文件路径 -> 将所有修改的文件添加到缓存区中将所有修改的文件添加到缓存区中

```
android@ubuntu:~/work/v2520Debug/baseline/vendor/tinno/platform/configs$ git add
```

4. git status

```
android@ubuntu:~/work/v2520Debug/baseline/vendor/tinno/requirment/sym_bd$ git status
要提交的变更:
(使用 "git reset HEAD <file>..." 撤出暂存区)
```

5. git commit -m "<REQ><jiraid><jiratitle>" -> 提交到本地仓库 git commit -m "<REQ><CFCAMBDA-106><V2520AN\_SYM\_BD\_6.0:[CMIS011953][BD][5288] [Camera] It does not show the name of preview photo or videos.[Always]>"

```
android@ubuntu:~/work/v2520Debug/baseline/vendor/tinno/platform/configs$ git commit -m "<REQ:
IS011953][BD][5288] [Camera] It does not show the name of preview photo or videos.[Always]>"
6. gitk.
                                                                     -> 查看是否提交的本地仓
```

7. git branch -a -> 获取所有分支

```
ndroid@ubuntu:~/work/v2520Debug/baseline/vendor/tinno/platform/configs$ git branch -a
             -> tinno/V2520AN 6.0 SYM BD V1.1
```

7. git push tinno HEAD:分支 ->提交到远程分支上。

android@ubuntu:-/work/v2520Debug/baseline/vendor/tinno/platform/configs\$ git push tinno HEAD:V2520AN\_6.0\_SYM\_BD\_V1.1 To gerriti89:/platform/sc/sc7731c/platform/vendor/tinno/platform

8. repo sync.

如果在提交过程中出现了错误,

1. git reflog

```
אבין). gtt push --הפרוף אינון אינון מטענ המגריוטואמרעט אין אינון מין אינון אי
                                                                                                                                                                                                                                                git reflog
[1]+ 已停止
```

2. git cherry-pick id

```
baseline/vendor/tinno/platform/: discarding 1 commits
android@ubuntu:-/work/v2520Debug/baseline/vendor/tinno/platform/configs$ git cherry-pick de98bfe
请执行如下命令: sudo apt-get install python-mysqldb
```

3. 如果提交过多,可以用它来删除 ,git未正式提交之前,可以用git reset HEAD

```
g提交的变更:
(使用 "git reset HEAD <file>..." 撤出暂存区)
 未暂存以备提交的变更:
(使用 "git add <file>..." 更新要提交的内容)
(使用 "git checkout -- <file>..." 丢弃工作区的改动)
```

git diff src/com/android/fmradio/FmRecordActivity.java 对比 git checkout XXXXX 还原文件。

合原型的某一条记录,通过id合并

- 1. gitk --all &
- 2. git cherry-pick (-nr 不提交)id; 合并 id 原型
- 3. git reset (--h 全部还原暂存区)

```
androt/dubuntu:-/work/v2520Ctx/baseline/packages/apps/Camera2$ gitk --all&
[1] 23087
androt/dubuntu:-/work/v2520Ctx/baseline/packages/apps/Camera2$ git cherry-pick 702fa0d570297c78017ea9d51026a5010157b841
```

- 3. git commit -m "<>"
- 4.git branch -a
- 5. git push tinno HEAD:

合并原型的所有记录,以分支的方式进行合并:

1. 同步最新的代码: repo sync, 找到原型git branch -a。原型一般是基线项目。

```
android@ubuntu:~/0_test_yy/3800/frameworks$ git branch -a
* (非分支)
remotes/m/sw -> tinno/V3800AN_7.0_IVA_AF_V1.1
remotes/tinno/ALPS-MP-NO.MP2-V1_TINNOOS80_WE_N_KERNEL_patch
remotes/tinno/MT6580_7.0_DEV_V1.1
remotes/tinno/MT6580_7.0_FEATURE_V1.1
remotes/tinno/MT6580_7.0_V1.1
remotes/tinno/V2600BN_7.0_LAX_TEL_MX_V1.1
remotes/tinno/V2600BN_7.0_LAX_TEL_MX_V1.1
remotes/tinno/V2600BN_7.0_LAX_TEL_MX_V1.1
remotes/tinno/V2600BN_7.0_LAX_TEL_MX_V1.1
remotes/tinno/V2600BN_7.0_LAX_TEL_MX_V1.1
remotes/tinno/V3610AN_7.0_V2.1
remotes/tinno/V3610AN_7.0_SIN_KH_V1.1
remotes/tinno/V3610AN_7.0_V1.1
remotes/tinno/V3610AN_7.0_V1.1
remotes/tinno/V3710AN_7.0_BQ_RU_BR1_V1.1
remotes/tinno/V3710AN_7.0_BQ_RU_BR1_V1.1
remotes/tinno/V3710AN_7.0_BQ_RU_BR1_V1.1
remotes/tinno/V3710AN_7.0_BQ_RU_BR1_V1.1
remotes/tinno/V3710AN_7.0_NCL_ZA_V1.1
remotes/tinno/V3710AN_7.0_NCL_ZA_V1.1
remotes/tinno/V3710AN_7.0_V2.1
remotes/tinno/V3710AN_7.0_V2.1
remotes/tinno/V3710AN_7.0_V2.1
remotes/tinno/V3710AN_7.0_V2.1
remotes/tinno/V3710AN_7.0_V2.1
remotes/tinno/V3710AN_7.0_V2.1
remotes/tinno/V3710AN_7.0_V2.1
remotes/tinno/V3710AN_7.0_V2.1
```

2. repo forall -p -c git merge <原型分支TAG> > merge\_0211.log

```
android@ubuntu:-/0_test_yy/3800$
android@ubuntu:-/0_test_yy/3800$ repo forall -p -c glt merge remotes/tlnno/V3710AN_7.0_V2.1 > merge_0211.log
android@ubuntu:-/0_test_yy/3800$
android@ubuntu:-/0_test_yy/3800$
android@ubuntu:-/0_test_yy/3800$
```

3. 提交修改。如果没有冲突直接push

```
android@ubuntu:-/0_test_yy/3800/kernel-3.18/drivers$ gitk
android@ubuntu:-/0_test_yy/3800/kernel-3.18/drivers$ git push tinno HEAD:V3800AN_7.0_IVA_AF_V1.1
Total 0 (delta 0), reused 0 (delta 0)
remote: Processing changes: (-)
remote: Processing changes: refs: 1, done
To gerrit207:/mto580n/platforn/kernel-3.18/drivers
2db5585..80c8dc9 HEAD -> V3800AN 7.0 IVA AF V1.1
```

如果有冲突, 先修改, 在commit, 最后push

```
and otogobuntu:-/o_test_yy/3800/kernel-3.18/drivers$ git commit -m "<REQ><PUBLIC-2><合并原型>"

出版文章性例会。

无文件要提交,干净的工作区

android@ubuntu:-/0_test_yy/3800/kernel-3.18/drivers$ gitk

android@ubuntu:-/0_test_yy/3800/kernel-3.18/drivers$ git push tinno HEAD:V3800AN_7.0_IVA_AF_V1.1

Total 0 (delta 0), reused 0 (delta 0)

remote: Processing changes: (-)

remote: Processing changes: refs: 1, done

To gerrit207:/mto580n/platforn/kernel-3.18/drivers

2db5585..80c8dc9 HEAD -> V3800AN_7.0_IVA_AF_V1.1
```

如果想回退到某一个ID号,仅仅是指针指向了当前ID。

git checkout id

```
ndroid@ubuntu:~/work/V3800_AF/3800/kernel-3.18/drivers$ gitk
ındroid@ubuntu:-/work/V3800_AF/3800/kernel-3.18/drivers$ git checkout 7124b867595cf7d5d80c43137095aff4c5b4b5fc
```

如果是回退服务器,可以强推

git push -f tinno HEAD:V3991AN\_6.0\_PATCH

如果仅仅对某一个ID进行回退,本地的代码。

# git log -number, 查看记录

```
thor: pan.ye <pan.ye@tinno.com>
te: Mon Jan 16 09:19:51 2017 +0800
 <PATCH><SCM-5><ALPS03125401 TINNO6580_NE_N_GPRS_HSPA_MOLY.WR8.W1449.MD.WG.MP.V91.5.P4 集成基线代码补丁,问题描诉:[Description]: NA</pre>
hor: pan.ye <pan.ye@tinno.com>
e: Fri Jan 13 11:36:35 2017 +0800
```

#### git revert id

```
ndroidgbuntu:-/work/test/3800/nodenS
qfoidgbuntu:-/work/test/3800/nodenS qtt revert bale013afd0d491cescBala20eacb370f7512f8f
分离头指针 e134cSa] Revert -<a href="ref">ref">ref">ref">ref"</a> -<a href="ref">ref">ref">ref"</a> -<a href="ref">ref">ref"</a> -<a href="ref">ref">ref"</a> -<a href="ref">ref">ref"</a> -<a href="ref">ref">ref"</a> -<a href="ref">ref"</a> -<a href">ref"</a> -<a href="ref">ref"</a> -<a href="
                  files changed, 4 insertions(+), 52 deletions(-) lete mode 188448 Patchlist V91.5 P4.txt each mode 180448 Patchlist V91.5 P4.txt each mode 180444 Patchlist V91.5 P4.txt each mode 180444 Patchlinos589 WE.N. GPBS/DEFA each mode 180444 Patchlinos589 WE.N. SPBS/DEFA each mode 180444 Patchlinos589 WE.N. SPBS/DEFA each mode 180444 Patchlinos589 WE.N. SPBS/DEFA
```

#### git commit -amend -m

```
<PATCH><SCM-5><ALPS03125401 TINNO6580_WE_N_GPRS_HSPA_MOLY.WR8.W1449.MD.WG.MP.V91.5.P4 集成基结</pre>
                              MP.V91.5.P4 集成基线代码补丁,问题描诉:[Des
```

# git branch -a

```
roid@ubuntu:~/work/test/3800/modem$
roid@ubuntu:~/work/test/3800/modem$ git branch -a
分集日 haioNi3 )
```

git push

或者在回退某一条记录时:

可以直接git revert id,然后会弹出一个vi编辑界面,进行编辑,将id号和标题进行处理。然后再push即可(去掉标题的 引号,及引号外面的东西,和commitid)。

```
hanges: refs. 1, done
MIADATOR / MORANGE / MO
                                                              /3800/modem$
/3800/modem$ git push tinno HEAD:V3800AN_7.0_IVA_AF_V1.1
                                                                          > V3800AN_7.0_IVA_AF_V1.1
```

# 合并原型补丁,针对某一仓库

```
m/: discarding 4 commits
oidgubuntu:-/work/test/3808/modem$ git merge remotes/tinno/V3710AN_7.0_V2.1
baieol3..4bdfbdb
-forward
```

如果给了一个 commit id,需要合并tag或patch,即可以git cherry-pick commitId.

git push

# 合基线patch

进.repo/manifests/下, gitk remotes/origin/patch

```
rigin/patch
bash: 进.repo/manifests/下 , gitk: 没有那个文件或目录
android@ubuntu:~/work/3702/.repo/manifests$ gitk remotes/origin/patch
```

repo forall -p -c git cherry-pick TINNO6580\_WE\_M\_ALPS-MP-M0.MP1-V2.34\_P53 > P06.xml

 $<\!default\ remote="tinno"\ revision="refs/tags/TINNO6580\_WE\_M\_ALPS-MP-M0.MP1-V2.34\_P53"/>$ 

```
androld@ubuntu:~/work/3/02/.repo/manltests$ repo forall -p -c glt cherry-pick fl
NNO6580_WE_M_ALPS-MP-M0.MP1-V2.34_P53 > ~/work/3702/patch/P53_patch.log
~/work/3702
```

### git push

 $< project name = "mt6580m/baseline" path = "baseline" revision = "1ce25627084038c6d734f2808f4f91426ef78513" upstream = "refs/tags/TINNO6580_WE\_M\_ALPS-MP-M0." and the project name = "mt6580m/baseline" path = "baseline" revision = "1ce25627084038c6d734f2808f4f91426ef78513" upstream = "refs/tags/TINNO6580_WE\_M\_ALPS-MP-M0." and the project name = "mt6580m/baseline" path = "baseline" revision = "1ce25627084038c6d734f2808f4f91426ef78513" upstream = "refs/tags/TINNO6580_WE\_M\_ALPS-MP-M0." and the project name = "mt6580m/baseline" path = "baseline" revision = "1ce25627084038c6d734f2808f4f91426ef78513" upstream = "refs/tags/TINNO6580_WE\_M\_ALPS-MP-M0." and the project name = "mt6580m/baseline" path = "baseline" revision = "1ce25627084038c6d734f2808f4f91426ef78513" upstream = "refs/tags/TINNO6580_WE\_M\_ALPS-MP-M0." and the project name = "mt6580m/baseline" path = "1ce25627084038c6d734f2808f4f91426ef78513" upstream = "refs/tags/TINNO6580_WE\_M\_ALPS-MP-M0." and the project name = "mt6580m/baseline" path =$ 

project name="mt6580m/platform/frameworks" path="baseline/frameworks" revision="e076378ad807d8e28a3e7b93fde9bbd9c93072df" upstream="refs/tags/TINN

# 在合基线时,还可以将每个仓库与patch ID记录下来,.

```
1 baseline (253, 254, 255, 256, 257, 258, 259, 260, 261, 262, 2 kernel-3.18 (253, 255, 259, 260, 261, 3 system (255, 262, 4 frameworks (256, 257, 258, 259, 262, 5 packages/apps/Messaging (256, 6 packages/apps/Nfc (262, 7 device/mediatek (259, 8 vendor/mediatek/proprietary/frameworks (259, 9 vendor/mediatek/proprietary/hardware (254, 259,
```

# 然后再进入每个仓库,针对每个修改进行合入

# gitk --all

```
文件(F) 编辑(E) 查看(V) 搜索(S) 终端(T) 帮助(H)
android@ubuntu:~/disk/2500_debug/baseline$ gitk --all
```

#git cherry-pick patch\_Id

右键 cherry-pick.对应的id.

#获取patch

git format-patch commit\_ID

#打patch

patch -p1 < 0001-Added-liuxingde-test.patch

repo forall -p -c git log > log.log, 遍历所有仓库的log,并打印出。一般可以对比前后两个版本的log,来查看是否有其他内容被提交。

合并原型,根据tag合并

1. git tag -l XXXXX (显示tag)

```
android@ubuntu:~/work/3730_debug/packages$ git tag -l
20160929_1156
20160929_1236
20160929_1425
20160929_1502
ALPS-MP-NO.MP2-V1_TINN06580_WE_N_KERNEL_00
ALPS-MP-NO.MP2-V1_TINN06580_WE_N_KERNEL_GIT_20170427
MT6580_7.0_00
MT6580_7.0_FEATURE_00
T2600BN_7.0_LAX_ATT_MX_01
T2600BN_7.0_LAX_ATT_MX_02
T2600BN_7.0_LAX_ATT_MX_03
T2600BN_7.0_LAX_ATT_MX_04
T2600BN_7.0_LAX_ATT_MX_05
T2600BN_7.0_LAX_CLA_GT_01
T2600BN_7.0_LAX_CLA_GT_01
T2600BN_7.0_LAX_CLA_GT_02
T2600BN_7.0_LAX_CLA_GT_02
T2600BN_7.0_LAX_CLA_GT_02
```

2. git show XXX(tag名) (显示tag的修改)

```
android@ubuntu:-/work/3730_debug/packages$ git show tinno6580_we_n_alps-mp-n0.mp2-V1_P99
commtt 6513c222abf63b6f7a6853425a9e274115bb77d6
Author: cheng.yuan <cheng.yuan <chen
```

3. repo forall -p -c git merge XXX(tag名) > ./xxxx.xml

合并原型,按分支合

1. git branch -a

```
android@ubuntu:~/work/3730_debug/packages$
android@ubuntu:~/work/3730_debug/packages$ git branch -a

* (分离自 c5d36f4)
remotes/m/sw -> tinno/V3730AN_7.0_SYM_BD_V1.1
remotes/tinno/ALP5-MP-N0.MP2-V1_TINNO580_WE_N_KERNEL_GIT
remotes/tinno/ALP5-MP-N0.MP2-V1_TINNO6880_WE_N_KERNEL_patch
remotes/tinno/MT6580_7.0_DEV_V1.1
remotes/tinno/MT6580_7.0_FEATURE_V1.1
remotes/tinno/MT6580_7.0_LAX_ATT_MX_V1.1
remotes/tinno/T2600BN_7.0_LAX_ATT_MX_V1.1
remotes/tinno/V2600BN_7.0_LAX_TEL_MX_V1.1
remotes/tinno/V2600BN_7.0_LAX_CLA_GT_V1.1
remotes/tinno/V2600BN_7.0_LAX_CLA_BA_V1.1
remotes/tinno/V2600BN_7.0_LAX_TEL_MX_V1.1
remotes/tinno/V2600BN_7.0_LAX_TEL_MX_V1.1
remotes/tinno/V2600BN_7.0_LAX_TEL_MX_V1.1
remotes/tinno/V2600BN_7.0_MUT_BR_BR1_V1.1
remotes/tinno/V2600BN_7.0_MUT_BR_BR1_V1.1
remotes/tinno/V2600BN_7.0_MUT_BR_V1.1
remotes/tinno/V2600BN_7.0_MUT_BR_V1.1
remotes/tinno/V2600BN_7.0_MUT_BR_V1.1
```

2. repo forall -p -c git merge XXX > ./xxxx.xml

android@ubuntu:~/work/3730\_debug/packages\$ repo forall -p -c remotes/tinno/V3720AN\_7.0\_MEC\_MX\_V1.1

repo forall -p -c git tag -f xxx

(不需要提交)

repo forall -p -c git log --author="xxx" >xxx.log

//使用review 提交

git push tinno HEAD:refs/for/K600AG\_7.1\_MAS\_V1.1