```
# p080dbconnect.rb
# gem install mysl2
require 'active record'
ActiveRecord::Base.establish connection(
adapter: "mysql2",
host: "localhost",
database: "students",
password: "root"
)
class Rubyist < ActiveRecord::Base</pre>
end
Rubyist.create(name: 'Mitali Talim', city: "Nashville, Tenessee")
Rubyist.create(name: 'Sunil Kelkar', city: "Pune, India")
Rubyist.create(name: 'Adam Smith', city: "San Fransisco, USA")
participant = Rubyist.find(:all)
participant.each {|participant| puts %Q{#{participant.name} stays in #
{participant.city}}}
Rubyist.delete_all(name: 'Mitali Talim', city: "Nashville, Tenessee")
Rubyist.delete all(name: 'Sunil Kelkar', city: "Pune, India")
Rubyist.delete_all(name: 'Adam Smith', city: "San Fransisco, USA")
=begin
Copyright (c) 2000, 2013, Oracle and/or its affiliates. All rights reserved.
Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.
Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.
mysql> CREATE DATABASE students;
Query OK, 1 row affected (0.03 sec)
mysql> SHOW TABLES;
ERROR 1046 (3D000): No database selected
mysql> USE students;
Database changed
```

```
mysql> SHOW TABLES;
Empty set (0.00 sec)
mysql> CREATE TABLE rubyists (name VARCHAR(50), city VARCHAR(50));
Query OK, 0 rows affected (0.28 sec)
mysql> SHOW TABLES;
+----+
| Tables_in_students |
+----+
rubyists
+----+
1 row in set (0.00 sec)
mysql> DESCRIBE rubyists;
+----+
+----+
| name | varchar(50) | YES | NULL |
city | varchar(50) | YES | NULL |
+----+
2 rows in set (0.01 sec)
SELECT * FROM rubyists;
=end
```