

Package ‘MSGARCH’

July 26, 2016

Type Package

Title Markov-Switching GARCH models

Version 0.09

Date 2016-06-11

Author Keven Bluteau [aut, cre],
David Ardia [aut]
Kris Boudt [ctb]
Brian Peterson [ctb]

Maintainer Keven Bluteau <keven.bluteau@unine.ch>

Description The MSGARCH package offer functionalities to fit (by Maximum Likelihood or Bayesian), simulate, and forecast various Markov-Switching GARCH processes.

License GPL (>= 2)

Imports Rcpp,
RcppArmadillo,
adaptMCMC,
DEoptim,
nloptr

LinkingTo Rcpp, RcppArmadillo

Depends RcppArmadillo

Suggests knitr,
rmarkdown

VignetteBuilder knitr

RoxygenNote 5.0.1

R topics documented:

MSGARCH-package	2
AIC	3
BIC	3
cdf	4
create.spec	5
DIC	7
fit.bayes	8
fit.mle	10

ht	11
kernel	12
pdf	13
pit	14
Plast	15
pred	15
Pstate	16
risk	17
rnd	18
sim	18
sp500ret	19
unc.vol	20
Index	21

MSGARCH-package	<i>The R package MSGARCH</i>
-----------------	------------------------------

Description

The R package MSGARCH aims to provide a comprehensive set of functionalities for Markov-switching GARCH processes, including fitting, filtering, forecasting, and simulating. Other functions related to Value-at-Risk, Expected-Shortfall, and conditional distributions are also available. The main functions of the package are coded in C++ with Rcpp (Eddelbuettel and Francois, 2011) and RcppArmadillo (Eddelbuettel and Sanderson, 2014). In the R package MSGARCH there is no equation for the mean as in the R package rugarch (Ghalanos, 2015). This means that we assume that before modeling, the user has filter the mean from their time series.

We provided a variety of single-regime GARCH process and regime-switching process as well as many conditional distributions. This allows for a rich modeling environment for Markov-switching GARCH model. This flexibility can come with problematic since the user must take care when optimizing since the optimizer is not always guaranteed to converge. As option, we provide the [kernel](#) method which allows the user to develop his own optimization process if none of the optimization options that the package provides is adequate.

The authors acknowledge Google for financial support via the Google Summer of Code 2016 project "MSGARCH"; see <https://summerofcode.withgoogle.com/projects/#6497774455488512>, the International Institute of Forecasting and Industrielle-Alliance.

References

- Eddelbuettel, D. & Francois, R. (2011). Rcpp: Seamless R and C++ Integration. *Journal of Statistical Software*, 40, pp. 1-18, <http://www.jstatsoft.org/v40/i08/>.
- Eddelbuettel, D. & Sanderson, C. (2014). RcppArmadillo: Accelerating R with High-Performance C++ Linear Algebra. *Computational Statistics & Data Analysis*, 71, pp. 1054-1063, <http://dx.doi.org/10.1016/j.csda.2013.02.005>.
- Ghalanos, A. (2015). rugarch: Univariate GARCH Models. <https://cran.r-project.org/web/packages/rugarch/>.

AIC

*Compute Akaike information criterion (AIC).***Description**

Compute Akaike information criterion (AIC).

Usage

```
AIC(fit)
```

Arguments

`fit` Fit object of type `MSGARCH_MLE_FIT` created with `fit.mle` or `MSGARCH_BAY_FIT` created with `fit.bayes`.

Details

If a matrix of MCMC posterior draws estimates is given, the AIC on the posterior mean is calculated.

Value

AIC value.

References

Akaike, H. (1974). A New Look at the Statistical Model Identification. *IEEE Transactions on Automatic Control*, 19, pp. 716-723.

Examples

```
data("sp500ret")

spec = MSGARCH::create.spec(model = c("sGARCH","sGARCH"), distribution = c("norm","norm"),
                             do.skew = c(FALSE,FALSE), do.mix = FALSE, do.shape.ind = FALSE)

fit = MSGARCH::fit.mle(spec = spec, y = sp500ret)

AIC = MSGARCH::AIC(fit = fit)
```

BIC

*Compute Bayesian information criterion (BIC).***Description**

Compute Bayesian information criterion (BIC).

Usage

```
BIC(fit)
```

Arguments

`fit` Fit object of type `MSGARCH_MLE_FIT` created with `fit.mle` or `MSGARCH_BAY_FIT` created with `fit.bayes`

Details

If a matrix of MCMC posterior draws estimates is given, the BIC on the posterior mean is calculated.

Value

BIC value.

References

Schwarz, G. (1978). Estimating the dimension of a model. *Annals of Statistics*, 6, pp. 461-464.

Examples

```
data("sp500ret")

spec = MSGARCH::create.spec(model = c("sGARCH", "sGARCH"), distribution = c("norm", "norm"),
                             do.skew = c(FALSE, FALSE), do.mix = FALSE, do.shape.ind = FALSE)

fit = MSGARCH::fit.mle(spec = spec, y = sp500ret)

BIC = MSGARCH::BIC(fit = fit)
```

cdf

*Cumulative density function at $T + 1$.***Description**

Method returning the cumulative density of a vector of points.

Usage

```
cdf(spec, x, theta, y, log = TRUE)
```

Arguments

`spec` Model specification of class `MSGARCH_SPEC` created with `create.spec`.
`x` Vector (of size N) of point to be evaluated.
`theta` Vector (of size d) or matrix (of size M x d) of parameter estimates.
`y` Vector (of size T) of observations.
`log` Boolean indicating if the log cumulative is returned. (default: `log = TRUE`)

Details

If a matrix of parameter estimates is given, each parameter estimates is evaluated individually. The `cdf` method uses the last variance estimate by filtering.

Value

Cumulative density or log-density of the points x (vector of size N or matrix of size $M \times N$).

Examples

```
data("sp500ret")

spec = MSGARCH::create.spec(model = c("sGARCH", "sGARCH"), distribution = c("norm", "norm"),
                             do.skew = c(FALSE, FALSE), do.mix = FALSE, do.shape.ind = FALSE)

set.seed(123)

x = rnorm(100)

cdf = MSGARCH::cdf(spec = spec, x = x, theta = theta, y = sp500ret, log = FALSE)
```

create.spec	<i>Specification creation</i>
-------------	-------------------------------

Description

Function for creating a variance specification before fitting and using the R package MSGARCH functionalities.

Usage

```
create.spec(model = c("sGARCH", "sGARCH"), distribution = c("norm", "norm"),
            do.skew = c(FALSE, FALSE), do.mix = FALSE, do.shape.ind = FALSE)
```

Arguments

model	Vector (of size K) containing the variance model specifications. Valid models are "sGARCH", "eGARCH", "gjrGARCH", "tGARCH", and "GAS". (default: model = c("sGARCH", "sGARCH"))
distribution	Vector (of size K) of conditional densities. Valid distribution are "norm", "std", and "ged". The vector must be of the same length as the models vector. (default: distribution = c("norm", "norm"))
do.skew	Vector (of size K) of boolean indicating if the conditional density is skewed. The vector must be of the same length as the distributions vector. (default: do.skew = c(FALSE, FALSE))
do.mix	Boolean indicating if the specification is a mixture type. If the argument is TRUE, a Mixture of GARCH is created, while if the argument is FALSE, a Markov-Switching GARCH is created. (default: do.mix = FALSE)
do.shape.ind	Boolean indicating if the distribution are Regime-Independent. If the argument is TRUE, all distributions are the same and the distribution parameters does not dependent on the regime in which the distribution is attributed to. If the argument is TRUE, all distributions in the distribution argument and all skew argument must be the same. (default: do.shape.ind = FALSE)

Details

The Markov-Switching specification created is based on the Haas et al. (2004a) MSGARCH specification. It is a MSGARCH model that is separated in K single-regimes specification which are updated in parallel. Under this specification, the conditional variance is a function of the past data and the current state. The Mixture of GARCH option is based on the Haas et al. (2004b). A Mixture of GARCH is a mixture of distribution where the variance process of each distribution is a single-regime process.

Value

A list of class `MSGARCH_SPEC` containing variables related to the created specification. The list contains:

Variables:

- `theta0` : Vector (of size d) of default parameters.
- `is.mix` : Boolean indicating if the specification is a mixture.
- `is.shape.ind` : Boolean indicating if the distribution parameter are regime-independent.
- `K` : Number of regimes.
- `sigma0` : Default parameters variance-covariance matrix (of size $K \times K$) used during Bayesian estimation.
- `lower` : Vector (of size d) of lower parameters bound.
- `upper` : Vector (of size d) of upper parameters bound.
- `ineqlb` : Vector (of size d) of lower inequality function bound.
- `inequb` : Vector (of size d) of upper inequality function bound.
- `n.params` : Vector (of size K) of the total number of parameters by regime including distribution parameters.
- `n.params.vol` : Vector (of size K) of the total number of parameters by regime excluding distribution parameters.
- `do.init` : Boolean indicating the default `do.init` argument.
- `label` : Vector (of size d) of parameters label.
- `name` : Vector (of size K) of specification name.
- `func` : List of \mathbb{R} functions internally used.
- `rcpp.func` : List of Rcpp functions internally used.

The `MSGARCH_SPEC` class possesses these methods:

- `sim` : Simulation method.
- `ht` : Conditional variance in each regime.
- `kernel` : Kernel method.
- `unc.vol` : Unconditional variance in each regime.
- `pred` : Predictive density method.
- `pit` : Probability Integral Transform at $T + 1$.
- `risk` : Value-at-Risk And Expected-Shortfall methods.
- `rnd` : Simulation method at $T + 1$.
- `pdf` : Probability density function at $T + 1$.

- `cdf` : Cumulative density function at $T + 1$.
- `Pstate` : State probabilities filtering method.
- `Plast` : State probabilities at $T + 1$.
- `fit.mle` : Maximum Likelihood estimation.
- `fit.bayes` : Bayesian estimation.

References

- Bollerslev, T. (1986). Generalized Autoregressive Conditional Heteroskedasticity. *Journal of Econometrics*, 31, pp. 307-327.
- Creal, D. Koopman, S. J. & Lucas, A. (2013). Generalized Autoregressive Score Models with Applications. *Journal of Applied Econometrics*, 28, pp. 777-795.
- Fernandez, C. & Steel, M. F. (1998). On Bayesian Modeling of Fat Tails and Skewness. *Journal of the American Statistical Association*, 93, pp. 359-371.
- Glosten, L. R. Jagannathan, R. & Runkle, D. E. (1993). On the Relation Between the Expected Value and the Volatility of the Nominal Excess Return on Stocks. *Journal of Finance*, 48, pp. 1779-1801.
- Haas, M. Mittnik, S. & Paoletta, M. S. (2004a). A New Approach to Markov-Switching GARCH Models. *Journal of Financial Econometrics*, 2, pp. 493-530.
- Haas, M. Mittnik, S. & Paoletta, M. S. (2004b). Mixed Normal Conditional Heteroskedasticity. *Journal of Financial Econometrics*, 2, pp. 211-250.
- Nelson, D. B. (1991). Conditional Heteroskedasticity in Asset Returns: A New Approach. *Econometrica*, 59, pp. 347-370.
- Zakoian, J.-M. (1994). Threshold Heteroskedastic Models *Journal of Economic Dynamics and Control*, 18, pp. 931-955.

Examples

```
spec = MSGARCH::f.create.spec(model = c("sGARCH", "gjrGARCH"), distribution = c("norm", "std"),
                               do.skew = c(TRUE, FALSE), do.mix = FALSE, do.shape.ind = FALSE)
```

DIC

Compute Deviance Information Criterion (DIC).

Description

Compute Deviance Information Criterion (DIC).

Usage

```
DIC(fit)
```

Arguments

`fit` Fit object of type `MSGARCH_BAY_FIT` created with `fit.bayes`.

Value

A list containing six variables:

- DIC : Deviance Information Criterion.
- IC : Bayesian Predictive Information Criterion.
- pD : Effective number of parameters ($pD = \bar{D} - \hat{D}$)
- pV : Effective number of parameters ($pV = \text{var}(\hat{D})/2$)
- D.bar: Expected value of the deviance over the posterior
- D.hat: Deviance at the mean posterior estimate

References

Gelman, A. Carlin, J. B. Stern, H. S. & Rubin, D. B. (2003). Bayesian Data Analysis. *Chapman and Hall/CRC*

Examples

```
data("sp500ret")

spec = MSGARCH::create.spec(model = c("sGARCH","sGARCH"), distribution = c("norm","norm"),
                             do.skew = c(FALSE,FALSE), do.mix = FALSE, do.shape.ind = FALSE)

fit = MSGARCH::fit.bay(spec = spec, y = sp500ret)

DIC = MSGARCH::DIC(fit = fit)
```

fit.bayes

Bayesian estimation.

Description

Method that performs Bayesian estimation of a [MSGARCH_SPEC](#) object on a set of observations.

Usage

```
fit.bayes(spec, y, l.ctr)
```

Arguments

- | | |
|-------|--|
| spec | Model specification of class MSGARCH_SPEC created with create.spec . |
| y | Vector (of size T) of observations. |
| l.ctr | A list of control parameters.
The control parameters have three components: <ul style="list-style-type: none"> • N.burn (integer ≥ 0): Number of discarded draws. (default: N.burn = 1000) • N.mcmc (integer > 0): Number of draws. (default: N.mcmc = 5000) • N.thin (integer > 0): Thinning factor (every N.thin draws are kept). (default: N.thin = 10) |

Details

The total number of draws is equal to `N.burn + N.mcmc`. The Bayesian estimation uses the R package `adaptMCMC` (Andreas, 2012) which implements the adaptive sampler of Vihola (2012).

Value

A list of class `MSGARCH_BAY_FIT` containing four variables:

- `theta` : The Bayesian chain (matrix from the R package `coda` (Plummer et al., 2006) of size `N.mcmc / N.thin`).
- `accept` : Acceptation rate of the sampler.
- `y` : Initial vector (of size T) of observations.
- `spec` : Initial specification.

The `MSGARCH_BAY_FIT` possess this method:

- `AIC` : Compute Akaike information criterion (AIC).
- `BIC` : Compute Bayesian information criterion (BIC).
- `DIC` : Compute Deviance Information Criterion (DIC).

References

Andreas, S. (2012). `adaptMCMC`: Implementation of a Generic Adaptive Monte Carlo Markov Chain Sampler. <https://cran.r-project.org/web/packages/adaptMCMC/>.

Metropolis, N.; Rosenbluth, A. W.; Rosenbluth, M. N.; Teller, A. H. & Teller, E. (1953). Equation of State Calculations by Fast Computing Machines. *Journal of Chemical Physics*, 21, pp. 1087-1092.

Plummer, M. Best, N. Cowles, K. & Vines, K. (2006). CODA: Convergence Diagnosis and Output Analysis for MCMC. *R News*, 6, pp.7-11. <https://cran.r-project.org/web/packages/coda/>.

Vihola, M. (2012). Robust Adaptive Metropolis Algorithm with Coerced Acceptance Rate. *Statistics and Computing*, 22, pp. 997-1008.

Examples

```
data("sp500ret")

spec = MSGARCH::create.spec(model = c("sGARCH", "sGARCH"), distribution = c("norm", "norm"),
                             do.skew = c(FALSE, FALSE), do.mix = FALSE, do.shape.ind = FALSE)

theta = spec$fit.bayes(spec = spec, y = sp500ret,
                       l.ctr = list(N.burn = 100, N.mcmc = 1000, N.thin = 1))
```

fit.mle

*ML estimation.***Description**

Method that performs Maximum Likelihood estimation of a `MSGARCH_SPEC` object on a set of observations.

Usage

```
fit.mle(spec, y, ctr = list())
```

Arguments

- | | |
|------|---|
| spec | Model specification created with <code>create.spec</code> . |
| y | Vector (of size T) of observations. |
| ctr | List of control parameters. The control parameters have two components to it: <ul style="list-style-type: none"> • <code>theta0</code> : Starting parameters (vector of size d). If no starting parameters is provided, the default starting parameters of the specification are used. • <code>do.init</code> : Boolean indicating if there is a pre-optimization with the R package <code>DEoptim</code> (Ardia et al., 2011). (default: <code>do.init = FALSE</code>) |

Details

The Maximum likelihood estimation uses the R package `nloptr` (Johnson, 2014) for main optimizer while it uses the R package `DEoptim` when `do.init = TRUE`.

Value

A list of class `MSGARCH_MLE_FIT` containing five variables:

- `theta` : Optimal parameters (vector of size d).
- `l_likelihood` : log-likelihood of y given the optimal parameters.
- `spec` : Initial specification.
- `is.init` : Indicating if estimation was made with `do.init` option.
- `y` : Initial vector (of size T) of observations..

The `MSGARCH_MLE_FIT` possess these methods:

- `AIC` : Compute Akaike information criterion (AIC).
- `BIC` : Compute Bayesian information criterion (BIC).

References

Ardia, D.; Mullen, K. M.; Peterson, B. G. & Ulrich, J. (2015). `DEoptim`: Differential Evolution in R. <https://cran.r-project.org/web/packages/DEoptim/>.

Johnson, S. G. (2014). The `NLOpt` Nonlinear-Optimization. <https://cran.r-project.org/web/packages/NLOpt/>.

Examples

```
data("sp500ret")

spec = MSGARCH::create.spec(model = c("sGARCH", "sGARCH"), distribution = c("norm", "norm"),
                             do.skew = c(FALSE, FALSE), do.mix = FALSE, do.shape.ind = FALSE)

theta = MSGARCH::fit.mle(spec = spec, y = sp500ret, ctr = list(do.init = TRUE))
```

ht	<i>Conditional variance in each regime.</i>
----	---

Description

Method returning the conditional variance of each regime.

Usage

```
ht(spec, theta, y)
```

Arguments

spec	Model specification of class <code>MSGARCH_SPEC</code> created with <code>create.spec</code> .
theta	Vector (of size d) or matrix (of size M x d) of parameter estimates.
y	Vector (of size T) of observations.

Details

If a matrix of parameter estimates is given, each parameter estimates is evaluated individually.

Value

Conditional variance time serie (array of size T + 1 x M x K) for each regime.

Examples

```
data("sp500ret")

spec = MSGARCH::create.spec(model = c("sGARCH", "sGARCH"), distribution = c("norm", "norm"),
                             do.skew = c(FALSE, FALSE), do.mix = FALSE, do.shape.ind = FALSE)

ht = MSGARCH::ht(spec = spec, theta = theta, y = sp500ret)
```

kernel	<i>Kernel function.</i>
--------	-------------------------

Description

Method returning the kernel value of a vector of observations.

Usage

```
kernel(spec, theta, y, log = TRUE)
```

Arguments

spec	Model specification of class <code>MSGARCH_SPEC</code> created with <code>create.spec</code> .
theta	Vector (of size d) or matrix (of size M x d) of parameter estimates.
y	Vector (of size T) of observations.
log	Boolean indicating if the log kernel is returned. (default: log = TRUE)

Details

If a matrix of parameter estimates is given, each parameter estimates is evaluated individually. The kernel is a combination of the prior and the likelihood function. The kernel is equal to $\text{prior}(\theta) + L(y|\theta)$ where L is the likelihood of y given the parameter θ . When doing optimization, the goal is to minimize the negative log-kernel.

- Details on the prior
The prior is different for each specification. It ensures that the θ makes the conditional variance process stationary, positive, and that it respect that the sums of the probabilities in the case of a multiple-regime models are all equal to 1. If any of these three conditions is not respected the prior return $-1e10$, meaning that the optimizer or sampler will know that θ is not a good candidate.

Value

Kernel or log-kernel value (scalar or vector of size M) of the vector of observations.

References

Hamilton, J. D. (1989) A New Approach to the Economic Analysis of Nonstationary Time Series and the Business Cycle. *Econometrica*, 57, pp.357-38

Examples

```
data("sp500ret")

spec = MSGARCH::create.spec(model = c("sGARCH", "sGARCH"), distribution = c("norm", "norm"),
                             do.skew = c(FALSE, FALSE), do.mix = FALSE, do.shape.ind = FALSE)

kernel = MSGARCH::kernel(spec = spec, theta = theta, y = sp500ret, log = TRUE)
```

pdf	<i>Probability density function at $T + 1$.</i>
-----	--

Description

Method returning the probability density of a vector of points.

Usage

```
pdf(spec, x, theta, y, log = TRUE)
```

Arguments

spec	Model specification of class <code>MSGARCH_SPEC</code> created with <code>create.spec</code> .
x	Vector (of size N) of point to be evaluated
theta	Vector (of size d) or matrix (of size M x d) of parameter estimates.
y	Vector (of size T) of observations.
log	Boolean indicating if the log-density is returned. (default: <code>log = TRUE</code>)

Details

If a matrix of parameter estimates is given, each parameter estimates is evaluated individually. The `pdf` method uses the last variance estimate by filtering.

Value

Probability density or log-density of the points x (vector of size N or matrix of size M x N).

Examples

```
data("sp500ret")

spec = MSGARCH::create.spec(model = c("sGARCH", "sGARCH"), distribution = c("norm", "norm"),
                             do.skew = c(FALSE, FALSE), do.mix = FALSE, do.shape.ind = FALSE)

set.seed(123)

x = rnorm(100)

pdf = MSGARCH::pdf(spec = spec, x = x, theta = theta, y = sp500ret, log = FALSE)
```

pit	<i>Probability Integral Transform at $T + 1$.</i>
-----	--

Description

Method returning the predictive Probability integral transform (PIT).

Usage

```
pit(spec, x, theta, y, do.norm = FALSE)
```

Arguments

spec	Model specification of class <code>MSGARCH_SPEC</code> created with <code>create.spec</code> .
x	Vector (of size N) of point to be evaluated
theta	Vector (of size d) or matrix (of size M x d) of parameter estimates.
y	Vector (of size T) of observations.
do.norm	Boolean indicating if the PIT value are transforms into standard Normal variate. (do.norm = FALSE)

Details

If a matrix of MCMC posterior draws estimates is given, the Bayesian Probability integral transform is calculated. The `do.norm` argument transforms the PIT value into Normal variate so that normality test can be done.

Value

Probability integral transform of the points x or Normal variate derived from the Probability integral transform of x (vector of size N).

Examples

```
data("sp500ret")

spec = MSGARCH::create.spec(model = c("sGARCH", "sGARCH"), distribution = c("norm", "norm"),
                             do.skew = c(FALSE, FALSE), do.mix = FALSE, do.shape.ind = FALSE)

set.seed(123)

x = rnorm(100)

pit = MSGARCH::pit(spec = spec, x = x theta = spec$theta0, y = sp500ret, do.norm = FALSE)
```

Plast	<i>State probabilities at $T + 1$.</i>
-------	---

Description

Method returning the state probabilities at $T + 1$.

Usage

```
Plast(spec, theta, y)
```

Arguments

spec	Model specification of class <code>MSGARCH_SPEC</code> created with <code>create.spec</code> .
theta	Vector (of size d) or matrix (of size $M \times d$) of parameter estimates.
y	Vector (of size T) of observations.

Details

If a matrix of parameter estimates is given, each parameter estimates is evaluated individually.

Value

State probabilities at $T + 1$ (matrix of size $M \times K$).

Examples

```
data("sp500ret")

spec = MSGARCH::create.spec(model = c("sGARCH", "sGARCH"), distribution = c("norm", "norm"),
                             do.skew = c(FALSE, FALSE), do.mix = FALSE, do.shape.ind = FALSE)

Plast = MSGARCH::Plast(spec = spec, theta = theta, y = sp500ret)
```

pred	<i>Predictive density function.</i>
------	-------------------------------------

Description

Method returning the predictive probability density of a vector of points.

Usage

```
pred(spec, x, theta, y, log = TRUE)
```

Arguments

spec	Model specification of class <code>MSGARCH_SPEC</code> created with <code>create.spec</code> .
x	Vector (of size N) of point to be evaluated
theta	Vector (of size d) or matrix (of size M x d) of parameter estimates.
y	Vector (of size T) of observations.
log	Boolean indicating if the log-density is returned. (default: log = TRUE)

Details

If a matrix of MCMC posterior draws estimates is given, the Bayesian predictive density is calculated.

Value

Predictive density or log-density of x (vector of size N).

Examples

```
data("sp500ret")

spec = MSGARCH::create.spec(model = c("sGARCH","sGARCH"), distribution = c("norm","norm"),
                             do.skew = c(FALSE,FALSE), do.mix = FALSE, do.shape.ind = FALSE)

set.seed(123)

x = rnorm(100)

pred = MSGARCH::pred(spec = spec, x = x, theta = theta, y = sp500ret, log = TRUE)
```

Pstate

State probabilities filtering function.

Description

Method returning the filtered state probabilities.

Usage

```
Pstate(spec, theta, y)
```

Arguments

spec	Model specification of class <code>MSGARCH_SPEC</code> created with <code>create.spec</code> .
theta	Vector (of size d) or matrix (of size M x d) of parameter estimates.
y	Vector (of size T) of observations.

Details

If a matrix of parameter estimates is given, each parameter estimates is evaluated individually.

Value

Filtered state probabilities (array of size T x M x K).

Examples

```
data("sp500ret")

spec = MSGARCH::create.spec(model = c("sGARCH", "sGARCH"), distribution = c("norm", "norm"),
                             do.skew = c(FALSE, FALSE), do.mix = FALSE, do.shape.ind = FALSE)

Pstate = MSGARCH::Pstate(spec = spec, theta = spec$theta0, y = sp500ret)
```

risk	<i>Value-at-Risk And Expected-shortfall functions.</i>
------	--

Description

Method returning the Value-at-Risk and Expected-shortfall.

Usage

```
risk(spec, theta, y, level = c(0.95, 0.99), ES = TRUE)
```

Arguments

spec	Model specification of class MSGARCH_SPEC created with create.spec .
theta	Vector (of size d) or matrix (of size M x d) of parameter estimates.
y	Vector (of size T) of observations.
level	Vector (of size A) of Value-at-risk and Expected-shortfall levels. (default: level = c(0.95, 0.99))
ES	Boolean indicating if Expected-shortfall is also calculated. (default: ES = TRUE)

Details

If a matrix of MCMC posterior draws estimates is given, the Bayesian Value-at-Risk and Expected-shortfall are calculated.

Value

A list containing one or two components:

- VaR : Value-at-Risk at the choosen levels (vector of size A).
- ES : Expected-shortfall at the choosen levels (vector of size A).

Examples

```
data("sp500ret")

spec = MSGARCH::create.spec(model = c("sGARCH", "sGARCH"), distribution = c("norm", "norm"),
                             do.skew = c(FALSE, FALSE), do.mix = FALSE, do.shape.ind = FALSE)

risk = MSGARCH::risk(spec = spec, theta = spec$theta0, y = sp500ret, level = c(0.95, 0.99), ES = TRUE)
```

<code>rnd</code>	<i>Simulation function at $T + 1$.</i>
------------------	---

Description

Method returning random draws at $T + 1$.

Usage

```
rnd(spec, n, theta, y = vector("double", 0), do.state = FALSE)
```

Arguments

<code>spec</code>	Model specification of class <code>MSGARCH_SPEC</code> created with <code>create.spec</code> .
<code>n</code>	Number of random draws to be generated.
<code>theta</code>	Vector (of size d) or matrix (of size $M \times d$) of parameter estimates.
<code>y</code>	Vector (of size T) of observations.
<code>do.state</code>	Boolean indicating if the simulated state are also output. (default: <code>do.state = FALSE</code>)

Details

If a matrix of parameter estimates is given, each parameter estimates is evaluated individually.

Value

A list containing one or two components:

- `draws`: vector (of size n) or matrix (of size $M \times n$) of simulated draws at $T + 1$.
- `state`: vector (of size n) or matrix (of size $M \times n$) of simulated states at $T + 1$. The state value appear only if `do.state = TRUE`.

Examples

```
spec = MSGARCH::create.spec(model = c("sGARCH", "sGARCH"), distribution = c("norm", "norm"),
                             do.skew = c(FALSE, FALSE), do.mix = FALSE, do.shape.ind = FALSE)

rnd = MSGARCH::rnd(spec = spec, n = 1000, theta = theta, y = sp500ret, do.state = TRUE)
```

<code>sim</code>	<i>Simulation function.</i>
------------------	-----------------------------

Description

Method returning a simulated process.

Usage

```
sim(spec, n, theta, burnin = 500, do.state = FALSE)
```

Arguments

spec	Model specification of class <code>MSGARCH_SPEC</code> created with <code>create.spec</code> .
n	Simulation length.
theta	Vector (of size d) or matrix (of size M x d) of parameter estimates.
burnin	(integer ≥ 0) Burnin period discarded (first simulation draws). (default: burnin = 500)
do.state	Boolean indicating if the simulated state are also output. (default: log = TRUE)

Details

If a matrix of parameter estimates is given, each parameter estimates is evaluated individually.

Value

A list of class `MSGARCH_SIM` containing one or two components.

- draws: vector (of size n) or matrix (of size M x n) of simulated draws.
- state: vector (of size n) or matrix (of size M x n) of simulated states. The state value appear only if `do.state = TRUE`.

Examples

```
spec = MSGARCH::create.spec(model = c("sGARCH", "sGARCH"), distribution = c("norm", "norm"),
                             do.skew = c(FALSE, FALSE), do.mix = FALSE, do.shape.ind = FALSE)

y = MSGARCH::sim(spec = spec, n = 1000, theta = theta, burnin = 500, do.state = TRUE)
```

sp500ret

Standard and poors 500 closing Value log return

Description

The S&P500 index closing value log return from 1987-03-10 to 2009-01-30 from Yahoo Finance <https://ca.finance.yahoo.com/>.

Usage

```
data("sp500ret")
```

Format

Vector containing 5523 observations.

Source

Yahoo Finance <https://ca.finance.yahoo.com/>

unc.vol	<i>Unconditional variance of each regime.</i>
---------	---

Description

Method returning the unconditional variance of the process in each state.

Usage

```
unc.vol(spec, theta, y = 0)
```

Arguments

spec	Model specification of class <code>MSGARCH_SPEC</code> created with <code>create.spec</code> .
theta	Vector (of size d) or matrix (of size M x d) of parameter estimates.

Details

If a matrix of parameter estimates is given, each parameter estimates is evaluated individually.

Value

Unconditional variance (vector of size K or matrix of size M x K) of each regime.

Examples

```
spec = MSGARCH::create.spec(model = c("sGARCH", "sGARCH"), distribution = c("norm", "norm"),
                             do.skew = c(FALSE, FALSE), do.mix = FALSE, do.shape.ind = FALSE)
```

```
unc.vol = MSGARCH::unc.vol(spec = spec, theta = theta)
```

Index

*Topic **datasets**

sp500ret, [19](#)

AIC, [3](#), [9](#), [10](#)

BIC, [3](#), [9](#), [10](#)

cdf, [4](#), [4](#), [7](#)

create.spec, [4](#), [5](#), [8](#), [10–20](#)

DIC, [7](#), [9](#)

fit.bayes, [3](#), [4](#), [7](#), [8](#)

fit.mle, [3](#), [4](#), [7](#), [10](#)

ht, [6](#), [11](#)

kernel, [2](#), [6](#), [12](#)

MSGARCH (MSGARCH-package), [2](#)

MSGARCH-package, [2](#)

MSGARCH_BAY_FIT, [3](#), [4](#), [7](#), [9](#)

MSGARCH_MLE_FIT, [3](#), [4](#), [10](#)

MSGARCH_SIM, [19](#)

MSGARCH_SPEC, [4](#), [6](#), [8](#), [10–20](#)

pdf, [6](#), [13](#), [13](#)

pit, [6](#), [14](#)

Plast, [7](#), [15](#)

pred, [6](#), [15](#)

Pstate, [7](#), [16](#)

risk, [6](#), [17](#)

rnd, [6](#), [18](#)

sim, [6](#), [18](#)

sp500ret, [19](#)

unc.vol, [6](#), [20](#)