

Package ‘GxEprsDummy’

May 30, 2023

Title What the Package Does (One Line, Title Case)

Version 0.0.0.9000

Description What the package does (one paragraph).

License `use_mit_license()`, `use_gpl3_license()` or friends to pick a license

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.3

Depends R (>= 2.10)

LazyData true

R topics documented:

Bcov_discovery	2
Bcov_target	3
Bphe_discovery	4
Bphe_target	4
DummyData	5
GWAS_binary	5
GWEIS_binary	6
PRS_binary	7
Qcov_discovery	8
Qcov_target	9
Qphe_discovery	10
Qphe_target	10
results_permuted_binary	11
results_regular_binary	11
summary_permuted_binary	12
summary_regular_binary	13
Index	15

Bcov_discovery	<i>Covariate data file of the discovery dataset when the outcome is binary This contains covariate information of the individuals in the discovery dataset following confounders</i>
----------------	--

Description

Covariate data file of the discovery dataset when the outcome is binary This contains covariate information of the individuals in the discovery dataset following confounders

Usage

```
Bcov_discovery
```

Format

A dataframe with 7916 rows and 18 columns

Column 1 Family ID

Column 2 Individual ID

Column 3 standardized covariate

Column 4 square of the standardized covariate

Column 5 confounder 1

Column 6 confounder 2

Column 7 confounder 3

Column 8 confounder 4

Column 9 confounder 5

Column 10 confounder 6

Column 11 confounder 7

Column 12 confounder 8

Column 13 confounder 9

Column 14 confounder 10

Column 15 confounder 11

Column 16 confounder 12

Column 17 confounder 13

Column 18 confounder 14

Bcov_target	<i>Covariate data file of the target dataset when the outcome is binary This contains covariate information of the individuals in the target dataset following confounders</i>
-------------	--

Description

Covariate data file of the target dataset when the outcome is binary This contains covariate information of the individuals in the target dataset following confounders

Usage

```
Bcov_target
```

Format

A dataframe with 1939 rows and 18 columns

Column 1 Family ID

Column 2 Individual ID

Column 3 standardized covariate

Column 4 square of the standardized covariate

Column 5 confounder 1

Column 6 confounder 2

Column 7 confounder 3

Column 8 confounder 4

Column 9 confounder 5

Column 10 confounder 6

Column 11 confounder 7

Column 12 confounder 8

Column 13 confounder 9

Column 14 confounder 10

Column 15 confounder 11

Column 16 confounder 12

Column 17 confounder 13

Column 18 confounder 14

Bphe_discovery	<i>Phenotype data file of the discovery dataset when the outcome is binary This contains phenotype information of the individuals in the discovery dataset</i>
----------------	--

Description

Phenotype data file of the discovery dataset when the outcome is binary This contains phenotype information of the individuals in the discovery dataset

Usage

Bphe_discovery

Format

A dataframe with 7916 rows and 3 columns

Column 1 Family ID

Column 2 Individual ID

Column 3 phenotype (1=controls, 2=cases)

Bphe_target	<i>Phenotype data file of the target dataset when the outcome is binary This contains phenotype information of the individuals in the target dataset</i>
-------------	--

Description

Phenotype data file of the target dataset when the outcome is binary This contains phenotype information of the individuals in the target dataset

Usage

Bphe_target

Format

A dataframe with 1939 rows and 3 columns

Column 1 Family ID

Column 2 Individual ID

Column 3 phenotype (0=controls, 1=cases)

DummyData	<i>PLINK binary data files This contains DummyData.fam, DummyData.bim and DummyData.bed files, all in one</i>
-----------	---

Description

PLINK binary data files This contains DummyData.fam, DummyData.bim and DummyData.bed files, all in one

Usage

```
DummyData
```

Format

The data files follow the general PLINK format

GWAS_binary	<i>GWAS_binary function This function performs GWAS using plink2 and outputs the GWAS summary statistics file with additive SNP effects named B_trd.sum</i>
-------------	---

Description

GWAS_binary function This function performs GWAS using plink2 and outputs the GWAS summary statistics file with additive SNP effects named B_trd.sum

Usage

```
GWAS_binary(
  plink_path,
  b_file,
  pheno_file,
  covar_file,
  n_confounders,
  thread,
  summary_output = NULL
)
```

Arguments

plink_path	Path to the PLINK executable application
b_file	Prefix of the binary files, where all .fam, .bed and .bim files have a common prefix
pheno_file	Name (with file extension) of the phenotype file containing family ID, individual ID and phenotype of the discovery dataset as columns, without heading
covar_file	Name (with file extension) of the covariate file containing family ID, individual ID, standardized covariate, square of standardized covariate, and/or confounders of the discovery dataset as columns, without heading

n_confounders	Number of confounding variables in the discovery dataset
thread	Number of threads used

Value

This function will perform GWAS and output

B_trd.sum

GWEIS_binary	<i>GWEIS_binary function This function performs GWEIS using plink2 and outputs the GWEIS summary statistics files with additive SNP effects named B_add.sum and interaction SNP effects named B_gxe.sum</i>
--------------	---

Description

GWEIS_binary function This function performs GWEIS using plink2 and outputs the GWEIS summary statistics files with additive SNP effects named B_add.sum and interaction SNP effects named B_gxe.sum

Usage

```
GWEIS_binary(
  plink_path,
  b_file,
  pheno_file,
  covar_file,
  n_confounders,
  thread,
  summary_output1 = NULL,
  summary_output2 = NULL
)
```

Arguments

plink_path	Path to the PLINK executable application
b_file	Prefix of the binary files, where all .fam, .bed and .bim files have a common prefix
pheno_file	Phenotype file containing family ID, individual ID and phenotype of the discovery dataset as columns, without heading
covar_file	Covariate file containing family ID, individual ID, standardized covariate, square of standardized covariate, and/or confounders of the discovery dataset as columns, without heading
n_confounders	Number of confounding variables in the discovery dataset
thread	Number of threads used

Value

This function will perform GWEIS and output

B_add.sum

B_gxe.sum

PRs_binary	<i>PRs_binary function</i> This function uses plink2 and outputs PRs of each individual in the target dataset, using pre-generated GWAS and GWEIS summary statistics files named B_trd.sum, B_add.sum and B_gxe.sum
------------	---

Description

PRs_binary function This function uses plink2 and outputs PRs of each individual in the target dataset, using pre-generated GWAS and GWEIS summary statistics files named B_trd.sum, B_add.sum and B_gxe.sum

Usage

```
PRs_binary(
  plink_path,
  b_file,
  summary_input1 = "B_trd.sum",
  summary_input2 = "B_add.sum",
  summary_input3 = "B_gxe.sum",
  summary_output1 = NULL,
  summary_output2 = NULL,
  summary_output3 = NULL
)
```

Arguments

plink_path	Path to the PLINK executable application
b_file	Prefix of the binary files, where all .fam, .bed and .bim files have a common prefix

Value

This function will output

B_trd.sscore

B_add.sscore

B_gxe.sscore

Qcov_discovery	<i>Covariate data file of the discovery dataset when the outcome is quantitative This contains covariate information of the individuals in the discovery dataset following confounders</i>
----------------	--

Description

Covariate data file of the discovery dataset when the outcome is quantitative This contains covariate information of the individuals in the discovery dataset following confounders

Usage

```
Qcov_discovery
```

Format

A dataframe with 6426 rows and 18 columns

Column 1 Family ID

Column 2 Individual ID

Column 3 standardized covariate

Column 4 square of the standardized covariate

Column 5 confounder 1

Column 6 confounder 2

Column 7 confounder 3

Column 8 confounder 4

Column 9 confounder 5

Column 10 confounder 6

Column 11 confounder 7

Column 12 confounder 8

Column 13 confounder 9

Column 14 confounder 10

Column 15 confounder 11

Column 16 confounder 12

Column 17 confounder 13

Column 18 confounder 14

Qcov_target	<i>Covariate data file of the target dataset when the outcome is quantitative This contains covariate information of the individuals in the target dataset following confounders</i>
-------------	--

Description

Covariate data file of the target dataset when the outcome is quantitative This contains covariate information of the individuals in the target dataset following confounders

Usage

```
Qcov_target
```

Format

A dataframe with 1579 rows and 18 columns

Column 1 Family ID

Column 2 Individual ID

Column 3 standardized covariate

Column 4 square of the standardized covariate

Column 5 confounder 1

Column 6 confounder 2

Column 7 confounder 3

Column 8 confounder 4

Column 9 confounder 5

Column 10 confounder 6

Column 11 confounder 7

Column 12 confounder 8

Column 13 confounder 9

Column 14 confounder 10

Column 15 confounder 11

Column 16 confounder 12

Column 17 confounder 13

Column 18 confounder 14

Qphe_discovery	<i>Phenotype data file of the discovery dataset when the outcome is quantitative This contains phenotype information of the individuals in the discovery dataset</i>
----------------	--

Description

Phenotype data file of the discovery dataset when the outcome is quantitative This contains phenotype information of the individuals in the discovery dataset

Usage

Qphe_discovery

Format

A dataframe with 6426 rows and 3 columns

Column 1 Family ID

Column 2 Individual ID

Column 3 phenotype

Qphe_target	<i>Phenotype data file of the target dataset when the outcome is quantitative This contains phenotype information of the individuals in the target dataset</i>
-------------	--

Description

Phenotype data file of the target dataset when the outcome is quantitative This contains phenotype information of the individuals in the target dataset

Usage

Qphe_target

Format

A dataframe with 1579 rows and 3 columns

Column 1 Family ID

Column 2 Individual ID

Column 3 phenotype

```
results_permuted_binary
```

results_permuted_binary function This function uses plink2 and outputs PRSs of each individual in the target dataset, using pre-generated GWAS and GWEIS summary statistics files named B_trd.sum, B_add.sum and B_gxe.sum

Description

results_permuted_binary function This function uses plink2 and outputs PRSs of each individual in the target dataset, using pre-generated GWAS and GWEIS summary statistics files named B_trd.sum, B_add.sum and B_gxe.sum

Usage

```
results_permuted_binary(
  Bphe_target,
  Bcov_target,
  n_confounders,
  input_score1 = "B_trd.sscore",
  input_score2 = "B_add.sscore",
  input_score3 = "B_gxe.sscore"
)
```

Arguments

Bphe_target	Phenotype file containing family ID, individual ID and phenotype of the target dataset as columns, without heading
Bcov_target	Covariate file containing family ID, individual ID, standardized covariate, square of standardized covariate, and/or confounders of the target dataset as columns, without heading
n_confounders	Number of confounding variables in the target dataset

Value

This function will output

```
Individual_risk_values.txt
```

```
results_regular_binary
```

results_regular_binary function This function uses plink2 and outputs PRSs of each individual in the target dataset, using pre-generated GWAS and GWEIS summary statistics files named B_trd.sum, B_add.sum and B_gxe.sum

Description

`results_regular_binary` function This function uses `plink2` and outputs PRSs of each individual in the target dataset, using pre-generated GWAS and GWEIS summary statistics files named `B_trd.sum`, `B_add.sum` and `B_gxe.sum`

Usage

```
results_regular_binary(
  Bphe_target,
  Bcov_target,
  n_confounders,
  input_score1 = "B_trd.sscore",
  input_score2 = "B_add.sscore",
  input_score3 = "B_gxe.sscore"
)
```

Arguments

<code>Bphe_target</code>	Phenotype file containing family ID, individual ID and phenotype of the target dataset as columns, without heading
<code>Bcov_target</code>	Covariate file containing family ID, individual ID, standardized covariate, square of standardized covariate, and/or confounders of the target dataset as columns, without heading
<code>n_confounders</code>	Number of confounding variables in the target dataset

Value

This function will output

`Individual_risk_values.txt`

`summary_permuted_binary`

summary_permuted_binary function This function uses `plink2` and outputs the p value of permuted model in the target dataset, using pre-generated GWAS and GWEIS summary statistics files named `B_trd.sum`, `B_add.sum` and `B_gxe.sum`

Description

`summary_permuted_binary` function This function uses `plink2` and outputs the p value of permuted model in the target dataset, using pre-generated GWAS and GWEIS summary statistics files named `B_trd.sum`, `B_add.sum` and `B_gxe.sum`

Usage

```
summary_permuted_binary(
  Bphe_target,
  Bcov_target,
  n_confounders,
  iterations = 1000,
  input_score1 = "B_trd.sscore",
  input_score2 = "B_add.sscore",
  input_score3 = "B_gxe.sscore"
)
```

Arguments

Bphe_target	Phenotype file containing family ID, individual ID and phenotype of the target dataset as columns, without heading
Bcov_target	Covariate file containing family ID, individual ID, standardized covariate, square of standardized covariate, and/or confounders of the target dataset as columns, without heading
n_confounders	Number of confounding variables in the target dataset

Value

This function will output
B_permuted_p.txt

summary_regular_binary

summary_regular_binary function This function uses plink2 and outputs the summary of regular model in the target dataset, using pre-generated GWAS and GWEIS summary statistics files named B_trd.sum, B_add.sum and B_gxe.sum

Description

summary_regular_binary function This function uses plink2 and outputs the summary of regular model in the target dataset, using pre-generated GWAS and GWEIS summary statistics files named B_trd.sum, B_add.sum and B_gxe.sum

Usage

```
summary_regular_binary(
  Bphe_target,
  Bcov_target,
  n_confounders,
  input_score1 = "B_trd.sscore",
  input_score2 = "B_add.sscore",
  input_score3 = "B_gxe.sscore"
)
```

Arguments

<code>Bphe_target</code>	Phenotype file containing family ID, individual ID and phenotype of the target dataset as columns, without heading
<code>Bcov_target</code>	Covariate file containing family ID, individual ID, standardized covariate, square of standardized covariate, and/or confounders of the target dataset as columns, without heading
<code>n_confounders</code>	Number of confounding variables in the target dataset

Value

This function will output

`Bsummary.txt`

Index

- * **datasets**
 - Bcov_discovery, [2](#)
 - Bcov_target, [3](#)
 - Bphe_discovery, [4](#)
 - Bphe_target, [4](#)
 - DummyData, [5](#)
 - Qcov_discovery, [8](#)
 - Qcov_target, [9](#)
 - Qphe_discovery, [10](#)
 - Qphe_target, [10](#)
- * **disease**
 - results_permuted_binary, [11](#)
 - results_regular_binary, [11](#)
- * **gwas**
 - GWAS_binary, [5](#)
- * **gwies,**
 - GWEIS_binary, [6](#)
- * **gxe**
 - GWEIS_binary, [6](#)
- * **individual**
 - results_permuted_binary, [11](#)
 - results_regular_binary, [11](#)
- * **interaction,**
 - GWEIS_binary, [6](#)
- * **profile**
 - PRS_binary, [7](#)
- * **prs,**
 - PRS_binary, [7](#)
- * **regression**
 - summary_permuted_binary, [12](#)
 - summary_regular_binary, [13](#)
- * **risk,**
 - results_permuted_binary, [11](#)
 - results_regular_binary, [11](#)
- * **risk**
 - results_permuted_binary, [11](#)
 - results_regular_binary, [11](#)
- * **scores,**
 - results_permuted_binary, [11](#)
 - results_regular_binary, [11](#)
- * **scores**
 - PRS_binary, [7](#)
- * **summary**
 - summary_permuted_binary, [12](#)
 - summary_regular_binary, [13](#)
- * **values,**
 - results_permuted_binary, [11](#)
 - results_regular_binary, [11](#)
- Bcov_discovery, [2](#)
- Bcov_target, [3](#)
- Bphe_discovery, [4](#)
- Bphe_target, [4](#)
- DummyData, [5](#)
- GWAS_binary, [5](#)
- GWEIS_binary, [6](#)
- PRS_binary, [7](#)
- Qcov_discovery, [8](#)
- Qcov_target, [9](#)
- Qphe_discovery, [10](#)
- Qphe_target, [10](#)
- results_permuted_binary, [11](#)
- results_regular_binary, [11](#)
- summary_permuted_binary, [12](#)
- summary_regular_binary, [13](#)