

# Processing 1000 Genomes reference data for ancestry estimation

*Hannah Meyer*

*2018-11-08*

## Contents

|  |          |
|--|----------|
| <b>Introduction</b>  | <b>1</b> |
| <b>Workflow</b>  | <b>1</b> |
| Set-up . . . . .   | 1        |
| PLINK software . . . . .   | 1        |
| Download and decompress 1000 Genomes phase 3 data . . . . .          | 2        |
| Convert 1000 Genomes phase 3 data to plink 1 binary format . . . . . | 2        |
| <b>References</b>  | <b>2</b> |

## Introduction

Genotype quality control for genetic association studies often includes the need for selecting samples of the same ethnic background. To identify individuals of divergent ancestry based on genotypes, the genotypes of the study population can be combined with genotypes of a reference dataset consisting of individuals from known ethnicities. Principal component analysis (PCA) on this combined genotype panel can then be used to detect population structure down to the level of the reference dataset.

The following vignette shows the processing steps required to use samples of the 1000 Genomes study [1],[2] as a reference dataset. Using the 1000 Genomes reference, population structure down to large-scale continental ancestry can be detected. A step-by-step instruction on how to conduct this ancestry analysis is described in this vignette.

## Workflow

### Set-up

We will first set up some bash variables and create directories needed; storing the names and directories of the reference will make it easy to use updated versions of the reference in the future. It is also useful to keep the PLINK log-files for future reference. In order to keep the data directory tidy, we'll create a directory for the log files and move them to the log directory here after each analysis step.

```
refdir='~/reference'
mkdir -r $qcdir/plink_log
```

### PLINK software

In addition to PLINK v1.9, which is a requirement for the `plinkQC` package, we will also need PLINK v2 for processing the downloaded dataset. In the following, when `plink` is invoked, this corresponds to v1.9, whereas `plink2` corresponds to v2.

## Download and decompress 1000 Genomes phase 3 data

1000 Genomes phase III (1000GenomesIII) is available in PLINK 2 binary format at [https://www.cog-genomics.org/plink/2.0/resources#1kg\\_phase3](https://www.cog-genomics.org/plink/2.0/resources#1kg_phase3). In addition, a sample file with information about the individuals' ancestry is available and should be downloaded as input for `plinkQC::chec_Ancestry()`. The following code chunk downloads and decompresses the data. The genome build of these files is the same as the original release of the 1000GenomesIII, namely CGRCh37.

NB: CGRCh38 positions in vcf format can be found [here](#) The remainder of this vignette will however look at the data processing required for the 1000GenomesIII available in PLINK 2 binary format.

```
cd $refdir

pgen=https://www.dropbox.com/s/afvtf1e15gqzsqa/all_phase3.pgen.zst?dl=1
pvar=https://www.dropbox.com/s/0nz9ey756xfocjm/all_phase3.pvar.zst?dl=1
sample=https://www.dropbox.com/s/yozrzsdwrqej63q/phase3_corrected.psam?dl=1

wget $pgen
mv 'all_phase3.pgen.zst?dl=1' all_phase3.pgen.zst
plink2 --zst-decompress all_phase3.pgen.zst > all_phase3.pgen

wget $pvar
mv 'all_phase3.pvar.zst?dl=1' all_phase3.pvar.zst
plink2 --zst-decompress all_phase3.pvar.zst > all_phase3.pvar

wget $sample
mv 'phase3_corrected.psam?dl=1' all_phase3.psam
```

## Convert 1000 Genomes phase 3 data to plink 1 binary format

We then convert the PLINK 2 binary format to the (at the moment) more standardly used PLINK 1 binary format.

```
plink2 --pfile $refdir/all_phase3 \
      --make-bed \
      --out $refdir/all_phase3
mv $refdir/all_phase3.log $refdir/log
```

## References

1. 1000 Genomes Project Consortium. An integrated map of structural variation in 2,504 human genomes. *Nature*. 2015;526: 75–81. doi:10.1038/nature15394
2. 1000 Genomes Project Consortium. A global reference for human genetic variation. *Nature*. 2015;526: 75–81. doi:10.1038/nature15393