### Short Read Workshop Day 4 Trimming, Mapping, IGV


Lynn Sanford and Georgia Barone 2024

### Day 4 overview

- Trimming fastq files
- Mapping fastq files
- More about mapped file formats
- Visualizing mapped files

### Goal of the Day

View sequencing data as reads aligned to a genome



50 base read:

TAGGCTAACTCTGTAGCCCCAGGTACCATGCATAATTGACCAGGATATAG

50 base read: TAGGCTAACTCTGTAGCCCAGGTACCATGCATAATTGACCAGGATATAG

Trimmomatic

40 base trimmed read: TAGGCTAACTCTGTAGCCCCAGGTACCATGCATAATTGAC

50 base read:

TAGGCTAACTCTGTAGCCCCAGGTACCATGCATAATTGACCAGGATATAG

Trimmomatic

40 base trimmed read:

TAGGCTAACTCTGTAGCCCCAGGTACCATGCATAATTGAC

HISAT2

Genome:

50 base read: TAGGCTAACTCTGTAGCCCCAGGTACCATGCATAATTGACCAGGATATAG

Trimmomatic

40 base trimmed read: TAGGCTAACTCTGTAGCCCCAGGTACCATGCATAATTGAC

HISAT2

Genome:

IGV

### Trimming fastq files with Trimmomatic

- Follow Variables/Trimmomatic worksheets to:
- Learn more about variables in bash
- Create Day4 directories
- Edit script to run Trimmomatic
   Input: fastq files with full-length reads
   Output: fastq files with trimmed/filtered reads

 Extra: Edit the d4\_trim\_qc.sbatch script to run pre-trim qc and compare the plots/stats to post-trim

# How do you trim polyA regions from both sides of reads?

## How do you trim polyA regions from both sides of reads?

- Make a new fasta file with a polyA segment, or append to the Illumina adapter file, if writeable
- ILLUMINACLIP:<new fasta file>:2:30:10

### Mapping fastq files with HISat2

- Follow Mapping/IGV worksheet to:
- Rsync the mapping script
- Edit script and run HISAT2
  - Input: trimmed fastq files
  - Outputs: .sam, .bam, .sorted.bam, .bam.bai files
- Visualize BAM file on the IGV web app

### Homework

Day 4 Homework – FASTQC, trimming, mapping, IGV

The assessment tomorrow will run many of the same steps as this homework. These steps are essential in ALL short read data processing.

### Variables – evaluating (calling)

#### \$variablename

echo \$a

grep \$gene\_name <filename>

trim\_script="\$filepath"/d4\_trim\_qc.sbatch OR

trim\_script=\${filepath}/d4\_trim\_qc.sbatch

wc \$filelist

#### Several ways of evaluating:

\$a

\${a}

"\$a"

These differ slightly, and you will see us use them all in scripts