L7.1 — UML Diagram Types

AICE2005 | Self-Study

University of Southampton

This session is self-reading

No live lecture for L7.1 — work through these notes at your own pace before the week 8 workshop.

- UML Cheat Sheet — quick-reference summary of the notation covered below
- Optional: LinkedIn Learning course — Software Design: Modeling with UML — not assessed, for anyone who wants a video walkthrough alongside these notes

© University of Southampton

UML — The 14 Diagram Types

> UML diagrams split into two families: **structure diagrams** (what the system is made of — static) and **behavior diagrams** (what the system does — dynamic).

0. Why UML, and why so many diagrams?

UML (Unified Modeling Language) is a standardized set of diagram notations for defining, visualizing, and documenting the artifacts of a software system — and sometimes a business model. It gives object-oriented teams a shared vocabulary to communicate designs, explore alternatives, and validate architecture before writing code.

© University of Southampton

UML — The 14 Diagram Types

There isn't one "UML diagram" because no single view can serve everyone on a project — an architect, a coder, a tester, and a technical writer each need a different angle and level of detail on the same system. UML covers that by splitting into 14 diagrams across two families:

Family	Diagrams
Structure (7)	Class, Object, Component, Deployment, Package, Composite Structure, Profile
Behavior (7)	Use Case, Activity, State Machine, Sequence, Communication, Interaction Overview, Timing

© University of Southampton

Structure Diagrams

1. Class Diagram

The central modeling technique in object-oriented design. Describes the **types of objects** in a system and the static relationships between them. A class box has three compartments: **name** (top, the only mandatory part), **attributes** (middle, `type` after the colon), **methods** (bottom, return type after the colon).

Visibility modifiers on attributes/methods:

Symbol	Visibility
`+`	Public
`-`	Private
`#`	Protected
`~`	Package

© University of Southampton

1. Class Diagram — perspectives

Method parameter direction: `in` (used, not changed by the method), `inout` (used and changed), `out` (purely a return channel).


Three perspectives for drawing the same class diagram, depending on project stage:

- **Conceptual** — real-world domain entities, language-independent.
- **Specification** — software abstractions/interfaces, no implementation detail.
- **Implementation** — the actual classes in a specific language/technology.

© University of Southampton

1. Class Diagram — six relationship types

This single diagram threads all six relationship types through one running example:



© University of Southampton

1. Class Diagram — relationships reference (1/2)

Relationship	Arrow	Meaning
Association	`-->` plain line, optional verb + multiplicity	A connects to B (e.g. *Person works for Company*)
Inheritance / Generalization	`<|--` hollow triangle → parent	Square/Rectangle/Circle are kinds of Shape
Realization	`<|..` dashed hollow triangle → interface	Person/Corporation implement the Owner interface

© University of Southampton

1. Class Diagram — relationships reference (2/2)

Relationship	Arrow	Meaning
Dependency	`..>` dashed arrow → depended-on class	Person.hasRead() uses Book without storing it
Aggregation	`o--` hollow diamond → whole	Workstation = Chair + Desk + Computer + Fan; delete the workstation, the parts survive
Composition	`*--` filled diamond → whole	A Body is made of Organs; delete the body, the organs die with it

© University of Southampton

1. Class Diagram — takeaway

> UML is a planning tool, not decoration — sketch the class diagram *before* writing the code, not after.


© University of Southampton

2. Object Diagram

An **instance** of a class diagram: a snapshot of concrete objects, their attribute values, and the links between them at one point in time. Limited but useful scope — mainly for illustrating data-structure examples or validating a class diagram against a test case. Object names are written `objectName : ClassName`, underlined.

© University of Southampton

2. Object Diagram — example



A robot's world-view: it has identified an enclosed area with three walls and a door.

© University of Southampton

3. Component Diagram

Shows how components are wired together into larger components or systems — the architecture of components and their dependencies, including runtime, executable, and source-code components. Each component exposes a **provided interface** (lollipop symbol — services it offers) and/or a **required interface** (socket symbol — services it needs) on its ports.

A **subsystem** is a special kind of component — same notation, marked `«subsystem»` instead of `«component»`.

© University of Southampton


3. Component Diagram — example



© University of Southampton

4. Deployment Diagram

Models the **physical** aspect of a system: hardware nodes and the software artifacts deployed on them. A 3D box represents a node (hardware or software); lines between nodes represent communication paths, optionally stereotyped with the protocol.



© University of Southampton

4. Deployment Diagram — planning checklist

Condensed from the full list: installation procedure and failure points, backups and rollback, data conversion, version-compatibility during rollout, staff/user training and documentation, integration with existing systems, reliability/failover equipment, and post-deployment security (firewalls, physical access).

© University of Southampton

5. Package Diagram

Groups related model elements into **packages** (UML's folders) to manage scope and show dependencies between subsystems/modules — e.g. a layered application. Packages can nest. One package depends on another (dashed arrow) if a change in the second can force a change in the first.


Element visibility inside a package:

Symbol	Visibility	Visible to
`+`	Public	Everyone who can see the namespace
`#`	Protected	Elements related by generalization
`~`	Package	Elements inside the same package
`-`	Private	Nothing outside the owning namespace

© University of Southampton

5. Package Diagram — dependency stereotypes

`«use»` (default — client uses supplier's public elements by name), `«import»` (supplier's public elements become public in the client), `«access»` (supplier's public elements become private in the client), `«trace»` (historical link between model versions, rare in practice).



Track Order and Order Details depend on each other (bidirectional use); Shipping imports Track Order for easier navigation; Track Order depends on the UI framework.


© University of Southampton

6. Composite Structure Diagram

Zooms inside a single class (or collaboration) to show its internal **parts**, **ports**, and **connectors** — the micro-level view that a plain class diagram's aggregation/composition arrows can't express. A part is named `partName : PartType[multiplicity]`. References to objects *outside* the class being modeled are drawn as dashed rectangles.

© University of Southampton

6. Composite Structure Diagram — example



© University of Southampton

6. Composite Structure Diagram — collaboration

A **collaboration** is the related concept at the behavior level: it names only the roles and connectors needed to achieve one specific goal (e.g. a car's *wheels* and *engine* as parts, *front axle*/*rear axle* as connectors), rather than modeling the whole structured classifier.

© University of Southampton

7. Profile Diagram


A general extension mechanism for customizing UML for a specific domain (aerospace, medical, finance) or platform (J2EE, .NET), via three mechanisms:

Mechanism	Purpose	Notation
Stereotype	New domain-specific "building block" derived from an existing metaclass	`«stereotypeName»` above the class name
Tag	Extra keyword–value metadata on an element (version, author, test status)	`{key = value}` in curly braces
Constraint	A semantic rule/condition that must always hold	`[constraint text]` in square brackets

© University of Southampton

7. Profile Diagram — example

A stereotype extends a metaclass (solid arrow, filled head, stereotype → metaclass). To use the stereotypes elsewhere, a package applies the profile (dashed arrow, open head, labeled `«apply»`, pointing from the application package to the profile).



© University of Southampton

Behavior Diagrams

8. Use Case Diagram

Captures the **functional requirements** of a system as a set of use cases, the actors who trigger them, and the relationships between use cases — without specifying the order of steps (that's what Activity/Sequence diagrams are for). Keep it simple: more than ~20 use cases on one diagram is a sign you're modeling wrong.


© University of Southampton

8. Use Case Diagram — relationships

Relationship	Notation	Meaning
Extend	Dashed arrow, open head, → base use case, labeled `«extend»`	Optional behavior under a condition (e.g. *Invalid Password* extends *Login*)
Include	Dashed arrow, open head, → included use case, labeled `«include»`	Mandatory reused behavior (e.g. *Request Schedule* includes *Search*)
Generalization	Solid line, hollow triangle → parent use case	Child inherits/overrides the parent's behavior

© University of Southampton

8. Use Case Diagram — example



© University of Southampton

9. Activity Diagram


An extended flowchart modeling **workflow**: how activities/actions are coordinated, including choice, iteration, and concurrency.

Node	Meaning
Initial / Final node	Starts / terminates the flow
Action	A task to perform
Decision / Merge node	Splits down one path / rejoins the paths
Fork / Join node	Splits into parallel flows / combines them back
Object node	An object produced/consumed by the flow (optional)
Swimlane	Groups activities by the actor responsible for them

© University of Southampton

9. Activity Diagram — example

Order-processing: received order forks into a fulfillment path and a billing path that rejoin before finalizing.



© University of Southampton

9. Activity Diagram — swimlanes

Swimlanes add "who does this" on top of the same flow — e.g. an onboarding process split into *Salesperson* (books the meeting, writes the follow-up), *Consultant* (presents, runs the meeting, drafts the contract), and *Secretary* (prepares the room) lanes.

© University of Southampton

10. State Machine Diagram

Describes an object's **state-dependent behavior**: the states it can be in, the events that trigger transitions, and the actions those transitions perform. Based on Harel statecharts. Used alongside sequence diagrams: a state diagram covers *all* events/states/transitions for *one* object; a sequence diagram covers *one* interaction across *all* objects.

Event types: **signal** (async message arrives), **call** (procedural operation invoked), **time** (a duration elapses), **change** (a watched condition becomes true).

© University of Southampton


10. State Machine Diagram — transitions & substates

A **transition** fires when its event occurs *and* its guard condition holds; an **action** executes on the transition (not interruptible). A **composite state** holds **substates**, which can nest; a filled circle marks the *initial* state, a circle-with-ring marks the *final* state, and a circled `H` marks a **history** state (re-enter whichever substate was active when the composite was last exited).

© University of Southampton

10. State Machine Diagram — simple transitions


A heating controller:



© University of Southampton

10. State Machine Diagram — concurrent substates

An auction processes a bid and authorizes payment in parallel; both must finish before the composite state exits.



© University of Southampton

11. Sequence Diagram

Shows how objects/actors interact **over time** for one scenario: participants laid out horizontally (**lifelines**), time flowing down the page. A thin rectangle on a lifeline (**focus of control** / activation) marks the span during which that element is executing. Arrow styles: filled-head solid = **synchronous** (caller waits), open-head solid = **asynchronous** (caller continues), dashed = **return**, arrow to self = **self-message**, arrow into a new box = **create**, large `X` = **destroy**.

© University of Southampton


11. Sequence Diagram — combined fragments

Operator	Meaning
`alt` / `opt`	If/else alternatives / optional block
`par` / `loop`	Concurrent fragments / repeats while true
`break` / `critical`	Early exit / must run uninterrupted
`neg` / `assert`	Invalid interaction / only valid continuation
`strict` / `seq`	Strictly ordered / loosely ordered messages
`ignore` / `ref` / `sd`	Drop listed messages / reference elsewhere / frame whole diagram

© University of Southampton

11. Sequence Diagram — example

Hotel search example, using `alt` for the validation branch:



© University of Southampton

12. Communication Diagram

Semantically equivalent to a sequence diagram (either can be derived from the other) — the difference is purely organizational: a **sequence diagram** arranges messages by **time**; a **communication diagram** arranges objects by **space/relationship** and numbers the messages instead (`1`, `1.1`, `1.2`, `2`, …) to show order. Best when the thing worth seeing is *who talks to whom*, not *when*.

© University of Southampton

12. Communication Diagram — example



Objects are either **suppliers** (receive the message) or **clients** (send it). A message an object sends to itself is drawn as a self-loop, same as in a sequence diagram.


© University of Southampton

13. Interaction Overview Diagram

A high-level **activity diagram whose nodes are interactions** (small sequence diagrams, or `ref` pointers to interactions defined elsewhere) instead of plain actions — useful for stitching several sequence diagrams into one controlled flow without redrawing them inline.

© University of Southampton

13. Interaction Overview Diagram — example



© University of Southampton

13. Interaction Overview Diagram — walkthrough

Employee onboarding: rejecting the offer skips straight to the end; accepting routes through three referenced interactions before the probation decision.


© University of Southampton

14. Timing Diagram

A specialized sequence diagram for showing **when** state or value changes happen, not just their relative order. Lifelines run horizontally (left → right = elapsed time); a **state lifeline** plots which state the object is in at each moment, a **value lifeline** plots a changing value — both change level only when the underlying state/value actually changes. Must stay consistent with the matching sequence/state diagrams for the same object.

© University of Southampton

14. Timing Diagram — example



A car-park gate's state over time — the same object modeled as a state machine diagram, just read along a time axis instead of as a graph of transitions.

© University of Southampton