L7.1 — UML Diagram Types

AICE2005 | Self-Study

University of Southampton

This session is self-reading

No live lecture for L7.1 — work through these notes at your own pace before the week 8 workshop.

- UML Cheat Sheet — quick-reference summary of the notation covered below
- Optional: LinkedIn Learning course — Software Design: Modeling with UML — not assessed, for anyone who wants a video walkthrough alongside these notes

© University of Southampton

UML — The 14 Diagram Types

> UML diagrams split into two families: **structure diagrams** (what the system is made of — static) and **behavior diagrams** (what the system does — dynamic).

0. Why UML, and why so many diagrams?

UML (Unified Modeling Language) is a standardized set of diagram notations for defining, visualizing, and documenting the artifacts of a software system — and sometimes a business model. It gives object-oriented teams a shared vocabulary to communicate designs, explore alternatives, and validate architecture before writing code.

© University of Southampton

UML — The 14 Diagram Types

There isn't one "UML diagram" because no single view can serve everyone on a project — an architect, a coder, a tester, and a technical writer each need a different angle and level of detail on the same system. UML covers that by splitting into 14 diagrams across two families:

Family	Diagrams
Structure (7)	Class, Object, Component, Deployment, Package, Composite Structure, Profile
Behavior (7)	Use Case, Activity, State Machine, Sequence, Communication, Interaction Overview, Timing

© University of Southampton

Structure Diagrams

1. Class Diagram

The central modeling technique in object-oriented design. Describes the **types of objects** in a system and the static relationships between them. A class box has three compartments: **name** (top, the only mandatory part), **attributes** (middle, `type` after the colon), **methods** (bottom, return type after the colon).

Visibility modifiers on attributes/methods:

Symbol	Visibility
`+`	Public
`-`	Private
`#`	Protected
`~`	Package

© University of Southampton

1. Class Diagram — perspectives

Method parameter direction: `in` (used, not changed by the method), `inout` (used and changed), `out` (purely a return channel).

Three perspectives for drawing the same class diagram, depending on project stage:

- **Conceptual** — real-world domain entities, language-independent.
- **Specification** — software abstractions/interfaces, no implementation detail.
- **Implementation** — the actual classes in a specific language/technology.

© University of Southampton

1. Class Diagram — six relationship types

This single diagram threads all six relationship types through one running example:

classDiagram class Person { -String name +hasRead(Book) bool } class Company { +String name } class Book Person "1" --> "many" Company : works for Person ..> Book : depends on (hasRead) class Shape class Square class Rectangle class Circle Shape <|-- Square Shape <|-- Rectangle Shape <|-- Circle class Owner { <<interface>> +buy() +sell() } class Corporation Owner <|.. Person Owner <|.. Corporation class Workstation class Chair class Desk class Computer class Fan Workstation o-- Chair Workstation o-- Desk Workstation o-- Computer Workstation o-- Fan class Body class Organ Body *-- Organ

© University of Southampton

1. Class Diagram — relationships reference (1/2)

Relationship	Arrow	Meaning
Association	`-->` plain line, optional verb + multiplicity	A connects to B (e.g. *Person works for Company*)
Inheritance / Generalization	`<|--` hollow triangle → parent	Square/Rectangle/Circle are kinds of Shape
Realization	`<|..` dashed hollow triangle → interface	Person/Corporation implement the Owner interface

© University of Southampton

1. Class Diagram — relationships reference (2/2)

Relationship	Arrow	Meaning
Dependency	`..>` dashed arrow → depended-on class	Person.hasRead() uses Book without storing it
Aggregation	`o--` hollow diamond → whole	Workstation = Chair + Desk + Computer + Fan; delete the workstation, the parts survive
Composition	`*--` filled diamond → whole	A Body is made of Organs; delete the body, the organs die with it

© University of Southampton

1. Class Diagram — takeaway

> UML is a planning tool, not decoration — sketch the class diagram *before* writing the code, not after.

© University of Southampton

2. Object Diagram

An **instance** of a class diagram: a snapshot of concrete objects, their attribute values, and the links between them at one point in time. Limited but useful scope — mainly for illustrating data-structure examples or validating a class diagram against a test case. Object names are written `objectName : ClassName`, underlined.

© University of Southampton

2. Object Diagram — example

```
flowchart LR r["r : Robot
state = moving"] --> w["w : World"] w --> a1["a1 : Area"] w --> a2["a2 : Area"] a2 --> wall1["wall1 : Wall
width = 2m"] a2 --> wall2["wall2 : Wall
width = 3m"] a2 --> wall3["wall3 : Wall
width = 2m"] a2 --> door1["door1 : Door"] wall1 --- wall2 wall2 --- wall3
```

A robot's world-view: it has identified an enclosed area with three walls and a door.

© University of Southampton

3. Component Diagram

Shows how components are wired together into larger components or systems — the architecture of components and their dependencies, including runtime, executable, and source-code components. Each component exposes a **provided interface** (lollipop symbol — services it offers) and/or a **required interface** (socket symbol — services it needs) on its ports.

A **subsystem** is a special kind of component — same notation, marked `«subsystem»` instead of `«component»`.

© University of Southampton

3. Component Diagram — example

flowchart LR PaymentGateway(["PaymentGateway
«required»"]) --> OrderService subgraph OrderService["«component» OrderService"] direction LR end
OrderService --> OrderAPI(["OrderAPI
«provided»"])

© University of Southampton

4. Deployment Diagram

Models the **physical** aspect of a system: hardware nodes and the software artifacts deployed on them. A 3D box represents a node (hardware or software); lines between nodes represent communication paths, optionally stereotyped with the protocol.

```
flowchart TD Client["«device»
Client PC"] -->|HTTP| WebServer["«node»
Web Server"] WebServer -->|SQL| DBServer["«node»
Database Server"]
```


© University of Southampton

4. Deployment Diagram — planning checklist

Condensed from the full list: installation procedure and failure points, backups and rollback, data conversion, version-compatibility during rollout, staff/user training and documentation, integration with existing systems, reliability/failover equipment, and post-deployment security (firewalls, physical access).

© University of Southampton

5. Package Diagram

Groups related model elements into **packages** (UML's folders) to manage scope and show dependencies between subsystems/modules — e.g. a layered application. Packages can nest. One package depends on another (dashed arrow) if a change in the second can force a change in the first.

Element visibility inside a package:

Symbol	Visibility	Visible to
`+`	Public	Everyone who can see the namespace
`#`	Protected	Elements related by generalization
`~`	Package	Elements inside the same package
`-`	Private	Nothing outside the owning namespace

© University of Southampton

5. Package Diagram — dependency stereotypes

`«use»` (default — client uses supplier's public elements by name), `«import»` (supplier's public elements become public in the client), `«access»` (supplier's public elements become private in the client), `«trace»` (historical link between model versions, rare in practice).

flowchart LR subgraph OrderProcessing["«package» Order Processing Subsystem"] TrackOrder["Track Order"] OrderDetails["Order Details"] Shipping["Shipping"] end UIFramework["«package» UI Framework"] TrackOrder -.->|"«use»"| OrderDetails OrderDetails -.->|"«use»"| TrackOrder Shipping -.->|"«import»"| TrackOrder TrackOrder -.->|"«use»"| UIFramework
Track Order and Order Details depend on each other (bidirectional use); Shipping imports Track Order for easier navigation; Track Order depends on the UI framework.

© University of Southampton

6. Composite Structure Diagram

Zooms inside a single class (or collaboration) to show its internal **parts**, **ports**, and **connectors** — the micro-level view that a plain class diagram's aggregation/composition arrows can't express. A part is named `partName : PartType[multiplicity]`. References to objects *outside* the class being modeled are drawn as dashed rectangles.

© University of Southampton

6. Composite Structure Diagram — example

flowchart TD subgraph ComputerSystem["«composite» Computer System"] PSU[Power Supply Unit] Motherboard CPU[Central Processing Unit] Memory[Memory Module] HDD[Hard Disk] DVD PSU --> Motherboard Motherboard --> CPU Motherboard --> Memory Motherboard --> HDD Motherboard --> DVD end

© University of Southampton

6. Composite Structure Diagram — collaboration

A **collaboration** is the related concept at the behavior level: it names only the roles and connectors needed to achieve one specific goal (e.g. a car's *wheels* and *engine* as parts, *front axle*/*rear axle* as connectors), rather than modeling the whole structured classifier.

© University of Southampton

7. Profile Diagram

A general extension mechanism for customizing UML for a specific domain (aerospace, medical, finance) or platform (J2EE, .NET), via three mechanisms:

Mechanism	Purpose	Notation
Stereotype	New domain-specific "building block" derived from an existing metaclass	`«stereotypeName»` above the class name
Tag	Extra keyword–value metadata on an element (version, author, test status)	`{key = value}` in curly braces
Constraint	A semantic rule/condition that must always hold	`[constraint text]` in square brackets

© University of Southampton

7. Profile Diagram — example

A stereotype extends a metaclass (solid arrow, filled head, stereotype → metaclass). To use the stereotypes elsewhere, a package applies the profile (dashed arrow, open head, labeled `«apply»`, pointing from the application package to the profile).

classDiagram class Component class AbstractBean { <<stereotype>> } class EntityBean class SessionBean Component <|-- AbstractBean : extends metaclass AbstractBean <|-- EntityBean AbstractBean <|-- SessionBean

The EJB profile: `AbstractBean` extends the `Component` metaclass; `EntityBean` and `SessionBean` are its two concrete stereotypes.

© University of Southampton

Behavior Diagrams

8. Use Case Diagram

Captures the **functional requirements** of a system as a set of use cases, the actors who trigger them, and the relationships between use cases — without specifying the order of steps (that's what Activity/Sequence diagrams are for). Keep it simple: more than ~20 use cases on one diagram is a sign you're modeling wrong.

© University of Southampton

8. Use Case Diagram — relationships

Relationship	Notation	Meaning
Extend	Dashed arrow, open head, → base use case, labeled `«extend»`	Optional behavior under a condition (e.g. *Invalid Password* extends *Login*)
Include	Dashed arrow, open head, → included use case, labeled `«include»`	Mandatory reused behavior (e.g. *Request Schedule* includes *Search*)
Generalization	Solid line, hollow triangle → parent use case	Child inherits/overrides the parent's behavior

© University of Southampton

8. Use Case Diagram — example

flowchart LR actorUser(["👤 User"]) actorStudent(["👤 Student"]) subgraph System["Account System"] Login(("Login to Account")) InvalidPwd(("Invalid Password")) CorrectPwd(("Correct Password")) RequestSchedule(("Request Schedule")) Search(("Search")) SearchByLecturer(("Search by Lecturer")) SearchByDate(("Search by Date")) end actorUser --- Login InvalidPwd -.->|"«extend»"| Login CorrectPwd -.->|"«extend»"| Login actorStudent --- RequestSchedule RequestSchedule -.->|"«include»"| Search SearchByLecturer --> Search SearchByDate --> Search

© University of Southampton

9. Activity Diagram

An extended flowchart modeling **workflow**: how activities/actions are coordinated, including choice, iteration, and concurrency.

Node	Meaning
Initial / Final node	Starts / terminates the flow
Action	A task to perform
Decision / Merge node	Splits down one path / rejoins the paths
Fork / Join node	Splits into parallel flows / combines them back
Object node	An object produced/consumed by the flow (optional)
Swimlane	Groups activities by the actor responsible for them

© University of Southampton

9. Activity Diagram — example

Order-processing: received order forks into a fulfillment path and a billing path that rejoin before finalizing.

flowchart TD Start((•)) --> OrderReceived[Order Received] OrderReceived --> Fork{fork} Fork --> DetermineDelivery[Determine Delivery Method] DetermineDelivery -->|standard| RegularDelivery[Regular Delivery] DetermineDelivery -->|urgent| OvernightDelivery[Overnight Delivery] RegularDelivery --> Join{join} OvernightDelivery --> Join Fork --> SendInvoice[Send Invoice] SendInvoice --> ReceivePayment[Receive Payment] ReceivePayment --> Join Join --> Finalize[Finalize Order Processing] Finalize --> End((•))

© University of Southampton

9. Activity Diagram — swimlanes

Swimlanes add "who does this" on top of the same flow — e.g. an onboarding process split into *Salesperson* (books the meeting, writes the follow-up), *Consultant* (presents, runs the meeting, drafts the contract), and *Secretary* (prepares the room) lanes.

© University of Southampton

10. State Machine Diagram

Describes an object's **state-dependent behavior**: the states it can be in, the events that trigger transitions, and the actions those transitions perform. Based on Harel statecharts. Used alongside sequence diagrams: a state diagram covers *all* events/states/transitions for *one* object; a sequence diagram covers *one* interaction across *all* objects.

Event types: **signal** (async message arrives), **call** (procedural operation invoked), **time** (a duration elapses), **change** (a watched condition becomes true).

© University of Southampton

10. State Machine Diagram — transitions & substates

A **transition** fires when its event occurs *and* its guard condition holds; an **action** executes on the transition (not interruptible). A **composite state** holds **substates**, which can nest; a filled circle marks the *initial* state, a circle-with-ring marks the *final* state, and a circled `H` marks a **history** state (re-enter whichever substate was active when the composite was last exited).

© University of Southampton

10. State Machine Diagram — simple transitions

A heating controller:

stateDiagram-v2 [*] --> Idle Idle --> CallingStartup : too_hot CallingStartup --> CallingReady : compressor_start CallingReady --> CallingRun : fan_run CallingRun --> Idle : ok CallingRun --> Failure : failure Failure --> Idle : error_reset

© University of Southampton

10. State Machine Diagram — concurrent substates

An auction processes a bid and authorizes payment in parallel; both must finish before the composite state exits.

stateDiagram-v2 [*] --> Auction state Auction { state BidProcessing { [*] --> Bidding Bidding --> Closed Closed --> [*] } -- state PaymentAuthorization { [*] --> Authorizing Authorizing --> Authorized Authorized --> [*] } } Auction --> [*]

© University of Southampton

11. Sequence Diagram

Shows how objects/actors interact **over time** for one scenario: participants laid out horizontally (**lifelines**), time flowing down the page. A thin rectangle on a lifeline (**focus of control** / activation) marks the span during which that element is executing. Arrow styles: filled-head solid = **synchronous** (caller waits), open-head solid = **asynchronous** (caller continues), dashed = **return**, arrow to self = **self-message**, arrow into a new box = **create**, large `X` = **destroy**.

© University of Southampton

11. Sequence Diagram — combined fragments

Operator	Meaning
`alt` / `opt`	If/else alternatives / optional block
`par` / `loop`	Concurrent fragments / repeats while true
`break` / `critical`	Early exit / must run uninterrupted
`neg` / `assert`	Invalid interaction / only valid continuation
`strict` / `seq`	Strictly ordered / loosely ordered messages
`ignore` / `ref` / `sd`	Drop listed messages / reference elsewhere / frame whole diagram

© University of Southampton

11. Sequence Diagram — example

Hotel search example, using `alt` for the validation branch:

sequenceDiagram actor Buyer participant System Buyer->>System: enter author name + click Search System->>System: validate search query alt valid query System->>System: search catalog for author's books System-->>Buyer: display results else invalid query System-->>Buyer: display error message end

© University of Southampton

12. Communication Diagram

Semantically equivalent to a sequence diagram (either can be derived from the other) — the difference is purely organizational: a **sequence diagram** arranges messages by **time**; a **communication diagram** arranges objects by **space/relationship** and numbers the messages instead (`1`, `1.1`, `1.2`, `2`, …) to show order. Best when the thing worth seeing is *who talks to whom*, not *when*.

© University of Southampton

12. Communication Diagram — example

flowchart LR Student -->|"1: returnBook()"| Librarian Librarian -->|"1.1: checkDueDate()"| Catalog[(Book Record)] Librarian -->|"1.2: calculateFine()"| Catalog Librarian -->|"2: confirmReturn()"| Student

Objects are either **suppliers** (receive the message) or **clients** (send it). A message an object sends to itself is drawn as a self-loop, same as in a sequence diagram.

© University of Southampton

13. Interaction Overview Diagram

A high-level **activity diagram whose nodes are interactions** (small sequence diagrams, or `ref` pointers to interactions defined elsewhere) instead of plain actions — useful for stitching several sequence diagrams into one controlled flow without redrawing them inline.

© University of Southampton

13. Interaction Overview Diagram — example

flowchart TD Start((•)) --> Offer{Accept offer?} Offer -->|reject| EndNode((•)) Offer -->|accept| RegisterHR[/"ref: Register with HR"/] RegisterHR --> ApplyCar[/"ref: Apply for Company Car"/] ApplyCar --> Onboard[/"ref: Onboard Customers"/] Onboard --> Probation{Completed probation?} Probation -->|no| Terminate[Contract Terminated] Probation -->|yes| EndNode Terminate --> EndNode

© University of Southampton

13. Interaction Overview Diagram — walkthrough

Employee onboarding: rejecting the offer skips straight to the end; accepting routes through three referenced interactions before the probation decision.

© University of Southampton

14. Timing Diagram

A specialized sequence diagram for showing **when** state or value changes happen, not just their relative order. Lifelines run horizontally (left → right = elapsed time); a **state lifeline** plots which state the object is in at each moment, a **value lifeline** plots a changing value — both change level only when the underlying state/value actually changes. Must stay consistent with the matching sequence/state diagrams for the same object.

© University of Southampton

14. Timing Diagram — example

flowchart LR Closed -->|"car arrives (t=0s)"| Opening Opening -->|"t=2s"| Open Open -->|"car passes (t=5s)"| Closing Closing -->|"t=7s"| Closed

A car-park gate's state over time — the same object modeled as a state machine diagram, just read along a time axis instead of as a graph of transitions.

© University of Southampton