

And on Wednesday... how is it evolving?



DEVELOPMENT PROGRESS


The "V" (or "Vee") model represents the development cycle of a product in a System Engineering manner.



adapted or allocated to their subsystem scope.

(Say a system – with a maximum failure rate λ requirement – is decomposed into two subsystems, each cannot have this same requirement, this would violate the system requirement → allocation is needed.)

The <u>descending</u> part of the V leads to the design and development of all components.




This is the Design Phase of the V.

From system to component specifications, architectures, technologies and designs are studied, discarded and selected.

In the end components are sized based on their respective requirements.

The <u>ascending</u> part of the V corresponds to the testing phase and integration of components and subsystems.



This is the Test & Integration Phase of the V.

The "V" shape is chosen to emphasize the different levels of system, subsystems and components – as horizontal bands on the development cycle.

Now comes the famous V&V of the V...




V&V stands for Verification and Validation.

Validation answers the question: does my system fulfill the needs it is intended to?

**Verification** answers the question: does my system meets the requirements it is designed for?

The **Verification** happens when testing – as these allow for comparison with the specification (yet some requirements are not easily testable).




DEVELOPMENT PROGRESS

V&V stands for Verification and Validation.

Proper Validation can only be performed by allowing the clients to use the final product and judge whether it fulfill their needs.

If the answer is no... this would be painful.

To minimize the risks, regular small "validation loops" can be conducted in the descending phase of the V to ensure the requirements are aligned with the needs of the higher-level system




DEVELOPMENT PROGRESS

Two axes are added here for guidance.

The V should be read as non-linear, as there could be iterations – if the verification fails, the system gets back to the design phase. However, the overall progress is toward the right side of the V.

And toward the bottom of the V, the level of detail increase. This is needed as component design shall be much refined before production than at system level for technology evaluation.



DEVELOPMENT PROGRESS

### Two notes on the System Engineering V-model?

- What is a system for one can be a subsystem for others. From the viewpoint of the aircraft manufacturer, the jet engines are a subsystem.
   From the perspective of the jet engine manufacturer, it is the system. This brings to the next point.
- 2. There is not a single V. As soon as the system is decomposed into subsystems, these are parallel developments until their integrations. Each would follow its own V.

There are more variants to this V model.

On Wednesday (Nov 27<sup>th</sup>), some will be presented.

Also, we are running <u>a poll</u> to understand which development cycle you are mainly using.

Please vote to let us know!

Comment if you need any further clarification or insights.

