

Introduction to R

Module 1: Basic Environment

Andrew Proctor

andrew.proctor@phdstudent.hhs.se

February 1, 2018



- 1 Intro
- 2 R & Statistical Programming
- 3 Getting Started in R
- 4 Data Types & Operations
- 5 Vectors & Matrices
- 6 Data Frames



Intro



Learning Outcomes

How to:

- Import and transform using standard R functions
- Extend R functionality through packages and user-written programming
- Create compelling presentations for data analysis projects
- Perform basic econometric analysis in R
- Learn basics of Bayesian methods in R



Format

Seven modules:

- Five introducing new topics, with the first ~ 30-45 minutes going over material and the remainder of the time working on exercises.
- One capstone module that brings together everything covered in the first 5 lessons.
- A brief Bayesian methods course at the end.

No homework etc - goal is for everything to be doable in the seminars.

Course content and helpful resources on the course website:

- andrewproctor.github.io/rminicourse/



R & Statistical Programming



Characteristics of R

- R is an open-source language specifically designed for statistical computing (and it's the most popular choice among statisticians)
- Because of its popularity and open-source nature, the R community's package development means it has the most prewritten functionality of any data analysis software.
- Differs from software like Stata, however, in that while you can use prewritten functions, it is equally adept at programming solutions for yourself.
- Because its usage is broader, R also has a steeper learning curve than Stata.



Comparison to other statistical programming software ctd

- **Python:** Another option based more on programming from scratch and with less prewritten commands. Python isn't specific to math & statistics, but instead is a general programming language used across a range of fields. Probably the most similar software choice to R at this point, with better general use (and programming ease) at the cost of less package development specific to econometrics/data analysis.
- **Matlab:** Popular in macroeconomics and theory work, not so much in empirical work. Matlab is powerful, but is much more based on programming “from scratch” using matrices and mathematical expressions.



Useful resources for learning R

- **DataCamp:** interactive online lessons in R.
 - Some of the courses are free (particularly community-written lessons like the one you'll do today), but for paid courses, DataCamp costs about 300 SEK / mo.
- **RStudio Cheat Sheets:** Very helpful 1-2 page overviews of common tasks and packages in R.
- **Quick-R:** Website with short example-driven overviews of R functionality.



Useful resources for learning R ctd

- **StackOverflow:** Part of the Stack Exchange network, StackOverflow is a Q&A community website for people who work in programming. Tons of incredibly good R users and developers interact on StackExchange, so it's a great place to search for answers to your questions.
- **R-Bloggers:** Blog aggregator for posts about R. Great place to learn really cool things you can do in R.
- **R for Data Science:** Online version of the book by Hadley Wickham, who has written many of the best packages for R, including the Tidyverse, which we will cover.



Getting Started in R



RStudio GUI

RStudio is an is an integrated development environment (IDE).

This means that in addition to a script editor, it also let's you view your environments, data objects, plots, help files, etc directly within the application.



RStudio GUI ctd

The screenshot shows the RStudio interface with the following components and callouts:

- Source Pane (Top Left):** Contains an R script file named "Example.R". The script defines a function `afunction` that takes `dataobj` as input and returns it. A red box labeled "Write Scripts" points to this pane.
- Environment Pane (Top Right):** Displays the current environment, showing variables `x` and `y` as numeric vectors. A red box labeled "View data objects" points to this pane.
- Console Pane (Bottom Left):** Shows the execution of the script, displaying the output of `examplemat` and the function definition. A red box labeled "Console to view results of scripts, enter commands outside script pane." points to this pane.
- Help Pane (Bottom Right):** Displays the "Save R Objects" help page. A red box labeled "View Help Files, Plots" points to this pane.

Executing code from the script

To execute a section of code, highlight the code and click “Run” or use Ctrl-Enter.

- For a single line of code, you don't need to highlight, just click into that line.
- To execute the whole document, the hotkey is Ctrl-Shift-Enter.



Style advise

Unlike Stata, with R you don't need any special code to write multiline code - it's already the default (functions are written with parentheses, so its clear when the line actually ends.)

- So there's no excuse for really long lines. Accepted style suggests using a 80-character limit for your lines.
- RStudio has the option to show a guideline for margins. **Use it!**
 - Go to **Tools -> Global Options -> Code -> Display**, then select **Show Margin** and enter 80 characters.

You can also write multiple expressions on the same line by using `;` as a manual line break.



Help files in R

You can access the help file for any given function using the **help function**. You can call it a few different ways:

- ❶ In the console, use **help()**
- ❷ In the console, use **?** immediately followed by the name of the function (no space inbetween)
- ❸ In the Help pane, search for the function in question.

? is shorter, so that's the most frequent method.

```
# Help on the lm (linear regression) function  
?lm
```



Setting the working directory

To set the working directory, use the function `setwd()`. The argument for the function is simply the path to the working directory, in quotes.

However: be sure that the slashes in the path are backslashes (\). For Windows, this is not the case if you copy the path from File Explorer.

```
# Set Working Directory  
setwd("C:/Users/AN.4271/OneDrive -  
Handelshögskolan i Stockholm/MyProject")
```



Comments

To create a comment in R, use a hash (*#*). For example:

```
# Here I add 2 + 2  
2 + 2
```

```
## [1] 4
```



Data Types & Operations



Math operations in R

Examples of basic mathematical operations in R:

```
# Addition and Subtraction
```

```
2 + 2
```

```
## [1] 4
```

```
# Multiplication and Division
```

```
2*2 + 2/2
```

```
## [1] 5
```

```
# Exponentiation and Logarithms
```

```
2^2 + log(2)
```

```
## [1] 4.693147
```



Logical operations in R

You can also evaluate logical expressions in R

```
## Less than
```

```
5 <= 6
```

```
## [1] TRUE
```

```
## Greater than or equal to
```

```
5 >= 6
```

```
## [1] FALSE
```

```
## Equality
```

```
5 == 6
```

```
## [1] FALSE
```



Logical operations in R ctd

You can also use AND (&) and OR (|) operation with logical expressions:

```
## Is 5 equal to 5 OR 5 is equal to 6  
(5 == 5) | (5 == 6)
```

```
## [1] TRUE
```

```
## 5 less 6 AND 6 < 5  
(5 < 6) & (7 < 6)
```

```
## [1] FALSE
```



Defining an object

To define an object, use `<-`. For example

```
# Assign 2 + 2 to the variable x  
x <- 2 + 2
```

Note: In R, there is no distinction between defining and redefining an object (*a la* gen/replace in Stata).

```
y <- 4 # Define y  
y <- y^2 # Redefine y  
y #Print y
```

```
## [1] 16
```



Data classes

Data elements in R are categorized into a few separate classes (ie types)

- **numeric:** Data that should be interpreted as a number.
- **logical:** Data that should be interpreted as a logical statment, ie. TRUE or FALSE.
- **character:** Strings/text.
 - Note, depending on how you format your data, elements that may look like logical or numeric may instead be character.
- **factor:** In affect, a categorical variable. Value may be text, but R interprets the variable as taking on one of limited number of possible values (e.g. sex, municipality, industry etc)



What's the object class?

```
a <- 2; class(a)
```

```
## [1] "numeric"
```

```
b <- "2"; class(b)
```

```
## [1] "character"
```

```
c <- TRUE; class(c)
```

```
## [1] "logical"
```

```
d <- "True"; class(d)
```

```
## [1] "character"
```



Vectors & Matrices



Creating vectors

To create a vector, use the function `c()`.

```
# Create `days` vectors  
days <- c("Mon", "Tues", "Wed",  
          "Thurs", "Fri")
```

```
# Create `temps` vectors  
temps <- c(13, 18, 17, 20, 21)  
# Display `temps` vector  
temps
```

```
## [1] 13 18 17 20 21
```



Naming vectors

You can name a vector by assigning a vector of names to `c()`, where the vector to be named goes in the parentheses.

```
# Assign `days` as names for `temps` vector  
names(temps) <- days  
# Display `temps` vector  
temps
```

```
##      Mon      Tues      Wed Thurs      Fri  
##      13       18       17     20       21
```



Subsetting vectors

There are multiple ways of subsetting data in R. One of the easiest methods for vectors is to put the subset condition in brackets:

```
# Subset temps greater than or equal to 10  
temps[temps>=18]
```

```
##    Tues Thurs    Fri  
##     18     20     21
```



Operations on vectors

Operations on vectors are element-wise. So if 2 vectors are added together, each element of the 2nd vector would be added to the corresponding element from the 1st vector.

```
# Temp vector for week 2
temps2 <- c(8,10,10,15,16)
names(temps2) <- days
# Create average temperature by day
avg_temp <- (temps + temps2) / 2
# Display `avg_temp`
avg_temp
```

##	Mon	Tues	Wed	Thurs	Fri
##	10.5	14.0	13.5	17.5	18.5



Matrices

- Data in a 2-dimensional structure can be represented in two formats, as a *matrix* or as a *data frame*.
- A matrix is used for 2D data structures of a single data type (like atomic vectors).
 - Usually, matrices are composed of numeric objects.
- To create a matrix, use the **matrix()** command.



Matrices ctd

The syntax of **matrix()** is:

```
matrix(x, nrow=a, ncol=b, byrow=FALSE/TRUE)
```

- x is the data that will populate the matrix.
- nrow* and *ncol* specify the number of rows and columns, respectively. Generally need to specify just 1 since the number of elements and a single condition will determine the other.
- byrow* specifies whether to fill in the elements by row or column. The default is **byrow=FALSE**, ie the data is filled in by column.



Creating a matrix from scratch

A simple example of creating a matrix would be:

```
matrix(1:6, nrow=2, ncol=3, byrow=FALSE)
```

```
##      [,1] [,2] [,3]  
## [1,]    1    3    5  
## [2,]    2    4    6
```

Note the difference in appearance if we instead **byrow=TRUE**

```
matrix(1:6, nrow=2, ncol=3, byrow=TRUE)
```

```
##      [,1] [,2] [,3]  
## [1,]    1    2    3  
## [2,]    4    5    6
```



Creating a matrix from scratch ctd

Using the same `c()` function as in the creation of a vector, we can specify the values of a matrix:

```
matrix(c(13,18,17,20,21,
         8,10,10,15,16),
       nrow=2, byrow=TRUE)
```

```
##      [,1] [,2] [,3] [,4] [,5]
## [1,]   13   18   17   20   21
## [2,]    8   10   10   15   16
```

- Note that the line breaks in the code are purely for readability purposes. Unlike Stata, R allows you to break code over multiple lines without any extra line break syntax.



Creating a matrix from vectors

Instead of entering in the matrix data yourself, you may want to make a matrix from existing data vectors:

```
# Create temps matrix
temps.matrix <- matrix(c(temps,temps2), nrow=2,
                        ncol=5, byrow=TRUE)

# Display matrix
temps.matrix
```

```
##      [,1] [,2] [,3] [,4] [,5]
## [1,]   13   18   17   20   21
## [2,]    8   10   10   15   16
```



Naming rows and columns

- Naming rows and columns of a matrix is pretty similar to naming vectors.

-Only here, instead of using `names()`, we use `rownames()` and `colnames()`

```
# Create temps matrix
rownames(temps.matrix) <- c("Week1", "week2")
colnames(temps.matrix) <- days
# Display matrix
temps.matrix
```

##		Mon	Tues	Wed	Thurs	Fri
##	Week1	13	18	17	20	21
##	week2	8	10	10	15	16



Matrix operations

In R, matrix multiplication is denoted by `%*%`, as in `A %*% B`

`A * B` instead performs *element-wise* (Hadamard) multiplication of matrices, so that `A * B` has the entries a_1b_1 , a_2b_2 etc.

- An important thing to be aware of with R's `A * B` notation, however, is that if either of the terms is a 2D vector, the terms of this vector will be distributed elementwise to each column of the matrix.



Elementwise operations with a vector and Matrix

```
vecA; matB
```

```
## [1] 1 2
```

```
##      [,1] [,2] [,3]  
## [1,]    1    2    3  
## [2,]    4    5    6
```

```
vecA * matB
```

```
##      [,1] [,2] [,3]  
## [1,]    1    2    3  
## [2,]    8   10   12
```



Data Frames



Creating a data frame

- Most of the time you'll probably be working with datasets that are recognized as data frames when imported into R.
- But you can also easily create your own data frames.
- This might be as simple as converting a matrix to a data frame:

```
mydf <- as.data.frame(matB)  
mydf
```

```
##      V1 V2 V3  
## 1     1  2  3  
## 2     4  5  6
```



Creating a data frame ctd

Another way of creating a data frame is to combine other vectors or matrices (of the same length) together.

```
mydf <- data.frame(vecA,matB)
mydf
```

```
##      vecA X1 X2 X3
## 1      1  1  2  3
## 2      2  4  5  6
```



Defining a column of a data frame (or other 2D object):

Once you have a multidimensional data object, you will usually want to create or manipulate particular columns of the object.

The default way of invoking a named column in R is by appending a dollar sign and the column name to the data object.



Example of adding a new column to a data frame

```
wages # View wages data frame
```

```
##           wage schooling      sex exper
## 1 134.23058          13 female      8
## 2 249.67744          13 female     11
## 3  53.56478          10 female     11
```

```
wages$expersq <- wages$exper^2; wages # Add expersq
```

```
##           wage schooling      sex exper expersq
## 1 134.23058          13 female      8       64
## 2 249.67744          13 female     11      121
## 3  53.56478          10 female     11      121
```



Viewing the structure of a data frame

Like viewing the class of a homogenous data object, it's often helpful to view the structure of data frames (or other 2D objects).

- You can easily do this using the `str()` function.

```
# View the structure of the wages data frame  
str(wages)
```

```
## 'data.frame':      3 obs. of  5 variables:  
## $ wage      : num  134.2 249.7 53.6  
## $ schooling: int   13 13 10  
## $ sex       : Factor w/ 2 levels "female","male": 1 1 1  
## $ exper     : int    8 11 11  
## $ expersq   : num   64 121 121
```



Changing the structure of a data frame:

A common task is to redefine the classes of columns in a data frame.

- Common commands can help you with this when the data is formatted suitably:
 - `as.numeric()` will take data that “looks like numbers” but are formatted as characters/factors and change their formatting to numeric.
 - `as.character()` will take data formatted as numbers/factors and change their class to character.
 - `as.factor()` will reformat data as factors, taking by default the unique values of each column as the possible factor levels.



More about factors

Although `as.factor()` will suggest factors from the data, you may want more control over how factors are specified.

With the `factor()` function, you supply the possible values of the factor and you can also specify ordering of factor values if your data is ordinal.



Example of creating ordered factors

A dataset on number of extramarital affairs from Fair (Econometrica 1977) has the following variables: number of affairs, years married, presence of children, and a self-rated (Likert scale) 1-5 measure of marital happiness.

```
str'affairs) # view structure
```

```
## 'data.frame':    3 obs. of  4 variables:  
## $ affairs: num  0 0 1  
## $ yrs marr: num  15 1.5 7  
## $ child : Factor w/ 2 levels "no","yes": 2 1 2  
## $ mrating: int  1 5 3
```



Example of creating ordered factors ctd

```
affairs$mrating <-factor(affairs$mrating,
  levels=c(1,2,3,4,5), ordered=TRUE)
str(affairs)
```

```
## 'data.frame':    3 obs. of  4 variables:
## $ affairs: num  0 0 1
## $ yrs marr: num  15 1.5 7
## $ child : Factor w/ 2 levels "no","yes": 2 1 2
## $ mrrating: Ord.factor w/ 5 levels "1"<"2"<"3"<"4"<..:
```

Note that the marital rating (*mrating*) initially was stored as an integer, which is incorrect. Using factors preserves the ordering while not asserting a numerical relationship between values.



Subsets and selections in data frames

Similar to subsetting a vector, matrices & data frames can also be subsetted for both rows and columns by placing the selection arguments in brackets after the name of the data object:

```
dataframe[RowArgs, ColArgs]
```

Arguments can be:

- Row or column numbers (eg `mydf[1,3]`)
- Row or column names
- Rows (ie observations) that meet a given condition



Example of subsetting a data frame

```
# Subset of wages df with schooling > 10, exper > 10  
wages[(wages$schooling > 10) & (wages$exper > 10),]
```

```
##           wage schooling      sex exper expersq  
## 2 249.6774          13 female    11      121
```

Notice that the column argument was left empty, so all columns are returned by default.

