

UAV Autonomous Landing

Team Expeditus

SDSMT MCS

December 9, 2015

UAV Autonomous Landing Project

Team Expeditus

Jonathan Dixon, Dylan Geyer, Christopher Smith, Steven Huerta

Sponsor

Dr. Larry Pyeatt

Goal

Demonstrate the capability of a UAV to autonomously take-off, navigate through some waypoints, return to the landing pad, and land with a minimum of distance and orientation error.

Requirements

Goal

- receive a set of waypoints
- autonomously take-off
- navigate through waypoints
- return to launch pad
- **land with $\pm .1\text{m}$ distance and $\pm 15^\circ$ orientation error**

Limitations

- landing platform is a fixed position
- landing platform is a stable, horizontal surface
- environment is ideal(no wind, gps available, no obstacles)

User Stories/Backlog

- **User 1(U-1):**

As a user, I want to communicate the waypoints to the UAV.

- **Owner 1(O-1):**

As an owner, I want the UAV to autonomously take-off from the landing pad.

- **Owner 2(O-2):**

As an owner, I want the UAV to autonomously navigate through a set of waypoints.

- **Owner 3(O-3):**

As an owner, I want the UAV to autonomously return to the location of the landing pad.

- **Owner 4(O-4):**

As an owner, I want the UAV to autonomously land on the landing pad without damaging the craft.

- **Owner 5(O-5):**

As an owner, I want the UAV to autonomously land on the landing pad with the correct orientation.

As a user, I want to communicate the waypoints to the UAV.

Task No.	Task	Date Completed	Sprint
1	Review previous method/interface for communicating coordinates to UAV.	10/05/15	1
2	Review code that communicates with quadrotor	10/16/15	2
3	Review code that allows a user to input waypoints	10/16/15	2

As an owner, I want the UAV to autonomously take-off from the landing pad.

Task No.	Task	Date Completed	Sprint
1	Review previous implementation for autonomous take-off.	10/05/15	1
2	Review code that enables the quadrotor to autonomously take-off from landing pad	10/16/15	2

As an owner, I want the UAV to autonomously navigate through a set of waypoints.

Task No.	Task	Date Completed	Sprint
1	Review previous implementation for navigating waypoints.	10/05/15	1
2	Review code that enables the quadrotor to autonomously navigate through a series of way-points	10/16/15	2

As an owner, I want the UAV to autonomously return to the location of the landing pad.

Task No.	Task	Date Completed	Sprint
1	Review previous implementation to autonomously return to location of landing pad	10/05/15	1
2	Review code that allows the autonomous return of the UAV to the landing pad.	10/16/15	2

As an owner, I want the UAV to autonomously land on the landing pad without damaging the craft

Task No.	Task	Date Completed	Sprint
1	Review previous implementation for autonomous landing	10/05/15	1
2	Install previous implementation	10/19/15	2
3	Test previous implementation	10/26/15	2

As an owner, I want the UAV to autonomously land on the landing pad with the correct orientation.

Task No.	Task	Date Completed	Sprint
1	Review previous implementation for autonomous landing	10/05/15	1
2	Install previous implementation	10/19/15	2
3	Test previous implementation	10/26/15	2

Initial Common Tasks

Task No.	Task	Date Completed	Sprint
1	Install Ubuntu 14.04 or some other ROS Indigo/Jade distro compliant OS.	09/25/15	1
2	Setup Gazebo 6.+	09/25/15	1
3	Download Rviz package	09/25/15	1
4	Setup Simulation Environment	11/02/15	2

C Continued

Initial Common Tasks

Task No.	Task	Date Completed	Sprint
5	Review previous iteration of project documentation	09/25/15	1
6	Inspect current quadrotor configuration	09/28/2015	2
7	Identify parts needed for quadrotor	11/02/2015	2
8	Acquire parts needed for hexrotor	12/01/2015	3

Sprint 1 - Successes

- Revised project scope
- Product Backlog - User Stories
- Setup Development Environment
- Review previous years hardware and software

Sprint 1 - Setbacks

- Previous years UAV unusable
- Previous years flight code unusable

Sprint 2 - Successes

- Visual Homography Code repurposed
- Created simulation environment
- Ordered parts for new Hex-copter

Sprint 2 - Setbacks

- Simulation only supports manual control


Sprint 3 - Successes

- Assembled Frame, Motors, ESC's
- Many SITL simulations
- Waypoint Publisher publishes mavros commands
- Working image homography code
- Becoming familiar with python openCV libraries


Sprint 3 - Setbacks

- Pixhawk delayed 2 weeks, build not completed
- SITL simulations rejected waypoint files
- SITL simulations rejected mavros commands

Design



Architecture



Hardware Requirements

- ODroid XU4
- Pixhawk Flight Controller
- GPS peripheral
- Camera
- Battery
- UAV(Frame, Motors, ESCs, Power Distribution Board)

Software Requirements

- Mavlink
- Python
- OpenCV
- Robot Operating System(ROS) Indigo/Jade Distro
- Ubuntu 14.04

UAV Design & Tech Specs

Physical design of the hex-copter is the **Turnigy Talon Hexcopter**




- Blob detection is used to detect colored circles
- For each color we are looking for, look for a group of pixels over a certain size
- that is considered a "blob"

Homography



Homography




Design & Tech

- Sarsa
- 2D State Space
- 3D State Space

Setbacks

- Research and familiarizing
- Simulation Environment

Simulation Design & Tech Specs



As an owner, I want the UAV to autonomously take-off from the landing pad.

Task No.	Task	Testing
1	Review previous implementation for autonomous take-off.	Send mission containing takeoff followed by hover command in simulation.
2	Review code that enables the quadrotor to autonomously take-off from landing pad	Upload code to physical UAV and send mission containing takeoff followed by hover command with manual override enabled.

As an owner, I want the UAV to autonomously navigate through a set of waypoints.

Task No.	Task	Test
1	Review previous implementation for navigating waypoints.	Send mission containing takeoff followed by waypoints and once the last waypoint is reached a hover command all in simulation.
2	Review code that enables the quadrotor to autonomously navigate through a series of way-points	Upload code to physical UAV and send mission again with manual override enabled

As an owner, I want the UAV to autonomously return to the location of the landing pad.

Task No.	Task	Test
1	Review previous implementation to autonomously return to location of landing pad	The last waypoint from the previous test should be the landing pad but to verify a image match will be used in simulation that will verify that the UAV is in fact above the landing pad.
2	Review code that allows the autonomous return of the UAV to the landing pad.	The physical UAV will match what it sees with its camera to a image it has stored of the landing pad at multiple heights.

Visual Homography Landing Testing - O-4

As an owner, I want the UAV to autonomously land on the landing pad without damaging the craft

Task No.	Task	Test
1	Review previous implementation for autonomous landing	The UAV should be able to detect the landing pad
2	Install previous implementation	The UAV should be able to begin to lower onto the pad
3	Test previous implementation	The UAV should land gently on the pad

Visual Homography Landing Testing - O-5

As an owner, I want the UAV to autonomously land on the landing pad with the correct orientation.

Task No.	Task	Test
1	Review previous implementation for autonomous landing	The UAV should be able to calculate its angle wrt the pad
2	Install previous implementation	The UAV should be able to rotate to match the pad
3	Test previous implementation	UAV should maintain orientation throughout descent

Integration - U-1

As a user, I want to communicate the waypoints to the UAV.

Task No.	Task	Test
1	Review previous method/interface for communicating coordinates to UAV.	Connect GPS to pixhawk and verify it receives a connection and in Mavros verify we can retrieve gps coordinates from gps in ROS.
2	Review code that communicates with quadrotor	Verify that all commands in Mavros can be sent to and accepted by the Pixhawk and it acts appropriately
3	Review code that allows a user to input waypoints	Verify that user entered waypoints can be uploaded into Pixhawk Successfully with mavros.



Remaining Backlog

- **User 1(U-1)**
- **Owner 1(O-1)**
- **Owner 2(O-2)**
- **Owner 3(O-3)**
- **Owner 4(O-4)**
- **Owner 5(O-5)**
- **Common**

Revised Goals

- Project Goals remain fixed

Risk Analysis

- Simulation: SITL has proven to be problematic
- UAV Build: Borrowing items from UAV Team (Radio and Control)
- UAV Build: One UAV for physical testing and demonstration
- Landing Algorithm: Many approaches, we may pick the wrong one

- Simulation:
 - Attempt HIL as Alternative
- UAV Build(Sharing)
 - Schedule use of tools to prevent conflict
 - Request more funding if schedule is untenable
- UAV Build(One Shot)
 - Integrate manual control override
 - Validate solutions through simulation

Sprint 3.5 12/16/15 to 1/10/16

- Finish UAV Build(C)
- Manual Flight of UAV(C)
- Autonomous Flight of UAV(C,U-1,O-1,O-2,O-3)
- Resolve Simulation Issues(C)

At the end of break, 3 backlog items will have been completed

Sprint 4 1/18/16 2/5/16

- Finish Landing Algorithm Simulations(O-4,O-5)

At the end of sprint 4, we should have a landing approach validated by simulation.

Timeline...continued

Sprint 5 2/15/16 3/4/16

- Integration of Landing Autonomy on UAV(O-4,O-5)

At the end of sprint 5, we should have completed the remainder of backlog items.

Sprint 6 3/21/16 4/15/16

- Refinement

At the end of sprint 6, project will be complete

Budget

Item	Qty	Price	Total
Frame	1	\$79.99	\$79.99
Motors	8	\$23.99	\$191.92
ESCs	8	\$17.78	\$142.24
Pixhawk	1	\$199.99	\$199.99
Power Distribution	1	\$19.99	\$19.99
GPS Mast	2	\$10.00	\$20.00
GPS	2	\$89.99	\$179.98
Power Module	1	\$24.99	\$24.99
Odroid XU4	1	\$75.95	\$75.95
Props(set of 4)	3	\$7.55	\$22.65
TOTAL			\$957.70

Intellectual Property:
Project is owned by SDSMT


Licensing for Dependencies:

- OpenCV: BSD
- ROS: BSD
- Mavlink: LGPL version 3
- QGroundControl: GPL version 3


Demos

- PX4 ROS SITL
- Ground Control Station
- Visual Homography


Simulation - PX4 ROS SITL



PX4 ROS SITL...continued



PX4 ROS SITL...continued




PX4 ROS SITL...continued


Ground Control Station - QGroundControl



Ground Control Station...continued




Ground Control Station...continued




Vision-Based Landing

- Began playing with last year's code
- Able to detect three blobs and distance to target




Vision-Based Landing...continued

- After our computer vision class, we considered adding a fourth circle
- This gives us a square target instead of triangle





frame



END

Questions