UAV Autonomous Landing

Team Expeditus

Dept. of Computer Science, SDSMT

October 20, 2015

Team

Team Expeditus
Jonathan Dixon, Dylan Geyer, Christopher Smith, Steven Huerta

Sponsor
Dr. Larry Pyeatt

Goal
Software to autonomously take-off, navigate to set waypoints, return to launch pad, and land

Phase Objectives

Phase I

- Build UAV
- Flight Controller Operating Correctly
- Simulation Environment Available

Phase II

- Autonomous landing ready for simulation
- Autonomous landing ready for UAV

Testing

Phase I

- Manual Flight of UAV
- Autonomous Flight of UAV

Phase II

- Autonomous Landing in Simulation
- Autonomous Landing of UAV
- Autonomous Take-off, Navigation, and Landing of UAV

Approach - UAV



Approach - Software



Approach - Landing Vision

Put some stuff here about the landing vision approach, maybe a picture or two

Approach - Landing AI

Artificial Neural Network (ANN) Approach:

- Use Flight Controller to reach landing pad waypoint
- Switch to landing mode using ANN
- Land on landing pad or get within some distance to switch to vision

Development - Software

Development OS: Ubuntu 14.04
Languages: C++ and Python

Software Tools

- Robot Operating System(ROS)
- Gazebo
- APM Planner

Simulation & Testing:

- Rotors Sim package - Provides Models for Gazebo



Development - Software Contd.

- MavRos - Communication with Pixhawk through ROS
- Testing - All components will be tested in simulation before being deployed on UAV



Hardware Constraints

- 6000mAh Battery
- Power ODroid + Peripherals
- Power 6x DC Motors



Development - Hardware Continued...

Item	Quantity	Total Weight
DC Motor	6	372g
Frame	1	1300g
Battery	1	680g
Camera	2	140g
ODroid	1	48g
GPS Module	1	17g
	Total	2557g

1 Motor at 100% produces 970g of lift
Maximum Lift = 5820g
Motors must run at 2557g / 5820g = 44%

Computational Constraints

- Images: 976 x 582 pixels at $\geq$ 5 images/sec
- Processing 1 image thus requires $\sim$570,000 operations
- ODroid has 8 cores at 1.4 GHz
  - Ideal throughput $\sim$10 Billion operations/sec

Cost

Build 1		Build 2	
Item	Cost	Item	Cost
Controller	$199.99	Controller	$199.99
ODroid	$75.95	ODroid	$75.95
Sensors	$167.23	Sensors	$167.23
Frame Kit	$242.48		
Power Kit	$119.98		
Radio Set	$100.00		
Extra Parts	$95.15		
TOTAL	$1000.78	**TOTAL**	$443.17

Work Accomplished

General

- Review previous iteration documentation & code
- Begin pilot training for manual control
- Review Landing Pad model with Landing Pad teams

Setup Development Environment

- Ubuntu 14.04
- Gazebo/Rviz
- ROS - Jade Distro

Inspect Current Quadrotor

- Identify missing or non-functioning components
- Generate order list

Setbacks/Risk

Risk

- Reliance on Flight Controller
- Dependency on external team for Landing Pad
- No UAV Backup

Setbacks

- Non-functional components
- Little carry-over from previous year

Conclusion

Conclusion-y stuff here

Questions?