

The NDDiss2 ϵ class*

2017-05-09

Abstract

The NDDiss2 ϵ class can be used to typeset dissertations submitted to the University of Notre Dame's Graduate School. This class conforms with the Graduate School guidelines as of Spring 2013 for the layout of the Ph.D. dissertations and Master's theses.

Contents

1	Introduction	2
1.1	Disclaimer	2
1.2	Dependencies and Limitations	2
1.3	History	3
2	Quick Start	3
3	Usage	4
3.1	Options	5
4	Arrangement of Contents	6
4.1	Title Page	7
4.2	Copyright Page	7
4.3	Abstract Page(s)	8
4.4	Dedication	8
4.5	Table of Contents; Lists of Figures and Tables	8
4.6	List of Symbols	8
4.7	Preface	9
4.8	Acknowledgments	9
4.9	Text	9
4.10	Appendix	9
4.11	Backmatter	9
4.12	Bibliography	9
4.13	Chapter-wise Bibliography	10

*Version 3.2017.2, dated 2017-05-09.

5	Note For Authors	10
5.1	Tips and Suggestions	11
5.2	You Found Errors?	13
6	Other Packages Used	13
6.1	Generating PDF document	14
7	The Implementation	15

1 Introduction

The L^AT_EX 2_ε document class NDdiss2_ε is suitable for producing dissertations and theses conforming to the Spring 2013 guidelines of the Graduate School at the University of Notre Dame. The package extends the standard L^AT_EX `book` class.

The latest version of this class and related documentation can be found in a few places:

- On CTAN: <https://ctan.org/pkg/nddiss>
- On GitHub: <https://github.com/ndlib/nddiss>
- On the University of Notre Dame's Graduate School website: <http://graduateschool.nd.edu/>

1.1 Disclaimer

While this class does as much formatting as it can, there are a few formatting items that you, the user, must do manually (see Section 5). Please keep in mind that only *you* are responsible for the correct formatting of your dissertation/thesis. Should you have questions, please consult the official formatting guide or email dteditor@nd.edu.

1.2 Dependencies and Limitations

This classfile depends on many other packages to be installed. All of these required packages are available through MiKTeX and TeXLive, and chances are good they are already installed by your TeX distribution. Refer to section 6 for a list of the essential packages.

The document class has only been tested with a small subset of available packages. There are numerous packages you may want to use for your work, but they may have to be modified accordingly. Things lacking include support for the `subfigure` and `subcaption` package and proper formatting of the captions in such an environment. Formatting of the captions could be much easier with the `caption`¹ in general, and is a thing-to-do for future versions. Permitting use of the `subfigure` and `subcaption` packages would also be a good thing to do if an update is

¹`caption` package by Axel Sommerfeldt v3.0b[2004/05/16] and higher

ever made for reasons other than resolving conflicts caused by changing Graduate School regulations. If you want to use a `subfigure` environment and don't need the caption capabilities of the `subcaption` package, adding the following code to your preamble may allow you to do this and still have your captions formatted according to the Graduate School's rules.

```
\usepackage{subcaption}
\makeatletter
\renewcommand\LT@makecaption[3]{%
  \LT@mcol\LT@cols c{\hbox to\z@{\hss\parbox[t]{\LTcapwidth{%
    \vskip\abovetableskip%
    \centering\normalspacing
    #1{#2 }\\[\single@skip]
    {#3}\par
    \endgraf\vskip\belowtablesip}%
    \hss}}}
\makeatother
```

1.3 History

The `NDdiss2 ϵ` package is an extensive rewrite by Sameer Vijay of an earlier `NDthesis` class for formatting dissertations. Megan Patnott updated `NDdiss2 ϵ` to the 2013 Graduate School Formatting guidelines. The `NDThesis` class was by D. A. Peterson.

2 Quick Start

This section provides a template you can use to get started. The distribution comes with a more detailed file, `template.tex`, that is similar, but more detailed.

```
\documentclass[numrefs,final]{nddiss2e}

\begin{document}

\frontmatter

\title{Title in Title Caps}
\author{Your Name}
\work{Dissertation}
\degaward{Doctor of Philosophy}
\advisor{}
\department{}
\maketitle
\makepublicdomain % There is also a copyright option

\begin{abstract}
Abstract here
```

```

\end{abstract}

% dedication is optional
\begin{dedication}
For Someone
\end{dedication}

\tableofcontents
\listoffigures
\listoftables

% list of symbols is optional
\begin{symbols}
\sym{a}{definition of a}
\end{symbol}

% preface is optional
\begin{preface}
Preface here
\end{preface}

\begin{acknowledge}
Thanks to everyone
\end{acknowledge}

\mainmatter

\chapter{A New Dawn} % Chapter 1
All the text ...

\appendix
\chapter{Additional Data} % Appendix A

\backmatter
\bibliographystyle{nddiss2e}
\bibliography{bibdatabase}

\end{document}

```

3 Usage

Invoke the NDdiss2_ϵ document class by adding `\documentclass[\langle options \rangle]{nddiss2e}` at the beginning of your \LaTeX source file. For most people the options `\documentclass[draft]{nddiss2e}` is good enough for the initial revisions. If you want your figures to display, use `\documentclass[review]{nddiss2e}`.

Use the option `\documentclass[final]{nddiss2e}` for your formatting check submission, and `\documentclass[final,noinfo]{nddiss2e}` for the final sub-

mitted version.

If you have two advisors, add the option `twoadvisors` here, and then use `\secondadvisor{}` later on the title page to give the name of the second advisor.

By default, all documents produced using this class are formatted as one-sided, doublespaced, letter-sized pages, per the Graduate School requirements. In theory, the class file’s specifications should override your system’s defaults. If, however, you are getting A4 paper, try adding `\pdfpagewidth{8.5in}` and `\pdfpageheight{11in}` immediately after the `\documentclass` in your file.

3.1 Options

draft Exactly *one* of these options must be used. The **draft** and **review** options enable faster processing of the document and also include annotations to help write and edit it.

The **draft** option enables a fast processing and preliminary document showing the labels for citations, tables, figures etc. and a black solid rule highlighting the horizontal overflows. Additionally, figures are replaced with placement boxes showing where the included figure would be placed. Such a document would be the one you would prepare for revising your text during writing stages.

The **review** option makes it possible to prepare a document that is one step closer to the final version. Almost all the formatting of the final version is present, but the labels and keys as in the **draft** option are also displayed. A document prepared with the **review** option would be the one to personally check for proper formatting and possibly giving to your advisor if she wished to suggest corrections.

The **final** option produces the document to be submitted to the Graduate School for formatting checks and as the final version.

twoadvisors The **twoadvisors** option will produce a title page with space for two advisors. Use the `\secondadvisor` macro command (discussed in Section 4.1) on the title page to give the name of the second advisor.

noinfo The **noinfo** option disables the information page produced when the **review** or **final** style options are used. It is recommended that you only use this option when making the final submission to the Graduate School.

nonatbib With this option, `nddiss2e` will not load the `natbib` package and allow to use a different bibliography package, e.g., `biblatex` instead.

numrefs These options determine how citations are displayed in the text. The default style is **numrefs**. The **numrefs** option produces a numbered citation style by using `natbib` and the “`nddiss2e`” or “`nddiss2enoarticletitles`” citation style file². The **textrefs** option changes the citation style to be similar to “author-date” style with the same files.

sort At most one of these options should be selected. The **sort** option will cause both numerical and “author-date” style references to be sorted in the order that they appear in the bibliography when multiple references are cited. The **compress** option compresses numerical citations, e.g. it turns [1,2,3] into [1-3], and does

²`nddiss2e.bst` is a slight modification of `abbrvnat.bst` in the `natbib` package; `nddiss2enoarticletitles.bst` is essentially the same as `nddiss2e`, but does not display the titles of journal articles, as this is the standard in some fields

nothing to “author-date” style references. The **sort&compress** option first sorts and then compresses numerical references, and only sorts “author-date” style references.

Since the same set of packages and style files result in differing citation formats, refer to the documentation for **natnotes.dvi** in your **TEXMF** tree, to be aware of the various ways in which you can make a citation in your text.

10pt These options adjust the font size of the body text. The choice is only applicable when the **draft** option is used, and defaults to **10pt**. When **review** or **final** is used, this option is ignored and **12pt** is used.

11pt
12pt
twoside The **twoside** option causes the class file to prepare a document meant to be printed double-sided. This option is strictly for if you want to prepare a two-sided document for your own use. The only difference from the one-sided document is in the page layout. Do NOT use this option when preparing to submit it to the Graduate School.

nocenter The **nocenter** option allows non-centered chapter titles. Do NOT turn in your document this way to the Graduate School!

openbib The **openbib** option formats your bibliography in the following manner:

Author

Article/book title

Other information

Website, if applicable

Usually you would not need to use this option since the default layout of the bibliography is acceptable.

4 Arrangement of Contents

A dissertation or a thesis document contains the following parts, in the order listed. Only those marked as optional may be omitted.

1. Title Page
2. Copyright page
3. Abstract (*optional for Master’s thesis*)
4. Dedication (*optional*)
5. Table of Contents
6. List of Figures
7. List of Tables
8. List of Symbols (*optional*)
9. Preface (*optional*)
10. Acknowledgments (*optional*)

11. Text
12. Appendix (or Appendices) (*optional*)
13. Bibliography (or References, or Works cited)

The macros and environments described below ease the formatting of these parts.

4.1 Title Page

`\maketitle` The title page is generated by `\maketitle` with no arguments. This macro has been modified for providing a title page in the correct format.

You can set information to display on the title page by using the following commands before invoking `\maketitle`.

- | | |
|-------------------------------|--|
| <code>\title{}</code> | <ul style="list-style-type: none"> • The title of the document, using the <code>\title</code> macro. You may use linebreaks within the title, protected via <code>\protect\\</code> and the title may be up to four lines long. |
| <code>\author{}</code> | <ul style="list-style-type: none"> • Give your name in full and exactly as registered with the Graduate School, using the <code>\author</code> macro, e.g. <code>\author{Gary Graham Gordon-Graeme}</code>). |
| <code>\work{}</code> | <ul style="list-style-type: none"> • Whether the document is a <i>Thesis</i> or a <i>Dissertation</i> as the argument of the <code>\work</code> macro, e.g. <code>\work{Dissertation}</code>). |
| <code>\degaward{}</code> | <ul style="list-style-type: none"> • Specify the degree you're aiming for with the <code>\degaward</code> macro. Should be one of <code>\degaward{Doctor of Philosophy}</code> (without the "in <i>subject</i>" or <code>\degaward{Master of Science\\in\\Engineering}</code>). |
| <code>\advisor{}</code> | <ul style="list-style-type: none"> • Give the name of your advisor with the <code>\advisor</code> macro. |
| <code>\secondadvisor{}</code> | <ul style="list-style-type: none"> • Give the name of your second advisor, if any, with the <code>\secondadvisor</code> macro. You also need to pass in the <code>twoadvisors</code> option in the <code>\documentclass</code> declaration. |
| <code>\department{}</code> | <ul style="list-style-type: none"> • Give the name of your department with the <code>\department</code> macro, e.g. <code>\department{Gnulogical Engineering}</code>). |
| <code>\degdate{}</code> | <ul style="list-style-type: none"> • The month and year of the defense of the thesis with the <code>\degdate</code> e.g. <code>\degdate{June 2004}</code>). If you forget to declare this, the current month/year will be used. |

4.2 Copyright Page

`\makecopyright` The `\makecopyright` macro should be invoked after `\maketitle` to produce a copyright page. Prior to calling `\makecopyright`, you may specify a different name for the copyright holder (the default is the name given through the `\author` macro) and for the copyright year (the default being the current year). Do this with the `\copyrightholder{<name>}` and `\copyrightyear{<year>}` macros.

`\makepublicdomain` Alternatively, you can use `\makepublicdomain` to produce a page with the message “This document is in the public domain.” Note that the absence of the copyright page does *not* place your dissertation in the public domain, you must declare it as such explicitly.

4.3 Abstract Page(s)

`abstract` The abstract text should be placed between `\begin{abstract}` and `\end{abstract}`. If the abstract is longer than one page, the environment will place the author’s name in the top-right header.

`\abstractname{}` You may use `\abstractname{<text>}` to change the abstract caption to `text`. Default name: `Abstract`. You probably don’t need to change it.

4.4 Dedication

`dedication` The dedication is optional. If you want one, use the `dedication` environment. The format of dedication is essentially free. This environment will center the text of your dedication vertically on the page.

`\dedicationname{}` You may use `\dedicationname{<text>}` to change the title for the dedication page. Default name: `\mbox{}` i.e. an empty title. You probably don’t need to change it.

4.5 Table of Contents; Lists of Figures and Tables

`\tableofcontents` Use the macros `\tableofcontents`, `\listoffigures` and `\listoftables`, *in this order*, to produce the required table of contents and lists of figures and tables.

`\listoffigures` You may use `\contentsname`, `\listfigurename` and `\listtablename` to

`\listoftables` change the titles for these sections. By default they are `CONTENTS`, `FIGURES`, and

`\contentsname{}` `TABLES`. You probably don’t need to change them.

`\listfigurename{}`

`\listtablename{}`

4.6 List of Symbols

`symbols` The list of symbols is optional. Use the `symbols` environment to format a list of symbols/abbreviations used in your work. The environment takes an optional argument specifying the desired format, e.g. `\begin{symbols}[c1]` for first column centered and the next column aligned left. By default, the first column will be right aligned and the second column will be left aligned. You may use any of the standard `tabular` column alignment options.

`\sym{}` The command `\sym{<symbol>}{<definition>}` may make the task of entering the symbols and their meanings in the `symbols` environment easier. `\sym` takes two arguments: the first, a math “object” and the second, the plain text describing the symbol. Since the first argument is in math mode, any plain text needs to be wrapped with `\mathrm{. .}`. Likewise, any math symbol in the second argument needs to be placed in `$. . $`. Example: `\sym{\beta_{\mathrm{norm}}}{Definition for β }`

`\symbolsname{}` You may use `\symbolsname{}` to change the title of the symbols section. Default name: `SYMBOLS`.

4.7 Preface

`preface` The `preface` environment is provided for formatting the preface to your work.
`\prefacename{}` You may use `\prefacename` to change the name of this section. Default name: PREFACE.

4.8 Acknowledgments

`acknowledgments` The environment `acknowledgments` is used to format the acknowledgment *chapter*.
`\acknowledgename{}` You may use `\acknowledgename` to change the name of this section. Default name: Acknowledgments.

4.9 Text

`\mainmatter` Use the macro `\mainmatter` to mark the beginning of your text. You can then use `\part`, `\chapter`, `\section`, `\subsection`, and `\subsubsection` commands, as you would with the `book` class. Text is formatted in `\normalspacing` i.e. double-spacing. The pages are numbered in `plain` pagestyle such that the page numbers are centered in the bottom. The `chapter` titles can be multi-line, and if so are formatted doubly spaced.

`\unnumchapter{}` Use the macro `\unnumchapter` to create to create unnumbered chapters that appear in the Table of Contents.

4.10 Appendix

`\appendix` Use the command `\appendix` after the last normal chapter to signal that all following chapters are to be appendices. This use is the same as in the `book` class. To begin an appendix, use the `\chapter{<title>}` macro.

4.11 Backmatter

`\backmatter` The `\backmatter` macro separates the bibliography, index and glossary from the main matter and any appendices.

4.12 Bibliography

`\bibliography` If you are using `BIBTEX` (and why would you not want to use `BIBTEX`?), use the `\bibliography{<bibfile>}` macro to generate the bibliography. You should refer to `BIBTEX` manual for details about making a `.bib` file and format for the entries.

For citing references in the text, the package `natbib` is included with either the settings `numbers,sort&compress` (`numrefs` option) or `authoryear,sort` (`textrefs` option). The package `natbib` is a package that has numerous macros for *citing* in different ways.

Warning: The packages `cite` and `citation` are NOT compatible with the `natbib` package, and will cause errors if used.

`thebibliography` If you are not using `BIBTEX` make your own bibliography by using the `thebibliography` environment. In this case, you would have to write the reference entries

in the right format in your `.tex` source file itself. If you are using the `textrefs` option, you'll need to consult the `natbib` manual to ensure that you enter your entries in the format required by the package.

`\bibname{}` You may use `\bibname{newbibname}` to change the name of this section. Default name: Bibliography.

4.13 Chapter-wise Bibliography

By default the bibliography appears at the end of your work and contains all the references from the entire entity. If you need to have a separate bibliography for each chapter, you can do it in the following way. First, load the package `chapterbib` without any options in the preamble of your main source file and redefine the commands `\bibname` and `\bibsection` as shown below.

```
%% Main source file %%
\documentclass[...]{nddiss2e}
\usepackage{chapterbib}
\renewcommand{\bibname}{Cited works}
\renewcommand{\bibsection}{\section{\bibname}}
...
\begin{document}
\include{chptr1}
...
\include{appndx}
\end{document}
```

To process the bibliography for each chapter individually, the chapters or sections must be separated into different files and *include* them in the main file, as shown above. Each such `\included` file must contain its own `\bibliographystyle{nddiss2e}` and `\bibliography{...}` command at an appropriate position. There should not be any bibliographic commands in the main source file.

After compiling the main tex file once (with `latex` or `pdflatex`), the `.aux` files needed by `bibtex` will have been created and you can then run `bibtex` on each of the separate source files to obtain a `.bbl` for each file. The remaining steps are the same as for a normal `.tex` file.

You can find more details of this in the `natbib` manual.

5 Note For Authors

The dissertation author must make sure that the following conditions are met in order to generate a dissertation acceptable by the Graduate School:

- The List of Figures must be *before* the List of Tables, i.e. the macro command `\listoffigures` comes before `\listoftables` in the frontmatter.

- Table captions must be *above* the corresponding table, In case of the `table` environment, this can be achieved by putting `\caption` before you include the table (e.g. in a `tabular` environment).
- Figure captions should be *below* the corresponding figure. In the `figure` environment, the `\caption` goes after the `\includegraphics` macro command.
- The bibliography is the last section/chapter of the thesis—unless you are using the *chapter-wise* bibliography.

5.1 Tips and Suggestions

- It is *strongly* recommended that you compile your document with pdfL^AT_EX. Compiling to dvi or postscript first may result in “fuzzy” fonts when viewing the document on your screen. Additionally, the benefits of `hyperref` and `pdfscape` are only available if you compile using pdfL^AT_EX.
- Use the `\toprule`, `\midrule` and `\bottomrule` macro commands (from the `booktabs` package) in tables for generating the appropriate horizontal rules. Refrain from using vertical rules to separate columns in tables as much as possible.
- Use the `threeparttable` environment for tables with tablenotes.
- Use the `longtable` environment for handling very long tabular materials. Example:

```
\begin{longtable}{lc}
\caption[] {LONG TABLE CAPTION \label{tab:longtable} }
\toprule
Heading 1 & Heading 2 \\
\midrule
\endfirsthead
\caption[] { } \\ % doesn't matter what text is in the continued caption.
\midrule
Heading 1 & Heading 2 \\
\midrule
\endhead
\endfoot
\bottomrule
\endlastfoot
% Now the tabular material %
Long & Table etc. \\
\end{longtable}
```

- If a figure or table is very wide and will not fit on a page, use the `landscape` environment (from the included `lscape` package) to format them in *landscape* mode. They will automatically appear on a separate page. If you use

pdfL^AT_EX to compile your document, then the included pdfscape package will flip this page on the screen for easier reading.

If the positioning of the landscape environment is inconvenient and leads to half-empty pages, the afterpage command, made available by the package with the same name, allows the text to flow around the landscape environment better:

```
\afterpage{%
  \begin{landscape}
    \centering
    \input{my_landscape_table}
  \end{landscape}
}
```

- The sidewaysstable environment (from the included rotating package) is incompatible with the current class and should be avoided.
- Usually the width of the figure and table captions is 90% of the textwidth (i.e. 0.9\textwidth). If needed, the width can be changed on a case-by-case basis by doing one of the following:
 - Use a minipage environment of appropriate width and enclose your tabular or figure float inside it, or
 - set the \capwidth inside the table or the figure environment, and \LTcapwidth *outside* the longtable environment, e.g.,

```
\begin{table}[H]
\setlength{\capwidth}{0.8\textwidth}
\centering
\caption{TABLE CAP\label{tab:this}}
\begin{tabular}{lc}
...
\end{tabular}
\end{table}

\setlength{\LTcapwidth}{6in}
\begin{longtable}{lccc}
...
\end{\longtable}
```

- Use the tabularx environment for the actual formatting of the tables (within the table environment). It differs slightly from tabular environment and you should refer to their documentation in the TEXMF tree for more information.
- If you've used a longtable environment in your document, it might be necessary to compile the document multiple times so as to get proper alignment of columns. This is documented in the longtable manual.
- If you wish to use \footnotes in the longtable environment, please read its documentation. There are some handicaps present.

- To cite a website in your bibliography³, use the following format in your .bib file:

```
@Misc{fairley2000,
author =      "N. Fairley",
title =       "Casa{XPS} {VAMAS} processing software",
howpublished = "Website",
note =        "\url{http://www.casaxps.com}",
}
```

When processed with the `nddiss2e.bst` citation style file this gives:
 111. N. Fairley. CasaXPS VAMAS processing software. Website. `http://www.casaxps.com`.

5.2 You Found Errors?

Errors in a \LaTeX document are to be expected. If you have a problem that is that seems to be more than a typo or unbalanced brace, it is possible that there is a conflict between the packages you have included and those that `NDdiss2 ϵ` uses. If you find yourself in that situation, there is a mailing list for handling support issues with `NDdiss2 ϵ` . Look through the archive, and if there are no answers, please send an email to `ND-LATEX-USERS@listserv.nd.edu` (registration required). The more effort you spend in isolating the problem or in troubleshooting will make it more likely that others can reproduce the problem and help you solve it. Also if you have a problem that you then solve, please also email the list. Your doing so will help the next person to have that problem, and will also make the maintainers aware of it, so future versions of the class file can be better.

6 Other Packages Used

A number of packages are required by default and must be present in your \TeX search path (if you use a package manager such as `MiKTeX` or `TeXLive`, it will take care of this for you). As far as possible, these have been tested for proper formatting style with the `NDdiss2 ϵ` class file. The list includes `ifthen`, `exscale`, `ifpdf`, `ifluatex`, `ifxetex`, `xspace`, `longtable`, `indentfirst`, `tabularx`, `showkeys`, `enumerate`, `latexsym`, `epsfig`, `color`, `graphicx`, `setspace`⁴, `amsmath`, `float`, `lscape`, `rotating`, `booktabs`, and `natbib`⁵. Sameer urges you to read the documentation of these packages available in the `TEXMF` tree, if you think you might use their features or want to tweak some advanced options. Of these packages, `ifpdf`, `longtable`, `natbib`, `booktabs`, `rotating`, and `setspace` are not part of the \LaTeX required distribution, so you may need to download them. They are all available through both `MiKTeX` and

³More info at <http://www.tex.ac.uk/cgi-bin/texfaq2html?label=citeURL>

⁴v6.7[2000/12/01] or above

⁵v8.31[2009/07/16] or above

TeXLive; note that `ifpdf` is part of the `oberdiek` bundle, which is what you need to download to get that package if it is not already installed on your system.

Other packages may or may not be appropriate for use with the `NDdiss2 ϵ` class when producing copies to be submitted to the Graduate School. Please be careful when using packages that change the default fonts, or the page layout.

In general, the official guidelines of the Graduate School are followed to the maximum extent possible. This includes proper formatting of the title page and the abstract page (from the `ndthesis` package), numbering of the pages in the *frontmatter*, generation of properly formatted table of contents, list of figures etc., as well as bibliography at the end. Per the guide, the number of different fonts and font sizes used is kept to a minimum. The contents, all lists and the bibliography are single-spaced but the inter-line spacing for the rest of the document is double.

6.1 Generating PDF document

The `NDdiss2 ϵ` class also allows production of pdf documents with pdfL^AT_EX . As of Spring 2013, this is the preferred method of compilation. In this case, the `hyperref` and `pdflscape` packages are also required. The `hyperref` package ensures that the generated pdf document contains internal as well as external links for citations and bookmarks. A document produced by this method also contains embedded fonts (*press quality* pdf) and is suitable for electronic submission to the library and for microfilm archiving. Although the most appropriate options for `hyperref` are passed on, for advanced features refer to its documentation. The `pdflscape` package flips pages with landscape orientation in the pdf file for easier reading, but the location of the page numbers does not change.

Figures must be in pdf, jpeg, png, or gif format, and not in encapsulated postscript (eps). An easy way to convert *eps* files to *pdf* files is to use the utility `epstopdf` or `eps2pdf`, which should be available on your unix-like distribution already (should you have one). It is also possible to convert your eps files to pdfs using an online conversion tool. Searching for “eps to pdf” brought up several free options in Fall 2012.

7 The Implementation

Following is our attempt at documenting the source of the `NDdiss2 ϵ` class file for the `TEX` hackers.

At the start, we define the base version of L^AT_EX 2 ϵ needed and the label information for the `NDdiss2 ϵ` class.

```

1 \NeedsTeXFormat{LaTeX2e}[1999/12/01]
2 \ProvidesClass{nddiss2e}
3     [2016/10/16 v3.2016%
4     Notre Dame Dissertation document class]
5 %

\disssfileversion The \disssfileversion and \disssfiledate macros contain the version and the date of
\disssfiledate    the release.

6 \providecommand{\disssfileversion}{3.2017.2}
7 \providecommand{\disssfiledate}{2017/05/09}
8 %

```

New boolean variables for the options used in `NDdiss2 ϵ` class are set here with default values.

```

9 \newif\ifdisss@draft           \disss@drafttrue
10 \newif\ifdisss@review         \disss@reviewfalse
11 \newif\ifdisss@final          \disss@finalfalse
12 \newif\ifinfo@page           \info@pagetrue
13 \newif\ifadvisors@two        \advisors@twofalse
14 \newif\ifdisss@dedication     \disss@dedicationfalse
15 \newif\ifnum@refs             \num@refstrue
16 \newif\ifnatbib@refs         \natbib@refstrue
17 \newif\ifcentered@chaptitle   \centered@chaptitletrue
18 \newif\if@ltfirstcaption
19 %

draft Exactly one of these options must be present in order to get a proper document. These
review options set appropriate boolean variables (flags) and pass some common options to the
final parent book class.

20 \DeclareOption{draft}{
21     \setlength\overfullrule{5pt}
22     \typeout{DRAFT MODE}\typeout{}\info@pagefalse%
23     \disss@drafttrue\disss@reviewfalse\disss@finalfalse
24     \PassOptionsToClass{letterpaper,oneside,draft}{book} }
25 %
26 \DeclareOption{review}{
27     \typeout{REVIEW MODE}\typeout{}\info@pagetrue%
28     \disss@draftfalse\disss@reviewtrue\disss@finalfalse
29     \PassOptionsToClass{12pt,letterpaper,oneside,final}{book} }
30 %
31 \DeclareOption{final}{

```

```

32 \setlength\overfullrule{0pt}
33 \typeout{FINAL MODE}\typeout{}\info@pagetrue%
34 \diss@draftfalse\diss@reviewfalse\diss@finaltrue
35 \PassOptionsToClass{12pt,letterpaper,oneside,final}{book} }
36 %

```

numrefs The options **numrefs** or **textrefs** select the appropriate citation style i.e. “numbered” or “textual”, respectively. By choosing **textrefs**, one can get “author-date” style of citation in the text. The default is **numrefs**.

```

37 \DeclareOption{numrefs}{
38 \typeout{NUMBERED REFERENCES}\num@refstrue}
39 \DeclareOption{textrefs}{
40 \typeout{TEXTUAL REFERENCES}\num@refsfalse}
41 \DeclareOption{nonatbib}{
42 \typeout{NO NATBIB}\natbib@refsfalse}

```

The option **nocenter** allows non-centered chapter titles.

```

43 \DeclareOption{nocenter}{\centered@chaptitelfalse}
44 %

```

The **openbib** option is useful in creating indented bibliography. Usually you would not need to use this option since the default layout of the **bibliography** is very much acceptable.

```

45 \DeclareOption{openbib}{%
46 \PassOptionsToPackage{openbib}{natbib}
47 }
48 %

```

The **sort** option is passed to **natbib**, and causes multiple citations to be listed in the sequence they appear in the bibliography.

```

49 \DeclareOption{sort}{%
50 \PassOptionsToPackage{sort}{natbib}
51 }
52 %

```

The **compress** option is passed to **natbib**, and causes numerical citations to be compressed so that, e.g. 1,2,3 becomes 1-3. Does not also sort.

```

53 \DeclareOption{compress}{%
54 \PassOptionsToPackage{compress}{natbib}
55 }
56 %

```

The **sort&compress** option sorts numerical citations, and then compresses them.

```

57 \DeclareOption{sort&compress}{%
58 \PassOptionsToPackage{sort&compress}{natbib}
59 }
60 %

```

The other options are declared in the following lines.

twoadvisors The **twoadvisors** option sets the flag for modifying the layout of the title page.

```

61 \DeclareOption{twoadvisors}{\typeout{TWO ADVISORS}\typeout{}}
62 \advisors@twotrue}
63 %

```


10pt The options 10pt, 11pt or 12pt are passed on to the book class if appropriate, depending
 11pt on whether the \diss@draft flag is set true.

```
12pt 64 \DeclareOption{10pt}{%
65   \ifdiss@draft%
66     \PassOptionsToClass{10pt}{book}%
67   \else%
68     \OptionNotUsed%
69     \ClassWarningNoLine{nddiss2e}%
70     {Font size 10pt not allowed; using 12pt}%
71   \fi%
72 }
73 \DeclareOption{11pt}{%
74   \ifdiss@draft%
75     \PassOptionsToClass{11pt}{book}%
76   \else%
77     \OptionNotUsed%
78     \ClassWarningNoLine{nddiss2e}%
79     {Font size 11pt not allowed; using 12pt}%
80   \fi
81 }
82 \DeclareOption{12pt}{%
83   \PassOptionsToClass{12pt}{book}%
84 }
85 %
```

```
86 \DeclareOption{noinfo}{\info@pagefalse}
87 %
```

The `twoside` option is for when you want to prepare a two-sided document for your own use. The only difference from the one-sided document is in the page layout. This option is passed on to the parent book class.

```
88 \DeclareOption{twoside}{\typeout{TWO SIDED DOCUMENT}}%
89 \PassOptionsToClass{twoside}{book} }%
90 %
```

All options other than those defined above are ignored and a warning is printed on the screen during compile-time. After processing all the options, the `book` class is loaded with the specified options.

```
91 \DeclareOption*{\ClassWarning{nddiss2e}%
92   {UnknownOption ‘\CurrentOption’} }%
93 \ProcessOptions\relax
94 \LoadClass{book}
95 %
```

At this stage, the packages `ifthen`, `exscale`, `etoolbox` `ifpdf`, `ifluatex`, `ifxetex`, `longtable`, `xspace`, `indentfirst`, `tabularx`, `enumerate` and `latexsym` are loaded. It is important to load these in a specific order so as not to cause conflicts in definitions of certain macros.

```
96 \RequirePackage{ifthen,exscale,etoolbox,xpatch}
97 \RequirePackage{ifpdf,ifluatex,ifxetex}
98 \RequirePackage[
99   plainpages=false,
```

```

100 pdfpagelabels,
101 bookmarks=true,%
102 bookmarksnumbered=true,%
103 linktocpage=true,%
104 breaklinks=true,%
105 bookmarkstyle=toc,%
106 colorlinks=false,%
107 pdfpagemode=UseOutlines]{hyperref}
108 \RequirePackage{longtable}
109 \RequirePackage[flushleft]{threeparttable}
110 \RequirePackage[flushleft]{threeparttablex}
111 \RequirePackage{xspace}
112 \RequirePackage{indentfirst}
113 \RequirePackage{tabularx}
114 \RequirePackage{enumitem}
115 \RequirePackage{latexsym}
116 \RequirePackage{textcase}
117 %

If the \diss@final is set false (when using draft or review option) then the showkeys
package is also loaded.

118 % \ifdiss@final\relax\else\RequirePackage{showkeys}\fi
119 %

Depending in whether you are using pdfLATEX or plain LATEX , epsfig, color and graphicx
are loaded with respective options.

120 \ifboolexpr{bool{pdf} or bool{xetex} or bool{luatex}}{%
121   \RequirePackage{epsfig}
122   \RequirePackage{color}
123   \RequirePackage{graphicx}
124   \AtBeginDocument{
125     \pdfadjustspacing=1
126   }
127 }{%
128   \RequirePackage[dvips]{epsfig}
129   \RequirePackage[dvips]{color}
130   \RequirePackage[dvips]{graphicx}
131 }
132 %

Now the natbib package is loaded with its options, appropriate to numrefs or textrefs
class option. If numrefs is specified, then natbib is read-in with its options for “numbered”
references and sorted & compressed (eg. [3-6,8-10]). In this case, the default delimiter
is square brackets and the default separator is a comma. For the textrefs option,
the natbib package is read-in so as to sort the references in an “author-date” style of
citations. The default delimiter and separator, in this case, are round brackets and
colon, respectively.

133 \ifnatbib@refs
134   \ifnum@refs
135     \RequirePackage[numbers]{natbib}
136   \else

```

```

137 \RequirePackage[authoryear]{natbib}
138 \fi
139 \fi

```

Additionally, the packages `amsmath`, `float`, `booktabs`, `rotating`, `url` and `setspace` are loaded when (pdf)LaTeX processes `\begin{document}`. Again, the order of these packages is important. Additionally when using pdfLaTeX, the package `hyperref` (for internal/external links in the document) is also loaded. The options for this package have been tested to produce a document which can be printed on laser printers without any problems because of colored link boxes. Megan added required package `pdfscape`, which is part of the oberdiek bundle in MiKTeX and TeXLive. Using this package will flip landscape pages on the screen so that it's easier to read.

```

140 \AtBeginDocument{
141 \RequirePackage{amsmath}
142 \RequirePackage{float}
143 \RequirePackage{booktabs}
144 \RequirePackage{rotating}
145 \RequirePackage{url}
146 \RequirePackage[doublespacing]{setspace}[2000/12/01]
147 \ifboolexpr{bool{pdf} or bool{xetex} or bool{luatex}}{%
148 \ifluatex
149 \RequirePackage[luatex]{pdfscape}
150 \else
151 \ifxetex
152 \RequirePackage{xetex}{pdfscape}
153 \else
154 \ifpdf
155 \RequirePackage{pdfscape}
156 \fi
157 \fi
158 \fi
159 }{}
160 }
161 \RequirePackage{metalogo}
162 %

```

Set the `\pagestyle` for the document to `plain` here and define default spacing.

```

163 \AtBeginDocument{
164 \pagestyle{plain}
165 \normalspacing
166 \typeout{Pagestyle and spacing normal}
167 }
168 %

```

Here, define some spacing macros for page layout and doublespacing.

```

169 \newcommand{\normalspacing}{\doublespacing}
170 \newcommand{\single@baselinestretch}{0.979}
171 \newcommand{\double@baselinestretch}{1.625}
172 \newlength{\usedtextsize}
173 \setlength{\usedtextsize}{\f@size pt}
174 \newlength{\single@skip}

```

```

175 \setlength{\single@skip}{\single@baselinestretch \usedtextsize}
176 \newlength{\double@skip}
177 \setlength{\double@skip}{\double@baselinestretch \usedtextsize}
178 \setlength{\footnotesep}{\double@skip}
179 %

```

Define new lengths for some variables for a proper layout of normal pages, pages with text and figures and pages with only floats. Note that although the geometry package is usually easier, when Megan tried to switch to that she discovered that something ends up overwriting it and, although the the showframe option showed that the margins were setting correctly, the text didn't look like they were. So these length values are set to what geometry said they should be to get a 1.5 in left margin and 1 in margins on all other sides (we'll use vspace commands later to get the 2 in top margin on pages where that's needed).

```

180 \setlength{\hoffset}{0pt}
181 \setlength{\voffset}{0pt}
182 \setlength{\topmargin}{-32pt}
183 \setlength{\headsep}{20pt}
184 \setlength{\marginparwidth}{47pt}
185 \setlength{\marginparsep}{7pt}
186 \setlength{\textheight}{648pt}
187 \setlength{\textwidth}{432pt}
188 \setlength{\oddsidemargin}{36pt}
189 \setlength{\evensidemargin}{36pt}
190 \setlength{\footskip}{30pt}
191 %
192 \setlength{\floatsep}{30pt}
193 \setlength{\intextsep}{50pt}
194 %
195 \newcommand{\cleareemptydoublepage}{\newpage{\pagestyle{empty}}%
196     \cleardoublepage}}
197 %

```

\niddiss Define the macro \niddiss that is the logo used in the titlepage and the stamp in the dissertation document.

```

198 \DeclareRobustCommand{\niddiss}{%
199     \textsf{{\scshape nd}diss}\kern-0.03em%
200     2$_\textsf{{\textstyle\varepsilon}}$}
201 %

```

\work Here define new macros for use in the dissertation title page.

```

\degaward 202 \renewcommand{\title}[1]{\def\@title{#1}}
\advisor 203 \newcommand{\work}[1]{\def\@work{#1}}
\secondadvisor 204 \newcommand{\degaward}[1]{\def\@degaward{#1}}
\department 205 \newcommand{\advisor}[1]{\def\@advisor{#1}}
\degdate 206 \ifadvisors@two
207     \newcommand{\secondadvisor}[1]{\def\@secondadvisor{#1}}
208 \fi
209 \newcommand{\department}[1]{\def\@department{#1}}
210 \newcommand{\degdate}[1]{\def\@degdate{#1}}

```

```

211 \degdate{\ifcase\month\or
212     January\or February\or March\or April\or May\or June\or
213     July\or August\or September\or October\or November\or December\fi
214     \space\number\year}
215 %

```

As a default, these macros have an empty argument. Only the `\degdate` macro takes on the current month-year combination in the absence of any assignment.

```

216 % Defaults are empty except the \degdate
217 \title{}
218 \author{}
219 \work{}
220 \degaward{}
221 \advisor{}
222 \ifadvisors@two \secondadvisor{} \fi
223 \department{}
224 %

```

`\@infopage` Define `\@infopage` macro that will create a page which contains important information about the document and the version of `NDdiss2 ϵ` used etc. for the end-user and the proofreader along with a standard disclaimer and details of where to find documentation for the `NDdiss2 ϵ` class file. This information can be suppressed by specifying the “`noinfo`” option while invoking the `NDdiss2 ϵ` class.

```

225 \DeclareRobustCommand{\@infopage}{
226     \thispagestyle{empty}
227     \null\vspace*{\single@skip}
228     \begin{center}
229         This \@work\space \\\ entitled \\\ \MakeTextUppercase{\@title} \\\
230         typeset with \nddiss\ v%
231         \dissfileversion\ (\dissfiledate) %
232         on \today\space for\\
233     \@author\\
234     \end{center}
235
236     \normalfont\normalsize\singlespacing
237
238     \noindent This \LaTeXe\space classfile conforms to the
239     University of Notre Dame style guidelines as of Fall
240     2012. However it is still possible to generate a
241     non-conformant document if the instructions in the class
242     file documentation are not followed!
243
244     \begin{center}
245     \begin{minipage}{0.75\textwidth}
246     \noindent Be sure to refer to the published Graduate
247     School guidelines at \url{http://graduateschool.nd.edu}
248     as well. Those guidelines override everything mentioned
249     about formatting in the documentation for
250     this \nddiss\space class file.
251     \end{minipage}

```

```

252   \end{center}
253
254   \noindent\itshape This page can be disabled by
255   specifying the ‘‘{\upshape\ttfamily noinfo}’’ option to the class invocation.
256   \upshape
257   (i.e.,{\ttfamily{\textbackslash}documentclass[\ldots,noinfo]{\nddiss2e}}
258 )
259   \begin{center}
260     {\bfseries\large\singlespacing This page is \slshape NOT
261     \upshape part of the dissertation/thesis. It should be disabled before
262     making final, formal submission, but should be included in the version
263     submitted for format check.}
264   \end{center}
265   \normalfont\normalsize
266   \nddiss\ documentation can be found at these locations:
267   \begin{center}
268     \url{http://graduateschool.nd.edu} \\
269     \url{https://ctan.org/pkg/nddiss}
270   \end{center}
271
272   \vfill
273   \normalfont\normalsize\normalspacing\eject}
274   %

```

\maketitle Redefine the macro `\maketitle` to produce the information page as well as the actual title page of the dissertation.

```

275 \renewcommand{\maketitle}{
276   \ifinfo@page\@infopage\else\relax\fi%
277   \clearemptydoublepage
278   \normalfont\normalsize\normalspacing

```

titlepage The structuring begins with checking the proper macros for obtaining correct formatting for the title page. If any of those are not defined, an error is issued and processing stopped. Most of the code for this was taken from the earlier `ndthesis` class and hence, the documentation is also picked from there.

```

279   \begin{titlepage}%
280   \ifthenelse{\equal{\@work}{}}{\ClassError{nddiss2e}%
281     {The \protect\work\space macro is undefined.\MessageBreak
282       The title page may be incorrectly formatted.}%
283     {Specify \protect\work\space as Dissertation or Thesis}}{\relax}
284   \ifthenelse{\equal{\@degaward}{}}{\ClassError{nddiss2e}%
285     {The \protect\degaward\space macro is undefined.\MessageBreak
286       The title page may be incorrectly formatted.}%
287     {Specify \protect\degaward\space. It defines the awarded degree%
288       (Ph.D., M.S., etc.)}}{\relax}
289   \ifthenelse{\equal{\@advisor}{}}{\ClassError{nddiss2e}%
290     {The \protect\advisor\space macro is undefined.\MessageBreak
291       The title page may be incorrectly formatted.}%
292     {Specify \protect\advisor\space It is who signs your walking papers!}}{\relax}
293   \ifthenelse{\equal{\@department}{}}{\ClassError{nddiss2e}%

```

```

294 {The \protect\department\space macro is undefined.\MessageBreak
295     The title page may be incorrectly formatted.}%
296 {Specify which \protect\department\space is awarding your degree?}}{\relax}
297 \ifadvisors@two
298 \ifthenelse{\equal{\@secondadvisor}{}}{\ClassError{nddiss2e}}%
299 {The \protect\secondadvisor\space macro is undefined.\MessageBreak
300     The title page may be incorrectly formatted.}%
301 {Use \protect\secondadvisor\space for your second advisor}}{\relax}
302 \fi
303 %

```

Now set up some skip registers to hold the inter-data spacing. The initial values will create a two-inch top margin for the title page, provided the title is only one line long. `\skip1` is the primary internal spacing command; `\skip2` is the spacing between the student's name and the line for the first adviser to sign if there are two advisers and `\skip3` is the spacing between the student's name and the line for the adviser to sign if there is only one adviser; `\skip4` controls the top margin. We'll account for titles longer than one line in a bit ...

```

304 \skip1=2.1\double@skip
305 \skip2=1.7\double@skip
306 \skip3=2.7\double@skip
307 \skip4=36pt
308 %

```

If the author has two advisers, we need to do a little tweaking to the internal spacing.

```

309 \ifadvisors@two
310     \skip1=1.6\double@skip
311 \else\relax
312 \fi

```

The 2012 formatting guidelines require the title to be 2" from the top of page. If it's more than one line long, we need to adjust the internal spacing:

```

313 \setbox0=\vbox{\MakeTextUppercase{\@title}}
314 \ifdim \ht0 > 3\double@skip
315     \advance \skip1 -.75\double@skip
316 \else
317     \ifdim \ht0 > 2\double@skip
318         \advance\skip1 -.5\double@skip
319     \else
320         \ifdim \ht0 > \double@skip
321             \advance\skip1 -.25\double@skip
322         \fi
323     \fi
324 \fi

```

Our default assumes a one-line degree field such as

Doctor of Philosophy

but we check to see if it is two or three lines long. If so, we need to remove those extra lines from the internal spacing.

```

325 \setbox1=\vbox{\@degaward}

```

```

326 \ifdim \ht1 > 2\double@skip
327 \advance\skip1 -.5\double@skip
328 \else
329 \ifdim \ht1 > \double@skip
330 \advance \skip1 -.25\double@skip
331 \else
332 \relax
333 \fi
334 \fi

```

If we have two advisers, a three or four line title, and a three line degree field or two advisers, a four line title, and a two line degree field, then we need to remove some spacing between the name and the first adviser and from the top margin, and give that space to the internal spacing.

```

335 \ifadvisors@two
336 \ifdim \ht0 > 3\double@skip
337 \ifdim \ht1 > \double@skip
338 \advance \skip4 -.675\double@skip
339 \advance \skip2 -.4\double@skip
340 \advance \skip1 .25\double@skip
341 \else \relax
342 \fi
343 \else
344 \ifdim \ht0 > 2\double@skip
345 \ifdim \ht1 > 2\double@skip
346 \advance \skip2 -.4\double@skip
347 \advance \skip1 .1\double@skip
348 \else \relax
349 \fi
350 \else \relax
351 \fi
352 \fi
353 \else \relax
354 \fi

```

Finally we start putting the text in place ...centered, of course.

```

355 \null\vspace*{\skip4}
356 \begin{center}%
357 \MakeTextUppercase{\@title} \par%
358 \vskip\skip1%
359 %

```

Now skip the required vertical space, declare that this is for the University of Notre Dame, and list what degree has been earned.

```

360 A \@work \par%
361 \vskip\skip1%
362 Submitted to the Graduate School \\
363 of the University of Notre Dame \\
364 in Partial Fulfillment of the Requirements \\
365 for the Degree of \par
366 \vskip\skip1%

```



```

367      \@degaward%
368      \vskip\skip1%
369      by \\\%
370 %

```

Now format the author's name.

```

371      \@author
372 %

```

Now skip the proper space and place the signature line for the advisor with his/her name typeset below it. This is accomplished by essentially centering a box that is twice as long as the required length of the signature line and placing the line in only the right-hand side.

```

373      \ifadvisors@two
374          \vskip\skip2
375          \hspace*{2.75in}\underline{\hspace{2.75in}}\\%
376          \hspace*{2.75in}\@advisor, Co-Director\\
377      \else
378          \vskip\skip3
379          \hspace*{2.75in}\underline{\hspace{2.75in}}\\%
380          \hspace*{2.75in}\@advisor, Director\\
381      \fi%
382 %

```

If there is a second advisor, place that line here now.

```

383 \ifadvisors@two %
384     \vskip\double@skip%
385     \hspace*{2.75in}\underline{\hspace{2.75in}}\\%
386     \hspace*{2.75in}\@secondadvisor, Co-Director\\
387 \fi
388 %

```

We end with the department and date; the internal spacing is chosen so that these are at the page bottom.

```

389 \vskip\skip1%
390 Graduate Program in \@department \\\%
391 Notre Dame, Indiana \\
392 \@degdate
393 \end{center}
394 \end{titlepage}%
395 }
396 %

```

copyrightpage The environment **copyrightpage** defines the defaults for proper formatting the copyright page (if opted).

```

397 \newenvironment{copyrightpage}{%
398     \clearemptydoublepage
399     \typeout{Copyright page}
400     \pagestyle{empty}
401     \null\vfil
402     \begin{center}\normalspacing}%
403 { \end{center}\vfil\null \clearpage }

```

```

404 %

\copyrightholder Define a few macros for defining the copyright holder and the year desired. By default,
\copyrightyear they are taken as the current year and the author of the dissertation.
405 \newcommand{\@copyrightyear}{\the\year}
406 \newcommand{\@copyrightholder}{\@author}
407 \newcommand{\@copyrightlicense}{All Rights Reserved}
408 \newcommand{\copyrightyear}[1]{\renewcommand{\@copyrightyear}{#1}}
409 \newcommand{\copyrightholder}[1]{\renewcommand{\@copyrightholder}{#1}}
410 \newcommand{\copyrightlicense}[1]{\renewcommand{\@copyrightlicense}{#1}}
411 %

\makecopyright Finally, the \makecopyright macro creates the copyright page as per defined in the
copyrightpage environment.
412 \newcommand{\makecopyright}{%
413 \ifdiss@final
414 \begin{copyrightpage}
415 \normalfont\normalsize
416 \copyright\space Copyright by \\\
417 \@copyrightholder \\\
418 \@copyrightyear\\
419 \@copyrightlicense \\\[10mm]
420 \end{copyrightpage}
421 \fi
422 }%
423 %

\makepublicdomain Or, if chosen, \makepublicdomain macro creates a copyright page (using earlier
copyrightpage environment) that puts the document in public domain.
424 \newcommand{\makepublicdomain}{%
425 \ifdiss@final
426 \begin{copyrightpage}
427 This document is in the public domain.
428 \end{copyrightpage}
429 \fi
430 }%
431 %

Define some new name macros and redefine other name macros as below. These are
the names of the respective sections in your dissertation document. If there's a need to
change any name, you must use a similar command in the preamble of your document.
432 \providecommand{\abstractname}{Abstract}
433 \providecommand{\dedicationname}{\mbox{}}
434 \providecommand{\prefacename}{Preface}
435 \providecommand{\acknowledgename}{Acknowledgments}
436 \providecommand{\symbolsname}{Symbols}
437 \renewcommand{\tablename}{Table}
438 \renewcommand{\figurename}{Figure}
439 \renewcommand{\partname}{Part}
440 \renewcommand{\chaptername}{Chapter}

```

```

441 \renewcommand{\appendixname}{Appendix}
442 \renewcommand{\contentsname}{Contents}
443 \renewcommand{\listfigurename}{Figures}
444 \renewcommand{\listtablename}{Tables}
445 \renewcommand{\bibname}{Bibliography}
446 \renewcommand{\indexname}{Index}
447 %

abstract This environment is adapted from the report class since the book class does not have one.
    Additionally, we add a \pdfbookmark for the abstract in the pdf document.
448 \newenvironment{abstract}{%
449   \ifbool{pdf} or bool{xetex} or bool{luatex}}{%
450     \pdfbookmark[0]{\abstractname}{abstract}%abstract.0
451 }{}
452 \typeout{Abstract page(s)}
453 \renewcommand{\@oddfoot}{\@empty}
454 \renewcommand{\@evenfoot}{\@empty}

    If the abstract extends to a second page, place the author's name in top right corner of
    that page. Make sure it's upright, as required by the University and that this appears
    at 0.75" from the top.
455 \let\@evenhead\@oddhead
456 \renewcommand{\@oddhead}{\hfil{\upshape\@author}}
457 \titlepage
458 \null
459 \begin{center}
460 \vspace*{36pt}
461 {\normalsize\mdseries \normalspacing
462   \MakeTextUppercase{\@title} \[\[3.5ex]
463   \normalsize\abstractname \[ by \[ \@author\space}%
464   \@endparpenalty \@M
465   \end{center}\par}%
466 {\par\vfil\null\endtitlepage}
467 %

dedication The dedication environment is similar to the abstract environment. This page is numbered
    2 and the subsequent pages are numbered accordingly. A pdfbookmark is not created
    because of a reported issue that Adobe products have with pdfbookmarks containing an
    \mbox.
468 \newenvironment{dedication}{%
469   \global\dis@dicationtrue
470   \typeout{Dedication page}
471   \chapter*{\dedicationname}%
472   \thispagestyle{plain}
473   \setcounter{page}{2}
474   \null\centering}
475 {\par\null\clearpage}%
476 %

\tableofcontents The \tableofcontents macro is redefined to begin at page 2 if the dedication environ-
    ment does not exist. It is single-spaced.

```

```

477 \renewcommand\tableofcontents{%
478   \ifdiss@dedication\relax\else\setcounter{page}{2}\fi
479   \chapter*{\contentsname}%
480   \ifboolexpr{bool{pdf} or bool{xetex} or bool{luatex}}{%
481     \pdfbookmark[0]{\contentsname}{contents}%contents.0
482   }{}
483   \singlespacing
484   \@starttoc{toc}%
485   \normalspacing
486 }
487 %

```

\listoffigures These macros are modified to add the **\listfigurename** and **\listoftables** to the Table of Contents. Both of these are also single spaced. The inter-entry spacing is changed by adding a **\vskip** after each entry. This is done in the **figure** and **table** environments later.

```

488 \renewcommand\listoffigures{%
489   \chapter*{\listfigurename}%
490   \addcontentsline{toc}{chapter}{\listfigurename}%
491   \typeout{List of figures - \listfigurename}
492   \singlespacing
493   \let\oldnumberline\numberline%
494   \renewcommand{\numberline}{\figurename~\oldnumberline}%
495   \@starttoc{lof}%
496   \normalspacing
497   \let\numberline\oldnumberline
498 }
499 %
500 \renewcommand\listoftables{%
501   \chapter*{\listtablename}%
502   \addcontentsline{toc}{chapter}{\listtablename}%
503   \typeout{List of tables - \listtablename}
504   \singlespacing
505   \let\oldnumberline\numberline%
506   \renewcommand{\numberline}{\tablename~\oldnumberline}%
507   \@starttoc{lot}%
508   \normalspacing
509   \let\numberline\oldnumberline%
510 }
511 %

```

preface These environments are similar to the **dedication** environment. They are defined as **\chapter*{}** so they are not numbered and not added to Table of Contents and so, add **acknowledgement** that manually by using **\addcontentsline**.

```

512 \newenvironment{preface}{%
513   \typeout{Preface page}
514   \chapter*{\prefacename}
515   \addcontentsline{toc}{chapter}{\prefacename}%
516 }%
517 {\par\null\clearpage}%

```

```

518 %
519 \newenvironment{acknowledge}{%
520   \typeout{Acknowledgment page}
521   \chapter*{\acknowledgename}
522   \addcontentsline{toc}{chapter}{\acknowledgename}%
523 }%
524 {\par\null\clearpage}%
525 %

\unnumchapter Allows the user to create unnumbered chapters that appear in the TOC.
526 \newcommand\unnumchapter[1]{%
527   \chapter*{#1}%
528   \addcontentsline{toc}{chapter}{#1}}

symbols Define symbols environment which lays out it as a \chapter* and adds \symbolsname
\sym to the TOC. The environment is actually a horizontally centered longtable environment.
To aid entry of a symbol and its definition, \sym macro command is also defined.
529 \newcommand{\sym}[2]{\ensuremath{#1} & #2 \\\}
530 \newenvironment{symbols}[1][r1]{%
531   \typeout{Symbols page}
532   \chapter*{\symbolsname}%
533   \addcontentsline{toc}{chapter}{\symbolsname}%
534   \begin{center}\begin{longtable}{#1}}%
535 {\end{longtable}\end{center}\par\null}
536 %

Modify chapter definition in \@chapter to put the word “Chapter” (\@chapapp) in the
Table of Contents. That is, now the TOC will contain “Chapter 1: First chapter” rather
than “1. First chapter.” The rest of the format code is essentially the same as that in
the book class.
537 \def\@chapter[#1]#2{
538   \ifnum \c@secnumdepth >\m@ne
539     \if@mainmatter
540       \refstepcounter{chapter}%
541       \typeout{\MakeTextUppercase{\@chapapp\space\thechapter.}}%
542       \addcontentsline{toc}{chapter}%
543         {\@chapapp\ \thechapter: #1}%
544       \else
545         \addcontentsline{toc}{chapter}{#1}%
546       \fi
547     \else
548       \addcontentsline{toc}{chapter}{#1}%
549     \fi
550     \chaptermark{#1}%
551     \addtocontents{lof}{\protect\addvspace{10\p@}}%
552     \addtocontents{lot}{\protect\addvspace{10\p@}}%
553     \makechapterhead{\MakeTextUppercase{#2}}%
554     \@afterheading }%
555 %

```

Modify part definition in `\@part` and `\@spart` to keep the font size for part headings `\normalsize` and `\mdseries`. It is otherwise the same as in the `book` class.

```

556 \def\@part[#1]#2{%
557   \ifnum \c@secnumdepth >-2\relax
558     \refstepcounter{part}%
559     \addcontentsline{toc}{part}{\thepart\hspace{1em}#1}%
560   \else
561     \addcontentsline{toc}{part}{#1}%
562   \fi
563   \markboth{}{}%
564   {\centering
565     \interlinepenalty \@M
566     \normalfont
567     \ifnum \c@secnumdepth >-2\relax
568       \normalsize\mdseries \partname\nobreakspace\thepart
569       \par
570       \vskip 20\p@
571     \fi
572     \normalsize\mdseries \MakeTextUppercase{#2}\par}%
573   \@endpart}
574 \def\@spart#1{%
575   {\centering
576     \interlinepenalty \@M
577     \normalfont
578     \normalsize\mdseries #1\par}%
579   \@endpart}
580 %

```

Now format section headings to conform to the official guidelines.

`\@makechapterhead` First, modify the chapter heading label to be `\normalsize`'d and centered. Instead of the bold-faced heading label, also make it `\mdseries`. If we are in the `\mainmatter`, we add "CHAPTER" and chapter number before actually putting the chapter name otherwise only the "chapter name" is put. Note that chapter/section headings must all be double-spaced.

```

581 \renewcommand{\@makechapterhead}[1]{%
582   \vspace*{30pt}%
583   {\parindent \z@ \raggedright
584     \ifnum \c@secnumdepth >\m@ne
585       \normalfont\normalsize%
586       \if@mainmatter
587         \ifcentered@chaptitle\center\else\relax\fi%
588         \MakeTextUppercase{\@chapapp{} \thechapter}\par\nobreak
589       \fi
590     \fi
591     \interlinepenalty \@M
592     \ifcentered@chaptitle\center\else\relax\fi%
593     \mdseries{#1}\par\nobreak
594     \vskip 30\p@
595   }}
596 %

```

`\@makeschapterhead` Make the TOC, LOF, LOT and other `\chapter*` headings in normal size, and `\mdseries` by modifying the macro `\@makeschapterhead`. Although these heading labels usually fit in a single-line, we copy the formatting for the chapter heading label (single-spacing) and make the spacing double again for the text.

```

597 \renewcommand{\@makeschapterhead}[1]{%
598   \vspace*{30pt}%
599   {\parindent \z@ \raggedright
600     \normalfont\normalsize%
601     \interlinepenalty\@M
602     \ifcentered@chaptitle\center\else\relax\fi
603     \mdseries{\MakeTextUppercase{#1}}\par\nobreak
604     \vskip 30\p@
605   }}
606 %

```

Now, set the section labels to `\mdseries` rather than bold-faced. We also make sure that these are set in normal spacing, font and size. This is done for each of `\section`, `\subsection`, `\subsubsection`, `\subsubsubsection`, `\paragraph` and `\subparagraph`.

```

607 \renewcommand\section{\suppressfloats[t]%
608   \@startsection {section}{1}{\z@}%
609   {-4.2ex \@plus -1ex \@minus -.2ex}%
610   {1.8ex \@plus .2ex}%
611   {\normalfont\normalsize\mdseries} }
612 \renewcommand\subsection{\suppressfloats[t]%
613   \@startsection{subsection}{2}{\z@}%
614   {-3.9ex \@plus -1ex \@minus -.2ex}%
615   {1.2ex \@plus .2ex}%
616   {\normalfont\normalsize\mdseries} }
617 \renewcommand\subsubsection{\suppressfloats[t]%
618   \@startsection{subsubsection}{3}{\z@}%
619   {-3.9ex \@plus -1ex \@minus -.2ex}%
620   {1.2ex \@plus .2ex}%
621   {\normalfont\normalsize\mdseries} }
622 \renewcommand\paragraph{%
623   \@startsection{paragraph}{4}{\z@}%
624   {3.9ex \@plus 1ex \@minus .2ex}%
625   {-1em}%
626   {\normalfont\normalsize\mdseries} }
627 \renewcommand\subparagraph{%
628   \@startsection{subparagraph}{5}{\parindent}%
629   {3.9ex \@plus 1ex \@minus .2ex}%
630   {-1em}%
631   {\normalfont\normalsize\mdseries} }
632 %

```

`\l@part` Modify the macro `\l@part` that formats part titles in the contents-like files (`.toc`, `.lof` and `.lot`) by adding a `\@dottedtocline` macro. The indent width is set to 1.5em - to line up a continued line with the section number below it. We also leave less space between each part and the last section entry than the default and don't change the font.

```

633 \renewcommand*\l@part[2]{%
634   \ifnum \c@tocdepth >-2\relax
635     \addpenalty{-\@highpenalty}%
636     \setlength\@tempdima{1.5em}%
637     \begingroup
638       {\leavevmode
639         \@dottedtocline{1}{0pt}{\@tempdima}{#1}{#2}
640       }\par
641       \nobreak
642       \global\@nobreaktrue
643       \everypar{\global\@nobreakfalse\everypar{}}%
644     \endgroup
645 \fi}
646 %

```

\l@chapter Modify the macro `\l@chapter` that formats chapter titles in the contents-like files (`.toc`, `.lof` and `.lot`) by adding a `\@dottedtocline` macro. The indent width is set to 1.5em - to line up a continued line with the section number below it. We also leave less space between each chapter and the last section entry than the default.

```

647 \renewcommand*\l@chapter[2]{%
648   \addpenalty{-\@highpenalty}%
649   \setlength\@tempdima{1.5em}%
650   \begingroup \leavevmode
651   \@dottedtocline{1}{0pt}{\@tempdima}{#1}{#2}
652   \par
653   \penalty\@highpenalty
654   \endgroup
655 }
656 %

```

\thesubsubsection We increase the number of section-depth by 1 and force subsubsection entry in the TOC by increasing the `\tocdepth`. In addition, the label number of `\subsubsection` is defined to be similar to that for `\subsection` i.e. all arabic numerals.

```

657 \addtocounter{secnumdepth}{1}
658 \addtocounter{tocdepth}{1}
659 \renewcommand{\thesubsubsection}{%
660   \thesubsection.\arabic{subsubsection}}
661 %

```

quote Redefine the `quote` environment to be single-spaced instead of being same as the rest of the text.

```

662 \renewenvironment{quote}
663   {\list{}{\rightmargin\leftmargin}%
664     \singlespacing
665     \item\relax}
666   {\endlist}
667 %

```

Have singlespaced items in lists.

```

668 \AtBeginEnvironment{itemize}{\par\singlespacing}

```



```

669 \AtBeginEnvironment{enumerate}{\par\singlespacing}
670 \AtBeginEnvironment{description}{\par\singlespacing}
671 \AtBeginEnvironment{tablenotes}{\footnotesize}
672 \xpatchcmd{\TPTdoTablenotes}{\itemsep\z@}{\itemsep10pt}{-}{-}
673 \xpatchcmd{\TPTdoTablenotes}{\itemindent\z@}{\itemindent18pt}{-}{-}

Set some lengths that are used in the table and the figure environments. Note that we
set the caption width (\capwidth) to be 90% of the \textwidth.

674 \setlength\abovecaptionskip{20\p@}
675 \newlength\capwidth
676 \setlength{\capwidth}{0.90\textwidth}
677 \newlength\abovetableskip
678 \newlength\belowtablesip
679 \newlength\abovefigureskip
680 \newlength\belowfigureskip
681 \setlength\abovetableskip\belowcaptionskip
682 \setlength\belowtablesip\abovecaptionskip
683 \setlength\abovefigureskip\abovecaptionskip
684 \setlength\belowfigureskip\belowcaptionskip
685 %

```

figure For the figure environment, first some skip lengths are set, then use `\@makefigurecaption` to format the captions instead of the default `\@makecaption`, since the layout is different for figure and the table environment. Further add a `\vskip` to each entry in .lof file so that the inter-caption spacing seems double-spaced.

```

686 \renewenvironment{figure}{%
687   \setlength{\abovecaptionskip}{\abovefigureskip}
688   \setlength{\belowcaptionskip}{\belowfigureskip}
689   \let\@makecaption\@makefigurecaption
690   \@float{figure}}%
691 {%
692   \addtocontents{lof}{\vskip 0.4em} }%
693   \end@float%
694 }
695 %

```

\@makefigurecaption The `\@makefigurecaption` is defined to format the caption in a parbox with width equal to `\capwidth` and is formatted in single-spacing. The interline-spacing is then changed to double after the caption.

```

696 \long\def\@makefigurecaption#1#2{%
697   \vskip\abovecaptionskip
698   \begin{center}
699     \parbox{\capwidth}{
700       \centering\singlespacing
701       {#1}. {#2}%\par
702       \vskip\belowcaptionskip\normalspacing }%
703   \end{center}
704 }%
705 %

```

table After setting the above and below skip lengths, the **table** environment is set to be single spaced. However, to obtain double-spacing between the entries, redefine the **\arraystretch** to be equivalent to the **\double@baselinestretch**. This way, while there are double-spaced entries, the entry itself is single-spaced. Similar to that in **\@makefigurecaption**, a **\vskip** is added to each entry in the .lot file.

```

706 \renewenvironment{table}[1][tbp]{%
707   \setlength{\abovecaptionskip}{\abovetableskip}
708   \setlength{\belowcaptionskip}{\belowtableskip}
709   \renewcommand{\arraystretch}{\double@baselinestretch}
710   \let\scaption\caption%
711   \renewcommand*{\caption}[2][ ]{%
712     \ifthenelse{\equal{##1}{}}{%
713       \def\shortcaption{##2}%
714     }{%
715       \def\shortcaption{##1}%
716     }%
717     \scaption[\shortcaption]{\MakeTextUppercase{##2}}%
718   }%
719   \let\@makecaption\@maketablecaption
720   \@float{table}[#1]%
721   \singlespacing%
722   }%
723   {%
724     \addtocontents{lot}{ { \vskip 0.4em } }%
725   \end@float%
726 }
727 %

```

\@maketablecaption The **\@maketablecaption** is defined similarly to **\@makefigurecaption** to have the table label and caption in separate lines and with normal-spacing (double-spaced).

```

728 \long\def\@maketablecaption#1#2{
729   \vskip\abovecaptionskip
730   \begin{center}
731     \makebox[\linewidth]{
732       \parbox{\capwidth}{
733         \centering\normalspacing
734         \MakeTextUppercase{#1}\[\single@skip]
735         {#2}%\par
736       \vskip\belowcaptionskip }%
737     }%
738   \end{center}
739 }
740 %

```

\longtable Similar to the **table** environment, the **longtable** environment is made singly-spaced but the **\arraystretch** is made equal to double the **baselinestretch**.

```

741 \renewcommand\longtable{%
742   \singlespacing
743   \renewcommand{\arraystretch}{\double@baselinestretch}
744   \begingroup

```

```

745 \letfirstcaptiontrue
746 \ifnextchar[\LT@array{\LT@array[x]}}
747 %

```

`\endlongtable` This bit is taken from `longtable.sty`. In order to obtain double-spacing in the list of tables, a `\vskip` of 0.4em is added to `.lot` file.

```

748 \renewcommand\endlongtable{%
749 \crrr
750 \noalign{%
751 \let\LT@entry\LT@entry@chop
752 \xdef\LT@save@row{\LT@save@row}}}%
753 \LT@echunk
754 \LT@start
755 \unvbox\z@
756 \LT@get@widths
757 \if@filesw
758 {\let\LT@entry\LT@entry@write\immediate\write\@auxout{%
759 \gdef\expandafter\noexpand
760 \csname LT@\romannumeral\c@LT@tables\endcsname
761 {\LT@save@row}}}%
762 \fi
763 \ifx\LT@save@row\LT@@@save@row
764 \else
765 \LT@warn{Column \@width s have changed\MessageBreak
766 in table \thetable}%
767 \LT@final@warn
768 \fi
769 \endgraf\penalty -\LT@end@pen
770 \addtocontents{lot}{\{\vskip 0.4em\} }%
771 \endgroup
772 \global\@mparbottom\z@
773 \pagegoal\vsize
774 \endgraf\penalty\z@\addvspace\LTpost
775 \ifvoid\footins\else\insert\footins{}\fi
776 }
777 %

```

`\LT@makecaption` For the `longtable` environment, the `\LTcapwidth` is set equal to `\capwidth`. In order to obtain consistent table captions, the command `\LT@makecaption` is modified in a similar manner as `\maketablecaption`.

```

778 \setlength{\LTcapwidth}{\capwidth}
779 \renewcommand\LT@makecaption[3]{%
780 \LT@mcol\LT@cols c{\hbox to\z@{\hss\parbox[t]\LTcapwidth{%
781 \vskip\abovetableskip%
782 \centering\normalspacing
783 \if@ltfirstcaption
784 #1{\MakeTextUppercase{#2} }\\[\single@skip]
785 \MakeTextUppercase{#3}\par
786 \else%
787 #1{\MakeTextUppercase{#2 (continued)} }\par

```

```

788     \fi
789     \global\letfirstcaptionfalse
790     \endgraf\vskip\belowtableskip}%
791     \hss}}}}
792 %

\timenow This macro is used in making the \drafthead and \reviewhead below. It outputs
time in HH:MM format.
793 \newcommand\timenow{%
794     \@tempcnta=\time \divide\@tempcnta by 60 \number\@tempcnta:\multiply
795     \@tempcnta by 60 \@tempcntb=\time \advance\@tempcntb by -\@tempcnta
796     \ifnum\@tempcntb <10 0\number\@tempcntb\else\number\@tempcntb\fi}
797 %

\diss@header This header is used in the dissertation document when the draft or review option is
used. These headers serve as a note for the date and time of the document compilation.
798 \newcommand{\diss@header}{%
799     \ifdiss@review Review \else Draft \fi document [\today\ at \timenow/]
800     }%
801 %

The header prepared above is put in the document by modifying the plain and empty
pagetypes except when the final option is chosen.
802 \ifdiss@final
803     \renewcommand{\ps@plain}{
804         \renewcommand{\@oddhead}{\@empty}
805         \renewcommand{\@oddfoot}{\hfil\thepage\hfil}
806         \let\@evenhead\@oddhead
807         \let\@evenfoot\@oddfoot
808     }%
809 \else
810     \renewcommand{\ps@plain}{
811         \renewcommand{\@oddhead}{\framebox[\textwidth]{
812             \centering\footnotesize\tt\diss@header}}%
813         \renewcommand{\@oddfoot}{\hfil\textrm{\thepage}\hfil}
814         \let\@evenhead\@oddhead
815         \let\@evenfoot\@oddfoot
816     }%
817     \renewcommand{\ps@empty}{
818         \renewcommand{\@oddhead}{\framebox[\textwidth]{
819             \centering\footnotesize\tt\diss@header}}%
820         \renewcommand{\@oddfoot}{\@empty}
821         \let\@evenhead\@oddhead
822         \let\@evenfoot\@oddfoot
823     }%
824 \fi
825 %

\bibsection By redefining \bibsection macro, add the \bibname to the table of contents and as a
chapter heading for the bibliography.

```

```

826 \ifnatbib@refs
827   \renewcommand{\bibsection}{
828     \chapter*{\bibname}%
829     \addcontentsline{toc}{chapter}{\bibname}%
830   }%
831 \fi
832 %

```

\bibfont Changed the **\bibfont** macro to obtain single-spacing within each bibliographic entry. Between different entries, it is still **\normalspacing**. In addition, when the **numrefs** option is selected, the **\@biblabel** is redefined to number the bibliographic entries as 1. xxxx instead of the default [1] xxxx.

```

833 \ifnatbib@refs
834   \renewcommand{\bibfont}{\singlespacing}
835   \ifnum@refs
836     \renewcommand{\@biblabel}[1]{\hfill#1.\hfill}
837   \fi
838 \fi
839 %

```

Lastly, after the bibliography in the final document, add a framed box which contains a blurb about the typesetting program and **NDdiss2_ε** version used for preparing the dissertation document.

```

840 \ifdiss@final
841 \AtEndDocument{
842   \vfill
843   \centering\singlespacing
844   \framebox[0.85\textwidth]{
845     \begin{minipage}{0.80\textwidth}\footnotesize%
846       \centering \itshape This document was prepared \& typeset with
847       \upshape
848       \ifluatex
849         \LuaLaTeX
850       \else\ifxetex
851         \XeLaTeX
852       \else\ifpdf
853         pdf\LaTeX
854       \else
855         \LaTeXe
856       \fi\fi\fi
857       \itshape , and
858       formatted with \upshape\nddiss\xspace\itshape classfile
859       (v\dissfileversion [\dissfiledate])
860     \end{minipage} }
861   \clearpage}
862 \else\relax\fi
863 %
864 % \endinput
865 % End of file 'nddiss2e.cls'.

```

Change History

v0.98		addition of support for parts. -	
General: Initial <i>beta</i> version	1	MP	1
v1.0		v3.2013 β	
Release: First release	1	Release: Initial release of updates	
v1.1		in order to comply with the	
General: Minor changes and		Graduate School's current	
clean-up	1	formatting regulations and to	
v2.0		take advantage of some LaTeX	
General: Some bugfixes, cleaned		package updates. Should be	
some of documentation	1	functional, and has been	
v2.1		approved by the	
General: More bugfixes, changes in		Dissertation/Thesis editors,	
documentation	1	but has not undergone	
v3.0		wide-scale testing. - Megan	
Release: Major revamp and		Patnott	1
clean-up of the code, added		v3.2016	
numrefs and textrefs to allow		Release: Fix natbib/showkeys	
different kinds of citation		ordering bug	1
styles, added some more		v3.2017.1	
macros and modified others,		Release: Display (CONTINUED)	
changed the titlepage a bit,		on multipage long table	
completed source		captions	1
documentation	1	v3.2017.2	
v3.2013		Release: Add LuaLaTeX support.	
Release: Some bug fixes, minor		Allow non-capitalized titles. . .	1
changes in documentation, and			