1outof2



3ballot



3parties-DHKE



3parties-JOUX



CBC-MAC



CBC-small



CBC



CCA-PKCS



CCA



CMAC



CTR



DESkey



DHkey



Davies-Meyer



ECB



ElGamal



HMAC



IBE



KDC



MDtransform



MS-PPTP



Miyaguchi-Preneel



NMAC



OAEP-plus



OAEP



OFB



OWF



SAEP-plus



SIV-CTR



TDES



VCBC-MAC



alice



attack-spn



authentication



baby-giant



bilinear-map



birthdayattack



blindsignature



cPRF



certificates



chain-sig



cipher-stealing



coinflipping



collision



combination



compute-sec



constructD



des



desx



differential



digitalsignature



dining



doubleE



ePRG



ecdhke



elgamal-con



ellipticcurve



encryptionwithpf



encryptionwithpg



feistel-prp



feistel



hash



hcp



hs-reduce-1



hs-reduce-2



hybrid-enc-proof



hybrid-encrypt



hybrideg



hybridproof



identification-schnorr



identification



integrity



interlock



keyed-func



linear



mac



macforge-exp



macwithprf



man-in-middle



meet-in-middle



multiple-enc-exp



owff



owfover



padding-oracle-lastbyte



padding-oracle-null



padding-oracle



pgfD



pgfMAC



pnp



prg-distinguisher



prg-sparse



pri-cpa-exp



pri-eav-exp



private-key



public-key



qr-qnr



rabinOT



reduction-prg



reduction



schnorr-signature

Sign: $k \leftarrow \mathbb{Z}_q$,
compute $I := g^k$,
$r := H(I, m)$,
$s := [rx + k \mod q]$
and output (r, s)

Vrfy: Compute I and
output 1 $\iff H(I, m) \stackrel{?}{=} r$.



schnorr



spn



ssl



suf-mac



synchronizedmode



tdp-cca1



tdp-cca2



tdp-cpa



tdp-pk



threepass



tls13hs



toy-OT

transmission



trapdoor



tree-sig



worldofpk



zkp-commitment



zkp-hanmilton



zkp-rsa



zkp