

The Art of Morph - (DRAFT)

Craft your own Morph

The screen is a window through which one sees a virtual world. The challenge is to make that world look real, act real, sound real, feel real.

—*Ivan Sutherland*

Hilaire Fernandes

“The Art of Morph - (DRAFT)” booklet is for Cuis-Smalltalk (7.0 or later), a free and modern implementation of the Smalltalk language and environment.

Copyright © 2025 Hilaire Fernandes

Thanks to Mark Volkmann to share his examples.

Thanks to ... for the reviews of the booklet, suggestions and borrowed texts. Your help is very valuable.

Compilation : 29 July 2025

Documentation source: <https://github.com/DrCuis/Template-booklet>

The contents of this booklet are protected under Creative Commons Attribution-ShareAlike 4.0 International.

You are free to:

Share – copy and redistribute the material in any medium or format

Adapt – remix, transform, and build upon the material for any purpose, even commercially.

Under the following terms:

Attribution. You must give appropriate credit, provide a link to the license, and indicate if changes were made. You may do so in any reasonable manner, but not in any way that suggests the licensor endorses you or your use.

Share Alike. If you remix, transform, or build upon the material, you must distribute your contributions under the same license as the original.

Complete license: <https://creativecommons.org/licenses/by-sa/4.0/legalcode>

Table of Contents

1	Introduction	1
1.1	A first glimpse	1
1.2	Mouse event	3
1.2.1	Mouse click	3
1.2.2	Mouse hovering	3
1.2.3	Grow on user request	4
1.3	Keyboard event	5
2	Design by reuse	8
2.1	From where to start?	8
2.2	Layout	9
2.2.1	Arrange visually	9
2.2.2	Be notified	10
2.3	Scroll pane	11
2.4	File Selector	12
2.4.1	Poor man implementation	12
2.4.2	First morph design by reuse	13
2.4.3	Beyond string request morph	15
3	Design from scratch	18
3.1	A bit of introspection	18
Appendix A	Documents Copyright	23
Appendix B	The Exercises	24
Appendix C	Solutions to the Exercises	25
	Design from scratch	25
Appendix D	The Examples	26
Appendix E	The Figures	27
Appendix F	Art of Morph package	28
Appendix G	Conceptual index	33

1 Introduction

The computer is simply an instrument whose music is ideas.

—*Alan Kay*

Cuis-Smalltalk offers the possibility to easily design your own Morphs – widgets you can interact with and later integrate in your GUI application. There are three ways to design a custom Morph: an aggregate of existing Morphs, a design from scratch or a combination of the two former approaches.

Building a new Morph with an aggregate of existing Morphs is mainly about laying out together Morphs and let the aggregated Morphs manage the low level drawings and input event operations. When there is a need for a custom Morph, this is the path to investigate first; if there is no way to do so, then consider designing from scratch a Morph.

Designing from scratch a Morph requires to deal with its appearance and the handling of the input events; for the former, Cuis offers a vector graphics anti-aliased canvas, the latter is done with a mechanism to filter and to handle mouse and keyboard events occurring in the scope of the custom Morph.

Let's start right away with a design from scratch.

1.1 A first glimpse

It's easy to create custom morphs. Just create a subclass of an existing morph class. Then implement the `drawOn:` method or add and layout sub morphs.

Let's make an example that draws an ellipse. Making it a subclass of `BoxMorph` gives it an extent instance variable which specifies its width and height.

```
BoxMorph subclass: #EllipseDemo
  instanceVariableNames: "
  classVariableNames: "
  poolDictionaries: "
  category: 'ArtOfMorph'
```

We adjust its default extent¹:

```
defaultExtent
  ↑ '200@200'
```

In our `EllipseDemo`, the `extent` represents the lengths of the `ox` and `oy` axis of the ellipse. We use it to draw it accordingly:

¹ Observe the backtricks to improve performance at execution.

```

drawOn: aCanvas
  | radius |
  radius := extent / 2.0.
  aCanvas fillColor: Color purple do: [
    aCanvas ellipseCenter: radius radius: radius]

```

Finally, we instruct Cuis-Smalltalk we want to use the Vector Graphic engine:

```

requiresVectorCanvas
  ↑ true

```

To display an instance of `EllipseDemo`, open a Workspace and execute `EllipseDemo new openInWorld`.




Figure 1.1: Ellipse with axes, resized to an extent approximatively equals to 300@100



The drawing always operates in the own morph coordinates system and we have to ensure our drawing operations remain in the bond defined by the morph origin, in the top-left corner, and its bottom-right corner delimited by its `extent` attribute, a point.

Before proceeding forward with events, we may want to add semantic to our protocol with `#center` and `#semiAxes` messages to use within the `drawOn:` method:

```

center
  ↑ extent / 2.0

semiAxes
  " the semi minor and major axis of the ellipse"
  ↑ extent / 2.0

```

```

drawOn: aCanvas
  aCanvas fillColor: Color purple do: [
    aCanvas ellipseCenter: self center radius: self semiAxes ]

```

1.2 Mouse event

Let's explore how custom morphs can react to mouse clicks, mouse hovers, and keystrokes.

1.2.1 Mouse click

Here is a modification of our previous example whose color toggles between red and green each time it is clicked.

As we need a color, we first modify our `EllipseDemo` to be a subclass of `ColoredBoxMorph`:

```
ColoredBoxMorph subclass: #EllipseDemo
  instanceVariableNames: "
  classVariableNames: "
  poolDictionaries: "
  category: 'ArtOfMorph'
```

Then we initialize it with the red color:

```
initialize
  super initialize.
  color := Color red
```

First, we request we want to handle the mouse click down event:

```
handlesMouseDown: aMouseEvent
  "This enables the morph to handle mouse events such as button presses."
  ↑ true
```

Then at each mouse click, we toggle the color attribute between red and green:

```
mouseButton1Down: aMouseEvent localPosition: aPosition
  color := (color = 'Color red') ifTrue: ['Color green'] ifFalse: ['Color red'].
  self redrawNeeded
```

Of course we adjust the drawing method to use the color attribute:

```
drawOn: aCanvas
  aCanvas fillColor: color do: [
    aCanvas ellipseCenter: self center radius: self semiAxes ]
```

To render this, open a Workspace and evaluate `EllipseDemo new openInWorld`. Click the circle several times to toggle its color.

1.2.2 Mouse hovering

Now let's modify our `EllipseDemo` to toggle its color based on whether the mouse cursor is hovering over it.

This time, we want to handle event when the mouse pointer is hovering our `EllipseMorph`:

handlesMouseOver: aMouseEvent

```
"This enables the morph to handle mouse enter and leave events."
```

```
↑ true
```

Of course we remove the `handlesMouseDown:` method, or alternatively we edit it so it return `false`, to let Cuis-Smalltalk handles this event:

handlesMouseDown: aMouseEvent

```
"This enables the morph to handle mouse events such as button presses."
```

```
↑ false
```

There are two event handlers associated when handling mouse over: when entering and when leaving a morph. We edit the methods accordingly to toggle the morph color:

mouseEnter: aMouseEvent

```
color := 'Color green'.
```

```
self redrawNeeded
```

mouseLeave: aMouseEvent

```
color := 'Color red'.
```

```
self redrawNeeded
```

Create an instance as seen previously, the hover onto and off of the ellipse to toggle its color.

Observe how the frontier between inside and outside of the ellipse is a rectangle, this is because our `EllipseDemo` is a kind of `BoxMorph` optimised for rectangular shape. To have exact pixel detection, including shape drawn with holes, our `EllipseDemo` would require to be a direct subclass of `PlacedMorph`. In the process, we will lose the `extent` and `color` attributes, and we will have to define ones of our own.

1.2.3 Grow on user request

Now let's combine the mouse hover and mouse click events: at button 1 click, the ellipse shrinks slightly; at button 2 click, it grows greatly.

To do so we introduce a `shrink` attribute initialized to 0:

initialize

```
super initialize.
```

```
color := Color red.
```

```
shrink := 0
```

Then it changes depending on user actions, its value increase slightly at button 1 click:

```
mouseButton1Down: aMouseEvent localPosition: aPosition
  shrink := (shrink + 0.5) min: (extent x min: extent y) // 2.
  self redrawNeeded
```

and decrease quickly at button 2 click,

```
mouseButton2Down: aMouseEvent localPosition: aPosition
  shrink := (shrink - 5) max: 0.
  self redrawNeeded
```

Of course we have to bound the `shrink` attribute between 0 and the smaller extent axis of the whole morph.

Then we adjust our `semiAxes` method used to draw the ellipse:

```
semiAxes
  ↑ (extent / 2.0) - shrink
```

1.3 Keyboard event

So far, we explored how a morph interacts with the mouse pointer, it may also respond to keyboard events. In this section, we modify our `EllipseDemo` to adjust its color at keyboard interaction.

First, identically to mouse event, we indicate our morph want to handle keyboard event:

```
handlesKeyboard
  "This enables the morph to handle key events if it has focus."
  ↑ self visible
```

We handle the keyboard event only when our morph is visible.

Keyboard event is associated with the concept of keyboard focus. In the world of morph, one or zero morph own the keyboard focus at a time, it means this morph will receive the keyboard event.

Moreover, in Cuis-Smalltalk there is this preference `#focusFollowsMouse`. When true, the keyboard focus is automatically changed to the morph the mouse pointer is hovering; when false, the keyboard focus is only changed to a morph at user mouse click on this specific morph.

To know what is the preference in your Cuis-Smalltalk system, execute the code:

```
Preferences at: #focusFollowsMouse
⇒ true
```

I personally prefer to explicitly inform the Cuis-Smalltalk system where the keyboard focus should go. Indeed, my mouse tends to slip on my desk, resulting on the keyboard focus to change annoyingly:

Preferences at: `#focusFollowsMouse` put: `false`

Our `EllipseDemo` honors this preference when the mouse pointer enter the morph:

```
mouseEnter: aMouseEvent
  color := 'Color green'.
  "If the user opted for focus to automatically
  move focus to the morph under the cursor then tell
  the cursor (event hand) to give focus to this morph."
  (Preferences at: #focusFollowsMouse) ifTrue: [aMouseEvent hand newKeyboardFocus: self].
  self redrawNeeded
```

The *hand* is the mouse pointer object in the Cuis-Smalltalk terminology. It manages the keyboard focus and it is informed when the focus should be affected to another morph.

When the mouse pointer leaves our morph we let its parent morph manages the focus:

```
mouseLeave: aMouseEvent
  super mouseLeave: aMouseEvent.
  color := 'Color red'.
  self redrawNeeded
```

accordingly to the `#focusFollowsMouse` system preference:

```
Morph>>mouseLeave: evt
  (Preferences at: #focusFollowsMouse)
    ifTrue: [evt hand releaseKeyboardFocus: self].
  ../..
```

To handle the keyboard strokes, we override the dedicated method `keyStroke:`. We first ensure the key stroke was not handled by the parent² then we do the handling specific to our `EllipseDemo` morph:

```
keyStroke: aKeyEvent
  | character |
  super keyStroke: aKeyEvent.
  aKeyEvent wasHandled ifTrue: [↑ self].
  character := Character codePoint: aKeyEvent keyValue.
  color := character
    caseOf: {
      [ $r ] -> [ 'Color red' ].
      [ $g ] -> [ 'Color green' ].
      [ $b ] -> [ 'Color blue' ] }
    otherwise: [color].
  self redrawNeeded
```

² For example, to manage keyboard shortcut or tabulation.

The event object is interrogated with dedicated messages to detect modifier keys (i.e. `#controlKeyPressed`). Browse the `UserInputEvent` class to discover them all.

To have more flexibility on the color used in our ellipse demo, let's implement the following features:

- Pressing *h*, *s* or *v* increase, respectively, the hue, the saturation and the brightness of the ellipse color.
- Pressing *Ctrl-h*, *Ctrl-s* or *Ctrl-v* decrease these same values.

keyStroke: aKeyEvent

```
| character increment h s v |
../..
h := color hue.
s := color saturation.
v := color brightness .
increment := aKeyEvent controlKeyPressed ifTrue: [-0.1] ifFalse: [0.1].
character
  caseOf: {
    [ $h ] -> [ h := h + (increment * 13) ].
    [ $s ] -> [ s := s + increment ].
    [ $v ] -> [ v := v + increment ] }
  otherwise: [].
color setHue: h saturation: s brightness: v.
self redrawNeeded
```

Our gentle introduction ends here, we have exposed several facets of the Morph system to build from scratch your own morph: drawing of the morph and handling of the mouse and keyboard input. In the following chapters we explore more in detail the design from scratch of your own morphs and how to combine them with existing morph.

2 Design by reuse

In this chapter you will learn how to design new morph – in the idea of a new widget – by assembling existing ones. We first illustrate the topic with existing morphs from the Cuis-Smalltalk system and the Cuis-Smalltalk-UI repository. Then we dive-in the design of a new morph – a file selector – gradually improving it from a quick design in a *Workspace* to a class of its own. Finally, its design is bullet proof tested by reusing it in an end-user GUI.

2.1 From where to start?

Design by reuse indeed, but from where to start? Which classes should we make reuse from? As often, the Cuis-Smalltalk system may be our best guide, let's interrogate it to learn which morph has more subclasses.

We collect, for each existing morph in the Cuis-Smalltalk system, the quantity of subclasses, then we sort the result.

```
| hallOfFame |
hallOfFame ← Morph allSubclasses collect: [:each |
    Array with: each with: each subclasses size].
hallOfFame ← hallOfFame sort: [:array1 :array2 | array1 second > array2 second]
```

```
▼ root: an OrderedCollection({PlacedMorph . 16})
▶ 1: {PlacedMorph . 16}
▶ 2: {BorderedBoxMorph . 15}
▶ 3: {LinearLayoutMorph . 11}
▶ 4: {ColoredBoxMorph . 10}
▶ 5: {SystemWindow . 9}
▶ 6: {ValueEntryPanel . 7}
▶ 7: {MethodSetWindow . 6}
▶ 8: {CodeWindow . 6}
▶ 9: {PluggableMorph . 5}
▶ 10: {LabelMorph . 5}
▶ 11: {BoxMorph . 5}
▶ 12: {DialogPanel . 4}
▶ 13: {PluggableListMorph . 4}
▶ 14: {PluggableScrollPane . 4}
▶ 15: {PluggableButtonMorph . 3}
▶ 16: {InnerPluggableMorph . 3}
▶ 17: {InlineMethodWizardStepWindow . 2}
▶ 18: {ChangeSelectorWizardStepWindow . 2}
▶ 19: {BrowserWindow . 2}
▶ 20: {CheckGroup . 2}
▶ 21: {PreviewMorph . 2}
▶ 22: {StringRequestMorph . 2}
▶ 23: {MenuItemMorph . 2}
▶ 24: {LayoutMorph . 2}
▶ 25: {Dialog . 2}
▶ 26: {MenuMorph . 2}
```

Figure 2.1: The hall of fame of morph subclasses count

Let's analyze some top ranked morphs:

1. **PlacedMorph**. Its subclasses need to override the `drawOn:` method. So not a candidate to design morph by reuse.

2. **BorderedMorph**, **ColoredBoxMorph** and **BoxMorph**. Those classes are **PlacedMorph** with a few additional characteristics. Subclassing these classes will require most of the time overriding the **drawOn:** method.
3. **LinearLayoutMorph**. It has 11 subclasses. It is designed to assemble morphs in a new morph, using this class for reuse makes perfectly sense and we already know how to use it.
4. **SystemWindow**. As a view representing a whole application, subclassing it makes sense to implement specific behaviors of one GUI application, but not as a morph you can reuse as a widget.
5. **PluggableMorph**. It seems very generic, may be a good candidate. It represents a view of an associated model, however its subclasses need to implement a specific **drawOn:** method. We may want to use it when designing a morph from scratch.
6. **PluggableScrollPane**. This morph encapsulates an arbitrary morph – called a *scroller* – in a pane with optional scrollbars when the scroller extent is too large. It is very handy, and in some circumstances it makes sense to subclass it.

All in all, we have two candidates to subclass when conceiving a morph by reuse: **LinearLayoutMorph** and **PluggableScrollPane**.

2.2 Layout

This section will be very familiar with the booklet *Design GUI with Morph*, and it is a good idea to read its <https://DrCuis.github.io/DesignGUI/Layout-components.html> (**Layout components**) chapter before.

Arranging a set of morphs is what does the **LinearLayoutMorph** class, therefore it makes sense to define a new morph based on layout then to install a set of morphs into. This is exactly what does the **LabelGroup** class of the **Cuis-Smalltalk-UI** package.

2.2.1 Arrange visually

This subclass of **LinearLayoutMorph** takes a collection of textual descriptions and morphs to arrange them in two columns of labels and morphs. The idea is to give a label to widgets presented in a view.




Figure 2.2: A group of three morphs, each with its own label

In one layout column, the label group arranges nicely each label and widget couple in a row so that all the label cells are of same width. What it takes is a collection of label and morph associations. The returned layout is to be added in a higher level view.

LabelGroup class>>example1

```

↑ self with: {
  'Name' -> (LabelMorph contents: 'send $25 for your name here').
  'Description which is very long...' -> (
    TextModelMorph withText: " :: emptyTextDisplayMessage: 'Why Smalltalk?').
  'Smalltalk variants' -> (
    PluggableListMorph
      withModel: (ListModel with: #('Cuis-Smalltalk' 'Pharo' 'Squeak' 'Amber'))
      listGetter: #list
      indexGetter: #listIndex
      indexSetter: #listIndex: ) } ::
  color: Color white paler ;
  yourself

```

The **LabelGroup** is a passive object, its only purpose is to arrange visually morphs: all the user interactions are managed by the widgets. However, in some circumstance, we want both to arrange widgets and be notified about specific user interactions. This is what does the **CheckGroup** and **RadioGroup** classes.

2.2.2 Be notified

Once morphs are arranged in a layout, it makes sense to be notified through events when the user interacts with some of the arranged morphs. Under this perspective, the **LabelGroup** class is absolutely passive, contrary to the **CheckGroup** class we will present now.

As a **LabelGroup**, a **CheckGroup** presents a collection of labels with associated widgets, here **CheckButtonMorph**. In a **CheckGroup**, zero or more **CheckButtonMorph** can be selected at once. In a **RadioGroup**, a subclass, only one **RadioButtonMorph** is selected at once.




Figure 2.3: A check group to select among the baby squeaks

Creating a check group only requires a collection of labels¹:

CheckGroup class>>example1

```

| group |
group := self fromList: #('Cuis-Smalltalk' 'Pharo' 'Squeak').
group buttons do: [:each |
  each when: #checkSelection send: #show: to: Transcript].
↑ group

```

In the example, the `#checkSelection` event emitted by each check button is captured for report purpose. The attentive reader will observe this event is not specific to the check

¹ As an alternative to textual label, arbitrary morphs can be used instead.

group. Indeed, the check group itself emits another specific event `#informCheckSelection` when a button is selected:

```
CheckGroup>>newSelection: radioButton
    " Inform we have a new selection "
    self triggerEvent: #informCheckSelection with: (self symbolForButton: radioButton)
```

The event is triggered with the button label as attribute. To observe its use, experiment with the method `CheckGroup class>>example2`.

2.3 Scroll pane

Compared to the `LinearLayoutMorph` class, the `PluggableScrollPane` class doesn't have much subclasses. We found ones for all sort of list of items or text editor with need to scroll contents.

This class doesn't need to be subclassed to be useful, each time you want to present a morph with a large extent, embed it in a scroll pane:

```
PluggableScrollPane new ::
    scroller: Sample02Bezier new;
    color: Color white;
    openInWorld
```

Example 2.1: Bezier curves on a scroller




Figure 2.4: A scroll pane encapsulating Bézier curves with scroll bars

Among its few subclasses, `FlowLayoutMorph` extends the behavior of the layout morph, but doesn't inherit from, to present a collection of morphs in a strip spanning in several rows. It is flanked with a vertical scroll bar, if needed, inherited from the behavior of the `PluggableScrollPane`.

Its use is simple:

FlowLayoutMorph class>>example1

```

| flow cells |
flow := self new openInWorld.
cells := OrderedCollection new.
50 timesRepeat: [ cells add: (
    ColoredBoxMorph new ::
        morphExtent: (5 to: 80) atRandom asPoint;
        color: Color random)].
flow cells: cells

```

When resizing the morph, particularly its width, the flow of morphs is updated simultaneously.




Figure 2.5: Flow of boxes of various sizes

2.4 File Selector

So far we have observed existing morphs. Let's now build our own new morph.

2.4.1 Poor man implementation

First, let's do something quick and fun: a poor man file selector. All it takes is to get the entries of a given directory, collect them as previews and add them all in a flow layout:

```

| directories |
directories := DirectoryEntry userBaseDirectory children collect: [:anEntry |
    FilePreviewMorph
        object: anEntry
        image: ((anEntry isFileEntry ifTrue: [Theme current genericTextIcon] ifFalse: [Theme current fetch: #( '16x16' 'places' 'folder' )]) magnifyTo: 64@64)
        buttons: nil
        label: anEntry baseName ::
        borderColor: Color transparent;
        color: Color transparent].
FlowLayoutMorph new ::
    openInWorld;
    cells: directories

```

Of course at this stage, we can't browse in the directories tree:




Figure 2.6: A basic tool to list the files in a folder

To add more behavior to our poor man file selector, we want to make our first morph by reusing existing components.

2.4.2 First morph design by reuse

Our morph presents visually files and directories at a given location in the disk of the host. As we want this morph to be reused by other GUI designer, it doesn't present itself in a window but in a simple surface, a pane. Therefore we name it `FileSelectorPane`, it emits event when the user selects a file. It updates itself with new contents when the user double-clicks on a folder.

Because we may have numerous files and directories to present, we create our `FileSelectorPane` as a subclass of `FlowLayoutMorph`:

```
FlowLayoutMorph subclass: #FileSelectorPane
  instanceVariableNames: ''
  classVariableNames: ''
  poolDictionaries: ''
  category: 'ArtOfMorph'
```

In its parents hierarchy, our `FileSelectorPane` has the `PluggableMorph` ancestor, this one is observing a `model`. In the present context, the `model` represents the currently observed `DirectoryEntry`. It is set by default to the user base directory:

```
initialize
  super initialize.
  self open: DirectoryEntry userBaseDirectory
```

When opening a new location, directories and files are collected and sorted separately, in two groups, to build meaningful pre-views:

open: aDirectoryEntry

```

| entryViews |
model := aDirectoryEntry.
entryViews := OrderedCollection new.
model isRoot ifFalse: [ | parentView |
    parentView := self entryPreviewFor: model parent.
    parentView relabel: '..' bold.
    entryViews add: parentView].
entryViews
    addAll: (self previewsFor: model directories);
    addAll: (self previewsFor: model files ).
self cells: entryViews

```

The directory and file entries are sorted appropriately and each one is flanked with a preview:

previewsFor: entries

```

↑ (entries sort: [:a :b | a baseName asUppercase < b baseName asUppercase ])
    collect: [:anEntry | self entryPreviewFor: anEntry]

```

The special directory “..” above is inserted first for the user to browse to the parent directory of the model.

Observe below how each directory preview is listening to the double click event, in that circumstance the related directory is opened.

entryPreviewFor: fileEntry

```

| fileView |
fileView := FilePreviewMorph
    object: fileEntry
    image: ((fileEntry isFileEntry
        ifTrue: [Theme current genericTextIcon]
        ifFalse: [Theme current fetch: #( '16x16' 'places' 'folder' )]) magnifyTo: 48@48)
    buttons: nil
    label: fileEntry baseName ::
    borderColor: Color transparent;
    color: Color transparent.
fileEntry isDirectoryEntry ifTrue: [
    fileView when: #doubleClick send: #open: to: self with: fileEntry].
↑ fileView

```

We are relying on FilePreviewMorph, a composition of several morphs, itself emitting events to notify about user activities.

To integrate this widget with other morph, particularly to behave as a file selector, we want it to trigger event when the user selects a file. A FilePreviewMorph emits a #selected event each time the user clicks it, let's capture this event to manage it internally:

entryPreviewFor: fileEntry

```

../..
fileView when: #selected send: #toggleSelection: to: self with: fileView.
↑ fileView

```

Then we define the behavior for the `#toggleSelection:` message:

toggleSelection: fileView

```

| selectedView |
selectedView := cells detect: [:aFileView | aFileView isSelected] ifNone: [nil].
selectedView = fileView
  ifTrue: [ " unselect view, no view selected anymore "
    fileView toggleSelection.
    selectedView := nil]
  ifFalse: [
    selectedView ifNotNil: [selectedView toggleSelection].
    fileView selected: true.
    selectedView := fileView].
selectedView
  ifNil: [self triggerEvent: #noSelection]
  ifNotNil: [self triggerEvent: #selectedFile with: selectedView fileEntry]

```

To visualise in the **Transcript** window the events propagation, instantiate a new file selector and capture its events:

```

| selector |
selector := FileSelectorPane new openInWorld.
selector when: #noSelection send: #print to: 'no entry'.
selector when: #selectedFile send: #show: to: Transcript

```

To stop listening to events, just send the `#removeAllActions` message to the listener: `selector removeAllActions`.

Morph are both listener and emitter of events. Doing so is important for decoupling the objects between each others and to improve objects reuse.

We designed the `FileSelectorPane` to be itself reusable in other morph. In the next section we illustrate its use to improve the usability of the `StringRequestMorph`, a morph used – among other things – to ask the user to key-in a file name; we want to improve to make it more user friendly.

2.4.3 Beyond string request morph

As illustrated by the sketch below, the idea is to have a file pane that expands on user request, the user then selects a file or a directory directly by pointing it on the pane.




Figure 2.7: A sketch depicting a file selector and its behavior

Let's extend the behavior of `StringRequestMorph`:

```
StringRequestMorph subclass: #FileRequestMorph
  instanceVariableNames: 'fileBrowser'
  classVariableNames: ''
  poolDictionaries: ''
  category: 'ArtOfMorph'
```

We add an the instance variable `fileBrowser` to hold our file selector when it is unfolded. We override a few methods from `StringRequestMorph`. We add a button to unfold/fold the file browser:

```
addTextPane
  super addTextPane.
  submorphs first addMorph:
    ((PluggableButtonMorph model: self action: #toggleFileBrowser)
     setBalloonText: 'Browse the file system to select a file or directory';
     icon: (Theme current fetch: #( '16x16' 'places' 'folder' )) )
```

When unfolding the file browser, we check its current status if absent we instantiate a new one just below the text entry, in the alternative we just delete it from screen:

toggleFileBrowser

```

fileBrowser ifNotNil: [
    fileBrowser delete.
    fileBrowser := nil.
    ^ self].
fileBrowser := FileSelectorPane new open: self directoryEntry.
fileBrowser when: #selectedFile send: #entry: to: self.
fileBrowser
    color: (Color white alpha: 0.8);
    morphPosition: self morphPosition + (0 (self morphHeight + 5));
    morphExtent: self morphExtent * (1@5);
    openInWorld

```

In this method two important points: the `directoryEntry` method answers the current directory as edited by the user and the `#selectedFile` event emitted by the `FileSelectorPane` is observed and dispatched to the `entry:` method. Each time the user selects a file, the message `#entry:` is sent to the `FileRequestMorph` instance:

entry: anEntry

```

textMorph hasUnacceptedEdits: false.
response := anEntry asString.
self changed: #response.
textMorph hasUnacceptedEdits: true

```




Figure 2.8: File request morph and its file browser unfolded

We end here our chapter on designing morph by reusing existing ones. From the usability perspective, our `FileRequestMorph` example is far to be complete; user interface grows on small details. There is a lot of room for improvements: the printed filenames below the icons are ridiculously short, a distinction between file and folder selection when the tool is invoked will allow a more precise usability behavior, the button to unfold & fold the file browser could have a selected state. These improvements are good exercises to strengthen your skill.

3 Design from scratch

When you imagine an unconventional way to interact with the computer, it may indicate you are on the verge to design new morphs from scratch: a new way to present information or/and to interact with. This chapter will help you in that circumstances.

As we did in the previous chapter, we take a look at existing morphs to learn from them, then we create our own morph.

3.1 A bit of introspection

Morphs implemented from scratch come with a `drawOn:` method to produce its visual representation. We already met this method in the Chapter 1 [Introduction], page 1. Let's interrogate our running Cuis-Smalltalk system to analyze which morphs are involved:

```
Morph allSubclasses size.  
⇒ 155.
```

```
(Morph allSubclasses select: [:each | each selectors includes: #drawOn:]) size.  
⇒ 69.
```

Example 3.1: How many morphs implement drawing operations?

We observe the majority of morphs are implemented by composing existing morphs, this was the topic of the previous chapter. We want to interrogate the Cuis-Smalltalk system a bit further by considering the line count of the `drawOn:` method of each morph.

```
| morphs |  
morphs := Morph allSubclasses select: [:each | each selectors includes: #drawOn:].  
morphs sort: [:classA :classB |  
  (classA sourceCodeAt: #drawOn:) lineCount > (classB sourceCodeAt: #drawOn:) lineCount]
```

Example 3.2: Line count of each `drawOn:`

This script should be executed to open on an object explorer, *Alt-Shift-I*.

Sadly, this result is not representative of the complexity of the drawing operations. Indeed, well written Smalltalk code tends to span over small & well factored methods. Nevertheless, the object explorer let us quickly jump from one method to another.

To improve the exploring experience, we can go a bit further in our previous script to present both the classes and the source codes of the `drawOn:` methods:

```
| morphs |  
morphs := Morph allSubclasses select: [:each | each selectors includes: #drawOn:].  
morphs := morphs sort: [:classA :classB |  
  (classA sourceCodeAt: #drawOn:) lineCount > (classB sourceCodeAt: #drawOn:) lineCount].  
morphs := morphs collect: [:each | each -> (each sourceCodeAt: #drawOn:)].  
morphs explore.
```

Example 3.3: Tooling to review each `drawOn:`

Once the code is executed, we have an object explorer to review methods. The items at the top of the object explorer are with longer `drawOn:` method:




Figure 3.1: Explorer of the draw methods

In this list, several items are `Sample***` classes, they are examples found in the `Morphic-Examples` class category. They demonstrate the capability of the `VectorGraphics` engine.

Let's take a look at `Sample01Cross` and its unique `drawOn:` method:

`drawOn: aCanvas`

```

aCanvas strokeWidth: 8 color: Color lightOrange fillColor: Color red do: [
aCanvas polyLine: { 100@0 . 140@0 . 140@240 . 100@240 . 100@0 } ].

```

```

aCanvas strokeWidth: 8 color: Color lightOrange fillColor: Color red do: [
aCanvas polyLine: { 0@100 . 0@140 . 240@140 . 240@100 . 0@100 } ]

```



Figure 3.2: `Sample01Cross` shape with two rectangles



Edit the `drawOn:` method to render a cross as shown in the image below (Figure 3.3).

Exercise 3.1: Better looking shape



Figure 3.3: A better looking cross

The method names involved in the code above will look familiar to users acquainted to SVG (Scalable Vector Graphic)¹. It is indeed inspired by its specifications, and it may serve as a loose reference². Nevertheless, your first reference to look at regarding the available drawing operations is the `AbstractVectorCanvas` class then some bits of its parent class, `MorphicCanvas`.

In this class, the methods are divided in two important categories: the helper methods of the **drawing** - categories and the fundamental Vector Graphics protocol in the **paths** & **strokes** categories.




Figure 3.4: Method categories of the `AbstractVectorCanvas`

In its **drawing - MorphicCanvas** category observe how its helper method to draw a straight line relates to Vector Graphics engine:

¹ <https://en.wikipedia.org/wiki/SVG>

² <https://www.w3.org/TR/SVG11/>

```

line: pt1 to: pt2 width: morphStrokeWidth color: aStrokeColor
  self strokeWidth: morphStrokeWidth color: aStrokeColor do: [
    self moveTo: pt1.
    self lineTo: pt2 ]

```

In the `strokeWidth:color:do:` method above, the argument of the `do:` keyword is the path followed by the sketch, it describes the outline of the shape to construct. It blends very nicely in the Smalltalk syntax as a bloc of code. Your drawing operations should always be presented in such a bloc. Of course, it can be factored in several smaller methods or iterative processes, making it a very powerful mean for drawing.

The **stroke & fill** method category shows the methods to adjust the style of the path stroke. All in all, there are four categories of parameters to play with:

- **width.** A float number representing the width of the line.
- **color.** The color of the stroke, it's a Cuis-Smalltalk Color instance.
- **fill color.** The filling color, a Color instance.
- **dash style.** There are three different parameters to play with to represent the style of the line.

To be able to use floating numbers instead of integers, help to obtain smoother visual rendering. To illustrate it, let's turn our simple cross as a flashing medical cross as seen above the drugstore.

Let's rename the class and add a `width` attribute:

```

PlacedMorph subclass: #MedicCross
  instanceVariableNames: 'width'
  classVariableNames: ''
  poolDictionaries: ''
  category: 'ArtOfMorph'

```

We initialize it properly:

```

initialize
  super initialize.
  width := 0

```

To pulse the cross, we use the morphic's step mechanism, generally involving 3 methods: in our `MedicCross` the `step` method is continuously executed at a period in milliseconds indicated by its `stepTime` method,

```

CrossMedic >> stepTime
  ↑ 10

```

then, to indicate we want the stepping to occur, its `wantsSteps` must return `true`,

CrossMedic >> wantsSteps

↑ true



Implement the `step` method in `MedicCross` so that its `width` increments by 0.1 until 10, then it is zeroed.

Exercise 3.2: `step` method makes it pulse



Figure 3.5: A flashing medic cross

Appendix A Documents Copyright

Cuis-Smalltalk mascot



The southern mountain cavy (*Microcavia australis*) is a species of South American rodent in the family Caviidae.

Copyright © Euan Mee

Appendix B The Exercises

Exercise 3.1: Better looking shape.....	20
Exercise 3.2: <code>step</code> method makes it pulse	22

Appendix C Solutions to the Exercises

Design from scratch

Exercise 3.1

To avoid the unpleasant overlapping of the two rectangles, all the drawing operations are to be conducted in an unique stroke. The polyline summit is then extended to follow the outline of the cross.

drawOn: aCanvas

```
aCanvas strokeWidth: 8 color: Color lightOrange fillColor: Color red do: [
  aCanvas polyline: {
    100@0 . 140@0 . 140@100 . 240@100 . 240@140 .140@140 .
    140@240 . 100@240 . 100@140 . 0@140 . 0@100 . 100@100 .
    100@0 } ]
```

Exercise 3.2

To enjoy the update, the `#redrawNeeded` is to be sent to `self`.

step

```
width := width + 0.1.
width > 10 ifTrue: [width := 0].
self redrawNeeded
```

Appendix D The Examples

Example 2.1: Bezier curves on a scroller	11
Example 3.1: How many morphs implement drawing operations?.....	18
Example 3.2: Line count of each <code>drawOn</code> :	18
Example 3.3: Tooling to review each <code>drawOn</code> :	18

Appendix E The Figures

Figure 1.1: Ellipse with axes, resized to an extent approximatively equals to 300@100 . 2	
Figure 2.1: The hall of fame of morph subclasses count	8
Figure 2.2: A group of three morphs, each with its own label.....	9
Figure 2.3: A check group to select among the baby squeaks	10
Figure 2.4: A scroll pane encapsulating Bézier curves with scroll bars	11
Figure 2.5: Flow of boxes of various sizes	12
Figure 2.6: A basic tool to list the files in a folder	13
Figure 2.7: A sketch depicting a file selector and its behavior	16
Figure 2.8: File request morph and its file browser unfolded.....	17
Figure 3.1: Explorer of the draw methods	19
Figure 3.2: Sample01Cross shape with two rectangles.....	19
Figure 3.3: A better looking cross	20
Figure 3.4: Method categories of the AbstractVectorCanvas	20
Figure 3.5: A flashing medic cross	22

Appendix F Art of Morph package

Download Art of Morph package (<https://github.com/DrCuis/TheArtOfMorph/blob/main/misc/ArtOfMorph.pck.st>)

```
'From Cuis7.5 [latest update: #7383] on 27 July 2025 at 6:09:55 pm'!
'Description '
!provides: 'ArtOfMorph' 1 7!
!requires: 'UI-Widgets' 1 54 nil!
!requires: 'UI-Panel' 1 130 nil!
SystemOrganization addCategory: #ArtOfMorph!

!classDefinition: #EllipseDemo category: #ArtOfMorph!
ColoredBoxMorph subclass: #EllipseDemo
    instanceVariableNames: 'shrink'
    classVariableNames: ''
    poolDictionaries: ''
    category: 'ArtOfMorph'!
!classDefinition: 'EllipseDemo class' category: #ArtOfMorph!
EllipseDemo class
    instanceVariableNames: ''!

!classDefinition: #FileRequestMorph category: #ArtOfMorph!
StringRequestMorph subclass: #FileRequestMorph
    instanceVariableNames: 'fileBrowser'
    classVariableNames: ''
    poolDictionaries: ''
    category: 'ArtOfMorph'!
!classDefinition: 'FileRequestMorph class' category: #ArtOfMorph!
FileRequestMorph class
    instanceVariableNames: ''!

!classDefinition: #FileSelectorPane category: #ArtOfMorph!
FlowLayoutMorph subclass: #FileSelectorPane
    instanceVariableNames: ''
    classVariableNames: ''
    poolDictionaries: ''
    category: 'ArtOfMorph'!
!classDefinition: 'FileSelectorPane class' category: #ArtOfMorph!
FileSelectorPane class
    instanceVariableNames: ''!

!EllipseDemo methodsFor: 'accessing' stamp: 'hlsf 6/14/2025 12:17:51'!
center
    ^ extent / 2.0! !

!EllipseDemo methodsFor: 'accessing' stamp: 'hlsf 6/14/2025 13:32:35'!
semiAxes
    " the semi minor and major axis of the ellipse"
    ^ (extent / 2.0) - shrink ! !

!EllipseDemo methodsFor: 'initialization' stamp: 'hlsf 6/11/2025 18:54:04'!
defaultExtent
    ^ 200@200! !

!EllipseDemo methodsFor: 'initialization' stamp: 'hlsf 6/19/2025 23:45:40'!
initialize
    super initialize.
    color := Color yellow.
    shrink := 0.
    'Hover over the circle to change its color and unhover to change it back.' print.
    'Click it with left or right button to shrink or to grow the ellipse.' print.
```

```

'Move mouse over the circle and press r, g, or b to change its color.' print!!

!EllipseDemo methodsFor: 'drawing' stamp: 'hlsf 6/14/2025 12:56:07'!
drawOn: aCanvas
    aCanvas fillColor: color do: [
        aCanvas ellipseCenter: self center radius: self semiAxes ]!!

!EllipseDemo methodsFor: 'event handling testing' stamp: 'hlsf 6/19/2025 23:48:44'!
handlesKeyboard
    "This enables the morph to handle key events if it has focus."
    ^ self visible!!

!EllipseDemo methodsFor: 'event handling testing' stamp: 'hlsf 6/14/2025 13:31:52'!
handlesMouseDown: aMouseEvent
    "This enables the morph to handle mouse events such as button presses."
    ^ true!!

!EllipseDemo methodsFor: 'event handling testing' stamp: 'hlsf 6/14/2025 12:53:26'!
handlesMouseOver: aMouseEvent
    "This enables the morph to handle mouse enter and leave events."
    ^ true!!

!EllipseDemo methodsFor: 'events' stamp: 'hlsf 6/29/2025 12:10:49'!
keyStroke: aKeyEvent
    | character increment h s v |
    super keyStroke: aKeyEvent.
    aKeyEvent wasHandled ifTrue: [^ self].
    character := Character codePoint: aKeyEvent keyValue.
    color := character
        caseOf: {
            [ $r ] -> [ `Color red` ].
            [ $g ] -> [ `Color green` ].
            [ $b ] -> [ `Color blue` ] }
        otherwise: [color].

    h := color hue.
    s := color saturation.
    v := color brightness .
    increment := aKeyEvent controlKeyPressed ifTrue: [-0.1] ifFalse: [0.1].
    character
        caseOf: {
            [ $h ] -> [ h := h + (increment * 13) ].
            [ $s ] -> [ s := s + increment ].
            [ $v ] -> [ v := v + increment ]
        }
        otherwise: [].
    color setHue: h saturation: s brightness: v.
    self redrawNeeded!!

!EllipseDemo methodsFor: 'events' stamp: 'hlsf 6/19/2025 23:52:50'!
mouseButton1Down: aMouseEvent localPosition: aPosition
    shrink := (shrink + 0.5) min: (extent x min: extent y) // 2.
    (Preferences at: #focusFollowsMouse) ifFalse: [aMouseEvent hand newKeyboardFocus: self].
    self redrawNeeded!!

!EllipseDemo methodsFor: 'events' stamp: 'hlsf 6/14/2025 13:33:22'!
mouseButton2Down: aMouseEvent localPosition: aPosition
    shrink := (shrink - 5) max: 0.
    self redrawNeeded!!

!EllipseDemo methodsFor: 'events' stamp: 'hlsf 6/19/2025 23:52:35'!
mouseEnter: aMouseEvent
    color := `Color green`.
    "If the user opted for focus to automatically
    move focus to the morph under the cursor then tell

```



```

        the cursor (event hand) to give focus to this morph."
        (Preferences at: #focusFollowsMouse) ifTrue: [aMouseEvent hand newKeyboardFocus: self].
        self redrawNeeded.!!

!EllipseDemo methodsFor: 'events' stamp: 'hlsf 6/28/2025 09:36:28'!
mouseLeave: aMouseEvent
    super mouseLeave: aMouseEvent.
    color := `Color red`.
    self redrawNeeded.!!

!EllipseDemo methodsFor: 'events' stamp: 'hlsf 6/14/2025 13:09:40'!
wantsContour
    ^ true!!

!EllipseDemo methodsFor: 'geometry testing' stamp: 'hlsf 6/11/2025 19:05:04'!
requiresVectorCanvas
    ^ true!!

!FileRequestMorph methodsFor: 'initialization' stamp: 'hlsf 7/27/2025 14:46:09'!
addTextPane
    super addTextPane.
    submorphs first addMorph:
        ((PluggableButtonMorph model: self action: #toggleFileBrowser)
            setBalloonText: 'Browse the file system to select a file or directory';
            icon: (Theme current fetch: #( '16x16' 'places' 'folder' )) )!!

!FileRequestMorph methodsFor: 'accessing' stamp: 'hlsf 7/27/2025 15:10:38'!
directoryEntry
    | editedContents |
    editedContents := textMorph scroller contents asPlainString.
    ^ editedContents asFileEntry exists
        ifTrue: [editedContents asFileEntry parent]
        ifFalse: [editedContents asDirectoryEntry exists
            ifTrue: [editedContents asDirectoryEntry ] ifFalse: [editedContents asDirectoryEntry parent] ]!!

!FileRequestMorph methodsFor: 'accessing' stamp: 'hlsf 7/27/2025 14:33:32'!
response: aText
    | answer |
    answer := super response: aText.
    (answer and: [fileBrowser notNil]) ifTrue: [fileBrowser delete].
    ^ answer!!

!FileRequestMorph methodsFor: 'accessing' stamp: 'hlsf 7/27/2025 12:59:21'!
toggleFileBrowser
    fileBrowser ifNotNil: [
        fileBrowser delete.
        fileBrowser := nil.
        ^ self].
    fileBrowser := FileSelectorPane new    open: self directoryEntry.
    fileBrowser when: #selectedFile send: #entry: to: self.
    fileBrowser
        color: (Color white alpha: 0.8);
        morphPosition: self morphPosition + (0 @ (self morphHeight + 5));
        morphExtent: self morphExtent * (1@5);
        openInWorld

    !!

!FileRequestMorph methodsFor: 'events' stamp: 'hlsf 7/27/2025 14:42:52'!
entry: anEntry
    textMorph hasUnacceptedEdits: false.
    response := anEntry asString.
    self changed: #response.
    textMorph hasUnacceptedEdits: true.!!

```

```

!FileRequestMorph methodsFor: 'private' stamp: 'hlsf 7/27/2025 12:50:16'!
cancel
    super cancel.
    fileBrowser ifNotNil: [fileBrowser delete]! !

!FileRequestMorph class methodsFor: 'as yet unclassified' stamp: 'hlsf 7/27/2025 18:09:49'!
example
"
    FileRequestMorph example
"
    ^ FileRequestMorph
        request: 'Select a file or directory'
        initialAnswer: DirectoryEntry userBaseDirectory asString
        orCancel: nil.
! !

!FileSelectorPane methodsFor: 'initialization' stamp: 'hlsf 7/19/2025 13:26:16'!
initialize
    super initialize.
    self open: DirectoryEntry userBaseDirectory
    ! !

!FileSelectorPane methodsFor: 'private' stamp: 'hlsf 7/27/2025 17:56:30'!
entryPreviewFor: fileEntry
    | fileView |
    fileView := FilePreviewMorph
        object: fileEntry
        image: ((fileEntry isFileEntry
            ifTrue: [Theme current genericTextIcon]
            ifFalse: [Theme current fetch: #( '16x16' 'places' 'folder' )]) magnifyTo: 64@64)
        buttons: nil
        label: fileEntry baseName ::
        borderColor: Color transparent;
        color: Color transparent.
    fileEntry isDirectoryEntry ifTrue: [
        fileView when: #doubleClick send: #open: to: self with: fileEntry].
    fileView when: #selected send: #toggleSelection: to: self with: fileView.
    ^ fileView ! !

!FileSelectorPane methodsFor: 'private' stamp: 'hlsf 7/19/2025 11:57:59'!
previewsFor: entries
    ^ (entries sort: [:a :b | a baseName asUppercase < b baseName asUppercase ]) collect: [:anEntry |
        self entryPreviewFor: anEntry]! !

!FileSelectorPane methodsFor: 'accessing' stamp: 'hlsf 7/27/2025 11:58:21'!
open: aDirectoryEntryorPreview
    | entryViews |
    model := aDirectoryEntryorPreview class = FilePreviewMorph
        ifTrue: [aDirectoryEntryorPreview fileEntry]
        ifFalse: [aDirectoryEntryorPreview ].
    entryViews := OrderedCollection new.
    model isRoot ifFalse: [ | parentView |
        parentView := self entryPreviewFor: model parent.
        parentView relabel: '..' bold.
        entryViews add: parentView].
    entryViews
        addAll: (self previewsFor: model directories);
        addAll: (self previewsFor: model files ).
    self cells: entryViews.
    self updateLayout ! !

!FileSelectorPane methodsFor: 'events' stamp: 'hlsf 7/25/2025 19:22:15'!
toggleSelection: fileView
    | selectedView |
    selectedView := cells detect: [:aFileView | aFileView isSelected] ifNone: [nil].

```

```
selectedView = fileView
  ifTrue: [
    fileView toggleSelection. " unselect view, no view selected anymore "
    selectedView := nil]
  ifFalse: [
    selectedView ifNotNil: [selectedView toggleSelection].
    fileView selected: true.
    selectedView := fileView].
selectedView
  ifNil: [self triggerEvent: #noSelection]
  ifNotNil: [self triggerEvent: #selectedFile with: selectedView fileEntry]! !
```

Appendix G Conceptual index

E

event,	
emitter	15
keyboard	5
key stroke	6
modifier keys	6
keyboard focus	5
listener	14
mouse	2
click	3
hovering	3
remove	15
#removeAllActions	15
#triggerEvent:	15
#triggerEvent:with:	15
#when:send:to:with:	14

L

layout,	
group of morphs	9
LabelGroup	9

M

morph,	
AbstractVectorCanvas	20
animation	21
CheckGroup	10
drawOn:	18
event	10
FilePreviewMorph	14
FileSelectorPane	13
FlowLayoutMorph	11
label	9
layout	9
PluggableMorph	9
PluggableScrollPane	9, 11
RadioGroup	10
step	21
StringRequestMorph	15
subclasses	8
SVG	20

P

preference,	
keyboard focus	5

T

tools,	
object explorer	18