# Composition of Web Services

# Oxford University Software Engineering Programme Dec 2012



# Business Process Management

- Hammer & Champy [1993] "A collection of activities that takes one or more kinds of input and creates an output that is of value to the customer."
- Davenport [1992] "A structured, measured set of activities designed to produce a specific output for a particular customer or market. It implies a strong emphasis on how work is done within an organization, in contrast to a product focus's emphasis on what."




# Composition

- Services provide platform- and language-independent access to software components
- But these components are *isolated*: they need to be *assembled* into *service-oriented architectures*
- Ideally, they should be recursively *composable* to form composite services in their own right
- Workflow languages for scripting or 'glue' between individual services
- BPMN, WSCI, WSFL, XLANG, BPEL. . .
- beyond mere business protocol specifications like RosettaNet, which are essentially paper specifications so can't be automated and won't scale



# Removal of Dependencies (Leymann and Roller)

• DBMS provides independence from data *representation*; workflow provides independence from control or data *flow*.





© Paul Fremantle 2012. Portions © Jeremy Gibbons 2010, © WSO2 2005-2012 used with permission of the author(s). Licensed under the Creative Commons 3.0 BY-SA (Attribution-Sharealike) license. See http://creativecommons.org/licenses/by-sa/3.0/

# Heritage

- Enterprise application integration (EAI)
  - resolving heterogeneity, typically via asynchronous message brokers
- Workflow management systems (WfMS): automating interactions
  - origins in office automation: admin processes
- Production workflows: from information between people to integration of systems
  - often associated with business process re-engineering: assessment, analysis, modelling, definition, implementation
- Service composition = EAI + WfMS



#### Motivations

- Model Business Processes
  - Understand what happens?
  - Who is responsible?
  - What is involved?
- Simulate
  - Improve and model
- Execute
  - Automate processes
  - Improve them more quickly
- Monitor
  - Get a real-time health status of processes



# Orchestration vs Choreography



http://www.flickr.com/photos/herrolm/



http://www.flickr.com/photos/tasuki/



© Paul Fremantle 2012. Portions © Jeremy Gibbons 2010, © WSO2 2005-2012 used with permission of the author(s). Licensed under the Creative Commons 3.0 BY-SA (Attribution-Sharealike) license. See http://creativecommons.org/licenses/by-sa/3.0/

# Orchestration vs Choreography

- Orchestration
  - Describes procedure
  - instructs participants globally imperative;
     centralized
  - typically deterministic: 'must'
- Choreography
  - Describes protocol
  - Constraints on interaction, but participants act locally – declarative; no 'current state'
  - Usually non-deterministic: 'may'
- Orchestra has a conductor, Ballet does not



# WS-Choreography Description Language

- http://www.w3.org/TR/ws-cdl-10/
- Never got past Candidate Recommendation
- Captures the flow of messages between parties
- Temporal and logical dependencies between messages
- features sequencing rules, correlation, exception handling and transactions
- Not executable




#### **BPMN** 1.1

- Designed to allow process designers to communicate
  - Think UML
- Activities, Gateways, Events
- Control and Data Flow
- Organization modelling (Pools, Swimlanes)




### BPMN Example





#### Swimlanes:

partition an activity diagram into the responsibilities of different entities






© Paul Fremantle 2012. Portions © Jeremy Gibbons 2010, © WSO2 2005-2012 used with permission of the author(s). Licensed under the Creative Commons 3.0 BY-SA (Attribution-Sharealike) license. See http://creativecommons.org/licenses/by-sa/3.0/

#### Data Flow

- Transitions between activities represent *control dependencies*: one activity must complete before another can start
- Workflows also have *data dependencies*: one activity produces a result that another requires
- UML activity diagrams allow *object flow* as well as *control flow*
- Dependent data is shown as an object icon (rectangle with underlined name and type)
  - dependencies shown as dashed arrows from generating activity to object, and from object to consuming activity(s)
  - same object may occur multiple times in an activity diagram, typically in different states (shown in square brackets after object name)



# Example Object Flow





# Business Process Execution Language (BPEL)

- Standardised XML language for executable processes
- Well defined execution
  - No deadlocks
  - Graphs must be acyclic
- Tied to WSDL concepts
- No built in support for human activities (though this has been added)
- No graphical notation



#### BPMN + BPEL

- In theory:
  - Process experts design and model in BPMN
  - Developers/Implementors implement in BPEL
- No standard bridging/mapping
  - Double the effort





#### **BPMN 2.0**

- A notation for a subset of BPEL
- Execution semantics for BPMN
- Notational support for choreography
- The best of both worlds?



#### **BPMN 2.0**







# How much BPMN do you need?

How Much Language is Enough?
Theoretical and Practical Use of the
Business Process Management Notation
<a href="http://papers.ssrn.com/sol3/">http://papers.ssrn.com/sol3/</a>
papers.cfm?abstract id=2038665





Fig. 1. Occurrence Frequency of BPMN Constructs




#### **BPEL**






#### **BPEL** Activities





© Paul Fremantle 2012. Portions © Jeremy Gibbons 2010, © WSO2 2005-2012 used with permission of the author(s). Licensed under the Creative Commons 3.0 BY-SA (Attribution-Sharealike) license. See http://creativecommons.org/licenses/by-sa/3.0/

# Fault Handling





#### Partner Links

- Interactions between business process and external parties
  - Partner link type defines one (for unidirectional links) or two (for bi-directional) roles of corresponding port type
- Partner links instantiate partner link types, specifying myRole (played by this process) and/or partnerRole (played by external party)
  - bindings of actual partners to external roles are omitted
- Who takes what role?
- A key concept for asynchronous messaging



#### BPEL data

- Control flow not data flow
- Variables are assigned on:
  - Input
  - Return
  - <assign>
- Often need to jump into XSLT
  - Cumbersome




#### BPEL extensions and extras

- BPEL4People/WS-HumanTasks
  - How people interact with BPEL
- BPELlight
  - WSDL-less BPEL
- BPEL JS/E4X
  - Simplified assignment
- BPELScript/simBPEL/SimPEL
  - DSL/textual notations for BPEL




#### Human Tasks





© Paul Fremantle 2012. Portions © Jeremy Gibbons 2010, © WSO2 2005-2012 used with permission of the author(s). Licensed under the Creative Commons 3.0 BY-SA (Attribution-Sharealike) license. See http://creativecommons.org/licenses/by-sa/3.0/

### Amazon Simple Workflow Service







#### Amazon SWF

- Maintains distributed application state
- Tracks workflow executions
- Ensures consistency of execution history
- Provides visibility into executions
- Holds and dispatches tasks
- Provides control over task distribution
- Retains workflow execution history



Cloud





http://aws.amazon.com/swf/



Workers for **Activity 1** 

Return Results

Mobile



Workers for **Activity 2** 



On Premises



Workers for **Activity 3** 



© Paul Fremantle 2012. Portions © Jeremy Gibbons 2010, © WSO2 2005-2012 used with permission of the author(s). Licensed under the Creative Commons 3.0 BY-SA (Attribution-Sharealike) license. See http://creativecommons.org/licenses/by-sa/3.0/

## Summary

- Process Management has a strong place in composing SOA systems
  - Externalising dependencies
  - Agility
  - Sharing with the business owners
- BPEL is the most common and standard model today
- BPMN 2.0 is gaining a lot of mindshare
- Other approaches like Amazon SWF may also appear

