

Exercise 2

Using SOAPUI to interact with a sample SOAP Service

Prior Knowledge

XML

Objectives

Deploy a ready built service into Tomcat

Call the service using SOAP message

See sample SOAP messages

Software Requirements

(see separate document for installation of these)

- Java Development Kit 7
- Tomcat 7.0.30 or later
- SOAPUI 4.5.1 or later



Step 1. Deploy the service into Tomcat

The sample service is already coded and available as a WAR file. It was written with Apache CXF and is available here:

<https://github.com/pzfreo/ox-soa/raw/master/lab-exercises/code/sample-service-1.0.war>

Simply copy the WAR file into <tomcat>/webapps/ directory

Now start Tomcat:

Rather than use the “daemon” server startup we will use the model that keeps the server running in the open window.

```
cd <tomcat>
bin/catalina.sh run [Linux/Mac]
bin\catalina.bat run [Windows]
```

For reference here is the Server Startup approach.

```
cd <tomcat>
bin/startup.sh [Linux/Mac]
bin\startup.bat [Windows]
```

Check to see if its running:


Browse <http://localhost:8080/sample-service-1.0/>

You should see a SOAP Web Service listed with a link to the WSDL. Copy the WSDL Link into the Clipboard.

Now start up SOAPUI

File->New SOAPUI Project






Type in a name for the project (e.g. Sample)
Paste the WSDL URI into the Initial WSDL field
Hit OK

Now open up the Request editor for one of the operations:

In the XML Payload, change any '?' fields into something useful. Now hit the little green arrow (Run) button.

You should see a response from the service.



Use some of the SOAP UI capabilities to inspect the HTTP Headers, etc.
Try some other options and see what happens.

