APPENDIX A

# Request lifecycles and safety controls

Three requests traced through the system as they ran against the live APIs, followed by the safety controls each clinical risk maps to and the tests that hold them in place.

## A1 Request lifecycles

Colour shows who acts at each step: clinician, model, code, outcome

### Retrieval with an ambiguous name

one model call, then code only

| CLINICIAN | SPEECH-TO-TEXT | MODEL | CODE | CLINICIAN | OUTCOME |
|---|---|---|---|---|---|
| *"Open Priya's latest OPG report"* | Transcribed in ≈0.4 s; passes the silence guard | `report_request`: open, "Priya", OPG, latest | Two patients match, so it asks which (ID, age, last scan) | *"Priya Sharma"*: resolved in code, no model call | R-1003 opened, with a look-alike alert (Priya Shetty) |

### Dictation to a structured draft

model recall, code precision

| CLINICIAN | MODEL | GROUNDING | PARSER MERGE | DRAFT | CLINICIAN |
|---|---|---|---|---|---|
| Dictates four sentences, including *"possible caries on 46"* | `draft_findings`: three findings, each with a quote | Quote present and names the finding; tooth and negation re-derived | Adds one missed finding: canal proximity at 48 | 4 findings, 1 flagged, the remark kept verbatim | Edits, links the patient and approves; the draft is frozen |

### Follow-up with session context

context is used only when it fits

| CLINICIAN | MODEL | CODE | OUTCOME | NEXT QUESTION |
|---|---|---|---|---|
| *"Summarize her report"* | `report_request`: summarize, pronoun female | Open patient P001 is female, so context is accepted | Extractive summary citing `R-1003#F1` to `F5` | *"Any caries?"* Not in R-1003; found in R-1002 and R-1001 |

## A2 Safety controls

Each control is enforced in code and covered by tests

| RISK | CONTROL | ENFORCED IN | VERIFIED BY |
|---|---|---|---|
| **Wrong patient: shared name** | Ask on two or more matches, confirm near-matches, and flag look-alike names with ID and age. | `match_patients` | `test_ambiguous_identity (9)` |
| **Wrong patient: model slip** | A patient name or ID from the model must appear in the utterance, or it is discarded. | `orchestrator` | `test_ambiguous_identity` |
| **Wrong patient: context** | A pronoun must fit the open patient; a spoken name beats context; an unknown name is never swapped for the open patient without a yes. | `orchestrator` | `test_followup (8)` |
| **Invented or altered findings** | A verbatim quote that names the finding is required; tooth, negation and hedging are re-derived from the words. | `ground_llm_findings` | `test_unsupported_claims (11)` |
| **Guessed tooth** | "Lower third molar" stays unresolved as 38 or 48, and approval is blocked until a tooth is picked. | `drafts.approve` | `test_api (7)` |
| **Silence read as a command** | Whisper silence phrases rejected, no-speech segments dropped, low-confidence transcripts flagged. | `OpenAICompatSTT` | `test_providers (18), live run` |
| **Malformed tool call** | Pydantic schemas with nulls treated as absent; an invalid call is re-interpreted, never executed. | `validate_tool_call` | `test_unsupported_claims` |
| **Cross-clinic access** | Every read is clinic-scoped; out-of-scope records return "not found", so existence is not leaked. | `Repository` | `test_retrieval (9)` |
| **Unreviewed draft** | No impression or advice is generated; drafts stay pending until approved, and approved drafts are frozen. | `tools/drafts` | `test_api` |
| **Data exposure to the model** | The model gets the utterance and a one-line context only; the audit log records IDs, not text. | `interpreter, _audit` | `request-shape test` |

APPENDIX B

# Design decisions, live verification and roadmap

The choices that shape the system, what running it against the real APIs showed, and the path from proof of concept to a clinical pilot.

## B1 Key design decisions


| DECISION | WHY | TRADE-OFF ACCEPTED |
|---|---|---|
| **The model proposes; code executes** | Identity, scope and evidence rules stay deterministic, auditable and tested. | Two layers to maintain. |
| **Rule-based twin, same internal calls** | Offline mode, deterministic tests, and a ≈1 ms fallback when the model fails. | Narrower phrasing coverage than the model. |
| **Extractive summaries and answers** | Every line traces back to a report field through `report_id#finding_id`. | Less fluent than generated prose. |
| **Grounding check plus parser merge** | The model brings recall, code brings precision; nothing enters a draft unquoted. | A 23-type vocabulary; the rest is kept verbatim. |
| **Three tools and a static prompt** | About 860 tokens per call, cacheable, and within free-tier limits. | One report tool with an action field. |
| **Hosted Whisper with a dental prompt** | 0.35–0.48 s per clip, with terms such as OPG and mesioangular recognised. | Real audio needs a DPA or self-hosting. |

## B2 Live verification

Groq free tier, Windows, 13 October 2026 · full log in docs/LIVE_RUN.md

**Latency by stage**

Range per request in the live run; the dot marks the mean of 9 model calls (966 ms)




- **9 of 9 tool calls correct**: six typed turns and three spoken clips
- **4 of 4 live API tests passed**; the 89 offline tests need no key
- **Whisper matched every clip**; "tooth 4-6" resolved to tooth 46
- **Silence rejected**: a silent clip read as "Thank you." never reached the model
- **No guessing**: "Priya" still produced a clarification

## B3 What live testing changed

Each issue now has a fix and a regression test

| FOUND AGAINST THE REAL APIS | FIX |
|---|---|
| Groq rejected tool calls with `null` arguments (HTTP 400) | Optional fields made nullable; nulls dropped before validation. |
| Whisper transcribed 0.5 s of silence as "Thank you." | Silence-phrase guard plus no-speech and low-confidence checks. |
| Free tier allowed ≈6 calls a minute at 1,300 tokens each | Merged tools and a static prompt: ≈860 tokens per call, instant fallback on 429. |
| The model skipped one dictated finding | Grounded parser findings merged in; misattributed qualifiers dropped. |
| The model once read "Priya's" as a pronoun | Spoken-name cross-check before session context is used. |

## B4 Roadmap to a clinical pilot

PHASE 1

### Pilot hardening

- OIDC sign-in and role-based approval
- Postgres for sessions, drafts and versions
- Immutable audit trail

PHASE 2

### Clinical quality

- Real clinic audio: Indian-English accents, code-switching, noise
- Track dental-term WER and extraction precision and recall

PHASE 3

### Scale and integration

- Streaming STT, rules-first routing
- In-region self-hosted models
- PACS/RIS via FHIR DiagnosticReport and DICOM SR