README.md 7/21/2020

Serial

main.cpp

```
#include <QCoreApplication>
#include <QObject>

#include "serial.h"

int main(int argc, char *argv[]) {
    QCoreApplication a(argc, argv);
    serial *s = new serial();
    QObject::connect(s, SIGNAL(sig_quit()), &a, SLOT(quit()));
    s->open("COM3");
    s->write("Hello World!");
    return a.exec();
}
```

serial.h

```
#ifndef SERIAL_H
#define SERIAL H
#include <iostream>
#include <QObject>
#include <QSerialPort>
class serial : public QObject
{
    Q_OBJECT
public:
    explicit serial(QObject *parent = nullptr);
    void open(const QString &name);
    void write(const QString &message);
public slots:
    void slot_messageWritten();
private:
    QSerialPort *serialPort;
```

README.md 7/21/2020

```
signals:
    void sig_quit();
};
#endif // SERIAL_H
```

serial.cpp

```
#include "serial.h"
serial::serial(QObject *parent) : QObject(parent)
    serialPort = new QSerialPort();
    connect(serialPort, SIGNAL(bytesWritten(qint64)), this,
SLOT(slot_messageWritten()));
    return;
}
void serial::open(const QString &name)
    serialPort->setPortName(name);
    serialPort->setBaudRate(115200);
    serialPort->setDataBits(QSerialPort::Data8);
    serialPort->setParity(QSerialPort::NoParity);
    serialPort->setStopBits(QSerialPort::OneStop);
    if (!serialPort->isOpen())
        serialPort->close();
    serialPort->open(QIODevice::ReadWrite);
    return;
}
void serial::write(const QString &message)
{
    std::cout << "Message: " << message.toStdString() << std::endl;</pre>
    int bytesWritten = serialPort->write(message.toUtf8());
    std::cout << "Bytes written: " << bytesWritten << std::endl;</pre>
    return;
}
```

README.md 7/21/2020

```
void serial::slot_messageWritten()
{
    serialPort->close();
    emit sig_quit();
    return;
}
```