Bill Of Materials for Bit Station

Design Title Bit Station

Author Dustin Stroh (J3RK)

Document Number

Revision 3.0

Design CreatedWednesday, June 7, 2023Design Last ModifiedWednesday, June 7, 2023

Total Parts In Design 83

0 Modules							
	<u> References</u>	<u>Value</u>	<u>PCB</u> <u>Package</u>	<u>Notes</u>			
Sub-totals:							
	pacitors						
<u>Quantit</u>	<u>y</u> <u>References</u>	<u>Value</u>	<u>PCB</u> <u>Package</u>	<u>Notes</u>			
1	C1	1uF	CAP10	X7R Ceramic is fine here. Just a Delayed 1 Injector for Shift Register			
1	C2	22uF	CAP10	X7R or Audio Grade Electrolytic for AC Coupling			
1	C3	100nF	CAP10	COG/NP0 MLCC / Ceramic / Film			
1	C4	10uF	CAP10	X7R or Audio Grade Electrolytic for AC Coupling			
Sub-tot	als:						
32 Resistors							
Quantit	<u> References</u>	<u>Value</u>	<u>PCB</u> <u>Package</u>	<u>Notes</u>			
3	R1,R19,R21	100R	RES30	1% (100PPM / 50PPM Recommended)			
9	R2-R9,R14	3K	RES30	1% (100PPM / 50PPM Recommended)			
3	R10,R13,R27	10K	RES30	1% (100PPM / 50PPM Recommended)			
1	R11	4.99K	RES30	1% (100PPM / 50PPM Recommended)			
5	R12,R16-R18,R31	100K	RES30	1% (100PPM / 50PPM Recommended)			
1	R15	130K	RES30	1% (100PPM / 50PPM Recommended)			
2	R20,R28	499K	RES30	1% (100PPM / 50PPM Recommended)			
3	R22,R24-R25	10k	RES30	1% (100PPM / 50PPM Recommended)			
1	R23	6.8K	RES30	1% (100PPM / 50PPM Recommended)			
1	R26	47k	RES30	1% (100PPM / 50PPM Recommended)			
1	R29	91K	RES30	1% (100PPM / 50PPM Recommended)			
1	R30	5.6K	RES30	1% (100PPM / 50PPM Recommended)			
1	R32	20K	RES30	1% (100PPM / 50PPM Recommended)			
Sub-tot	als:			,			
9 Integrated Circuits							
Quantit	<u>y</u> <u>References</u>	<u>Value</u>	PCB Package	<u>Notes</u>			
2	U1-U2	4041	DIL14	CD4041 Quad Complement Buffer			
1	U3	4094	DIL16	CD4094 Shift Register			
1	U4	LM311	DIL08	Comparator			
1	U5	OPA2134PA	DIL08	Choose Low Drift / Low Bias / Low Offset / DC Accurate (OPA2132, LF412, etc.)			
1	U6	4070	DIL14	CD4070 Quad XOR			
1	U7	40106	DIL14	CD40106 Hex Schmitt Inverter			
2	U8-U9	TL071	DIL08	Noise Output Buffers. Any single op amp will work here. (TL071, LF356, etc.)			
Sub-totals:							
2 Transistors							
Quantit	<u>y</u> <u>References</u>	<u>Value</u>	<u>PCB</u>	Notes			

Package

2	Q1,Q3	2N3904	TO92	Any standard TO-92 NPN Transistor (EBC Pinout on board.)				
Sub-totals:								
1 Diodes								
Quantity	References	<u>Value</u>	PCB Package	<u>Notes</u>				
1 Sub-totals	D1 s:	1N4738A	DO41	Zener Diode between 8.2V and 10V.				
35 Miscellaneous								
Quantity	References	<u>Value</u>	PCB Package	<u>Notes</u>				
13	BP1-BP13	100nF	0805	Decoupling / Bypass SMT 0805 Capacitors. C0G/NP0 Preferred				
6	CLOCKIN, COMPIN, CVOUT, DNZ, NZ, SERIAL	CONN-SIL1	CONN- SIL1	On PCB Solder Pads. (no component needed)				
2	FB1-FB2	0R	RES30	Ferrite Beads Recommended				
1	J1	SIL-156-04	SIL-156-04	MTA-156 Friction Lock Power Header.				
8	LED1-LED8	LED-BIRG	CONN- SIL2	2 Lead BiColor LED				
1	LFCMP1	SW-SPDT	CONN- SIL3	SPDT Toggle Switch. NKK Recommended.				
2	PF1-PF2	100uF	ELEC- RAD13	Power Filtering Electrolytic Capacitors				
1	RN1	10k	CONN- SIL10	R/2R Resistor Network (CV Output DAC) Bourns Recommended				
1	THRESH1	100K	CONN- SIL3	Panel Pot (Linear)				
Sub-totals:								

Totals:

Wednesday, June 7, 2023 10:39:05 AM