## **Bill Of Materials for PulseLatch**

**Design Title** PulseLatch

**Author** Dustin Stroh (J3RK)

**Document Number** 

**Revision** REV 1.2

**Design Created** Wednesday, March 20, 2024 **Design Last Modified** Wonday, September 9, 2024

**Total Parts In Design** 73

0 Mod	ules							
Quantity	References	<u>Value</u>	<u>PCB</u> <u>Package</u>	<u>Notes</u>				
Sub-totals:								
6 Capacitors								
Quantity	<u>References</u>	<u>Value</u>	<u>PCB</u> <u>Package</u>	<u>Notes</u>				
1	C1	330nF	CAP10	C0G/NP0 MLCC / Ceramic / Film				
1	C2	10nF	CAP10	C0G/NP0 MLCC / Ceramic / Film				
1	C3	100nF	CAP10	C0G/NP0 MLCC / Ceramic / Film				
1	C4	4.7uF	CAP10	X7R Ceramic / MLCC / Film (Electrolytic OK too, but check polarity!!!)				
2	C5-C6	2200pF	CAP10	C0G/NP0 MLCC / Ceramic / Film				
Sub-totals:								
16 Res	sistors							
_	References	<u>Value</u>	<u>PCB</u> <u>Package</u>	<u>Notes</u>				
3	R1-R2,R13	10K	RES40	1/4W 50-100PPM 1% Resistor				
4	R3-R6	680R	RES40	1/4W 50-100PPM 1% Resistor				
4	R7-R10	100R	RES40	1/4W 50-100PPM 1% Resistor				
2	R11-R12	4.99K	RES40	1/4W 50-100PPM 1% Resistor				
1	R14	100K	RES40	1/4W 50-100PPM 1% Resistor				
2	R15-R16	220R	RES40					
Sub-total	ls:							
9 Integ	rated Circuits							
Quantity	References	<u>Value</u>	<u>PCB</u> <u>Package</u>	<u>Notes</u>				
4	U1,U5-U6,U9	40106	DIL14	DIP CMOS 4000				
1	U2	7805	TO220	TO220 (1.5A used to support extra function sub PCBs)				
1	U3	4013	DIL14	DIP CMOS 4000				
1	U4	4072	DIL14	DIP CMOS 4000				
1	U7	4041	DIL14	DIP CMOS 4000				
1	U8	LF347	DIL14	Any Quad Op Amp will work here. (TL07x for exmaple)				
Sub-totals:								
0 Transistors								
Quantity	References	<u>Value</u>	PCB Package	<u>Notes</u>				
Sub-totals:								
2 Diodes								
Quantity	<u>References</u>	<u>Value</u>	<u>PCB</u> <u>Package</u>	<u>Notes</u>				
2	D1-D2	DIODE	DIODE30	Small Signal Switching Diode (1N4148 or equivalent)				
Sub-total								
40 Miscellaneous								

	Quantity	References	<u>Value</u>	PCB Package	<u>Notes</u>			
	16	+5,+12,-12,0V,B1IL,B1IM,B1L,B1M,B2IL,B2IM,B2L,B2M,NOR1-NOR2,P1I,P2I	CONN- SIL1	CONN- SIL1	On PCB Solder Pads. (no component needed)			
	11	BP1-BP11	100nF	0805	0805 SMT COG/NP0 MLCC Bypass/Decoupling Capacitors			
	2	FB1-FB2	0R	RES40	Axial Ferrite Bead			
	1	J1	SIL-156-04	SIL-156-04	MTA-156 Friction Lock Power Header			
	6	LED1-LED6	LED-BIRG	CONN- SIL2	2-Lead BiColor LEDs (LED5 and LED6 can be single color.)			
	2	PF1-PF2	10uF	ELEC- RAD10	Electrolytic Power Filtering Capacitor (10uF - 100uF is fine)			
	2	SW1-SW2	SW-SPST	CONN- SIL2	SPST Momentary Pushbutton (arcade type work well)			
Sub-totale:								

Sub-totals:

Totals:

Monday, September 9, 2024 8:43:19 AM