

```
In [1]: # The normal imports
import numpy as np
from numpy.random import randn
import pandas as pd

# Import the stats library from numpy
from scipy import stats

# These are the plotting modules and libraries we'll use:
import matplotlib as mpl
import matplotlib.pyplot as plt
import seaborn as sns


# Command so that plots appear in the iPython Notebook
%matplotlib inline
```

```
In [2]: # Now we'll learn how to combine plot styles
```

```
In [4]: # Create dataset
dataset = randn(100)


# Use distplot for combining plots, by default a kde over a histogram is shown
sns.distplot(dataset, bins=25)
```

```
Out[4]: <matplotlib.axes._subplots.AxesSubplot at 0x192bce48>
```



```
In [5]: # hist, rug, and kde are all input arguments to turn those plots on or off
sns.distplot(dataset, rug=True, hist=False)
```


Out[5]: <matplotlib.axes.\_subplots.AxesSubplot at 0x1965ec50>



```
In [19]: # TO control specific plots in distplot, use [plot]_kws argument with dictionary
#Here's an example
```

```
sns.distplot(dataset, bins=25,
               kde_kws={'color': 'indianred', 'label': 'KDE PLOT'},
               hist_kws={'color': 'blue', 'label': 'HISTOGRAM'})
```

Out[19]: <matplotlib.axes.\_subplots.AxesSubplot at 0x1b794198>



```
In [22]: # WE can also use pandas data objects for this
```

```
from pandas import Series

# Create Series form dataset
ser1 = Series(dataset, name='My_DATA')
```

```
In [25]: # Plot Series  
sns.distplot(ser1,bins=25)
```

```
Out[25]: <matplotlib.axes._subplots.AxesSubplot at 0x1c215fd0>
```



```
In [ ]: # Next up: We'll learn about box and violin plots!
```